



US00D930349S

(12) **United States Design Patent** (10) **Patent No.:** **US D930,349 S**
Bitici (45) **Date of Patent:** **** Sep. 14, 2021**

(54) **PIN CUSHION BELT**
(71) Applicant: **Zoya Bitici**, Falls Church, VA (US)
(72) Inventor: **Zoya Bitici**, Falls Church, VA (US)
(**) Term: **15 Years**
(21) Appl. No.: **29/687,938**
(22) Filed: **Apr. 17, 2019**
(51) **LOC (13) Cl.** **02-07**
(52) **U.S. Cl.**
USPC **D3/22**
(58) **Field of Classification Search**
USPC D3/18, 20, 22, 27, 215, 271.4; D2/629
CPC A45F 5/021; Y10S 224/904; D05B 91/00;
D05B 91/12; A41H 17/00; A41H 31/00
See application file for complete search history.

D406,455 S * 3/1999 Wagner, II D3/226
D414,929 S * 10/1999 Brucki D3/226
6,073,823 A * 6/2000 Gordon A45F 5/02
224/661
D433,227 S * 11/2000 Evans D2/629
D433,228 S * 11/2000 Wentling, Jr. D3/224
D490,239 S * 5/2004 Wagner, II D3/226
D495,484 S * 9/2004 Marks D3/215
D510,480 S * 10/2005 McCarter D3/224
D529,896 S * 10/2006 Anderson D14/189
D572,900 S * 7/2008 Savage D3/27
D605,399 S * 12/2009 Faribault D3/226
D647,279 S * 10/2011 Shi D2/629

(Continued)

FOREIGN PATENT DOCUMENTS

CN 203969326 U 12/2014
CN 106235461 A 12/2016

Primary Examiner — Steven J Czyz
(74) *Attorney, Agent, or Firm* — Bacon & Thomas, PLLC

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,084,327 A * 1/1914 Giugliano et al. . B65D 83/0847
221/70
1,827,607 A * 10/1931 Pfaffinger D05B 91/12
24/3.2
1,828,494 A * 10/1931 Fasulo A41H 31/00
223/108
2,605,032 A * 7/1952 Hunt D05B 91/12
223/109 R
2,730,976 A * 1/1956 Loden D05B 35/068
112/151
3,933,286 A * 1/1976 Karkas A41H 17/00
224/219
D290,185 S * 6/1987 DiCavalcante D3/230
D298,484 S * 11/1988 Austin D3/22
D299,585 S * 1/1989 Corwin 224/223
D302,626 S * 8/1989 Robinson, Jr. D2/629
D307,073 S * 4/1990 Butler D15/72
D351,060 S * 10/1994 Randazzo D3/218
D374,983 S * 10/1996 Brucki D3/226
D392,799 S * 3/1998 Perrin D3/221


(57) **CLAIM**

The ornamental design for a pin cushion belt, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a pin cushion belt shown with environment;
FIG. 2 is a perspective view of the pin cushion belt shown in use and with environment;
FIG. 3 is a front view of the pin cushion belt;
FIG. 4 is a top view thereof;
FIG. 5 is a right view thereof;
FIG. 6 is a bottom view thereof;
FIG. 7 is a left view thereof; and,
FIG. 8 is a right view thereof.
The broken lines depict portions of the article and environment that form no part of the claimed design.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

8,727,189 B2 * 5/2014 Zieman D05B 91/00
223/109 A
D738,618 S * 9/2015 Do D3/226
D783,273 S * 4/2017 Kanner D3/226
9,611,574 B2 * 4/2017 Iwasaki D05B 91/12
D812,344 S * 3/2018 Brazile A45F 3/005
D2/627
D831,335 S * 10/2018 Crease D3/218
D831,340 S * 10/2018 Pomerantz D3/226
D831,342 S * 10/2018 Farkas D3/226
D865,320 S * 11/2019 Willows D2/629
D893,830 S * 8/2020 Scott D2/629

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4



FIG. 5




FIG. 6




FIG. 7




FIG. 8