

US00D942595S

(12) **United States Design Patent** (10) **Patent No.:** **US D942,595 S**
Schilling et al. (45) **Date of Patent:** **** *Feb. 1, 2022**

(54) **HOSE ASSEMBLY WITH REINFORCED FIRE SLEEVE**

DESCRIPTION

- (71) Applicant: **Eaton Corporation**, Cleveland, OH (US)
- (72) Inventors: **Patrick Alan Schilling**, Jackson, MI (US); **Justin Troy Straley**, Chelsea, MI (US); **John Paul Brittain**, Jackson, MI (US)
- (73) Assignee: **Eaton Intelligent Power Limited**, Dublin (IE)
- (*) Notice: This patent is subject to a terminal disclaimer.
- (**) Term: **15 Years**
- (21) Appl. No.: **29/562,322**
- (22) Filed: **Apr. 25, 2016**
- (51) **LOC (13) Cl.** **23-01**
- (52) **U.S. Cl.**
USPC **D23/266**
- (58) **Field of Classification Search**
USPC D23/259, 262–263, 266, 223, 249;
D24/129; D13/155; 138/103, 105,
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D21,561 S * 5/1892 Wilkinson D23/266
 - D46,944 S * 2/1915 Coughlin D23/266
- (Continued)

Primary Examiner — Amy C Wierenga
(74) *Attorney, Agent, or Firm* — Benesch, Friedlander, Coplan & Aronoff LLP

(57) **CLAIM**

What is claimed is the ornamental design for a hose assembly with reinforced fire sleeve, as shown and described.

FIG. 1 is a perspective view of a first embodiment of a hose assembly with reinforced fire sleeve;
 FIG. 2 is a front elevation view of the hose assembly with reinforced fire sleeve of FIG. 1;
 FIG. 3 is a rear elevation view of the hose assembly with reinforced fire sleeve of FIG. 1;
 FIG. 4 is a left side elevation view of the hose assembly with reinforced fire sleeve of FIG. 1;
 FIG. 5 is a right side elevation view of the hose assembly with reinforced fire sleeve of FIG. 1;
 FIG. 6 is a top plan view of the hose assembly with reinforced fire sleeve of FIG. 1;
 FIG. 7 is a bottom plan view of the hose assembly with reinforced fire sleeve of FIG. 1;
 FIG. 8 is a perspective view of a second embodiment of a hose assembly with reinforced fire sleeve;
 FIG. 9 is a front elevation view of the hose assembly with reinforced fire sleeve of FIG. 8;
 FIG. 10 is a rear elevation view of the hose assembly with reinforced fire sleeve of FIG. 8;
 FIG. 11 is a left side elevation view of the hose assembly with reinforced fire sleeve of FIG. 8;
 FIG. 12 is a right side elevation view of the hose assembly with reinforced fire sleeve of FIG. 8;
 FIG. 13 is a top plan view of the hose assembly with reinforced fire sleeve of FIG. 8;
 FIG. 14 is a bottom plan view of the hose assembly with reinforced fire sleeve of FIG. 8;
 FIG. 15 is a perspective view of a third embodiment of a hose assembly with reinforced fire sleeve;
 FIG. 16 is a front elevation view of the hose assembly with reinforced fire sleeve of FIG. 15;
 FIG. 17 is a rear elevation view of the hose assembly with reinforced fire sleeve of FIG. 15;
 FIG. 18 is a left side elevation view of the hose assembly with reinforced fire sleeve of FIG. 15;
 FIG. 19 is a right side elevation view of the hose assembly with reinforced fire sleeve of FIG. 15;
 FIG. 20 is a top plan view of the hose assembly with reinforced fire sleeve of FIG. 15;

(Continued)





FIG. 21 is a bottom plan view of the hose assembly with reinforced fire sleeve of FIG. 15;
 FIG. 22 is a perspective view of a fourth embodiment of a hose assembly with reinforced fire sleeve;
 FIG. 23 is a front elevation view of the hose assembly with reinforced fire sleeve of FIG. 22;
 FIG. 24 is a rear elevation view of the hose assembly with reinforced fire sleeve of FIG. 22;
 FIG. 25 is a left side elevation view of the hose assembly with reinforced fire sleeve of FIG. 22;
 FIG. 26 is a right side elevation view of the hose assembly with reinforced fire sleeve of FIG. 22;
 FIG. 27 is a top plan view of the hose assembly with reinforced fire sleeve of FIG. 22;
 FIG. 28 is a bottom plan view of the hose assembly with reinforced fire sleeve of FIG. 22;
 FIG. 29 is a perspective view of a fifth embodiment of a hose assembly with reinforced fire sleeve;
 FIG. 30 is a front elevation view of the hose assembly with reinforced fire sleeve of FIG. 29;
 FIG. 31 is a rear elevation view of the hose assembly with reinforced fire sleeve of FIG. 29;
 FIG. 32 is a left side elevation view of the hose assembly with reinforced fire sleeve of FIG. 29;
 FIG. 33 is a right side elevation view of the hose assembly with reinforced fire sleeve of FIG. 29;
 FIG. 34 is a top plan view of the hose assembly with reinforced fire sleeve of FIG. 29; and,
 FIG. 35 is a bottom plan view of the hose assembly with reinforced fire sleeve of FIG. 29.
 The hose assembly with reinforced fire sleeve is shown with a symbolic break in its length. The appearance of any portion of the hose between the break lines forms no part of the claimed design.
 The broken lines shown in the drawings illustrate portions of the hose assembly with reinforced fire sleeve that form no part of the claimed design.

1 Claim, 20 Drawing Sheets

(58) **Field of Classification Search**
 USPC 138/120-124, 118, 118.1, 126, 128, 137, 138/141, 157, 109-110, 129-130; 285/47, 124.1, 124.5
 CPC F16L 11/21; F16L 11/16; F16L 9/22; F16L 39/00; F16L 11/10; F16L 11/125; F16L 57/04; B29D 13/001
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,798,798	A *	3/1931	Leguillon	F16L 11/086 138/126
D180,850	S *	8/1957	Stahl	D23/266
D184,225	S *	1/1959	Greizin	D23/266
4,675,221	A	6/1987	Lalikos et al.	
D344,822	S *	3/1994	Miller	D32/31
5,803,129	A *	9/1998	Coronado	D04C 1/06 138/125
5,894,865	A *	4/1999	Winter	B29C 63/18 138/121
D413,657	S *	9/1999	Lidgett	D23/266
D413,968	S *	9/1999	Lester	D23/266
6,012,742	A *	1/2000	Kocian	F16L 49/00 285/94
D425,184	S *	5/2000	Lidgett	D23/266
6,302,152	B1 *	10/2001	Mulligan	F16L 11/10 138/109
D478,969	S *	8/2003	Mezzalira	D23/266
D605,737	S *	12/2009	von Glanstaetten	D23/266
D642,245	S *	7/2011	Mezzalira	D23/266
D642,246	S *	7/2011	Mezzalira	D23/266
8,127,800	B2	3/2012	Ramaswamy et al.	
D724,187	S *	3/2015	Savage	D23/266
D731,033	S *	6/2015	Kury	D23/266
9,091,375	B1 *	7/2015	DeBlasi	F16L 11/088
D742,604	S *	11/2015	Kim	D32/31
D743,658	S *	11/2015	Kim	D32/31
2006/0151043	A1 *	7/2006	Nanney	B32B 1/08 138/125
2008/0190506	A1 *	8/2008	Cleveland	F16L 57/04 138/110
2013/0092276	A1 *	4/2013	Caneva	D04B 21/205 138/123
2015/0136269	A1 *	5/2015	Chung	F16L 11/24 138/124

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 5




FIG. 4




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 12




FIG. 11




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 19




FIG. 18




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 33




FIG. 32




FIG. 34




FIG. 35