



US00D949154S

(12) **United States Design Patent** (10) **Patent No.:** **US D949,154 S**
Hornung (45) **Date of Patent:** **** Apr. 19, 2022**

(54) **STAND FOR COORDINATE INPUT DEVICE**

(71) Applicant: **Wacom Co., Ltd.**, Kazo (JP)

(72) Inventor: **Thilo Naoki Hornung**, Toyko (JP)

(73) Assignee: **Wacom Co., Ltd.**, Kazo (JP)

(**) Term: **15 Years**

(21) Appl. No.: **29/703,120**

(22) Filed: **Aug. 23, 2019**

(30) **Foreign Application Priority Data**

Feb. 25, 2019 (JP) 2019-003699

(51) **LOC (13) Cl.** **14-02**

(52) **U.S. Cl.**
USPC **D14/447; D14/457**

(58) **Field of Classification Search**
USPC D14/315, 457, 224, 316, 324, 447, 451,
D14/469

CPC A47B 21/0314; A47B 2021/0307; A47B
2021/0321; A47B 2200/0076; A47B
2210/15; Y10S 248/918

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D288,097 S * 2/1987 Harter D14/457
D392,956 S * 3/1998 Gillis D14/457
D494,980 S * 8/2004 Pao D14/457
D754,008 S * 4/2016 Huebner D10/65
D800,734 S 10/2017 Lewis et al.
D810,750 S * 2/2018 Chang D14/434
D852,794 S * 7/2019 Huebner D14/341
D855,056 S * 7/2019 Raken D14/439
D856,322 S * 8/2019 Huebner D14/341
D870,117 S * 12/2019 Akana D14/457
D893,507 S * 8/2020 Chen D14/458
D898,022 S * 10/2020 Hornung D14/336
D916,696 S * 4/2021 Yang D14/318

D916,697 S * 4/2021 Hornung D14/341
D928,143 S * 8/2021 Yeom D14/315
D928,775 S * 8/2021 Yeom D14/341
D931,274 S * 9/2021 Hwang D14/315
2007/0221811 A1* 9/2007 Hauser A47B 23/043
248/454

FOREIGN PATENT DOCUMENTS

BX 87806-01 S 11/2018
CN 303348225 S 8/2015
CN 304868221 S 10/2018
EM 002755637-0002 S 9/2015
JP d1417785 S 7/2011
JP D1461403 S 2/2013
JP D1608200 S 7/2018

* cited by examiner

Primary Examiner — Christian P. McLean

Assistant Examiner — Kourosh Taie-Tehrani

(74) *Attorney, Agent, or Firm* — Christensen O'Connor
Johnson Kindness PLLC

(57) **CLAIM**


The ornamental design for a stand for coordinate input device, as shown and described.

DESCRIPTION

FIG. 1 is a front-top-right perspective view of a stand for coordinate input device according to my new design; FIG. 2 is a rear-bottom-left perspective view thereof; FIG. 3 is a front elevational view thereof; FIG. 4 is a rear elevational view thereof; FIG. 5 is a right side elevational view thereof; FIG. 6 is a left side elevational view thereof; FIG. 7 is a top plan view thereof; and, FIG. 8 is a bottom plan view thereof.

The dashed broken lines in the drawings show portions of the stand for coordinate input device that form no part of the claimed design.

1 Claim, 6 Drawing Sheets






Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.




Fig. 7.




Fig. 8.