

US00D960887S

(12) **United States Design Patent** (10) **Patent No.:** **US D960,887 S**
Levine (45) **Date of Patent:** **** Aug. 16, 2022**

- (54) **ACCESSORY DISPLAY DEVICE**
- (71) Applicant: **Alex Cole Levine**, Austin, TX (US)
- (72) Inventor: **Alex Cole Levine**, Austin, TX (US)
- (**) Term: **15 Years**
- (21) Appl. No.: **29/713,535**
- (22) Filed: **Nov. 15, 2019**

Related U.S. Application Data

- (63) Continuation of application No. 16/673,920, filed on Nov. 4, 2019, now Pat. No. 10,809,762.
- (51) **LOC (13) Cl.** **14-02**
- (52) **U.S. Cl.**
USPC **D14/371**
- (58) **Field of Classification Search**
USPC D14/316, 373, 315, 327, 356-357, 371,
D14/432, 448-450, 464, 469; D19/113;
D3/900, 902
CPC G06F 1/1607; G06F 1/1616; G06F 1/1632;
G06F 1/1654; G06F 1/1647
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 6,151,401 A * 11/2000 Annaratone G06F 1/1616
361/679.23
- D449,302 S 10/2001 Jung
- 6,532,146 B1 3/2003 Duquette
- 6,794,798 B2 * 9/2004 Watanabe H04R 5/02
310/334
- D534,214 S * 12/2006 Marcy D19/113
- D594,236 S * 6/2009 Sidiropoulos D14/450
- D599,357 S * 9/2009 Kaufman D14/449
- D615,082 S 5/2010 Taichi
- D634,745 S 3/2011 Park et al.
- D652,832 S 1/2012 Wu et al.
- 8,243,471 B2 * 8/2012 Liang G06F 1/1603
361/829
- D679,707 S 4/2013 Aarrestad et al.
- D694,754 S 12/2013 Nakada

- 8,854,278 B2 * 10/2014 Parker G06F 3/1431
345/1.1
- D761,800 S * 7/2016 Muller D14/448
- 9,395,757 B2 7/2016 Relf
- 9,441,782 B2 * 9/2016 Funk F16M 13/02
- D770,447 S * 11/2016 Endo D14/371
- D770,448 S * 11/2016 Endo D14/371
- D810,079 S * 2/2018 Boesiger D14/371
- 9,927,839 B2 * 3/2018 Kummer H04M 1/0235
- 10,168,739 B1 * 1/2019 Chen G06F 1/1616
- D864,958 S * 10/2019 Yuksek D14/349
- 10,809,762 B1 * 10/2020 Levine G06F 1/1647
- 10,817,020 B1 * 10/2020 DeMaio G06F 1/1632
- 10,871,801 B2 * 12/2020 Yao G06F 1/1679
- D910,624 S * 2/2021 Hudgins D14/371
- D914,089 S * 3/2021 Tang D19/113
- 10,944,937 B2 * 3/2021 Pei F16M 11/2092
- D920,975 S * 6/2021 Yao D14/375
- D938,436 S * 12/2021 Gu D14/448
- 2005/0006331 A1 * 1/2005 Engel A47F 3/063
211/151
- 2005/0253775 A1 11/2005 Stewart
- 2006/0059751 A1 * 3/2006 Chen H04N 5/64
40/610
- 2006/0082518 A1 4/2006 Ram
- 2009/0201222 A1 8/2009 Damian
- 2010/0039350 A1 * 2/2010 Wakefield G06F 1/1647
345/1.3
- 2010/0053027 A1 3/2010 Tonnison
- 2011/0019360 A1 * 1/2011 Thabit G06F 1/1611
361/679.55
- 2012/0280603 A1 * 11/2012 Hsu G06F 1/1624
312/312
- 2020/0278722 A1 * 9/2020 Hudgins G06F 1/1616


FOREIGN PATENT DOCUMENTS

- CA 189545 * 12/2020
- CN 305087700 * 3/2019

OTHER PUBLICATIONS

Duo Triple Screen Device, Xebec, cnx-software.com, published by Stephen Vicinanza on Oct. 28, 2019 © 2021 CNX Software Limited, online, site visited Sep. 2, 2021. Available at URL: <https://www.cnx-software.com/2019/10/28/xebec-laptop-addon-triple-monitor-laptop/> (Year: 2019).*

Portable Triple Screen Computer Laptop, Matrixnn, thematrixnn.com, author and date unlisted © 2021 thematrixnn, online, site visited Nov. 1, 2021. Available at URL: <https://www.thematrixnn.com>



com/products/matrixnn-portable-triple-screen-computer-laptop-monitor-workstation (Year: 2021).*

Tri-Screen, Xebec (Alex Levine and Trevor Russo), thexebec.com, author unlisted, published on Sep. 25, 2020 per wayback machine © Xebec, Inc., online, site visited Feb. 4, 2022. Available at URL: <https://www.thexebec.com/pages/about> (Year: 2020).*

“Slidenjoy—Le Slide”, <https://yourslide.com> as viewed Nov. 13, 2019, United States.

“DUEX”, <https://www.mobilepixels.us/products/duex> as viewed Nov. 13, 2019, United States.

“Sidetrak”, <https://sidetrak.com> as viewed Nov. 14, 2019, United States.

* cited by examiner

Primary Examiner — Sandra Snapp

Assistant Examiner — Altaira J Swangin

(74) *Attorney, Agent, or Firm* — Stovall Legal; Blake D. Stovall

(57) **CLAIM**

The ornamental design for an accessory display device, as shown and described.

DESCRIPTION

FIG. 1 is a top perspective view of an accessory display device in a closed position according to a first embodiment; FIG. 2 is a bottom perspective view of the accessory display device shown in FIG. 1 in a closed position;

FIG. 3 is a left side view of the accessory display device shown in FIG. 1 in a closed position;

FIG. 4 is a right side view of the accessory display device shown in FIG. 1 in a closed position;

FIG. 5 is a front view of the accessory display device shown in FIG. 1 in a closed position;

FIG. 6 is a rear view of the accessory display device shown in FIG. 1 in a closed position;

FIG. 7 is a top view of the accessory display device shown in FIG. 1 in a closed position;

FIG. 8 is a bottom view of the accessory display device shown in FIG. 1 in a closed position;

FIG. 9 is a top perspective view of the accessory display device shown in FIG. 1 in an open position;

FIG. 10 is a bottom perspective view of the accessory display device shown in FIG. 1 in an open position;

FIG. 11 is a left side view of the accessory display device shown in FIG. 1 in an open position;

FIG. 12 is a right view of the accessory display device shown in FIG. 1 in an open position;

FIG. 13 is a front view of the accessory display device shown in FIG. 1 in an open position;

FIG. 14 is a rear view of the accessory display device shown in FIG. 1 in an open position;

FIG. 15 is a top view of the accessory display device shown in FIG. 1 in an open position;

FIG. 16 is a bottom view of the accessory display device shown in FIG. 1 in an open position;

FIG. 17 is a top perspective view of an accessory display device in a closed position according to a second embodiment;

FIG. 18 is a bottom perspective view of the accessory display device shown in FIG. 17 in a closed position;

FIG. 19 is a left side view of the accessory display device shown in FIG. 17 in a closed position;

FIG. 20 is a right side view of the accessory display device shown in FIG. 17 in a closed position;

FIG. 21 is a front view of the accessory display device shown in FIG. 17 in a closed position;

FIG. 22 is a rear view of the accessory display device shown in FIG. 17 in a closed position;

FIG. 23 is a top view of the accessory display device shown in FIG. 17 in a closed position;

FIG. 24 is a bottom view of the accessory display device shown in FIG. 17 in a closed position;

FIG. 25 is a top perspective view of the accessory display device shown in FIG. 17 in an open position;

FIG. 26 is a bottom perspective view of the accessory display device shown in FIG. 17 in an open position;

FIG. 27 is a left side view of the accessory display device shown in FIG. 17 in an open position;

FIG. 28 is a right view of the accessory display device shown in FIG. 17 in an open position;

FIG. 29 is a front view of the accessory display device shown in FIG. 17 in an open position;

FIG. 30 is a rear view of the accessory display device shown in FIG. 17 in an open position;

FIG. 31 is a top view of the accessory display device shown in FIG. 17 in an open position;

FIG. 32 is a bottom view of the accessory display device shown in FIG. 17 in an open position;

FIG. 33 is a top perspective view of an accessory display device in a closed position according to a third embodiment;

FIG. 34 is a bottom perspective view of the accessory display device shown in FIG. 33 in a closed position;

FIG. 35 is a left side view of the accessory display device shown in FIG. 33 in a closed position;

FIG. 36 is a right side view of the accessory display device shown in FIG. 33 in a closed position;

FIG. 37 is a front view of the accessory display device shown in FIG. 33 in a closed position;

FIG. 38 is a rear view of the accessory display device shown in FIG. 33 in a closed position;

FIG. 39 is a top view of the accessory display device shown in FIG. 33 in a closed position;

FIG. 40 is a bottom view of the accessory display device shown in FIG. 33 in a closed position;

FIG. 41 is a top perspective view of the accessory display device shown in FIG. 33 in an open position;

FIG. 42 is a bottom perspective view of the accessory display device shown in FIG. 33 in an open position;

FIG. 43 is a left side view of the accessory display device shown in FIG. 33 in an open position;

FIG. 44 is a right view of the accessory display device shown in FIG. 33 in an open position;

FIG. 45 is a front view of the accessory display device shown in FIG. 33 in an open position;

FIG. 46 is a rear view of the accessory display device shown in FIG. 33 in an open position;

FIG. 47 is a top view of the accessory display device shown in FIG. 33 in an open position; and,

FIG. 48 is a bottom view of the accessory display device shown in FIG. 33 in an open position.

The broken lines show portions of the accessory display device and form no part of the claimed design.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6



FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14



FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22



FIG. 23



FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30



FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39



FIG. 40




FIG. 41




FIG. 42




FIG. 44




FIG. 43




FIG. 45




FIG. 46



FIG. 47




FIG. 48