



US00D962089S

(12) **United States Design Patent**  
**Sarsak et al.**

(10) **Patent No.:** **US D962,089 S**

(45) **Date of Patent:** **\*\* Aug. 30, 2022**

(54) **SENSOR DEVICE**

(71) Applicant: **Teledyne FLIR Detection, Inc.**,  
Stillwater, OK (US)

(72) Inventors: **Ali Sarsak**, Stillwater, OK (US);  
**Zhenmei Mao**, Richmond (CA);  
**Matthew Szabo**, Stillwater, OK (US)

(73) Assignee: **Teledyne FLIR Detection, Inc.**,  
Stillwater, OK (US)

(\*\*) Term: **15 Years**

(21) Appl. No.: **29/706,531**

(22) Filed: **Sep. 20, 2019**

(51) **LOC (13) Cl.** ..... **10-04**

(52) **U.S. Cl.**  
USPC ..... **D10/53; D10/81**

(58) **Field of Classification Search**  
USPC ..... D10/46, 52, 53, 81  
CPC ..... G01N 29/04; G01N 31/22; G01N 31/224;  
G01N 33/62; Y10T 428/14; Y10T  
428/1471; Y10T 428/1476; Y10T  
428/149; Y10T 428/15; Y10T 428/16;  
Y10T 428/161; Y10T 428/162; Y10T  
428/163; Y10T 428/164; Y10T 428/169;  
Y10T 428/18; Y10T 428/183; Y10T  
428/23; Y10T 428/231; Y10T 428/232;  
Y10T 428/24; Y10T 4236/110833; Y10T  
436/25875; Y10T 436/173076; Y10T  
436/17; Y10T 4236/19; Y10T  
436/175383; Y10T 436/171538

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D310,339 S \* 9/1990 Tofte ..... D10/46  
D333,992 S \* 3/1993 Anderson ..... D10/81  
D725,522 S \* 3/2015 Kousuge ..... D24/186

D727,764 S \* 4/2015 Nothacker ..... D10/81  
D731,341 S \* 6/2015 Kobayakawa ..... D10/81  
D744,881 S \* 12/2015 Nothacker ..... D10/81  
D748,509 S \* 2/2016 Ammon ..... D10/78  
D752,997 S \* 4/2016 Miller ..... D10/52

(Continued)

*Primary Examiner* — Antoine Duval Davis

(74) *Attorney, Agent, or Firm* — Haynes and Boone, LLP

(57) **CLAIM**



The ornamental design for a sensor device, as shown and described.

**DESCRIPTION**

FIG. 1 is a front, left, and bottom perspective view of a sensor device embodying the new design;  
FIG. 2 is a rear, right, and top perspective view thereof;  
FIG. 3 is a bottom plan view thereof;  
FIG. 4 is a top plan view thereof;  
FIG. 5 is a right side elevational view thereof;  
FIG. 6 is a left side elevational view thereof;  
FIG. 7 is a front elevational view thereof;  
FIG. 8 is a rear elevational view thereof;  
FIG. 9 is a front, left, and bottom perspective view of a sensor device shown with an example of the attachment and the extension;  
FIG. 10 is a rear, right, and top perspective view thereof;  
FIG. 11 is a bottom plan view thereof;  
FIG. 12 is a top plan view thereof;  
FIG. 13 is a right side elevational view thereof;  
FIG. 14 is a left side elevational view thereof;  
FIG. 15 is a front elevational view thereof;  
FIG. 16 is a rear elevational view thereof;  
FIG. 17 is a front, left, and bottom perspective view of the attachment and a portion of the extension; and,  
FIG. 18 is a front elevational view thereof.

The broken lines in the figures are shown for the purpose of illustrating portions of the sensor device and/or environmental matter and form no part of the claimed design.

**1 Claim, 15 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

D821,894 S \* 7/2018 Verity ..... D10/46  
D839,116 S \* 1/2019 Hirose ..... D10/81  
D869,311 S \* 12/2019 Khattak ..... D24/129  
D915,226 S \* 4/2021 Matthes ..... D10/52  
D935,923 S \* 11/2021 Liu ..... D10/78

\* cited by examiner







FIG. 1

FIG. 2







*FIG. 3*



*FIG. 4*




*FIG. 5*




*FIG. 6*

*FIG. 7*



*FIG. 8*









FIG. 9



*FIG. 10*




FIG. 12




FIG. 11




FIG. 13






FIG. 14

*FIG. 15*





*FIG. 16*







FIG. 17





**FIG. 18**