



US00D963500S

(12) **United States Design Patent** (10) **Patent No.:** **US D963,500 S**
Lu (45) **Date of Patent:** **** Sep. 13, 2022**

(54) **CALIBRATION ACCESSORY OF TIRE WEARING DETECTOR**

(71) Applicant: **AUTEL INTELLIGENT TECHNOLOGY CORP., LTD.,**
Guangdong (CN)

(72) Inventor: **Boming Lu, Guangdong (CN)**

(73) Assignee: **AUTEL INTELLIGENT TECHNOLOGY CORP., LTD.,**
Shenzhen (CN)

(**) Term: **15 Years**

(21) Appl. No.: **29/769,550**

(22) Filed: **Feb. 5, 2021**

(30) **Foreign Application Priority Data**

Aug. 14, 2020 (CN) 202030463405.5

(51) **LOC (13) Cl.** **10-04**

(52) **U.S. Cl.**
USPC **D10/86; D10/78**

(58) **Field of Classification Search**

USPC D10/78, 83, 84, 85, 86

CPC B60C 23/0408; B60C 23/041; B60C

23/0411; B60C 23/0413; B60C 23/0415;

B60C 23/0416; B60C 23/0418; B60C

23/042; B60C 23/0422; B60C 23/0423;

B60C 23/0425; B60C 23/0427; B60C

23/0428; B60C 23/043; B60C 23/0432;

B60C 23/0433; B60C 23/0435; B60C

23/0437; B60C 23/0438; B60C 23/044;

B60C 23/0442; B60C 23/0444; B60C

23/0445; B60C 23/0447; B60C 23/0449;

B60C 23/045; B60C 23/0452; B60C

23/0454; B60C 23/0455; B60C 23/0457;

B60C 23/0459; B60C 23/0461; B60C

23/0462; B60C 23/064; B60C 23/0466;

B60C 23/0467; B60C 23/0469; B60C

23/0471; B60C 23/0472; B60C 23/0474;
B60C 23/0476; B60C 23/0477; B60C
23/0479; B60C 23/0481; B60C 23/0483;
B60C 23/0484; B60C 23/086; B60C
23/0488; B60C 23/0489; B60C 23/0491;
B60C 23/0493; B60C 23/0494; B60C
23/0496; B60C 23/098; B60C 2019/004;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

D366,846 S * 2/1996 Handfield D10/86

D611,856 S * 3/2010 Minagawa D10/85

(Continued)

Primary Examiner — Antoine Duval Davis

(57) **CLAIM**

I claim the ornamental designs for a calibration accessory of a tire wearing detector, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a calibration accessory of a tire wearing detector showing our first new design;

FIG. 2 is a back elevational view thereof;

FIG. 3 is a left side elevational view thereof;

FIG. 4 is a right side elevational view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a perspective view thereof;

FIG. 7 is a front elevational view of a calibration accessory of a tire wearing detector showing our second new design;

FIG. 8 is a back elevational view thereof;

FIG. 9 is a left side elevational view thereof;


FIG. 10 is a right side elevational view thereof;

FIG. 11 is a top plan view thereof;

FIG. 12 is a bottom plan view thereof; and,

FIG. 13 is a perspective view thereof.

1 Claim, 9 Drawing Sheets



(58) **Field of Classification Search**

CPC B60C 2019/006; B60C 2019/007; G01L
19/0007; G01L 19/0084; G01L 19/0092;
G01L 19/04; G01L 19/06; G01L 19/14;
G01L 19/141; G01L 19/142; G01L
19/143; G01L 19/144; G01L 19/145;
G01L 19/146; G01L 19/147; G01L
19/148; G01L 19/149

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D671,434 S * 11/2012 Kawai D10/86
D719,472 S * 12/2014 Sakaue D10/85
D750,519 S * 3/2016 Leigh D10/83
2013/0106596 A1* 5/2013 Mouchet B60C 23/0472
340/445
2014/0139332 A1* 5/2014 Mouchet B60C 23/0479
340/442
2014/0361884 A1* 12/2014 Yu B60C 23/0479
340/447
2016/0075193 A1* 3/2016 Huang B60C 23/0401
340/447

* cited by examiner




FIG. 1




FIG. 2



FIG.3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8



FIG.9



FIG. 10



FIG. 11



FIG. 12




FIG.13