

US00D964261S

(12) **United States Design Patent** (10) **Patent No.:** **US D964,261 S**
Tatsuta et al. (45) **Date of Patent:** **** Sep. 20, 2022**

(54) **TIRE FOR AUTOMOBILE**

D569,337 S * 5/2008 Iwabuchi D12/605
D584,682 S * 1/2009 Tanaka D12/605
D649,111 S * 11/2011 Tokizaki D12/605
D671,066 S * 11/2012 Morito D12/605

(71) Applicant: **SUMITOMO RUBBER INDUSTRIES, LTD.**, Hyogo (JP)

(Continued)

(72) Inventors: **Masahiro Tatsuta**, Kobe (JP); **Ryota Ikeda**, Kobe (JP); **Kohei Hayama**, Kobe (JP); **Yuta Sakakibara**, Kobe (JP); **Akiko Miura**, Kobe (JP)

Primary Examiner — Darlington Ly

(74) *Attorney, Agent, or Firm* — Birch, Stewart, Kolasch & Birch, LLP

(73) Assignee: **SUMITOMO RUBBER INDUSTRIES, LTD.**, Kobe (JP)

(57) **CLAIM**

The ornamental design for a tire for automobile, as shown and described.

(**) Term: **15 Years**

(21) Appl. No.: **35/511,858**

(22) Filed: **Nov. 9, 2020**

DESCRIPTION

(80) **Hague Agreement Data**

Int. Filing Date: **Nov. 9, 2020**

Int. Reg. No.: **DM/211264**

Int. Reg. Date: **Nov. 9, 2020**

Int. Reg. Pub. Date: **May 14, 2021**

1. Tire for automobile

1.1 is a front elevation view of a tire for automobile embodying my new design;

1.2 is an enlarged and partial front elevation view thereof for area marked as A-B in **1.1**;

1.3 is an enlarged and partial front elevation view thereof for area marked as C-D in **1.1**;

1.4 is a rear elevation view thereof;

1.5 is a top plan view thereof;

1.6 is a bottom plan view thereof;

1.7 is a right side elevation view thereof;

1.8 is a left side elevation view thereof;

1.9 is an enlarged and partial cross-sectional view thereof taken along line E-E in **1.2** and showing only the end face at the line E-E in **1.2**;

1.10 is an enlarged and partial cross-sectional view thereof taken along line F-F in **1.2** and showing only the end face at the line F-F in **1.2**;

1.11 is an enlarged view of the area marked as G-G in **1.9**;

1.12 is an enlarged view of the area marked as H-H in **1.9**;

1.13 is an enlarged view of the area marked as I-I in **1.10**; and

1.14 is an enlarged view of the area marked as J-J in **1.10**.

The broken lines in the drawings illustrate portions of the tire for automobile that form no part of the claimed design.

(51) **LOC (13) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/605**


(58) **Field of Classification Search**
USPC D12/500–501, 506, 534–538, 569–573,
D12/604–605, 900; D5/30; D7/396.4,
D7/396.5
CPC B06C 1/00; B06C 13/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D87,418 S * 7/1932 Smith D12/535
D87,419 S * 7/1932 Smith D12/535
D380,713 S * 7/1997 Attinello D12/601
D452,203 S * 12/2001 Kajikawa D12/605
D517,003 S * 3/2006 Shondel D12/605

1 Claim, 14 Drawing Sheets



(56)


References Cited

U.S. PATENT DOCUMENTS


D683,695	S	*	6/2013	Takeshima	D12/605
D695,211	S	*	12/2013	Yasunaga	D12/605
D700,886	S	*	3/2014	Matsumoto	D12/605
D711,816	S	*	8/2014	Iwabuchi	D12/605
D739,344	S	*	9/2015	Kuwano	D12/605
D740,747	S	*	10/2015	Sato	D12/605
D773,987	S	*	12/2016	Ishikawa	D12/605
D777,656	S	*	1/2017	Maxwell	D12/605
D791,068	S	*	7/2017	Ishikawa	D12/605
D792,842	S	*	7/2017	Itoi	D12/605
D800,646	S	*	10/2017	Sato	D12/605
D802,526	S	*	11/2017	Ishikawa	D12/605
D830,960	S	*	10/2018	Sato	D12/605

* cited by examiner


1.1




1.2



1.3



1.4




1.5




1.6




1.7




1.8




1.9




1.10




1.11



1.12



1.13



1.14

