

US00D967438S

(12) **United States Design Patent** (10) **Patent No.:** **US D967,438 S**
Andersen et al. (45) **Date of Patent:** **** Oct. 18, 2022**

(54) **SENSOR WITH BATTERY**
(71) Applicant: **GE Precision Healthcare LLC**,
Milwaukee, WI (US)
(72) Inventors: **Klaus Axel Andersen**, Helsinki (FI);
Emma Elina Hellman, Espoo (FI); **Lei Xia**, Shanghai (CN)
(73) Assignee: **GE Precision Healthcare LLC**,
Milwaukee, WI (US)
(**) Term: **15 Years**
(21) Appl. No.: **29/764,731**
(22) Filed: **Dec. 31, 2020**
(51) **LOC (13) Cl.** **24-02**
(52) **U.S. Cl.**
USPC **D24/187**
(58) **Field of Classification Search**
USPC D24/107, 164–169, 185, 186, 187, 200,
D24/240; D13/103, 107, 110, 120, 123,
D13/133; D14/356, 358, 383–386, 432,
D14/433, 434, 435, 435.1, 437,
D14/480.1–480.7, 484, 484.1
CPC H05K 5/006; H01R 31/005; H01R 27/02;
B60R 16/02; A61B 5/1473; A61B 5/6833;
A61B 5/688; A61B 5/0002; A61B 5/042;
A61B 5/0404; A61B 5/0416; G01D
11/245
See application file for complete search history.

D825,568 S * 8/2018 Morris D14/433
D856,285 S * 8/2019 Szymura D13/147
D877,152 S * 3/2020 Maus D14/435.1
D904,417 S * 12/2020 Cueto D14/240
D939,504 S * 12/2021 Zhang D14/433
D943,532 S * 2/2022 Zhang D13/133

FOREIGN PATENT DOCUMENTS

JP D2019-25276 * 8/2020

OTHER PUBLICATIONS

Annual Physical in a Patch: GE Scientists Developing Wearable Multi-Device Sensor Patch that Measures Sweat, Interstitial Fluids and other Key Vitals. Online, published date Sep. 5, 2019. Retrieved on Mar. 4, 2022 from URL: <https://www.ge.com/news/press-releases/annual-physical-patch-ge-scientists-developing-wearable>.*

* cited by examiner

Primary Examiner — Omeed Agilee

(74) *Attorney, Agent, or Firm* — McCoy Russell LLP

(57) **CLAIM**

The ornamental design for a sensor with battery, as shown and described.

DESCRIPTION

FIG. 1 is a front-left perspective view of a sensor with battery according to the claimed design.

FIG. 2 is a rear-left perspective view of the sensor with battery.

FIG. 3 is a front view of the sensor with battery.

FIG. 4 is a rear view of the sensor with battery.

FIG. 5 is a right side view of the sensor with battery.

FIG. 6 is a left side view of the sensor with battery.

FIG. 7 is a top view of the sensor with battery; and,

FIG. 8 is a bottom view of the sensor with battery.


The broken lines in the drawings depict portions of the sensor with battery that form no part of the claimed design.

1 Claim, 8 Drawing Sheets

(56) **References Cited**

U.S. PATENT DOCUMENTS

D393,830 S * 4/1998 Tobler D13/133
D603,966 S * 11/2009 Jones D24/165
D606,656 S * 12/2009 Kobayashi D24/167
D618,803 S * 6/2010 Lash D24/168
D621,041 S * 8/2010 Mao D24/135
D678,202 S * 3/2013 Corona D13/133
D766,183 S * 9/2016 Corona D13/133
D773,057 S * 11/2016 Vandiver D24/186






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7



FIG. 8