



US00D977476S

(12) **United States Design Patent**
Tully et al.

(10) **Patent No.:** **US D977,476 S**

(45) **Date of Patent:** **** Feb. 7, 2023**

(54) **SENSOR DEVICE**

(71) Applicant: **SPLUNK Inc.**, San Francisco, CA (US)

(72) Inventors: **Timothy Tully**, Menlo Park, CA (US);
Tishan Mills, Toronto (CA); **Jesse Chor**, Saratoga, CA (US); **Robert Fullerton**, Morgan Hill, CA (US)

(73) Assignee: **SPLUNK Inc.**, San Francisco, CA (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/768,604**

(22) Filed: **Jan. 29, 2021**

(51) **LOC (14) Cl.** **14-02**

(52) **U.S. Cl.**
USPC **D14/358**

(58) **Field of Classification Search**
USPC D10/46, 49, 50, 52, 53; D13/162;
D14/125, 230, 242, 314, 336, 358, 371,
D14/384
CPC G06F 11/323; G06F 11/0709; G06F
11/3476; G06F 17/40; G06F 11/3006;
G06F 16/24568; G06F 11/0787; G06F
2201/86; H04W 4/38; H04W 4/70; H04L
43/04; H04L 67/12; H04L 43/045
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D491,563 S *	6/2004	Sato	D14/242
D549,191 S *	8/2007	Paradise	D14/125
D566,661 S *	4/2008	Ludwig	D13/162
D648,641 S *	11/2011	Wallaert	D10/49
D648,642 S *	11/2011	Wallaert	D10/49
D667,005 S *	9/2012	Lutz	D14/314
D678,084 S *	3/2013	Beland	D10/50
D684,872 S *	6/2013	Bias	D10/49
D705,746 S *	5/2014	Lin	D14/125

D727,857 S *	4/2015	Acera	D13/162
D729,793 S *	5/2015	Hickok	D14/336
D729,797 S *	5/2015	Hickok	D14/371
D733,591 S *	7/2015	Golden	F24F 11/59 D10/50
D734,179 S *	7/2015	Golden	G01D 11/245 D10/50
D738,756 S *	9/2015	Jiang	G05D 23/19 D10/50
D744,433 S *	12/2015	Baumgartner	D10/49
D756,976 S *	5/2016	Jou	D14/242
D789,360 S *	6/2017	Moon	D14/240
D830,860 S *	10/2018	Berman	D10/50
D854,429 S *	7/2019	Gentle	D10/50
D860,011 S *	9/2019	Berman	H04W 4/70 D10/50
D862,405 S *	10/2019	Russo	D14/125

(Continued)

Primary Examiner — George D. Kirschbaum

Assistant Examiner — Lillian Windham

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP


(57) **CLAIM**

The ornamental design for sensor device, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a sensor device showing our new design;
FIG. 2 is a rear perspective view thereof;
FIG. 3 is a bottom perspective view thereof;
FIG. 4 is a top plan view thereof;
FIG. 5 is a bottom plan view thereof;
FIG. 6 is a front elevation view thereof;
FIG. 7 is a rear elevation view thereof;
FIG. 8 is a left-side elevation view thereof; and,
FIG. 9 is a right-side elevation view thereof.
The broken lines shown illustrate portions of the sensor device that form no part of the claimed design.

1 Claim, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D863,990 S * 10/2019 Hu D10/53
D864,194 S * 10/2019 Perry D14/336
D864,773 S * 10/2019 Zhang D10/52
D874,950 S * 2/2020 Gentle D10/50
D876,402 S * 2/2020 Liu D14/230
D882,528 S * 4/2020 Fariello D13/162
D900,796 S * 11/2020 Wang D14/242
D901,314 S * 11/2020 Atwood D10/50
D917,439 S * 4/2021 Mochizuki D14/358
D933,061 S * 10/2021 Kao D14/336
2015/0323941 A1 * 11/2015 Pariseau G05D 23/19
236/1 C
2020/0116377 A1 * 4/2020 Heintzelman F24F 11/59
2020/0116533 A1 * 4/2020 Read G01D 11/245
2021/0241926 A1 * 8/2021 Chor H04W 4/70

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9