



US00D985485S

(12) **United States Design Patent**
Kuriyama

(10) **Patent No.:** **US D985,485 S**

(45) **Date of Patent:** **** May 9, 2023**

- (54) **TIRE**
- (71) Applicant: **Toyo Tire Corporation**, Itami (JP)
- (72) Inventor: **Hikaru Kuriyama**, Itami (JP)
- (73) Assignee: **Toyo Tire Corporation**, Itami (JP)
- (**) Term: **15 Years**

- D791,067 S * 7/2017 Iwabuchi D12/605
- D791,693 S * 7/2017 Iwabuchi D12/605
- D795,798 S * 8/2017 Kamada D12/605
- D800,643 S * 10/2017 Scheifele D12/605
- D803,149 S * 11/2017 Ishikawa D12/605
- D804,402 S * 12/2017 Kamada D12/605
- D807,284 S * 1/2018 Iwabuchi D12/605
- D808,333 S * 1/2018 Iwabuchi D12/605
- D813,799 S * 3/2018 Maxwell D12/605
- D843,930 S * 3/2019 Itoi D12/605
- D856,915 S * 8/2019 Nagase D12/605

(Continued)

(21) Appl. No.: **29/817,321**

(22) Filed: **Nov. 30, 2021**

(30) **Foreign Application Priority Data**

Jun. 4, 2021 (JP) 2021-012000 D

(51) **LOC (14) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/605**

(58) **Field of Classification Search**
USPC D12/604, 605
CPC B60C 13/00; B60C 1/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D449,576 S * 10/2001 Kajikawa D12/605
- D450,034 S * 11/2001 Kajikawa D12/605
- D452,203 S * 12/2001 Kajikawa D12/605
- D550,150 S * 9/2007 Shondel D12/605
- D569,336 S * 5/2008 Onoe D12/605
- D590,332 S * 4/2009 Sato D12/605
- D593,486 S * 6/2009 Yonetsu D12/605
- D600,199 S * 9/2009 Ibaraki D12/605
- D618,165 S * 6/2010 Sato D12/605
- D662,877 S * 7/2012 Arrant D12/605
- D666,143 S 8/2012 Sato
- D693,761 S 11/2013 Nakamura
- D709,025 S * 7/2014 Takahashi D12/605
- D768,565 S * 10/2016 Yasunaga D12/605
- D769,807 S * 10/2016 Ishikawa D12/605

FOREIGN PATENT DOCUMENTS

CN 301432282 S 1/2011

Primary Examiner — Michelle E. Wilson

Assistant Examiner — Clese Moore, Jr.

(74) *Attorney, Agent, or Firm* — Sterne, Kessler, Goldstein & Fox P.L.L.C.

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a tire showing the claimed design;

FIG. 2 is a front view thereof;

FIG. 3 is a rear view thereof;

FIG. 4 is a top plan view thereof, the bottom plan view being the same;


FIG. 5 is a left side view thereof, the right side view being the same;

FIG. 6 is an enlarged view of the portion between lines 6-6 and 6'-6' in FIG. 2; and,

FIG. 7 is an enlarged cross-sectional view taken along line 7-7 in FIG. 6.

In the drawings, the broken lines show portions of the tire that form no part of the claimed design.

1 Claim, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

| | | | | | | |
|----------|---|---|---------|----------|-------|---------|
| D858,431 | S | * | 9/2019 | Yamaoka | | D12/605 |
| D865,658 | S | * | 11/2019 | Kuwano | | D12/605 |
| D867,982 | S | * | 11/2019 | Iwabuchi | | D12/605 |
| D879,029 | S | * | 3/2020 | Tanaka | | D12/605 |
| D880,416 | S | * | 4/2020 | Ishikawa | | D12/605 |
| D896,166 | S | * | 9/2020 | Yamaoka | | D12/605 |

* cited by examiner




FIG. 1




FIG. 2




FIG. 3



FIG. 4



FIG. 5




FIG. 6




FIG. 7