

US00D997006S

(12) **United States Design Patent** (10) **Patent No.:** **US D997,006 S**
Marasco et al. (45) **Date of Patent:** **** Aug. 29, 2023**

(54) **BEACON**

(71) Applicant: **Google LLC**, Mountain View, CA (US)

(72) Inventors: **Carly Marasco**, Los Gatos, CA (US);
Warit Tulyathorn, San Francisco, CA (US); **Li Xu**, San Francisco, CA (US)

(73) Assignee: **GOOGLE LLC**, Mountain View, CA (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/708,559**

(22) Filed: **Oct. 8, 2019**

(51) **LOC (14) Cl.** **20-03**

(52) **U.S. Cl.**
USPC **D20/42**

(58) **Field of Classification Search**
USPC D10/109.1–115, 121; D20/10, 19, 21,
D20/41, 42; D26/37, 60, 72
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

D476,374 S * 6/2003 Boire D20/41
D514,165 S * 1/2006 McCudden D20/41
(Continued)

Primary Examiner — Joseph Kukella

(74) *Attorney, Agent, or Firm* — LEASON ELLIS LLP

(57) **CLAIM**

The ornamental design for a beacon, as shown and described.

DESCRIPTION

The patent or application file contains at least one drawing executed in color. Copies of this patent or patent application publication with color drawing(s) will be provided by the Office upon request and payment of the necessary fee.

FIG. 1 is a perspective view of a first embodiment of a beacon according to our new design;

FIG. 2 is a left side view thereof;

FIG. 3 is a right side view thereof;

FIG. 4 is a front view thereof;

FIG. 5 is a rear view thereof;

FIG. 6 is a top view thereof;

FIG. 7 is a bottom view thereof; and

FIG. 8 is the perspective view of FIG. 1 showing the beacon in its environmental context.

FIG. 9 is a perspective view of a second embodiment of a beacon according to our new design shown in a lit state in which a glow is shown in broken lines to portray illumination;

FIG. 10 is a left side view thereof;

FIG. 11 is a right side view thereof;

FIG. 12 is a front view thereof;

FIG. 13 is a rear view thereof;

FIG. 14 is a top view thereof;

FIG. 15 is a bottom view thereof;

FIG. 16 is the perspective view of FIG. 9 showing the beacon in its environmental context.

FIG. 17 is a perspective view of a third embodiment of a beacon according to our new design;

FIG. 18 is a left side view thereof;

FIG. 19 is a right side view thereof;

FIG. 20 is a front view thereof;

FIG. 21 is a rear view thereof;

FIG. 22 is a top view thereof;

FIG. 23 is a bottom view thereof; and

FIG. 24 is the perspective view of FIG. 17 showing the beacon in its environmental context.

FIG. 25 is a perspective view of a fourth embodiment of a beacon according to our new design shown in a lit state in which a glow is shown in broken lines to portray illumination;

FIG. 26 is a left side view thereof;

FIG. 27 is a right side view thereof;

FIG. 28 is a front view thereof;

(Continued)




FIG. 29 is a rear view thereof;
FIG. 30 is a top view thereof;
FIG. 31 is a bottom view thereof; and,
FIG. 32 is the perspective view of FIG. 25 showing the beacon in its environmental context.
The broken line showing of a pivot in the bottom views of the several embodiments and the retail display fixture upon which the beacon can be seated, and the portrayal of a glow in the embodiments having a lit state, illustrate environmental structure and form no part of the claimed design.

1 Claim, 24 Drawing Sheets
(10 of 24 Drawing Sheet(s) Filed in Color)

(58) Field of Classification Search
CPC F21V 21/00; F21V 21/02; F21V 21/041
See application file for complete search history.

(56)		References Cited			
		U.S. PATENT DOCUMENTS			
D602,092	S *	10/2009	Tonnessen		D20/42
D608,734	S *	1/2010	Smith		D20/19
D657,425	S *	4/2012	Podd		D20/43
D660,367	S *	5/2012	Podd		D20/43
D660,368	S *	5/2012	Podd		D20/43
D660,369	S *	5/2012	Podd		D20/43
D660,370	S *	5/2012	Podd		D20/43
D665,030	S *	8/2012	Podd		D20/42
D753,770	S *	4/2016	McCulough		D20/42
D764,592	S *	8/2016	Zenoff		D20/42
D791,242	S *	7/2017	Lemberger		D20/41
D791,878	S *	7/2017	Loew		D20/41
D797,855	S *	9/2017	Katsuno		D12/415
D803,943	S *	11/2017	Loew		D20/41
D835,723	S *	12/2018	Basha		D20/41
D842,382	S *	3/2019	Loew		D20/41
D872,801	S *	1/2020	Formel		D20/42
D894,279	S *	8/2020	Loew		D20/41

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8



Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13

Fig. 14





Fig. 15






Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29

Fig. 30





Fig. 31






Fig. 32