

[54] **TUBULAR CONNECTION**
 [75] Inventor: **Thomas L. Blose, Houston, Tex.**
 [73] Assignee: **Hydril Company, Los Angeles, Calif.**
 [21] Appl. No.: **911,117**
 [22] Filed: **May 31, 1978**

Related U.S. Patent Documents

Reissue of:

[64] Patent No.: **3,989,284**
 Issued: **Nov. 2, 1976**
 Appl. No.: **570,633**
 Filed: **Apr. 23, 1975**

[51] Int. Cl.³ **F16L 15/00**
 [52] U.S. Cl. **285/332.2; 285/334; 403/343**
 [58] Field of Search **285/334, 333, 355, 390, 285/332.2, 332.3; 403/343, 118; 85/46**

[56] **References Cited**

U.S. PATENT DOCUMENTS

671,274	4/1901	Fischer	85/46 X
1,474,375	11/1923	Moore	285/355 X
2,206,223	7/1940	Dearborn .	
2,207,005	7/1940	Haas .	
2,239,942	4/1941	Stone et al.	285/334 X
2,267,923	12/1941	Johnson	85/46 X
2,532,632	12/1950	MacArthur .	
2,543,100	2/1951	Engh	85/46 X
2,781,206	2/1957	Ragland	285/106
2,893,759	7/1959	Blose	285/334
2,980,451	4/1961	Taylor et al.	285/332.3
3,047,316	7/1962	Wehring et al.	285/334
3,100,656	8/1963	MacArthur	285/55
3,224,799	12/1965	Blose et al.	285/334
3,266,821	8/1966	Safford	285/40

3,307,860	3/1967	Blount et al.	285/55
3,336,054	8/1967	Blount et al.	285/55
3,345,084	10/1967	Hanes et al.	285/27
3,345,085	10/1967	Hanes	285/27
3,345,087	10/1967	Hanes et al.	285/39
3,346,278	10/1967	Yocum	285/333
3,359,013	12/1967	Knox et al.	285/13
3,419,289	12/1968	Lari	285/178
3,425,719	2/1969	Burton	285/382.2
3,467,413	9/1969	Madrelle	285/332.2
3,489,437	1/1970	Duret	285/55
3,495,854	2/1970	Fether	285/173
3,497,246	2/1970	Weiner	285/333
3,572,777	3/1971	Blose	285/334
3,574,373	4/1971	LeDerf .	
3,600,011	8/1971	Alvis	285/305
3,850,461	11/1974	Fujioka et al.	285/332.2
3,994,516	11/1976	Fredd	285/39
4,002,359	1/1977	Lari	285/331
4,004,832	1/1977	Connelly	285/333
4,009,893	3/1977	Schatton et al.	285/110
4,040,756	8/1977	Donegan	403/307

FOREIGN PATENT DOCUMENTS

568114	1/1933	Fed. Rep. of Germany	403/343
137777	1/1920	United Kingdom	85/46
528932	11/1940	United Kingdom .	

Primary Examiner—Thomas F. Callaghan
Attorney, Agent, or Firm—Pravel, Gambrell, Hewitt, Kirk, Kimball & Dodge

[57] **ABSTRACT**

A pipe joint includes pin and box members having inter-engaged threads characterized as producing hoop tension in the pin member and hoop compression in the box members.

61 Claims, 9 Drawing Figures




FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.




FIG. 5.




FIG. 6a.




FIG. 6.




FIG. 7.




FIG. 8.





FIG. 9.



TUBULAR CONNECTION

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

BACKGROUND OF THE INVENTION

This invention relates generally to thread connected joints as usable in oil well tubing, casing, line pipe and drill pipe (all of which will be referred to as pipe, for convenience). More particularly, it concerns a means for connecting joint pin and box members in a manner to provide minimal hoop, radial or axial stresses induced by assembly or applied torque.

With increased concern for protection of our environment, it is becoming more important that tubular joint connections used in oil industry be capable of performing with maximum security under all conditions characteristic of the operating tasks they are relied upon to fulfill. Basic fundamental technology required to meet these performances must be satisfied through all operating stress or strain levels. Today there are no tubular connections produced anywhere in the world which will meet these requirements through all operating stress or strain conditions characteristic of services to which they may be exposed. In most cases, margins of safety are inherently smaller as severity of performance increases. There is a need for a connection that will have mechanical integrity which will not be weakened by load stresses or strains induced by tension, compression, internal pressure, external pressure, torsion, bending, thermal variances, or any combination of these until the material itself has failed by limitations of metallurgical properties in rupture or fracture.

SUMMARY OF THE INVENTION

It is a major object of the invention to provide a pipe joint meeting the above need. Basically, the joint comprises interengaged thread means on pin and box members for producing hoop tension in the pin member and hoop compression in the box member in response to forcible make-up of the members, the thread means having a dove-tail interfit. As will appear, the thread means includes helical threading on each of the pin and box members, with greater pitch distance at the thread tip than at the thread root. Also, the threading typically has progressively reducing axial width along its helical length, so that the conditions of hoop tension and compression as described will be created upon final make-up, at which time the interengaged threads preferably having wedging flank interfit to limit such make-up.

As will appear, the dove-tail (semi or full) thread flanks will interlock the elements of the connection. When torque is applied to assemble the connection, rotational movement between elements will stop when the wedges (threads) are made up on the flanks of the groove between the threads. Since the threads are wedge type and interlocked by a negative face angle on the back flank and the crests and roots are parallel, the strain reactions to applied torque are primarily axial in direction. Torque is resisted by the axial "squeezing" of the threads. Since back flank is intended to always be negative (back flank to the root plane will be less than 90°), thread strain reactions against this surface will cause the box member to be pulled radially inward and the pin member to be pulled radially outward. There-

fore, the box member attains a condition of hoop compression while the pin will be in hoop tension. Excessive torque will only result in high axial squeezing forces on the threads and have very little effect in inducing other extraneous stresses other than some minor degree of bending of end threads.

Further, the threads are so designed that possible clearances between mating crests and roots will be minimal while flanks will be in wedging interference. In this manner the threads will be functionally leak resistant. The primary resistance to leakage through this connection will typically be accomplished by a separately functional metal to metal seal. One or more such seals may be incorporated for this requirement. In any case, the seals will be located adjacent to or within the thread areas so that they can receive the benefits of the interlocking threads. When properly located and suitable interference (radial) established, the leak resistance of the connection will not be affected by torque, tension, internal or external pressures, bending axial compression, or radical thermal changes in response to internal or externally applied temperature differences.

It is another object of the invention to provide a pin and box connection employing thread means as described which will interlock in such manner as to prevent opening up of a seal between the members in response to fluid pressure (internal or external) application to the seal zone; further, it is an object to provide the interlock at axially opposite sides of the seal zone so that the pin and box members are clamped against relative radial separation at opposite ends of the seal zone, preventing opening up of the latter in response to fluid pressure application.

Accordingly important objects and benefits to be obtained from a tubular connection constructed as described are:

1. To offer torsional strength equivalent to that of the full pipe body, without the use of either an internal or an external shoulder.
2. To obtain a joint strength in either tension or compression equivalent to the strength of the full pipe body.
3. To resist radial strain differentials caused by the application of either external or internal pressures which normally reduce the effective interferences between sealing elements.
4. To mechanically interlock the two joint elements so that high bending stresses will be ineffective to the leak resistant integrity of the connection.
5. To produce a connection or non-upset pipe that will have full performance properties comparable to those of integral upset products.
6. To make it possible to recover used or damaged upset pipe by cutting off the upset ends and apply the new connection as threaded and coupled, with performance capabilities comparable to new integral upset end connections.
7. To make a connection for line pipe that will be virtually self-locking with high resistance to unscrewing.

These and other objects and advantages of the invention, as well as the details of illustrative embodiments, will be more fully understood from the following description and drawings, in which:

DRAWING DESCRIPTION

FIG. 1 is a section in an axial radial plane through a pipe joint embodying the invention;

FIG. 2 is an enlarged view of made-up threading (full dove-tail) in the FIG. 1 joint;

FIG. 3 is an enlarged view of pin or box member threading as seen in FIG. 2;

FIG. 4 is a perspective showing of a projected thread as seen in FIG. 3;

FIG. 5 is a view like FIG. 2, but showing the threading prior to completion to make-up;

FIG. 6 is a section in an axial radial plane through a two-step pipe joint embodying the invention;

FIG. 6a is a view like FIG. 6 showing a variation;

FIG. 7 is an enlarged view of made-up threading (semi-dove-tail) in the FIG. 6 joint;

FIG. 8 is an enlarged view of pin or box member threading as seen in FIG. 7; and

FIG. 9 is a view like FIG. 2 but showing axially tapering threading.

DETAILED DESCRIPTION

Referring first to FIGS. 1-5, a pipe joint 10 includes pin and box members 11 and 12, the joint defining an axis 13. Interengaged thread means on the members include helical threading or threads 14 and 15 characterized as producing hoop tension in the pin member, and hoop compression in the box member in response to forcible make-up of the members. As such time, the threads 14 and 15 have dove-tail interfit as at flank 16 on thread 14 engaged with flank 17 on thread 15, and opposite flank 18 on thread 14 engaged with flank 19 on thread 15. In other words, the angles α and β as shown are acute, angle α formed between flank 18 and root wall 20 of thread 14 (or between flank 19 and root wall 21 of thread 15); and the angle β formed between flank 16 and root wall 20 (or between flank 17 and root wall 21). Walls 20 and 21 are cylindrical, and parallel to axis 13. Note the clearances at 22 and 23 between those root walls and the cylindrical tips 24 and 25 of the threads 14 and 15, respectively. Further, flanks 16 and 18 on thread 14 flare toward the thread lips 24, and flanks 17 and 19 flare toward thread tip 25. Thus threads 14 and 15 define full dove-tail.

It will be noted the helical thread 14 has greater pitch distance (i.e. in an axial direction) between flanks 16 and 18 at the thread tip than at the thread root; likewise, helical thread 15 has greater axial pitch distance between flanks 17 and 19 at the thread tip than at the thread root. Further, each thread 14 and 15 has progressively reducing width, or pitch distance, along the helical length thereof. This is clear from FIG. 1 by comparison of the widths of the thread 15 at locations 15a . . . 15f, and of the widths of the thread 14 at axially spaced locations 14a . . . 14c. The linear projection of thread 14 in FIG. 4 clearly shows progressive width decrease along the thread length. At the same time, the pitch distance between corresponding points on successive thread turns, in axial radial planes, is the same as is clear from comparison of FIGS. 2 and 5.

It is a further clear from FIGS. 1 and 2 that the threads 14 and 15 have vertically wedging interfit to limit make-up. Prior to completion of such make-up, i.e. in partially made-up condition, there are gaps between the threads 14 and 15, as is clear from FIG. 5. The latter may, for example, illustrate the position of thread section 15a, as it is rotated past section 14b, such section

also being indentified in FIG. 1. Note gaps 30 and 31 in FIG. 5.

The angles α and β should be less than about 85° to enable the interengaged flanks to resist unscrewing or disassembly of the joint. When the connection is assembled power tight, the sealing surfaces will be locked together because of the thread from which secures the two joint elements in intimate contact through any degree of, or direction of, radial strain. Maximum load stresses can be transmitted through the connection in any direction (radial or axial) without disengagement of the two mating elements. Multi-directional stresses may be applied without decreasing performance capabilities of the connection. The wedging action of the front and back flanks of made up threads not only offers a positive stop for make-up without the use of an auxiliary shoulder but offers maximum attainable resistance to torque, tension, compression, or any other induced load condition without resulting in detrimental strain reaction to the sealing qualities of the joint. This flank wedging action also prevents the normal tendency of threads to bend or deflect under high axial load conditions which normally lead to possible "pullout" or joint separation followed by leakage, or telescoping from compressive loads. The connection is securely interlocked in a manner which resists strain differentials between the two joint elements when subjected to load stresses in any direction or from any operational cause.

FIG. 1 also shows the provision of annular beveled shoulders 33 and 34 on the respective members 11 and 12, and having metal-to-metal sealing interfit in response to joint make-up. In addition, the interengaged flanks 16 and 17, and 18 and 19, provide metal-to-metal seals along the thread length.

FIGS. 6-8 illustrate another form of the invention, wherein semi dove-tail threads 40 and 41 are formed on pin and box members 42 and 43 forming joint 44. The latter is shown in the form of a two step thread, with a second pair of threads 40' and 41' (corresponding to threads 40 and 41) at a greater radius from the center line or axis 45 than threads 40 and 41. Note metal-to-metal annular seals which are established at locations 46 and 47 upon full make-up of the joint.

In FIG. 7, the angularity γ of interengaged flanks 48 and 49 (of respective threads 40 and 41) from the direction of the axis 45 should be less than about 85° , but greater than zero, in a manner similar to angles α and β in FIG. 2; on the other hand, interengaged flanks 51 and 52 on threads 40 and 41 extend radially, in axial radial planes.

Referring back to FIG. 6, a tapered metal-to-metal annular seal is formed at 55 between the pin and box members; also, the nose 56 the pin 42 annularly engages a non-metallic (as for example molded tetrafluoroethylene) seal ring 57 received in an annular recess 58 in the box member 43 to block leakage of corrosive well fluid to the interengaged threads.

FIG. 9 illustrates an application of the invention to a joint 60 wherein threads 61 and 62 on pin and box members 63 and 64 taper, axially. Note the fully dove-tailed threading of the type seen in FIG. 2; however the tips 65 and 66 of the threads progress toward axis 67 along the thread lengths.

FIG. 6a is like FIG. 6, but varies in that annular shoulders are provided on the members at 89 and 90, these being axially tapered as shown. Such shoulders come into pressural interengagement upon make-up of the members, and have sealing interfit in a zone between

axial cylinders indicated at 91 and 92. Cylinder 91 is defined by the crests of threads 140 (corresponding to threads 40 in FIG. 6) which mesh with threads 141 (corresponding to threads 41 in FIG. 6), and cylinder 92 is defined by the crests of threads 141' (corresponding to threads 41' in FIG. 6) meshing with threads 140' (corresponding to threads 40' in FIG. 6). The interengaged threads at the two steps serve to positively lock or clamp the pin and box members 142 and 143 together against relative radial separation, at or proximate opposite ends of the sealing interfit shoulders 89 and 90, whereby the latter cannot open up to leak fluid pressure therebetween. All of this may be provided in a non-upset joint, or in an upset joint, as desired. Fracture of the joint cannot occur at the seal zone because strain is minimized or non-existent in the members defining the seal zone, due to the positive interlock provided by the interlocked threads.

Finally, the thread elements of the connection may be either single or multiple pitch. The variance in pitch between joints will be related to product requirements of performance rather than size or other physical dimensions.

I claim:

1. In a pipe joint including pin and box members, the joint having an axis,

- a. a pair of interengaged threads on said members for producing hoop tension in the pin member and hoop compression in the box member in response to forcible make-up of said members,
- b. the threads on said members having dove-tail interfit,
- c. said thread on each member having progressively changing axial width along substantially the entire helical length thereof and at selected radial distance from said axis, whereby upon complete make-up of the joint the interengaged thread flanks produce forces tending to urge the members radially together.

2. The joint of claim 1 wherein each thread has greater pitch width at the thread tip than at the thread root.

3. The joint of claim 2 wherein each thread has opposite flanks one of which in axial radial planes extends radially.

4. The joint of claim 3 wherein the other flank flares toward the thread outer extent relative to said one flank in axial radial planes.

5. The joint of claim 2 wherein each thread has opposite flanks both of which flare toward the outer extent of the thread in axial radial planes.

6. The joint of claim 2 wherein said threads have opposed tips and root walls with clearances formed therebetween, thread flanks forming angles with said thread tips and root walls in axial radial planes, said angles being less than about 85°.

7. The joint of claim 2 wherein the threads on said members in fully made up condition have mutually wedging interfit to limit said make-up.

8. The joint of claim 2 including annular shoulders on said members having sealing interfit in response to said make-up.

9. The joint of claim 8 wherein both of said shoulders are metallic.

10. The joint of claim 8 wherein at least one of said shoulders is non-metallic.

11. The joint of claim 1 including a second pair of interengaged threads like said first pair, said two pairs defining a multiple-step thread.

12. The joint of claim 1 wherein said threads are axially tapered.

13. The joint of claim 11 including annular shoulders on said members having sealing interfit between two of the thread steps.

14. The joint of claim 13 wherein said sealing interfit shoulders taper axially, the interengaged threads at said two steps locking the pin and box members together against relative radial separation at opposite ends of said sealing interfit shoulders.

15. In a pipe joint including pin and box members, the joint having an axis,

- a. annular shoulders on the members having sealing interfit, and
- b. first and second interengaged threads on the respective members, the threads having dovetail interfit and locking the members together against relative separation proximate one axial side of said annular shoulders, each thread having progressively changing axial width along substantially the entire helical length thereof at selected radial distance from said axis, whereby upon complete make-up of the joint the interengaged thread flanks produce forces tending to urge the members radially together.

16. The pipe joint of claim 15 including third and fourth interengaged threads on the respective members, the third and fourth threads having dovetail interfit and locking the members together against relative separation proximate the other axial side of said annular shoulders, each of the third and fourth threads having progressively changing axial width along substantially the entire helical length thereof at selected radial distance from said axis.

17. In a joint including pin and box members, the joint having an axis,

- a. a pair of interengaged threads on said members for producing circumferential tension in the pin member and circumferential compression in the box member in response to forcible make-up of said members,
- b. the threads on said members having dove-tail interfit,
- c. said thread on each member having progressively changing axial width along substantially the entire helical length thereof and at selected radial distance from said axis, whereby upon complete make-up of the joint the interengaged thread flanks produce forces tending to urge the members radially together.

18. The joint of claim 17 wherein each thread has greater pitch width at the thread tip than at the thread root.

19. The joint of claim 18 wherein each thread has opposite flanks, one of which in axial radial planes extends radially.

20. The joint of claim 19 wherein the other flank flares toward the thread outer extent relative to said one flank in axial radial planes.

21. The joint of claim 18 wherein each thread has opposite flanks both of which flare toward the outer extent of the thread in axial radial planes.

22. The joint of claim 18 wherein said threads have opposed tips and root walls with clearances formed therebetween, thread flanks forming angles with said

thread tips and root walls in axial radial planes, said angles, being less than about 85°.

23. The joint of claim 18 wherein said threads on said members in fully made up condition have mutually wedging interfit to limit said make-up.

24. The joint of claim 18 including annular shoulders on said members having sealing interfit in response to said make-up.

25. The joint of claim 24 wherein both of said shoulders are metallic.

26. The joint of claim 24 wherein at least one of said shoulders is non-metallic.

27. The joint of claim 17 including a second pair of interengaged threads like said first pair, said two pairs defining a multiple-step thread.

28. The joint of claim 17 wherein said threads are axially tapered.

29. The joint of claim 24 wherein said sealing interfit shoulders taper axially, the interengaged threads locking the pin and box members together against relative radial separation at opposite ends of said sealing interfit shoulders.

30. A thread structure for a pin member adapted for use in a pipe joint, said pin member having an axis and adapted to be made-up with a mating box member having a complementary thread structure, said thread structure for said pin member comprising:

a helical pin thread structure having at least one dove-tail flank adapted for interfitting with a complementary helical thread flank on a mating box member for producing hoop tension in said pin member and hoop compression in such box member in response to forcible make-up of said pin member with such box member to form a joint;

said helical pin thread structure having progressively changing axial width along substantially the entire helical length thereof and at selected radial distance from the axis, whereby upon complete make-up of the joint the interengaged thread flanks produce forces tending to urge said pin member radially toward such box member;

said pin member including a second pin thread like said first pin thread, said two threads defining a multiple step thread; and

said pin member, including an annular seal shoulder on said pin member between said thread steps adapted for sealing interfit with such box member.

31. The pin member of claim 30, wherein said annular seal shoulder tapers axially, the pin threads at said two steps adapted for locking the pin and box members together against relative radial separation at opposite ends of said seal shoulder.

32. A thread and seal structure for a pin member adapted for use in a pipe joint, said pin member having an axis and adapted to be made-up with a mating box member having a complementary thread structure to form the joint, said thread and seal structure for said pin member comprising:

an annular seal shoulder formed on said pin member adapted for sealing interfit with such box member upon make-up of the joint;

a first helical pin thread structure on said pin member adapted for interengagement with a complementary helical thread structure on such box member upon make-up of the joint;

said first pin thread structure having a flank adapted to have a dove-tail interfit with such thread flank on such box member for locking the pin member and box

member together against relative separation proximate one axial side of said annular seal shoulder upon make-up of the joint; and

said first pin thread structure having progressively changing axial width along substantially the entire helical length thereof at selected radial distance from the axis wherein upon complete make-up of the joint the interengaged thread flanks produce forces tending to urge said pin member and such box member radially together.

33. A thread structure for a pin member adapted for use in a joint, said pin member having an axis and adapted to form a joint upon make-up with a mating box member having a complementary thread structure, said thread structure for said pin member comprising:

a helical pin thread structure on said pin member adapted for producing circumferential tension in said pin member and circumferential compression in such box member in response to forcible make-up with such box member to form the joint;

said helical pin thread structure having a dove-tail flank; and

said helical pin thread structure on said pin member having progressively changing axial width along substantially the entire helical length of said pin thread structure and at a selected radial distance from said axis, whereby upon complete make-up of the joint the thread flanks produce forces tending to urge said pin member radially together with such box member.

34. The pin member of claim 33, wherein said pin thread structure has greater pitch width at the thread tip than at the thread root.

35. The pin member of claim 34, wherein said pin thread structure has opposite flanks, one of which in axial radial planes extends radially.

36. The pin member of claim 35, wherein the other flank flares toward the thread outer extent relative to said one flank in axial radial planes.

37. The pin member of claim 34, wherein said pin thread structure has opposite flanks both of which flare toward the outer extent of the thread in axial radial planes.

38. The pin member of claim 34, wherein said pin thread flank forms an angle with said thread tips and root walls in axial cylindrical planes, said angle being less than about 85°.

39. The pin member of claim 34, wherein the thread structure on said pin member is adapted in fully made-up condition to have mutually wedging interfit with such box member having complementary thread structure to limit said make-up.

40. The pin member of claim 34, including an annular shoulder on said member adapted for sealing interfit with a complementary shoulder on such box member in response to said make-up.

41. The pin member of claim 40, wherein said pin member annular shoulder is metallic.

42. The pin member of claim 40, wherein said pin member annular shoulder is non-metallic.

43. The pin member of claim 33, including a second thread structure like said first thread structure, said pair defining a multiple-step thread structure.

44. The pin member of claim 33, wherein said thread structure is axially tapered.

45. The pin member of claim 40, wherein said annular shoulder tapers axially.

46. A thread structure for a box member adapted for use in a pipe joint, said box member having a complementary

thread structure, said thread structure for said box member comprising:

a helical box thread structure having at least one dove-tail flank adapted for interfitting with a complementary helical thread flank on a mating pin member for producing hoop compression in said box member and hoop tension in such pin member in response to forcible make-up of said box member with such pin member to form a joint;

said helical box thread structure having progressively changing axial width along substantially the entire helical length thereof and at selected radial distance from the axis, whereby upon complete make-up of the joint the interengaged thread flanks produce forces tending to urge said box member radially towards such pin member;

said box member including a second box thread like said first box thread, said two box threads defining a multiple step thread; and

said box member including an annular seal shoulder on said box member between said thread steps adapted for sealing interfit with such pin member.

47. The box member of claim 46, wherein said annular seal shoulder tapers axially, the box threads at said two steps adapted for locking the pin and box members together against relative radial separation at opposite ends of said shoulder.

48. A thread structure and seal for a box member adapted for use in a pipe joint, said box member having an axis and adapted to be made-up with a mating pin member having a complementary thread structure to form the joint, said thread structure and seal for said box member comprising:

an annular seal shoulder formed on said box member adapted for sealing interfit with such pin member upon make-up of the joint;

a first helical box thread structure on said box member adapted for interengagement with a complementary helical thread structure on such pin member upon make-up of the joint;

said first box thread structure having a flank adapted to have a dove-tail interfit with such thread flank on such pin member for locking the box member and pin member together against relative separation proximate one axial side of said annular seal shoulder upon make-up of the joint; and

said first box thread structure having progressively changing axial width along substantially the entire helical length thereof at selected radial distance from the axis wherein upon complete make-up of the joint the interengaged thread flanks produce forces tending to urge said box member and such pin member radially together.

49. A thread structure for a box member adapted for use in a joint, said box member having an axis and adapted to

be made-up with a mating pin member having a complementary thread structure, said thread structure for said box member comprising:

a helical box thread structure on said box member adapted for producing circumferential compression in said box member and circumferential tension in such pin member in response to forcible make-up with such pin member;

said helical box thread structure having a dove-tail flank; and

said helical box thread structure having progressively changing axial width along substantially the entire helical length of said box thread structure and at a selected radial distance from said axis, whereby upon complete make-up of the joint the thread flanks produce forces tending to urge said box member radially together with such pin member.

50. The box member of claim 49, wherein said box thread structure has greater pitch width at the thread tip than at the thread root.

51. The box member of claim 50, wherein said box thread structure has opposite flanks, one of which in axial radial planes extends radially.

52. The box member of claim 51, wherein the other flank flares toward the thread outer extent relative to said one flank in axial radial planes.

53. The box member of claim 50, wherein said box thread structure has opposite flanks both of which flare toward the outer extent of the thread in axial radial planes.

54. The box member of claim 50, wherein said box thread flank forms an angle with said thread tips and root walls in axial cylindrical planes, said angle being less than about 85°.

55. The box member of claim 50, wherein the thread structure on said box member is adapted in fully made-up condition to have mutually wedging interfit with such pin member having complementary thread structure to limit said make-up.

56. The box member of claim 50, including an annular shoulder on said member adapted for sealing interfit with a complementary annular shoulder on such pin member in response to said make-up.

57. The box member of claim 56, wherein said box member annular shoulder is metallic.

58. The box member of claim 56, wherein said box member annular shoulder is non-metallic.

59. The box member of claim 49, including a second thread structure like said first thread structure, said pair defining a multiple step thread structure.

60. The box member of claim 49, wherein said thread structure is axially tapered.

61. The box member of claim 56, wherein said annular shoulder tapers axially.

* * * * *