



US00RE35655E

United States Patent [19]

[11] E

Patent Number: Re. 35,655

Hoshino et al.

[45] Reissued Date of Patent: \*Nov. 11, 1997

[54] CONDENSER FOR USE IN A CAR COOLING SYSTEM

[75] Inventors: Ryoichi Hoshino, Oyamashi; Hironaka Sasaki, Tochigiken; Takayuki Yastuake, Oyamashi, all of Japan

[73] Assignee: Showa Aluminum Corporation, Japan

[\*] Notice: The portion of the term of this patent subsequent to May 2, 2006, has been disclaimed.

[21] Appl. No.: 505,494

[22] Filed: Jul. 21, 1995

Related U.S. Patent Documents

Reissue of:

[64] Patent No.: 5,190,100
Issued: Mar. 2, 1993
Appl. No.: 671,365
Filed: Mar. 19, 1991

Which Was Subject of:

Reexamination
Certificate No.: B1 5,190,100
Dated: Aug. 30, 1994
Request No.: 90/003,073
Filed: Jun. 3, 1993

U.S. Applications:

[60] Continuation of Ser. No. 509,901, Apr. 16, 1990, Pat. No. 5,025,855, which is a division of Ser. No. 328,896, Mar. 27, 1989, Pat. No. 4,936,379, which is a division of Ser. No. 77,815, Jul. 27, 1987, Pat. No. 4,825,941.

[30] Foreign Application Priority Data

Jul. 29, 1986 [JP] Japan ..... 61-179763
Sep. 19, 1986 [JP] Japan ..... 61-144775
Nov. 2, 1986 [JP] Japan ..... 61-263138

[51] Int. Cl.6 ..... F28F 13/08

[52] U.S. Cl. .... 165/146; 165/110; 165/176; 165/DIG. 482

[58] Field of Search ..... 165/110, 146, 165/150, 152, 153, 174, 176

[56] References Cited

U.S. PATENT DOCUMENTS

Table with 4 columns: Patent No., Date, Inventor, and Patent No. Includes entries like Pitts et al. 165/146, Force et al., Askin 257/255, Benzinger, Coy 257/28, Tadewald 257/130, Oddy 165/151, LaPorte et al. 29/157.3, Benjumedra et al. 165/129, Ristow 165/1, Mosier et al. 29/157.3

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

Table with 4 columns: Patent No., Date, Office, and Patent No. Includes entries like European Pat. Off. 0002687 12/1978, European Pat. Off. 255313 7/1983, European Pat. Off. 0138435 9/1984

(List continued on next page.)

Primary Examiner—Allen J. Flanigan


[57] ABSTRACT

A condenser adapted for use in the car cooling system, the condenser comprising a pair of headers provided in parallel with each other; a plurality of tubular elements whose opposite ends are connected to the headers; fins provided in the air paths between one tube and the next; wherein each of the headers is made of a cylindrical pipe of aluminum; wherein each of the tubular elements is made of a flat hollow tube of aluminum by extrusion; and wherein the opposite ends of the tubular elements are inserted into slits produced in the headers so that they are liquid-tightly soldered therein.

REEXAMINATION RESULTS

The questions raised in reexamination request No. 90/003, 919, filed Aug. 7, 1995, have been considered and the results thereof are reflected in this reissue patent which constitutes the reexamination certificate required by 35 U.S.C. 307 as provided in 37 CFR 1.570(e).

14 Claims, 6 Drawing Sheets



U.S. PATENT DOCUMENTS

3,759,321 9/1973 Ares ..... 165/125  
 3,860,038 1/1975 Forni ..... 138/94.3  
 4,141,409 2/1979 Woodhull, Jr. et al. .... 165/110  
 4,201,263 5/1980 Anderson ..... 165/146  
 4,209,059 6/1980 Anthony et al. .... 165/1  
 4,330,034 5/1982 Lang et al. .... 165/113  
 4,332,293 6/1982 Hiramatsu .  
 4,569,390 2/1986 Knowlton et al. .... 165/149  
 4,688,311 8/1987 Guntly .  
 4,825,941 5/1989 Hoshino et al. .... 165/190  
 4,998,580 3/1991 Guntley et al. .... 165/133

FOREIGN PATENT DOCUMENTS

0219974 9/1986 European Pat. Off. .  
 1431920 2/1966 France .  
 2287963 5/1976 France .  
 2367996 5/1978 France .  
 2390694 12/1978 France .  
 2574175 6/1986 France .  
 2129965 12/1971 Germany .  
 2238858 8/1972 Germany .  
 2603968 8/1977 Germany .  
 3005751 2/1980 Germany .  
 3206298 2/1982 Germany .  
 3423746 6/1984 Germany .  
 3536325 11/1985 Germany .

54-17158 8/1952 Japan .  
 48-49054 7/1973 Japan .  
 48-100746 12/1973 Japan .  
 49-114145 10/1974 Japan .  
 55-72795 5/1980 Japan .  
 55-100963 7/1980 Japan .  
 55-10072 8/1980 Japan .  
 56-149295 1/1981 Japan .  
 57-38169 3/1982 Japan .  
 57-66389 4/1982 Japan .  
 57-87576 6/1982 Japan .  
 58-221390 12/1983 Japan .  
 59-19880 6/1984 Japan .  
 59-173693 10/1984 Japan .  
 59-37564 10/1984 Japan .  
 59-181997 12/1984 Japan .  
 60-91977 6/1985 Japan .  
 60-101483 6/1985 Japan .  
 60-191858 12/1985 Japan .  
 61-179763 3/1986 Japan .  
 61-114094 5/1986 Japan .  
 61-93387 5/1986 Japan .  
 61-263138 5/1986 Japan .  
 2167850 6/1966 United Kingdom .  
 1601954 5/1978 United Kingdom .  
 2090652 1/1981 United Kingdom .  
 WO8401208 3/1984 WIPO .




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 14

FIG. 15




FIG. 16





FIG. 17





## CONDENSER FOR USE IN A CAR COOLING SYSTEM

Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of the reexamination certificate or this reissue specification; matter printed in italics indicates the additions made by the reexamination certificate. Matter enclosed in double heavy brackets [ [ ] ] appears in the reexamination certificate but forms no part of this reissue specification; matter printed in bold face indicates the additions made by this reissue.

### RELATED APPLICATION

This is a continuation of application Ser. No. 509,901, filed Apr. 16, 1990 U.S. Pat. No. 5,025,855 the text of which is hereby incorporated by reference, which is a division of co-pending application "Condenser For Use In A Car Cooling System," Ser. No. 328,896, filed Mar. 27, 1989, U.S. Pat. No. 4,936,379, which is a division of co-pending patent application entitled "Condenser for Use in a Car Cooling System", Ser. No. 077,815, filed Jul. 27, 1987 U.S. Pat. No. 4,825,941.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to a condenser for use as a cooler in automobiles, and more particularly to a condenser for such use, which is made of aluminum. Herein "aluminum" includes aluminum alloys.

#### 2. Description of the Prior Art

In general heat exchangers as car coolers use a high pressure gaseous coolant, and they must have an anti-pressure construction.

To this end the known heat exchangers are provided with a core which includes flat tubes arranged in zigzag forms, each tube having pores, and fins interposed between one tube and the next. Hereinafter this type of heat exchanges will be referred to as a serpentine type heat exchanger.

The serpentine type heat exchangers are disadvantageous in that the coolant undergoes a relatively large resistance while flowing throughout the tubes. To reduce the resistance the common practice is to use wider tubes so as to increase the cross-sectional area thereof. However this leads to a large core, and on the other hand an accommodation space in the automobile is very much limited. As a result this practice is not always effective.

Another practice is to placing more fins by reducing the distances between the tubes. This requires that the height of each fin is reduced. However, when the fins are too small the bending work becomes difficult, and takes more time and labor.

In general the condenser has a coolant path which consists of two sections, that is, an inlet section, hereinafter referred to as "condensing section" in which the coolant is still gaseous, and an outlet section, hereinafter referred to as "supercooling section" in which it becomes liquid. In order to increase the heat exchange efficiency it is essential to increase the area for effecting heat transfer in the condensing section, whereas it is no problem for the supercooling section to have a reduced area for heat transfer.

The conventional serpentine type heat exchangers have a coolant passageway which consists of a single tube. It is impossible for a single tube to be large in some part, and small in others. If the tube is to have a wider cross-sectional

section the tube per se must be large throughout the entire length; in other words a large tube must be used. This of course leads to a larger condenser.

As is evident from the foregoing description it is difficult to improve the conventional serpentine type heat exchangers merely by changing the dimensional factors thereof.

Basically the serpentine type heat exchangers involve the complicate process which consists of bending tubes, and then assembling them into a core in combination with fins. This is why it is difficult to produce the heat exchangers on automatic mass production line. Non-automatic production is costly.

### OBJECTS AND SUMMARY OF THE INVENTION

The present invention aims at solving the difficulties pointed out with respect to the conventional serpentine type heat exchangers, and has for its object to provide a condenser having a relatively small core which nevertheless includes a large effective cross-sectional area for coolant passageways, thereby reducing a possible resistance to the flow of coolant.

Another object of the present invention is to provide a condenser having coolant passageways which are divided into a condensing section and a supercooling section which are different in the numbers of tubes from each other.

A further object of the present invention is to provide a condenser having a core whose construction is adapted for enhancing the heat exchange efficiency.

Other objects and advantages of the present invention will become more apparent from the following detailed description, when taken in conjunction with the accompanying drawings which show, for the purpose of illustration only, one embodiment in accordance with the present invention.

According to the present invention there is provided a condenser adapted for use in the car cooling system, the condenser comprising:

- a pair of headers provided in parallel with each other;
- a plurality of tubular elements whose opposite ends are connected to the headers;
- fins provided in the air paths between one tube and the next;
- wherein each of the headers is made of a cylindrical pipe of aluminum;
- wherein each of the tubular elements is made of a flat hollow tube of aluminum by extrusion; and
- wherein the opposite ends of the tubular elements are inserted into slits produced in the headers so that they are liquid-tightly soldered therein.

As is evident from the summary of the invention, the present invention adopts a multi-flow pattern system, whereby the coolant flows through a plurality of tubular elements at one time. The effective cross-sectional area for coolant passageways can be increased merely by increasing the number of tubular elements, thereby reducing resistance acting on the coolant. This leads to the reduction in the pressure loss of coolant.

In general, the multi-flow pattern system is difficult to withstand a high pressure provided by a pressurized gaseous coolant because of the relatively fragile joints between the headers and tubular elements, and the headers per se which are constructed without presupposing the high pressure which would act thereon by the coolant. In order to solve this problem encountered by the multi-flow pattern system the

condenser of the present invention uses a cylindrical pipe for the header, and flat tubes for the tubular elements, whose opposite ends are inserted in the slits produced in the headers and soldered therein, thereby ensuring that the condenser withstands a high pressure provided by the coolant.

Each of the headers is internally divided by a partition into at least two sections; that is, a condensing section and a supercooling section, wherein the condensing section has a coolant in its gaseous state whereas the supercooling section has coolant in its liquid state. When the coolant is in a gaseous state its volume is large, which requires a relatively large effective cross-sectional area for the coolant passageways. When it is in a liquid state the volume reduces, thereby allowing the coolant passageway to have a relatively small cross-sectional area.

According to the present invention there are provided dimensional relationships among the width, height and pitch of the tubular elements and fins as follows:

Width of the tubular element: 6 to 12 mm

Height of the tubular element: 5 mm or less

Height of each fin: 8 to 16 mm

Fin Pitch: 1.6 to 3.2 mm

The tubular elements are jointed to the headers; more specifically, the opposite ends of each tubular element are inserted into slits produced in the headers so that they fit therein in a liquid-tight manner and then they are soldered therein. Prior to the insertion the tubular elements or the headers or both are provided with a layer of a soldering substance. All the soldering is effected at one time by placing the assembled unit in a furnace, thereby saving time and labor in the assembling work.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front view showing a condenser embodying the present invention;

FIG. 2 is a plan view showing the condenser of FIG. 1;

FIG. 3 is a perspective view showing the joint between the header and the individual tubes;

FIG. 4 is a cross-sectional view through the line 4—4 in FIG. 1;

FIG. 5 is a cross-sectional view showing the joint between the header and the tube;

FIG. 6 is a cross-sectional view of the tube exemplifying a dimensional relationship about it;

FIG. 7 is a cross-sectional view of the fin exemplifying a dimensional relationship about it;

FIG. 8 is an explanatory view showing a flow pattern of coolant;

FIG. 9 is a perspective view showing a modified version of the joint between the tubes and the header;

FIG. 10 is a cross-sectional view showing the relationship between the tube and the header after they are jointed to each other;

FIGS. 11A-11C are cross-sectional views showing a modified version of the stopper produced in the tube;

FIGS. 12A-12C are cross-sectional views showing another modified version of the stopper;

FIGS. 13A-13C are cross-sectional views showing a further modified version of the stopper;

FIG. 14 is front view showing a modified version of the condenser;

FIG. 15 is a graph showing the relationship between the width of the tubes and the rate of air passage therethrough;

FIG. 16 is a graph showing the relationship between the height of the tubes and the pressure loss of air; and

FIG. 17 is a graph showing variations in the heat exchange efficiency with respect to the height of the fins and the pressure loss of air.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

As shown in FIG. 1 the condenser 10 of the present invention includes a plurality of planar tubes 11, and corrugated fins 12 alternately arranged. The tubes 11 are connected to headers 13 and 14 at their opposite ends.

The tube 11 is planar, made of aluminum; preferably, of a multi-hollow type.

The header 13, 14 is made of a cylindrical pipe of aluminum. It is provided with slits 15 produced at equal intervals along its length, where the ends of the tubes 11 are soldered to the respect headers 13, 14. The left-hand header 13 is provided with a coolant inlet pipe 16 at its upper end and a plug 17 at the lower end. The right-hand header 14 is provided with a coolant outlet pipe 18 at its lower end and a plug 19 at its upper end. The coolant inlet and outlet are diametrically located. The reference numerals 23 and 24 denote side plates fixed to the fins 12 located at the outermost positions.

Each header 13, 14 is provided with a partition 20, 21, respectively, thereby dividing the internal chamber into upper and lower sections, wherein the partition 20 is the header 13 is located slightly toward the inlet 16, whereas the partition 21 in the header 14 is located about  $\frac{1}{3}$  the length toward the outlet 18.

Because of the provision of the partitions 20 and 21 in the headers 13 and 14 the flow pattern of the coolant is formed as shown in FIG. 8; that is, the coolant passageway is grouped into an inlet section (A), a middle section (B) and an outlet section (C). As seen from FIG. 8 the coolant flows in three different directions. In addition, the tubes are different in number from group to group; that is, the group (B) has more tubes than the group (C) (outlet section), and the group (A) (inlet section) has more tubes than the group (B). This means that the group (A) has a larger effective cross-sectional area for coolant passageway than the group (B), which in turn has a greater area for it than the group (C).

Referring to FIG. 8 the coolant introduced into the core through the inlet pipe 16 flows to the right-hand header 14 in the inlet section (A), and then in a reversed direction in the middle section (B). In the outlet section (C) the flow of coolant is again reversed, and led to the right-hand header 14, where it is discharged through the outlet pipe 18. While the coolant is flowing through the sections (A), (B) and (C) heat exchange takes place between the coolant and the air passing through the fins 12. In the inlet section (A) the coolant is in its gaseous state, but because of the large effective cross-sectional area in the section (A) heat exchange proceeds efficiently between the coolant and the air. In the section (C) the coolant is in its liquid state, and reduced in its volume, which allows the section (C) to have a relatively small cross-sectional area for coolant passageway as compared with the section (B). In this way the coolant passes through the first condensing section (A), the second section (B) and the third supercooling section (C), in the course of which heat exchange smoothly and efficiently takes place.

In the illustrated embodiment the numbers of tubes are progressively decreased from the section (A) to the section (B) and to the section (C). However, it is possible to give the

same number of tubes to the section (A) and (B), and a smaller number of tubes to the section (C). Alternatively it is possible to arrange so that each section (A) to (C) has the same number of tubes but their cross-sectional areas are progressively reduced from the section (A) to the section (B) and to the section (C). As a further modification the intermediate section (B) can be omitted; in this case the flow pattern is called a two-path system. In contrast, the above-mentioned embodiment is called a three-path system. As a still further modification one or more intermediate sections can be added.

The illustrated embodiment has the headers located at the left-hand side and the right-hand side but they can be located at the upper side and the lower side wherein the tubes and fins are vertically arranged.

To joint the tubes 11 to the headers 13, 14 the tubes or the headers or both are previously provided with a layer of a soldering substance on their adjoining surfaces. More specifically, as shown in FIG. 3 there is an aluminum pipe 13a, such as a clad metal pipe, which is used as the headers 13 and 14. The clad pipe 13a has a layer of a soldering substance 13b. The pipe 13a is electrically seamed but can be made by extrusion or any other known method. For the soldering substance an Al.Si alloy preferably containing 6 to 13% by weight of Si is used. The tubes 11 are inserted in the slits 15 for their end portions to be held therein. Then they are heated together to melt the soldering substance. In this case, as clearly shown in FIG. 5 the adjoining parts of the tube 11 and the clad pipe 13a have fillets 29, whereby the header 13, 14 and the tubes 11 are jointed to each other without gaps interposed therebetween. Likewise, the corrugated fins 12 can be provided with a layer of a soldering substance, thereby effecting the soldering joint between the fins 12 and the tubes 11 simultaneously when the tubes 11 are jointed to the headers 13, 14. This facilitates the soldering joint among the headers 13, 14, the tubes 11 and the fins 12, thereby saving labor and time in the assembling work. The layer of a soldering substance can be provided in the inner surface of the clad pipe 13a but the place is not limited to it.

The partitions 20, 21 are jointed to the respective headers 13, 14 in the following manner:

The clad pipe 13a is previously provided with a semicircular slit 28 in its wall, wherein the slit 28 covers half the circumference of the pipe 13a. The partition 20, 21 is made of a disc-shaped plate having a smaller circular portion 20a and a larger circular portion 20b, wherein the smaller circular portion 20a has a diameter equal to the inside diameter of the pipe 13a, and wherein the larger circular portion 20b has a diameter equal to the outside diameter of the pipe 13a. The larger diameter portion 20b is inserted and soldered in the slit 28. The headers 13, 14 and the partitions 20, 21 are preferably provided with layers of soldering substances as described above, so that the soldering joint between them can be performed simultaneously when the tubes 11 are soldered to the headers 13, 14. This finishes the soldering joint among the headers, the tubes, the fins and the partitions at one time. The larger diameter portion 20b fits in the slit 28 so that no leakage of coolant is likely to occur, and that the appearance of an outer surface of the pipe 13a is maintained. In addition, the larger diameter portion 20b is embedded in the slit 28, thereby preventing the partition 20, 21 from being displaced by an unexpected force acting thereon.

As is generally known in the art, a possible pressure loss of air largely depends on the relative positional relationship between the tubes 11 and the fins 12. A reduced pressure loss

leads to the increased heat exchange efficiency. Accordingly, the heat exchange efficiency depends on this positional relationship between them. Now, referring to FIGS. 6 and 7 this positional relationship will be described:

It is prescribed so that the tube 11 has a width (W) of 6 to 12 mm, and a height (Ht) of not larger than 5 mm, and that the fin 12 has a height (Hf) of 8 to 16 mm, and a fin pitch (Fp) of 1.6 to 3.2 mm. Referring to FIGS. 15, 16 and 17 the reasons for the prescriptions are as follows:

As shown in FIG. 15, if the tube 11 has a width of smaller than 6 mm the fin 12 will be accordingly narrower, thereby reducing the number of louvers 12a. The reduced number of louvers 12a leads to less efficient heat exchange. If the tube is wide enough to allow an adequate number of louvers 12a to be provided on the fins 12, the heat exchange efficiency will be enhanced. However if the width (W) of the tube is more than 12 mm, the fins 12 will be accordingly widened, thereby increasing its weight. In addition too wide fins and too many louvers are likely to increase resistance to the air passing therethrough thereby causing a greater pressure loss of air.

If the tubes 11 have a height (Ht) of more than 5 mm the pressure loss of air will increase. The inside height (Hp) of the tube 11 is preferably not smaller than 1.8 mm. The inside height (Hp) is important in that it defines the size of an effective coolant passageway. If it is smaller than 1.8 mm the pressure loss of coolant will increase, thereby reducing the heat exchange efficiency. In order to maintain a height (Hp) of at least 1.8 mm for coolant passageway, the height (Ht) of the tube 11 will have to be at least 2.5 mm, inclusive of the thickness of the tube wall.

As shown in FIG. 17, if the height (Hf) of the fin 12 is smaller than 8 mm the pressure loss of air will increase, but if it is larger than 16 mm the number of fins will have to be reduced, thereby reducing the heat exchange efficiency.

If the pitch (Fp) of fins 12 is smaller than 1.6 mm there will occur an interference between the adjacent louvers 12a, thereby amplifying the pressure loss of air. However if it exceeds 3.2 mm the heat exchange efficiency will decrease.

Referring to FIGS. 9 and 10 a modified version will be described:

This embodiment is characteristic in that it is provided with shoulders 25 which work as stop means to prevent the tube from being inserted too deeply into the header 13, 14. More specifically, the tube 11 includes a body 111 and a head 111a which has shoulders 25 therebetween. The shoulders 25 are adapted to come into abutment with the heater 13, 14 when the tube 11 is inserted into the slit 15.

As modified versions of the stop means various examples are shown in FIGS. 11 to 13:

FIG. 11 shows the process of forming stop means 125. In (a) the tube 211 has sharp or acute corners. The corners are cut away in such a manner as to form bulged portions 125, which provide stop means. FIG. 12 shows a tube 311 having round corners, which are split lengthwise in such a manner as to form shoulders 225. FIG. 13 shows a tube 411 having a relatively thin wall. In this case the cutting and splitting are jointly used in such a manner as to form shoulders 325.

FIG. 14 shows an example of the condenser embodying the present invention characterized in that the condenser is provided with a space 27 void of any tube or fin so that an obstacle 26 is avoided when it is installed in an engine room or somewhere. This embodiment has a pair of headers 113 and 14, and the left-hand header 113 is divided into two parts 113a and 113b. The tubes 11 consist of longer tubes 11a and

shorter tubes 11b, which are connected to the header 113b at their left-hand ends. The other ends thereof are connected to the header 14. The outlet pipe 18 is provided on the header 113b. The coolant introduced through the inlet pipe 16 flows in the direction of arrows up to the right-hand header 14, and makes a U-turn to flow through the shorter tubes 11b up to the header 113b, where it is let out through the outlet pipe 18. The number of the space 27 is determined in accordance with that of an obstacle 26; when three spaces are to be given, three kinds of lengths of tubes are used.

What is claimed is:

1. A condenser for liquefying gaseous coolant in an air conditioning system of an automobile after the system has compressed the coolant, said condenser comprising:

- (i) a plurality of flat tubular elements defining flow paths and disposed in a spaced, substantially parallel relation, each element including at least one inside wall;
- (ii) a plurality of fin members, each fin member disposed between adjacent tubular elements;
- (iii) a pair of headers disposed in a spaced, substantially parallel relation at opposite ends of the tubular elements, the one and/or the other header defining a coolant inlet and a coolant outlet for the condenser, each header being a substantially round, elongate member and defining, for each tubular element, an opening through which it receives the tubular element and establishes fluid communication with the element;
- (iv) at least one partitioning plate mounted in one of the header transversely of the header to divide the inside opening of the header, said plate including a first portion which extends into a slit in the header and a second portion which is generally co-extensive with the inside opening of the header, *said second portion of the partitioning plate being without any perforations;*

the coolant flowing from the inlet into one header and making a first pass through a plurality of the tubes to the other header, the coolant also making a final pass through a plurality of tubes to the outlet, the tubular elements and headers forming a first zone which receives gaseous coolant from the inlet and a final zone through which the coolant flows before discharging through the outlet, the effective cross sectional area of the flow paths defined by the tubular elements through which the coolant makes the final pass being smaller than the effective cross sectional area of the flow paths of those through which the coolant makes the first pass; said condenser being able to resist internal pressures greater than 10 atmospheres.

2. The condenser of claim 1, in which one header defines the inlet and outlet and includes the partitioning plate.

3. The condenser of claim 1, in which each header has at least one partition and wherein the coolant makes a second pass between the first and the final passes through a plurality of tubular elements.

4. A condenser as defined in claim 3, wherein the effective cross-sectional area of the coolant passageways formed through the tubular elements is reduced stepwise from the first pass, to the second pass, to the final pass.

5. A condenser as defined in claim 4, wherein the number of the tubular elements is reduced stepwise from the first pass towards the final pass.

6. A condenser as defined in claim 1, wherein each header is a clad pipe having either one or both of its surfaces coated with the brazing agent layer.

7. A condenser as defined in claim 1, wherein each header is a seam-welded pipe.

8. A condenser as defined in claim 1, wherein the partitioning plate is a disc which has a large diameter portion and a small diameter portion.

9. A condenser as defined in claim 1, wherein the tubular elements are extruded, elongate members.

10. A condenser as defined in claim 1, wherein each tubular element is a seam-welded pipe.

11. A condenser as defined in claim 1, wherein the tubular elements have:

- a width of 6-12 mm;
- a height of 5 mm or less; and
- the flow path within each tube being 1.8 mm or more in height; and
- each fin member having a height of 8-16 mm; and
- the pitch of the fin members being 1.6-3.2 mm.

12. A condenser as defined in claim 1, wherein the headers, tubular elements, fin members and partitioning plate are made of an aluminum alloy.

13. A condenser as defined in claim 1, wherein each tubular element has an elongate cross-section and the inside wall of the tubular element extends between opposite outer walls of the element.

14. A condenser as defined in claim 1, wherein the inside wall is continuous and extends along substantially the entire length of the tubular element.

\* \* \* \* \*