



US00RE36592E

United States Patent [19]
Giebel et al.

[11] E

Patent Number: Re. 36,592

[45] **Reissued Date of Patent: Feb. 29, 2000**

[54] **OPTICAL RECEIVER STUB FITTING**

FOREIGN PATENT DOCUMENTS

[75] Inventors: **Markus A. Giebel; Terry L. Cooke,**
both of Hickory, N.C.

0 199 267 A1	4/1986	European Pat. Off. .
1247410	10/1960	France .
2662270	5/1990	France .
2670303	12/1990	France .
38 20 950 A1	12/1989	Germany .
58-11906	1/1983	Japan .
61-282807	6/1985	Japan .
2030723	4/1980	United Kingdom .

[73] Assignee: **Siecor Corporation,** Hickory, N.C.

[21] Appl. No.: **08/856,106**

[22] Filed: **May 14, 1997**

OTHER PUBLICATIONS

Related U.S. Patent Documents

Reissue of:

[64] Patent No.: **5,416,874**
 Issued: **May 16, 1995**
 Appl. No.: **08/272,975**
 Filed: **Jul. 1, 1994**

[51] **Int. Cl.**⁷ **G02B 6/44**

[52] **U.S. Cl.** **385/100; 385/103; 385/106;**
385/113; 385/114; 428/392; 174/23 R

[58] **Field of Search** 385/62, 81, 87,
385/100-117; 428/392, 34.9; 174/23 R

“Fiber Optic Transport Connector,” Production Products Company, Publication No. 05-01-92.

Amphenol Strain Relief Assembly, Drawing No. 909-116-12 1981.

“Back-fed Cable Stub Installation,” Siecor Recommended Procedure SRP-009-002, Issue 1, pp. 1-3 (Jan. 1993).

“Siecor Front-fed Cable Stub Installation,” Siecor Recommended Procedure SRP-009-003, Issue 1, pp. 1-4 (Apr. 1993).

“Installation of Siecor Fanout Assemblies on Loose Tube Fiber Optic Cable,” Siecor Recommended Procedure SRP-000-082, Issue 1, pp. 1-8 (Nov. 1991).

“Installation of Siecor Fan-Out Assemblies on Loose Tube and Mini Bundle® Riser Fiber Optic Cable,” Siecor Recommended Procedure SRP-000-082, Issue 2, pp. 1-10 (Dec. 1992).

“Installation of Siecor Fan-Out Assemblies on Loose Tube and Mini Bundle® Riser Fiber Optic Cable,” Siecor Recommended Procedure SRP-000-082, Issue 3, pp. 1-10 (Jul. 1993).

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,153,332	5/1979	Longoni	350/96.23
4,262,913	4/1981	Parfree et al.	277/1
4,319,802	3/1982	Bowes .	
4,365,865	12/1982	Stiles .	
4,447,120	5/1984	Borsuk .	
4,460,159	7/1984	Charlebois et al. .	
4,549,037	10/1985	Bawa et al.	174/65
4,697,873	10/1987	Bouvard et al. .	
4,709,983	12/1987	Plessner et al.	350/96.23
4,786,137	11/1988	Cornelison et al. .	
4,928,135	5/1990	Kayoun et al. .	
4,948,222	8/1990	Corke et al. .	
4,984,865	1/1991	Lee et al. .	
5,181,272	1/1993	Hopper	385/139
5,217,808	6/1993	Cobb	428/392
5,249,248	9/1993	Arroyo et al.	385/113
5,271,080	12/1993	Hopper et al.	385/76
5,373,100	12/1994	Arroyo et al.	174/23 R
5,418,874	5/1995	Carlisle et al.	385/76
5,574,819	11/1996	Gunther et al.	385/139
5,588,086	12/1996	Fan	385/138

(List continued on next page.)


Primary Examiner—Phan T. Palmer

Attorney, Agent, or Firm—Nixon Peabody LLP

[57] **ABSTRACT**

A cable assembly for attachment to an entry port of an optical enclosure. The assembly includes a plug for an end of an optical cable in a sealed housing having a single rigid tube and a single sealed nut. Connectorized optical fibers or an optical ribbon extend from the plug into the equipment enclosure.

37 Claims, 8 Drawing Sheets



OTHER PUBLICATIONS

“Installation of Siecor Fan-Out Assemblies on Loose Tube and Mini Bundle® Riser Fiber Optic Cable,” Siecor Recommended Procedure SRP-000-082, Issue 4, pp. 1-10 (Nov. 1994).

“Installation of Siecor Fan-Out Assemblies on Loose Tube and Mini Bundle® Riser Fiber Optic Cable,” Siecor Recommended Procedure SRP-000-082, Issue 5, pp. 1-7 (Mar. 1996).

Siecor Recommended Procedure, SRP-004-018, Issue No. 1, pp. 1-4 (1988).

Siecor Recommended Procedure, SRP-004-018, Issue 5, pp. 1-6 (Jun. 1991).

Siecor Recommended Procedure, SRP-004-018, Issue 7, pp. 1-6 (Jan. 1993).

Siecor Recommended Procedure, SRP-004-018, Issue 8, pp. 1-7 (Apr. 1994).

Siecor Recommended Procedure, SRP-004-018, Issue 9, pp. 1-7 (Dec. 1994).

IBM/Siecor Recommended Procedure, SRP-009-001, Issue 3, pp. 1-4 (Apr. 1991).

IBM/Siecor Recommended Procedure, SRP-009-001, Issue 5, pp. 1-4 (Jun. 1991).

IBM/Siecor Recommended Procedure, SRP-009-001, Issue 6, pp. 1-9 (Feb. 1992).

IBM/Siecor Recommended Procedure, SRP-009-001, Issue 11, pp. 1-10 (Oct. 1992).

FIG. 1




FIG. 2





FIG. 3






FIG. 5a




FIG. 5b




FIG. 6






FIG. 7





OPTICAL RECEIVER STUB FITTING

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

This application is a Reissue of application Ser. No. 08/272,975 U.S. Pat. No. 5,416,874, filed Jul. 1, 1994.

BACKGROUND OF THE INVENTION

Fiber optic cable assemblies for connection to optical enclosures are currently available. Such assemblies must securely anchor the cable and be environmentally sealed. Certain connectors anchor the cable by means of a clamping mechanism requiring two nuts in addition to a rear sealing nut. Although these connectors provide some anchoring and environmental sealing, the anchoring strength of the connector is limited due to the limited tolerance of many cables to clamping. A further disadvantage of such connectors is the additional opening between the two clamping nuts which must be sealed.

Objects of the invention are to provide a simple means for anchoring cable strength elements and to eliminate a possible moisture entry point.

SUMMARY OF THE INVENTION

The invention provides an improved cable assembly joining optical cables having optical fibers or optical fiber ribbons to optical enclosures such as patch panels or optoelectronic enclosures for optical networks. The cable holds the proximal span of a plurality of optical fibers or an optical ribbon including optical fibers. Connectorized or unconnectorized distal ends of the optical fibers or optical ribbon are contained within an optical enclosure having an internally threaded optical entry port. Mediate spans of the optical fibers or the optical ribbon are each surrounded by a flexible tube. A water-impervious plug encases a portion of the mediate span of each of the optical fibers or optical ribbon and the flexible tube or tubes, the plug also preferably encasing a portion of at least one cable strength member. The plug extends over a portion of the cable sheath. A metallic rigid jacket preferably encases the plug. Over the plug is an environmentally sealed housing for attaching the cable to the enclosure. As the housing does not depend on cable clamping, it requires only two members, namely a single rigid tube having two ends, a first end having an externally threaded extension connected to the entry port such that the rigid tube is outside the enclosure, and a second internally threaded end to which is attached a sealing nut having an externally threaded extension. A grommet is preferably present over the cable jacket between the sealing nut and the plug, and O-rings are placed in slots behind the external threads of the rigid tube and the sealing nut. The assembly may be grounded if desired.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1 and 2 are perspective views of portions of a plurality of bundled flexible tubes;

FIG. 3 is a perspective view of the assembly prior to formation of the sealed plug;

FIG. 4 is a perspective view of the assembly including the plug and the optical connectors;

FIG. 5a is a perspective view of the assembly including the housing;

FIG. 5b is a perspective view of the assembly according to the embodiment including an optical ribbon;

FIG. 6 is a perspective view of the assembly including an optical enclosure; and,

FIG. 7 is a perspective view of a heat shrinkable tube applied over the assembly as attached to an optical enclosure.

FIG. 8 is a perspective view of the cable pulls.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Nut 31 and grommet 30 are first placed over cable sheath 14. An array of flexible tubes 10 are bundled as shown in FIG. 1 by two strips 11, 12 of heat shrinkable material which are preferably ¼ inch wide. Tubes 10 are preferably made of a lightweight, low friction, highly flexible plastic such as Teflon® plastic. Strips 11, 12 are placed ⅜ inch apart. Strip 12 is located around ¼ inch from one end of tubes 10.

After strips 11, 12 have cooled, spiral wrap material 13 is placed over the bundle of tubes 10, with one edge over strip 11 and the remainder proceeding in the direction opposite strip 12.

An optical cable is then prepared as shown in FIG. 3. After one end of cable sheath 14 has been stripped back, a buffer tube including optical fibers 17 extends a short distance. A cable strength member such as aramid yarn 29 also extend a short distance. Each optical fiber 17 is threaded through a flexible tube 10, with an optical connector 18 being placed on the distal end of each optical fiber 17. As shown in FIG. 4, tubes 10 extend to meet the rear of connectors 18. A protective boot on each connector 18 may cover the end of a tube 10. After one end of tubes 10 have been placed inside a tube 15, an adhesive lined piece of heat shrinkable material 16 is placed over the junction of buffer tube 15 and flexible tubes 10. Heat is then applied to produce the configuration of FIG. 3.

The assembly of FIG. 3 is then placed in a rigid aluminum tubular jacket 19 held in a vertical fixture such that the end of cable sheath 14 and strength members 29 lie at the lower end of jacket 19 and spiral wrap material 13 and tubes 10 extend from the upper end of jacket 19. After grommet 30 is placed at the lower end of jacket 19, an epoxy is injected into the jacket to produce a cylindrical water impervious plug 34. If grounding is desired, jacket 19 should not be filled to the top in order to ensure electrical continuity between jacket 19 and rigid tube 32, made of an electrically conductive material such as aluminum. A conductor wire or spring would also be connected between metallic cable armor and jacket 19, made of a conductive metal such as aluminum. The wire may also be connected directly to enclosure 24. The assembly then has the appearance shown in FIG. 4.

Alternate preferred embodiments are shown in FIGS. 5a and 5b. A section of heat shrinkable tubing 25 is not shown to the left of nut 31. Grommet 30 is located around sheath 14 between nut 31 and jacket 19 within rigid tube 32. Rigid tube 32 has on one end an externally threaded extension 36 for fitting to an enclosure. A single tube 10 containing an optical ribbon is attached to a ribbon connector 35 as shown in FIG. 5b, or tubes 10 each containing an optical fiber proceed to connectors 18. Spiral wrap 13 protects a tube 10 in either case.

Threaded end 36 is then inserted into an internally threaded optical entry port 40 of optical enclosure 24. Nut 31 is threaded into rigid tube 32, providing a compressive fit with grommet 30. For added environmental protection, heat shrinkable tubing 25 is then cured over rigid tube 32 and nut 31.

The invention can also be used in cable pulls as shown by the assembly in FIG. 8. Pulling eye 52 is mounted to a flexible, strong tubular hose 51 which may be a mesh of flexible metal wires or other material such as strong plastic. A nut 50, having the same connection geometry as port 40, is attached to hose 51. A protective member such as a split foam or plastic tube is placed over the optical elements extending from the member 32 into hose 51.

It will be appreciated that variations of the preferred embodiments may be used within the scope of the claims.

What is claimed is:

1. A cable assembly for use with optical enclosures, comprising:

a plurality of optical fibers, each optical fiber including a proximal span in which the optical fiber is held within a sheathed cable, a distal end, and a mediate span therebetween[.];

a plurality of flexible tubes, each said flexible tube surrounding a mediate span of one of [the] said optical fibers;

a water-impervious plug encasing a portion of the mediate span of the plurality of optical fibers and the flexible tubes, the plug extending over a portion of the cable sheath; [and,]

a rigid jacket encasing the plug; and

an environmentally sealed housing over the rigid jacket for attaching the cable to an optical equipment enclosure.

2. A cable assembly as recited in claim 1 further comprising a cable strength member having a portion thereof extending into and embedded in the plug.

[3. A cable assembly as recited in claim 1 further comprising an environmentally sealed housing over the rigid tube for attaching the cable to an optical equipment enclosure.]

4. A cable assembly as recited in claim [3] 1, wherein the housing comprises a single rigid tube and a single nut directly connectable to the rigid tube, the housing having no third nut.

5. A cable assembly, comprising:

an optical enclosure having an internally threaded optical entry port;

a single rigid tube having first and second ends, the first end having an externally threaded extension connected to the entry port such that the rigid tube is outside the enclosure, and means environmentally sealing such connection;

a plurality of optical fibers each including a proximal span held in a sheathed cable, a distal end within the enclosure, and a mediate span therebetween;

a plurality of flexible tubes, each said flexible tube surrounding a mediate span of one of the optical fibers; and,

a water-impervious plug contained in the rigid tube, the plug encasing a portion of the mediate span of the plurality of the optical fibers and flexible tubes, the plug extending over a portion of the cable sheath.

6. A cable assembly as recited in claim 5, further comprising a rigid jacket encasing the plug.

7. A cable assembly as recited in claim 5, further comprising a cable strength member having a portion thereof extending into and embedded in the plug.

8. A cable assembly as recited in claim 5, further comprising a single environmentally sealed nut directly connectable to the second end of the rigid tube in the absence of a third nut.

9. A cable assembly for use with optical enclosures, comprising:

an optical ribbon including a proximal span in which the optical fiber is held within a sheathed cable, a distal end, and a mediate span therebetween:

a flexible tube surrounding the mediate span of the optical ribbon; and,

a water-impervious plug encasing a portion of the mediate span of the optical ribbon and the flexible tube, the plug extending over a portion of the cable sheath.

10. A cable assembly as recited in claim 9, further comprising a rigid jacket encasing the plug.

11. A cable assembly as recited in claim 9, further comprising a cable strength member extending into and embedded in the plug.

12. A cable assembly as recited in claim [9] 10, further comprising an environmentally sealed housing over the rigid [tube] jacket for attaching the cable to an optical enclosure.

13. A cable assembly as recited in claim 12, wherein the housing comprises a single rigid tube and a [Single] single nut directly connectable to the rigid tube, the housing having no third nut.

14. A cable assembly for cable pulls, comprising:

an optical element including a proximal span in which the optical element is held within a sheathed cable, a distal end, and a mediate span therebetween:

a flexible tube surrounding the mediate span of the optical element;

a water-impervious plug encasing a portion of the mediate span of the optical element and the flexible tube, the plug extending over a portion of the cable sheath; and,

a strong, flexible tubular hose holding the optical element distal end, the hose having two ends, one hose end mounted to a cable pulling eye and the other hose end mounted to a housing over the plug.

15. A cable assembly as recited in claim 1, wherein the housing further comprises:

a rigid tube having opposed first and second openings and a connector configured to fit into the first opening.

16. A cable assembly as recited in claim 15, wherein the rigid tube and the connector each threadably engage one another so that the connector fits into the first opening of the rigid tube.

17. A cable assembly as recited in claim 16, wherein the rigid tube is internally threaded at the first opening to receivably engage a threaded end of the connector.

18. A cable assembly as recited in claim 15, wherein the housing is placed over the rigid jacket so that the first opening is remote from the distal end of the plurality of optical fibers.

19. A cable assembly as recited in claim 15, wherein the rigid tube is threaded to facilitate connection of the cable assembly to an optical enclosure through a threaded optical entry port in the optical enclosure.

20. A cable assembly as recited in claim 19, wherein the second end of the rigid tube comprises an externally threaded extension to facilitate connection of the cable assembly to an optical enclosure through an internally threaded optical entry port in the optical enclosure.

21. A cable assembly as recited in claim 1 further comprising:

a heat shrinkable tube over the housing.

22. A cable assembly as recited in claim 1 further comprising:

a plurality of optical connectors at the distal end of the plurality of optical fibers.

5

23. A cable assembly as recited in claim 15 further comprising:

a grommet within the rigid tube between the jacket and the connector.

24. A cable assembly as recited in claim 1, wherein the plurality of optical fibers is an optical fiber ribbon within a single tube.

25. A cable assembly comprising:

a plurality of optical fibers, each optical fiber including a proximal span in which the optical fiber is held within a sheathed cable, a distal end, and a mediate span therebetween;

a plurality of flexible tubes, each said flexible tube surrounding a mediate span of one of said optical fibers; a water-impervious plug encasing a portion of the mediate span of the plurality of optical fibers and the flexible tubes, the plug extending over a portion of the cable sheath; and

an environmentally sealed housing separate from the plug and around the plug.

26. A cable assembly as recited in claim 25, wherein the housing further comprises:

a rigid tube having opposed first and second openings and a connector configured to fit into the first opening.

27. A cable assembly as recited in claim 26, wherein the rigid tube and the connector each threadably engage one another so that the connector fits into the first opening of the rigid tube.

28. A cable assembly as recited in claim 27, wherein the rigid tube is internally threaded at the first opening to receivably engage a threaded end of the connector.

29. A cable assembly as recited in claim 26, wherein the housing is placed over the plug so that the first opening is remote from the distal end of the plurality of optical fibers.

30. A cable assembly as recited in claim 26, wherein the rigid tube is threaded to facilitate connection of the cable assembly to an optical enclosure through a threaded optical entry port in the optical enclosure.

31. A cable assembly as recited in claim 30, wherein the second end of the rigid tube comprises an externally threaded extension to facilitate connection of the cable assembly to an optical enclosure through an internally threaded optical entry port in the optical enclosure.

32. A cable assembly as recited in claim 25 further comprising:

a heat shrinkable tube over the housing.

6

33. A cable assembly as recited in claim 25 further comprising:

a plurality of optical connectors at the distal end of the plurality of optical fibers.

34. A cable assembly as recited in claim 26 further comprising:

a rigid jacket encasing the plug and within the housing.

35. A cable assembly as recited in claim 34 further comprising:

a grommet within the rigid tube between the jacket and the connector.

36. A cable assembly as recited in claim 25 further comprising:

a cable strength member having a portion thereof extending into said embedded in the plug.

37. A cable assembly as recited in claim 25, wherein the plurality of optical fibers is an optical fiber ribbon within a single tube.

38. A cable assembly comprising:

a plurality of optical fibers, each optical fiber including a proximal span in which the optical fiber is held within a sheathed cable, a distal end, and a mediate span therebetween;

a plurality of flexible tubes, each said flexible tube surrounding a mediate span of one of said optical fibers;

a water-impervious plug encasing a portion of the mediate span of the plurality of optical fibers and the flexible tubes, the plug extending over a portion of the cable sheath;

a rigid jacket encasing the plug; and

an environmentally sealed housings around the rigid jacket, wherein the housing comprises:

a rigid tube having opposed first and second openings with the first opening being remote from the distal end of the plurality of optical fibers and the second opening being externally threaded to facilitate connection of the cable assembly to an optical enclosure through an internally threaded optical entry port in the optical enclosure and

a connector configured to fit into the first opening, wherein the rigid tube is internally threaded at the first opening to receivably engage a threaded end of the connector.

* * * * *