



US00RE37238E

(19) **United States**
(12) **Reissued Patent**
Song

(10) **Patent Number:** **US RE37,238 E**
(45) **Date of Reissued Patent:** **Jun. 26, 2001**

(54) **APPARATUS FOR ROASTING COFFEE BEANS**

(56) **References Cited**

(75) Inventor: **Eugene Song**, Seoul (KR)
(73) Assignee: **Hearthware Home Products, Inc.**,
Wheeling, IL (US)
(21) Appl. No.: **09/172,427**
(22) Filed: **Oct. 14, 1998**

U.S. PATENT DOCUMENTS

4,271,603	6/1981	Moore, III .
4,325,191	4/1982	Kumagai et al. .
4,484,064	11/1984	Murray .
4,494,314	1/1985	Gell, Jr. .
4,602,147	7/1986	Gell .
4,841,849	6/1989	Shimomura et al. .
4,860,461	8/1989	Tamaki et al. .
4,895,308	1/1990	Tanaka .
5,269,072	12/1993	Waligorski .
5,359,788	11/1994	Gell, Jr. .
5,500,237	3/1996	Gell, Jr. et al. .
5,573,802	11/1996	Porto .

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **5,564,331**
Issued: **Oct. 15, 1996**
Appl. No.: **08/506,708**
Filed: **Jul. 25, 1995**

U.S. Applications:

(63) Continuation-in-part of application No. 08/333,762, filed on Nov. 3, 1994, now abandoned.

(30) **Foreign Application Priority Data**

May 9, 1995 (KR) 95-11209

(51) **Int. Cl.**⁷ **A23N 12/00**; A47J 31/42;
A47J 42/52

(52) **U.S. Cl.** **99/469**; 34/225; 34/233;
34/594; 99/286; 99/476; 99/483; 99/525

(58) **Field of Search** 99/286, 357, 469,
99/476, 483, 518, 525, 600, 601, 609-611;
34/233, 533, 594, 225, 68, 267, 609, 136,
560, 181, 589; 366/101, 107, 165; 219/385,
386, 389, 400; 241/65, 100; 426/466, 467

Primary Examiner—Timothy Simone

(74) *Attorney, Agent, or Firm*—Wood, Phillips, VanSanten,
Clark & Mortimer

(57) **ABSTRACT**

The present invention relates to an apparatus for roasting raw coffee beans which apparatus can instantly roast a small quantity of raw coffee beans according to personal taste and provide a unique taste and fragrance of coffee, and in particular to an apparatus suitable for home use. The apparatus has a roasting vessel for containing raw coffee beans to be roasted. A plurality of air openings are provided for creating a whirling vertical motion to a heated airstream ascending therethrough, whereby the raw beans are roasted and also caused to have their hulls separated and caused to ascend upwardly with the airstream to a hull-receiving vessel.

32 Claims, 11 Drawing Sheets




FIG. 1




FIG. 2




FIG.3




FIG. 4




FIG.5




FIG.6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11



APPARATUS FOR ROASTING COFFEE BEANS

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in *italics* indicates the additions made by reissue.

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation-in-part of my application, Ser. No. 08/333,762 filed on Nov. 3, 1994 which is now abandoned.

BACKGROUND OF THE INVENTION

The present invention relates to an apparatus for roasting raw coffee beans, which apparatus is capable of instantly roasting a small quantity of raw coffee beans according to personal taste, and provides a unique taste and fragrance of coffee, and in particular to an apparatus suitable for home use.

Coffee is a popular drink. Drinking coffee has been prepared by boiling raw beans with a percolator or by mixing coffee powders in boiling water. In the present days, however, people have a tendency to prefer raw bean coffee which is superior in taste and fragrance.

In spite of its quality, the taste and fragrance of raw bean coffee can be changed not only by the ways of processing raw beans, but also in the manner it is stored. Thus, in order to enjoy the particular taste and fragrance of raw bean coffee, after purchasing raw beans in a small quantity, people have to instantly process raw beans properly whenever required.

SUMMARY OF THE INVENTION

The present invention was made with a view to satisfying the aforementioned requirements, and its object is to provide an apparatus for roasting raw coffee beans at home according to personal taste.

To accomplish the object of the present invention there is provided an apparatus for roasting raw coffee beans comprising a main housing having an air inlet; a blower fan assembly mounted on the main housing for blowing air; a heater assembly mounted on the housing and above the blower fan assembly for generating heat, the blower fan assembly directing the heat upwardly; a roasting vessel above the heater assembly for containing raw coffee beans to be roasted; a hull-receiving vessel for receiving and storing the hulls of the raw coffee beans blown along the air stream directed thereto from the roasting vessel, the hull-receiving vessel having an air outlet; a cover for covering the roasting vessel, the cover guiding hulls from the raw coffee beans along the path of the air stream; and a power means for providing power to the blower fan assembly and the heater assembly.

The apparatus of the invention is adapted to roast raw coffee beans by means of a heated airstream for a predetermined period of time, to simultaneously remove raw-bean hulls, and then to apply a cooling airstream at the end of the roasting process.

BRIEF DESCRIPTION OF THE DRAWINGS

The above object and other advantages of the present invention will become more apparent by describing in detail preferred embodiments thereof with reference to the attached drawings in which:

FIG. 1 is a perspective view of an apparatus according to one embodiment of the present invention in its assembled state;

FIG. 2 is a side view of the apparatus illustrated in FIG. 1;

FIG. 3 is a vertical cross-sectional view of the apparatus illustrated in FIG. 1;

FIG. 4 is a perspective view showing the exploded state of a seal and roasting-vessel mounting member according to one embodiment of the present invention;

FIG. 5 is a perspective view showing the exploded state of a blowing fan and a heater unit according to one embodiment of the present invention;

FIG. 6 is a perspective view showing a roasting vessel according to one embodiment of the present invention;

FIG. 7 is a perspective view showing the exploded state of the cover and hull-receiving vessel according to one embodiment of the present invention;

FIG. 8 is a vertical cross-sectional view showing the apparatus according to one embodiment of the present invention during operation;

FIG. 9 is a perspective view showing the exploded state of an apparatus according to another embodiment of the present invention;

FIG. 10 is a perspective view showing the assembled state of the apparatus according to another embodiment of the present invention; and

FIG. 11 is a cross-sectional view showing the assembled state of the apparatus illustrated in FIG. 10.

DESCRIPTION OF THE PREFERRED EMBODIMENT

The preferred embodiments of the present invention will be described hereinafter in more detail by reference to the accompanying drawings.

Referring to FIGS. 1-8, the apparatus for roasting raw coffee beans according to one embodiment of the present invention comprises a main housing having an air inlet; a blower fan assembly mounted on the main housing for blowing air; a heater assembly mounted in the housing and above the blower fan assembly for generating heat, the blower fan assembly directing the heat upwardly; a roasting vessel above the heater assembly for containing raw coffee beans to be roasted; a hull-receiving vessel for receiving and storing the hulls of the raw coffee beans blown along the air stream directed thereto from the roasting vessel, the hull-receiving vessel having an air outlet; a cover for covering the roasting vessel, the cover guiding hulls from the raw coffee beans along the path of the air stream; and a power means for providing power to the blower fan assembly and the heater assembly, wherein the roasting vessel includes a plurality of holes for allowing the heated air stream from the heater assembly to enter into the interior of the roasting vessel, and the cover has a hull-guide means for directing the hulls from the roasted coffee beans along a specific downstream path.

Particularly, the apparatus according to one embodiment of the present invention includes a main body or housing 110, a timer 120, a heater assembly 140 (FIG. 3), a roasting vessel 150 in which is placed raw coffee beans that are to be roasted, a cover 160, and a hull-receiving vessel 170 for receiving and storing therein separated hulls of the roasted beans (FIG. 3). The structure and characteristics of each element are explained below.

Main housing 110 has a central section which is similar to a cylindrical shape, and is open from above, and has an air

inlet **111** (FIG. 3) formed therein, a blowing fan/heater mounting portion **112** (FIG. 4), a roasting vessel mounting portion **113**, and a hull-receiving vessel mounting portion **114**.

There are provided a plurality of air inlets **111**, formed at the bottom of main housing **110**, so that ambient air is inducted from the exterior of housing **110** to the interior. Blowing fan/heater mounting portion **112** of main housing **110** has a cylindrically-shaped, interior space, so that a blowing fan **132** (FIG. 3) and heater assembly **140** may be mounted thereon.

Roasting-vessel mounting portion or receptacle **113** has an annular flange or bead that projects inwardly to the inside of housing **110** at the upper circumference of blowing fan/heater mounting portion **112**, so that roasting vessel **150**, which will be explained hereinafter, can be safely mounted. Hull-receiving vessel mounting portion **114** enables hull-receiving vessel **170**, which will be explained hereinafter, to be safely mounted at rear of housing **110**, in which air recovering openings are formed.

Conventional timer **120** is installed in front of housing **110**, and operated in a rotary manner, in order to allow for the performance of a roasting step and a cooling step. In other words, when timer **120** is in the roasting step, a blowing fan assembly **130** and heater assembly **140** are adapted to be operated, and when timer **120** is in the cooling phase, only blowing fan assembly **130** is adapted to be operated, while heater assembly **140** is not operated. It is preferred that timer **120** indicates the sign with regard to the roasting step and the cooling step at the front part of housing **110** at which timer **120** is installed, so that timer **120** can adjust the operating time of heater assembly **140** according to the quantity of raw coffee beans to be processed.

For example, the roasting state indicates the number of cups of coffee to be extracted from raw beans to be processed, and the cooling state is indicated in the unit of minutes, it being proper for the time to be set up to three minutes.

Fan assembly **130** comprises a motor **131** and a fan **132**, and is installed at the bottom side of main housing **110**, and is located in blowing fan/heater mounting portion **112**. Preferably, a small-size motor, the capacity of which is around 10,000 ppm, is used. Fan **132** is structured such that it is made from a flat sheet that has vanes bent radially outwardly, as seen in FIG. 5, and is fabricated to the size which can be installed in heater assembly **140**. Heater assembly **140** is operatively positioned above blowing fan **132** and consists of an outer casing **141** and a heating element **142** installed therein. Casing **141** has a lower casing section **141a** and an upper casing section **141b** having blow openings **141c** and **141d**, respectively.

Blow openings **141c** in lower case **141a** are formed largely in the part thereof which is opposite motor **131**, in order to maximize the airstream. Blow openings **141d** in upper casing **141b** are formed in large number but in small size, and they extend over a large, wide area in order to disperse the airstream. Heating element **142** is fixed between a pair of insulating plates **143**, an upper plate **143b** and a lower plate **143a** (FIG. 5). Lower insulating plate **143a** is affixed to outer casing **141** between parts **141a** and **141b** thereof, with its diameter being larger than upper insulating plate **143b**. The heating assembly includes a thermostat **144** and a temperature fuse **145** connected to heating element **142**, in order to prevent overheating, in the conventional manner.

Roasting vessel **150** is placed in roasting-vessel mounting portion **113** formed in main housing **110**, such that it is

positioned above and over heater assembly **140**, and it consists of a bottom portion **153** and a main body portion **155**. Bottom portion **153** is made of a nonferrous metal having good thermal conductivity, such as aluminum, with the interior of bottom **151** projected upwardly like a cone, in which radially arranged blow openings **152a** and **152b** are formed.

Air openings **152a** are formed in the central part of bottom **151** (FIG. 6), and air openings **152b** are formed about the outer part. Three, or more, air openings **152a** are arranged like steps. That is, each opening **152a** is formed as a linear slot that marks the termination or outlet of a raised, upwardly sloping upper wall **152'**. Each upper, sloping wall **152'** begins substantially at a lower vertical level coplanar with the rest of the bottom surface **151**, in which are formed air openings **152b**, and then each rises in approximately 15 degree radical arc about bottom surface **151**, and then terminates in the horizontal-slot air openings **152a**. Three such air openings **152a** thus provide swirling air current motion. Three air openings **152b** are located at bottom surface **151**, and are interspersed between three air openings **152b**, whereby three air openings are spaced 120 degrees apart. However, it is possible to provide just one air opening **152b** in order to apply the upward air current.

A circumferential portion **154** of bottom portion **153** is adapted to support the open bottom of main body portion **155**. It is preferred that main body portion **155** be made of transparent glass having a low thermal conductivity, in order for the inside to be visible, so that a measuring indicator may be provided. For example, a user may measure the quantity accurately by indicating the number of cups of coffee to be extracted according to the quantity of raw beans fed into roasting vessel **150**. In addition, main body portion **155** is equipped with a handle **156**, and its cross-sectional area is preferably H-shaped to enlarge its thermal emitting effect.

Cover **160** (FIG. 7) for the roasting vessel is made from synthetic resin material for a good moldability. Cover **160** forms an air path so as to accomplish the functions of not only opening and closing the upper part of body portion **155** of the roasting vessel, but also directing and discharging separated raw-bean hulls to hull-receiving vessel **170** by being connected to it by means of hinge openings **162** located at both lateral sides of its rear. At the upper side of this cover **160**, first air outlets **163** and second air outlets **164** are formed in the shape of long slots, and preferably, the first outlets are arranged radially on the central part of a cover, while the second outlets are arranged on the extended portion at which the airstream path is formed. Hull-receiving vessel **170** has projections **171** formed at its sides, so as to pivotally mount cover **160**, and is fabricated so as to be safely placed in hull-receiving vessel mounting portion **114** located at the backside of housing **110**. Hull-receiving vessel **170** forms a chute with inner and downwardly extending inclined surfaces, and has a plurality of air openings in its bottom surface similar to first and second air outlets **163** and **164**, so that the airstream from cover **160** is finally discharged therethrough.

A seal **180** is further provided (FIGS. 4 and 8), in order to provide an air seal when roasting vessel **150** is placed on main housing **110**. Also provided is a mounting member **190** that allows roasting vessel **150** to be attached to, or detached from, main housing **110**. Annular seal or packing **180** is made of silicone having good heat-resistance, and is dimensioned such that the inner circumference thereof is placed on the outer annular edge of the upper surface of casing section **141b** of heater assembly casing **141**, while the outer circumference thereof is placed on the outer annular edge of the

upper surface of casing section **141b** of heater assembly casing **141**, while the outer circumference thereof is placed on annular bead or flange of the roasting-vessel mounting portion **113** of housing **110**. A groove is formed in the bottom surface of seal **180** in order to improve its compressibility. Roasting vessel mounting member **190** is also in annular form, and has a plurality of downwardly-extending projections **191** that are formed in its bottom surface, and which are affixed to the inner diameter part thereof. Mounting member **190** also has an inwardly-projecting, annular bead **192** formed at an intermediate inner circumference thereof, for abutment against the upper surface of seal **180**. The outer diameter of annular bead **192** is approximately equal to the outer diameter of seal **180**, whereby seal **180** snugly fits inside the lower portion of mounting member **190** against the bottom surface of bead **192**. Thus, annular bead **192** provides a seal-bearing surface for compressing the seal. A plurality of upwardly-extending projections **193** are also provided, with an inclined groove **194** being formed at the upper side of roasting vessel mounting member **190**, in order to attach and detach roasting vessel **150**. Namely, roasting vessel **150** can be fixed by providing the same number of mating projections **157** on the outside of bottom surface **153** at the location corresponding to projections **193**.

The assembly of the present invention of the aforementioned construction will now be explained.

Firstly, timer **120** is assembled in the front of housing body **110**. Blowing fan **132** is integrally combined with motor **131**, such that fan **132** is placed in lower casing **141a** of heater assembly **140**, when blowing fan assembly **130** and heater assembly **140** are assembled. Then, insulating plate assembly **143** having heating element **142** is installed in casing **141**. In this case, lower insulating plate **143a** is affixed at the location where lower casing **141a** and upper casing **141b** meet. Thus, blowing fan **132** is positioned at the lower side of heating assembly **142**, and the blowing fan and heater are assembled integrally under the condition of being installed in casing **141**. Body portion **155** of the roasting vessel is combined with bottom portion **153**, with tight fitness. Cover **160** and hull-receiving vessel **170** are then combined, the former being adapted to be hinged to the latter by inserting projections **171** into holes **162**. After each element has been assembled, blowing fan assembly **130** and heater assembly **140** are emplaced, so that they are positioned in blowing fan/heater housing portion **112** of main housing **110**. At this time, motor **131** is affixed at the bottom of housing **110**, while the upper part of heater casing **141** is close to roasting vessel mounting annular flange **113**. Next, after putting seal **180** on roasting-vessel mounting flange **113** and on the upper surface-edge of casing part **141b**, mounting member **190** is attached to roasting-vessel mounting flange **113**, as seen in FIG. 3 by means of the projections, or feet, **191**. Projections **191** abut against the underside of roasting vessel mounting flange **113**, with annular bead **192** abutting against the upper surface of seal **180** for sandwiching the seal tight. Then, in order to mount roasting vessel **150**, its main body portion **155** is rotated clockwise when its bottom portion **153** is positioned in mounting member **190**, of which rotation is accomplished by holding handle **156** of main body portion **155**. The rotation causes mating projections **157** to be inserted in inclined grooves **194** of mounting member **190**. At this time, the annular bottom edge of bottom portion **153** of the roasting vessel is supported on the upper part of seal **180**, as seen in FIG. 8. Thus, a grooved portion **181** of seal **180** is widened, which results in greater surface contact between bottom portion **153** and seal **180**. In this way, an air-tightness is ensured. Furthermore, if body

portion **155** is rotated counter-clockwise, removal is achieved. Cover **160** is then placed on the entrance of main body portion **155** of the roasting vessel, and hull-receiving vessel **170** is placed in hull-receiving mounting portion **114** of main housing **110**. The apparatus of the present invention is, then, in a usable state.

The use of the present invention assembled as above is in the order set forth below.

- a) A suitable quantity of raw beans are put into roasting vessel **150**. At this time, the required quantity can be determined on the basis of the scale on main body portion **155**.
- b) Roasting vessel **150** containing raw beans is placed on mounting member **190**, and thereafter, locked by being rotated clockwise.
- c) After cover **160** is hinged to hull-receiving vessel **170**, hull-receiving vessel **170** is placed in hull-receiving mounting portion **114** of main housing **110**, and roasting vessel **150** is covered with cover **160**.
- d) The timer is set to the desired indicia on the scale thereof, according to the quantity of raw beans to be roasted. At this time, if controlled in accordance with the scale indicated on main body portion **155**, a roasting step and a cooling step are accomplished, in order. For the roasting step, fan assembly **130** and heater assembly **140** are operated, so that motor **131** and fan **132** are rotated at the speed of about 10,000 rpm or over, and heating element **142** is heated to about 240° C. Thus, ambient air is sucked through air inlets **111** of the bottom of housing **110** and openings **141c** of heater casing **141**, and a heated airstream is generated to ascend rapidly through heater casing **141d**. Since the ascending heated airstream is sealed via seal **180**, it is discharged through openings **152a** and **152b** formed at the bottom of a bottom portion **153** of the roasting vessel, without leakage to the outside. Thus, the airstream passing through air openings ascends vertically, and the ascending airstream passing through air openings whirls around in the circumferential direction.

Consequently, a compound, ascending stream is generated at the inside of roasting vessel **150**. By such heated and partially turbulent hot airstream, raw beans in roasting vessel **150** are mixed uniformly, roasted and gradually hulled. The hulls removed from the raw beans by the turbulent airstream ascend upwardly. At this time, the heated wind ascending in roasting vessel **150** is diminished in its quantity, because a part of it is discharged through first outlets **163** and second outlets **164** in cover **160**, and the hulls ascending to cover **160** are directed to hull-receiving vessel **170** along the upstream blowing path.

The hulls then descend along with a stream of air discharged to hull-receiving vessel **170**, in order to accumulate in hull-receiving vessel **170**. The raw beans being roasted with their hulls removed have a deep brown color. When raw beans have been roasted adequately, timer **120** causes the apparatus to enter into the cooling stage after finishing the roasting step. In the cooling stage, since the power source is continuously connected only to blowing fan **132** and disconnected from heater unit **140**, only blowing fan **132** operates. Since a cooling air is introduced, the raw beans are cooled, and oil does not leak out, at the surfaces of raw scrubbing. The cooling step continues for about three minutes. Interruption of the power source to blowing fan **130** ends the cooling stage.

- e) After raw beans have been roasted, cover **160** is lifted up and the handle of roasting vessel **150** is rotated

counter-clockwise to separate roasting vessel **150** from housing **110**, to thereby obtain the roasted beans.

- f) Afterward, the hulls are separated from cover **160** by pressing both sides of hull-receiving vessel **170**, and thrown out. Raw beans obtained through a roasting process as above are pulverized by means of a pulverizer and extracted using an extracting machine, and usable as raw bean coffee.

Another preferred embodiment of the present invention will be described in detail with referring to FIGS. 9–11.

The apparatus for roasting raw coffee beans according to another embodiment of the present invention comprises a main housing having an air inlet; a blower fan assembly mounted on the main housing for blowing air; a heater assembly mounted on the housing and above the blower fan assembly for generating heat, the blower fan assembly directing the heat upwardly; a whirlwind generating plate above the heater assembly; a roasting vessel above the heater assembly for containing raw coffee beans to be roasted; a hull-receiving vessel for receiving and storing the hulls of the raw coffee beans blown along the air stream directed thereto from the roasting vessel, the hull-receiving vessel having an air outlet; a filter provided in the air outlet; a cover for covering the roasting vessel, the cover guiding hulls from the raw coffee beans along the path of the air stream; and a power means for providing power to the blower fan assembly and the heater assembly.

Particularly, the apparatus according to another embodiment of the present invention includes a heater **240**, a blowing fan assembly **230**, a whirlwind generating plate **251** above heater **240**, a roasting vessel **250** made of transparent glass, vertically combined on whirlwind generating plate **251**, a roasting vessel handle **256a** provided at one side of roasting vessel **250** by means of a sealing bean **253**, a groove portion **257** formed at the upper edge of roasting vessel handle **256a**, a hull-receiving vessel **270** which is detachably inserted onto roasting vessel **250**, a discharge hole **273** and a hull-receiving part **272** separated by an exhaustion inducing inclined plane **271** formed at the inner portion of hull-receiving vessel **270**, a plurality of exhausting holes **274** perforated at the upper portion of hull-receiving vessel **270**, a filter **275** provided in exhausting holes **274**, a hull-receiving vessel handle **276** which is combined, with one side of hull-receiving vessel **270** and of which lower portion is placed on groove portion **257** and a cover **260** which closes hull-receiving vessel **270**.

Roasting vessel **250** is made of transparent glass material for visibility into and has a cylindrical shape of which upper and lower portion are opened. Whirlwind generating plate **251** is provided under roasting vessel **250**.

Hull-receiving vessel **270** is separated into discharge hole **273** and hull-receiving part **272** by exhaustion inducing inclined plane **271**, and is provided with a projection **277** at the middle of hull-receiving vessel **270**, on which the lower portion of filter **275** is suspended. Also provided is a suspending projection **278** at the lower portion of hull-receiving vessel **270**, which is suspended on roasting vessel **250**. An inclined portion **279** is formed at the lower portion of discharge hole **273** to accomplish smooth exhaustion of air including hulls from wide portion to narrow portion.

Filter **275** formed in exhausting hole **274** plays the role of a filter for exhausting only air outwardly.

The bottom of whirlwind generating plate **251** is formed as a continuous inclined plate **254**. Blow openings **252** are formed in terraces at steps between inclined plane **254**.

Blow openings **252** are formed alternately as long and short openings to generate a whirlwind.

Cover **260** is formed as a dome-shape and induces the exhausted air through discharge hole **273** downwardly to drop hulls into hull-receiving part **272**.

When roasting raw coffee beans using the apparatus of the present invention, an appropriate amount of raw coffee beans is put in roasting vessel **250** and the vessel is combined with a main body **210**. Then, hull-receiving vessel **270** including cover **260** is provided onto roasting vessel **250**.

When hull-receiving vessel **270** is inserted into roasting vessel **250**, hull-receiving vessel handle **256b** comes into contact with roasting vessel handle **256a** to give a simple look.

The raw coffee beans could also be placed through discharge hole **273** after opening cover **260**, even when roasting vessel **250** and hull-receiving vessel **270** are combined as shown in FIG. 9.

At this stage, timer **220** is set to a desired division to proceed with the roasting step and the cooling step.

As the roasting step, blowing fan **230** rotates at about 1,000 rpm and heater **240** is heated to about 240° C. The airstream flowing into the apparatus by means of blowing fan **230** is heated by heater **240** and rises spirally and rapidly through blow openings **252** in terraces of whirlwind generating plate **251**.

The air flow through blow openings **252** in terraces forms a rising stream while whirling.

At this time, the raw coffee beans in roasting vessel **250** drop and roll over and over to be mixed uniformly and to be cooked by the hot air stream. The raw coffee beans change their rotating direction which chips off the hulls during rolling and the removed hulls rise by the air through discharge hole **273** in the middle of hull-receiving vessel **270**.

The raised air through discharge hole **273** is spread above hull-receiving vessel **270** to all directions to reduce its velocity and is exhausted through filter **275** and exhausting hole **274**.

As the air stream is spread and exhausted, the hulls of the raw coffee beans drop into hull-receiving part **272** separated from discharge hole **273** by exhaustion inducing inclined plane **271**.

Meanwhile, since roasting vessel **250** is transparent, the raw coffee beans could be observed with naked eyes. If dark brown color is represented, the raw coffee beans are regarded as being roasted appropriately.

After appropriate roasting for about 3–5 minutes, the cooling step in which blowing fan assembly **230** is operated is started by means of a timer **220**.

After cooling for about 3 minutes, the power is turned off. Hull-receiving vessel **270** is detached while catching a hull-receiving vessel handle **256b** and roasting vessel **250** is detached while catching roasting vessel handle **256a** to thereby obtain the roasted beans and complete the roasting of the raw beans.

The roasted beans are pulverized using a pulverizer and extracted using an extracting machine for drinking.

Since the apparatus according to the above-mentioned embodiment includes housing **210**, roasting vessel **250** and hull-receiving vessel **270** successively, housing **210** could be designed at will. Moreover, housing **210** and hull-receiving vessel **270** can not possibly be damaged by the heat from heater **240**.

In addition, since the air stream rises through discharge hole **273** and is spread to all directions, while reducing its velocity, the hulls of the raw coffee beans drop advantageously into hull-receiving part **272** without generating powdered hulls.

The preferred embodiments of the present invention aforementioned can be fabricated to a small size so as to be

used easily at home, and it can provide raw bean coffee by roasting a small quantity of raw beans whenever required. Additionally, it enables users to enjoy a variable taste and fragrance of raw beans by adjusting the processing time according to a personal taste.

While the present invention has been particularly shown and described with reference to particular embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be effected therein without departing from the spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. An apparatus for roasting raw coffee beans comprising: a main housing having an air inlet; a blower fan assembly mounted on said main housing for blowing air; a heater assembly mounted in said housing and above said blower fan assembly for generating heat, said blower fan assembly directing the heat upwardly; a roasting vessel above said heater assembly for containing raw coffee beans to be roasted; a hull-receiving vessel for receiving and storing hulls of said raw coffee beans blown along the air stream directed thereto from said roasting vessel, said hull-receiving vessel having an air outlet; a cover for covering said roasting vessel, said cover guiding hulls from said raw coffee beans along the path of the air stream; and a power means for providing power to said blower fan assembly and said heating assembly, wherein said roasting vessel includes a plurality of holes for allowing the heated air stream from said heater assembly to enter into the interior of said roasting vessel, and said cover has a hull-guide means for directing the hulls from the roasted coffee beans along a specific downstream path.
2. The apparatus for roasting raw coffee beans as claimed in claim 1, further comprising an annular seal upon which said roasting vessel is at least partially supported, said seal being supported by a portion of said heater assembly and a part of said main housing.
3. The apparatus for roasting raw coffee beans as claimed in claim 2, wherein said seal comprises an annular groove for aiding in its sealing function.
4. The apparatus for roasting raw coffee beans as claimed in claim 1, further comprising an annular, detachable mounting member for mounting said roasting vessel.
5. The apparatus for roasting raw coffee beans as claimed in claim 4, wherein said mounting member comprises a bottom, and plurality of mounting projections formed at said bottom, said projections being operatively associated with a part of said main housing for mounting said mounting member and said roasting vessel; said mounting member further comprising an interior annular bead for contact against said seal, and at least one upwardly extending finger-member for detachably supporting roasting vessel.
6. The apparatus for roasting raw coffee beans as claimed in claim 1, further comprising a timer for controlling the operation of said power means; said timer having a first stage for coupling said power means to both said fan assembly and said heater assembly, and a second stage for coupling said power means to said fan assembly and for disconnecting said power means from said heater assembly, whereby a cooling cycle is provided for cooling the roasted coffee beans.
7. The apparatus for roasting raw coffee beans as claimed in claim 1, wherein said roasting vessel comprises a main

body portion, and a bottom portion, said bottom portion having an interiorly, upwardly-projecting, substantially conically-shaped bottom surface; said plurality of holes in said roasting vessel being formed in said bottom surface; said plurality of holes comprising a first set and a second set for creating a whirling vertical motion to the heated airstream ascending therethrough, whereby said raw coffee beans are roasted and also caused to have their hulls separated to ascend upwardly with the airstream to said hull receiving vessel.

8. The apparatus for roasting raw coffee beans as claimed in claim 7, wherein said roasting vessel comprises a handle having an H-shaped cross section for increasing thermal emission.

9. The apparatus for roasting raw coffee beans as claimed in claim 7, wherein said bottom portion of said roasting vessel comprises at least one projection for cooperating with at least one upwardly extending finger member for detachably mounting said roasting vessel.

10. The apparatus for roasting raw coffee beans as claimed in claim 1, wherein said cover opens and closes the upper entrance of said roasting vessel, said cover being pivotally connected to said hull-receiving vessel.

11. An apparatus for roasting raw coffee beans comprising:

- a main housing having an air inlet;
- a blower fan assembly mounted on said main housing for blowing air;
- a heater assembly mounted in said housing and above said blower fan assembly for generating heat, said blower fan assembly directing the heat upwardly;
- a roasting vessel above said heater assembly for containing raw coffee beans to be roasted;
- a hull-receiving vessel for receiving and storing hulls of said raw coffee beans blown along the air stream directed thereto from said roasting vessel, said hull-receiving vessel having an air outlet;
- a cover for covering said roasting vessel, said cover guiding hulls from said raw coffee beans along the path of the air stream;
- a power means for providing power to said blower fan assembly and said heating assembly;
- a whirlwind generating plate above said heater assembly; and
- a filter provided in said air outlet.

12. The apparatus for roasting raw coffee beans as claimed in claim 11, wherein the bottom of said whirlwind generating plate is formed as a continuous inclined plane and is provided with blow openings at steps between said inclined plane.

13. The apparatus for roasting raw coffee beans as claimed in claim 12, wherein a first group of said blow openings having a first length and a second group of said blow openings having a second length longer than the first length are alternately arranged.

14. The apparatus for roasting raw coffee beans as claimed in claim 11, wherein said roasting vessel is made of transparent glass and is fixed on said whirlwind generating plate.

15. The apparatus for roasting raw coffee beans as claimed in claim 14, wherein a roasting vessel handle is provided on one side of said roasting vessel using a sealing band.

16. The apparatus for roasting raw coffee beans as claimed in claim 11, wherein a hull-receiving vessel handle is provided on one side of said hull-receiving vessel.

11

17. The apparatus for roasting raw coffee beans as claimed in claim 16, wherein said hull-receiving vessel handle comes in contact with said roasting vessel handle when combining said hull-receiving vessel with said roasting vessel.

18. The apparatus for roasting raw coffee beans as claimed in claim 11, wherein said discharge hole having said inclined plate is formed at the center of said hull-receiving vessel, whereby air stream including hulls is smoothly blown from wide to narrow portion.

19. The apparatus for roasting raw coffee beans as claimed in claim 11, further comprising a projection for fixing said filter in said hull-receiving vessel.

20. The apparatus for roasting raw coffee beans as claimed in claim 11, further comprising a suspending projection which is suspended at the upper portion of said roasting vessel at the lower portion of said hull-receiving vessel.

21. The apparatus for roasting raw coffee beans as claimed in claim 11, wherein said cover is formed in a dome-shape, whereby the air stream blown through said discharge hole is directed downwardly to drop the hull in said hull-receiving part.

22. An apparatus for roasting raw coffee beans comprising:

a main housing having an air inlet;

a blower fan assembly mounted on said main housing for blowing air;

a heater assembly mounted in said housing for generating heat, said blower fan assembly directing the heat in a heated airstream; and

a roasting vessel for containing raw coffee beans to be roasted, said roasting vessel including an interiorly, upwardly projecting, substantially conical-shaped bottom surface, said surface including a plurality of holes to allow entry of the heated airstream into the interior of said roasting vessel.

23. The apparatus for roasting raw coffee beans according to claim 22, wherein said plurality of holes comprises a first set and a second set, with each of the holes of the first set being larger than each of the holes of the second set.

24. The apparatus for roasting coffee beans according to claim 23 wherein said first set of holes are provided in the form of elongate slots having a first length, and the second of holes are provided in the form of elongate slots having a second length shorter than the first length.

25. An apparatus for roasting raw coffee beans comprising:

a main housing including at least one upwardly extending finger;

a blower fan assembly mounted on said main housing for blowing air;

a main heater assembly mounted in said housing for generating heat, said blower fan assembly directing the heat in a heated airstream; and

a roasting vessel for containing raw coffee beans to be roasted, the roasting vessel including at least one projection adapted to engage the at least one upwardly extending finger to detachably mount the roasting vessel to the main housing.

26. An apparatus for roasting raw coffee beans comprising:

a main housing;

a blower fan assembly mounted on said main housing for blowing air;

12

a heater assembly mounted in said housing for generating heat, said blower fan assembly directing the heat in a heated airstream; and

a roasting vessel for containing raw coffee beans to be roasted, said roasting vessel formed as a separate unit that can be removed from the main housing, said roasting vessel including a plurality of openings in the form of slots to allow entry of heated air into the roasting vessel.

27. An apparatus for roasting raw coffee beans comprising:

a main housing;

a blower fan assembly mounted on said main housing for blowing air;

a heater assembly mounted in said housing for generating heat, said blower fan assembly directing the heat in a heated airstream; and

a roasting vessel for containing raw coffee beans to be roasted said roasting vessel formed as a separate unit that can be removed from the main housing, said vessel including a whirlwind generating plate.

28. An apparatus for roasting raw coffee beans comprising:

a main housing;

a blower fan assembly mounted on said main housing for blowing air;

a heater assembly mounted in said housing for generating heat, said blower fan assembly directing the heat in a heated airstream; and

a roasting vessel for containing raw coffee beans to be roasted, said roasting vessel formed as a separate unit that can be removed from the main housing, at least a majority of the roasting vessel defined by a transparent, cylindrical shaped container.

29. The apparatus for roasting raw coffee beans of claims 28 wherein the roasting vessel comprises a transparent upper portion and a lower portion having holes formed therein for the entry of the heated airstream into the roasting vessel, the upper portion having a continuous cylindrical shape with a circular, open end engaged with the lower portion.

30. An apparatus for roasting raw coffee beans comprising:

a main housing having an air inlet;

a blower fan assembly mounted on said main housing for blowing air;

a heater assembly mounted in said housing for generating heat, said blower fan assembly directing the heat in a heated airstream;

a roasting vessel above said heater assembly for containing raw coffee beans to be roasted; and

a plate positioned to direct the heated airstream into the roasting vessel, the plate including a first group of slotted blow openings having a first length and a second group of slotted blow openings having a second length longer than the first length.

31. A coffee roaster of the class which roasts coffee by forcing heated air through a bed of coffee beans comprising:

a main housing;

a duct on said main housing;

a heater;

a blower positioned to force air through said heater and said duct;

an oven for holding a charge of coffee beans during the roasting process;

13

said oven including a lower section dimensioned to permit insertion of said lower section into said duct and removal of said lower section from said duct.

32. A method of roasting coffee, including the steps of: placing a removable oven partially into a heated air supply;

forcing heated air from said supply into said removable oven via elongated slots in said removable oven;

14

converting said green coffee beans into roasted coffee beans by heat transfer from said heated air; and

removing said removable oven from said heated air supply after said green coffee beans have been converted to said roasted coffee beans having a desired degree of roast.

* * * * *