



US00RE37395B1

(19) **United States**  
(12) **Reissued Patent**  
**Kunert et al.**

(10) **Patent Number: US RE37,395 E**  
(45) **Date of Reissued Patent: Oct. 2, 2001**

(54) **METHOD OF CENTERING WINDSHIELD GLAZINGS**

(75) Inventors: **Heinz Kunert**, Cologne; **Gerd Cornils**, Merzenich-Girbelsrath; **Heinrich Schnitter**, Simmerath, all of (DE)

(73) Assignee: **Saint-Gobain Glass France (FR)**

(\* ) Notice: This patent is subject to a terminal disclaimer.

(21) Appl. No.: **09/084,365**

(22) Filed: **May 27, 1998**

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **5,519,979**  
Issued: **May 28, 1996**  
Appl. No.: **08/309,307**  
Filed: **Sep. 20, 1994 U.S. Applications:**

(63) Continuation of application No. 07/450,345, filed on Dec. 13, 1989, now Pat. No. 5,384,995, which is a continuation-in-part of application No. 07/242,387, filed on Sep. 9, 1988, now Pat. No. 4,938,521, and application No. 07/360,654, filed on Jun. 2, 1989, now Pat. No. 4,933,032, and application No. 07/436,280, filed on Nov. 14, 1989, now Pat. No. 5,057,265.

(30) **Foreign Application Priority Data**

Sep. 10, 1987 (DE) ..... 37 30 345  
Jun. 3, 1988 (DE) ..... 38 18 930  
Sep. 12, 1989 (DE) ..... 39 30 414

(51) **Int. Cl.<sup>7</sup>** ..... **B60R 11/00**; B60J 1/00; E06B 3/54

(52) **U.S. Cl.** ..... **52/745.15**; 52/745.2; 52/204.591; 52/204.62; 52/204.69; 52/208; 296/146.15; 296/93; 296/201

(58) **Field of Search** ..... 52/208, 204.591, 52/204.62, 204.64, 204.69, 745.15, 745.16, 745.2; 296/93, 146.15, 201

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,429,223	9/1922	Bruening .	
1,763,603	6/1930	Donahue .	
2,606,635	8/1952	Clingman .	
3,478,475	11/1969	Strack .	
3,774,363	11/1973	Kent .	
3,779,794	12/1973	De Santis .	
4,151,620	5/1979	Heuzonter .	
4,296,961	10/1981	Hunt et al. .	
4,433,010	2/1984	Pedain et al. .	
4,551,372	11/1985	Kunert .....	428/38
4,571,278	2/1986	Kunert .....	156/108
4,581,276	4/1986	Kunert et al. .	
4,606,159	8/1986	Kunert .	
4,628,655	12/1986	Scheiderer .	
4,648,222	3/1987	Mivata et al. .	

(List continued on next page.)

**FOREIGN PATENT DOCUMENTS**

82 02672 6/1982 (DE) .

(List continued on next page.)


*Primary Examiner*—Robert Canfield

(74) *Attorney, Agent, or Firm*—Pennie & Edmonds LLP

(57) **ABSTRACT**

A motor vehicle glazing (1) prepared for installation according to the adhesive process is provided with a profiled spacer (8) produced by extrusion of an extrudable polymer directly onto glazing (1) and subsequent setting. During installation of glazing (1) in the window opening of the motor vehicle body, profiled spacer (8) acts as an intermediate member between glazing (1) and assembly adhesive extrudate (13). Profiled spacer (8) is provided along its outer periphery with a lip portion (10) projecting beyond peripheral area (3) of glazing (1). In the installed position of glazing (1), lip portion (10) rests against the window frame flange (4) running parallel to peripheral area (3) of glazing (1) and acts, upon insertion of the glazing during the setting process of assembly adhesive (13), as a support and centering element for glazing (1).

**16 Claims, 3 Drawing Sheets**



# US RE37,395 E


Page 2

## U.S. PATENT DOCUMENTS

4,681,794	7/1987	Kunert et al. ....	428/188	122636	4/1983	(EP)	.
4,707,958	11/1987	Armbruster .		0 121 480	10/1984	(EP)	.
4,765,673	8/1988	Frabotta et al. .		148797	7/1985	(EP)	.
4,775,570	10/1988	Ohlenforst et al. ....	428/83	306070	3/1989	(EP)	.
4,833,847 *	5/1989	Inayama et al. ....	52/204.591 X	0310262	4/1989	(EP)	.
4,839,122	6/1989	Weaver .		319262	6/1989	(EP)	.
4,876,132	10/1989	Kunert .		0 345 134 *	6/1989	(EP)	.
4,879,853	11/1989	Braendle et al. .		298788	11/1989	(EP)	.
4,881,773	11/1989	Ichinose .		22131	1/1991	(EP)	.
4,888,072	12/1989	Ohlenforst et al. .		0 545 896	10/1994	(EP)	..... B60J/10/02
4,910,071	3/1990	Kunert .....	428/192	0 421 833	2/1995	(EP)	..... B60J/1/02
4,933,032	6/1990	Kunert .		1135684	5/1957	(FR)	.
4,938,521	7/1990	Kunert .....	296/96.21	2266669	10/1975	(FR)	.
5,057,265	10/1991	Kunert et al. .		1 207 483	10/1970	(GB)	.
5,062,248	11/1991	Kunert .....	52/208	1219511	3/1971	(GB)	.
5,085,021	2/1992	Kunert .....	52/208	2143569	2/1985	(GB)	.
5,095,669 *	3/1992	Kunert et al. ....	52/208	2147244	5/1985	(GB)	.
5,154,028	10/1992	Hill et al. .		2217375	10/1989	(GB)	.
5,233,805	8/1993	Hirai et al. .		47-32523	11/1972	(JP)	.
5,255,483	10/1993	Agranal et al. .		57-58509	4/1982	(JP)	.
5,316,829 *	5/1994	Cordes et al. ....	428/192	161218	8/1985	(JP)	.
5,338,087	8/1994	Gross et al. .		60-166517	8/1985	(JP)	.
5,443,673 *	8/1995	Fisher et al. ....	52/208 X	61-37412	2/1986	(JP)	.
5,580,628 *	12/1996	Cordes et al. ....	428/38	61-247513	11/1986	(JP)	.
5,591,528 *	1/1997	Fisher et al. ....	428/411.1	62-125913	6/1987	(JP)	.
5,688,016 *	11/1997	Gold .....	52/208 X	62-155123	7/1987	(JP)	.
5,806,257 *	9/1998	Cornils et al. ....	52/208	62-163818	7/1987	(JP)	.
				62-178421	8/1987	(JP)	.
				62-251229	11/1987	(JP)	.
				63-192608	8/1988	(JP)	.
				63-215417	9/1988	(JP)	.
				1-109116	4/1989	(JP)	.
				1-63518	4/1989	(JP)	.
				1-113012	7/1989	(JP)	.

## FOREIGN PATENT DOCUMENTS

\* cited by examiner






FIG. 2




FIG. 3




FIG. 4

## METHOD OF CENTERING WINDSHIELD GLAZINGS

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.**

This a continuation of application Ser. No. 07/450,345, filed Dec. 13, 1989, now U.S. Pat. No. 5,384,995, which is in turn a continuation-in-part of application Ser. No. 07/242,387, filed Sep. 9, 1988, now U.S. Pat. No. 4,938,521, of application Ser. No. 07/360,654, filed Jun. 2, 1989, now U.S. Pat. No. 4,933,032, and of application Ser. No. 07/436,280, filed Nov. 14, 1989, now U.S. Pat. No. 5,057,265.

### FIELD OF THE INVENTION

The invention relates to a glazing provided for bonding to the attachment flange of a window frame, in particular a motor vehicle glazing, with a profiled spacer, preferably produced by extrusion of a polymer on the side of the glazing opposite the attachment flange. The profiled spacer, acts as a support and centering element upon insertion of the glazing, as well as during the setting of the assembly adhesive. The invention describes the process for the production of such a glazing as well as a process and apparatus for performing the process.

### BACKGROUND OF THE INVENTION

Motor vehicle glazings are often attached today by direct bonding to the attachment flange of the window frame in the motor vehicle body. It has proven useful to prepare the glazing prior to the assembly process, by providing the glazing with an adhesive material that is produced by extrusion on the glazing, which after setting, acts as an intermediate body between the glazing and the assembly adhesive. This eliminates the requirement of cleaning and priming the glazing on the assembly line of the motor vehicle plant, necessary for the bonding of the glazing, which results in the insertion of the glazing into the body being performed more economically. This process is known, for example, from EP-O 121 401-A1.

When inserting the glazing into the window frame of the body, the glazing must be correctly positioned and then held stationary during the setting phase of the assembly adhesive. As a rule, additional assembly aids and/or support elements are required for this purpose EP 307 317-A1 describes a motor vehicle glazing comprised of a spacer oriented perpendicular to the glazing surface and having a support surface that bears the weight component of the glazing running in the direction of the glazing plane in the installation position, and a bracket having a support element that interacts with the support surface of the spacer. The support surface and support element cooperate to properly position and set the glazing. This known solution, however, requires additional support elements in the window frame. Further, it is required that the support elements in the window frame lie at a constant distance from the outwardly visible periphery of the window frame. Otherwise, the junction between the peripheral area of the glazing and the flange of the window frame opposite the peripheral area will exhibit a varying width, which results in the requirement to cover this juncture with an additional covering profile.

One object of the invention is to configure a motor vehicle glazing comprised of an extruded profiled spacer so that the proper centering and bracing of the glazing, during the setting phase of the assembly adhesive, is guaranteed without additional support elements being required in the window frame.

## SUMMARY OF THE INVENTION

The invention provides a profiled spacer which acts as a support and centering element for the glazing. The profiled spacer includes a lip portion which is oriented approximately parallel to the glazing surface and which projects beyond the peripheral or edge of the glazing. The lip portion, in the installation position of the glazing, rests against the flange of the window frame running parallel to the peripheral area of the glazing.

The profiled spacer described in the invention is dimensioned in thickness and length so that the lip portion may deform during insertion of the glazing into the window frame. The lip portion is bent from about 45 to 90 degrees relative to the original orientation of the lip portion. While the lip portion of the spacer carries the dead weight of the glazing on the one side, it simultaneously assumes the centering and sealing function for the surrounding gap between the peripheral area of the glazing and the flange of the window frame opposite the peripheral area. This results in said gap having a constant width. The covering of said gap by an additional sealing or decorative profile is therefore, no longer necessary. Hence, an extraordinarily economical solution is provided by the invention.

If the said gap remaining between the peripheral area of the glazing and the opposite flange of the window opening of the body is not covered by an additional sealing or decorative profile, the lip portion projecting beyond the peripheral area of the glazing is outwardly visible. In this case, special measures must be taken to configure the transition zone between the beginning and the end of the extruded profile spacer to obtain a continuous spacer.

### BRIEF DESCRIPTION OF THE DRAWINGS

Further details and advantages of the invention are described in detail below based on the drawings, wherein:

FIG. 1 disclose a motor vehicle glazing made according to the invention in the installed state, in the form of a sectional drawing;

FIG. 2 discloses the position and configuration of a profile spacer according to the invention in place on the glazing prior to assembly in vehicle;

FIG. 3 discloses another spacer and bracket for the bottom of a windshield; and

FIG. 4 discloses yet another spacer and bracket for the bottom of a windshield according to the invention.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the case represented in FIG. 1, glazing 1 is a windshield that is inserted in the corresponding window opening of a motor vehicle body. The window opening is delineated by attachment flange 2, which runs parallel to the glazing surface, and by frame section 4 that runs parallel to peripheral area 3 of glazing 1. Glazing 1 is represented as a monolithic glazing, but said glazing may also be comprised of a multilayer laminated glazing. Along the periphery of glazing 1 there is provided, on the side facing attachment flange 2, an opaque layer 5 that consists, for example, of a baked enamel. The object of layer 5 is to prevent the adhesive compound lying behind layer 5 from being outwardly visible and simultaneously to protect the adhesive compound from UV rays.

Glazing 1 is provided on the side facing the attachment flange 2 with a profiled spacer 8, made of a polymer that is

elastomeric in the set state. Profiled spacer **8** adheres to opaque layer **5**. In the further description, this opaque, layer **5** is not represented for the sake of greater clarity.

Profiled spacer **8** exhibits a continuous lip portion **10**. Before installation of glazing **1** in the window frame, lip portion **10** has a straight form, as shown in FIG. 2. Lip portion **10** is oriented approximately parallel to the glazing surface and projects beyond peripheral area **3** of glazing **1** by about 5 to 10 mm. During insertion of the glazing into the window frame, lip portion **10** is bent back as shown and rests over its entire periphery against the window frame section **4** which runs parallel to peripheral area **3** of the glazing. During insertion of the glazing into the window frame, glazing **1** is automatically centered, so that a gap **12** of even width remains all around glazing **1**. At the same time, lip portion **10** acts in the lower area of glazing **1** to support the glazing weight, so that no additional support measures are required during the setting process of the assembly adhesive. Finally, lip portion **10** achieves the further object of closing and sealing the gap **12**.

The dimensioning of lip portion **10**, i.e., in length and thickness, shall be selected so the stated objects of lip portion **10** are fulfilled in an optimal way.

The connection of glazing **1** equipped in advance with the profiled spacer **8**, to the attachment flange **2** is performed with the aid of an assembly adhesive bead **13**. The assembly adhesive bead **13** consists of a polymer that adheres solidly and permanently to the profiled spacer **8**; for example, a moisture setting one-component polyurethane. The pressing of the glazing **1** against the attachment flange **2** required during the setting time of adhesive bead **13**, is also guaranteed by the lip portion **10** of the profiled spacer **8** which, because of its high coefficient of friction and its relative stiffness, absorbs restoring forces possibly exerted by the adhesive bead **13**.

The production of profiled spacer **8** is performed, with the aid of the extrusion technique generally known in the art, by extruding a suitable polymer that adheres to the glazing by bonding. As for polymers used in the production of the profiled spacer **8**, one-component polyurethane prepolymers in paste form the set after extrusion, under the influence of atmospheric moisture, into high modulus elastomers are acceptable. Such polyurethane systems are described in U.S. Pat. No. 3,779,794. Polyurethane systems on a two-component basis may also be used. For example, adhesive systems as described in European patents 0 083 797 and 0 024 501. Depending on the adhesive compound used, the surface on which the adhesive material is applied is to be pretreated in the required manner and as an option, provided with one or more suitable priming layers.

To produce the profiled spacer **8** on the glazing **1**, a method and apparatus are described in U.S. patent application Ser. No. 436,280 filed Nov. 14, 1989 the content of which is expressly incorporated herein by reference thereto. This spacer **8** is preferably applied to the glazing **1** by a compression molding technique.

During the production of the profiled spacer, it is desirable to utilize a release film **33, 34** which adhere to the polymer material, but does not bond thereto. For this reason, after the setting of the polymer material, films **33** and **34** can easily be removed from profiled spacer **8** by simple pulling.

Films **33** and **34** consist of a material whose surface has anti-adhesive properties to the polymer material of the profile spacer **8**. Thin films of polyester or polyethylene have proven themselves useful for this purpose. If a moisture setting system is used as polymer material for profiled

spacer **8**, films **33, 34** must exhibit a sufficient water vapor permeability, so the moisture necessary for the setting process can diffuse through the films. Optionally, films **33, 34** may exhibit a specific porosity or a microperforation.

Films **33, 34** confer on lip portion **10** an additional rigidity during the setting process, and a thin layer between two films **33, 34** and sets into a flash or tab **41** projecting beyond edge **40** of lip portion **10**. After the setting of the polymer is finished, this flash or tab **41** is cut along edge **40** of the lip portion **10** together with films **33** and **34** and is removed. This results in a clean final edge of lip portion **10** being achieved, even in the transition zone of profile spacer **8**. Remaining film pieces **33, 34** are then removed from profile spacer **8** and lip portion **10**.

FIG. 3 illustrates another embodiment of a spacer **146** in the lower part of a window opening. Here the spacer **146** is placed along the lower edge of glazing **1** and serves as a rigid support bonded to the glazing. The spacer **146** will rest on the upper edge **147** of sheet metal bracket **148**. Also, spacer **146** is equipped along its lower face with a groove **149** in which the upper edge **147** of sheet metal bracket **148** becomes engaged. The immobilization achieved by spacer **146** lasts at least as long as is necessary for the bead of glue **110** to set.

FIG. 4 shows an embodiment in which glazing **1** is equipped with a spacer **152**, which, when placed over the entire periphery, achieves a positioning in three dimensions through its interaction with the sheet metal bracket **155**. The edge **154** of sheet metal bracket **155** is inserted into the groove **156** of the inner peripheral portion **153** in such a way as to achieve precise positioning of the glazing within its plane. The outer peripheral portion **157** has a height **H** which corresponds to the desired distance between the glazing and the sheet metal bracket **155**. This peripheral portion functions as a stop during placement of the glazing into the window opening. Thus, the bead of glue **110** is pressed on by the glazing in the direction of the sheet metal bracket **155** to the limit established by the peripheral portion involved. Therefore, a precise positioning of the glazing in the direction perpendicular to its surface is also obtained.

The embodiments of the invention described relate to the windshield of a motor vehicle. But the invention can also be applied in the same manner to glazings intended for doors, side windows, end gates, sun roofs, sliding roofs, rear flaps, and headlight flaps of motor vehicles. Further, the invention can be applied in other areas wherever glazings are attached in a frame by the adhesive method. In the vehicle field, for example, it may be used successfully also for the windows of trailers and railroad cars. It can also be used equally successfully for the windows of window openings in the construction sectors as well as for the installation of glazings in appliances and furniture, for example, household refrigerators.

We claim:

1. A method of centering a substantially planar glazing upon a bracket which comprises

providing substantially the entire periphery of said glazing with a spacer comprising a lip portion which extends beyond the edge of said glazing and is initially oriented essentially parallel to the plane of said glazing and

placing said glazing parallel to an edge of a mounting bracket and within the bracket, whereby said lip portion of the spacer contacts said bracket to provide a force for centering said glazing thereon, which force is sufficient to maintain centering of the glazing on the bracket and

5

to provide a gap between the glazing edge and the bracket around substantially the entire periphery of the glazing.

2. The method of claim 1 which further comprises dimensioning said lip portion in length and thickness to provide said centering force.

3. The method of claim 1 which further comprises forming said lip portion of an elastomer having a modulus of elasticity which is sufficiently high to provide said centering force.

4. The method of claim 1 which further comprises securing said glazing to said bracket with a bead of adhesive.

5. The method of claim 4 which further comprises configuring said spacer supporting said bead of adhesive.

6. The method of claim 5 which further comprises configuring the spacer to have a recessed portion to receive said adhesive bead.

7. The method of claim 6 which further comprises providing said spacer with a pair of leg portions which define the sides of said recessed portion.

8. The method of claim 4 which further comprises forming said lip portion having a modulus of elasticity and a coefficient of friction with said bracket which are sufficiently high to fix the glazing against said bracket during setting of said adhesive bead.

9. The method of claim 1 wherein the centering force is sufficient to prevent said glazing edge from contacting said bracket.

10. The method of claim 1 wherein the centering force is sufficient to provide a gap between the glazing edge and the bracket around the entire periphery of the glazing.

11. A method of centering a glazing upon a mounting bracket, said glazing having a surface with a periphery for receiving a spacer, said periphery including a glazing edge, the method comprising:

*providing at least a portion of said periphery of said glazing with a spacer having a lip portion which extends beyond the glazing edge of said glazing and is initially oriented essentially parallel to said surface along said portion of said periphery; and*

*placing said glazing parallel to an edge of said mounting bracket and within said mounting bracket, whereby said lip portion of the spacer contacts said bracket to provide a force for centering said glazing thereon, which force is sufficient to maintain centering of the glazing on the bracket and to provide a gap between said glazing edge and the bracket along said portion of said periphery of the glazing.*

12. A method of centering a glazing upon a mounting bracket having opposed frame sections, said glazing having a glazing surface with a periphery for receiving a spacer, said periphery including opposed glazing edges, said method comprising:

*providing at least a portion of the periphery adjacent each of said opposed glazing edges of said glazing with a spacer having a lip portion which extends beyond the glazing edge and is initially oriented essentially parallel to said surface along said portion of said periphery; and*

6

*placing said glazing within said mounting bracket with said opposed glazing edges facing said opposed frame sections of said bracket, whereby said lip portion of each spacer contacts one of said opposed frame sections of said bracket to provide a force for centering said glazing thereon, which force is sufficient to maintain centering of the glazing on said bracket so as to provide a gap between the opposed glazing edges and the opposed frame sections of said bracket.*

13. The method of claim 12 wherein the contacting of the lip portion of each spacer with the opposed frame section of said bracket includes resiliently bending the lip portion as said glazing is placed within said bracket to provide said force for centering said glazing.

14. A method of centering a glazing upon a mounting bracket, said glazing having a surface with a periphery for receiving a spacer, said periphery including a glazing edge, the method comprising:

*providing a glazing that has a spacer on at least a portion of its periphery, said spacer having a lip portion which extends beyond the glazing edge of said glazing and is initially oriented essentially parallel to said surface along said portion of said periphery; and*

*placing said glazing parallel to an edge of said mounting bracket and within said mounting bracket, whereby said lip portion of the spacer contacts said bracket to provide a force for centering said glazing thereon, which force is sufficient to maintain centering of the glazing on the bracket and to provide a gap between said glazing edge and the bracket along said portion of said periphery of the glazing.*

15. A method of centering a glazing upon a mounting bracket having opposed frame sections, said glazing having a glazing surface with a periphery for receiving a spacer, said periphery including opposed glazing edges, said method comprising:

*providing a glazing that has a spacer on at least a portion of its periphery adjacent each of said opposed glazing edges, said spacer having a lip portion which extends beyond the glazing edge and is initially oriented essentially parallel to said surface along said portion of said periphery; and*

*placing said glazing within said mounting bracket with said opposed glazing edges facing said opposed frame sections of said bracket, whereby said lip portion of each spacer contacts one of said opposed frame sections of said bracket to provide a force for centering said glazing thereon, which force is sufficient to maintain centering of the glazing on said bracket so as to provide a gap between the opposed glazing edges and the opposed frame sections of said bracket.*

16. The method of claim 15 wherein the contacting of the lip portion of each spacer with the opposed frame section of said bracket includes resiliently bending the lip portion as said glazing is placed within said bracket to provide said force for centering said glazing.

\* \* \* \* \*