



US00RE38927E

(19) **United States**  
(12) **Reissued Patent**  
**Martwick**

(10) **Patent Number:** **US RE38,927 E**  
(45) **Date of Reissued Patent:** **\*Dec. 27, 2005**

(54) **SYSTEM MANAGEMENT MEMORY FOR  
SYSTEM MANAGEMENT INTERRUPT  
HANDLER INDEPENDENT OF BIOS AND  
OPERATING SYSTEM**

5,307,482 A \* 4/1994 Bealkowski et al. .... 714/30  
5,896,534 A \* 4/1999 Pearce et al. .... 710/17  
5,954,812 A \* 9/1999 Shiell et al. .... 712/39  
6,145,048 A \* 11/2000 Klein .... 710/264  
6,463,492 B1 \* 10/2002 Engfer et al. .... 710/260

(75) Inventor: **Andrew W. Martwick**, Folsom, CA  
(US)

#### FOREIGN PATENT DOCUMENTS

(73) Assignee: **Intel Corporation**, Santa Clara, CA  
(US)

DE 2136762 \* 7/1971 ..... G06F/9/18  
EP 0 617 367 A2 \* 9/1994 ..... G06F/13/24

(\*) Notice: This patent is subject to a terminal disclaimer.

\* cited by examiner

(21) Appl. No.: **10/742,693**

*Primary Examiner*—Glenn A. Auve

(22) Filed: **Dec. 19, 2003**

(74) *Attorney, Agent, or Firm*—Jeffrey B. Huter

#### (57) **ABSTRACT**

#### Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,418,498**  
Issued: **Jul. 9, 2002**  
Appl. No.: **09/475,726**  
Filed: **Dec. 30, 1999**

(51) **Int. Cl.**<sup>7</sup> ..... **G06F 9/48**  
(52) **U.S. Cl.** ..... **710/269**  
(58) **Field of Search** ..... 710/260, 261,  
710/267, 269


A memory controller with an integrated system management memory region is disclosed. The memory controller receives an SMI acknowledge signal from a processor. The processor then delivers a system management memory address to the memory controller. Instead of fetching SMI handler instructions from the address indicated by the processor, the memory controller instead fetches SMI handler instructions from its integrated system management memory region. At the end of the integrated system management memory's SMI handler, the processor is instructed to fetch instructions from the address originally specified by the processor. In this manner, a BIOS SMI routine may be executed after the integrated SMI routine is executed.

#### (56) **References Cited**

##### U.S. PATENT DOCUMENTS

5,263,168 A \* 11/1993 Toms et al. .... 713/1

**34 Claims, 3 Drawing Sheets**






Figure 1




Figure 2




Figure 3



1

# SYSTEM MANAGEMENT MEMORY FOR SYSTEM MANAGEMENT INTERRUPT HANDLER INDEPENDENT OF BIOS AND OPERATING SYSTEM

Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

## FIELD OF THE INVENTION

The present invention pertains to the field of computer systems. More particularly, this invention pertains to the field of integrating a system management memory into a memory controller for a system management interrupt handler that is independent of both BIOS and operating system.

## BACKGROUND OF THE INVENTION

A large majority of today's personal computer systems implement a system management interrupt (SMI). An SMI signal is asserted to a processor to alert the processor that an SMI event has occurred. The SMI signal is typically asserted to the processor by a system logic device that includes a memory controller. The system logic device may assert the SMI signal for any of a large number of possible reasons. For example, the SMI signal may be asserted if a system resource seeks access to a certain range of memory or to a particular input/output address. These memory and input/output addresses can be programmable via a set of registers that typically reside in the system logic device. The SMI signal may also be asserted if certain system events occur. For example, a computer system may be implemented with a variety of timers for timing a variety of system events. The SMI signal may be asserted if any of these timers expire.

An assertion of the SMI signal indicates to the processor that the processor should begin to fetch instructions from an address stored in one of the processor's registers. This register is sometimes referred to as the system management memory base address register. The memory space located at the address indicated by the system management memory base address register may be referred to as system management memory (SMM). The SMM has stored therein an SMI handler routine. The SMI handler may be implemented to perform any of a wide variety of functions. For example, the SMI handler may perform power management functions, or may try to correct system malfunctions.

The SMM, and therefore the SMI handler, is under control of the computer system's Basic Input/Output System (BIOS). The BIOS is typically designed and implemented by one of several BIOS software companies. The SMI handler is typically installed in the computer system during the system manufacturing process.

Often, there is a need to make changes to the SMI handler after the manufacturing process. One such situation can occur when a chipset manufacturer desires to provide a solution for an erratum or desires to either enable new features or disable old features. These desires can be met by altering the SMI handler. However, a chipset manufacturer's product may be utilized in computer systems built by dozens of different computer system manufacturers. Further, these system manufacturers typically use any of a number of BIOS software companies to design and implement the SMI handler. Therefore, if the chipset manufacturer needs to have the SMI handlers modified, it must negotiate with many different parties to have the changes made. The chipset manufacturer may also try to negotiate with operating sys-

2

tem vendors to have the operating systems implement the chipset manufacturer's requests. Neither of these alternatives is desirable, in large part to the large amount of time and effort required to perform the negotiations and to implement the chipset manufacture's requests.

## BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be understood more fully from the detailed description given below and from the accompanying drawings of embodiments of the invention which, however, should not be taken to limit the invention to the specific embodiments described, but are for explanation and understanding only.

FIG. 1 is a block diagram of a computer system including one embodiment of a memory controller implemented in accordance with the invention.

FIG. 2 is a flow diagram of an embodiment of a method for utilizing an integrated system management memory region.

FIG. 3 is a flow diagram of an embodiment of an additional method for utilizing a system management memory integrated into a memory controller.

## DETAILED DESCRIPTION

An embodiment of a memory controller with an integrated system management memory region will be described. The memory controller receives an SML acknowledge signal from a processor. The processor then delivers a system management memory address to the memory controller. Instead of fetching SMI handler instructions from the address indicated by the processor, the memory controller instead fetches SMI handler instructions from its integrated system management memory region. At the end of the integrated system management memory's SMI handler, the processor is instructed to fetch instructions from the address originally specified by the processor. In this manner, a BIOS SMI routine may be executed after the integrated SMI routine is executed. The integrated system management memory region allows chipset or other system component manufacturers to distribute proprietary SMI routines without the need to involve BIOS or operating system vendors. The proprietary SMI routines may be utilized for any purpose that can be accomplished via a software routine, including, but not limited to, providing solutions for errata or enabling or disabling system or chipset features.

FIG. 1 is a block diagram of a computer system **100** that includes a processor **110** coupled to a memory controller **120**. The system **100** also includes a system main memory **150** that is also coupled to the memory controller **120**.

The memory controller **120** includes a host interface unit **122** that facilitates communication with the processor **110**. When an SMI event occurs, the host unit asserts a system management interrupt signal **111** to the processor **110**. Systems may be implemented with a wide variety of SMI events, including, but not limited to, power management functions and accesses to particular regions of memory. The term "SMI event" as used herein is meant to indicate a broad range of computer system activities that computer system designers may wish to implement as activities that trigger the execution of a system management interrupt handler routine.

After the processor **110** receives the system management interrupt signal **111**, the processor returns a system management interrupt acknowledge signal **113** to the memory controller **120**. The processor **110** also delivers a fetch



## 3

address to the memory controller via a host bus **115**. The fetch address delivered by the processor **110** corresponds to an address stored in a system management memory base address register in the processor (not shown). The address stored in the system management memory base address register indicates where in memory space BIOS system management memory resides.

The fetch address delivered by the processor **110** over the host bus **115** is latched by a latch **134** that is located in a system management interrupt address decode unit **130**. The fetch address is delivered to the latch **134** via an address path **121** that couples the host unit **122** with other units in the memory controller **120**. Once the fetch address is latched in the latch **134**, a set signal **131** is delivered to a flip-flop **135**. The set signal **131** causes an select signal **137** to be asserted. The select signal **137** indicates to a decoder **132** to fetch the SMI handler routine from a system management memory **124** that is integrated into the memory controller **120**. The decoder fetches SMI handler instructions from the system management memory **124**, and the instructions are delivered to the processor **110**. The processor **110** executes the delivered SMI handler instructions.

The SMI handler routine stored in the system management memory **124** includes at the conclusion of the routine an instruction that tells the processor **110** to jump to the address stored in the latch **134**. A compare unit **136** receives addresses delivered by the processor **110** to the host interface unit **122** over the address path **121**. The compare unit **136** compares the received addresses with the contents of the latch **134**. A match between a newly received address and the contents of the latch **134** indicates that the SMI routine stored in the system management memory **124** has been completely executed and that the processor **110** is now attempting to access the SMI routine stored at the address originally specified in the processor's system management memory base address register. When a match is found, the compare unit **136** delivers a reset signal **133** to the flip-flop **135**. The reset signal **133** results in the selected signal **137** being deasserted. The decoder **132** will then fetch instructions from the SMM space pointed to by the matched address.

The SMM space originally pointed to by the address stored in the processor's system management memory base address register may reside in a BIOS system management memory space **152** that is located in the system main memory **150**. The decoder **132** accesses the BIOS system management memory space **152** via a system main memory interface **126**.

The status of a BIOS SMI enable register **138** determines whether the SMI routine stored in BIOS system management memory space **152** will be executed following the execution of the SMI routine stored in the system management memory **124**. The BIOS SMI enable register **138** communicates its status to the decoder **132** via an enable signal **139**.

Another embodiment of the memory controller **130** may include an enable register that when cleared would prevent the integrated SMI routine from executing. Setting this register would allow the integrated SMI handler routine to execute as described above.

FIG. **2** is a flow diagram of a method for executing an SMI handler routine stored in an integrated system management memory. At step **210**, a system management interrupt acknowledge signal is received from a processor. At step **220**, system management interrupt handler instructions are fetched from a system management memory integrated into

## 4

a memory controller. The instruction fetch from the integrated system management memory is in response to the receipt of the system management interrupt acknowledge signal at step **210**.

FIG. **3** is a flow diagram of an additional embodiment of a method for executing an SMI handler stored in a system management memory integrated into a memory controller. At step **310**, a system management interrupt acknowledge signal is received from a processor. Following step **310**, a system management memory address delivered by the processor is latched at step **320**. A system management interrupt handler instruction is then fetched from an integrated system management memory at step **330**. The fetch is from the integrated memory regardless of what address was specified by the processor. At step **340** the processor executes the fetched instruction.

At step **350** a compare operation is performed to determine whether an address newly delivered by the processor matches the address previously latched at step **320**. If the addresses do not match, then the process flow returns to step **330**. If, however, the addresses do match, then at step **360** a system management interrupt handler is fetched from a BIOS controlled area of system memory.

Although the example embodiments described above discuss the system management memory regions as being integrated into a memory controller, other embodiments are possible with the system management memory region located elsewhere. Having a system management memory region that is physically separate from the BIOS controlled system management memory region and also separate from system main memory has a benefit in that neither the BIOS nor any other operating system or program can inadvertently overwrite the system management memory.

In the foregoing specification the invention has been described with reference to specific exemplary embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention as set forth in the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than in a restrictive sense.

What is claimed is:

1. An apparatus, comprising:

an integrated system management memory region; and  
a system management interrupt address decode unit to fetch instructions from the integrated system management memory region in response to a system management interrupt acknowledge signal asserted by a processor, the system management interrupt decode unit to fetch instructions from the integrated system management memory region regardless of a system management interrupt address received from the processor.

2. The apparatus of claim 1, the system management interrupt address decode unit to latch the system management interrupt address received from the processor.

3. The apparatus of claim 2, wherein the system management interrupt address is the first address received following the assertion of the system management interrupt acknowledge signal by the processor.

4. The apparatus of claim 3, wherein the system management interrupt address decode unit includes a compare unit to compare a plurality of addresses received from the processor with the latched system management interrupt address.

5. The apparatus of claim 4, the system management interrupt address decode unit to fetch system management



5

interrupt handler instructions stored in a system main memory in response to the compare unit finding a match between the latched system management interrupt address and one of the plurality of addresses received from the processor.

6. The apparatus of claim 5, wherein the system management interrupt handler instructions stored in the system main memory are part of a basis input/output system (BIOS).

7. The apparatus of claim 6, wherein the integrated system management memory region is at least 128 bytes in size.

8. A method, comprising:

receiving a system management interrupt acknowledge signal from a processor; and

fetching a plurality of system management interrupt handler instructions from an integrated system management memory in a memory controller regardless of a system management memory address indicated by the processor in response to the system management interrupt acknowledge signal.

9. The method of claim 8, further comprising latching the system management memory address indicated by the processor.

10. The method of claim 9, wherein latching the system management memory address includes latching a first address delivered by the processor following receiving the system management interrupt acknowledge signal.

11. The method of claim 10, further comprising comparing a plurality of addresses received from the processor with the latched address.

12. The method of claim 11, further comprising fetching a plurality of system management interrupt handler instructions from a section of BIOS code in a system main memory if comparing a plurality of addresses received from the processor with the latched address results in a match.

13. A system, comprising:

a processor;

a system main memory; and

a memory controller coupled between the processor and the system main memory, the memory controller including

an integrated system management memory region, and a system management interrupt address decode unit to fetch instructions from the integrated system management memory region in response to a system management interrupt acknowledge signal asserted by the processor, the system management interrupt decode unit to fetch instructions from the integrated system management memory region regardless of a system management interrupt address received from the processor.

14. The system of claim 13, the system management interrupt address decode unit to latch the system management interrupt address received from the processor.

15. The system of claim 14, wherein the system management interrupt address is the first address received by the memory controller following the assertion of the system management interrupt acknowledge signal by the processor.

16. The system of claim 15, wherein the system management interrupt address decode unit includes a compare unit to compare a plurality of addresses received from the processor with the latched system management interrupt address.

17. The system of claim 16, the system management interrupt address decode unit to fetch system management interrupt handler instructions stored in the system main memory in response to the compare unit finding a match between the latched system management interrupt address and one of the plurality of addresses received from the processor.

6

18. The system of claim 17, wherein the system management interrupt handler instructions stored in the system main memory are part of a basis input/output system (BIOS).

19. The system of claim 18, wherein the integrated system management memory region is at least 128 bytes in size.

20. An apparatus, comprising:

a system management memory; and

a system management interrupt address decode unit to fetch instructions from the system management memory in response to a system management interrupt acknowledge signal asserted by a processor, the system management interrupt decode unit to fetch instructions from the system management memory regardless of a system management interrupt address received from the processor.

21. The apparatus of claim 20, the system management interrupt address decode unit to latch the system management interrupt address received from the processor.

22. The apparatus of claim 21, wherein the system management interrupt address is the first address received following the assertion of the system management interrupt acknowledge signal by the processor.

23. The apparatus of claim 22, wherein the system management interrupt address decode unit includes a compare unit to compare a plurality of addresses received from the processor with the latched system management interrupt address.

24. The apparatus of claim 23, wherein the system management interrupt address decode unit fetches system management interrupt handler instructions stored in a system main memory in response to the compare unit finding a match between the latched system management interrupt address and one of the plurality of addresses received from the processor.

25. The apparatus of claim 24, wherein the system management interrupt handler instructions stored in the system main memory are part of a basic input/output system (BIOS).

26. A method, comprising:

receiving a system management interrupt acknowledge signal from a processor; and

in response to the system management interrupt acknowledge signal, fetching a plurality of system management interrupt handler instructions from a system management memory instead fetching a plurality of system management interrupt handler instructions of a basic input/output system (BIOS) identified by a system management memory address regardless of the system management memory address indicated by the processor.

27. The method of claim 26, further comprising latching the system management memory address indicated by the processor.

28. The method of claim 27, further comprising comparing a plurality of addresses received from the processor with the latched address, and fetching a plurality of system management interrupt handler instructions from the BIOS in response to the latched address matching an address of the a plurality of addresses received from the processor.

29. The method of claim 26, further comprising fetching a plurality of system management interrupt handler instructions from the BIOS in response to the system management memory address matching an address of another system management memory address previously received from the processor.



7

30. A system, comprising:  
 a processor;  
 a system management memory,  
 a basic input/output system, and  
 a system management interrupt address decode unit to  
 fetch instructions from the system management memory  
 in response to a system management interrupt acknowl-  
 edge signal asserted by the processor, the system man-  
 agement interrupt address decode unit to fetch instruc-  
 tions from the system management memory instead of  
 fetching instructions of the basic input/output system  
 identified by a system management interrupt address  
 regardless of a system management interrupt address  
 received from the processor.  
 31. The system of claim 30, the system management  
 interrupt address decode unit to latch the system manage-  
 ment interrupt address received from the processor.

8

32. The system of claim 31, wherein the system manage-  
 ment interrupt address is the first received address received  
 by the system management interrupt decode unit following  
 the assertion of the system management interrupt acknowl-  
 edge signal by the processor.  
 33. The system of claim 32, wherein the system manage-  
 ment interrupt address decode unit includes a compare unit  
 to compare a plurality of addresses received from the  
 processor with the latched system management interrupt  
 address.  
 34. The system of claim 33, wherein the system manage-  
 ment interrupt address decode unit fetches system manage-  
 ment interrupt handler instructions of the BIOS in response  
 to the compare unit finding a match between the latched  
 system management interrupt address and one of the plu-  
 rality of addresses received from the processor.

\* \* \* \* \*