

US00RE38952E

(19) **United States**
(12) **Reissued Patent**
Hale et al.

(10) **Patent Number:** **US RE38,952 E**
(45) **Date of Reissued Patent:** **Jan. 31, 2006**

(54) **HEAT ACTIVATED INK JET INK**

3,977,828 A 8/1976 Becker et al.

(76) Inventors: **Nathan S. Hale**, 427 Rice Hope Dr.,
Mt. Pleasant, SC (US) 29464; **Ming**
Xu, 2808 Gaston Gate, Mt. Pleasant,
SC (US) 29466

(Continued)

FOREIGN PATENT DOCUMENTS

DE 2 633260 7/1976
EP 87303687.5 11/1987

(21) Appl. No.: **10/195,922**

(Continued)

(22) Filed: **Jul. 15, 2002**

OTHER PUBLICATIONS

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **5,830,263**
Issued: **Nov. 3, 1998**
Appl. No.: **08/807,964**
Filed: **Feb. 28, 1997**

Wolfgang Gerhartz, Ullmann's Encyclopedia of Industrial
Chemistry, 1987, pp. 565, 573-574, 577-601, vol. A 8; VCH
Publishers, Inc., New York, NY, no month available.

(Continued)

Primary Examiner—Helene Klemanski
(74) *Attorney, Agent, or Firm*—B. Craig Killough

U.S. Applications:

(60) Division of application No. 08/710,171, filed on Sep. 12,
1996, now Pat. No. 5,640,180, which is a continuation-in-
part of application No. 08/695,121, filed on Aug. 5, 1996,
now Pat. No. 5,642,141, which is a continuation-in-part of
application No. 08/565,999, filed on Dec. 1, 1995, now Pat.
No. 5,601,023, which is a continuation-in-part of application
No. 08/207,756, filed on Mar. 8, 1994, now Pat. No. 5,487,
614, and a continuation-in-part of application No. 08/506,
894, filed on Jul. 25, 1995, now Pat. No. 5,734,396, which
is a continuation-in-part of application No. 08/299,736, filed
on Sep. 1, 1994, now Pat. No. 5,488,907.

(57) **ABSTRACT**

[A method of printing a liquid ink which is produced from
a heat activated dye which is selected from a limited group
of dyes which are capable of transfer at low energy. A printer
which uses liquid ink, such as an ink jet printer, prints an
image onto an intermediate substrate medium. The dyes
contained in the ink are not substantially activated during the
process of printing on to the medium. The image formed by
the printed ink is transferred from the medium to a final
substrate by the application of heat and pressure for a short
period of time to activate the ink. The dye and dispersing/
emulsifying agent(s) are selected from a limited group to
produce an ink which permits thermal transfer at low energy,
with the resulting image, as deposited on the final substrate,
having an optical density of 1.0 or greater.] *Liquid ink is
produced using heat activated dyes selected from a limited
group of dyes that are capable of heat activation. The dyes
are not substantially soluble in the liquid carrier, such as
water. One or more emulsifying agents stabilize the ink
formulation. A printer that uses liquid ink, such as an ink jet
printer, is used to print the ink, and the dye is heat activated
after printing.*

(51) **Int. Cl.**
C09D 11/02 (2006.01)

(52) **U.S. Cl.** **106/31.27; 106/31.33;**
106/31.35

(58) **Field of Classification Search** 106/31.27,
106/31.33, 31.35


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,844,806 A 10/1974 Wegmann et al.
3,948,828 A 4/1976 Becker et al.
3,969,302 A 7/1976 Wegmann et al.

14 Claims, 2 Drawing Sheets



U.S. PATENT DOCUMENTS

4,042,320 A 8/1977 Becker et al.
4,079,026 A 3/1978 Mone
4,205,991 A 6/1980 Becker et al.
4,207,067 A 6/1980 Becker et al.
4,265,630 A * 5/1981 Bauerle
4,265,631 A 5/1981 Becker
4,281,999 A 8/1981 Becker et al.
4,370,144 A 1/1983 Skepley et al.
4,422,854 A * 12/1983 Hahnle et al.
4,436,522 A 3/1984 Niwa et al.
4,460,374 A 7/1984 Abel et al.
4,559,150 A 12/1985 Becker et al.
4,689,078 A 8/1987 Koike et al.
4,692,188 A 9/1987 Ober et al.
4,713,081 A 12/1987 Becker
4,725,849 A 2/1988 Koike et al.
4,969,951 A 11/1990 Koike et al.
5,028,262 A * 7/1991 Barlow, Jr. et al.
5,102,448 A 4/1992 Parton et al.
5,164,232 A 11/1992 Henseleit et al.
5,175,566 A 12/1992 Ejiriet et al.
5,229,786 A 7/1993 Suga et al.
5,250,121 A 10/1993 Yamamoto et al.
5,281,261 A 1/1994 Lin
5,643,387 A 7/1997 Berghauser et al.
5,645,888 A 7/1997 Titterington et al.
5,746,816 A * 5/1998 Xu 106/31.25
6,105,502 A * 8/2000 Wagner et al. 101/491
6,123,758 A * 9/2000 Colt 106/31.43

FOREIGN PATENT DOCUMENTS



EP 0 506 395 9/1992
EP 93309425.2 6/1994
EP 0 606 490 7/1994
EP 94103892.9 9/1994
EP 0 633 347 1/1995
EP 95115241.2 4/1996
GB 1527396 10/1978
GB 2105735 A 3/1983
GB 2189436 10/1987
JP 60-8959 3/1985
JP 60-42317 9/1985
JP 61-118477 6/1986
JP 62-57750 12/1987


JP 2-189373 7/1990
JP 05-255626 10/1993
WO WO 92/00852 1/1992
WO WO 95/21739 8/1995
WO PCT/NL 97/426 1/1998
WO PCT/US99/09387 11/1999

OTHER PUBLICATIONS

Amiga Magazine, 1992, p. 14, Compedo Spezialfarbbänder GmbH, Postfach 1352, no month available.
Nicholas L. Moore, Heat-transfer Printing, J. Soc. Dyers and Colourists, pp. 318-325, Watford College of Technology, Watford; Sep. 1974.
Rompps Chemie-Lexikon, 8. Aufl., Franckhsche Verlagshandlung Stuttgart, 1981, pp. 986, 987, 1126, 1127, no month available.
Hermann Rath, Lehrbuch der Textilchemie, 1972, Springer Verlag, Berlin-Heidelberg, p. 725, New York, NY, no month available.
AF Encyclopedia of Textiles, p. 472, 2nd Edition, Doric Publishing Company, Mar. 1973.
PCM, pp. 145, 147, Aug. 1992.
Lies Muller, PC-Active, No. 42, 1992, pp. 42, 43, no month available.
AMIGA Special, 1991, p. 40, No. 3/91, Compedo Pennekamp-Dorsch GbR, Postfach 1352, 5860 Iserlohn, no month available.
PC Praxis, 1994, p. 48, no month available.
AMIGA Advertisement, Compedo Spezialfarbbänder GMB, Sep. 1993.
Drew Myers, Surfactant Science and Technology, 1946, pp. 60, 61, VCH Publishers, Inc., New York, NY, no month available.
Lesley Brown, The New Shorter Oxford English Dictionary on Historical Principles, 1993, pp. 961, 962, vol. 1, A-M, Oxford University Press, Inc., New York, NY, no month available.
Borregaard Ligno Tech, Dyestuffs, Web Page, no date available.
BYK Chemie, Disperbyk, Web Page, no date available.

* cited by examiner

**FIG 1**



HEAT ACTIVATED INK JET INK

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

This application is a divisional of U.S. Ser. No. 08/710,171, filed Sep. 12, 1996, now U.S. Pat. No. 5,640,180, which is a continuation-in-part of U.S. Ser. No. 08/695,121, filed Aug. 5, 1996, now U.S. Pat. No. 5,642,141, which is a continuation-in-part of U.S. Ser. No. 08/565,999, filed Dec. 1, 1995, now U.S. Pat. No. 5,601,023, which is a continuation-in-part of U.S. Ser. No. 08/207,756, filed Mar. 8, 1994, now U.S. Pat. No. 5,487,614, and a continuation-in-part of U.S. Ser. No. 08/506,894, filed Jul. 25, 1995, which is a continuation-in-part of U.S. Ser. No. 08/299,736, filed Sep. 1, 1994, now U.S. Pat. No. 5,488,907.

FIELD OF THE INVENTION

[This invention relates to printing heat sensitive, dye diffusion or sublimation inks generally, and is more specifically related to a method of printing inks comprising these dyes onto an intermediate transfer sheet by means of an ink jet printer or other printer which uses liquid inks, and subsequently transferring the printed image from the intermediate sheet by the application of heat and pressure.]

This invention relates to printing heat sensitive dye diffusion or sublimation inks, generally and is more specifically related to a liquid ink comprising these dyes which may be used in an ink jet printer.

BACKGROUND OF THE INVENTION

Words and designs are frequently printed onto clothing and other textile materials, and other objects. The use of computer technology allows substantially instantaneous printing of images. For example, video cameras or scanning may be used to capture an image to a computer. The image may then be printed by any suitable printing means, including mechanical thermal printers, ink jet printers and laser printers. These printers will print multiple color images.

Color ink jet printers are in common use. Color ink jet printers use combinations of cyan, yellow and magenta inks or dyes to produce multiple color images. Most ink jet printers in common use employ inks which are in liquid form.

Heat activated, dye diffusion and sublimation ink solids change to a gas at about 400° F., and have a high affinity for polyester and other synthetic materials at the activation temperature, and a limited affinity for most other materials. Once the bonding from gassification and condensation takes place, the ink is permanently printed, and is resistant to change or fading caused by laundry products, heat or light.

Hale, U.S. Pat. Nos. 5,246,518, 5,248,363, 5,302,223, and 5,485,614 and Hale et al., U.S. Pat. No. 5,488,907, disclose the use of printers to produce an image on a medium or transfer sheet wherein the image is comprised of sublimation, dye diffusion or other heat activated inks. The ink is not activated during the printing of the medium or transfer sheet.

Problems are associated with liquid inks prepared from insoluble dye solids. The orifices or nozzles of most ink jet printers are not designed for the dispensing of dye solids contained within a liquid material. The orifices of these printers are typically 5–30 microns in diameter, and clogging of the orifice will occur when ink solids of large particle size or in high volume or transferred through the orifice.

Further, when the ink solids are placed into a liquid carrier, the ink solids tend to separate from the liquid over time and fall to the bottom of the ink container. The ink is typically packaged in a container at a manufacturing facility for subsequent mounting of the container within the ink Jet printer, meaning that a substantial storage time for the ink composition exists prior to use. Separation of the liquid and solids comprising the ink formulation presents problems with regard to the mechanical operation of the printer and the print quality achieved from the use of the ink formulation. Agents which are included within the ink formulation to inhibit separation must also inhibit agglomeration of the solid dye particles, but the agents must not inhibit activation of the dye during the final transfer at elevated temperatures, by insulating the dye or reacting with the dye, or otherwise.

Accordingly, the production of stable liquid inks from dyes which are not water soluble is difficult to achieve without destroying or reducing the properties of the dye which are required for practicing the process of the invention. In the prior art, liquid inks have been produced from dyes that initially have properties suitable for practicing the process. However, the production of liquid inks from these dyes changes or masks the required properties, and therefore, the resulting inks cannot be satisfactorily used to practice the process. For example, additives which will inhibit the dye particles from settling out of the liquid carrier, or which will inhibit agglomeration, tend to insulate the dye particles, meaning that the energy required for sublimation, diffusion or activation of the dye is elevated to unacceptable levels for practicing the process. Other additives which are used in the prior art to produce a liquid ink from the solid dyes are reactive with the dye, and modify or eliminate required properties of the dyes. Other “side effects” of using these additives include undesired color modification or contamination, bonding with the intermediate substrate, or optical density on the final substrate which is inadequate.

While certain solvents will dissolve the dyes, the requirements of the process makes the use of these solvents impractical. Dye materials solubilized to the molecular level have a tendency to bond with fibers, both synthetic and natural. Accordingly, the dyes cannot be effectively transferred from a substrate used as an intermediate transfer sheet by the application of heat and pressure as required by the process of the present invention.

SUMMARY OF THE PRESENT INVENTION

This invention is a [method of printing] liquid ink which is produced from sublimation, dye diffusion, or heat sensitive dyes. A printer that uses liquid ink, such as an ink jet printer, prints the image onto a medium, or intermediate substrate, which may be paper. The sublimation, dye diffusion, or heat sensitive dyes (hereinafter collectively referred to as “heat activated dyes”) contained in the ink are not substantially sublimated or activated during the process of printing on to the medium. The image formed by the printed ink is transferred from the medium to a final substrate by the application of heat and pressure which sublimates or activate the ink. This thermal transfer step is achieved at low energy when compared to other sublimation or activation processes known and used in the art. One of the goals of the process requires that the thermal transfer occur by applying heat and pressure for no more than three and one-half minutes, and preferably less time. In the prior art, heat at the activation temperature is applied for up to thirty minutes. Accordingly, as used herein, a low energy transfer is a thermal transfer of the image from the intermediate sheet

3

to the final substrate by applying a temperature which is not higher than 450° F., for no more than three and one-half minutes, with the resulting image, as deposited on the final substrate, having an optical density of 1.0 or greater, as measured by an X-Rite 418 densitometer in the density operation mode with background corrections.

The dyes, or perhaps pigments, which are suitable for practicing the invention are dyes which are capable of low energy transfer from the medium onto the final substrate to produce an image on the final substrate which is waterfast and colorfast. After transfer, the dyes are no longer substantially heat sensitive. Dyes which have these characteristics are found in various classifications of dyes, including disperse dyes, solvent dyes, basic dyes, acid dyes and vat dyes. However, none of the dyes which are currently available and which are suitable for producing a liquid ink for practicing the invention are soluble in water.

Accordingly, only a relatively small range of dyes in combination with a relatively small range of dispersing/emulsifying agents will produce a stable liquid ink which will allow the printing method to be practiced. Characteristics of acceptable dyes and dispersing/emulsifying agents which will produce a liquid ink with which to practice the printing method are disclosed herein.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram showing the printing process.

FIG. 2 illustrates an example of a design printed by a printer using the printing process.

FIG. 3 is a diagrammatic illustration showing exemplary elements of computer and printing systems which could be used to achieve the printing process.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

An image is input into a computer 4. The computer directs a printer 6 to print the image. Any means of forming an image which may be printed from a computer may be used, including images generated by software. Available computer design graphic software may be used, or still photography may be used. The design may be read and communicated by a scanner 2, which is connected to computer 4. The design may be photographic, graphic artistic, or simply letters or words. The use of cyan, yellow and magenta ink compositions allow the printer to print in full color or multi-color designs.

After the image is printed onto the medium, the image may be permanently transferred by thermal means. Most commonly, the design will be transferred onto a textile substrate, such as a shirt 8, although the image may be transferred onto other materials which act as a substrate, such as metal, ceramic, wood, or plastic. The design 3, which is printed onto the medium 9 without activating the ink, is placed against the final substrate which may be a shirt 8. A temperature which is sufficient to activate the dye is applied. This temperature will typically be around 400° F. This temperature is applied for a time sufficient to heat activate and transfer the ink solids in accordance with the requirements of the invention. A heat transfer machine 10 may be used to accomplish the transfer of the inks from the medium to the substrate. Activation, or sublimation, of the dye does not take place at the time of printing the image onto the medium, but occurs during the transfer from the medium to the substrate. The group of heat activated dyes from which dyes may be selected for use in the invention are dyes which

4

substantially sublimate or activate at low energy to form an image which has an optical density value of no less than 1.0, and which is waterfast and colorfast. Each of the dyes which comprise this group will achieve an optical density of 1.25 or greater after activation, when optical density is measured by an X-Rite 418 densitometer in the density operation mode with background correction.

The invention requires the dyes to be transferred at low energy (as defined above) after the dyes are formulated into a liquid ink as described herein and printed onto the medium (the "acceptable dyes"). While a larger group of dyes can be sublimated at low energy, dyes which are not acceptable cannot be formulated into a liquid ink which retains the required properties. While most of the acceptable dyes are disperse dyes, certain other dyes which will perform according to the goals of the invention are included in the group of acceptable dyes.

In general, the acceptable dyes are not reactive, and do not have strong polar function groups, such as sulfonate or carboxyl groups. Reacting the dyes with chemical agents added to the formulation in order to form a liquid ink, as is sometimes done in the prior art, tends to inhibit the activation of the dyes at low energy, which is contrary to the present invention. The acceptable dyes have a molecular weight which is less than 600, and is preferably within a range of 200–400. Most of the acceptable dyes are disperse dyes but certain solvent dyes, vat dyes, basic or cationic dyes (such as carbinol base dyes or anthraquinone type dyes having a quarternary amine), acid dyes, direct dyes, mordant dyes and oxidizing colors also fall within the group of acceptable dyes.

The ink formulation prepared according to the invention is a liquid. Dye solids of small particle size are dispersed in a liquid carrier, and one or more agents are used to maintain what may be called, according to various definitions, a colloidal, dispersion or emulsion system. The term "emulsion" is used herein to describe the system, even though the system could, in some forms, be called a colloid or a dispersion.

The heat activated solid dye particles are of small size. It is preferred that the individual solid dye particles have no dimension which is greater than 0.5 microns.

The solid dye particles are dispersed into the liquid carrier. The dispersion is normally achieved by the introduction of a dispersing agent, although mechanical or other physical means could be used. An emulsifying agent is introduced to prevent coagulation or coalescence of the individual dye particles and to stabilize the system.

As set forth in the examples, a single agent may be used as a dispersing and emulsifying agent. Multiple agents may be used in accordance with the goals of the invention. The agent or agents stabilize the system, so that the system remains sufficiently homogenous over time to allow successful printing and transfer of the dye according to the method of the invention. Further, the agent shields the individual particles from the adverse effects of the storage, transportation and printer environments, such as heat, cold and light. While the agent shields the dye particles while they are in the liquid system, it does not inhibit low energy transfer of the dyes in the form of the printed image.

The agents used to disperse and/or emulsify the dye particles include various dispersant materials, surfactants (including cationic, anionic, amphoteric, and nonionic surfactants) and polymeric surfactants. Polymeric materials with dispersing ability, but which are not surfactants, can also be used. Either synthetic or natural materials can be

5

used. The dispersing/emulsifying agents each have a molecular weight which is less than 100,000, and preferably less than 10,000. Thermal stability of the agents is essential to prevent decomposition and/or chemical reaction between the agents and the other components in the systems.

As with the dye, to accomplish the printing method of the invention, the agent(s) do not have active function groups which will react or crosslink with the medium, or which will react or crosslink with the dye or pigment in the system, since such reactions or linkages inhibit the required properties of the dye at the time of activation. The agent(s) must form the emulsion from the finely divided dye [particles] *particles* and the liquid carrier, but must not materially insulate or otherwise materially inhibit the activation of the dye at the time of final transfer.

Agents having the required properties when used with some or all of the acceptable dyes include Lignosulfonate products such as Marasperse 52CP (Lignotech), Lignosol FTA (Lignotech), Lignosol SFX-65 (Lignotech), Marasperse CBA-1 (Lignotech), Temsperser S002 (Temfibre, Inc.) Stepsperse DF series (Stephan Co.), and Weschem NA-4 (Wesco Technologies, LTD), Kraft lignin products such as Diwatex XP (Lignotech), and Reax 85 (Westvaco), and oxygignin products such as Marasperse CBOS-6 and Vanisperse CB.

Other examples of emulsifying agents and dispersants are alkylaryl polyether alcohol nonionic surfactants, such as Triton X series (Octylphenoxy-polyethoxyethanol); alkylamine ethoxylates nonionic surfactants such as Triton FW series, Triton CF-10, and Tergitol (Union Carbide Chemicals); polysorbate products such as Tween (ICI Chemicals and Polymers); polyalkylene and polyalkylene modified surfactants, such as Silwet surfactants (polydimethylsioxane copolymers) and CoatOSil surfactants from OSI Specialties; alcohol alkoxyates nonionic surfactants, such as Renex, BRII, and Ukanil; Sorbitan ester products such as Span and Arlacel; alkoxyated esters/PEG products, such as Tween, Atlas, Myrj and Cirrasol surfactants from ICI Chemicals and Polymers; unsaturated alcohol products such as surfynol series surfactants from Air Products Co., alkyl phosphoric acid ester surfactant products, such as amyl acid phosphate, Chemphos TR-421; alkyl amine oxide such as Chemoxide series from Chemron Corporation; anionic sarcosinate surfactants such as Hamposyl series from Hampshire Chemical corporation; glycerol esters or polyglycol ester nonionic surfactants such as Hodag series from Calgene Chemical, Alphenate (Henkel-Nopco), Solegal W (Hoechst AG), Emultex (Auschem SpA); and polyethylene glycol ether surfactants such as Newkalgen from Takemoto Oil and Fat Co.

Multiple agents may be used in combination to improve the emulsification of the system and to stabilize the system, as long as the agents are not reactive and do not cause precipitation or otherwise negatively impact upon the emulsification process or the transfer process.

Organic solvents, cosolvents, and/or humectants can also be used as additional additives. Aliphatic and/or aromatic alcohols (thioalcohols), alkoxyated alcohols (thioalcohols), halogenated alcohols (thioalcohols) and carboxylated alcohols (thioalcohols), including mono-alcohol (thioalcohol), diol (thiodialcohol), triol (thiotriolalcohol) and polyol (thiopolyalcohol), aminoxide, diamine, triamine material, may be used to improve dye dispersibility, solubility and/or stability in the final ink composition. Examples of solvent materials are diethylene glycol, DMSO and dipropylene glycol.

6

Other additives can also be introduced into the ink, such as surfactants, corrosion control agents, foam control agents, antioxidants, radiation stabilizers, thermal stabilizers, flame retarding agents, pH control agents, viscosity control agents, or surface (interfacial) tension control agents can be added during or after the emulsification process. Other materials, including dispersants, emulsifying agents, and stabilizers, may be included in the formulation by means of methods known in the art.

EXAMPLES

An example of a liquid ink composition usable in an ink jet printer is as follows:

Material	Weight %
heat sensitive dye(s)	0.05–20%
dispersant/emulsifying agent	0.05–30%
solvent(s)/cosolvent(s)	0–45%
additive(s)	0–15%
water	40–98%
Total	100%

The heat sensitive dye may be a red (magenta), blue (cyan), yellow or brown dye. The dispersant/emulsifying agent may be a sulfonated lignin such as Marasperse CBA-1. The additive(s) may be Tergitol 15-s-9, Triton X-165, Triton X-405 or Surfynol 465. The solvents and/or co-solvents may be diethylene glycol and/or thioglycol and/or 2-pyrrolidone and/or 1-methoxy 2-propanol.

Example A

30 grams of finely divided Spirit Blue Base (CAS# 68389-46-8) is mixed with 15 grams of Ultrazine NA (Lignotech, USA) and 500 grams of de-ionized water. An ultrasonic pulverizer is used to disperse the dye into the aqueous phase for approximately 30 minutes. Two (2.0) grams of Solsperser 27000 (Zenica Colors, USA) is added into the mixture, which is pulverized for another 10 minutes to achieve a stable emulsion. The mixture is filtered to remove particles larger than 0.25 microns. The printing ink for use in the ink jet printer is formulated from the emulsion as follows:

Material	Weight %
Emulsion	87.0
Glycol	4.0
1-methoxy,2-propanol	7.0
Ammonyx LO (1)	2.0
Total	100%

(1) Stepan Co

The resulting ink is printed by the HP 560 Deskjet printer onto plain copy paper in a dark cyan color, and is transferred from the paper medium or receiver onto a polyester fabric substrate by thermal transfer at 400° F. temperature with 40 lb. pressure applied for 20 seconds. The image as applied to the polyester fabric substrate has an optical density value of 1.4–1.5 for the cyan color as read by an X-Rite 418 densitometer.

Example B

Twenty (20) grams of Disperse Yellow 9 (CAS# 6373-73-5) is mixed with four (4) grams of Sulfynol 131 (Air

Products) and 5.0 grams of glycerol (CAS# 56-81-5) and 480 grams of de-ionized water. The pulverizer is used to disperse the dye into the aqueous phase for approximately 25 minutes. One (1.0) gram of Sulfynol 104 E (Air Products) is added to the mixture and pulverized for another 10 minutes to produce an emulsion. The mixture is filtered to remove particles larger than 0.25 microns. The liquid ink for use in the ink jet printer is formulated as follows:

Material	Weight %
Emulsion	78.5
Diethylene Glycol	8.0
Thiodiethanol	5.0
Sulfynol 465	4.0
1-2.Propandiol	4.0
DEA	0.5
Total	100%

The resulting liquid ink is printed by a Canon Bubble Jet 4100 printer onto plain copy paper. The printed image is thermally transferred from the paper medium to a polyester textile substrate at 400° F., while applying 40 lb. pressure for 20 seconds. An intense yellow color having an optical density of 1.4, as measured by an X-Rite 418 densitometer with background correction, appears on the substrate.

Example C

Twenty-five (25) grams of finely divided Solvent Red 52 (CAS# 81-390), is mixed with twenty-two (22) grams of Transferin® N-38 (Boehme Filatex, Inc.) and one hundred and fifty (150) grams of de-ionized water. An ultrasonic pulverizer is used to finely divide the dye and to disperse and micronize the solid dye particles into the aqueous phase by operating the pulverizer for approximately Forty-five (45) minutes. Five (5) grams of Tergitol™ 15-S-15 (Union Carbide, USA). Ten (10) grams of 1,4-butanediol, and two hundred and twenty (220) grams of de-ionized water are then added into the dispersion and pulverized for an additional ten (10) minutes. The dispersion is then filtered to remove solid particulate have a dimension which is larger than 0.25 microns. A liquid ink is formulated using the homogenized emulsion as follows:

Component	Weight %
Emulsion	85.0
Tergitol™ 15-S-9 ⁽¹⁾	3.997
1-pyrrolidinone	2.0
1-ethoxy-2-propanol	6.0
IPA	3.0
Kathon® PFM ⁽²⁾	0.003
Total	100%

⁽¹⁾Union Carbide, USA
⁽²⁾Rohm & Haas Company

The liquid ink is then printed by an Epson Stylus Color Pro or Epson Stylus Color IIs piezo electric ink jet printer to form an image on plain copy paper. The image is transferred from the paper to a polyester fabric substrate by the application of pressure and heat at a temperature of 400° F. for 25 seconds. The image as transferred has an optical density of 1.45 for the magenta color, as measured by an X-Rite 418 densitometer with background correction.

What is claimed is:

[1. A liquid ink for use in ink jet printers prepared from heat activated dye solids, comprising:

Material	Weight %
heat sensitive dye solid	0.05–20%
dispersant/emulsifying agent	0.05–30%
solvent	0–45%
water	40–98%
Total	100%

wherein the heat sensitive dye solid is not substantially insoluble in the water.]

[2. A liquid ink for use in ink jet printers prepared from heat activated dye solids, as described in claim 1, further comprising 0.01% to 15% surfactant.]

[3. A liquid ink for use in ink jet printers prepared from heat activated dye solids, as described in claim 1, wherein said dispersant/emulsifying agent is a sulfonated lignin.]

[4. A liquid ink for use in ink jet printers prepared from heat activated dye solids, as described in claim 2, wherein said dispersant/emulsifying agent is a sulfonated lignin.]

[5. A liquid ink for use in ink jet printers prepared from heat activated dye solids, as described in claim 1, wherein said heat activated dye is a dye which, after the liquid ink is printed, transfers by the application of heat at a temperature which is not higher than 450° F. for no more than three and one-half minutes, with the resulting image, as deposited on the final substrate having an optical density of 1.0 or greater, as measured by an X-Rite 418 densitometer in the density operation mode with background corrections.]

[6. A liquid ink for use in ink jet printers prepared from heat activated dye solids as described in claim 5, further comprising 0.01% to 15% surfactant.]

[7. A liquid ink for use in ink jet printers prepared from heat activated dye solids as described in claim 5, wherein said dispersant/emulsifying agent is a sulfonated lignin.]

[8. A liquid ink for use in ink jet printers prepared from heat activated dye solids as described in claim 6, wherein said dispersant/emulsifying agent is a sulfonated lignin.]

[9. A liquid ink for use in ink jet printers prepared from heat activated dye solids as described in claim 1, further comprising 0.01% to 45% solvent.]

[10. A liquid ink for use in ink jet printers prepared from heat activated dye solids as described in claim 5, further comprising 0.01% to 45% solvent.]

[11. A liquid ink for use in ink jet printers prepared from heat activated dye solids as described in claim 6, further comprising 0.01% to 45% solvent.]

[12. A liquid ink for use in ink jet printers prepared from heat activated dye solids as described in claim 7, further comprising 0.01% to 45% solvent.]

13. A liquid ink jet ink, comprising:

Material	Weight %
heat activated dye solids	0.05–20%
at least one dispersant and emulsifying agent	0.05–30%
solvent	0–45%
water	40–98%
Total	100%

wherein said heat activated dye solids are substantially insoluble in said water, and wherein said at least one dispersant and emulsifying agent inhibits agglomeration of individual particles of said heat activated dye solids within the liquid ink to limit a particle size of said individual particles of said heat activated dye solids within the liquid ink and sustain stability of the liquid ink, wherein said at least one dispersant and emulsifying agent does not materially increase an activation temperature of said heat activated dye solids.

14. A liquid ink jet ink as described in claim 13, further comprising 0.01% to 15% surfactant.

15. A liquid ink jet ink as described in claim 13, wherein said at least one dispersant and emulsifying agent is a sulfonated lignin.

16. A liquid ink jet ink as described in claim 13, wherein said heat activated dye is a dye which, after the liquid ink is printed, transfers by the application of heat at a temperature which is not higher than 450° F., for no more than three and one-half minutes, with the resulting image, as deposited on the final substrate, having an optical density of 1.0 or greater, as measured by an X-Rite 418 densitometer in the density operation mode with background corrections.

17. A liquid ink jet ink as described in claim 13, wherein said heat activated dye solids are finely divided.

18. A liquid ink jet ink as described in claim 13, wherein individual particles of said heat activated dye solids are 0.5 microns or less in size.

19. A liquid ink jet ink as described in claim 13, wherein said at least one dispersant and emulsifying agent comprises at least one dispersant and at least one emulsifying agent, and wherein said at least one emulsifying agent emulsifies said heat activated dye solids within the liquid ink.

20. A liquid ink jet ink, comprising:

Material	Weight %
heat activated dye solids	0.05–20%
at least one dispersant and emulsifying agent	0.05–30%
solvent	0–45%
water	40–98%
Total	100%

wherein the heat activated dye solids are substantially insoluble in the water, and wherein said at least one dispersant and emulsifying agent emulsifies said heat activated dye solids within the liquid ink.

21. A liquid ink jet ink as described in claim 20, further comprising 0.01% to 15% surfactant.

22. A liquid ink jet ink as described in claim 20, wherein said at least one dispersant and emulsifying agent is a sulfonated lignin.

23. A liquid ink jet ink as described in claim 20, wherein said heat activated dye is a dye which, after the liquid ink is printed, transfers by the application of heat at a temperature which is not higher than 450° F., for no more than three and one-half minutes, with the resulting image, as deposited on the final substrate, having an optical density of 1.0 or greater, as measured by an X-Rite 418 densitometer in the density operation mode with background corrections.

24. A liquid ink jet ink as described in claim 20, wherein said heat activated dye solids are finely divided.

25. A liquid ink jet ink as described in claim 20, wherein individual particles of said heat activated dye solids are 0.5 microns or less in size.

26. A liquid ink jet ink as described in claim 20, wherein said at least one dispersant and emulsifying agent comprises at least one dispersant and at least one emulsifying agent, and wherein said at least one emulsifying agent emulsifies said heat activated dye solids within the liquid ink.

* * * * *