



US00RE39304E

(19) **United States**
(12) **Reissued Patent**
Kasen et al.

(10) **Patent Number: US RE39,304 E**
(45) **Date of Reissued Patent: Sep. 26, 2006**

(54) **UPRIGHT EXTRACTION CLEANING MACHINE**

(75) Inventors: **Timothy E. Kasen**, Jenison, MI (US);
Gary A. Kasper, Grand Rapids, MI (US)

(73) Assignee: **Bissell Homecare, Inc.**, Grand Rapids, MI (US)

(21) Appl. No.: **10/607,727**

(22) Filed: **Jun. 27, 2003**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,286,181**
Issued: **Sep. 11, 2001**
Appl. No.: **09/575,929**
Filed: **May 23, 2000**

U.S. Applications:

(62) Division of application No. 09/112,527, filed on Jul. 8, 1998, now Pat. No. 6,167,587.

(60) Provisional application No. 60/075,924, filed on Feb. 25, 1998, and provisional application No. 60/052,021, filed on Jul. 9, 1997.

(51) **Int. Cl.**
A47L 11/30 (2006.01)

(52) **U.S. Cl.** **15/320; 15/332; 15/355; 15/368**


(58) **Field of Classification Search** **15/320, 15/332, 355, 361, 368, 371, 373**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

561,548 A *	6/1896	McMahon	213/185
1,151,029 A *	8/1915	McKinley	116/274
1,346,972 A *	7/1920	Orr	15/361
1,462,071 A *	7/1923	Rieman	
1,844,212 A *	2/1932	De Lancey	116/274
1,893,233 A *	1/1933	Hull	116/274

2,149,138 A *	2/1939	Gasner	474/140
2,156,805 A *	5/1939	Dow	15/334
2,375,331 A *	5/1945	Taylor	356/600
2,416,418 A *	2/1947	Taylor	15/330
2,613,242 A *	10/1952	Shumaker et al.	310/258
2,680,260 A *	6/1954	Danielsson et al.	15/50.1
2,850,756 A *	9/1958	Ziegler, Jr. et al.	15/323
2,850,757 A *	9/1958	Duff	15/359
2,955,674 A *	10/1960	Krammes	55/357
2,980,939 A *	4/1961	Sparklin et al.	15/377
3,012,267 A	12/1961	Kemnitz	
3,031,710 A *	5/1962	Huening, Jr.	15/359
3,126,570 A *	3/1964	Green	15/331
3,204,281 A *	9/1965	Walter et al.	15/364
3,448,485 A *	6/1969	Worwag	15/332
3,579,699 A *	5/1971	Balzer	15/361
3,624,861 A *	12/1971	Freiheit	15/320
3,634,905 A *	1/1972	Boyd	15/350
3,639,941 A *	2/1972	Kirwan et al.	15/372
3,896,520 A *	7/1975	Williams	15/320
3,908,223 A *	9/1975	Brooks et al.	15/383
3,911,524 A *	10/1975	Parise	15/353
3,939,527 A *	2/1976	Jones	15/353
3,959,844 A *	6/1976	Cyphert	15/320
4,114,229 A *	9/1978	Jones et al.	15/320
4,194,262 A *	3/1980	Finley et al.	15/314
4,196,492 A *	4/1980	Johnson et al.	15/320
4,216,563 A *	8/1980	Cyphert	15/321
4,245,371 A *	1/1981	Satterfield	15/320
4,287,635 A *	9/1981	Jacobs	15/321
4,333,202 A *	6/1982	Block	15/320
4,349,935 A *	9/1982	Knestele	15/320
4,353,145 A *	10/1982	Woodford	15/321
4,458,377 A *	7/1984	Frohbieter	15/320
4,488,329 A *	12/1984	Lackenbach	15/322
4,498,214 A *	2/1985	Oxel	
4,559,665 A *	12/1985	Fitzwater	15/339
4,586,208 A *	5/1986	Trevarthen	8/158
4,660,246 A *	4/1987	Duncan et al.	15/329
4,685,171 A *	8/1987	Beaudoin	15/391
4,709,442 A *	12/1987	Sletten, II	15/320
4,724,574 A *	2/1988	Bowerman et al.	15/351
4,745,877 A *	5/1988	Chang	116/274
4,782,552 A *	11/1988	Bartlett et al.	15/333
4,809,397 A *	3/1989	Jacobs et al.	15/320
4,811,450 A *	3/1989	Steadings	15/337
4,912,805 A *	4/1990	Krasznai et al.	15/392



4,940,082	A	*	7/1990	Roden	15/321
4,940,397	A	*	7/1990	Kuhlen	417/435
4,956,891	A	*	9/1990	Wulff	15/320
4,976,003	A	*	12/1990	Williams		
4,980,945	A	*	1/1991	Bewley	15/339
4,993,108	A	*	2/1991	Genge et al.	15/383
5,101,352	A	*	3/1992	Rembert	705/8
5,101,532	A	*	4/1992	Dyson et al.		
5,129,128	A	*	7/1992	Bowerman et al.	15/413
5,134,750	A	*	8/1992	King et al.	15/333
5,134,752	A	*	8/1992	Shipman	15/412
5,218,736	A	*	6/1993	Bartasevich et al.	15/344
5,237,719	A	*	8/1993	Dwyer et al.	15/321
5,243,734	A	*	9/1993	Maurer et al.	15/334
5,244,003	A	*	9/1993	Boomgaarden	137/1
5,247,720	A	*	9/1993	Sovis et al.	15/334
5,297,312	A	*	3/1994	Zuiderveen et al.	15/391
5,329,666	A	*	7/1994	Bowerman et al.	15/323
5,345,650	A	*	9/1994	Downham et al.	15/331
5,351,361	A	*	10/1994	Buchtel	15/334
5,355,549	A	*	10/1994	Steinberg et al.	15/334
5,386,613	A	*	2/1995	Woo	15/326
5,394,587	A	*	3/1995	Parise	15/353
5,406,673	A	*	4/1995	Bradd et al.	15/320
5,493,752	A	*	2/1996	Crouser et al.	15/321
5,500,977	A	*	3/1996	McAllise et al.	15/320
5,526,547	A	*	6/1996	Williams et al.	15/320
5,537,712	A	*	7/1996	Weber et al.	15/391
5,542,147	A	*	8/1996	Merten	15/321
5,551,120	A	*	9/1996	Cipolla et al.		
5,615,448	A	*	4/1997	Crouser et al.		
5,632,060	A	*	5/1997	Steinberg et al.	15/391
5,640,738	A	*	6/1997	Williams et al.	15/320
5,867,857	A	*	2/1999	Crouser et al.	15/50.1
5,974,625	A	*	11/1999	Garner	15/354

FOREIGN PATENT DOCUMENTS

CA	1262201	*	10/1989		
GB	610918	*	10/1948	15/368

* cited by examiner

Primary Examiner—Terrence R. Till
(74) Attorney, Agent, or Firm—McGarry Bair PC

(57) ABSTRACT

A portable surface cleaning apparatus including a base module [for movement along a surface], an upright handle pivotally attached to the base module, a liquid dispensing system [including a flexible bladder defining a fluid supply chamber for holding a supply of cleaning fluid], a fluid recovery system [including a tank on the base module

having a fluid recovery chamber for holding recovered fluid and housing the flexible bladder, and a fluid passageway between the fluid supply chamber and the recovery chamber, whereby the recovery chamber is in fluid communication with the fluid supply chamber and the pressure in the flexible bladder is equalized with the pressure in the tank as the cleaning fluid is dispensed from the supply chamber and the dirty liquid is collected in the recovery chamber. In a further embodiment the tank has an outlet opening in a bottom portion thereof and a drain plug is removably mounted in the outlet opening. In another embodiment a lid mounted on the tank defines an expansion chamber having an inlet opening, an outlet passage, and first and second diverters against which the working air flow reverses direction twice between the inlet opening of the expansion chamber and the tank. In another embodiment the working air conduit includes a manual actuator knob having an over-center linkage mechanism connected to a conversion valve for movement between first and second positions and thereby selectively moving the conversion valve between open and closed positions, whereby fluid communication between the tank and the suction nozzle is selectively opened and closed. In a further embodiment, a flow indicator is mounted to the base module and has a visibility window observable to a user and the flow indicator is disposed in the fluid supply conduit and is responsive to the flow of fluid through the fluid supply conduit to visually indicate the flow of fluid through the supply conduit to the user. Another embodiment includes a pump primer connected to the pump and having a housing defining a priming chamber with a valved opening connected to the vacuum source, an inlet opening connected to the fluid supply chamber, and an outlet opening connected to an inlet for the pump. A further embodiment includes a first mechanical connector extending between the motor drive shaft and the pump drive shaft, whereby the motor drives both the agitation brush and the pump. In a further embodiment, the base module includes an upper housing portion and a lower housing portion and an upright handle is pivotally mounted to the rear portion of the base module through at least one bearing for rotatable reception in the housing. In another embodiment], an elevator assembly [is] reciprocally mounted to the base module and movable in response to movement of the upright handle from an operative position to the upright position for upwardly pivoting a pivot arm mounting an agitation brush.

30 Claims, 17 Drawing Sheets




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 5A




Fig. 5B




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 14A




Fig. 14B




Fig. 15




Fig. 16




Fig. 18




Fig. 20




Fig. 19




Fig. 21




Fig. 22

UPRIGHT EXTRACTION CLEANING MACHINE

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a divisional application of U.S. patent application Ser. No. 09/112,527, filed Jul. 8, 1998, now U.S. Pat. No. 6,167,587, issued Jan. 2, 2001, which claims the benefit of U.S. Provisional Application Serial No. 60/075,924, filed on Feb. 25, 1998, and U.S. Provisional Application Serial No. 60/052,021, filed on Jul. 9, 1997.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to an extraction cleaning machine and, more particularly, to an upright extraction cleaning machine.

2. Description of Related Art

Upright extraction cleaning machines have been used for removing dirt from surfaces such as carpeting, upholstery, drapes and the like. The known extraction cleaning machines can be in the form of a canister-type unit as disclosed in U.S. Pat. No. 5,237,720 to Blase et al. or an upright unit as disclosed in U.S. Pat. No. 5,500,977 to McAllise et al. and U.S. Pat. No. 4,559,665 to Fitzwater.

Current upright extraction cleaning machines can be made easier to use by limiting the weight and number of components, such as fluid storage tanks, on the pivoting handle of the upright cleaning machine. Reducing the weight that a user must support as the handle is tilted rearwardly can also lower the center of gravity for the machine, which results in a better feel to the user.

Furthermore, the current extraction cleaning machines can be made easier to use and better adapted for a variety of cleaning conditions. For example, none of the current extraction cleaning machines includes an elevator responsive-to-handle position for restraining a floating roller-type agitation brush, which is automatically height adjustable in response to changes on the surface being cleaned. Another problem inherent with the known extraction cleaning machines is the difficulty of filling and emptying the fluid supply chamber and fluid recovery chamber, particularly with bladder-within-a-tank type assemblies. Further, none of the current upright extraction cleaning machines are simply convertible to a pre-spray applicator for directing cleaning solution to and agitating the surface to be cleaned without applying suction. Finally, current extraction cleaning machines do not use a the same motor to drive an agitation brush as well as an impeller. In some cases a separate motor is used. In other cases, a turbine is used to drive the agitation brush or brushes which diminishes the suction power available to extract the dirty solution from the floor surface.

A more recent development in the extraction cleaning industry is the use of steam or hot water as a cleaning agent. The cleaning machine incorporates a boiler or other means for generating steam or hot water, which is pumped to an applicator where it is brought into contact with the surface being cleaned. Because the steam is airborne, it may be unsafe to include detergents and the like in the cleaning

solution. Further, while the steam systems have the advantage of creating a temperature that effectively kills a wider range of microbes, bacteria, microorganisms, and mites, the steam systems generally suffer from poor cleaning performance. Additionally, the high power requirement for generating steam may not be sufficient with ordinary 120V power supplies for running a vacuum motor as well as the steam generator, so cleaning performance is further hindered. Also, by adding a heater to a fluid supply chamber, the user may be inconvenienced by the amount of time required to heat the contents of the supply chamber to the desired temperature. Conversely, conventional detergent cleaning systems are somewhat effective at cleaning surfaces, but could be made more effective by raising the temperature of the cleaning solution to some temperature below the boiling point. There is an optimal temperature at which cleaning performance is maximized without causing damage to carpets or setting stains. This temperature is around 150° Fahrenheit.

SUMMARY

According to the invention, a portable surface cleaning apparatus comprises a base module for movement along a surface and having a rear portion, an upright handle pivotably attached to the rear portion of the base module, a liquid dispensing system and a fluid recovery system. The liquid dispensing system comprises a liquid dispensing nozzle associated with the base module for applying liquid to a surface to be cleaned, a flexible bladder defining a fluid supply chamber for holding a supply of cleaning fluid and a fluid supply conduit fluidly connected to the fluid supply chamber and to the dispensing nozzle for supplying liquid to the dispensing nozzle. The fluid recovery system comprises a fluid tank on the base module having a recovery chamber for holding recovered fluid and enclosing the flexible bladder, a suction nozzle associated with the base, a working air conduit extending between the tank and the suction nozzle and a vacuum source in fluid communication with the tank for generating a flow of working air from the nozzle through the working air conduit and through the tank to thereby draw dirty liquid from the surface to be cleaned through the nozzle and working air conduit and into the tank.

In accordance with one embodiment of the invention, a fluid passageway is provided between the fluid supply chamber and the recovery chamber of the tank, whereby the tank is in fluid communication with the fluid supply chamber and the pressure in the flexible bladder is equalized with the pressure in the tank as the cleaning fluid is dispensed and the dirty liquid is collected in the tank. The flexible bladder preferably includes an outlet opening in the bottom portion thereof connected to the fluid supply conduit. In one embodiment, the flexible bladder extends between a bottom surface of the tank and an upper portion of the tank.

In a preferred embodiment, the fluid passageway between the fluid supply chamber and the recovery chamber of the tank comprises a filling spout disposed in an upper portion of the flexible bladder. A baffle plate is mounted within the upper portion of the tank and includes an opening. The filling spout on the flexible bladder extends through the opening in the baffle plate and is supported thereby. Preferably, the tank includes a removable lid on a top portion thereof and a filling spout is disposed between the baffle plate and the lid.

Further according to the invention, in one embodiment, the tank has an outlet opening in a bottom portion thereof and a drain plug is removably mounted in the outlet opening.

3

In another embodiment, a lid mounted on the tank defines an expansion chamber having an inlet opening and an outlet passage between the expansion chamber and the tank. The working air conduit is connected to the lid inlet opening so that the working air is drawn through the expansion chamber in the lid and into the tank. A first diverter baffle in the expansion chamber reverses the direction of flow of the working air between the inlet opening and the outlet passage. A second diverter baffle in the outlet passage reverses the direction of flow of the working air between the expansion chamber and the tank. Thus, the working air flow reverses direction twice between the inlet opening of the expansion chamber and the tank. The lid is preferably removably mounted to the tank. In one embodiment, the outlet passage extends beneath the expansion chamber and includes an outlet opening and the filling spout in the flexible bladder includes an opening beneath the lid and substantially above the outlet opening in the outlet passage. Further, the filling spout is disposed between the baffle plate and the lid and the lid includes a shroud extending downwardly from the bottom surface thereof surrounding the filling spout to a point below the opening of the filling spout. Preferably, the shroud extends beneath the outlet opening of the outlet passage.

In another embodiment, the working air conduit includes a conversion valve for selectively opening and closing fluid communication between the tank and the suction nozzle. A manual actuator knob is connected to the conversion valve for movement between first and second positions and thereby selectively moving the conversion valve between open and closed positions. According to the invention, an over-center linkage mechanism is connected to the manual actual knob to bias the conversion valve to the open and closed positions. In a preferred embodiment, the over-center linkage mechanism comprises a spring-biased plunger assembly mounted to the actuator knob for movement therewith. The actuator knob is preferably mounted to the base module for rotational movement between the first and second positions and the spring-biased plunger assembly is mounted to the actuator knob for rotational movement therewith. In a preferred embodiment, the conversion valve is pivotably mounted to the base for rotational movement between the open and closed positions and the conversion valve includes an arm having a distal end extending to the plunger assembly and rotatably connected thereto. The rotational motion of the actuator knob is translated to rotational movement of the conversion valve through the arm.

In yet another embodiment, a flow indicator is mounted to the base module and has a visibility window observable to a user and the flow indicator is disposed in the fluid supply conduit and is responsive to the flow of fluid through the fluid supply conduit to visually indicate the flow of fluid through the supply conduit to the user. In a preferred embodiment, the flow indicator comprises an impeller rotatably mounted in a flow indicator housing and driven by the fluid flowing through the flow indicator.

In still another embodiment of the invention, a fluid supply conduit in the liquid dispensing system includes a pump fluidly connected to the fluid supply chamber and to the dispensing nozzle for supplying cleaning fluid to the dispensing nozzle. A pump primer is connected to the pump for priming the pump and includes a valved opening connected to the vacuum source. According to the invention, the pump primer includes a housing defining a priming chamber with an inlet opening connected to the fluid supply chamber and an outlet opening connected to an inlet for the pump. In a preferred embodiment of the invention, the valved opening

4

is in an upper portion of the priming chamber. Further, the pump primer includes a valve chamber and a plunger chamber. The valve chamber has an inlet opening defined by the valved opening in the primer chamber and an outlet opening defining an inlet opening to the plunger chamber. The plunger chamber has an outlet opening in fluid communication with the vacuum source. A buoyant plunger is reciprocally mounted in the plunger chamber for generally vertical movement therein. A valve is mounted in the valve chamber and reciprocally movable between the inlet opening and the outlet opening thereof and connected to the plunger for movement therewith. By this structure, the valve closes the outlet opening to the valve chamber when fluid in the plunger chamber raises the plunger and the valve closes the inlet opening when fluid in the plunger chamber falls to a predetermined level. In a preferred embodiment of the invention, the valve in the valve chamber is an umbrella valve.

In a further embodiment of the invention, the surface cleaning apparatus includes a fluid supply conduit including a pump fluidly connected to the fluid supply chamber and to the dispensing nozzle for supply cleaning fluid to the dispensing nozzle. The pump has a drive shaft for driving the pump. An agitation brush is mounted in the forward portion of the base module. A motor is mounted in the base housing and has a motor drive shaft connected to the agitation brush for rotatably driving the agitation brush. According to the invention, a first mechanical connector extends between the motor drive shaft and the pump drive shaft, whereby the motor drives both the agitation brush and the pump. In a preferred embodiment of the invention, the motor drive shaft is connected to the agitation brush through a second mechanical connector between the pump drive shaft and the agitation brush. The pump drive shaft has a mechanical step-down device connecting the drive shaft to the first mechanical connector to step down the speed of rotation of the motor shaft in the pump drive shaft. Preferably, the first and second mechanical connectors are belts, with the second connector preferably being a timing belt and the first connector preferably being a stretch belt. Typically, the stretch belt rides directly on the motor drive shaft. In a preferred embodiment of the invention, inner and outer pulleys are mounted in axially spaced relationship on the pump shaft, wherein the timing belt is reeved around the outer pulley and the stretch belt is reeved around the inner pulley. Further, there is a baffle between the inner and outer pulleys to minimize liquid transfer between the inner and outer pulleys- The inner and outer pulleys are preferably of a size to step down the speed of rotation of the motor shaft at the pump drive shaft and at the agitation brush. Further according to the invention, the base module includes a housing with an opening adjacent to the first mechanical connector and a removable door is selectively mounted to the housing to cover the opening. Preferably, the removable door includes a flange and the housing includes a groove and the flange is slidably received in the groove to at least partially support the door in the opening. The housing preferably includes a second removable door which forms a portion of the baffle between the inner and outer pulleys.

Further according to the invention, the base module includes an upper housing portion and a lower housing portion and an upright handle is pivotably mounted to the rear portion of the base module through at least one bearing for rotatable reception in the housing. According to the invention, a socket is formed between the upper and lower housing portions for rotatably receiving the bearing.

5

Preferably, the bearing is formed integral with the lower portion of the upright handle. Desirably, the socket is formed by arcuate surfaces in mated edges of the upper and lower housing portions. The lower portion of the upright handle includes diverging arms, each including a bearing. Each bearing is formed integral with the lower portion of the upright handle. Typically, wheels are mounted to an axle which are received within the bearings for rotationally mounting the wheels to the handle.

In accordance with another embodiment of the invention, a portable surface cleaning apparatus has a base module with a brush assembly having an agitation brush generally disposed in the front portion of the base module and a pivot arm for pivotably supporting the agitation brush relative to the base module. A first end of the pivot arm is mounted to the agitation brush for rotation of the agitation brush with respect to the pivot arm and a second end of the pivot arm is pivotably mounted to the base module, whereby the brush assembly is free-floating to adjust to different surface heights. According to the invention, an elevator assembly is reciprocally mounted to the base module and movable in response to movement of the upright handle from an operative position to the upright position. The elevator assembly includes an arm disposed at one end adjacent the pivot arm and having a lifting surface for upwardly pivoting the pivot arm and a second end extending toward the handle and having a contacting surface for sliding along the outer surface of the lower portion of the handle. Movement of the arm toward the front portion of the base module by pivoting the upright handle to the storage position is translated into movement of the agitation brush away from the surface to be cleaned. Preferably, a spring biases the arm toward the handle.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described with reference to the drawings wherein:

FIG. 1 is a perspective view of the extraction cleaning machine according to the invention;

FIG. 2 is an exploded view of a base module of the extraction cleaning machine shown in FIG. 1;

FIG. 3 is an exploded view of a base module and tank assembly of the extraction cleaning machine of FIG. 1;

FIG. 4 is an exploded view of a handle assembly and portions of the base module for the extraction cleaning machine of FIG. 1;

FIG. 5 is a partial sectional side view of the foot module of the extraction cleaning machine of FIG. 1;

FIG. 5A is an exploded view of a floating brush assembly for the extraction cleaning machine of FIG. 1;

FIG. 5B is a perspective view of an alternative brush assembly for the extraction cleaning machine of FIG. 1;

FIG. 6 is a partial sectional side view of the extraction cleaning machine of FIG. 1 with the handle assembly in a tilted position;

FIG. 7 is a side sectional view of the pump and pump priming assembly of the extraction cleaning machine of FIG. 1 with a plunger in a first position;

FIG. 8 is a side sectional view of the pump and pump priming assembly of the extraction cleaning machine of FIG. 1 with a plunger in a second position;

FIG. 9 is a partial perspective view of the belt access door assembly of the extraction cleaning machine of FIG. 1;

FIG. 10 is a partial sectional view of the auto-mix valve of the extraction cleaning machine of FIG. 1 with a valve stem in a first position;

6

FIG. 11 is a partial view of the auto-mix valve of the extraction cleaning machine of FIG. 1 with a valve stem in a second position;

FIG. 12 is a partial side sectional view of a diverter valve with the valve plate shown in a first position and in phantom for a second position for the extraction cleaning machine of FIG. 1;

FIG. 13 is a partial side view of the valve assembly of FIG. 12 with the valve plate in the second position;

FIG. 14 is a sectional view of the air/water separator lid along line 14—14 of FIG. 3;

FIG. 14A is a partial side view of a closure plate in three positions relative an air exit from the air/water separator lid of FIGS. 13 and 14;

FIG. 14B is a partial sectional view taken along lines 14B—14B of FIG. 14;

FIG. 15 is a sectional view of the air/water separator lid along line 15—15 of FIG. 14;

FIG. 16 is a partial sectional view of the tank assembly and handle assembly of the extraction cleaning machine shown in FIG. 1;

FIG. 17 is a fluid flow diagram for the extraction cleaning machine of FIG. 1;

FIG. 18 is an exploded view of the in-line heater of the extraction cleaning machine of FIG. 1;

FIG. 19 is a top view of the fluid flow indicator of the extraction cleaning machine of FIG. 1;

FIG. 20 is a side sectional view of the fluid flow indicator of FIG. 19;

FIG. 21 is a bottom perspective view of a drain plug of the base module and tank assembly of FIG. 3; and

FIG. 22 is a top perspective view of the drain plug of the base module and tank assembly of FIG. 3 and illustrated in FIG. 22.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings and to FIG. 1 in particular, an upright extraction cleaning machine 12 according to the invention is shown. The machine 12 is a portable surface cleaning apparatus including a base module 14 adapted to roll across a surface to be cleaned and an upright handle assembly 16 pivotably mounted to a rear portion of the base module 14.

As best shown in FIGS. 1–3, the base module 14 includes a lower housing portion 15 and an upper housing portion 17, which together define an interior for housing components and a well 730 for receiving a tank assembly 50. Further, a well 732 in the upper housing portion 17 receives a detergent supply tank 870, as best shown in FIG. 3. The upper housing portion 17 receives a transparent facing 19 for defining a first working air conduit 704 and a suction nozzle 34, which is disposed at a front portion of the base module 14 adjacent the surface being cleaned for recovering fluid therefrom. The handle assembly 16 has a closed loop grip 18 provided at the uppermost portion thereof and a combination hose and cord wrap 20 that is adapted to support an accessory hose 22 and a electrical cord (not shown) when either is not in use. A latch assembly 21 is pivotably mounted to the rear portion of the base module 14 adjacent the rotational union of the handle assembly 16 therewith for releasably locking the handle assembly 16 in its upright position.

As shown in FIG. 2, the base module 14 houses a drive motor 196 that is connected to a source of electricity by the

electrical cord. A motor compartment **500** within the base module **14** is a clamshell-shaped housing for holding a motor assembly in place and preventing rotation thereof. The clamshell motor compartment **500** includes an upper half **502** and a lower half **504**. The upper half **502** is removable from the lower half **504**, which is integral to the extraction cleaner base module **14**. Thus, a bottom wall of the lower half **504** is the bottom surface of the extraction cleaner base module **14**. An arm **651** extends upwardly from the motor housing **500** in the base module **14** to support the flow indicator **650**, which is mounted to an upper end thereof. An opening **653** in the upper housing portion **17** receives the flow indicator **650** when that portion is mounted to the lower housing portion **15**.

The motor compartment **500** includes a large circular impeller fan housing **510** and a smaller motor housing **512**, further having a generally T-shaped cross section. The impeller fan housing **510** surrounds an inner housing **41** defining a vacuum source **40**, which is created preferably by an impeller (not shown) disposed within the housing **41**. The housing **41** includes a large aperture **516** for mounting a vacuum intake duct **530**, which is sealed to the aperture **516** by a gasket **520**. The vacuum intake duct **530** connects the vacuum source **40** to an air/water separation chamber **750** (shown in FIGS. **3**, **14**, **14A**, **14B** and **15**) in a lid **700** on the tank assembly **50**, as well as the suction nozzle **34** on the front portion of the base module **14** and a suction nozzle (not shown) on a distal end of the accessory hose **22**. The smaller end **512** includes a small aperture **524** for receiving there-through a motor drive shaft **198**. A stretch belt **204** is received on the motor drive shaft **198** outside of the clamshell motor compartment **500**. Further, an upper surface **520** of the motor compartment **500** supports and secures an accessory hose intake duct **540** partially defining a second working air conduit **706** (as shown best in FIGS. **12-14**), which connects the suction nozzle on the distal end of the accessory hose **22** to the vacuum source **40**.

The drive shaft **198** of the drive motor **196** is connected to an interim drive shaft **200** of a solution pump **202** by the stretch belt **204**, which in turn, is connected to a rotatably mounted agitation brush **206** by a timing belt **208**, as best illustrated in FIGS. **5** and **6**. On the opposite side of the motor **196**, the motor drive shaft **198** supports the impeller (not shown) within the impeller housing **41**, which provides the vacuum source **40** and is mounted inside the housing **510** of the motor compartment **500**. With this configuration, a single drive motor **196** is adapted to provide driving force for the impeller, the solution pump **202**, and the agitation brush **206**.

As best seen in FIGS. **2**, **5**, **5A**, and **6**, the rotatably mounted agitation brush **206** is adapted for floor-responsive adjustment by a floating brush assembly **400** mounted within an agitation brush housing **26** disposed within a forward portion of the base module **14**. The floating movement of the agitation brush **206** is a horizontally oriented arcuate path for reciprocation toward and outward of the agitation brush housing **26**. Ends **452** of an agitation brush shaft **206** are received in bearings **454**, which in turn, are press fit into inwardly extending bosses **456** to provide a pair of opposed articulating arm members **458**. Alternatively, stub shafts (not shown) can extend from the arm members **458** and the ends **452** can be replaced with bearings similar to **454** for rotational installation of the brush **206** on the arm members **458**.

Each arm member **458** comprises a back plate **460** with a pivot pin **462** provided at the rear of the plate **460**. In addition, a laterally extending belt guard **466** is preferably integrally formed with the articulating arm **458**. The belt

guard **466**, which extends laterally inwardly enough to cover the timing belt **208**, minimizes the lodging of threads and other foreign material in the timing belt **208** and protects the carpet or other surface positioned below the base assembly **14** from the rotating belt **208**.

As best shown in FIGS. **5-6**, **9**, the timing belt **208** is [reeved through] *trained around* a pulley **216** mounted at one end of the brush **206** and a pulley **222** on the interim drive shaft **200** of the pump **202**, which includes a separate pulley **220** [through] which is [reeved] *received around* the strength belt **204**, which, in turn, extends around the drive shaft **198** of the motor **196**. As best shown in FIGS. **7** and **9**, the radius of the pulley **220** is larger than the radius of the pulley **222**. Further, the pulley **220** has a convex cross section of its periphery, whereby it is adapted to receive the smooth stretch belt **204**, while the pulley **222** has a toothed perimeter adapted for registration with the teeth in the timing belt **208**.

The pivot pins **462** of the arm member **458** are rotatably supported secured in a bearing (not shown) mount integrally formed with an internal wall of the agitation brush housing **26**. Further, the pivot pins **462** are held in the bearing by a support **478** on the non-belt side of the base module **14** and the an arm **258** of the second belt access door **252** on the belt side of the base module, as best shown in FIG. **5A**. Both the arm **258** and support **478** are secured to the agitation brush housing **26** by a conventional fastener (not shown) inserted through an aperture in each part. The arm members **458** are preferably limited in their downward movement relative to the agitation brush housing **26** by the length of the timing belt **208** as well as the engagement of the brush guards **466** with the arm **258** and the support **478**. As the floating brush assembly **400** extends further and further downwardly, the belt **208** will stretch and resist further downward movement. Eventually, the brush guards **466** on each arm **458** will contact respectively the arm **258** and the support **478**, which prevents any further downward movement.

With this floating agitation brush assembly **400**, the cleaning machine **12** according to the invention can almost instantaneously adapt to varying carpet naps or other inconsistencies on the surface being cleaned. The arm members **458** also allow the rotating brush **206** to drop below the normal floor plane, as shown in FIG. **6**, to, for example, provide contact with a bare floor.

As an alternative to the floating, rotatably mounted agitation brush **206**, a floating strip agitation brush **224** could be incorporated into the cleaning machine **12**, as seen in FIG. **5B**. In this embodiment, the strip brush **224** comprises a linear brush portion **492** with bristles **494** extending downwardly therefrom, and a pair of integrally molded arms **496** having pivot pins **502**, which can mount to the arm members **458** in place of the pivot pins **462** supporting the agitation brush **206**. With this structure, the strip brush **224** can move vertically in response to changes to the carpet nap or other inconsistencies in the floor being cleaned.

As shown in FIGS. **2**, **5** and **6**, an elevator assembly **410** comprises a central support member **412** having at one end an L-shaped actuating arm **418**, and at another end, the ramped surface **414** on a forward arm **404** opposed by a guide **416**. Between the guide **416** and the ramped surface **414** is mounted a spring assembly **406**, which biases the assembly **410** rearward toward the handle assembly **16**. The spring assembly **406** includes a spring **436**; a stop **426**, which is attached to the base module **14** and through which the forward arm **404** travels; and a flange **428**, which is integral with the forward arm **404**. The spring **436** is held

between the flange 428 and stop 426, and biases the assembly 410 rearward relative the stop 426 through force on the flange 428.

The arm 418 extends from within the base module 14 where it is mounted, through an aperture 402, towards the handle assembly 16. The actuating arm 418 is forced horizontally forward when the rotatably mounted handle 16 on the base module 14 is put in the upright position, which forces an upper portion 422 of the actuating arm 418 in a horizontal and forward direction. More specifically, as shown in FIG. 5, a curved surface 424 on the handle assembly 16 strikes a rounded distal end 420 of the L-shaped actuating arm 418 when the handle assembly 16 is put in its storage or non-use position. When the handle assembly 16 is pivoted rearwardly for use, as shown in FIG. 6, the curved surface 424 shifts rearwardly and the springbiased elevator assembly 410 follows, with end 420 riding the curved surface 424, until the elevator assembly 410 reaches a rearward, rest position.

Thus, forward movement of the actuating arm 418 forces the support member 410 and ramped surface 414 forward, wherein the ramped surface 414 contacts the underside of the brush guards 466 on each arm 458, thereby raising the floating brush assembly 400 as the elevator assembly 410 moves from a rearward position to a forward position in the base module 14. That is, as the ramped surface 414 moves towards the front of the base module 14, the agitation brush assembly 400 slowly rises as the brush guards 466 ride the ramped surfaces 414. Such a construction eliminates the need for a manual arm for lowering and raising the agitation brush assembly 400 for storage or use of the accessory hose 22, thereby eliminating risks of damage to the brush assembly and protecting the carpet from the agitation brush assembly 400 resting thereon. When the handle 16 is moved to the in-use position, the spring assembly biases the elevator assembly to its normal, rearward position.

As seen best in FIGS. 1 and 4, the base module 14 is supported at the rear portion thereof by a pair of opposed rear wheels 552. The handle assembly 16 includes a U-shaped lower portion 560 having opposed arms 562 and 564 including cylindrical bearings 578 for mounting the handle assembly 16 to the base module 14 and supporting axles 554 on a common axis for rotatably mounting the wheels 552 to the extraction cleaner base module 14. More particularly, the handle assembly 16 tapers from its wide, lower portion 560 to a thinner handle portion 570, having a thin handgrip portion 572, including the closed loop grip 18 at its uppermost end, by which the user moves the extraction cleaner. The bearing 578 include a central circumferential groove 576 for receiving arcuate portions 588, 589 of the base module 14 whereby rotation of the handle assembly 16 is facilitated.

The handle assembly 16 further comprises a front portion 580 and a rear portion 582 defining a substantially hollow interior supported by multiple ribs 558. Mounts 584, disposed radially on the interior of the front and rear portions 580 and 582 support an in-line heater 54, as will be described in detail below. The substantially flat front portion 580 is secured to the mated rear portion 582 by conventional fasteners, such as screws. The rear portion 582 further includes the combined accessory hose and electrical cord mount 20.

Returning to the lower portion 560, the arms 562, 564 comprise portions of both the front portion 580 and the rear portion 582. When the assembly 16 is secured together, these arms 562, 564 pivot about the bearing 578 integrally

formed with the arms 562, 564. The bearings 578, in turn, receive axles 554, on each side, respectively, for mounting wheels 552. The axles 554 extend through the wheels 552, apertures 586 through the rear portion 582 of the lower arms 562, 564, and the bearings 578 integrally formed with the arms 562, 565. The axles 554, 556 are secured by large diameter axle mounting clips 594, disposed, when installed, adjacent the bearings 578 and within the base module 14. A side edge 598 of the extraction cleaner base module 14 includes an arcuate surface 588 to accommodate the handle bearings 578 secured on inside portions of each arm 562, 564 of the rear portion 582.

Once the handle assembly 16 is mounted to each base module 14, with the axles 554 secured by the mounting clips 594, the extraction cleaner upper housing portion 17 is secured to the lower housing portion 15. The upper housing portion 17 also has an arcuate surface 589 formed in a side thereof for accommodating and securing the integral bearings 578 of the arms 562, 564. More specifically, the arcuate surfaces 588, 589 of the side walls of the housings 15, 17 are received in the central circumferential groove 576 formed in the circumference of each integral bearing 578. Thus, when the base module 14 is formed of the housings 15, 17, the bearings 578 of the arms 562 are secured therebetween such that they can only rotate between an upright, stored position and an in-use position and the wheels are mounted to axles 554, 556 received through apertures in the bearings 578 and secured by mounting clips 594.

The concentric wheel axle and handle pivot transfers all the force on the handle assembly 16 to the wheels 552 to keep downward force on the suction nozzle 34 constant. Further, the tank assembly 50, as shown in FIG. 3, center of gravity is close to the wheel center so that changing tank volume does not alter the downward force on the suction nozzle 34 and allows the weight of the tank assembly 50 to be carried on the wheels 552 fairly evenly. Also, the handle assembly 16 supports very little weight and therefore keeps the weight that the user feels through the handle assembly 16 to a minimum. This creates an upright extraction cleaning machine 12 that is easy to use and less tiring for the operator.

The handle assembly 16 is releasably locked against rotation from its upright position by a latch assembly 21, which is pivotally mounted to the rear portion of the base module 14 adjacent the rotational union of lower leg 564. The latch assembly 21 includes an upright lower portion which is pivotally mounted to the base module 14 at a rear corner thereof and an upper portion which extends upwardly and rearwardly of the lower portion. A molded-in spring arm extends rearwardly from the lower portion of the latch assembly 21 and bears against a rear portion of the base module 14 to bias the lower portion forwardly and against the rear portion of the lower leg 564. The upper end of the lower portion of the latch assembly 21 forms a horizontal latching surface which bears against the rear portion of the lower leg 564 and engages projections thereon to lock the handle in the upright position in a conventional fashion. Thus, as the handle assembly 16 is pivoted upright, the rear portion of the lower leg 564 rides along the horizontal latching surface until the edge catches the projection on the rear portion of the lower leg 564, at which point the handle assembly 16 is locked upwardly. To release the latch assembly 21, the user pushes the step downwardly and against the bias of the molded-in spring to release the horizontal latching surface from the projection. The latching mechanism is conventional and forms no part of the invention of this application- Any conventional latching mechanism can be used with the handle and base module in the invention.

The tank assembly **50** is removably supported on the rear of the base module **14**. An air/water separator lid **700** seals the top of the tank assembly **50**, which includes a valve mechanism **80** on a bottom portion for controlling the flow of cleaning solution fluid from the fluid supply chamber **49**. The base module **14** includes a valve seat **88** complementary to the valve mechanism **80**, and the bottom portion of the tank assembly **50** and the valve seat **88** are substantially complementary to one another so that the upwardly extending valve seat **88** is substantially surrounded by and received in the bottom of the tank assembly, as will be described further below.

The lid **700** is secured to the tank assembly **50** by a rotatable handle **790**, as best shown in FIG. **16**, which can be moved between a storage position, in which the tank **50** is sealed by the lid **700** and the handle **790** is disposed rearwardly horizontal (as shown in solid lines); a transport position, in which the tank **50** is sealed and the handle **790** extends vertically upward (shown in phantom lines) for ease in carrying by the user; and a service position, in which the lid **700** can be removed from the tank assembly **50** and the handle **790** is disposed forwardly at an acute angle relative the lid (shown in dashed lines). The U-shaped tank handle **790** rotates about a pivot **792** projecting from a side of the lid **700**. The pivot **792** is received in a bushing **794** disposed centrally in a circular mounting portion **796** at the ends of the handle **790**. An arcuate wall **798** extending transversely from the mounting portion **796**, integral therewith, and having an opening **788** surrounds the bushing **794**. When the handle **790** is rotated about the pivot on the lid, an inside surface **784** of the wall **798** engages a tab **786** extending transversely from an upper lip **782** of the tank assembly **50** for locking the lid **700** to the tank assembly. The surface **784** of the wall **798** engages the tab **786** when the handle **790** is in either the storage or transport position. When in the service position, the tab **786** is aligned with the opening **788** in the wall **798**, whereupon the lid **700** can be removed from the tank assembly **50**.

As best shown in FIGS. **3**, **14**, **15**, a flexible bladder **120**, which is used as a clean water reservoir, is mounted inside a rigid tank assembly **50**. Thus, the tank assembly **50** is divided into two fluid chambers by the bladder **120**: a fluid supply chamber **49**, comprising the interior of the bladder **120**, and a fluid recovery chamber **48**, comprising the volume between the flexible bladder **120** and the rigid walls of the tank housing **46**. The bladder **120** is molded from a pliable thermoplastic material and is collapsible when empty to accommodate recovered fluid in the volume between the bladder **120** and the tank housing **46**. Initially, the bladder **120** is full of water or cleaning solution and occupies the vast majority of the volume within the tank housing **46**. As the user sprays the cleaning solution onto the surface to be cleaned, the volume of fluid in the bladder **120** is reduced corresponding to the volume of solution sprayed on the surface. During suction, recovered dirt and water are received in the tank housing **46** in the volume between the bladder **120** and the tank housing **46**. The volume available in the bladder **120** due to application of the cleaning solution is made available to recovered fluid by the pressure of the recovered fluid collapsing the bladder **120**, thereby forcing air out of the bladder **120**. Because recovery of the used cleaning solution is always less than 100% of the solution applied, there will always be ample room inside the tank housing **46** once the cleaning solution has been applied to the surface.

The bladder **120** is disposed within the tank assembly **50** between a bottom surface **860** of the rigid tank housing **46**

and a snap-in baffle plate **800**, which will be explained in further detail below. An aperture **824** in the baffle plate **800** has a diameter approximately matching that of a small diameter end **125** of a funnel-shaped filling spout **124** of the bladder **120**. Further, an upstanding collar **828** surrounds the aperture **824**. A cylindrical shroud **770**, as best shown in FIG. **17**, is mounted on the inside of the air/water separator lid **700** and extends downwardly therefrom to capture the filling spout **124**. Thus, the increasing diameter outside surface of the funnel-shaped filling spout **124** is retained in the aperture **824** and supported by the collar **828**, thereby holding the flexible bladder **120** in an upright position in the tank housing **46** between the bottom surface **860** and the baffle plate **800** therein. As space between the upstanding collar **828** and the downwardly extending shroud **770** defines a fluid passageway between the fluid supply chamber **49** and the recovery chamber **48**, whereby the fluid supply chamber **49** and the recovery chamber **48** maintain the same pressure, negative or otherwise.

The flexible bladder **120** includes an outlet **130** disposed in a lower corner of the flexible bladder **120**. The outlet **130** is mated with an outlet aperture **862**, as best viewed in FIG. **16**, in the bottom surface **860** of the rigid outer shell for supplying fluid to a fluid application system **950** and securing the bladder **120** to the rigid bottom surface **860** of the tank housing **46**.

The funnel-shaped filling spout **124** of the bladder **120** facilitates filling the bladder **120** and equalizing air pressure between the fluid supply chamber **49** and recovery chamber **48**. The filling spout **124** is always open, so as to vent air from the bladder **120** as it collapses in volume and the usable volume within the rigid outer walls of the tank housing **46** expands in volume. Further, the open filling spout **124** ensures that both chambers **48**, **49** are at substantially the same atmospheric pressure, which is preferably negative relative to standard atmospheric pressure because of the communication of the vacuum source **40** to the tank assembly **50** via the air/water separator lid **700**, as will be explained further below. The volume of the bladder **120** is preferably one gallon.

As best shown in FIG. **17**, the valve mechanism **80** is provided within the outlet aperture **862** through the bottom surface **860** of the tank housing **46** and the aligned outlet **130** in the bladder **120** for controlling the flow of cleaning solution fluid from the fluid supply chamber **49**. The valve mechanism **80** comprises a valve member (not shown) mounted within the aligned aperture **862** and outlet **130**, which together are selectively covered by the valve member to enable or prevent the flow of fluid to the fluid application system **950**.

The base module **14** includes a valve seat **88**, shown best in FIG. **17**, that has a fluid reservoir **90** adapted to receive fluid through the fluid aperture **862** and conduct this fluid to one end of the conduit **140**, the other end being mounted to a clean water inlet **332** of a mixing valve assembly **310**. The bottom wall **860** of the tank housing **46** and the valve seat **88** are substantially complementary to one another so that the upwardly extending valve seat **88** is substantially surrounded by and received in the bottom wall **860**. A projection **94** is provided in the fluid reservoir **90** and is adapted to contact a head of a shaft of the valve member (not shown). A spring received on the shaft of the valve member is adapted to bias the valve member into the closed position thereby preventing the flow of fluid through the fluid apertures. When the tank housing **46** is seated on the base module **14**, the head of the valve member contacts the projection **94** and deflects the valve upwardly thereby per-

mitting the flow of fluid around the valve, through the fluid apertures into the fluid reservoir **90** of the valve seat **88**, and to the fluid application system **950**. A gasket **81** seals the junction between the valve mechanism **80** and the seat **88**. When the tank housing **46** is removed from the base module **14**, the projection **94** is removed from contact with the head **96** of valve member. Therefore, the spring biases the valve downwardly into the closed position thereby preventing the flow of fluid through the fluid aperture **862** to the fluid application system **950**.

The fluid application system **950** conducts fluid from the fluid supply chamber **49** to fluid dispensing nozzles **100**, which are mounted in the brush housing **26** of the base module **14**, and a fluid dispensing nozzle (not shown), which is mounted on an accessory cleaning tool (not shown), as best illustrated in FIG. **17**. From the fluid supply chamber **49**, clean water is conducted through conduit **140** to an inlet **332** to the mixing valve assembly **310**, which also includes a detergent inlet **336** that is fluidly connected to a detergent supply tank **870** by a conduit **314**. Mixed detergent and clean water form a solution that exits the mixing valve assembly **310** via an outlet **340**, which is fluidly connected by a conduit **142** to a pump priming system **280** disposed adjacent the pump **202**. An inlet port **282** for the pump priming system **280** is connected to the conduit **142**, and pressurized fluid is expelled from the pump **202** through a pump outlet port **283**, which is fluidly connected via a conduit **146** to a T-connector **150**. The T-connector **150** supplies pressurized fluid to both the accessory tool (not shown) and the heater **54** via conduits **148**, **138**, respectively. The conduit **148** includes a grip valve **132** by which the user can manually displace a valve member, thereby enabling the flow of non-heated, pressurized fluid to the spray tip on the accessory tool.

The conduit **138** includes a trigger valve **134** having a displaceable valve member actuatable by a trigger assembly **430**, as best shown in FIG. **4**, for selectively supplying the in-line heater **54** with pressurized cleaning solution. The trigger assembly **430** includes a switch **432** mounted conveniently within the closed loop grip **18** of the upright handle assembly **16**, through which the user can depress the switch for actuating a manual link **434** for displacing the valve member in the trigger valve **134**, thereby allowing fluid to flow to the inlet port **72** of the in-line heater **54**.

Heated while passing through the heater **54**, the fluid exits the in-line heater **54** via an outlet port **74**, which is fluidly connected via a conduit **136** to an inlet **652** for a flow indicator **650**. An outlet **654** for the flow indicator is fluidly connected to a T-connector **156** via a conduit **134**. The T-connector **156** supplies fluid dispensing nozzles **100**, which are mounted in the brush housing **26** of the base module **14**, and supplied with heating cleaning solution via conduits **126**, **128**.

A detergent supply tank **870**, as best illustrated in FIG. **3**, is received within a well formed in the upper housing **19** of the base module **14**. The supply tank **870** includes a top surface **872** shaped complimentary to the exterior of the upper housing **17**. A bottom surface **874** of the supply tank **870**, as best shown in FIG. **17**, includes an aperture **876** surrounded by a threaded spout **878**, which receives a mated threaded cap **880** having a valve mechanism **882** there-through. The valve mechanism **882** will not be described here as its structure and function mimics that valve mechanism **80** described above for the tank assembly **50**, as it too seats on a projection **94** in a valve seat **318** for displacing the valve mechanism **882**. The valve seat **318** of the mixing valve assembly **310** includes a fluid reservoir **320** for

receiving and conducting fluid to one end of an L-shaped conduit **314**, the other end being mounted to a detergent inlet **336** of the mixing valve assembly **310**. The threaded cap **880** also includes an air return conduit **890** mounted there-through for equalizing the pressure inside the detergent supply tank **870** with the outside atmosphere.

The mixing valve assembly **310** is positioned intermediate the tank assembly **50** and the solution pump **202**. Preferably, the mixing valve **310** is a variable mixing valve to accommodate differing mixtures of detergent and clean water. As seen in FIGS. **10**, **11** and **17**, the variable mixing valve **310** comprises a valve body **330** having a clean water inlet **332** that is fluidly connected to the fluid supply chamber **49** and a detergent inlet **336** that is fluidly connected to a detergent supply tank **870** by the valve seat **318** and, via the fluid reservoir **320**, the L-shaped conduit **314**. The mixed solution outlet **340** is also formed on the valve body **330** and is adapted to conduct the clean water and detergent mixture, i.e., the cleaning solution, from the mixing valve **310** to a fluidly connected pump priming system **280** adjacent the inlet of the pump **202**.

The valve assembly **310** includes an end cap **344** mounting a coaxial plunger **350** in a central body portion **346**. The end cap **344** partially receives a thread **372** of a knob **374** such that the plunger **350** can be raised or lowered in the valve body **346** when the knob **374** is turned.

The plunger **350** includes an annular groove **356** formed in a distal end **276** thereof. The groove **356** is received within an O-ring **358**. The distal end **276** and O-ring **358** are adapted to create a fluid seal inside the circular valve body **346** when the plunger **50** is in its lowermost portion, as shown in FIG. **11**, and define a mixing chamber **360** when the plunger **350** is raised from its lowermost position, as shown in FIG. **10**.

The distal end **276** of the plunger **350** further includes a tapered groove **364**, which is tapered so that the groove has a greater cross-sectional area immediately adjacent the head end **276** than it does a distance spaced upwardly therefrom. The tapered groove is positioned in the detergent inlet **336** opening to control the flow of detergent therethrough. That is, the tapered groove **364** accommodates varying flow rates of detergent from the detergent supply **870**, through the conduit **318**, and through the detergent inlet **336** into the valve body **346**. The lower the plunger **350** is seated in the inlet **336**, the less the area of exposure of the tapered groove **364** in the valve body **346**, thereby limiting the flow of detergent thereto.

The control knob **374** is mounted on an outside wall of the upper housing of the extraction cleaner for controlling the water to detergent ratio in the cleaning solution delivered to the fluid application system **950**. The control knob **374** is mounted adjacent the end cap **344** and includes a thread **372** that is received in a groove **380** of the end cap **344**, so that turning the knob **374** lowers or raises the plunger **350** in the valve body **346**. In a first position shown in FIG. **10**, with the plunger **350** extended upwardly from the valve body **346**, the maximum cross-sectional area of the tapered groove **364** is exposed to define an inlet aperture **382** into the valve body **346**. Therefore, the maximum amount of detergent will be drawn into the valve body **346** to mix with clean water supplied via inlet **332**, and ultimately discharged to the pump assembly **280** and fluid dispensing nozzles **100**. The other extreme position of the plunger **350** lowers the tapered groove **364** from the mixing chamber **360** completely so if there is no aperture **382** and thus no fluid flow communication between the detergent inlet **336** and the valve body

346. Therefore, only water will be directed to the pump assembly 280 and spray tips.

As should be evident, rotation of the threaded knob 374 will provide an infinite number of detergent-to-water mixing ratios between the two extremes described above. In the preferred embodiment, however, the housing adjacent the knob 374 is marked with three concentration indicators: The first indicator is a water only or "rinse" position; second, a maximum detergent-to-water mixing ratio where the tapered groove 364 is fully exposed in the valve body 346; or third, a standard mixing ratio approximately half way between the extremes described previously. Of course, any variation of the indicated concentration positions can be employed by simply rotating the knob 374 to a position between any two indicated positions. The extreme positions are defined by the shape of the length of the thread 372, which includes opposite ends defining a pair of extreme positions for limiting the rotation of the knob 374 relative the cap 344.

In use, the knob 374 is intended to be positioned at the standard mixing ratio position for the vast majority of cleaning operations. When a high-traffic or heavily stained area is encountered, the knob 374 can be rotated to the maximum detergent position. If a clean-water rinsing operation is desired, then the knob 374 can be rotated to the water only position.

As best illustrated in FIG. 17, the mix of detergent and water is delivered via conduit 142 to the inlet port 282 for the pump priming system 280, which is disposed adjacent an inlet nose 288 of the pump 202. Thus, in operation, the drive motor 196 is activated, thereby imparting rotation through the drive shaft 198 to the interim drive shaft 200, and the pump 202 is primed, as will be explained below. Rotation of the interim drive shaft 200 causes the pump 202 to pressurize the fluid received from the fluid supply chamber 49, via the mixing valve assembly 310 and priming assembly 280. Further, rotation of the interim drive shaft 200 causes the agitation brush 206 to rotate. Pressurized fluid flowing from a pump outlet port 283 is conducted to the in-line heater 54, a flow indicator 650, and then a plurality of conventional fluid dispensing nozzles 100 provided near the front of the base module 14 adjacent the agitation brush 206. The pressurized cleaning solution sprays down onto the surface to be cleaned in a fan-shaped pattern extending substantially the entire width of the base module 14. A fluid outlet port 74 of the in-line heater 54 is also fluidly connected to a conduit 144, which is integrated into the accessory hose 22. Fluid flows through the conduit 144 to the accessory hose cleaning tool (not shown) provided at the terminal end of the hose 22. With this configuration, pressurized cleaning solution is available on demand for both the accessory cleaning tool and the fluid dispensing nozzles 100.

Referring to FIGS. 2, 5 and 6, the drive shaft 198 of the drive motor 196 is interconnected to the interim drive shaft 200 of the centrifugal solution pump 202 by the stretch belt 204, which allows dry, high speed operation and operates as a clutch during brush roll-jam conditions. The interim pump shaft 200 is interconnected to the rotatably mounted agitation brush 206 by the timing belt 208, which allows a slower, high torque wet operation.

The interim pump drive shaft 200 functions as an interim drive providing a step down from the drive shaft 198 to the stretch belt 204 and the timing belt 208 to the agitation brush 206. Because of the step down structure, the drive motor 196 can be a high efficiency, high speed motor (30,000 plus rpm), which is stepped down at the interim drive pump shaft (approximately 12,000 rpm), and further stepped down at the agitation brush 206 (approximately 3,500 rpm).

The pump shaft 200 includes the pair of coaxial spaced-apart pulleys 220, 222, as best seen in FIGS. 2, 8-9, for receiving each respective belt 204, 208, with a radially extending baffle 218 disposed between the pulleys so that the inwardly disposed stretch belt 204 is insulated from the wet environment in which the outwardly disposed timing belt 208 operates to drive the agitation brush 206. A barrier coplanar with the radial baffle 218 insulates the environments from each other as formed by the juncture of a pair of belt access doors 250, 252, as will be described below. The stretch belt 204 also functions as a clutch when the agitation brush 206 is jammed. Because the agitation brush 206 is connected to the interim pump drive shaft, and the interim pump drive shaft 200 is connected to the motor drive shaft 198, there must be some mechanism to provide relief to the motor 196 when the agitation brush 206 is jammed. This relief occurs at the drive shaft 198, which will turn inside the stretch belt 204 without rotating the stretch belt 204 when the interim pump shaft 200 stalls due to an agitation brush 206 jam.

As best shown in FIGS. 5-9, the timing belt 208 is structurally walled off from the stretch belt 204 by the barrier defined in part by the first belt access door 250, second access door 252, and the baffle 218. Removing the first belt access door 250 provides access to the timing belt 208 connecting the pump drive shaft 202 and the agitation brush 206. Access to the stretch belt 204 connecting the motor drive shaft 198 to the pump drive shaft 202 is provided only when the second belt access door 252, disposed within a brush housing 26, is removed. As illustrated in FIG. 2, the first belt access door 250, having a substantially L-shaped cross-section, includes a substantially vertical portion 266 and an angular, but substantially horizontal portion 264. As best shown in FIG. 9, the second belt access door 252 is rectangular, including an arcuate groove 254 in a front portion of a top surface 256 and a transversely extending arm 258 in a rear portion of the top surface. The arm 258 secures the second door 252 in place in the brush housing 26 and supports the pivot pin 462 on the pivot arm 460 of the floating brush assembly, as best shown in FIG. 5A.

More specifically, as shown in FIG. 2, the substantially vertical portion 266 of the first door 250 includes sides 240 that are received in a mated recess 242 surrounding an access aperture 236. Further, the first door 250 includes a depending flange 234 mounted to and spaced apart from a back portion of the door 250 and extending downwardly parallel to the door 250 and further including an arcuate groove 244 in a lower end. Each side of the substantially horizontal portion 264 includes a flexible tab 226 on each side that is received in a respective slot 228 disposed on the substantially horizontal face 222 of the upper housing 17 at each end of the access aperture 236 that receives the first belt access door 250. Thus, as the first belt access door 250 is slid into place, the depending flange 234 extends behind the upper housing 17 defining the access aperture 236, the sides are received in grooves 242 in the upper housing 17 surrounding access aperture 236, and the tabs 226 engage the slots 228 formed on the substantially horizontal portion 248 of the housing, whereby the first access door 250 is secured in place. The first access door 250 can be removed from the aperture 236 by flexing the tabs 226 inwardly to release them from their receiving slots 228. As shown in FIG. 9, the inner depending flange 234, including groove 244, mates with the radially extending baffle 218 between the pulleys 220, 222 on the shaft 200 and the arcuate groove 254 in the arm 258 of the second belt access door 252 to separate the motor/pump stretch belt 204 from the pump/agitator timing belt 208.

The pump priming system **280** is disposed adjacent the pump inlet nose **288**, and draws from the fluid supply chamber **49** and the detergent tank **870**. The fluid supply chamber **49** is under negative pressure because it is in fluid communication with the recovery chamber **48** and the vacuum source. Once primed, the pump **202** draws solution from the mixing valve assembly **310**, and delivers the mixture to a spray tip **100** or an accessory tool **44** for spraying on the surface to be cleaned. When the pump **202** stops, the solution in the supply conduit is drawn into the low-pressure fluid supply chamber **49** and away from the pump **202**. A centrifugal pump is incapable of developing sufficient pressure to prime itself by overcoming the negative tank pressure.

With reference to FIG. 7, a pump priming assembly **280** as described herein overcomes this problem. The pump-priming assembly **280**, includes a priming chamber **260** for flooding the inlet nose **288** of the pump **202**, an inlet port **282** for the chamber **260** that is fluidly connected to the nose **288** of the pump **202**, and a pump outlet port **283**. A vacuum port **284** is fluidly connected to the vacuum source **40**, or a portion of the recovery chamber **48** that is in fluid communication with the vacuum source **40**.

The pump-priming assembly **280** also includes a hollow valve body **298** having a plunger chamber **286** and a valve chamber **292**. A valved opening **295** joins the valve chamber **292** and the priming chamber **260**. An outlet opening **291** joins the valve chamber **292** and the plunger chamber **286**. Also, an aperture **294** is formed at an upper inside portion of the valve body **298** to fluidly connect the valve body **298** and the outlet **284**. An elongate buoyant plunger **290** having a top portion **297** at one end and a rubber umbrella valve **296** at the other is received for reciprocal movement inside the valve body **298**. More specifically, the umbrella valve **296** reciprocates between the valved opening **295** and the outlet opening **291** and within the valve chamber **292**. Thus, the plunger chamber **286** substantially houses the elongate plunger **290**, while the valve chamber **292** houses the umbrella valve **296**, which is coaxially attached to the elongate plunger **290** for reciprocal axial movement therewith.

In operation, the pump **202** will be primed with fluid from the fluid supply chamber **49** by activating the pump **202** and the vacuum motor **196**, which will exert negative pressure on the vacuum outlet **284**, thereby drawing any air out of the priming chamber **260** and plunger chamber **286**, and further overcoming the negative pressure exerted on the fluid in the conduits **140**, **142** connecting the fluid supply chamber **49** to the pump **202**. The air will be drawn through the valve body **298** into the vacuum impeller fan housing **510**. Preferably, the weight and dimension of the plunger **290** is coordinated with the amount of negative air pressure applied to the pump priming assembly **280** from the vacuum source **40** so that the negative air pressure applied to the plunger chamber **286** is insufficient by itself to draw the plunger **290** upwardly and seal the outlet opening **291**.

As the vacuum motor operates to draw the air from the system, fluid fills the chamber **260** and enters the chambers **292**, **286**. Eventually, the fluid level will fill the valve chamber **292** and rise inside the plunger chamber **286**, pushing the plunger **290** upwardly causing the umbrella valve **296** to seal the outlet opening **291**, thereby preventing water from rising further in the plunger chamber **286** and being sucked into the vacuum source **40**. Because the pump nose **288** is submersed at this point, water enters the pump **202** and primes it. As the pump **202** sucks water from the priming chamber **260**, the plunger **290** is drawn downward

in the plunger chamber **286**, and the umbrella valve **296** descends therewith in the valve chamber **292** to activate a seal in the opposite direction, as the umbrella valve **296** seats in the valved opening **295**. The reverse seal prevents air from being sucked into the priming chamber **260** from the fluidly connected chambers **292**, **286**. This cycle repeats each time a trigger **432** in the closed loop handle **18** is activated or the unit is powered off and on again. Once the reverse seal has been established, the chamber **260** should remain filled, the nose **288** of the pump **202** flooded, and, thus, the pump **202** sufficiently primed for normal operation.

From the pump **202**, the pressurized fluid flows through a conduit **146** to a T-connector **150** for supplying both floor nozzles **100** and an accessory tool **44**. The T-connector **150** includes outlets **152**, **154** for supplying both the in-line block heater **54**, and a floor spray nozzle **64**, or an accessory cleaning tool **44**, respectively. Specifically, the first outlet **152** of the T-connector **150** is connected to fluid conduit **148** that is adapted to supply non-heated and pressurized cleaning solution to a spray nozzle (not shown) on an accessory cleaning tool (not shown) mounted at the terminal end of the accessory hose **22**. The second outlet **154** is fluidly connected via a conduit **138** to the in-line block heater **54**, shown best in FIG. **18**.

The in-line block heater **54** receives pressurized cleaning solution from the pump **202**, via the T-connected **150**, and further has a heating element **56** that is electrically connected to a source of electricity (not shown). As shown in FIG. **18**, the heater **54** includes an aluminum body **84** having an inlet port **72**, an outlet port **74**, a heating element **56** disposed within the aluminum body **84**, and a serpentine channel **78** disposed on a top face **76** of the block heater **54**. A cover **79**, via a gasket **70** seals the top face **76**, and thus the channel **78**, and fasteners **86**. The heating elements **56** located in the aluminum body **84** of the block heater **54** uniformly heat the fluid as it passes through the channel **78** across the block heater **54**. The channel **78** includes an outlet port **74** through which heated fluid exits the channel **78** to the conduit **136**. The heater **54** is mounted within the handle assembly **16** via shafts **71** and plugs **73** to bosses (not shown) in the handle assembly **16**.

The size of the aluminum body **84** and the heating elements **56** are selected to effectively deliver approximately 500 watts of power to the heating block **54** to heat the cleaning fluid in the serpentine channel **78** to a temperature of about 150–180° during the dry cycle of the cleaner and apply that heated cleaning fluid during the wet cycle, as will be described more completely below. Use of approximately 500 watts of power for the heater **54** leaves sufficient power from a convention 120 volt power line for the vacuum motor, agitation brush and pump while beating the solution to the target temperature with a minimal warm-up time of approximately one minute. To enhance this process, hot lap water (defined as approximately 110–120° Fahrenheit) can be dispensed into the reservoir from a household tap. The solution that passes through the in-line block heater **54** is heated approximately 30° to 35° to reach a target temperature of approximately 150° Fahrenheit. A thermostatic controller is preferably mounted to a face of the heater **54** to limit the block temperature to 180° F. The solution that passes to the upholstery attachments does not get the temperature boost. A non-heated solution is preferred for upholstery, which is more sensitive to heat damage.

Powered by approximately 500 watts, the in-line block heater **54** will boost the temperature of water 16° Fahrenheit on a continuous basis at 850 milliliters a minute. Since an approximately 30° temperature increase is desired, it is

necessary to store heat energy in the aluminum body **84** of the in-line heater block **54** during the dry cycle and deliver it to the solution during the wet cycle. The recommended cleaning process with the extraction cleaning machine **12** described herein is two wet strokes, defined as movement of the extraction cleaning machine **12** while cleaning solution is sprayed from the nozzles **100** to the carpet being cleaned, followed by two dry strokes, defined as cleaning solution and dirt removal through the suction action of the suction nozzle **34**. There is thus an opportunity to effectively deliver 1000 watts of heat energy to the solution by storing 500 watts during the dry cycle. Furthermore, a typical cleaning stroke is about 10 seconds maximum, so the heat reservoir must have the capacity to store 500 watts for approximately 20 seconds, which equals approximately 10,000 Joules of energy.

The heating element **56** is embedded into the aluminum body **84**, which is of ample mass to store the energy at some temperature below the boiling point of water (212° Fahrenheit). The larger the mass of aluminum, the smaller the differential temperature needs to be to store the required energy. On the other hand, the larger the mass, the longer the initial heat-up period becomes. Thus, there is an optimal size of aluminum block that is calculated based on a thermostat shut-off point of 180° Fahrenheit. This block temperature keeps stagnant water from boiling and also heats the solution that passes through the serpentine channels **78** on the block face **76** to a temperature of approximately 150° Fahrenheit before leaving the in-line block heater **54** through outlet port **74**.

In operation, when the heater **54** is initially energized electrically, it heats to its thermostatically controlled shut-off temperature in approximately one minute. A thermostat **92** is included on a lower face **108** of the body **84**. During use, the cleaning solution passes through the heating channel **78** in the in-line block heater **54**, drawing energy from the aluminum body **84** and from the heating element **56** embedded therein adjacent the underside of the solution channel **78**. The aluminum body **84** cools somewhat during the 20 second cycle and reaches a temperature slightly below its starting temperature. During the dry cycle, the aluminum body **84** is reheated to its previous temperature of approximately 180° Fahrenheit. The heated solution leaving the in-line block heater **54** is applied to the carpet after passing through the conduit **136** to the flow indicator **650**, and the conduit **134** from the indicator **650** to the fluid dispensing nozzle **100**, which are positioned between the agitation brush **206** and the suction nozzle **34**.

The flow indicator **650** is placed in the fluid flow path to provide a visible indication of fluid flow to the fluid dispensing nozzles **100**. As shown in FIGS. **19** and **20**, the flow indicator **650** is mounted to an upper end of the arm **651**, which extends upwardly from the motor housing **500** in the base module **14**. An opening **653** in the upper housing portion **17** receives the flow indicator **650** when that portion is mounted to the lower housing portion **15**. Alternatively, the flow indicator **650** can be mounted to the handle assembly **16** in a position to be easily viewed by the operator. The flow indicator **650** comprises a circular body **660** having an inlet **652**, outlet **654**, and a clear lid **662** having a threaded lip **670**. As seen in FIG. **20**, the indicator body **660** preferably houses an impeller **664** superjacent a screen filter **666**, both of which are superjacent the fluid inlet **652** and the fluid outlet **654**. The fluid inlet **652** is near the periphery of the body **660** and the outlet **654** is disposed centrally. The lid **662** has threads **670** on the outside of the body **660**.

The lid **662** is clear, preferably made from the transparent plastic, so that the user can see the fluid flowing into the

indicator **650** and rotating the impeller **664**. Alternatively, one or more articles, such as a ball or disk can be mounted within the indicator body **660** and subjacent the lid **662**, whereby the operator can determine if there is fluid flow by movement of the article. Further, while a body **660** mounting an impeller **664** is the preferred flow indicator, other suitable indicators include a float ball, spring plunger, or gravity plunger.

A float ball-type flow indicator can include a flow conduit having a T-shaped portion having a transversely oriented tube extending from a cylindrical body defining the fluid flow path. A ball or other article can be mounted at the junction of the transverse tube and cylindrical body for reciprocation within the transverse tube. When fluid is flowing through the cylindrical body, the ball or article moves into the transversely oriented tube, whereupon it is visible to the operator and indicates proper fluid flow.

A spring plunger-type flow indicator can include a light spring to bias a ball, plunger, or other article in a housing having a window visible to the operator. With fluid flowing through the housing, the ball, plunger, or other article moves against the bias of the spring to become visible in the window, thereby indicating to the operator that fluid is flowing properly. Alternatively, the ball, plunger, or other article can always be partially visible, and include portions corresponding to proper fluid flow, such as green for proper fluid flow and red for no fluid flow, whereby fluid flow causing movement of the ball, plunger, or other article against the spring bias would change the portion of the ball, plunger, or other article visible to the operator through the window, thereby indicating proper fluid flow.

A gravity plunger-type flow indicator can include a housing having a ball or other article mounted on a ramp adjacent a window. As fluid flows through the housing, the ball or other article is forced up the ramp, whereby it is visible to the operator to indicate proper fluid flow. Alternatively, like that for the spring plunger, a portion of the ball or other article previously not visible through the window can be visible when fluid flows through the housing to indicate to the operator that fluid flow is proper.

After pressurized fluid leaves the in-line heater **54**, it enters the inlet **652** of the flow indicator **650** under pressure, such that it causes the impeller **664** to rotate in a clockwise direction as pictured in FIG. **20**. The fluid rotates the impeller **664** until it reaches the center of the body **660**, where it is forced through the screen filter **666** and outlet **654** by the continuous flow of pressurized fluid into the flow indicator body **660**.

The screen filter **666** prevents any debris from exiting the flow indicator **650**. Any debris trapped by the screen filter **666** remains visible to the operator through the lid **662**. The operator can simply clean the flow indicator **650** by removing the threaded lid **662** and lifting the screen filter **666** from within the body **660** for cleaning. The screen filter **666** preferably includes apertures defined by the screen of a diameter smaller than the diameter a passageway through the spray nozzle **64**. This is of particular importance if the spray nozzle is not easily serviceable by the operator or a service provider. Further, when using an in-line heater **54**, a screen filter **666** is a precaution against plugging the passageway through the spray nozzle **64** from scales forming in the heater **54**.

After the cleaning solution has been applied to the surface to be cleaned via the spray nozzle **64**, or multiple spray nozzles **64**, the used cleaning solution and entrapped dirt are removed from the surface being cleaned through the suction

nozzle 34, which opens into the first working air conduit 704 extending along the top of the base module 14 between the upper housing portion 17 and the transport facing 19, as best shown in FIGS. 2, 12 and 13. The first working air conduit 704 terminates at a junction 740 with the second working air conduit 706, which is defined by passageway communicating the vacuum source 40 with the suction nozzle (not shown) on the distal end of the accessory hose 22. With this configuration, the drive motor 196 creates the vacuum source 40 that is applied to the surface being cleaned through either working air conduit 704, 706.

The terminal end of the accessory hose 22 is secured to a hose mounting 702 at a distal end of the accessory hose intake duct 540 partially defining the second working air conduit 706, which extends, in a U-shape, to the junction 740 with the working air conduit 704, as best seen in FIGS. 1 and 12. A flapper valve 114 pivots at the junction 740, disposed in the base module 14, to alternatively close the first working air conduit 704, between the suction nozzle 34 and the air/water separator lid 700, and the second working air conduit 706 between the hose mounting 702 and the air/water separator lid 700, as best shown in FIGS. 12 and 14. The valve 114 seats on a gasket 113 about the junction 740. When the user is cleaning floors, the flapper valve 114 is in position to direct all of the working air generated by the vacuum source 40 to the suction nozzle 34. However, when the user desires to use the accessory hose 22, the flapper valve 114 is pivoted to an accessory hose position, as shown in phantom lines in FIG. 12. In this position, the flapper valve 114 seals the working air conduit 704 and connects the accessory hose 22 to the vacuum source 40. Regardless of whether the machine is operating for on-the-floor cleaning or accessory hose cleaning, all of the dirt and water recovered are directed into the recovery chamber 48.

An over-center diverter valve assembly 110 including a movable flapper valve 114 in the junction 740 between working air conduits 704, 706, and actuable by an actuator knob 180, on the extraction cleaner housing controls the diversion between the conduits 704, 706. More specifically, the actuator knob 180 to flapper valve 114 linkage assembly, as shown best in FIGS. 12 and 13, includes an arm 160 attached at an upper end to the flapper valve 114, which includes a transversely extending support axle 162, and at a lower end to a cup-shaped bearing 170 on the end of a piston 172. The support axle 162 is mounted for rotation in the junction 740 between the working air conduits 704, 706, whereupon the valve can pivot between two extreme positions, as shown in FIG. 12. At a lower end, the arm 160 ends in a transversely extending leg 164, which moves relative the center of the actuator knob 180 depending on the position of the actuator knob 180 when turned by the user.

The actuator knob 180 includes a handle 184, and a piston assembly 190 on a back face. The piston assembly 190 includes piston housing 176, piston 172, and a compression spring 174. The piston 172 slides coaxially in the housing 176, and is biased upwardly by the spring 174 mounted therein. Specifically, the spring 174 biases the piston 172 out of an opening 196 in a top portion of a tubular piston housing 176.

When the actuator knob 180 is turned by the user, the lower leg 164 moves closer or farther from the knob rotation axis, thereby increasing or decreasing the distance between the lower leg 164 and the axis. As this distance increases, the spring-biased piston 172 forces the lower leg 164 upwardly. The arcuate path of the lower leg 164 as it travels over the center of the knob axis rotation imparts rotation to the flapper valve 114 about the fixed support axle 162. The

rotation is in response to the changed distance of the mounting of the piston assembly 190 from the actuator knob 180 rotation center. As it moves away from the center, the piston 172 expands at an angle relative to the support axle 162. The lower leg 164 of the L-shaped arm 160 must rotate in the cupshaped bearing 170 at the end of the piston 172 because the axle 162 is fixed. Thus, the flapper valve 114 rotates in response to the angle of the joint between the expanded piston 172 and the lower leg 164 (not shown). Tabs formed on the back face of the knob 180 limit the rotation of the knob so as to effectively define two positions correlating to the open conduit 704/closed conduit 706 position and the open conduit 706/closed conduit 704 positions.

The diverter valve assembly 110 described above permits the upright extraction cleaner fluid dispensing mechanism to be used as a pre-spray applicator. That is, by diverting the suction to the accessory hose 22, and applying solution through the fluid dispensing nozzles 100 adjacent the agitation brush 206, the upright extraction cleaner 12 can be used to dispense fluid and agitate the carpet without having the applied solution immediately extracted from the carpet through the suction nozzle 34 adjacent the agitation brush 206 and fluid dispensing nozzles 100. Thus, the fluid application system 950 remains operable regardless of the position of the flapper valve 114.

As best seen in FIGS. 12-14, 14A and 14B, the working air conduit 704 terminates at the junction 740 with the working air conduit 706. The junction 740 connects the selected conduit 704, 706 to a U-shaped inlet 780 to the air/water separator lid 700, which is secured to the tank assembly 50 by the rotatable handle 790. Thus, from the U-shaped inlet 780 to the air inlet 764, the air path entering the lid 700, as shown in FIG. 14, is substantially horizontal.

From the tank air inlet 764, the air/water/debris mixture is conducted into a center portion of a tank lid separation chamber 750, where the cross sectional area is greater than the flow conduits 704, 706, junction 740, and inlets 780, 764 to slow down the velocity of the air stream for gravity separation of the air from the liquid, dirt and debris. Because the lid 700 is formed of a transparent plastic material, the user can easily observe the dirt and water passing up through the intermediate flow conduit and the fluid level inside the tank assembly 50.

The substantially rectangular chamber 750 is defined by a transparent lower portion 752 substantially surrounded on all sides by a transparent side wall integral with the underside of the air/water separation lid 700. The chamber 750 is further defined upwardly by a transparent face 756 of the lid 700. The air inlet opening 764 is disposed adjacent an air outlet opening 776. The underside of the face 756 further includes a circular downwardly extending shroud 770 adapted to surround in part the open flexible bladder filling spout 124, which is retained by the baffle plate 800 and positioned adjacent the separation chamber 750.

The working air flow enters the hollow interior of the separation chamber 750 via the air and water inlet 764 and passes horizontally beneath the transparent face 756 to a rear wall defining a first diverter baffle 755 at which it is redirected 180° forwardly through an opening 751 to a rectangular, extended outlet passage 757 formed in a lower, intermediately disposed portion of the bottom wall 752 at which it is again redirected 180° by a second diverter baffle 759 defined by a front wall disposed forward, transverse, and beneath the opening 751. The air flow then exits the separation chamber 750 through an inlet outlet 760, whose

position is dictated by tank geometry, as the preferred position is a "dead spot" in tank air flow to maximize air/water separation. From here, the water is directed into the interior of the tank between the **750** and the baffle **800**, and away from the separation chamber **750** to the air exit **762**. It is significant that all air/water separation occurs above the baffle plate **800**, thus minimizing interference with the recovered water (i.e., no foaming) in the area disposed below the baffle plate **800**. This characteristic is necessitated by the inclusion of a flexible bladder disposed in the tank recovery chamber.

In summary, air and water enters the inlet **764**, from where it is channeled to the air/water separation chamber **750** in which it strikes the first diverter baffle **755**, is redirected approximately 180° and through the opening **751** to the outlet passage **757**, where it is again redirected approximately 180° by second diverter baffle **759**, and then passes into the interior of the recovery chamber **48**. The multiple changes in direction as well as the expansion in volume in the separation chamber **750** facilitate the separation of water and debris from the air. As best seen in FIG. **14**, the air, free of water and debris, exits the tank via rectangular outlet **762**, and traverses a horizontal conduit **774** to a vertical exit conduit **776**, which is disposed adjacent the horizontal inlet **780** leading air into the separation lid **700** via air inlet opening **764**. Thus, the air inlet **780** and air exit conduit **776** are vertically adjacent. The air exit conduit **776** feeds the vacuum intake duct **530**, which is connected to the vacuum source **40**, as best seen in FIGS. **2** and **15**.

As best shown in FIGS. **3**, a fluid containment baffle **800** is mounted inside the hollow interior of the tank assembly **50** immediately below the separation lid **700**, and is intended to prevent the excessive sloshing of the recovered dirt and liquid and also contain any foam generated inside the tank assembly **50**. The planar baffle **800** comprises a flat body **810** mated to snap fit within the tank housing **46**. Further, apertures **820** are formed through the plate **800** for receiving the recovered fluid into the recovery chamber **48** of the tank assembly **50**. A circular aperture **826** retains the bladder filling spout **124** in position by preventing it from floating upwardly in the tank and further locking the bladder in place while giving it mechanical support.

The baffle plate **800** is snapped into place by retainers **830** that are received on tabs **836** formed on the interior of tank housing **46** to secure the baffle plate **800** in the tank assembly **50**. The apertures are centrally mounted in the baffle plate **800** to prevent air movement, while facilitating fluid and debris deposits, into a lower portion of tank assembly **50** so that the recovered fluid remains undisturbed. Further, the baffle plate **800** is closed at the edges to prevent sloshing of the recovered fluid into an upper portion of the tank assembly **50** during movement of the cleaning machine **12**.

As shown best in FIGS. **14** and **14A**, a float assembly **900** extends through the baffle plate **800** for moving an integral door across the exit port of the tank to prevent recovered solution from entering the tank exhaust in an overflow condition. As best shown in FIG. **3**, the flag-shaped float assembly **900** comprises a buoyant base **902** and a closure plate **904** interconnected to one another by a support plate **906**. The closure plate **904** is dimensioned to fully seal the air exit **762** to the tank to prevent recovered solution from entering the tank exhaust in an overflow condition as illustrated in phantom lines in FIG. **14A**. The closure plate **904** further includes a pair of triangular projections **905** extending transversely from a substantially vertical front face. The front face engages the wall **768** defining the air exit **762** from

the tank, and the projections **905** cam along that wall **768** to prevent premature and partial closing of the exit **762** as the plate **904** is drawn against the exit by the suction there-through.

The float assembly **900** is limited primarily to vertical movement with respect to the tank assembly **50**, with the closure plate **904** positioned above the fluid containment baffle **800** and the buoyant base **902** positioned below the baffle **800**. A narrow slot **920** is provided in a front portion of the baffle **800** through which the support plate **906** of the float extends. Further, a housing **910** secured to the interior of the tank housing **46** guides the buoyant base, and thus the float assembly **900**, in a vertical direction. In the assembled position, the closure plate **904** is positioned above the baffle **800** and the buoyant base **902** is positioned below the baffle **800**.

As the recovered fluid within the tank assembly **50** rises, the float assembly **900** will also rise until, eventually, the closure plate **904** nears the tank exhaust exit opening, at which point the closure plate **904** is sufficiently drawn against the exit **762** opening by the suction from the vacuum motor to close the airflow therethrough. As discussed above and illustrated in FIG. **14A**, the triangular projection **905** extending from the front face **907** ensure the closure plate is not drawn against the exit **762** prematurely, which would result in a partial closure of the opening. Rather, the projections **905** ride the housing defining the opening until drawn into total closure of the exit **762**. Once this happens, the pitch of the operating vacuum changes sufficiently to warn the user that the fluid recovery chamber **48** is full and must be emptied.

As best shown in FIG. **3**, a drain plug **850** seals an aperture through a wall in a lower portion of the rigid housing **46** of the tank assembly **50** through which recovered fluid can be removed without tipping the tank assembly **50**, and also through which the tank assembly **50** can be cleaned by flow-through rinsing. More specifically, a rounded wall of the rigid tank housing **46** includes the drain plug **850** mounted in an aperture **854**. A bottom portion of the aperture **854** is substantially planar with a bottom wall **860** of the tank housing **46**. Thus, any recovered fluid will flow through the aperture **854** when the drain plug **850** is removed therefrom. Further, the tank assembly **50** can be cleaned without having to tip the tank assembly **50** since the drain plug **850** can be removed for flow-through rinsing. This feature is particularly important because the flexible bladder **120** defining the fluid supply chamber **49** remains in place while the recovered fluid is drained from the recovery chamber **48**. The drain plug **850** eases cleaning of both the interior of the rigid housing **46** and the exterior of the flexible bladder **120**.

As best shown in FIGS. **21** and **22**, the drain plug **850** comprises a knob **851** extending through a circular washer **856** which mounts two resilient legs **853**. The resilient legs **853** are located diametrically on a lower face of the washer **856** and comprise, on an outer face of each leg **853**, an upper ridged protrusion **857** and a lower ridged protrusion **858**. The lower ridged protrusion **857** is rounded so that it forms a detent mechanism with the opening in the tank wall. The upper ridged protrusion **857** has a slanted outer surface so that the legs are resiliently deflected as the drain plug is installed into the aperture **854**, and has a sharp return inner surface so that the return inner surface will bear against the inner surface of the wall of the tank housing as the drain plug **850** is pulled outwardly of the tank. Thus, the drain plug is easily installed into the aperture **854**, but is retained therein by the inner surface when the plug is removed from the aperture **854** for draining the tank. In the normal, closed

position of the drain plug **850**, the lower face of the washer **856** abuts the rear wall of the tank housing **46**. The drain plug further has a pair of retaining flanges **859** which fit behind the wall of the tank adjacent the aperture **854**. To this end the aperture has indented slots to receive the flanges **859**. The To drain fluid through the aperture **854**, the drain plug **850** is rotated a quarter turn counterclockwise and pulled toward the rear of the upright extraction cleaning machine **12** a suitable distance such that the upper ridged protrusion **857** of the resilient legs **853** moves past the rear wall of the tank housing **46** and the lower ridged protrusion **858** of the resilient legs **853** abuts the inner wall of the tank housing **46**. The diameter of the aperture **854** is less than the normal distance between the resilient legs **853** so that the legs **853** are pressed inwardly and thereby prevent the drain plug **850** from separating from the tank housing **46**. The drain plug **850** is restored to its normal, closed position by pressing the drain plug **850** toward the front of the upright extraction cleaning machine **12** to cause the washer **856** to abut the rear of the tank housing **46** and turning the drain plug **850** one-quarter turn clockwise.

In use, the operator removes the tank assembly **50** from the well **36** in the base module **14**, and further removes the lid **750** from the tank housing **46** to expose the open filling spout **124** of the flexible bladder **120**, whereupon the bladder **120** can be filled with water from a source such as a household tap. Next, the user replaces the lid **750** and swings the handle **790** upwardly to seal the lid **750** to the tank housing **46**, whereupon the tank assembly **50** can be carried to the well **36** of the base module **14** and replaced therein for use. Upon replacement, the valve member **82** in the valve mechanism **80** mounted in the bottom surface **862** of the tank housing **46** is displaced by the projection **94** in the valve seat **88**, whereupon the clean water in the fluid supply chamber **49** is in fluid communication with the fluid application system **950**. The detergent supply tank **870** is removed from its well **884**, and then its cap **880** is removed so that the tank **870** can be filled with concentrated detergent. Once the supply tank **870** is filled and the cap **880** is replaced thereon, the supply tank **870** is replaced in its well **884**, whereupon its valve mechanism **882** permits the flow of concentrated detergent through the conduit **318** to the mixing valve assembly **310**.

The extraction cleaning machine **12** can then be powered by activating an main power switch **534** disposed on the handle assembly **16**, whereby the motor **196** is activated, and the vacuum source **40** for the working air flow conduits **704**, **708** are operable. Further, the heater **54** is separately operable by a heater power switch **536** when the main power switch **534** is in the "on" position. The user then supplies pressurized cleaning solution to the agitation brush **206** by depressing the switch **432** in the closed loop grip **18**, whereupon solution flows to and through the fluid dispensing nozzles **100**. As the user applies cleaning fluid and agitates the surface being cleaned with the brush **206**, the user pushes the cleaning machine **12** forward and rearward, with the forward strokes being defined as wet cycles and the rearward strokes being defined as dry cycles. During the wet cycles, the cleaning solution is applied to the surface via the fluid dispensing nozzles **100** and the agitation brush **206** scrubs the subjacent surface. During the dry cycles, the suction nozzle **34** removes applied solution, as well as dirt and debris, from the surface being cleaned and carries it to the recovery chamber **49** via the working air conduit **704**.

The cleaning machine **12** can also be used as a pre-spray applicator and agitator by simply diverting the air from working air conduit **704** to the working air conduit **708**,

which connects the vacuum source **40** to the accessory hose **22**. In this use, the accessory hose **22** functions solely as a bypass aperture for the working air supplied by the vacuum source **40**. Thus, fluid is applied via the fluid dispensing nozzles **100** and agitated into the surface being cleaned by the brush **206**, but there is no suction at the suction nozzle **34**, and thus no dry cycle. When the solution has been adequately applied and the surface adequately agitated, the user can divert suction back to the working air conduit **704**, whereupon the applied solution and other debris can be removed from the surface without application of solution, which is controlled by the user through trigger **432**.

To use the accessory cleaning tool (not shown), the user diverts working air flow from the conduit **704** to the conduit **708**, whereupon the accessory hose **22** is fluidly connected to the vacuum source **40**. Furthermore, the user can apply pressurized cleaning fluid to the surface to be cleaned by pressing the grip valve **132** on the accessory cleaning tool. In sum, cleaning solution can be applied by actuating the grip valve **132** and removed via the suction nozzle (not shown) in communication with the vacuum source **40** via the working conduit **708**. Also, the accessory tool may further include an agitation brush driven by an impeller that is driven by ambient air drawn through an aperture distinct from the suction nozzle in the accessory tool, but towards the same vacuum source **40**.

Once the surfaces have been cleaned, or the recovery chamber **48** has become filled and the float assembly **900** has blocked the air exit **762** from the air/water separator lid **750**, power to the cleaning machine **12** is turned off and the tank assembly **50** is removed from the well in the base module **14** and carried by its handle **790**, which seals the lid **750** to the tank housing **46**, and carried to a point of disposal, such as a sink drain, whereupon the contents of the recovery chamber **48** can be emptied by removing the drain plug **850** from the aperture **854** through wall **852**. Once removed, the contents of the recovery chamber **48** flow through the aperture **854**. Furthermore, the tank assembly **50** can be rinsed with clean water, which also flows through the aperture **854** in the wall **852** of the tank housing **46**.

While particular embodiments of the invention have been shown, it will be understood, of course, that the invention is not limited thereto since modifications may be made by those skilled in the art, particularly in light of the foregoing teachings. Reasonable variation and modification are possible within the scope of the foregoing disclosure of the invention without departing from the spirit of the invention.

What is claimed is:

1. A portable surface cleaning apparatus, comprising:
 - a base module for movement along a surface and having a front portion and a rear portion;
 - a brush assembly having an agitation brush generally disposed in the front portion of the base module and a pivot arm for pivotally supporting the agitation brush relative to the base module;
 - a first end of the pivot arm is mounted to the agitation brush and a second end of the pivot arm is pivotally mounted to the base module, whereby the brush assembly is free floating to adjust to different surface heights;
 - a handle pivotally attached to the rear portion of the base module for movement between an upright position and an inclined position, and including a lower portion having an outer surface;
 - a fluid recovery system comprising:
 - a tank on the base module having a fluid recovery chamber for holding recovered fluid;

a suction nozzle associated with the base module;
 a working air conduit extending between the recovery chamber and the suction nozzle;
 a vacuum source in fluid communication with the recovery chamber for generating a flow of working air from the nozzle through the working air conduit and through the recovery chamber to thereby draw dirty liquid from the surface to be cleaned through the nozzle and working air conduit and into the recovery chamber;
 a liquid dispensing system comprising:
 a liquid dispensing nozzle;
 a fluid supply chamber for holding a predetermined amount of supply fluid;
 a fluid supply conduit fluidly connected to the fluid supply chamber and to the dispensing nozzle for supplying liquid to the dispensing nozzle; the improvement comprising:
 an elevator assembly including an elevator arm reciprocally mounted to the base module and movable between rear and forward positions in response to movement of the upright handle from the inclined position to the upright position;
 a first end of the elevator arm is disposed adjacent the pivot arm and is adapted to lift the pivot arm from the surface as the elevator assembly moves between the rear and forward positions and a second end of the arm is engagable with the handle for moving the elevator assembly between the rear and forward positions as the handle moves between the inclined and upright positions;
 whereby pivoting the upright handle from the inclined position to the upright position is translated into movement of the agitation brush away from the surface to be cleaned.

2. A portable surface cleaning apparatus according to claim 1 wherein the first end of the elevator arm has a lifting surface for upwardly pivoting the pivot arm and the lifting surface is a ramp that slides along a bottom surface of the pivot arm.

3. A portable surface cleaning apparatus according to claim 2 and further comprising a spring that biases the elevator arm toward the handle.

4. A portable surface cleaning apparatus according to claim 3 wherein the second end of the elevator arm abuts the outer surface of the lower portion of the handle in the upright position.

5. A portable surface cleaning apparatus according to claim 1 wherein the agitation brush is pivotally mounted to the first end of the elevator arm.

6. A portable surface cleaning apparatus, comprising:
 a base module for movement along a surface to be cleaned and having a front portion and a rear portion;
 a brush assembly having an agitation brush generally disposed in the front portion of the base module for contact with the surface to be cleaned and a support arm for supporting the agitation brush for free floating vertical movement relative to the base module;
 a handle pivotally attached to the rear portion of the base module for movement between an upright position and an inclined position;
 a dirt collector on the base module for holding recovered dirt;
 a suction nozzle associated with the base module;
 a working air conduit extending between the dirt collector and the suction nozzle;
 a vacuum source in fluid communication with the dirt collector for generating a flow of working air from the

nozzle through the working air conduit and into the dirt collector to thereby draw dirt and debris from the surface to be cleaned through the nozzle and working air conduit and into the dirt collector;
 the improvement comprising:
 an elevator reciprocally mounted to the base module and movable between rear and forward positions in response to movement of the upright handle from the inclined position to the upright position;
 a first end of the elevator is disposed adjacent the support arm and is adapted to lift the support arm from the surface as the elevator moves between the rear and forward positions and a second end of the elevator is engagable with the handle for moving the elevator between the rear and forward positions as the handle moves between the inclined and upright positions;
 whereby pivoting the upright handle from the inclined position to the upright position is translated into movement of the agitation brush away from the surface to be cleaned.

7. A portable surface cleaning apparatus according to claim 6 wherein the elevator includes an elevator arm that has a forward end that is disposed adjacent the support arm and is adapted to lift the support arm from the surface to be cleaned as the elevator moves between the rear and forward positions.

8. A portable surface cleaning apparatus according to claim 7 wherein the support arm is pivotally mounted to the base module.

9. A portable surface cleaning apparatus according to claim 8 wherein a first end of the support arm is mounted to the agitation brush and a second end of the pivot arm is pivotally mounted to the base module.

10. A portable surface cleaning apparatus according to claim 7 wherein the forward end of the elevator arm has a lifting surface for lifting the support arm and the lifting surface is a ramp that slides along a bottom surface of the pivot arm.

11. A portable surface cleaning apparatus according to claim 7 wherein the elevator arm has a second end that abuts the outer surface of the lower portion of the handle in the upright position.

12. A portable surface cleaning apparatus according to claim 7 wherein the support arm is pivotally mounted to the base module.

13. A portable surface cleaning apparatus according to claim 6 and further comprising a spring that biases the elevator rearwardly.

14. A portable surface cleaning apparatus according to claim 6 wherein the agitation brush is pivotally mounted to the support arm.

15. A portable surface cleaning apparatus according to claim 6 wherein a first end of the support arm is mounted to the agitation brush and a second end of the pivot arm is pivotally mounted to the base module.

16. A portable surface cleaning apparatus, comprising:
 a base module for movement along a surface and having a front portion and a rear portion;
 a brush assembly having an agitation brush generally disposed in the front portion of the base module and mounted therein for substantially vertical reciprocal relative floating movement with respect thereto;
 a handle pivotally attached to the rear portion of the base module for movement between an upright position and an inclined position, and including a lower portion having an outer surface;

29

a fluid recovery system comprising:

- a tank having a fluid recovery chamber for holding recovered fluid;
- a suction nozzle associated with the base module;
- a working air conduit extending between the recovery chamber and the suction nozzle;
- a vacuum source in fluid communication with the recovery chamber for generating a flow of working air from the nozzle through the working air conduit and through the recovery chamber to thereby draw dirty liquid from the surface to be cleaned through the nozzle and working air conduit and into the recovery chamber;

a liquid dispensing system comprising:

- a liquid dispensing nozzle;
- a fluid supply chamber for holding a predetermined amount of supply fluid;
- a fluid supply conduit fluidly connected to the fluid supply chamber and to the dispensing nozzle for supplying liquid to the dispensing nozzle;

the improvement comprising:

- an elevator assembly including an elevator arm reciprocally mounted to the base module and movable between free and lift positions in response to movement of the upright handle from the inclined position to the upright position;
- a first end of the elevator arm is disposed adjacent the brush assembly and is adapted to lift the brush assembly from the surface as the elevator assembly moves between the free and lift positions and a second end of the arm is engageable with the handle for moving the elevator assembly between the free and lift positions as the handle moves between the inclined and upright positions;

whereby pivoting the upright handle from the inclined position to the upright position is translated into movement of the agitation brush away from the surface to be cleaned.

17. A portable surface cleaning apparatus according to claim 16 wherein the first end of the elevator arm has a lifting surface for upwardly pivoting the pivot arm and the lifting surface is a ramp that slides along a bottom surface of the pivot arm.

18. A portable surface cleaning apparatus according to claim 17 and further comprising a spring that biases the elevator arm toward the handle.

19. A portable surface cleaning apparatus according to claim 18 wherein the second end of the elevator arm abuts the outer surface of the lower portion of the handle in the upright position.

20. A portable surface cleaning apparatus according to claim 16 wherein the agitation brush is pivotally mounted to the first end of the elevator arm.

21. A portable surface cleaning apparatus, comprising:

- a base module for movement along a surface to be cleaned and having a front portion and a rear portion;
- a brush assembly having an agitation brush generally disposed in the front portion of the base module for contact with the surface to be cleaned and a support arm for supporting the agitation brush for free floating vertical movement relative to the base module;
- a handle pivotally attached to the rear portion of the base module for movement between an upright position and an inclined position;

30

a dirt collector for holding recovered dirt;

- a suction nozzle associated with the base module;
- a working air conduit extending between the dirt collector and the suction nozzle;
- a vacuum source in fluid communication with the dirt collector for generating a flow of working air from the nozzle through the working air conduit and into the dirt collector to thereby draw dirt and debris from the surface to be cleaned through the nozzle and working air conduit and into the dirt collector;

the improvement comprising:

- an elevator reciprocally mounted to the base module and movable between free and lift positions in response to movement of the upright handle from the inclined position to the upright position;
- a first end of the elevator is disposed adjacent the support arm and is adapted to lift the support arm from the surface as the elevator moves between the rear and forward positions and a second end of the elevator is engageable with the handle for moving the elevator between the free and lift positions as the handle moves between the inclined and upright positions;
- whereby pivoting the upright handle from the inclined position to the upright position is translated into movement of the agitation brush away from the surface to be cleaned.

22. A portable surface cleaning apparatus according to claim 21 wherein the elevator includes an elevator arm that has a forward end that is disposed adjacent the support arm and is adapted to lift the support arm from the surface to be cleaned as the elevator moves between the rear and forward positions.

23. A portable surface cleaning apparatus according to claim 22 wherein the support arm is pivotally mounted to the base module.

24. A portable surface cleaning apparatus according to claim 23 wherein a first end of the support arm is mounted to the agitation brush and a second end of the pivot arm is pivotally mounted to the base module.

25. A portable surface cleaning apparatus according to claim 22 wherein the forward end of the elevator arm has a lifting surface for lifting the support arm and the lifting surface is a ramp that slides along a bottom surface of the pivot arm.

26. A portable surface cleaning apparatus according to claim 22 wherein the elevator arm has a second end that abuts the outer surface of the lower portion of the handle in the upright position.

27. A portable surface cleaning apparatus according to claim 22 and further comprising a spring that biases the elevator rearwardly.

28. A portable surface cleaning apparatus according to claim 21 wherein the agitation brush is pivotally mounted to the support arm.

29. A portable surface cleaning apparatus according to claim 21 wherein the support arm is pivotally mounted to the base module.

30. A portable surface cleaning apparatus according to claim 21 wherein a first end of the support arm is mounted to the agitation brush and a second end of the pivot arm is pivotally mounted to the base module.