



US00RE39371E

(19) **United States**
(12) **Reissued Patent**
Johnson

(10) **Patent Number: US RE39,371 E**
(45) **Date of Reissued Patent: Oct. 31, 2006**

(54) **LAP DANCE LINER**
(76) Inventor: **Wesley K. Johnson**, 7417 Van Nuys Blvd., #Q, Van Nuys, CA (US) 91405
(21) Appl. No.: **10/371,786**
(22) Filed: **Feb. 21, 2003**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,406,462**
Issued: **Jun. 18, 2002**
Appl. No.: **09/904,255**
Filed: **Jul. 11, 2001**

(51) **Int. Cl.**
A61M 1/00 (2006.01)
A61F 5/44 (2006.01)
A61F 13/15 (2006.01)
A41D 27/12 (2006.01)
A41B 9/02 (2006.01)

(52) **U.S. Cl.** **604/327; 604/349; 604/394; 2/54; 2/403**

(58) **Field of Classification Search** **604/327, 604/346, 347, 349-354, 394, 385.09; 128/844; 2/54, 82, 83, 403**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,366,116 A * 1/1968 Huck 604/347
4,601,716 A * 7/1986 Smith 604/349
4,888,007 A * 12/1989 Loeb et al. 604/352
4,961,419 A * 10/1990 Tribble et al. 602/70
5,163,449 A * 11/1992 van der Valk 128/844
5,327,911 A * 7/1994 Pien 128/844
5,524,298 A * 6/1996 Plunkett 2/403
5,531,725 A * 7/1996 Steer 604/349
5,547,466 A * 8/1996 McRoberts et al. 602/70
5,618,279 A * 4/1997 Pudlo 604/385.09
5,623,946 A * 4/1997 Hessel 128/844

5,649,913 A * 7/1997 Cohen 604/353
5,716,350 A * 2/1998 Ryan 604/385.09
6,007,524 A * 12/1999 Schneider 604/327
6,061,840 A * 5/2000 Alligator 2/403
6,209,543 B1 * 4/2001 Star 128/844
6,245,036 B1 * 6/2001 McRoberts et al. 602/67
6,338,729 B1 * 1/2002 Wada et al. 604/385.09
6,406,462 B1 * 6/2002 Johnson 604/327
6,443,930 B1 * 9/2002 Silverstein 604/353
6,487,728 B1 * 12/2002 Cook 2/403
6,569,083 B1 * 5/2003 Kassman 600/38
6,569,135 B1 * 5/2003 Mula 604/349
6,662,378 B1 * 12/2003 Vartanyan 2/403
2002/0134389 A1 * 9/2002 Badgett 128/844
2003/0028161 A1 * 2/2003 Carballo 604/349
2004/0087919 A1 * 5/2004 Tanaka et al. 604/327
2004/0097893 A1 * 5/2004 Elfstrom et al. 604/358
2004/0106909 A1 * 6/2004 Browning 604/349


* cited by examiner

Primary Examiner—Larry I. Schwartz
Assistant Examiner—Michael G. Bogart
(74) *Attorney, Agent, or Firm*—Gene Scott, Patent Law & Venture Group

(57) **ABSTRACT**

A combination pouch and underwear pant is worn by a man for facilitating sexual activity such as lap dancing. The pouch is worn over the sex organs of a man under the underwear pant, which is adapted by an elastic waistband for compressively pinning the pouch in place. The pouch is made of a flexible and elastic material. A top edge of the pouch provides access to an interior of the pouch of a hand and wrist of the wearer so as to facilitate insertion of the wearer's sex organs into the pouch through an aperture, which encircles penis and scrotum. The aperture elastically compresses between a top surface at the base of the penis of the wearer and a bottom surface at the base of the scrotum of the wearer. With the pouch in place, the wearer is able to facilitate the capture of body fluids without fear of the pouch moving away from its preferred position relative to the torso of the wearer.

8 Claims, 2 Drawing Sheets






Fig. 1




Fig. 2

LAP DANCE LINER

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

BACKGROUND OF THE INVENTION

1. Field of the Invention:

This invention relates generally to protective or prophylactic devices for use during sexual activities, and more particularly to a plastic pouch and under-pant combination used for fully clothed sexual activity when penetration is not intended.

2. Description of Related Art:

The following art defines the present state of this field:

Hessel, U.S. Pat. No. 5,623,946, teaches a thin-walled, condom-like tubular protection device for protecting against the transfer of infectious matter during sexual intercourse. The condom-like device has an open end and a collar-shaped outwardly extending portion with an apparatus for radially stretching the collar. The device also has an inner diameter which is sufficiently large to permit movement of a penis with respect to the protective device during coitus.

Steer, U.S. Pat. No. 5,531,725, teaches an improved male incontinence device which has a condom located within a hollow tubular applicator open at both ends, which has an adhesive for securing the device to the penis.

Van der Valk, U.S. Pat. No. 5,163,449, teaches a device for use with a male condom that has a substantially rigid ring with a substantially axial width and a radial thickness. The internal diameter of the device is sized to fit loosely around the base of a penis, adjusting the fit of an ordinary condom and facilitating coitus.

Loeb, et al., U.S. Pat. No. 4,888,007, teaches a pubic shield which has a resilient tubular element and which is secured to the user with a bio-adhesive. The shield is designed for use with a condom.

Smith, U.S. Pat. No. 4,601,716, discloses a disposable sanitary sheath for wearing around the penis of the user. The sheath contains a moisture absorbent pad and is surrounded with an outer moisture resistant layer.

Pien, U.S. Pat. No. 5,327,911, discloses a universal contraceptive device having a condom support device of annular configuration and including an inwardly opening groove formed on the periphery thereof. A securing device secures the support device in place on a person's body, and the support device holds a condom which fits loosely around an erect male organ.

The prior art teaches various condom or other sheathing devices to fit over a man's penis to protect the user from disease transmission and to contain body fluids. However, the prior art does not teach a pouch and underpant combination designed specifically for providing frictional stimulation to the penis during fully clothed sexual activity. The present invention fulfills these needs and provides further related advantages as described in the following summary.

SUMMARY OF THE INVENTION

The present invention teaches certain benefits in construction and use which give rise to the objectives described below.

A combination pouch and underwear pant is worn by a man for facilitating sexual activity such as lap dancing. The

pouch is worn over the sex organs of a man and under the underwear pant, which is adapted by an elastic waistband for compressively pinning the pouch in place. The pouch is made of a flexible and elastic material with a rough interior surface. A top edge of the pouch provides access to an interior of the pouch of a hand and wrist of the wearer so as to facilitate insertion of the wearer's sex organs into the pouch through an aperture which encircles penis and scrotum compressively. The aperture elastically compresses between a top surface at the base of the penis of the wearer and a bottom surface at the base of the scrotum of the wearer so that the pouch is held in place during use. With the pouch in place, the motion of a lap dancer against the outer clothes of the wearer is able to cause the roughened surface of the pouch to slide against the penis in such a manner that the penis is stimulated so as to simulate intercourse. The pouch captures fluids released prior to, and during the lap dance act.

A primary objective of the present invention is to provide a lubricated, loose fitting liner, which covers a user's genitals during sexual activity, the device having advantages not taught by the prior art.

Another objective is to provide a liner device, which is held in place by an underwear pant, thus eliminating the need for any further attachment devices, or requiring the liner device to clamp or adhere to any part of the user's torso.

A further objective is to provide a device enabled for capturing body fluids, such as ejaculate, protecting the user's clothes and facilitating cleanup after sexual activity.

Another objective is to provide a liner device, which is lubricated and rough surfaced to enhance physical pleasure when the user's genitals are manipulated and to allow motion to cause sliding stimulation against the genital area.

A final objective is to provide a device as described which is not noticeable when worn.

Other features and advantages of the present invention will become apparent from the following more detailed description, taken in conjunction with the accompanying drawings, which illustrate, by way of example, the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWING

The accompanying drawings illustrate the present invention. In such drawings:

FIG. 1 is a cutaway perspective view showing the front panels of a pouch and pant combination of the preferred embodiment of the present invention, the pant being cutaway to reveal the pouch within, a front panel of the pouch cutaway to reveal the sex organs of a man positioned within the pouch through an aperture on a rear panel of the pouch; and

FIG. 2 is a perspective view of the pouch thereof showing the rear panel.

DETAILED DESCRIPTION OF THE INVENTION

The above described drawing figures illustrate the preferred embodiment of the invention, a combination pouch 10 and underwear pant 20 worn by a man 30 for facilitating sexual activity when the intention is to perform such activity while fully clothed and when sexual penetration is not intended.

The underwear pant 20 is a common article of clothing well known in the art and provides a tight fitting elastic

3

waistband **22** for compressively encircling a torso **32** of a wearer, normally a man. The waistband **22** may also be of the type that is drawn and tied, or other types that may provide similar function, all of which is well known.

The pouch **10** is of a type that is not known, and comprises features that enable a new and valuable use. The pouch **10** and pant **20**, when used together in the manner described and shown, provides a combination that is not known in the art. The pouch **10** is generally rectangular in shape, as shown in FIG. **2**, and is made of a flexible and elastic material such as a rubberized plastic combination or similar materials. The pouch is folded to provide a front panel **14** and a rear panel **12**. A top edge **18** of the pouch is open, providing access to an interior **19** of the pouch by a hand and wrist of the wearer. The rear panel **12** of the pouch provides an aperture **11**, enabled by its size for admitting the penis and scrotum of the wearer into the pouch **10** as is illustrated in FIG. **1**. This aperture **11** is adapted by size and the elastic property of the pouch **10** for compressive engagement between a top surface **34** at the base of a penis of the wearer and a bottom surface **36** at the base of a scrotum of the wearer. This aspect of the invention is critical to its use. Being elastic and flexible, and preferably lubricated, the pouch **10** would be normally easily dislodged from its preferred engagement with the sex organs of the wearer, as shown in FIG. **1** because of the vigorous activity the sex organs and pouch **10** are subjected to during use. However, it has been found that with a moderate elastic compressive force around the penis and scrotum, the pouch **10** is more permanently fixed in place and is therefore not easily dislodged. A further important feature of the pouch **10** is that it is of such length, see "L" in FIG. **2**, as to extend upwardly and under the waistband **22** of the pant **20**. This enablement allows the pant waistband **22** to control the position of the pouch essentially pinning it in place during use. The pouch is at least 2½ inches in width and preferably larger so as to admit the hand and wrist to the interior **19** of the pouch **10**. An important feature of the pouch **10** is that the interior sidewall surface **13** has a roughness of at least ½ mm in height. This roughness is necessary for appropriate stimulation to the male sex organ for stimulation thereof and is a critical element in the novelty of the invention. The pouch is approximately 13 inches in length; dimension "L." The aperture is at least 1 inch in diameter; dimension "d." These dimensions have been found to be critical to the proper fitting of the invention to the average male. A lubricating layer, such as a layer of Vaseline® is deposited on the interior sidewall surface **13** adjacent the male organ. A reinforcing grommet **15**, such as a reinforcing circular portion, as shown, is preferably placed integral with the sidewall **12** of the pouch around the aperture **11** and has been found to be critical to the ability of providing proper elastic force for holding the pouch **10** in place, i.e., sufficient elastic force, while enabling the material of the pouch **10** to be sufficiently thin to enable the pouch to slide and respond to pressures during lap dancing. In FIG. **2**, the dimension "h" represents the relaxed length or size of the aperture **11**, while the dimension "H" represents the extended length or size of the aperture **11** when it is pulled to stretch around the penis and scrotum. The material of the pouch **10** including the grommet **15** is of sufficient elastic property for encompassing a range of male size sufficient to

4

the intended market of users. It is the ability of the material that the pouch **10** is made of to stretch elastically to provide the holding power necessary during use.

In use, the pouch **10** is placed into the pant **20** and, with a hand and arm inserted into the pouch, the aperture **11** is manually stretched to receive the sex organs of the wearer into the pouch **10**. If the pouch **10** is not pre-lubricated, a lubricant is applied to the interior surface **13** of the pouch **10** around the sex organs. The upper portion of the pouch is drawn upward with the top edge **18** pinned in place by the pant **20**. The wearer normally wears a trousers and shirt over the invention. During sexual play well known as "lap dancing" the wearer receives friction from a lap dancing person with direct physical contact onto the sexual organs of the wearer. During this play body fluids may be released by the wearer, and these fluids are captured within the pouch **10**. The tight fit of the stretched aperture and the elastic band **22** prevent these fluids from leaving the interior **19** of the pouch **10**.

While the invention has been described with reference to at least one preferred embodiment, it is to be clearly understood by those skilled in the art that the invention is not limited thereto. Rather, the scope of the invention is to be interpreted only in conjunction with the appended claims.

What is claimed is:

1. A combination liner device and underwear pant worn by a man for facilitating sexual activity, the combination comprising: an underwear pant adapted by a tight fitting waistband for compressively encircling a torso of a wearer; and, positioned within the underwear pant, a [generally rectangular] pouch of a flexible and elastic material, the pouch having a front and a rear [panels] *panel* and a top edge [providing access to an interior of the pouch by a hand and wrist of the wearer]; the rear panel of the pouch providing an aperture enabled by size for admitting a penis and scrotum of the wearer into the pouch, and adapted by size and elastic property for elastic compressive engagement between a top surface of a base of [a] *the* penis of the wearer and a bottom surface of a base of [a] *the* scrotum of the wearer; the pouch adapted by length for extending under the elastic waistband for securing the pouch in a preferred position.

2. The combination of claim 1 wherein the pouch is at least 2½ inches in width.

3. The combination of claim 1 wherein the front and rear panels provide an interior surface having a roughness of at least ½ mm in height.

4. The combination of claim 1 wherein the pouch is approximately 13 inches in length.

5. The combination of claim 1 wherein the aperture is at least 1 inch in diameter.

6. The combination of claim 3 further comprising a lubricating layer on the interior surface.

7. The combination of claim 1 further comprising a reinforcing grommet around the aperture.

8. *The combination of claim 1 further comprising access to an interior of the pouch by a hand and wrist of the wearer through the top edge.*

* * * * *