

US00RE39416E

(19) **United States**  
(12) **Reissued Patent**  
**Shin et al.**

(10) **Patent Number:** **US RE39,416 E**  
(45) **Date of Reissued Patent:** **Dec. 5, 2006**

(54) **STRUCTURE OF ROTOR FOR OUTER ROTOR TYPE BRUSHLESS MOTOR**

EP 0655824 5/1995

(Continued)

(75) Inventors: **Hyoun Jeong Shin**, Seoul (KR); **Jin Soo Park**, Seoul (KR); **Ho Seon Rew**, Seoul (KR); **Sang Wook Hong**, Seoul (KR)

OTHER PUBLICATIONS

English Language Abstract of JP 8-289523.  
English Language Abstract of JP 55-53153.  
English Language Abstract of JP 10-94203.  
English Language Abstract of JP 9-322489.  
English Language Abstract of JP 10-210727.  
English Language Abstract of JP 9-285089.  
English Language Abstract of JP 61-236350.

(73) Assignee: **LG Electronics Inc.**, Seoul (KR)

(21) Appl. No.: **10/854,782**

(22) Filed: **May 27, 2004**

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **6,396,177**  
Issued: **May 28, 2002**  
Appl. No.: **09/479,366**  
Filed: **Jan. 7, 2000**

*Primary Examiner*—Karl Tamai

(74) *Attorney, Agent, or Firm*—Greenblum & Bernstein, P.L.C.

(57) **ABSTRACT**

(30) **Foreign Application Priority Data**

Jan. 8, 1999 (KR) ..... 99-268  
Jan. 21, 1999 (KR) ..... 99-1754  
Mar. 31, 1999 (KR) ..... 99-11220

The present invention relates to a structure of a rotor for a brushless motor which can improve structural stiffness, restrict noise generation by reducing vibration during the rotation, use cheap materials, reduce a fabrication cost by fabricating a back yoke and a base plate unit in a single body, improve durability, and efficiently cool a heat generated in the motor during the operation by facilitating an external air inflow. The structure of the rotor for the brushless motor includes: a steel plate frame provided with a base plate unit in a disc shape having a plurality of insertion holes at its center portion, a plurality of radiation holes being formed at a circumferential portion of the insertion holes, a plurality of blades being formed at side portions of the radiation holes by cutting; a back yoke unit curved and extended in the upward direction, having a predetermined height at the circumferential portion of the base plate unit; and a radius-direction enhancing unit formed at the upper end portion of the back yoke unit; one or a plurality of ring type permanent magnets fixedly connected to the inner side portion of the back yoke unit; a connecting member inserted into the insertion hole positioned at the center, and connected to the steel plate frame; and a fixing unit fixing a driving shaft inserted into the connecting member and connected to the other constitutional elements.

(51) **Int. Cl.**  
**H02K 21/22** (2006.01)  
**H02K 9/06** (2006.01)

(52) **U.S. Cl.** ..... **310/63; 310/67 R; 310/156.21; 310/156.26; 68/23.7**

(58) **Field of Classification Search** ..... **310/67 R, 310/63, 156.21, 156.26; 68/23.7**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**


5,083,052 A \* 1/1992 Ochi ..... 310/64  
5,453,650 A \* 9/1995 Hashimoto et al. .... 310/268

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE 3329720 2/1984

**23 Claims, 8 Drawing Sheets**



# US RE39,416 E

Page 2

## U.S. PATENT DOCUMENTS

5,497,040	A	*	3/1996	Sato .....	310/67 R
5,528,092	A		6/1996	Ohta .....	310/67 R
5,659,216	A	*	8/1997	Bisantz .....	310/156.26
5,744,881	A	*	4/1998	Ishizuka et al. ....	310/67 R
5,907,206	A		5/1999	Shiga et al. ....	310/156.05
5,942,821	A	*	8/1999	Shin .....	310/67 R
6,049,930	A	*	4/2000	Hisano et al. ....	8/159
6,091,172	A	*	7/2000	Kakinuma et al. ....	310/71

## FOREIGN PATENT DOCUMENTS

JP	30-17529	11/1955
JP	50-36123	10/1975
JP	52-59210	4/1977
JP	53-54719	5/1978
JP	55-53153	4/1980
JP	57040354	* 3/1982
JP	57-040354	* 3/1982
JP	57-58736	4/1982
JP	59-216455	12/1984
JP	60197136	* 10/1985
JP	60-197136	* 10/1985
JP	61-17877	2/1986
JP	61-236350	* 10/1986
JP	61236350	* 10/1986
JP	61-244912	10/1986
JP	62-188975	12/1987
JP	63-176360	11/1988

JP	1-170354	7/1989
JP	1-166468	11/1989
JP	2-14278	1/1990
JP	4-33536	2/1992
JP	4-38149	* 2/1992
JP	04-033536	* 2/1992
JP	04-038149	* 2/1992
JP	4-80248	7/1992
JP	5-41358	6/1993
JP	6-41379	5/1994
JP	7-59327	3/1995
JP	7-059315	* 3/1995
JP	07-059315	* 3/1995
JP	08-019229	* 1/1996
JP	8-019229	* 1/1996
JP	8-82316	3/1996
JP	8-149750	6/1996
JP	3030340	* 8/1996
JP	8-214480	8/1996
JP	8-289523	11/1996
JP	9-285089	10/1997
JP	9-322489	12/1997
JP	10-94203	4/1998
JP	10-210727	8/1998
JP	10210727	* 8/1998
JP	10-256031	9/1998
KR	95-1327	1/1995

\* cited by examiner

FIG. 1  
CONVENTIONAL ART




FIG. 2A  
CONVENTIONAL ART




FIG. 2B  
CONVENTIONAL ART






FIG. 3A  
CONVENTIONAL ART




FIG. 3B  
CONVENTIONAL ART




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7A




FIG. 7B






FIG. 8




FIG. 9




FIG. 10





FIG. 11



## STRUCTURE OF ROTOR FOR OUTER ROTOR TYPE BRUSHLESS MOTOR

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.**

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to a structure of a rotor for an outer rotor type brushless motor (BLDC), and in particular to a structure of a rotor for an outer rotor type brushless motor (BLDC) which can improve structural stiffness, restrict noise generation by reducing vibration during the rotation, efficiently cool a heat generated in the motor, decrease a fabrication cost and improve durability.

#### 2. Description of the Background Art

As illustrated in FIG. 1, a general outer rotor type brushless motor (BLDC) includes: a stator 100 where a coil is wound round a magnetic core 10; a resin frame 220 in a predetermined shape fabricated with a resin by using a die; a rotor 200 positioned outside the stator 100 in order to be alternately rotated in the right and left directions; and a sensor unit 300 connected to the stator 100, detecting a position of a permanent magnet 210 of the rotated rotor 200, and sequentially transmitting a current to the stator 100.

A driving shaft 400 is inserted into a center portion of the rotor 200.

The structure of the rotor 200 will now be described in more detail.

As depicted in FIGS. 2a and 2b, in the conventional outer rotor type brushless motor, the resin frame 220 forming an outer shape of the rotor 200 is formed having a predetermined height, a permanent magnet supporting unit 222 connected with the permanent magnet 210 being vertically curved and extended in an upward direction, and curved toward the center portion, at the outer circumferential portion to a disc-shaped base unit 221.

A ring-shaped deposition groove 223 having a predetermined height and width is formed at the inner wail of the permanent magnet supporting unit 222. A ring-shaped back yoke 230 having a predetermined width is inserted into the deposition groove 223. The plurality of permanent magnets 210 are stacked and adhered to the inner side portion of the back yoke 230 at predetermined intervals in a circumference direction.

The back yoke 230 is fabricated by rolling a thin steel plate, and serves to form a magnetic circuit of the permanent magnet 210. The back yoke 230 and the permanent magnet 210 are formed in a single body by a thermoplastic resin.

On the other hand, a boss unit 224 having a predetermined height is formed at the center portion of the base unit 221. A through hole 224a is formed at the center portion of the boss unit 224. A serration unit 225 having a plurality of triangle-shaped teeth is formed at the inner circumferential surface of the through hole 224a.

A shaft serration unit 401 formed at the outer circumferential surface of the driving shaft 400 is inserted into the serration unit 225 of the resin frame 220, and thus the resin frame 220 and the driving shaft 400 are combined. A spacer 410 is inserted into the lower portion of the shaft serration unit 401 inserted into the serration unit 225 of the resin frame 220. A nut 420 is fastened to a lower portion of the spacer 410, namely an end portion of the driving shaft 400.

On the other hand, a radiation fan blade 226 and a radiation hole 227 are provided on the bottom surface of the base unit 221 in order to cool a heat which is always generated during the rotation of the rotor 200 by means of an external air inflow.

As shown in FIG. 2b, a plurality of radiation blades 226 are formed in the base unit 221 in a radial shape centering around the boss unit 224. The plurality of radiation blades 226 have a predetermined thickness and width, and are formed in a vertical direction from the boss unit 224 to the permanent magnetic supporting unit 222.

In addition, a plurality of radiation holes 227 are formed in the base unit 221 at predetermined intervals in a circumferential direction. The plurality of radiation holes 227 are positioned to form a concentric circle, and cross the radiation blades 226.

In the above-described rotor 200, the permanent magnets 210 are positioned having a predetermined space from the stator 100. The driving shaft 400 connected to the resin frame 220 is fixedly connected to other constitutional elements.

In the conventional outer rotor type brushless motor, when a current sequentially flows to the coil 20 wound round the stator 100, the rotor 200 is rotated according to interaction between the current flowing in the coil 20 and the permanent magnet 210. The rotation force of the rotor 200 is transmitted to other constitutional elements through the driving shaft 400.

For example, in case the outer rotor type brushless motor adapts to a washing machine, the stator 100 is deposited in an outer casing including an inner casing, the driving shaft 400 is connected to the inner casing of the washing machine, and thus the driving force of the rotor can be transmitted to the devices such as the washing machine through the driving shaft 400.

During the rotation of the rotor 200, the air flows into the motor by the radiation fan blades 226 and the radiation holes 227, thereby cooling the heat generated in the motor.

However, while rotated by the interaction force with the current applied to the winding coil of the stator, as depicted in FIGS. 3a and 3b, the rotor for the conventional outer rotor type brushless motor is vibrated in a shaft direction and a radius direction.

The vibration is generated because the resin frame connected with the permanent magnet consists of the resin, and thus stiffness of the material is weak (approximately 15% of the steel plate). Especially, the vibration of the resin frame resulting from the vibration in the radius direction increases noise.

Moreover, since the frame consists of the resin, the serration unit of the frame connected to the driving shaft transmitting the driving force generated from the rotor is easily abraded under the operational conditions of high temperature, high torque and impact load, and thus a life span thereof is reduced.

In addition, the radiation fan blades for cooling the inside of the motor with the external air are formed in a vertical direction. Therefore, when the rotor is rotated in one direction, an amount of the air which flows into the motor and is discharged therefrom is increased. As the thermal conductivity of the resin is low, radiation is not efficient.

Furthermore, the frame consisting of the resin is very weak to a fatigue destruction resulting from a repeated stress generated by alternation of the washing machine. Accordingly, the radiation hole must be formed small.



However, the small radiation holes cannot sufficiently perform a cooling operation. As a result, when the cooling operation is ill-performed, a resistance of the coil is increased, motor efficiency is reduced, a temperature of the coil is more increased, and thus the coil may be easily damaged. Consequently, an expensive coil of high quality must be used.

The resin frame consists of the resin, and thus a price thereof is relatively high. Also, it is necessary to separately fabricate and connect the back yoke in order to form the magnetic circuit, which results in increased production and assembly costs.

#### SUMMARY OF THE INVENTION

Accordingly, it is a primary object of the present invention to provide a structure of a rotor for a brushless motor (BLDC) which can improve structural stiffness, reduce noise by restricting generation of vibration, use cheap materials, reduce a fabrication cost by forming a back yoke and a base plate unit in a single body, and improve durability.

It is another object of the present invention to provide a structure of a rotor for a brushless motor (BLDC) which can efficiently cool a heat generated in a motor during the operation by promoting inflow of an external air.

In order to achieve the above-described objects of the present invention, there is provided a structure of a rotor for an outer rotor type brushless motor (BLDC), including: a steel plate frame provided with a base plate unit in a disc shape having a plurality of insertion holes at its center portion, a plurality of radiation holes being formed at a circumferential portion of the insertion holes, a plurality of blades being formed at side portions of the radiation holes by cutting, a back yoke unit curved and extended in the upward direction, having a predetermined height at the circumferential portion of the base plate unit, and a radius-direction enhancing unit formed at the upper end portion of the back yoke unit; one or a plurality of ring type permanent magnets fixedly connected to the inner side portion of the back yoke unit; a connecting member inserted into the insertion hole positioned at the center, and connected to the steel plate frame; and a fixing unit fixing a driving shaft inserted into the connecting member and connected to the other constitutional elements.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become better understood with reference to the accompanying drawings which are given only by way of illustration and thus are not limitative of the present invention, wherein:

FIG. 1 is a front cross-sectional view illustrating a conventional outer rotor type brushless motor (BLDC);

FIG. 2a is a front cross-sectional view illustrating a structure of a rotor for the conventional outer rotor type brushless motor;

FIG. 2b is a plan view illustrating the structure of the rotor for the conventional outer rotor type brushless motor;

FIG. 3a is a front cross-sectional view illustrating a state where the rotor is vibrated in a radius direction during the driving of the conventional outer rotor type brushless motor;

FIG. 3b is a front cross-sectional view illustrating a state where the rotor is vibrated in a shaft direction during the driving of the conventional outer rotor type brushless motor;

FIG. 4a is a front cross-sectional view illustrating the structure of the rotor for the outer rotor type brushless motor in accordance with the present invention;

FIG. 4b is a plan view illustrating the structure of the rotor for the outer rotor type brushless motor in accordance with the present invention;

FIG. 4c is a bottom view illustrating a structure of a rotor for an outer rotor type brushless motor in accordance with a preferred embodiment of the present invention;

FIG. 5a is a cross-sectional view illustrating an enhancing rib formed on the rotor for the outer rotor type brushless motor in accordance with the present invention;

FIG. 5b is a cross-sectional view illustrating another embodiment of FIG. 5a;

FIG. 6 is a bottom view illustrating another embodiment of FIG. 4c;

FIG. 7a is a cross-sectional view illustrating radiation holes and blades formed on the rotor for the outer rotor type brushless motor in accordance with the present invention;

FIG. 7b is a cross-sectional view illustrating another embodiment of FIG. 7a;

FIG. 8 is a front cross-sectional view schematically illustrating a first example of a support frame connected to an outer circumferential portion of a back yoke unit of the rotor of the outer rotor type brushless motor in accordance with the present invention;

FIG. 9 is a front cross-sectional view schematically illustrating a second example of the support frame in FIG. 8;

FIG. 10 is a front cross-sectional view schematically illustrating a third example of the support frame in FIG. 8; and

FIG. 11 is a front cross-sectional view schematically illustrating a fourth example of the support frame of FIG. 8;

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A structure of a rotor for an outer rotor type brushless motor (BLDC) in accordance with preferred embodiments of the present invention will now be described with reference to the accompanying drawings.

Here, the identical constitutional elements to the conventional art are provided with the same reference numerals.

As illustrated in FIGS. 4a to 4c, the rotor for the outer rotor type brushless motor in accordance with the present invention includes a steel plate frame 510 in a cylinder shape having a plurality of insertion holes 511 at its center portion, an upper portion of which being opened. A back yoke unit 513 is curved and extended in the upward direction, having a predetermined height at the outer circumferential portion of a base plate unit 512, a plurality of permanent magnets 520 being fixedly connected to an inner side portion of the back yoke unit 513.

The base plate unit 512 is formed in a disc shape, a center portion of which being protruded in the upward direction, making an irregular shape with peripheral portions.

The plurality of insertion holes 511 are formed at the center portion, and include a shaft insertion hole 511a which a driving shaft 400 is inserted into; and a plurality of fastening member insertion holes 511b which are formed at the outer circumferential portion of the shaft insertion hole 511a, and which a fastening member 520 is inserted into.

On the other hand, a connection guide unit 514 is protrusively formed in the upward direction at the outer circumferential portion of the fastening member insertion hole 511b in the base plate unit 512, so that a connecting member 530 fastened to the steel plate frame 510 by the fastening member 520 can be easily connected to the base plate unit 512.



## 5

The connecting member **530** consists of a steel material, and is fixedly connected to the steel plate frame **510**.

As depicted in FIGS. **4b** and **4c**, in order to increase a natural frequency of the rotor **500**, a plurality of enhancing ribs **515** which are longitudinally embossed in a radius direction are formed in a radial shape at a predetermined portion of the base plate unit **512**.

The enhancing ribs **515** serve to prevent generation of resonance with other constitutional elements during the driving of the rotor **500**.

As illustrated in FIGS. **5a** and **5b**, the end portion of the enhancing rib **515** is advantageously formed in an isosceles triangle shape. The embossing direction is protruded toward the upper or lower portion of the base plate unit **512**.

In addition, a plurality of radiation holes **516** are formed at the outer circumferential portions of the plurality of insertion holes **511** formed at the center portion of the base plate unit **512**. A blade **517** for guiding an air inflow by rotation of the rotor **500** is formed at the side portions of the respective radiation holes **516**.

The radiation hole **516** and the blade **517** may be formed by a press process at the same time, or the blade **517** may be adhered after forming the radiation hole **516**. One or more radiation holes **516** and blades **517** are formed between the enhancing ribs **515** at predetermined intervals.

According to a preferred embodiment as shown in FIG. **4c**, one radiation hole **516** and one blade **517** are formed between the enhancing ribs **515**. According to another embodiment as shown in FIG. **6**, two radiation holes **516** and two blades **517** are formed between the enhancing ribs **515**.

In general, it is preferable that the radiation holes **516** are formed in a maximum number so long as the structural stiffness of the base plate unit **512** is maintained, and thus maximizes an amount of air flowing into the motor.

The shape of the radiation hole **516** will now be described in detail. The radiation hole **516** is longitudinally formed in a radius direction at the base plate unit **512**. The blade **517** is fixed after an edge of a cutting portion of the radiation hole **516** is rotated by a predetermined angle.

In more detail, as illustrated in FIGS. **7a** and **7b**, in order to form the radiation hole **516**, a predetermined portion of the base plate unit **512** is cut in the radius direction. The cutting portion is rotated by a predetermined length (h), centering around a portion corresponding to a length (L) to the circumferential direction of the radiation hole **516**, and fixed, thereby forming the blade **517**.

In every embodiment, it is advantageous to form the plurality of blades **517** to be sloped in the same direction, and to form a width of the radiation hole **516** to be equal to or greater than a height of the blade **517** ( $h/L \leq 1$ ). In addition, the blade **517** slopes toward the inner or outer side of the stator coil **20**. Here, an angle of slope is preferably between  $60^\circ$  and  $90^\circ$  in regard to the surface of the base plate unit **512**, as shown in FIGS. **7a** and **7b**.

FIG. **7a** shows a state where the blade **517** is fixedly sloped toward the stator coil **20**, and FIG. **7b** shows a state where the blade **517** is fixedly sloped away therefrom. In the former, a large amount of air flows into the motor, but an accident may take place during components assembly. In the latter, an amount of air flowing into the motor is more or less small, but an accident is prevented.

## 6

In order to receive one or more ring-shaped permanent magnets **540** in the circumferential direction at predetermined intervals, a jaw **513a** having a predetermined width in a horizontal direction and a contact surface **513b** extended in a vertical direction to the jaw **513a** are formed at the inner surface of the back yoke unit **513**.

The permanent magnets **540** are positioned on the jaw **513a**, contacted with the contact surface **513b**, and fixedly connected to the back yoke unit **513** by an adhesive or, by positioning a resin for adhesion **550** at their upper portions.

In order to enhance stiffness of the steel plate frame **510** in the radius direction, a radius-direction enhancing unit **518** vertically curved and extended in the outward direction is formed at the upper end portion of the back yoke unit **513**.

In accordance with a second embodiment of the present invention, as shown in FIG. **8**, in order to more enhance stiffness in the radius direction, a radius-direction enhancing unit **618** is inwardly curved at an upper portion of a region supporting the magnets **540**, thereby supporting the magnets **540** by an elastic force of the base plate unit **512**. In addition, in order to enhance stiffness of the base plate unit **512** consisting of a steel material in the radius direction, a support frame **660** is provided at the outer portion of the base plate unit **512**, and an upper end portion thereof is horizontally curved and extended in the outward direction.

That is to say, the support frame **660** is curved several times, thus partially surrounding the outsides of the bottom and side portions of the back yoke unit **613**. The upper end portion thereof is outwardly curved and extended.

On the other hand, in accordance with a third embodiment of the present invention, as illustrated in FIG. **9**, a radius-direction enhancing unit **718** is vertically curved and extended in the outward direction at the upper end portion of a back yoke unit **713**, and a support frame **760** is curved, thereby surrounding the whole outsides of the bottom and side portions of the back yoke unit **713**.

In accordance with a fourth embodiment of the present invention, as shown in FIG. **10**, a radius-direction enhancing unit **818** is extendedly formed in a reverse U shape in the outward direction at the upper end portion of the back yoke unit **813**.

According to a fifth embodiment of the present invention, as depicted in FIG. **11**, a radius-direction enhancing unit **918** is vertically curved and extended in the outward direction at the upper end portion of the back yoke unit **913**, and a support frame **960** is formed in a disc shape with its center portion empty, as if covering the upper circumferential portion of the steel plate frame **512**, facing an inner portion thereof.

As described above, the support frame in accordance with the respective embodiments of the present invention is protrusively formed in the inward or outward direction of the base plate unit **512**, thereby sufficiently enhancing the stiffness in the radius direction.

On the other hand, the connecting member **530** includes: a ring-shaped flange unit **531** having a predetermined thickness and area; a boss unit **532** upwardly extended at the center portion of the flange unit **531**, and having a predetermined outside diameter and height; a serration hole **533** formed at an inner circumferential portion of a through hole **532a** formed at the boss unit **532** in upper and lower directions, and engaged with the shaft serration unit **401** formed at the driving shaft **400**; and a plurality of connecting member combining units **534** formed at the flange unit **531**, and fastened to the fastening member **520**.



The plurality of connecting member combining units **534** formed at the flange unit **531** are screw holes making a concentric circle shape.

A guide hole **535** which the connection guide unit **514** formed at the upper portion of the base plate unit **512** is inserted into is formed having a predetermined depth at the lower portion of the connecting member combining unit **534**.

On the other hand, although not illustrated in the drawings, a specific guide pin may be formed in the connection guide unit **514**.

The fastening unit **520** includes a plurality of bolts. The bolts are passed through the fastening unit insertion holes **511b**, and thereafter fastened to the connecting member combining unit **534**, thereby connecting the connecting member **530** to the base plate unit **512** of the steel plate frame **510**. A specific nut may be fastened to the fastening unit **520**.

The shaft serration unit **401** is formed at the outer circumferential portion of the driving shaft **400** transmitting the rotation force of the rotor **500** in order to be engaged with the serration hole **533** of the connecting member **530**, and a male screw unit **402** is formed at the lower portion thereof.

The driving shaft **400** is connected to the serration hole **533** of the connecting member **530** connected to the steel plate frame **510**. At the same time, the spacer **410** is inserted into the end portion of the driving shaft **400**, and the nut **420** which is a fixing unit is fastened to the male screw unit **402**, thereby fixedly connecting the driving shaft **400** to the steel plate frame **510**.

The assembly process of the rotor for the outer rotor type brushless motor in accordance with the present invention will now be explained.

Firstly, the shape of the steel plate frame **510** is manufactured by a press. The permanent magnets **540** are positioned at the inner circumferential portion of the back yoke unit **513** of the steel plate frame **510**. Thereafter, the permanent magnets **540** are fixedly adhered to the back yoke unit **513** by the adhesive or resin for adhesion **550**.

The screw hole **534** which is the connecting member combining unit accords with the fastening unit insertion hole **511b** of the base plate unit **512** of the steel plate unit **510**, and a bolt which is the fastening unit **520** is fastened thereto, thereby connecting the connecting member **530** to the steel plate frame **510**.

The shaft serration unit **401** of the driving shaft **400** is inserted into the serration hole **533** of the connecting member **530**, the spacer **401** is inserted into the lower portion of the driving shaft **400**, and the nut **420** is fastened to the male screw unit **402** of the driving shaft **400**, thereby fixedly connecting the driving shaft **400**, the steel plate frame **510** and the connecting member **530**.

In accordance with the outer rotor type brushless motor of the present invention, the permanent magnets **540** composing the rotor **500** are positioned to surround the stator **100**, and the driving shaft **400** is connected to other constitutional elements.

According to the outer rotor type brushless motor of the present invention, when a current is applied to the coil **20** composing the stator **100**, the rotor **500** is rotated by the interaction force between the current flowing in the coil **20** and the permanent magnets **540**, and the driving shaft **400** connected to the rotor **500** transmits the rotation force generated from the rotor **500** to the other constitutional elements.

In accordance with the present invention, the steel plate frame **510** consists of a steel material, and thus stiffness is relatively high. In addition, at the base plate unit of the steel plate frame **510**, the enhancing rib **515** is formed in order to enhance stiffness in the shaft direction, and the radius-direction enhancing unit **518** if formed in order to enhance stiffness in the radius direction. The support frame is connected to the outer portion of the enhancing unit **518**, thus increasing the structural stiffness and reducing the vibration. As a result, the noise generation is restricted.

Also, the blades **517** formed at the base plate unit **512** of the steel plate frame **510** are protrusively sloped in one direction, and thus the external air may smoothly flow into the motor during the rotation. Accordingly, the heat generated in the motor can be efficiently cooled.

Furthermore, the connecting member **530** connected to the driving shaft **400** is firmly fastened to the steel plate frame **510** by the bolt which is the fastening unit **520**. Also, the material stiffness is high, and thus resists the high torque, impact load and high temperature. As a result, the components may not be abraded or damaged, and durability thereof is improved.

Moreover, the steel plate frame **510** and other components consist of a steel material, and thus a fabrication cost thereof is reduced by approximately 5 times, as compared with the resin in the conventional art. In addition, while the back yoke **230** is fabricated by rolling a thin steel plate in the conventional art, it is not specially fabricated, but formed in a single body with the steel plate frame **510** in accordance with the present invention.

As discussed earlier, the structure of the rotor for the outer rotor type brushless motor in accordance with the present invention increases the structural stiffness, and restricts generation of the vibration and noise during the operation, thereby improving reliability. In addition, the present invention efficiently cools the heat generated in the motor during the operation, thereby improving the efficiency of the motor. Moreover, the back yoke unit is not specially fabricated, but formed in a single body with the steel plate frame, thereby reducing the fabrication cost.

As the present invention may be embodied in several forms without departing from the spirit or essential characteristics thereof it should also be understood that the above-described embodiments are not limited by any of the details of the foregoing description, unless otherwise specified, but rather should be construed broadly within its spirit and scope as defined in the appended claims, and therefore all changes and modifications that fall within the meets and bounds of the claims, or equivalences of such meets and bounds are therefore intended to be embraced by the appended claims.

What is claimed is:

1. A structure of rotor for an outer rotor type brushless motor, comprising:

a steel plate frame including:

a base plate unit in a disc shape having:

- a plurality of insertion holes at its center portion;
- a plurality of radiation holes being formed at a circumferential portion of the insertion holes;
- a plurality of radially extending blades being formed at side portions of the radiation holes by cutting;
- a connection guide unit being protrusively formed adjacent a circumferential portion of a shaft insertion hole of the plurality of insertion holes;
- a plurality of enhancing ribs which are longitudinally embossed in a radial direction formed in intermediate between a center and an outer edge thereof;



9

- a back yoke unit curved at the edge portion of the base plate unit and formed integrally therewith and extended in the upward direction, having a predetermined height at an outer circumferential portion of the base plate unit; and
- a radius-direction enhancing unit formed radially extending outwardly at an upper end portion of the back yoke unit;
- one or a plurality of ring type permanent magnets fixedly connected to the inner side portion of the back yoke unit;
- a connecting member inserted into the shaft insertion hole of the plurality of insertion holes positioned at the center, and connected to the steel plate frame by a fastening member; and
- a fixing unit fixing a driving shaft inserted into the connecting member which connected to the other constitution elements.
2. The structure according to claim 1, wherein a jaw having a predetermined width in a horizontal direction and a contact surface extended in a vertical direction to the jaw are formed at an inner surface of the back yoke unit.
3. The structure according to claim 2, wherein the permanent magnets are positioned on the jaw, contacted with the contact surface, and fixedly connected to the back yoke unit by an adhesive or by positioning a resin for adhesion at their upper portions.
4. The structure according to claim 1, wherein the plurality of insertion holes are formed at the center portion of the base plate unit, and comprise the shaft insertion hole which the driving shaft is inserted into, and a plurality of fastening member insertion holes which are formed at the outer circumferential portion of the shaft insertion hole, and a fastening member is inserted into.
5. The structure according to claim 4, wherein a connection guide unit is protrusively formed in the upward direction at the outer circumferential portion of the fastening member insertion hole.
6. The structure according to claim 1, wherein the connecting member comprises:
- a ring-shaped flange unit having a predetermined thickness and area;
- a boss unit upwardly extended at the center portion of the flange unit, and having a predetermined outside diameter and height;
- a serration hole formed at an inner circumferential portion of a through hole formed at the boss unit in upper and lower directions, and engaged with a shaft serration unit formed at the driving shaft; and
- a plurality of connecting member combining units formed at the flange unit and fastened to the fastening member.
7. The structure according to claim 6, wherein a guide hole which the connection guide unit protrusively formed at adjacent a circumferential portion of a shaft insertion hole of the plurality of insertion holes which inserted into is reamed having a predetermined depth at the lower portion of the connecting member combining unit.
8. The structure according to claim 1, wherein a cross-section of the enhancing ribs is symmetric in the radius direction.
9. The structure according to claim 1, wherein an embossing direction of the enhancing ribs is protruded inwardly toward a stator coil.
10. The structure according to claim 1, wherein an embossing direction of the enhancing ribs is protruded outwardly away from where a stator coil is located.

10

11. The structure according to claim 1, wherein a plurality of enhancing ribs embossed and longitudinally formed in a radial shape are formed in the radius direction at a predetermined portion of the base plate unit, and one or more radiation holes and blades are formed between the enhancing ribs.
12. The structure according to claim 1, wherein the plurality of radiation holes are longitudinally formed in the radius direction of the base plate unit.
13. The structure according to claim 12, wherein a width of the radiation holes is equal to or greater than a height of the blades.
14. The structure according to claim 1, wherein the respective blades are sloped inwardly or outwardly toward or away from a stator coil.
15. The structure according to claim 14, wherein a slope angle of each of the blades is between 85° and 95° relative to the surface of the base plate unit.
16. The structure according to claim 1, wherein the radius-direction enhancing unit is vertically curved and extended in the outward direction at the upper end portion of the back yoke unit.
17. The structure according to claim 1, wherein the radius-direction enhancing unit is extendedly formed in a reverse U shape in the outward direction at the upper end portion of the back yoke unit.
18. The structure according to claim 1, wherein a support frame is connected to the outer portion of the back yoke unit.
19. The structure according to claim 18, wherein a radius-direction enhancing unit is inwardly curved and extended at the upper portion of the back yoke unit, and thus the permanent magnets are supported by an elastic force of the back yoke unit itself.
20. The structure according to claim 18, wherein the support frame is curved several times, and thus partially surrounds the outsides of the bottom and side portions of the back yoke unit.
21. The structure according to claim 18, wherein a radius-direction enhancing unit is vertically curved and extended in the outward direction at the upper end portion of the back yoke unit, and the support frame is curved, and thus surrounds the whole outsides of the bottom and side portions of the back yoke unit.
22. The structure according to claim 18, wherein the radius-direction enhancing unit is vertically curved and extended in the outward direction at the upper end portion of the back yoke unit, and the support frame is formed in a disc shape with its center portion empty, as if covering the upper circumferential portion of the steel plate frame, facing an inner portion thereof.
23. *A rotor for an outer rotor type brushless motor for a washing machine, comprising:*
- a steel plate frame including:*
- a base plate unit in a disc shape having:*
- a plurality of insertion holes at its center portion;*
- a plurality of radiation holes formed at a circumferential portion of the insertion holes;*
- a plurality of radially extending blades formed at side portions of the radiation holes;*
- a connection guide unit protrusively formed adjacent a circumferential portion of a shaft insertion hole of the plurality of insertion holes;*
- a plurality of enhancing ribs which are longitudinally embossed in a radial direction formed intermediate a center and an outer edge thereof;*
- a back yoke unit curved at the edge portion of the base plate unit and formed integrally therewith*

**11**

*and extended in an upward direction, having a predetermined height at an outer circumferential portion of the base plate unit; and*  
*a radius-direction enhancing unit formed radially extending outwardly at an upper end portion of the back yoke unit;*  
*at least one ring type permanent magnet fixedly connected to the inner side portion of the back yoke unit;*

**12**

*a connecting member inserted into the shaft insertion hole of the plurality of insertion holes positioned at the center, and connected to the steel plate frame by a fastening member; and*  
*a fixing unit fixing a driving shaft inserted into the connecting member which is connected to the other elements of the washing machine.*

\* \* \* \* \*