



US00RE39695E

(19) **United States**
(12) **Reissued Patent**
Ungchusri et al.

(10) **Patent Number: US RE39,695 E**
(45) **Date of Reissued Patent: Jun. 19, 2007**

(54) **SWIVEL JOINT WITH STEPPED BEARING RACES**

(75) Inventors: **Tep Ungchusri**, The Woodlands, TX (US); **Sergio A. Castillo**, Spring, TX (US)

(73) Assignee: **FMC Technologies, Inc.**, Houston, TX (US)

(21) Appl. No.: **10/387,023**

(22) Filed: **Mar. 11, 2003**

2,499,837 A	*	3/1950	Sheets et al.	384/512
3,142,498 A	*	7/1964	Press	285/276 X
3,372,715 A	*	3/1968	Ashton	285/134 X
3,971,604 A	*	7/1976	Kapaan	384/513
4,418,947 A	*	12/1983	Talafuse	285/168
4,501,511 A	*	2/1985	Albert, Jr.	403/24
4,930,791 A		6/1990	Ungchusri et al.	
5,118,205 A	*	6/1992	Hoffmann	384/512 X
5,149,148 A		9/1992	Taeuber, Jr. et al.	
5,160,229 A	*	11/1992	Yoshino	408/59
5,176,457 A	*	1/1993	Hofmann et al.	384/512 X
5,226,737 A	*	7/1993	Sandy, Jr.	384/512
6,164,707 A	*	12/2000	Ungchusri et al.	285/276

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,371,527**
Issued: **Apr. 16, 2002**
Appl. No.: **09/703,575**
Filed: **Nov. 1, 2000**

U.S. Applications:

(63) Continuation of application No. 08/742,520, filed on Nov. 1, 1996, now Pat. No. 6,164,707, which is a continuation of application No. 08/260,160, filed on Jun. 15, 1994, now abandoned.

(51) **Int. Cl.**
F16L 27/04 (2006.01)

(52) **U.S. Cl.** **285/276; 285/98; 384/512**

(58) **Field of Classification Search** 285/276, 285/121.2, 121.3, 121.4, 121.5, 121.6, 98, 285/272, 134, 136, 145.1; 384/504, 512, 384/513, 516

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

434,479 A	*	8/1890	Simonds	384/453
466,436 A	*	1/1892	Simonds	384/453
633,798 A	*	9/1899	Carley	384/512
738,503 A	*	9/1903	Waters	285/276 X
990,946 A	*	5/1911	Badger	384/513
1,325,113 A	*	12/1919	Rohn	384/512
1,452,603 A	*	4/1923	Himes	384/513
2,412,287 A	*	12/1946	Phillips	285/138

FOREIGN PATENT DOCUMENTS

DE	1907428	*	9/1970	285/276
DE	35032215	*	8/1986	384/512
GB	19089	*	11/1889	384/512
GB	15984	*	8/1899	384/512
GB	174917	*	3/1922	384/512
GB	2643458	*	12/1926	384/512
GB	983980	*	2/1965	384/512
SE	127402	*	2/1950	384/512
WO	WO 93/172251	*	9/1993	

* cited by examiner


Primary Examiner—David Bochna



(74) *Attorney, Agent, or Firm*—Williams, Morgan & Amerson, P.C.



(57) **ABSTRACT**

A swivel joint comprises a tubular male member having at least first and second outer annular grooves formed on an outer surface, a tubular female member having at least first and second inner annular grooves formed on an inner recess, and a plurality of balls disposed in at least first and second annular races which are formed by the alignment of the first and second outer grooves with the first and second inner grooves when a first end of the male member is received within the recess of the female member. In addition, the radius of the first race is greater than the radius of an adjacent race closer to the first end of the male member, and the number of balls in the first race is just one more than the number of balls in the adjacent race closer to the first end.

22 Claims, 3 Drawing Sheets










FIG. 4a
PRIOR
ART




FIG. 4b




FIG. 6

1

SWIVEL JOINT WITH STEPPED BEARING RACES

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

This application is a continuation of U.S. patent application Ser. No. 08/742,520 filed on Nov. 1, 1996, *now U.S. Pat. No. 6,164,707*, which is a continuation of U.S. patent application Ser. No. 08/260,160 filed on Jun. 15, 1994, now abandoned, both of which applications are hereby incorporated herein by reference.

BACKGROUND OF THE INVENTION

The present invention relates to a swivel joint and, more particularly, to a swivel joint having stepped bearing races.

Swivel joints are used in connect fluid pipes in oilfields and in other applications. Swivel joints are generally comprised of interfitting male and female members rotatably connected by a bearing assembly. Typically, inner and outer grooves are incorporated in the male and female members to form a bearing race, and a plurality of ball bearings are housed within the race. Higher demand for compatibility with increased service pressure, wider operating temperature range, and a greater variety of corrosive chemicals has resulted in swivel joint designs with multiple bearing races rather than one bearing race. Even with multiple bearing races high pressures can sometimes cause deformation or brinelling of the bearing races. Such brinelling relaxes the compression of the seal between the male and female members and causes the seal to leak, preventing the swivel joint from swiveling smoothly under pressure and reducing the bearing race life significantly. In addition, erosive wear in the male member under the bearing race can quickly reduce the integrity of the swivel joint.

SUMMARY OF THE INVENTION

The present invention provides a swivel joint having two or more bearing races situated in a stepped relationship wherein each bearing race is positioned coaxially with respect to and has an incrementally greater radius than the next adjacent bearing race closer to the end of the male member which engages the female member. The radius of each bearing race is preferably determined as a function of the radius of the ball bearings and the cross sectional areas of the male and female members at the bearing race. In a preferred embodiment of the invention, the radius of each race is determined such that the number of balls in each race is one more than the number of balls in the adjacent race closer the end of the male member which engages the female member.

The present invention improves sealing under extreme conditions and specifically eliminates bearing race brinelling at pressures much greater than is attained with conventional or known swivel joints with minimal increase in weight and cost. This stepped configuration more equally distributes hydrostatic end loading to each bearing race section, enabling maximum total end loading while minimizing load concentration on a particular bearing race. In addition, the stepped configuration permits the male member to have a relatively larger cross section under the bearing race without increasing the overall diameter of the swivel joint, which enables the male member to withstand a relatively greater amount erosive wear and thereby improves the overall integrity of the swivel joint.

2

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a partial cross-sectional view of a prior art swivel joint having three bearing races;

FIG. 2 is a partial cross-sectional view of a swivel joint of the present invention having three stepped bearing races;

FIG. 3a is an enlarged, partial cross-sectional view of the prior art swivel joint of FIG. 1;

FIG. 3b is an enlarged, partial cross-sectional view of another embodiment of a swivel joint of the present invention having a straight bore seal;

FIG. 4a is an enlarged, cross-sectional view of a ball bearing race in a prior art swivel joint;

FIG. 4b is an enlarged, cross-sectional view of a ball bearing race in a swivel joint according to another embodiment of the present invention;

FIG. 5 is a partial cross-sectional view of another embodiment of a swivel joint of the present invention; and

FIG. 6 is a partial cross-sectional view of the swivel joint of FIG. 2, but having the bore seal depicted in FIG. 1.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 shows a known, prior art swivel joint 10 having a male connector 12 rotatably received inside of a female connector 14. A sealed fluid flow passage 16 is formed therethrough, in communication with fluid conduits or pipes (not shown) extending from each connector. Each connector 12, 14 has respectively formed thereon a plurality of annular grooves 18, 20. When the connectors 12 and 14 are inserted together, the grooves 18 and 20 align with each other forming annular bearing races 22. A plurality of ball bearings 24 are housed in each race 22 to provide bearing support and to enable swiveling of the connectors 12, 14 relative to each other. The races 22 and ball bearings 24 are coaxially positioned around a center axis 26 of the flow passage 16. The races 22 all have substantially the same radius. An annular elastomer compression seal 28 is positioned between axial faces of the male connector 12 and the female connector 14 to prevent fluid flow therebetween. The compression seal 28 is pre-stressed.

When fluid under pressure is introduced into the flow passage 16 there results a hydrostatic end load causing the male and female connectors 12, 14 to be biased axially away from each other. The ball bearings 24 are then subject to axial resultant forces which are transmitted through contact surfaces between the ball bearings 24 and the races 22. The resultant force to which each bearing race 22 is subject is distributed in relation to the relative position of each race. For instance, the male member groove 18 closest to the seal 28 is subject to a first load, the second groove is subject to a second load which is cumulative of the first load, and so on. Thus, with each successive bearing race 22 moving away from the seal 28, the cumulative load on the male member groove 18 increases. The female connector 14 is subject to analogous loading, with the race closest to the seal bearing the greatest cumulative load.

In a typical tri-race bearing assembly 10 as shown in FIG. 1, the load distribution for each race 22 beginning with that closest to the seal 28 is approximately 47%, 31% and 22%. It is desirable then to distribute the load more equally so as to reduce the load on the first race without reducing the overall load bearing capacity of the bearing assembly. The present invention accomplishes this through the stepped configuration.

The first embodiment of the present invention is shown in FIG. 2. A swivel joint 110 has a male connector 112 rotatably

received inside of a female connector **114**. A sealed fluid flow passage **116** is formed therethrough, in communication with fluid conduits or pipes (not shown) extending from each connector. Each connector **112**, **114** has respectively formed thereon a plurality of annular grooves **118**, **120**. When the connectors **112** and **114** are inserted together, the grooves **118** and **120** align with each other forming annular bearing races **122**. A plurality of ball bearings **124** are housed in each race **122** to provide bearing support and to enable swiveling of the connectors **112**, **114** relative to each other. The races **122** and ball bearings **124** are coaxially positioned around a central axis **126** of the flow passage **116**.

The present invention provides for a stepped arrangement wherein the [radii of the bearing races **122** increase progressively in consecutive races **122** in a direction moving away from the male connector end which contacts the female connector **114**] *radius of each bearing race 122 as measured from the central axis 126 becomes progressively larger the farther the bearing race is located from the male connector end, which is defined herein as the end of the male connector 112 which engages the female connector 114.* This stepped design more uniformly distributes loading per ball bearing **124** by more uniformly distributing tensile stress across each hub section at each respective race **122**. The number of steps can vary from two or more and there can be one or more races per step. The radius of each bearing race, as measured from the central axis **126**, is preferably determined as a function of the cross-sectional areas of the male and female connectors at the race, the maximum end load which the swivel joint **110** is designed to accommodate, and the diameter of the balls **124**. The radii of the bearing races are calculated to distribute the end load more evenly among the bearing races than in the prior art swivel joint of FIG. 1. It is desirable, though not required, that the ball bearings **124** are of uniform size throughout the assembly **110** and, thus, each race **122** will contain a different number of ball bearings **124**.

In the embodiment of the invention wherein the diameter of all the balls **124** is the same *and each step comprises only one bearing race 122*, the radius of each bearing race **122** is preferably determined such that the number of balls in each race is one more than the number of balls in each adjacent race closer to the male connector end [which contacts the female connector **114**]. The increase in the radius of each consecutive bearing race **122** necessary to accommodate one additional ball **124** has been found to be sufficient to distribute the hydrostatic end load more evenly over the bearing races. As is known in the art, the number of balls of a given diameter which can be accommodated in a bearing race depends on the circumference of the bearing race. Conversely, given a desired number of balls of a certain diameter, the required circumference of the bearing race can be determined. Thus, once the radius of the bearing race **122** closest to the male connector end [which contacts the female connector] has been determined, the radii of the remaining bearing races can be determined. For example, in the exemplary $2\frac{3}{4}$ " swivel joint **110** shown in FIG. 2, the balls **124** are each $\frac{3}{8}$ " in diameter and the [first] bearing race **122** closest to the male connector end houses 34 balls, the [second] next bearing race houses 35 balls and the [third] bearing race farthest from the male connector end houses 36 balls.

In accordance with the present invention, therefore, the radius of the bearing race 122 which is located farthest from the male connector end is larger than the radius of the bearing race which is located closest to the male connector end. In the embodiment of the invention shown in FIG. 2, for example, the radius of the first bearing race 122, which is

located farthest from the male connector end, is larger than the radius of the third bearing race, which is located closest to the male connector end, by an amount sufficient to enable the first bearing race to accommodate two more balls 124 than the third bearing race. Of course, the sizing of the radii of the first and third bearing races 122 will enable the second bearing race to have a radius which will allow it to accommodate one less ball 124 than the first bearing race and one more ball than the third bearing race. However, the second bearing race 122 need not have a different radius than either the first or third bearing races; it may, for example, have the same radius as the third bearing race. In this event, the radius of the first bearing race 122 is preferably selected such that the first bearing race can accommodate at least one and preferably two more balls than the second and third bearing races.

The present invention utilizes a straight bore seal **128** of the type disclosed in U.S. Pat. No. 4,930,791 made of non-metallic compositions such as "TEFLON" having different properties than conventional elastomer compression seals such as the seal **28** of FIG. 1. Conventional elastomer seal materials have inherent limitations with respect to fluid compatibility, temperature range, and rupture. The axial ends of the male and female connectors **112**, **114** have recessed sections **130** and **132**, respectively, which form one recessed groove **134** when the connectors **112**, **114** are fitted together as shown in FIG. 2. The straight bore seal **128** is received therein such that the inner circumferential surface **138** of the seal **128** is flush with the inner surface of the flow passage **116**. The recessed sections **130** and **132** have axial end portions **140** and **142** facing toward each other which receive the axial ends of the straight bore seal **128**. The end portions **140** and **142** are engaged by axial ends **144** and **146** of the straight bore seal **128**. The outer circumferential surface **148** forms a seal with the inner circumferential surface of the groove **134**. Because the geometry and material of the straight bore seal **128** allows a substantially smaller cross-sectional area than a comparable capacity conventional elastomer seal **28**, hydrostatic end loading and, thus, contact force between each ball bearing **124** and race **122** are reduced significantly, resulting in less brinelling of the race **122**. The assembly **110** embodied in FIG. 2 further includes a ball bearing port **150** and secondary elastomer O-ring or other suitable seals **152**. A leak detection port **154** is also provided.

In order to further illustrate the novelty of the present invention, FIGS. 3a and 3b show the prior art assembly **10** of FIG. 1 juxtaposed with a second embodiment **210** of the present invention assembly along centerline **200**. Because the straight bore seal **228** has a lower seal profile than the conventional seal **28**, the sealing radius **256** of the present invention is smaller than the sealing radius **56** of the conventional seal **28**. This results in a smaller area of the connectors subject to hydrostatic pressure and, thus, a reduced hydrostatic end load. While the conventional seal **28** is subject to pre-stress axial compression, the straight bore seal **228** is free of axial loading. Thus, axial forces between the connectors and the seal **228** are generally non-existent, while the conventional seal **28** contacts the female connector **14** on inner circumferential and axial surfaces and contacts the male connector **12** on an axial surface.

Referring to FIG. 6, however, the swivel joint **110**, which includes a stepped bearing arrangement in accordance with the present invention, can comprise a conventional seal **28** to seal between the male and female connectors **112**, **114**. The seal **28** has several features which may make it more suitable than the straight bore seal **128** for certain applications.

5

FIG. 4a illustrates a conventional bearing arrangement subject to hydrostatic loading in which a ball bearing 24 is received in a race 22 formed by male and female connector grooves 18, 20. Typical bearing races such as the one illustrated in FIG. 4a are machined as grooves 18,20 having a constant radius 321. The groove radius 321 must be greater than the radius 322 of the ball bearings to the extent that assembly is possible. This results in concentrated contact areas 318,320 when the connectors shift under axial load. Such load concentrations subject the races to brinelling.

In order to reduce concentration of contact areas as described above, the present invention provides grooves having offset radii as illustrated in FIG. 4b. As shown in FIG. 4b, the female connector groove 420 is formed with substantially the same radius as the ball bearing 424 except that at the apex 422 of the groove 420 there is a straight line portion 425 formed by offsetting the center point 426 of the radius of the groove 420 to an offset center point 428. Thus the groove 420 does not form, in profile, a perfect half circle due to the straight line portion 425 on the perimeter of the groove at the apex 422. The male connector groove 418 can be formed with substantially the same radius as the ball bearing 424. This design provides enough clearance to facilitate assembly while maximizing the contact areas between the ball bearing 424 and the respective grooves 418,420, thereby minimizing brinelling. Either connector groove for an individual race can have the offset radius feature, or both grooves can have a reduced offset distance.

FIG. 5 illustrates a third embodiment of the invention utilizing the stepped configuration illustrated in the embodiment of FIG. 2, having connectors 512,514 that are placed end to end and joined by a collar 513 which fits around the connectors 512,514. Each connector 512,514 has a plurality of stepped grooves 518,519 corresponding to a plurality of stepped grooves 520,521 in the collar 513. A single straight bore seal 538 is utilized. The embodiment herein operates essentially the same way and utilizes essentially the same features as the first embodiment described in FIG. 2.

Although the best mode contemplated for carrying out the invention has been herein shown and described, it is understood that modifications and variations may be made without departing from what is regarded as the subject matter of the invention.

What is claimed is:

1. A swivel joint comprising:

a central axis;

a tubular male member having an outer annular surface, a first end and at least first and second outer annular grooves formed on the outer surface coaxial with the central axis;

a tubular female member having an inner annular recess, an annular shoulder formed at an inner end of the recess and at least first and second inner annular grooves formed on the recess coaxial with the central axis;

wherein the outer surface of the male member is adapted to be received in the recess of the female member such that the first end is disposed proximate the shoulder and each outer groove is aligned with a corresponding inner groove to thereby define at least first and second annular races;

a plurality of balls disposed in each race to secure said male and female members together and to facilitate relative rotation of the male and female members about the central axis;

wherein the radius of each race as measured from the central axis is greater than the radius of each adjacent race closer to the first end of the male member; and

6

wherein the number of balls in each race is just one more than the number of balls in each adjacent race closer to the first end.

2. The swivel joint of claim 1, further comprising means for sealing between the male and female members.

3. The swivel joint of claim 2, wherein the sealing means comprises an annular seal disposed between the first end of the male member and the shoulder of the female member.

4. The swivel joint of claim 3, wherein the annular seal is comprised of an elastomer.

5. The swivel joint of claim 2, wherein the sealing means comprises a straight bore seal which is disposed in a seal pocket formed in adjacent portions of the male and female members.

6. The swivel joint of claim 1:

wherein the cross section of at least each outer groove or each inner groove comprises first and second accurate segments each having a distinct centerpoint and substantially the same radius;

wherein the centerpoint of the first segment is offset from the centerpoint of the second segment in a direction parallel to the central axis; and

wherein the radius of the first and second segments is substantially the same as the radius of the balls.

7. A swivel joint comprising:

a central axis;

a tubular male member having an outer annular surface, a first end and at least first and second outer annular grooves formed on the outer surface coaxial with the central axis;

a tubular female member having an inner annular recess, an annular shoulder formed at an inner end of the recess and at least first and second inner annular grooves formed on the recess coaxial with the central axis;

wherein the outer surface of the male member is adapted to be received in the recess of the female member such that the first end is disposed proximate the shoulder and each outer groove is aligned with a corresponding inner groove to thereby define at least first and second annular races;

a plurality of balls disposed in each race to secure said male and female members together and to facilitate relative rotation of the male and female members about the central axis;

wherein the radius of each race as measured from the central axis is greater than the radius of each adjacent race closer to the first end of the male member by an amount sufficient to enable each race to accommodate just one more ball than is disposed in the adjacent race.

8. The swivel joint of claim 7, further comprising means for sealing between the male and female members.

9. The swivel joint of claim 8, wherein the sealing means comprises an annular seal disposed between the first end of the male member and the shoulder of the female member.

10. The swivel joint of claim 9, wherein the annular seal is comprised of an elastomer.

11. The swivel joint of claim 8, wherein the sealing means comprises a straight bore seal which is disposed in a seal pocket formed in adjacent portions of the male and female members.

12. The swivel joint of claim 7:

wherein the cross section of at least each outer groove or each inner groove comprises first and second accurate segments each having a distinct centerpoint and substantially the same radius;

7

wherein the centerpoint of the first segment is offset from the centerpoint of the second segment in a direction parallel to the central axis; and

wherein the radius of the first and second segments is substantially the same as the radius of the balls.

13. A swivel joint comprising:

a central axis;

a pair of tubular members each having a first end and a plurality of outer annular grooves formed coaxial with the central axis;

a collar member comprising a pair of inner cylindrical recesses each having a plurality of inner annular grooves formed coaxial with the central axis;

wherein each tubular member is adapted to be received in a corresponding recess of the collar member such that the first ends are proximate one another and each outer groove is aligned with a corresponding inner groove to thereby define a plurality of annular races;

a plurality of balls disposed in each race to secure said tubular members in said collar and to facilitate relative rotation of the tubular members about the central axis;

wherein the radius of each race as measured from the central axis is greater than the radius of each adjacent race closer to the first ends of the tubular members; and

wherein the number of balls in each race is just one more than the number of balls in each adjacent race closer to the first ends of the tubular members.

14. The swivel joint of claim 13, further comprising means for sealing between each tubular member and the collar member.

15. The swivel joint of claim 14, wherein the sealing means comprises an annular seal disposed between the first ends of the tubular members.

16. The swivel joint of claim 15, wherein the annular seal is comprised of an elastomer.

17. The swivel joint of claim 14, wherein the sealing means comprises a straight bore seal which is disposed in a seal pocket formed in adjacent portions of the first ends of the tubular members.

18. The swivel joint of claim 13:

wherein the cross section of at least each outer groove or each inner groove comprises first and second arcuate segments each having a distinct centerpoint and substantially the same radius;

wherein the centerpoint of the first segment is offset from the centerpoint of the second segment in a direction parallel to the central axis; and

wherein the radius of the first and second segments is substantially the same as the radius of the balls.

19. A swivel joint comprising:

a central axis;

a tubular male member having an outer annular surface, a first end and at least first and second outer annular grooves formed on the outer surface coaxial with the central axis;

a tubular female member having an inner annular recess and at least first and second inner annular grooves formed on the recess coaxial with the central axis;

wherein the first end of the male member is adapted to be received in the recess of the female member such that each outer groove is aligned with a corresponding inner groove to thereby define at least first and second annular races;

a plurality of balls disposed in the first and second races to secure the male and female members together and to

8

facilitate relative rotation of the male and female members about the central axis;

wherein the radius of the first race as measured from the central axis is greater than the radius of an adjacent race closer to the first end of the male member; and

wherein the number of balls in the first race is just one more than the number of balls in the adjacent race closer to the first end of the male member.

20. A swivel joint comprising:

a central axis;

a tubular male member having an outer annular surface, a first end and at least first, second and third outer annular grooves formed on the outer surface coaxial with the central axis;

a tubular female member having an inner annular recess and at least first, second and third inner annular grooves formed on the recess coaxial with the central axis;

wherein the first end of the male member is adapted to be received in the recess of the female member such that each outer groove is aligned with a corresponding inner groove to thereby define at least first, second and third annular races;

wherein the first race is located farther from the first end of the male member than either the second or third races, the third race is located closer to the first end than either the first or second races, and the second race is located between the first and third races;

a plurality of balls disposed in the first, second and third races to secure the male and female members together and to facilitate relative rotation of the male and female members about the central axis;

wherein the radius of the first race as measured from the central axis is greater than the radius of third race; and wherein the number of balls in the first race is just two more than the number of balls in the third race.

21. A swivel joint comprising:

a central axis;

a tubular male member having an outer annular surface, a first end and at least first and second outer annular grooves formed on the outer surface coaxial with the central axis;

a tubular female member having an inner annular recess and at least first and second inner annular grooves formed on the recess coaxial with the central axis;

wherein the first end of the male member is adapted to be received in the recess of the female member such that each outer groove is aligned with a corresponding inner groove to thereby define at least first and second annular races;

a plurality of balls disposed in the first and second races to secure the male and female members together and to facilitate relative rotation of the male and female members about the central axis;

wherein the radius of the first race as measured from the central axis is greater than the radius of an adjacent race closer to the first end of the male member by an amount sufficient to enable the first race to accommodate just one more ball than the adjacent race.

22. A swivel joint comprising:

a central axis;

a tubular male member having an outer annular surface, a first end and at least first, second and third outer annular grooves formed on the outer surface coaxial with the central axis;

9

a tubular female member having an inner annular recess and at least first, second and third inner annular grooves formed on the recess coaxial with the central axis;

wherein the first end of the male member is adapted to be received in the recess of the female member such that each outer groove is aligned with a corresponding inner groove to thereby define at least first, second and third annular races;

wherein the first race is located farther from the first end of the male member than either the second or third races, the third race is located closer to the first end

10

than either the first or second races, and the second race is located between the first and third races;

a plurality of balls disposed in the first, second and third races to secure the male and female members together and to facilitate relative rotation of the male and female members about the central axis;

wherein the radius of the first race as measured from the central axis is greater than the radius of the third race by an amount sufficient to enable the first race to accommodate just two more balls than the third race.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : RE 39,695 E
APPLICATION NO. : 10/387023
DATED : June 19, 2007
INVENTOR(S) : Tep Ungchusri and Sergio A. Castillo

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Col. 6, line 17 (claim 6, line 3), change "accurate" to -- arcuate --.

Col. 6, line 65 (claim 12, line 3), change "accurate" to -- arcuate --.

Col. 7, line 43 (claim 18, line 2), change "lest" to -- least --.

Signed and Sealed this

Thirty-first Day of July, 2007

A handwritten signature in black ink on a light gray dotted background. The signature reads "Jon W. Dudas" in a cursive style.

JON W. DUDAS

Director of the United States Patent and Trademark Office