

#### US00RE39938E

## (19) United States

## (12) Reissued Patent

#### **Brain**

### (10) Patent Number: US RE39,938 E

#### (45) Date of Reissued Patent: Dec. 18, 2007

#### (54) GASTRO-LARYNGEAL MASK

(75) Inventor: Archibald Ian Jeremy Brain, Chertsey

(GB)

(73) Assignee: Indian Ocean Medical, Inc., Mahe

(SC)

(21) Appl. No.: 09/803,452

(22) Filed: Mar. 8, 2001

#### Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **5,878,745** 

Issued: Mar. 9, 1999
Appl. No.: 08/921,169
Filed: Aug. 29, 1997

U.S. Applications:

(63) Continuation of application No. 08/609,521, filed on Mar. 1, 1996, now abandoned.

(51) **Int. Cl.** 

 A61M 16/00
 (2006.01)

 A61M 29/00
 (2006.01)

 A61M 5/32
 (2006.01)

 A62B 9/06
 (2006.01)

(58) Field of Classification Search ......................... 128/200.26,

128/207.15, 207.14, 200.24; 604/103.07, 604/96–103

See application file for complete search history.

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

2,839,788 A 6/1958 Dembiak 2,862,498 A 12/1958 Weekes

(Continued)

#### FOREIGN PATENT DOCUMENTS

CA	2141167	7/1995
CA	2067782	6/1999

CA 2012750 8/1999

#### (Continued)

#### OTHER PUBLICATIONS

Oxford University Press, "Concise Medical Dictionary, Fourth Edition", 1994, pp. 582–585 and 641–642. U.S. Appl. No. 07/919,289, filed Jul. 24, 1992, Brain. Abdelatti, "A Cuff Pressure Controller for Tracheal Tubes and Laryngeal Mask Airway," Anaesthesia, 1999, vol. 54, pp. 981–986.


#### (Continued)

Primary Examiner—Justine R. Yu
Assistant Examiner—Annette Dixon
(74) Attorney, Agent, or Firm—Wilmer, Cutler, Pickering,
Hale and Dorr LLP

#### (57) ABSTRACT

A gastro-laryngeal mask features softly compliant construction of the distal half of the mask, wherein the mask is of generally elliptical configuration, with an inflatable peripheral cuff to seal and support the mask around the laryngeal inlet. A back cushion is inflatable to engage the back wall of the pharynx and thus to forwardly load the peripheral-cuff seal to the laryngeal inlet. An evacuation tube for external removal of a possible gastric discharge completes an evacuation or discharge passage contained within the mask and opening through the distal end of the peripheral cuff. Special provision is made for assuring integrity of the discharge passage within the flexible distal half of the mask, i.e., assuring against collapse of the distal-end half of the softly compliant evacuation tube in the distal region of the mask, such that inflation of the mask does not compromise viability of the evacuation tube by compressing softly compliant material of the evacuation tube during periods of mask inflation. The special provision also favors such collapse of the mask when deflated as to provide a leading flexible edge for piloting a safe and correct advancing insertional advance of the deflated mask in the patient's throat, in avoidance of epiglottis interference and to the point of locating engagement in the upper sphincter of the oesophagus.

#### 45 Claims, 3 Drawing Sheets



# US RE39,938 E Page 2

II S DATENIT	DOCUMENTS	5	,554,673	Δ	9/1996	Shah	
U.S. IAIENI	DOCUMENTS		,569,219			Hakki et al.	
3,529,596 A 9/1970	Garner		,577,693		11/1996		
3,554,673 A 1/1971	Schwartz et al.		5,582,167		12/1996		
3,683,908 A 8/1972	Tantrimudalige et al.		,584,290		12/1996	-	
3,794,036 A 2/1974	Carroll		5,599,301			Jacobs et al.	
3,931,822 A 1/1976	Marici		,623,921			Kinsinger et al.	
, ,	Winicki et al.		,626,151		5/1997	•	
4,104,357 A 8/1978			,632,271		5/1997		
4,116,201 A 9/1978			•			Callaghan et al	604/103.07
4,134,407 A 1/1979			,653,229			Greenberg	004/103.07
	Walker		,			2	
4,178,938 A 12/1979			5,655,528 5,682,880			•	
4,178,940 A 12/1979		_	6,682,880				
	Scarberry 128/	_	,692,498 ,694,929			Lurie et al. Christopher	
	Dryden 128/. Gezari et al.		5,711,293			<b>-</b>	
, ,	Scarberry 128/		5,738,094				
4,331,330 A 3/1982 4,446,864 A 5/1984	-		5,743,254		4/1998		
4,471,775 A 9/1984			,746,202		5/1998		
4,501,273 A 2/1985			,771,889		6/1998	•	
	Brain 604/		,778,872			Fukunaga et al.	
4,510,273 A 4/1985			,791,341			•	
4,526,196 A 7/1985			,			Komesaroff	
4,553,540 A 11/1985			,819,723		10/1998		
4,583,917 A 4/1986			,832,916			Lundberg et al.	
	Weerda et al.		,850,832		12/1998	~	
4,689,041 A 8/1987	Corday et al.	5	,855,203	A	1/1999	Matter	
	Eliachar	5	,856,510	A	1/1999	Meng et al.	
4,770,170 A 9/1988	Sato et al.	5	,860,418	A	1/1999	Lundberg et al.	
4,793,327 A 12/1988	Frankel	5	,865,176	A	2/1999	O'Neil	
4,798,597 A 1/1989	Vaillancourt	5	,878,745	A	3/1999	Brain	
4,825,862 A 5/1989	Sato et al.	5	,881,726	A	3/1999		
4,832,020 A 5/1989	Augustine		,893,891			Zahedi et al.	
	Farahany		,896,858		4/1999		
, ,	Kowalewski et al.		,915,383		6/1999		
4,872,483 A 10/1989			,924,862		7/1999		
, ,	Levinson		,937,860		8/1999		
, ,	Poole, Jr.		,957,133		9/1999		
	Bombeck, IV		,979,445			Neame et al.	
, ,	Brain 128/.		,983,891			Fukunaga	
, ,	Parker		,983,890 ,983,897			Fukunaga et al.	
5,042,469 A 8/1991 5,042,476 A 8/1991	Smith		,988,167			~	
	Augustine		,996,582			Turnbull	
	Turnbull et al.		5,003,510		12/1999		
, ,	Levinson		,			Fukunaga et al.	
	Nguyen et al.		5,003,514		12/1999	~	
	Brain 128/	_	5,012,452			C	
5,249,571 A 10/1993			,021,779		2/2000	•	
5,273,537 A 12/1993			,050,264			Greenfield	
5,277,178 A 1/1994		6	,062,219	A	5/2000	Lurie et al.	
	Brain 128/	207.15	,070,581	A	6/2000	Augustine et al.	
5,297,547 A * 3/1994	Brain 128/	/207.15	,079,409	A	6/2000	Brain	
5,303,697 A * 4/1994	Brain 128/	<sup>207.15</sup> I	0429,811	S	8/2000	Bermudez et al.	
5,305,743 A * 4/1994	Brain 128/	207.15	,095,144	A	8/2000	Pagan	
5,311,861 A 5/1994	Miller et al.	6	,098,621	A	8/2000	Esnouf et al.	
5,331,967 A 7/1994	Akerson et al.	6	5,110,143	A	8/2000	Kamen	
5,339,805 A 8/1994	Parker		5,116,243		9/2000	~	
, ,	Don Michael		,119,695			Augustine et al.	
	Brain 128/		5,131,571			Lampotang et al.	
5,361,753 A 11/1994			5,149,603		11/2000		
5,391,248 A 2/1995			5,155,257			Lurie et al.	
	Pirak et al.		,		-	Block et al.	
	Cinberg et al.		5,224,562 5,234,985			Lurie et al.	
5,452,715 A 9/1995 5,459,700 A 10/1995	Boussignac et al.		5,234,985 5,240,922		6/2001	Lurie et al.	
,	Levinson		5,251,093			Valley et al.	
, ,	Fukuhara		5,269,813			Fitzgerald et al.	
	Champeau		5,315,739			Merilainen et al.	
	Virag et al.		,390,093		-	Mongeon	
	Lurie et al.		,427,686			Augustine et al.	
			-				

6,439,232	В1	8/2002	Brain
6,450,164	B1	9/2002	Banner et al.
6,631,720	B1	10/2003	Brain et al.
6,647,984	B1	11/2003	O'Dea et al.
6,651,666	B1	11/2003	Owens
6,705,318	B1	3/2004	Brain
7,004,169	B2	2/2006	Brain et al.
7,040,322	B2	5/2006	Fortuna et al.
7,051,096	B1	5/2006	Krawiec et al.
7,097,802	B2	8/2006	Brain et al.
7,128,071	B2	10/2006	Brain et al.
7,134,431	B2	11/2006	Brain et al.
7,156,100	B1	1/2007	Brain et al.
7,159,589	B2	1/2007	Brain
2003/0051734	$\mathbf{A}1$	3/2003	Brain
2003/0101998	$\mathbf{A}1$	6/2003	Zocca et al.
2003/0131845	$\mathbf{A}1$	7/2003	Lin
2003/0172925	A1	9/2003	Zocca et al.
2005/0274383	A1	12/2005	Brain
2006/0124132	A1	6/2006	Brain
2006/0254596	<b>A</b> 1	11/2006	Brain

#### FOREIGN PATENT DOCUMENTS

DE	10042172	4/2001
EP	0389272	9/1990
$\mathbf{EP}$	0402872	12/1990
EP	0294200	4/1992
$\mathbf{EP}$	0580385	5/1996
EP	0712638	5/1996
$\mathbf{EP}$	0 732 116 A	2 9/1996
EP	0796631	9/1997
$\mathbf{EP}$	0845276	6/1998
EP	0865798	9/1998
EP	0922465	6/1999
EP	1125595	8/2001
EP	1119386 B	1 9/2005
GB	2111394	7/1983
GB	2205499	1/1991
GB	2298797 A	9/1996
GB	2317342	3/1998
GB	2317830	4/1998
GB	2318735	5/1998
GB	2319478	5/1998
GB	2321854	8/1998
GB	2323289	9/1998
GB	2323290	9/1998
GB	2323291	9/1998
GB	2323292	9/1998
GB	2359996	9/2001
JP	10118182	5/1998
JP	10216233	8/1998
JP	10263086	10/1998
JP	10277156	10/1998
JP	10314308	12/1998
JP	10323391	12/1998
JP	10328303	12/1998
JP ID	11128349	5/1999 7/1000
JP ID	11192304	7/1999 8/1999
JP WO	11206885	3/1991
WO	WO-91/03207 WO-91/07201	5/1991 5/1991
WO	WO-91/07201 WO-91/12845	9/1991
WO	WO-91/12843 WO-92/13587	8/1991
WO	WO-92/13387 WO-95/33506	12/1995
WO	WO-95/33300 WO-97/12640	4/1997
WO	WO-97/12641	4/1997
WO	WO-98/16273	4/1998
WO	WO-99/06093	2/1999
WO	WO 00/09189	2/2000
WO	WO-00/22985	4/2000
WO	WO-00/23135	4/2000
<del>-</del>		

WO WO-00/61212 10/2000

#### OTHER PUBLICATIONS

Benumof, "Laryngeal Mask Airway and teh ASA Difficult Airway Algorithm," Anesthesiology, 1996, vol. 84(3), pp. 686–699.

Bernhard et al., "Adjustment of Intracuff Pressure to Prevent Aspiration," Anesthesiology, 1979, vol. 50(4), pp. 363–366. Bernhard et al., "Physical Characteristics of and Rates of Nitrous Oxide Diffusion into Tracheal Tube Currs," Anesthesiology, 1978, vol. 48, pp. 413–414.

Brain, "The Laryngeal Mask—A New Concept in Airway Management," Br. J. Anaesth., 1983, vol. 55, pp. 801–805. Brain, "The Laryngeal Mask Airway—A Possible New Solution to Airway Problems in the Emergency Situation," Archives of Emergency Medicine, 1984, vol. 1, pp. 229–232.

Brain, "The Laryngeal Mask Airway," Anaesthesia, 1985, vol. 40, pp. 356–361.

Brain, "Three Cases of Difficult Intuition Overcome by the Laryngeal Mask Airway," Anaesthesia, 1985, vol. 40, pp. 353–355.

Brain, et al., "A New Laryngeal Mask Prototype," Anaesthesia, 1995, vol. 50, pp. 42–48.

Brimacombe, "The Split Laryngeal Mask Airway," p. 639. Broderick et al., "The Laryngeal Mask Airway," Anaesthesia, 1989, vol. 44, pp. 238–241.

Burgard, et al., "The Effect of Laryngeal Mask Cuff Pressure on Postoperative Sore Throat Incidence," J. Clinical Anesthesia, 1996, vol. 8, p. 198–201.

Caplan, et al., "Adverse Respiratory Events in Anesthesia: A Clsoed Claims Analysis", Anesthesiology 72: 828–833, 1990.

Communication of a notice of opposition, European Patent Office, Feb. 15, 2006 (cover page and pp. 1–4).

Craven, "Prevention of Hospital-Acquried Pneumonia: Measuring Effect in Ounces, Pounds, and Tonds," Annals of Internal Medicine, 1995, vol. 122(3), pp. 229–231.

Cuff-Pressure-Control DCR, 2000, LogoMed.

Davies, et al., "Laryngeal Mask Airway and Tracheal Tube Insertion by Unskilled Personnel," The Lancet, vol. 336, pp. 977–979.

DeMello, et al., "The Use of the Laryngeal Mask Airway in Primary Anaesthesia," Anaesth. Corresp., 1990, vol. 45, pp. 793.

Doyle et al., "Intraoperative Awareness: A Continuing Clinical Problem," http://doyle.ibme.utoronoto.ca/anesthesia/aware.htm.

Engbers, "Practical Use of 'Diprifusor' Systems," Anaesthesia, 1998, vol. 53(1), pp. 28–34.

Eriksson et al., "Functional Assessment of the Pharynx at Rest and During Swallowing in Partially Paralyzed Humans," Anesthesiology, 1997, vol. 87(5), pp. 1035–1042. Glen, "The Development of 'Diprifusor': A TCI System for Propofol," Anaesthesia, 1998, vol. 53(1), pp. 13–21.

Gray et al., "Development of the Technology for 'Diprifusor' TCI Systems," Anaesthesia, 1998, vol. 53(1), pp. 22–27. Heath, "Endotracheal Intubation Through the Laryngeal Mask—Helpful When Laryngoscopy is Difficult or Dangerous," European J. of Anaesthesiology, 1991, vol. 4, pp. 41–45.

Hickey, et al., "Cardiovascular Response to Insertion of Brain's Laryngeal Mask," Anesthesia, 1990, vol. 45, pp. 629–633.

Inomata et al., "Transient Bilateral Vocal Cord Paralysis After Insertion of a Laryngeal Mask Airway," Anesthesiology, 1995, vol. 82, pp. 787–788.

Jacobson et al., "A Study of Intracuff Pressure Measurements, Trends and Behaviours in Patients During Prolonged Period of Tracheal Intubation," Br. J. Anaesth., 1981, vol. 53, pp. 97.

Kambic et al., "Intubation Lesions of the Larynx," Br. J. Anasth. 1978, vol. 50, pp. 587–590.

Lindholm, "Prolonged Endotracheal Intubation," ACTA Anaesthesiologica Scandinavica, 1969, vol. 33, pp. 32–46. Majumder et al., "Bilateral Lingual Nerve Injury Following the Use of the Laryngeal Mask Airway," Anaesthesia, 1998, vol. 53, pp. 184–186.

Miller, "A Pressure Regulator for the Cuff of a Tracheal Tube," Anaesthesia, 1992, vol. 47, pp. 594–596.

Muthuswamy et al., "The Use of Fuzzy Integrals and Bispectral Analysis of the Electroencephalogram to Predict Movement under Anesthesia," IEEE Transactions on Biomedical Engineering, 1999, vol. 46(3), pp. 290–299.

Nagai, "Unilateral Hypoglossal Nerve Paralysis Following the Use of the Laryngeal Mask Airway," Anaesthesia, 1994, vol. 49, pp. 603–604.

Observations by Third Party Concerning European Patent Application No. 99 947 765.6–2318, European Patent Office, Munich, Germany, Jan. 18, 2005 (3 pgs.).

Patel et al., "Tracheal Tube Cuff Pressure," Anaesthesia, 1984, vol. 39, pp. 862–864.

Pennant, "Comparison of the Endotracheal Tube and Laryngeal Mask in Airway Management by Paramedical Personnel," Anesth. Analg., 1992, vol. 74, pp. 531–534.

Pippin et al., "Long–Term Tracheal Intubation Practice in the United Kingdom," Anaesthesia, 1983, vol. 38, pp. 791–795.

Raeder et al. "Tracheal Tube Cuff Pressures," Anaesthesia, 1985, vol. 40, pp. 444–447.

Response to Complaint Matter No.: 4b 0 440–05, In the Matter of: LMA Deutschland GmbH versus *Ambu* (*Deutschland*) *GmbH*, Feb. 10, 2006, pp. 1–47.

Seegobin et al., "Endotracheal Cuff Pressure and Tracheal Mucosal Blood Flow: Endoscopic Study of Effects of Four Large Volume Cuffs," British Medical Journal, 1984, vol. 288.

Willis et al., "Tracheal Tube Cuff Pressure," Anaesthesia, 1988, vol. 43, pp. 312–314.

Worthington, et al., "Proceedings of the Anaesthetic Research Society," Br. J. Anaesthesia, 1995, vol. 75, pp. 228P–229P.

Wynn et al., "Tongue Cyanosis After Laryngeal Mask Airway Insertion," Anesthesiology, 1994, vol. 80(6), pp. 1403.

Benumof, JL, "Management of the Difficult Adult Airway with Special Emphasis on Awake Tracheal Intubation", Anesthesiol., vol. 75, No. 6, pp. 1087–1110, 1991.

"Improving Anaesthesia", Med Pro Monthly, Nov.–Dec., 1998, pp. 311–312.

Kapila, A. et al., "Intubating LMA; A Preliminary Assessment of Performance", British Journal of Anaethsia, vol. 75, pp. 228–229, 1995 (abstract).


Laryngeal Mask Publications, 74 pages, Dec. 1998, www.saga.nl/lma/lmapub.htm.


Martin, T., "Patentability of Methods of Medical Treatment: A Comparative Study", Journal of the Patent and Trademark Office Society, pp. 381–423, Jun. 2000.


Neurometric Assessment of Adequacy of Intraoperative Anesthetic. Mar. 1999, 3 pages, www.pnl.gov/medical/info/neuro.htm.

Rieger et al., Anesthesiology, vol. 87, No. 1, Jul. 1997.

<sup>\*</sup> cited by examiner







#### GASTRO-LARYNGEAL MASK

Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions 5 made by reissue.

#### RELATED CASE

This application is a continuation of original application, Ser. No. 08/609,521, filed Mar. 1, 1996, now abandoned. 10

#### BACKGROUND OF THE INVENTION

This invention relates to a laryngeal-mask airway (LMA) device, which is an artificial airway device designed to facilitate lung ventilation in an unconscious patient by forming a low-pressure seal around the laryngeal inlet. An inflatable-ring seal surrounds an appropriately shaped mask which fits into the lower pharynx and is attached to a tube which emerges from the mouth, as for connection to medical gas-supply tubing.

More particularly, the invention relates to a variety of laryngeal masks, known as gastro-laryngeal masks (GLM), wherein, provision is made for airway assurance to the stomach contents while unconscious. U.S. Pat. No. 5,241, 956 deals with this problem by providing an evacuation tube which is open through the center of the inflatable seal of the laryngeal mask, thus utilizing the distal end of the inflatable ring as an inflatable-cuff formation which establishes peripherally sealed engagement to the upper sphinctral region of the oesophagus and centrally supports the distal end of the evacuation tube. In addition, said U.S. Pat. No. 5,241,956 discloses a further inflatable cuff carried by the laryngeal mask and by the evacuation tube, for referencing inflation against the back wall of the pharynx, thus making it possible to establish the laryngeal-inlet seal with reduced inflation pressure, as compared with prior structures not having such an additional inflatable cuff.

U.S. Pat. No. 5,305,743 discloses moulding techniques for manufacture of a variety of laryngeal masks, including a gastro-laryngeal mask, wherein an inflatable back cushion provides such referencing inflation against the back wall of the pharynx as to widely distribute the back-wall reference, over substantially the full area of the laryngeal mask. Such a back-cushion construction has been found to be mechanically simple and highly effective, and U.S. Pat. No. 5,355, 879 discloses such a back cushion for each of several representative laryngeal-mask constructions.

In practice, although a gastro-laryngeal-mask as described in said U.S. Pat. No. 5,355,879 works well, it has the disadvantage that the gastric evacuation channel needs to be sufficiently stiff to prevent its collapse under the influence of the increased pressure within the back-cushion cuff, when it is inflated in the pharynx. A suitably stiff tube is readily provided, but the whole device is then more difficult to insert into the patient's throat, since insertion involves flexing the device around the angle at the back of the tongue. Provision of a pre-curved airway tube facilitates passage around the back of the tongue, but the advancing distal tip end of the device is then more likely to collide with the glottis (or entrance to the larynx), and indeed it may block the larynx by so doing, with consequent danger to the patient.

#### BRIEF STATEMENT OF THE INVENTION

It is an object of the invention to provide an improved gastro-laryngeal mask.

2

A specific object is to meet the above object with a construction that specifically avoids problems or difficulties with constructions of said U.S. patents.

Another specific object is to provide for ready compression and flexure of a gastric passage within a back-cushioned or cuffed gastro-laryngeal mask, when the mask is in deflated condition for insertion into the patient's throat.

Furthermore, for the deflated condition of the mask, i.e., in readiness for insertion into the patient's throat, it is an object to enable formation of a flattened flexible leading distal-end edge to self-adapt to and resiliently ride the outer limit of curvature of the patient's airway, throughout the insertional course of the deflated mask and into its locating engagement with the hypopharynx.

It is a further specific object, in conjunction with the foregoing specific objects, to provide for assurance of full patency of the gastric passage within the mask, when the mask has been inflated.

which emerges from the mouth, as for connection to medical gas-supply tubing.

More particularly, the invention relates to a variety of laryngeal masks, known as gastro-laryngeal masks (GLM), wherein. provision is made for airway assurance to the patient who is at. risk from vomiting or regurgitation of stomach contents while unconscious. U.S. Pat. No. 5,241, 956 deals with this problem by providing an evacuation tube which is open through the center of the inflatable seal of the

In a preferred embodiment of the invention, an artificial airway device to facilitate a patient's lung ventilation comprises an airway tube, an evacuation tube, and a laryngeal mask at one end of both tubes. The mask is of generally elliptical configuration and comprises a body or backplate of relatively stiffly compliant nature, and an inflatable annular cuff or ring of relatively softly compliant nature is connected to and surrounds the body or backplate. When inflated, the annular cuff adapts to and seals around the laryngeal inlet, and an inflatable cushion on the exterior of the inflated annulus bears against the back wall of the pharynx, to thereby forwardly load the inflated annulus into sealed relation with the laryngeal inlet, with the backplate dividing the mask between a laryngeal-chamber side and a pharyngeal-chamber side. The relatively stiff backplate is formed for connection to the airway tube for exclusive communication to the larynx through an opening in the backplate; and the backplate is also configured to guide and support a relatively soft flexible evacuation tube within the pharyngeal-chamber side, from a distally open end for reception of gastric products, to a proximal end for connection to an externally discharging evacuation tube.

It is a feature of the invention that along an aligning path for the flexible evacuation tube within the pharyngealchamber side of the mask, a first significant angular fraction of the periphery of the flexible tube is bonded to a stabilizing portion of the backplate, and that a second angular fraction of the periphery of the flexible tube is continuously bonded to the inner surface of the flexible back cushion, such that generally opposite unbonded further angular regions exist between the bonded regions. These unbonded further regions are provided with external stiffening ribs at a succession of axial intervals, to reinforce the unbonded regions against lateral compression when the back cushion and the inflatable ring are under inflation pressure. In this way, inflation of the annular laryngeal-inlet sealing ring and of the 65 flexible back cushion will assure a maximally open evacuation passage within the mask in inflated condition, essentially without antero-posterior or lateral compression of the

passage. And it is further assured that upon deflation of the mask, evacuation-passage compression will be essentially in the sense of achieving a squeezing and somewhat flattening deformation of the discharge passage against the formed back-plate area of evacuation-passage support; such flattening is maximal at the oesophageal end of the discharge passage, so that, when correctly deflated, the device forms a wedge shape for correct insertion.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be illustratively described in detail for a presently preferred embodiment, and for certain other embodiments, all in conjunction with the accompanying drawings, in which:

FIG. 1 is a simplified view, generally in side elevation, for the presently preferred embodiment of an artificial airway device, having at its distal end a laryngeal mask with a gastric-drainage feature of the invention, the same being shown in position for use in a patient;

FIG. 2 is a fragmentary plan view, to an enlarged scale showing the back or pharynx-facing side of the mask of FIG. 1:

FIG. 3 is a plan view to the scale of FIG. 2, showing a softly compliant moulded inflatable component of the mask, 25 as seen from the aspect of FIG. 2;

FIG. 4 is a plan view to the scale of FIG. 2, showing a relatively stiffly compliant rigidising or reinforcing backplate component of the mask, as seen from the aspect of FIG. 2;

FIG. 5 is a longitudinal section of the softly compliant component of FIG. 3, to the scale of FIGS. 2 to 4 and taken generally in the vertical plane 5—5 of substantial symmetry, but prior to an inside-out deformation step, to create the appearance of FIG. 3;

FIG. 5A is a section, taken at 5A-5A in FIG. 5;

FIG. 6 is another view in longitudinal section, to the scale of FIGS. 2 to 5 and in the vertical plane 5—5 of FIG. 3, showing the relatively stiff component of FIG. 4 in assembled relation to the softly compliant component of FIG. 3; to the general plane of ring 18 and in with the axis of the laryngeal inlet, and in the vertical plane 5—5 of FIG. 3, with the axis of the laryngeal inlet, and in the vertical plane of ring 18 and in with the axis of the laryngeal inlet, and in the vertical plane of ring 18 and in with the axis of the laryngeal inlet, and in the vertical plane of ring 18 and in with the axis of the laryngeal inlet, and in the vertical plane of ring 18 and in with the axis of the laryngeal inlet, and in the vertical plane of ring 18 and in with the axis of the laryngeal inlet, and in the vertical plane 5—5 of FIG. 4 in assembled relation to the softly compliant component of the laryngeal inlet, and in the vertical plane 5—5 of FIG. 4 in an evacuation only with the laryngeal inlet, and in the vertical plane 5—5 of FIG. 2 in the plane of ring 18 and in the vertical plane of ring 18 and in the vertical plane of ring 18 and in the vertical plane of FIG. 3 in a second relation to the softly compliant component of the laryngeal inlet, and the vertical plane of ring 18 and in the vertical plane of FIG. 3 in a second relation to the softly compliant component of the laryngeal inlet, and the vertical plane of ring 18 and in the vertical plane of FIG. 3 in a second relation to the softly compliant component of the laryngeal inlet, and the vertical plane of ring 18 and in the vertical plane of FIG. 3 in a second relation to the softly compliant component of the laryngeal inlet, and the vertical plane of ring 18 and in t

FIG. 7 is an end view, being a proximally directed view, of the distal end of the rigidising component of FIG. 4;

FIG. 8 is a simplified cross-sectional view of the inflated 45 mask of FIG. 2, taken at 8—8 in FIG. 2;

FIG. 9 is a simplified cross-sectional view of the deflated mask of FIG. 2, taken at 8—8 in FIG. 2;

FIG. 10 is a view similar to FIG. 2, to show a first modification;

FIG. 11 is a view similar to FIG. 4, to show the back-plate component in the modification of FIG. 10;

FIG. 12 is a sectional view, taken at 12—12 in FIG. 11; and

FIG. 13 is a plan view to the scale of FIG. 2 to illustrate an intermediate product which is a modification of that shown in FIGS. 5 and 6.

#### DETAILED DESCRIPTION

Referring first to the preferred embodiments of FIGS. 1 to 9, the invention is shown in application to an airway system comprising a laryngeal-mask unit 10 and its airway tube 11, installed through the mouth 12 of a patient. The mask unit 10 may be generally as described in any of the above-65 identified U.S. patents and therefore need not now be described in detail. It suffices to say that mask unit 10

4

comprises a relatively stiff body or backing-plate member, generally indicated at 13, and an apertured relatively thin body-membrane portion or panel 13' having an aperture or lumen 14 through which the airway tube 11 can establish a free externally accessible ventilation passage, via the patient's mouth 12 and throat 15, and past the epiglottis 16 to the larynx 17. The body member 13 of mask 10 may be described as generally dome-shaped, with its concave side terminating in a generally elliptical footing, and facing the laryngeal inlet; and its convex side faces the backwall of the pharynx. Body 13 is suitably of an elastomer such as silicone rubber and relatively stiff; and body member 13 is surrounded by an inflatable ring 18 which is generally elliptical and which is circumferentially united to body member 13 in essentially a single plane. The inflatable ring 18 may also be of silicone rubber, although preferably relatively soft and flexible compared to body member 13. An externally accessible tube 19 is the means of supplying air to the inflatable ring 18 and of extracting air from (and therefore collapsing) 20 ring 18 for purposes of insertion in or removal from the patient; check-valve means 21 in tube 19 will be understood to hold a given inflation or to hold a given deflation of ring **18**.

In the installed position of FIG. 1, the projecting but blunted distal end 27 of ring 18 is shaped to conform with the base of the hypopharynx where it has established limited entry into the upper sphinctral region of the oesophagus 24. The back side of body member 13 is covered by a thin flexible panel 25 (FIG. 2) which is peripherally bonded to the inflatable ring 18 (FIG. 1) and in sealed engagement at peripheral line 25' around the entrance of tubes 11 and 23 to the mask structure to define an inflatable back cushion which assures referencing to the back wall of the pharynx and thus is able to load the mask unit forward for enhanced effectiveness of inflated-ring sealing engagement to the laryngeal inlet. The inflated ring, thus-engaged to the laryngeal inlet, orients the distal-end of the airway tube 11 at an acute angle to the general plane of ring 18 and in substantial alignment with the axis of the laryngeal inlet, for direct airway com-

The laryngeal-mask unit 10 is of the GLM variety in which an evacuation tube 23 (FIG. 2) serves for extraction and external removal of gastric-discharge products from the oesophagus. Tube 23 follows the general course of the airway tube 11, with sealed entry alongside airway tube 11, beneath the back-cushion panel 25, and with passage through the interior of ring 18, near the distal end of the mask; in FIG. 3, the distally open end of the evacuation tube 23 is defined by a re-entrant tubular conduit formation 26 integrally formed with the relatively soft material of ring 18. As explained in U.S. Pat. No. 5,241,956, inflation-air supply to the back cushion may be the same (19) as for ring 18, or separate inflating means (not shown) may be provided for these separate inflatable means.

More specifically, for the particular construction shown, the relatively softly compliant flexible components may be integrally formed in a single moulding operation, in which the moulded intermediate product is an inside-out version of what will become the finished more flexible part of the finished mask unit 10. The moulded intermediate product may thus have the appearance shown in FIG. 5, following the technique described in U.S. Pat. No. 5,305,743, to which reference is made for detailed description. It suffices here to identify the inflation-air inlet formation 28, directed inwardly on a central axis 29 which also includes the outwardly directed distal-end formation of the evacuation tube 26; the central axis 29 may also be understood as

identifying the equator plane (perpendicular to the drawing of FIG. 5) which applies to the inflatable annular ring 18, after evacuation tube 26 has been swung upward (counterclockwise), in the sense suggested by arrow 30, and generally for 180° of rotation about an axis 31, which (axis 31) is normal to the plane of the drawing of FIG. 5. This 180° rotation tucks tube 26 into the flange relatively large edge 32 of the open skirt of the moulded intermediate product of FIG. 5 and makes it a simple matter to turn the remainder of the skirt inside-out, thus defining ring 18, with the edge flange 32 seated on a ledge 33 of the upper dome-shaped feature (body-membrane portion or liner 13') of the moulded intermediate product.

In the preferred form shown, the mask body member 13 (FIGS. 4 and 7) is a separately moulded component of relatively stiff nature as compared to the moulded intermediate product of FIG. 5. Stiffness vs. softness will be understood to be relative terms and not necessarily to imply that these components are formed from different materials.

In FIG. 4, the body component 13 is seen to comprise an apertured panel which is essentially a moulded dome or bowl 34 having a concave inner surface which conforms to the convex moulded contour of the dome shape 35 of the relatively soft (i.e., thin-walled) component of FIG. 5, these components being shown in FIG. 6 in assembled relation. Relative stiffness (thickness) in the bowl or dome 34 of FIG. 4 is generally in the range 2 to 5 mm, with gradually reducing thickness for greater flexibility in approach to the lower or distal end. The bowl or dome 34 has a peripheral edge which terminates in a single plane, for adhesively bonded seating to the ledge 33 of the relatively soft component of FIG. 5, after making the inside-out inversion.

The stiffness of body member 13 is greatest in the region of proximal-end seating to ledge 33, above which an inlet-air formation 36 is oriented on an axis 37 which is not only 35 inclined at an acute angle  $\alpha$  to the plane of seating to ledge 33., but is also laterally offset from the central longitudinal plane of symmetry of the mask, denoted 5—5 in FIG. 3. Relative stiffness of body member 13 is also enhanced (i) by the fact that its distal half features a slot **38** of width less than 40 the diameter of the re-entrant distal-end tube 26, (ii) by the fact that the re-entrant tube 26 is adhesively retained in cradled support by and between confronting edges of slot 38, and (iii) by the fact that the distal end of evacuation tube 23 is preferably preformed (as seen in FIG. 2) with a quarter- 45 turn helical advance to track the course of slot 38 in the upper or proximal half of body member 13. The evacuation tube 23 is preferably relatively stiff, e.g., stiffness (thickness) in the order of magnitude of the material at the upper (proximal) half of body member 13, and is seen in 50 FIG. 2 to have telescoping fit to the proximally directed upper end of re-entrant tube 26; this is an adhesively sealed fit.

Stated in other words and in explanation of the distal and proximal halves of the body member 13 and the relation of 55 these halves to the relatively thin material and distal-half extent of re-entrant tubular conduit 26, said tubular conduit may be said to extend proximally to approximately 50 percent of the longitudinal extent of the inflatable ring 18; alternatively, said tubular conduit 26 may be said to extend 60 proximally to at least substantially 50 percent of the longitudinal extent of the inflatable ring 18, consistent with the drawings of FIGS. 2, 3, and 6. Furthermore, as seen in FIG. 4, the distal half of backing-plate member 13 is essentially straight, thus determining a straight proximal direction of 65 tubular conduit 26 for substantially the distal half of the longitudinal extent of the mask.

6

As also seen in FIG. 2, the back-cushion panel 25 covers a substantial part of the posterior surface of the mask, being peripherally sealed around the generally elliptical course of inflatable ring 18, and also being centrally adhered to the re-entrant tube 26 for substantially the entire length of tube 26, as suggested by cross-hatching 39. Finally, to assure integrity of the inflatable ring 18, the re-entrant tube 26 is adhesively sealed to the adjacent edges of tube-26 local passage through ring 18 at the distal location designated 40 in FIG. 3; for purposes of avoiding undue complexity in the drawings, this adhesively sealed region is not shown but will be understood to be along the line of tube-26 intercept with locally adjacent walls of inflatable ring 18. In FIG. 5, this intercept line is accounted for by a local cut-out 40' at the distal end of the skirt of the intermediate product of FIG. 5.

The simplified sectional diagram of FIG. 8 illustrates the functional cooperation of described component parts and features of the described gastro-laryngeal mask construction, in inflated condition, to account for diametrically opposite section cuts through right and left halves of the inflatable ring 18, spaced by sealed fit of body member 13 to the inner profile of ring 18. The back-cushion panel 25, being centrally adhered at 39 to the upper central region of re-entrant tube 26, provides a lifting force which is in the direction to hold open the evacuation tube and, therefore, not to collapse tube 26 when the back cushion is inflated; without this force, in opposition to a retaining force attributable to adhesive connection to body member 13 (along edges of slot 38), there would be no tendency to hold a softly compliant tube 26 against collapse, in that the cushion panel would outwardly expand itself to a bowed shape 25' suggested by phantom outline in FIGS. 6 and 8.

Preferably, the effective arcuate extent of adhesive connection 39 is in the range 45° to 90° about the central axis of tube **26**, as seen in FIG. **8**. Preferably also, the adhesive connection of tube 26 along the straight edges of the distal half of slot 38 accounts for a corresponding range of support of tube 26 against collapse in the circumstance of backcushion inflation. In other words, inflation of the ring 18 and back cushion 25 will assure developed vertical forces to hold the evacuation passage of re-entrant tube **26** in substantially open condition, but the transversely opposed arcuate regions (each of approximately 90° arcuate extent) between these adhesively connected regions are vulnerable to compressionally inward bowing, thus reducing the sectional area of tube 26 while the mask is inflated. The invention resolves this vulnerability by providing axially spaced stiffening ribs or ridges 42 as integral formations of the re-entrant tube 26, in the initially moulded intermediate product of FIG. 5. As shown, there are three mutually opposed pairs of ridges 42, at axial spacings which are in the order of the unstressed bore diameter of tube **26**. For the indicated silicone-rubber material of the product of FIG. 5, the incremental local thickness at ridges 42 is suitably twice or three times the otherwise uniformly thin moulded product of FIG. 5, as seen in FIG. **5**A.

In FIG. 8, a section taken near the location of tube 26 connection to the more stiffly compliant evacuation tube 23, the inflated condition of the GLM mask of the invention is seen to have an overall "height" dimensions H<sub>1</sub>, meaning front-to-back (i.e., laryngeal inlet-to-pharynx back wall). When the mask is deflated, this dimension H<sub>1</sub> is seen to be reduced by approximately 50 percent, as shown at H<sub>2</sub> in FIG. 9 for the deflated condition of the same mask. When deflated, as has been pointed out in U.S. Pat. No. 5,297,547, the ring 18 collapses into flattened double walls (marked 18') which are upwardly dished; and although deflation does

little to compress tube 26 other than at the region 39' of adhesion to the back-cushion panel 25, the overall deflated extent H<sub>2</sub> is essentially unchanged from the dimension H<sub>2</sub> which applies for collapse of ring 18. On the other hand, at the distal end of the mask, the collapse of ring 18 is operative 5 upon the formed distal-end opening 43 of tube 26 to somewhat flatten the opening 43, into a generally shovel-shaped distal lip feature which merges smoothly into the adjacent upwardly dished double-wall. shape 18' shown in the longitudinal mid-section of FIG. 9.

It will be appreciated that the GLM device described thus far has an airway tube 11 that is of larger diameter than the evacuation tube 23; in this circumstance, the airway tube 11 is large enough to accommodate guided insertion of an endotracheal tube. The tubes 11, 23 enter the described laryngeal mask 10 in side-by-side relation and are preferably 15 adhesively secured to each other in this side-by-side relation, and along their full longitudinal extent, in order to provide a measure of torsional resistance against twisting, thereby aiding a medically qualified person in quickly and correctly installing a fully deflated GLM in a patient, with 20 assurance that, upon inflation of ring 18 and the backcushion panel 25, an exclusive and sealed airway connection will be established to the laryngeal inlet, via lumen 14 and from the airway tube 11; concurrently, a similarly exclusive evacuation connection is established to the upper sphinctral 25 region of the oesophagus, via the distal-end opening 43 of tube 26, through the evacuation tube 23, and to suitable waste-collection means (not shown) external to the patient.

More specifically as to insertion of the fully deflated GLM device in a patient, it will be understood that a range of GLM 30 sizes is available from which to select a sufficiently correct size for the patient. Deflation is accomplished via external means (not shown) and via check-valve means 21 to hold the deflated condition wherein the dome shape of body member collapsed ring 18. A skilled operator is quickly able to develop the desired appearance of the GLM in its deflated state; but for a uniformly correct deflated shaping, it is recommended to use a forming tool as described in U.S. Pat. No. 5,711,293.

When correctly shaped and in its deflated condition, and at the distal end of the GLM, the opening 43 will have been flattened, and this distal end merges with the peripheral lip 18' of the collapsed ring 18. Noting that the entire distal half of the mask is of relatively soft material, stiffened only by 45 indicated adhesive connection, the distal end projects distally and at its upwardly flared merge with lip 18', for low acute-angle incidence to the posterior arcuate profile of the patient's throat passage. That being the case, a medical technician need only make sure that upon inserting the mask 50 via the patient's mouth and throat, the flattened distal end rides the outer (posterior) arcuate contour of the patient's airway, in that the softly flexible nature of the distally projecting and somewhat flattened distal end will be flexibly self-adapting to local irregularities (if any) in the course of 55 passage into the pharynx; final insertional location is noted by an increase in encountered resistance, upon distal-end engagement of the GLM with the upper sphinctral region of the oesophagus. At this juncture, inflation air supplied via line 19 and retained by check-valve means 21 establishes (i) 60 the described seal of ring 18 to the laryngeal inlet, (ii) back cushion (panel 25) contact with the back wall of the pharynx, and (iii) full opening of the evacuation tube 26 for maximum accommodation of a possible gastric discharge from the oesophagus.

Beyond what has been described, FIG. 10 illustrates at phantom outline 26' that the flexible length of the re-entrant

tube 26 may be of even greater length than the approximately half-mask length shown by the solid lines of FIG. 5. In that event, arcuate stiffener ridges as described at 42 will be preferred, as long as lateral support is needed to prevent side-wall collapse of the extended tube 26', in the inflated condition of the mask, i.e., including inflation of backcushion panel 25.

FIGS. 10 to 12 illustrate another GLM embodiment wherein an airway tube 50 and an evacuation tube 51 are of 10 equal size, adhered (as suggested at 52) to each other in side-by-side relation for torsionally resistant and symmetrically positioned entry into corresponding side-by-side ports 53, 54 of the dome like moulded backing plate or body member 55 of FIGS. 11 and 12. The backing plate 55 may be similar to plate 13 of FIG. 4, except that in FIG. 11 the somewhat helically arcuate conduit path from the inserted distal end of evacuation tube 51 to the point 56 of softly compliant re-entrant tube (26) connection is provided by an integral passage formation 57 of the backing plate 55. At point 56 in FIG. 11, the formation 57 is seen to be in the central vertical plane 58 of symmetry of the bowl or domeshape of backing plate 55 and in alignment for accepted proximal-end insertional accommodation of a re-entrant tube 26 of thin-walled material to which backing plate 55 is to be assembled, with edges of the straight slot 38' supporting tube **26** in the manner already described. Also integrally formed with backing plate 55 is an inlet-connection counterbore for coupled connection of airway tube 50 to the laryngeally exposed side of the mask. Features in FIG. 10, such as the back-cushion panel 25, the inflatable ring 18, and the adhesively bonded connection 39 of panel 25 to tube 26 are all as previously described.

It will be understood that the inside-out technique described in connection with FIGS. 5 and 6 for initially 13 rises from within the dished peripheral lip 18' of the 35 moulding and then inverting the skirt of the moulded product, is but one illustration of a way to create the mask and its inflatable ring, in which case the flexible drainage conduit does not get inverted. That being the case, the reinforcement ribs 42 are initially formed portions of the 40 outer surface of the moulded product. On the other hand, another technique for forming the mask with its inflatable ring, involves moulding the mask bowl integrally with an elliptically configured product as shown in FIG. 13, wherein completion of inflatable-ring (18) integrity requires only an adhesively bonded completion of the ring peripherally around the inner substantially elliptical profile, where backing-plate (13) connection is also adhesively secured. In that case, the drainage tube 26 is integrally-moulded with the non-invertible ring (18), so that an inversion of tube 26 is necessary, to have it project re-entrantly, in the proximal direction, and the moulded product which is to become inflatable ring 18 must be cut away as at 40, to permit inverted tube 26 to "pass through" the inflatable ring, in order to develop a relationship which is suggested by FIG. 5. Of course, if tube 26 is to be inverted, the reinforcement ribs 42 are preferably integrally formed as radially inward rib reinforcements or discontinuities in the moulded bore of tube 26. Inversion of tube 26 places these rib reinforcements on the outer surface of tube 26, so that the bore of tube 26 is inherently smooth.

What is claimed is:

- 1. A laryngeal mask construction for concurrent airway service to a patient's laryngeal inlet and for removal of gastric-discharge products from the oesophagus, said con-65 struction comprising:
  - an inflatable ring in the form of a generally elliptical annulus having an outer periphery configured for con-

9

tinuously sealed adaptation to the laryngeal inlet, said ring extending longitudinally between proximal and distal ends and having an inflation port connection at its proximal end, said ring being a moulded product of relatively thin and softly pliant elastomeric material, said ring including within the inner periphery of said annulus an apertured panel or membrane establishing separation between a pharyngeal-chamber side and a laryngeal-chamber side, said ring further integrally including at its distal end a distally open tubular conduit for operative engagement and communication with the oesophageal inlet, said tubular conduit extending from its distally open end and in the proximal direction adjacent said panel and on the pharyngeal side of said panel;

- a domed backing-plate member of relatively stiff elastomeric material and having a concave side which terminates in a generally elliptical footing in a geometric plane and is sealed engagement with said panel at the inner periphery of said annulus, said backing-plate member having an airway-tube connecting formation on a proximally directional axis that is at an acute angle with said geometric plane, said backing-plate member providing stability to the inner periphery of said annulus and directional stability for said tubular conduit;
- an airway tube connected to said connecting formation; and
- a gastric-discharge tube connected to said tubular conduit.
- 2. The mask construction of claim 1, in which said airway tube and said gastric-discharge tube are bonded to each other 30 in side-by-side relation.
- 3. The mask construction of claim 1, in which said tubular conduit extends proximally to approximately 50 percent of the longitudinal extent of said inflatable ring.
- 4. The mask construction of claim 1, in which said tubular 35 conduit extends proximally to at least 50 percent of the longitudinal extent of said inflatable ring.
- 5. The mask construction of claim 1, in which said backing-plate member is formed for directionally guiding relation to said tubular conduit, to determine a straight 40 proximal direction of said tubular conduit for substantially the distal half of the longitudinal extent of said mask.
- **6**. The mask construction of claim **5**, in which said backing-plate member is further formed for tubular-conduit guidance on generally a helical arc to a location of gastric- 45 discharge tube entry to said mask alongside said airway tube.
- 7. The mask construction of claim 1, further including an inflatable back cushion comprising a panel of softly compliant elastomeric material bonded peripherally to the 50 pharyngeal-chamber side of said annulus and extending over said tubular conduit.
- 8. The mask construction of claim 7, in which said back-cushion panel is peripherally bonded to said tubular conduit.
- 9. The mask construction of claim 8, in which said back-cushion bond to said tubular conduit extends for substantially the distal half of the longitudinal extent of said inflatable ring.
- 10. The mask construction of claim 8, in which (a) a first 60 arcuate circumferential fraction of said tubular conduit is connected to said backing-plate member, (b) the bond of said back cushion to said tubular conduit is angularly spaced from and generally opposite the connection of said tubular conduit to said backing-plate member, the bond to said back 65 cushion being over a second arcuate circumferential fraction of said tubular conduit, (c) the arcuate circumferential extent

**10** 

by which said angular tubular-member connections are made to said backing-plate member and to said back cushion being reinforced with circumferentially arcuate stiffener formations.

- 11. The mask construction of claim 10, in which said stiffener formations are arcuate ribs in axially spaced array.
- 12. The mask construction of claim 11, in which said ribs project radially outward of said tubular conduit.
- 13. A laryngeal mask construction for concurrent airway service to a patient's laryngeal inlet and for removal of gastric-discharge products from the oesophagus, said construction comprising:
  - an inflatable/deflatable ring in the form of a generally elliptical annulus having an outer periphery configured for continuously sealed adaptation to the laryngeal inlet, said ring being a moulded product of relatively thin and softly pliant elastomeric material, said ring integrally including at its distal end a distally open tubular conduit through a distal opening in said ring, said distally open tubular conduit being for operative engagement and communication with the oesophageal inlet;
  - a backing-plate member of relatively stiff elastomeric material having a concave front side which is adapted to face the laryngeal inlet and which terminates in an elliptical footing in a geometric plane and in peripherally sealed engagement with the inner periphery of said inflatable/deflatable ring, said backing-plate member having an airway-tube connecting formation on a proximally directional axis that is at an acute angle with said geometric plane, said backing-plate member having a lumen for airway-tube communication with the laryngeal inlet, and said backing-plate member providing stability to the inner periphery of said annulus and proximally directed directional stability for said tubular conduit;
  - an airway tube connected to said connecting formation; and
  - a gastric-discharge tube connected to said tubular conduit. 14. A Laryngeal mask construction, including:
  - (A) a generally elliptical inflatable ring defining a distal end, the ring being adapted for sealed engagement to a laryngeal inlet of a patient;
  - (B) a backing plate defining an air inlet, the backing plate being sealed to the ring, the backing plate establishing a laryngeal-chamber side and a pharyngeal-chamber side of the construction;
  - (C) an inflatable back cushion disposed on the pharyngeal-chamber side, the back cushion when inflated contacting a pharyngeal wall of the patient and biasing the ring away from the pharyngeal wall;
  - (D) a tubular conduit defining a distal end, the distal end of the tubular conduit being disposed near the distal end of the ring for communication with an esophageal inlet of the patient, a first portion of the conduit being adhered to a portion of the back cushion, a second portion of the conduit being adhered to a portion of the backing plate; and
  - (E) one or more stiffening ribs, the ribs being disposed on a third portion of the tubular conduit, the third portion of the tubular conduit being disposed between the first and second portions of the tubular conduit.
- 15. The laryngeal mask construction according to claim 14, further including an airway tube, a distal end of the airway tube being sealed to the air inlet.
- 16. The laryngeal mask construction according to claim 14, further including a gastric discharge tube, a distal end

of the gastric discharge tube being sealed to a proximal end of the tubular conduit.

- 17. The laryngeal mask construction according to claim 14, wherein the ribs and the tubular conduit are of a monolithic construction.
- 18. The laryngeal mask construction according to claim 14, wherein the tubular conduit and the ring are of a monolithic construction.
- 19. The laryngeal mask construction according to claim 14, wherein the backing plate is domed.
- 20. The laryngeal mask construction according to claim 14, wherein the backing plate defines a groove.
- 21. The laryngeal mask construction according to claim 14, wherein the ring is of relatively thin and softly pliant elastomeric material.
- 22. The laryngeal mask construction according to claim 14, wherein the ring is a molded product.
  - 23. A laryngeal mask construction, including:
  - (A) a generally elliptical inflatable ring defining a distal end, the ring being adapted for sealed engagement to 20 a laryngeal inlet of a patient;
  - (B) a backing plate defining an air inlet, the backing plate being sealed to the ring, the backing plate establishing a laryngeal-chamber side and a pharyngeal-chamber side of the construction;
  - (C) an inflatable back cushion disposed on the pharyngeal-chamber side, the back cushion when inflated contacting a pharyngeal wall of the patient and biasing the ring away from the pharyngeal wall;
  - (D) a tubular conduit defining a distal end, the distal end of the tubular conduit being disposed near the distal end of the ring for communication with an esophageal inlet of the patient, a first portion of the conduit being adhered to a portion of the back cushion; and
  - (E) one or more stiffening ribs, the ribs being disposed on a second portion of the tubular conduit.
  - 24. A laryngeal mask construction, including:
  - (A) a generally elliptical inflatable ring defining a distal end, the ring being adapted for sealed engagement to 40 a laryngeal inlet of a patient;
  - (B) a backing plate defining an air inlet, the backing plate being sealed to the ring, the backing plate establishing a laryngeal-chamber side and a pharyngeal-chamber side of the construction;
  - (C) an inflatable back cushion disposed on the pharyngeal-chamber side, the back cushion when inflated contacting a pharyngeal wall of the patient and biasing the ring away from the pharyngeal wall;
  - (D) a tubular conduit defining a distal end, the distal end  $^{50}$ of the tubular conduit being disposed near the distal end of the ring for communication with an esophageal inlet of the patient, a first portion of the conduit being adhered to a portion of the back plate; and
  - (E) one or more stiffening ribs, the ribs being disposed on a second portion of the tubular conduit.
  - 25. A laryngeal mask construction, including:
  - (A) a generally elliptical inflatable ring defining a distal end, the ring being adapted for sealed engagement to a laryngeal inlet of a patient;
  - (B) a backing plate defining an air inlet, the backing plate being sealed to the ring, the backing plate establishing a laryngeal-chamber side and a pharyngeal-chamber side of the construction;
  - (C) an inflatable back cushion disposed on the pharyngeal-chamber side, the back cushion when

inflated contacting a pharyngeal wall of the patient and biasing the ring away from the pharyngeal wall; and

- (D) a tubular conduit defining a distal end, the distal end of the tubular conduit being disposed near the distal end of the ring for communication with an esophageal inlet of the patient, a first portion of the conduit being adhered to a portion of the back cushion, a second portion of the conduit being adhered to a portion of the backing plate, the first portion extending from a first location to a second location, the first location being near the distal end of the tubular conduit, the second location being spaced apart from the first location in a direction towards a center of the generally elliptical inflatable ring.
- 26. A laryngeal mask construction, including:
- (A) an airway tube;
- (B) a gastric discharge tube;
- (C) a generally elliptical inflatable ring defining a distal end, the ring being adapted for sealed engagement to a laryngeal inlet of a patient;
- (D) a backing plate defining an air inlet, the air inlet being sealed to the airway tube, the backing plate being sealed to the ring, the backing plate establishing a laryngeal-chamber side and a pharyngeal-chamber side of the construction;
- an inflatable back cushion disposed on the pharyngeal-chamber side, the back cushion when inflated contacting a pharyngeal wall of the patient and biasing the ring away from the pharyngeal wall;
- (F) a tubular conduit defining a proximal end and a distal end, the proximal end of the tubular conduit being sealed to the gastric-discharge tube, the distal end of the tubular conduit being disposed near the distal end of the ring for communication with an esophageal inlet of the patient, a first portion of the conduit being adhered to a portion of the back cushion, a second portion of the conduit being adhered to a portion of the backing plate; and
- (G) one or more stiffening ribs, the ribs being disposed on a third portion of the tubular conduit, the third portion of the tubular conduit being disposed between the first and second portions of the tubular conduit.
- 27. A laryngeal mask construction including:
- (A) a mask adapted for positioning inside of a patient near the patient's larynx, a central plane dividing the construction into a left portion and a right portion;
- (B) an airway tube coupled to the mask, at least a portion of the airway tube extending away from the mask and defining a central axis, the central axis portion of the airway tube being disposed on one side of the central plane; and
- (C) a gastric discharge tube coupled to the mask, at least a portion of the discharge tube extending away from the mask and defining a central axis, the central axis of the portion of the discharge tube being disposed on the other side of the central plane.
- 28. The laryngeal mask construction according to claim 27, wherein an outer diameter of the airway tube is sub-60 stantially equal to an outer diameter of the discharge tube.
  - 29. The laryngeal mask construction according to claim 27, wherein an outer diameter of the airway tube is not equal to an outer diameter of the discharge tube.
    - 30. A device, including:
    - (A) an airway tube for supplying air to a patient;
    - (B) an evacuation tube for communication with an esophageal inlet of the patient;

- (C) a mask adapted for sealed engagement with a laryngeal inlet of the patient, the mask including a back cushion for contacting a pharyngeal wall of the patient and biasing at least part of the mask away from the pharyngeal wall, a first portion of the back cushion being sealed to a first portion of the evacuation tube, the first portion of the back cushion extending from a first location to a second location, the first location being near the distal end of the evacuation tube, the second location being spaced apart from the first location in a direction towards a center of the mask.
- 31. A device according to claim 30, a second portion of the evacuation tube being sealed to the mask, the second portion being disposed opposite to the first portion.
- 32. A device according to claim 30, the mask including a generally elliptical inflatable ring.
- 33. A device according to claim 32, the mask further including a body, a second portion of the evacuation tube being sealed to the body.
- 34. A device according to claim 33, the body defining a slot, the evacuation tube extending along the slot.
  - 35. A device including:
  - (A) an inflatable mask adapted for sealed engagement 25 with a laryngeal inlet of the patient;
  - (B) a single airway tube for supplying air to a patient, the airway tube being coupled to the mask, a portion of the airway tube extending away from the mask;
  - (C) a single evacuation tube for communication with an esophageal inlet of the patient, the evacuation tube being coupled to the mask, a portion of the evacuation tube extending away from the mask, the portions of the airway and evacuation tubes being coupled to one 35 another in side-by-side relation such that a center of one of the airway and evacuation tubes is dosposed on a left side of the device and a center of the other one of the airway and evacuation tubes is disposed on a right side of the device.
- 36. A device according to claim 35, the evacuation tube including a conduit extending through a portion of the mask.
- 37. A device according to claim 36, further including an inflation line coupled to the mask for inflating and deflating the mask.
  - 38. A device, including:
  - (A) an airway tube for supplying air to a patient;
  - (B) an evacuation tube extending from a proximal end to a distal end, the distal end being adapted for commu- 50 nication with an esophageal inlet of the patient;
  - (C) a mask adapted for sealed engagement with a laryngeal inlet of the patient, the mask including a back cushion for contacting a pharyngeal wall of the patient and biasing at least part of the mask away from the pharyngeal wall, a first portion of the evacuation tube being sealed to a portion of the back cushion, the first portion of the evacuation tube extending from near the distal end of the evacuation tube.

- 39. A device including:
- (A) an inflatable mask, the mask being insertable, at least when deflated, through a mouth of the patient to an inserted location within a patient, the inserted location being near a laryngeal inlet of the patient;
- (B) an airway tube coupled to the mask, the airway tube extending from a proximal end located outside of the patient's mouth through an interdental gap to the mask when the mask is at the inserted location, the interdental gap being a space between the patient's lower teeth and the patient's upper teeth;
- (C) an evacuation tube for communication with an esophageal inlet of the patient, the evacuation tube being coupled to the mask, the evacuation tube extending from a proximal end located outside of the patient's mouth through the interdental gap to the mask when the mask is at the inserted location, one of the airway and evacuation tubes being greater than or equal to the other of the airway and evacuation tubes where the tubes pass through the interdental gap, the airway and evacuation tubes being coupled together in side-by-side relation such that the interdental gap need not be greater than the one tube when the mask is at the inserted location.
- 40. A device according to claim 39, a diameter of the airway tube being equal to a diameter of the evacuation tube.
- 41. A device according to claim 39, the mask including a generally elliptical inflatable ring.
- 42. A device according to claim 41, the mask further including an inflatable back cushion, the back cushion contacting a pharyngeal wall of the patient and biasing at least part of the mask away from the pharyngeal wall when inflated and when the mask is at the inserted location.
- 43. A device according to claim 41, the mask further including a body, a portion of the evacuation tube being sealed to the body.
- 44. A device according to claim 43, the body defining a slot, the evacuation tube extending along the slot.
  - 45. A device including an airway tube, an evacuation tube, and an inflatable mask, the mask being insertable, at least when deflated, through a mouth of the patient to an inserted location within a patient, the inserted location being near a laryngeal inlet of the patient, the airway tube extending from a proximal end located outside of the patient's mouth through an interdental gap to the mask when the mask is at the inserted location, the interdental gap being a space between the patient's lower teeth and the patient's upper teeth, the evacuation tube being coupled to the mask, the evacuation tube extending from a proximal end located outside of the patient's mouth through the interdental gap to the mask when the mask is at the inserted location, one of the airway and evacuation tubes being greater than or equal to the other of the airway and evacuation tubes where the tubes pass through the interdental gap, the airway and evacuation tubes being coupled together in side-by-side relation such that the interdental gap need not be greater than the one tube when the mask is at the inserted location.

\* \* \* \* \*