

US00RE40232E

(19) **United States**  
(12) **Reissued Patent**  
**Zittel et al.**

(10) **Patent Number:** **US RE40,232 E**  
(45) **Date of Reissued Patent:** **\*Apr. 8, 2008**

(54) **METHOD FOR PROCESSING FOOD PRODUCT**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **David R. Zittel**, Columbus, WI (US);  
**Steven W. Hughes**, Beaver Dam, WI (US); **Daniel D. Maupin**, Corvallis, OR (US)

DE	1274428	8/1968
DE	2161446	3/1973
GB	769456	3/1957
GB	814871	6/1959
GB	814872	6/1959
GB	909015	10/1962
WO	01/26483 A1	4/2001
WO	2004/110229 A2	12/2004

(73) Assignee: **Lyc0 Manufacturing, Inc.**, Columbus, WI (US)

OTHER PUBLICATIONS

(\*) Notice: This patent is subject to a terminal disclaimer.

Blueprint of Hughes blancher dated Jun. 16, 1997 of 1997 its blancher installation at Campbell Soup's factory in Listowel, Canada.

(21) Appl. No.: **10/791,694**

(22) Filed: **Mar. 2, 2004**

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **6,214,400**  
Issued: **Apr. 10, 2001**  
Appl. No.: **09/419,716**  
Filed: **Oct. 14, 1999**

(51) **Int. Cl.**  
**A23L 1/00** (2006.01)

(52) **U.S. Cl.** ..... **426/509**; 426/510; 426/511;  
426/520

(58) **Field of Classification Search** ..... 426/509,  
426/510, 511, 520, 523; 99/438, 404, 409,  
99/479, 516, 536

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

697,272 A	4/1902	Plummer
1,168,799 A	1/1916	Grier
1,231,002 A	6/1917	Dawson
1,290,396 A	1/1919	Steere
1,581,933 A	4/1926	Larsen
1,609,705 A	12/1926	Forrest
1,806,957 A	5/1931	Stocking

(Continued)


*Primary Examiner*—Drew Becker

(74) *Attorney, Agent, or Firm*—Michael Best & Friedrich LLP

(57) **ABSTRACT**

A method and rotary blancher for processing food product using a heat transfer medium and directed flows of a fluid that can comprise a liquid, a gas, a vapor or a combination thereof. The directed flows can be discharged from orifices or banks of orifices that are distributed around the food products in the blancher. The flows are discharged at a high flow rate, a high pressure, or a combination of both. Where a liquid is discharged, it preferably is discharged at a flow rate of at least 20 gpm and at least 30 psi. Where a gas is discharged, it is discharged at a flow rate of at least 60 CFM at a pressure of at least 2 psi or at a flow rate of at least 10 CFM at a pressure of at least 80 psi. If desired, discharged fluid can be recirculated to save energy. To help increase agitation and help break up clumps of food products in the blancher, direct-contact mechanical agitation devices, such as baffles, can be used. Such a blancher and method can be used to process food product by blanching, cooking and pasteurizing, is suited for processing relatively heavy food products having a density of at least 55 lbs/ft<sup>3</sup> using discharged liquid and gas, and is suited for processing food products having a lesser density using only discharged gas.


**51 Claims, 9 Drawing Sheets**



U.S. PATENT DOCUMENTS							
2,299,080	A	10/1942	De Back .....	426/509	5,329,842	A	7/1994 Zittel
2,314,871	A	3/1943	De Back		5,341,729	A	8/1994 Zittel
2,418,519	A	4/1947	McBeth		5,427,015	A	6/1995 Zittel
2,585,293	A	2/1952	Ashton		5,429,041	A	7/1995 Zittel
2,805,639	A	9/1957	Martin		5,456,091	A *	10/1995 Zittel ..... 62/375
3,086,444	A	4/1963	De Back		5,517,906	A	5/1996 Zittel et al.
3,420,157	A	1/1969	Frish		5,587,073	A	12/1996 Zittel
3,722,401	A	3/1973	Davidson et al.		5,589,214	A	12/1996 Palm
3,760,714	A	9/1973	Lortz		5,592,869	A	1/1997 Zittel
3,982,481	A	9/1976	Console et al.		5,632,195	A	5/1997 Zittel
4,238,997	A	12/1980	Hengstenberg		5,669,288	A	9/1997 Zittel et al.
4,525,370	A	6/1985	Parkes		5,752,431	A	5/1998 Zittel
4,688,476	A	8/1987	Zittel		5,780,088	A	7/1998 Zittel et al.
4,875,344	A	10/1989	Zittel		5,802,961	A	9/1998 Hay et al.
4,942,810	A	7/1990	Zittel et al.		5,809,787	A	9/1998 Zittel
4,949,629	A	8/1990	Leary et al.		6,095,035	A	8/2000 Zittel et al.
5,133,249	A *	7/1992	Zittel ..... 99/348		6,105,485	A *	8/2000 Zittel ..... 99/348
5,146,841	A	9/1992	Zittel		6,187,360	B1 *	2/2001 Zittel ..... 426/510
5,173,122	A	12/1992	Tilby et al.		6,205,913	B1	3/2001 Zittel et al.
5,284,085	A	2/1994	Palm		6,214,400	B1 *	4/2001 Zittel et al. .... 426/509
5,289,759	A	3/1994	Hufford		6,263,785	B1 *	7/2001 Zittel ..... 99/348
5,327,817	A	7/1994	Zittel				

\* cited by examiner





**FIG. 1**




FIG. 2




FIG. 3




FIG. 4






FIG. 5




FIG. 6




FIG. 7






FIG. 8





FIG. 9





## METHOD FOR PROCESSING FOOD PRODUCT

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.**

### FIELD OF THE INVENTION

The present invention relates to rotary blanchers and more particularly to a method and rotary blancher for processing food products that comprises introducing a fluid into the heat transfer medium in the blancher to more efficiently and more uniformly heat the food products in the blancher and which can be used to blanch, cook or pasteurize the food products.

### BACKGROUND OF THE INVENTION

A wide variety of food products, such as pasta, beans, corn, peas, and other vegetables and fruit, are processed every day around the world by blanching or heating. For many years, the basic rotary blancher consisted of an elongate cylindrical perforate drum received in a tank filled with heated water. Food products are continuously introduced through an inlet in one end of the drum and heated by the water in the tank. During operation, flights of a helical auger in the drum rotate and urge the food products from the drum inlet toward a drum outlet.

However, food products tend to clump together as the drum rotates resulting in poor heat transfer and uneven heating, especially for those food products in the middle of the clump. To combat this problem, straight and curved baffles have been employed between adjacent flights of the auger to lift and tumble food product during rotation of the drum to help improve heat transfer and more evenly heat food product. Examples of such baffles are disclosed in Zittel, U.S. Pat. Nos. 5,632,195 and 5,456,091. As a result of this improvement, blanching capacity was not only roughly doubled, but the food products were more uniformly blanched. For example, where nine inches of one specific type of food product could previously be blanched, a blancher equipped with these baffles could more uniformly blanch about eighteen inches of the same food product.

In addition to this type of mechanical agitation, other methods have also been employed to improve heat transfer. For example, as is disclosed in Zittel, U.S. Pat. Nos. 5,752,431 and 5,632,195, air and steam have been introduced into the water in the tank to help increase heat transfer efficiency. Air has also been used to improve cooling efficiency in food cooling applications. For example, U.S. Pat. No. 4,875,344 discloses injecting relatively low volumes of low-pressure air, namely warm air into cold water, to improve cooling of food products in a rotary drum chiller. In some food product cooling applications, manifolds connected to nozzles that introduce the air into the chiller have been located between the tank and drum at the five o'clock and seven o'clock positions relative to the drum's center. However, in each of these applications, the air was injected at a pressure of no greater than 150 pounds per square inch (psi) at a flow rate no more than 25 cubic feet per minute (CFM).

Directed flows of water have also been used to increase heat transfer. For example, U.S. Pat. No. 5,456,091 discloses improved cooling by directing flows of water from nozzles connected to a manifold toward the drum to agitate food products in the drum. However, a relatively low volume of water of no more than 8 gallons per minute per foot of blancher length (gpm/ft) at a pressure no greater than 40 psi

was used for these cooling applications. While directed flows of water have also been tried in blanchers to improve heat transfer, it has been done using pressures no greater than 8 psi and flow rates no greater than 10 gpm/ft.

It is believed that greater pressures and flow rates of directed water flows have not been tried before because the lower pressures and flow rates previously tried did not increase efficiency so dramatically as to predict a correspondingly greater efficiency increase. Moreover, the cost of bigger and more powerful pumps and other equipment needed to deliver greater flow rates, particularly at higher pressures, was thought to be so cost prohibitive that any possible performance advantage was believed not to be worth it.

It has always been very difficult for rotary blanchers to process food products that are relatively heavy, typically having a density greater than 55 pounds per cubic foot (lbs/ft<sup>3</sup>). Examples of food products that are relatively heavy include packaged meats, such as hot dogs and turkey breasts, as well as other types of food products that are not packaged. While baffles have been used to help turn over and agitate food products during operation, heavier food products tend to clump together on the bottom and along the side of the rotating drum where the drum leaves the water. This is believed to be caused, at least in part, by the increased weight of the food products causing them to sink and by the increased friction between the food products and the rotating drum.

Testing has shown that, most, if not virtually all, heavy food products congregate along one side of the drum near the bottom of the drum in a region that occupies less than about 20% of the total volume of the drum dramatically reducing the amount of food product surface area actually exposed directly to the hot water. By congregating in a clump, the food products inside the clump are not heated directly by the water but by other outer food products, which means it takes more time to heat all of the food products to the desired temperature than is acceptable. Other experiments have shown that these lower turbulence (i.e. lower volume and pressure) flows of air and water used in the past, even if the blancher is equipped with agitating baffles, will not break up and agitate heavy food products enough to achieve the desired level of heat transfer needed to make blanching of heavy food products commercially viable.

Pasta is a relatively heavy food product that has a density less than 55 lbs/ft<sup>3</sup>. Pasta, however, is relatively fragile and must be handled much more carefully during blanching than most other types of food products, which has limited attempts in the past to increase heat transfer. Past attempts to increase heat transfer include the use of baffles and the introduce of air having a pressure no greater than 2 psi at a volume no greater than 40 CFM per foot of blancher length. As a result, throughput for a 72-inch diameter blancher has been heretofore limited to about 3500 pounds of pasta per hour, making production undesirably slow.

While the food processing industry has always been driven to find ways of processing more food product faster, it has been more recently been tempered by the need to do so in a manner that ensures the food is not contaminated. Thus, there has been a move to not only heat the food products until they are cooked, but to pasteurize the food products which takes longer, requires more heat, and thus is more costly.

Consequently, there has arisen a great need for a method and rotary blancher that processes food products, including heavy and fragile food products, more efficiently and more



quickly and which is capable or more cost-effectively cooking, blanching and pasteurizing food products.

#### SUMMARY OF THE INVENTION

A rotary blancher and method of processing food products by heating are provided. The blancher and method uses a heat transfer medium and heat transfer enhancers that include one or more of a high volume fluid, a high pressure fluid, or a high pressure and high volume fluid. In its preferred embodiment, the blancher includes a housing that has an inlet and an outlet and a food product-receiving chamber. Food products enter through the inlet, are received and heat in the food product-receiving chamber, and exit through the outlet. A rotary food product transport mechanism urges food products received in the chamber toward the outlet. While inside the chamber, a heat transfer medium heats the food products preferably to blanch, cook or pasteurize them. The heat transfer medium can be a liquid, such as water, or another fluid that can comprise a vapor, if desired.

In a preferred embodiment, the housing is comprised of a tank and preferably includes a cover that can be attached to the tank in a clamshell arrangement. The rotary food product transport mechanism preferably comprises an auger or screw disposed in the tank and which is made of helical spaced apart flights. If desired, one or more of the flights can carry one or more mechanical agitation devices, such as generally radially extending baffles. Preferably, the auger is disposed in a perforate drum that is received in the blancher housing. An exemplary blancher of the aforementioned construction has a length that typically is four feet or longer.

The blancher includes a plurality of orifices that discharge fluid into the heat transfer medium. In one embodiment, the discharged fluid forms directed flows that help break up food products and help prevent food products from clumping together. One or more flows of fluid can be directed at one or more locations within the blancher where food products tend to gather to break up clumps as well as to prevent clumping.

In another embodiment, there is a plurality of spaced apart manifolds that each has at least a plurality of orifices through which fluid is discharged. One or more manifolds can be disposed below the lid in communication with the tank in a quadrant of the tank adjacent the direction of rotation of the auger. Preferably, the manifolds are spaced apart. One or more manifolds, or groups of orifices, can be disposed around the periphery of the auger at or adjacent one or more of the following positions: 3 o'clock, 4 o'clock, 5 o'clock, 6 o'clock, 7 o'clock, 8 o'clock, and 9 o'clock positions. In another preferred arrangement, one or more manifolds, or groups of orifices, are located between at least one or more of the following positions: between 3 o'clock and 4 o'clock, between 4 o'clock and 5 o'clock, between 5 o'clock and 6 o'clock, between 5 o'clock and 7 o'clock, between 6 o'clock and 7 o'clock, between 7 o'clock and 8 o'clock and/or between 8 o'clock and 9 o'clock.

In a still further preferred embodiment, one or more manifolds or groups of orifices can be disposed between 3 o'clock and 5 o'clock or lie within a band located between 45° and 65° from a perpendicular drum centerline in a direction opposite the direction of drum rotation (measured from the center of the drum and centerline). One or more manifolds or groups of orifices can be disposed between 4 o'clock and 6 o'clock or lie within a band located between 25° and 40° from the centerline in a direction opposite the direction of drum rotation. One or more manifolds or groups

of orifices can be disposed between 5 o'clock and 7 o'clock or lie within  $\pm 25^\circ$  of the centerline. One or more manifolds or groups of orifices can be disposed between 6 o'clock and 8 o'clock or lie within a band located between 25° and 40° from the centerline in a direction the same as the direction of drum rotation. One or more manifolds or groups of orifices can be disposed between 7 o'clock and 9 o'clock or lie within a band located between 45° and 65° from the centerline in a direction the same as the direction of drum rotation.

The fluid discharged can comprise liquid, such as water, or gas, such as air. If desired, vapor, such as steam or water vapor, can be discharged. Liquid can be discharged from one or more groups each comprising one or more orifices, and/or gas can be discharged from one or more different groups each comprising one or more orifices. If desired, vapor can be discharged from one or more groups of one or more orifices.

Where liquid is discharged, it preferably is either discharged at a high flow rate, a high pressure, or both. For example, where liquid is discharged, it preferably is discharged at a flow rate of at least 20 gallons per minute (gpm) at a pressure of at least 30 psi. Where liquid is discharged at a higher flow rate, the liquid is discharged at a flow rate of at least 60 gpm. Preferably, at least 60 gpm per foot (gpm/ft) of blancher length is discharged. In another preferred method, at least 80 gpm per minute is discharged. Where liquid is discharged at a higher pressure, it preferably is discharged at a pressure of at least 80 psi. Where the pressure is at least 80 psi, at least 20 gpm/ft preferably is discharged.

Where gas is discharged, it preferably is either discharged at a high flow rate, a high pressure, or both. For example, where gas is discharged, it preferably is discharged at a flow rate of at least 60 CFM at a pressure of at least 2 psi. In another preferred method, the gas is discharged at a higher flow rate of at least 100 CFM. Preferably, at least 100 CFM per foot (CFM/ft) of blancher length is discharged. In still another preferred method, the gas is discharged at an even higher flow rate of at least 200 CFM. Preferably, at least 200 CFM/ft is discharged. Where gas is discharged at a high pressure, it preferably is discharged at a pressure of at least 80 psi. Where the pressure is at least 80 psi, at least 10 CFM/ft is discharged.

If desired, vapor, such as steam, can be discharged from one or more of the orifices at the above-mentioned gas flow rates and pressures. Where steam is discharged, it preferably is discharged from each orifice at a flow rate of at least 20 pounds per hour (lbs/hr) at a discharge flow rate of at least 15 psi.

In one preferred method, high pressure, high volume or high pressure and high volume liquid and gas is discharged into a liquid heat transfer medium to help in the processing of relatively heavy food products having a density of at least 55 lb/ft<sup>3</sup>. Such food products include hot dogs, pouched hot dogs, meats, pouched meats, and other heavier food products. If desired, one or more flights carry one or more direct-contact mechanical agitation devices that can be radially extending baffles. Discharging such liquid and gas, a blancher can process at least eight inches of depth of such relatively heavy food product, and preferably at least twelve inches of depth of the food product, in the food product receiving chamber. Discharging such liquid and gas, a blancher can process at least 8000 lbs/hr of food product, and preferably at least 10000 lbs/hr of food product. Preferably, the food product-receiving chamber is disposed in the drum that surrounds the auger.



## 5

In another preferred method, high pressure, high volume, or high pressure, high volume gas is discharged into a liquid heat transfer medium to help in the processing of food products having a density of no more than 55 lb/ft<sup>3</sup> and to help process more fragile food products. An example of such a food product that is relatively fragile is pasta. Preferably, none of the flights are equipped with direct-contact mechanical agitation devices. Discharging such gas, a blancher can process at least eight inches of depth of food product, and preferably at least twelve inches of depth of food product, in the food product-receiving chamber. Discharging such gas, a / can process at least 4500 lbs/hr of food product, and preferably at least 7000 lbs/hr of food product.

In another preferred embodiment and method, heat transfer medium and atmosphere within a blancher can be withdrawn and returned to the blancher in the form of gas, vapor and/or liquid discharged through one or more the orifices. Where the fluid is recirculated, a pump such as a liquid-ring vacuum pump or compressor is used to withdraw fluid from the blancher through a conduit and deliver the withdrawn fluid to one or more orifices or one or more manifolds.

It is an object of the present invention to utilize higher pressure directed flows of fluid inside the blancher to increase turbulence and heat transfer to the food products inside the blancher.

It is another object of the present invention to utilize higher flow rate directed flows of fluid inside the blancher to increase turbulence and heat transfer to the food products inside the blancher.

It is still another object of the present invention to utilize higher pressure and higher flow rate directed flows of fluid inside the blancher to increase turbulence and heat transfer to the food products inside the blancher.

It is a still further advantage of the present invention to utilize at least some of the heat transfer medium and/or atmosphere from within the blancher as a source of the directed fluid flows.

It is an advantage of the present invention to utilize higher flow rate and/or higher pressure directed flows of gas inside the blancher to increase the buoyancy of food products inside the blancher to prevent them from gathering near the bottom.

It is another advantage of the present invention to increase the amount of food products that can be substantially simultaneously processed at one time.

It is an additional advantage of the present invention to prevent food products in the blancher from clumping together with other food products.

It is a still another advantage of the present invention to significantly increase the rate of food product processing.

It is a further advantage of the present invention to reduce and preferably substantially completely prevent damage to fragile food products, such as pasta.

It is another advantage of the present invention to increase the amount of fragile food products that can be substantially simultaneously processed at one time.

It is a still another advantage of the present invention to significantly increase the rate of processing of relatively fragile food products.

It is another advantage of the present invention to increase the amount of relatively heavy food products that can be substantially simultaneously processed at one time.

It is a still another advantage of the present invention to significantly increase the rate of processing of relatively heavy food products.

## 6

It is a further advantage of the present invention to reduce and preferably substantially completely prevent damage to relatively heavy food products, such as hot dogs and turkey breasts.

Other advantages, features and objects of the present method is that it saves processing time, increases production, is economical, is versatile in that it can be employed in the blanching, cooking or pasteurizing of food products, is capable of recirculating the discharged fluids to save energy, and is simple, reliable, easy to control, and can be used to help process many different types of food products.

Additional objects, features and objects of the invention include a blancher that is simple, reliable, rugged, durable, and which is of economical construction and which is easy to make and assemble.

Other objects, features, and advantages of the present invention will become apparent to those skilled in the art from the detailed description and the accompanying drawings. It should be understood, however, that the detailed description and accompanying drawings, while indicating preferred embodiments of the present invention, are given by way of illustration and not of limitation. Many changes and modifications may be made within the scope of the present invention without departing from the spirit thereof, and the invention includes all such modifications.

## BRIEF DESCRIPTION OF THE DRAWINGS

At least one preferred exemplary embodiment of the invention is illustrated in accompanying drawings in which the reference numerals represent like parts throughout and in which:

FIG. 1 is an exploded perspective view of a rotary blancher of this invention;

FIG. 2 is a side view of the rotary blancher with a section broken away;

FIG. 3 is a sectional view of the blancher taken along line 3—3 of FIG. 2 with its cover removed and depicting an orifice from which fluid is being injected toward food products in a drum of the blancher;

FIG. 4 is a sectional view of the orifice and blancher taken along line 4—4 of FIG. 3;

FIG. 5 is a sectional view of another preferred blancher embodiment;

FIG. 6 is a sectional view of still another preferred blancher embodiment;

FIG. 7 is a sectional view of a further preferred blancher embodiment;

FIG. 8 is a sectional view of a still further preferred blancher embodiment;

FIG. 9 is a sectional view of a blancher with a schematic depiction of recirculation systems for recirculating fluid from the blancher; and

FIG. 10 is a sectional view of a blancher with a schematic depiction of recirculation systems for heating and recirculating fluid from the blancher.

## DETAILED DESCRIPTION

FIGS. 1—4 illustrate an exemplary rotary blancher 20 of this invention that utilizes directed flows of a fluid during operation to enhance heat transfer. As is shown more clearly in FIG. 6, the blancher 20 is comprised of a housing that includes a cover 22 that mates with a tank 24 that holds a heated fluid, that preferably is a liquid 26, which heats food



products 32 during operation. The tank 24 is supported by a frame 28 that has legs 30, which rest on the floor or ground.

The tank 24, preferably made of stainless steel or another material suitable for food processing applications, has an inlet endwall 34 and an outlet endwall 36. The endwalls 34 and 36 are joined to a tank underside 38 that defines the bottom and lengthwise sides of the tank 24. The tank underside 38 may be a single, continuous, curved plate running lengthwise between endwalls 34 and 36, or may be made of several long flat plates positioned side by side and angularly joined together to form a generally curved shape. Each endwall 34 and 36 has a through opening, 40 and 42 respectively, that preferably is arcuate or semicircular.

A food product transport mechanism 44 is received within the blancher 20 and preferably is disposed between the tank underside 38 and cover 22. The food product transport mechanism 44 is constructed and arranged to transport food products 32 received in blancher 20 toward the blancher outlet 62. In its preferred embodiment, the food product transport mechanism 44 comprises an auger or helical screw 48 received within the blancher 20 and which rotates during operation to urge food products 32 received in the blancher 20 toward the outlet 62.

The auger 48 has a plurality of pairs of axially spaced apart and interconnected flights 50 and extends substantially the length of the interior of the tank 24. Preferably, the auger 48 has at least four flights and can have as many as twenty flights or more depending upon the application and length of the blancher 20. While the auger flights 50 can be carried by an elongate generally cylindrical central support core 51 (FIG. 3), the auger 48 can be of a coreless construction, such as is shown in FIGS. 1 and 2.

Preferably, the auger 48 is housed in a drum 52. The drum 52 has a sidewall 54, an inlet endwall 56, an outlet endwall 58, and inlet and outlet 60 and 62, through which food products 32 are introduced into the blancher 20 and discharged from the / 20. Annular drum journals 64 extend from each end of the drum 52 beyond each drum endwall 54 and 56. Each journal 64 provides a support surface upon which the weight of the drum 52 can rest particularly while it rotates during operation. Preferably, each drum journal 64 is rotatively supported on trunnions 66 which are mounted to the frame 28 and which are positioned so that the weight of the drum 52 does not rest upon the tank endwalls 34 and 36.

The drum 52 is constructed and arranged to receive food products 32 and a heat transfer medium 33 (FIG. 3) such that the heat transfer medium 33 can surround and contact the food products 32 within the drum 52 during operation. In its preferred embodiment, the drum 52 is of perforate construction. For example, the drum sidewall 54 can be constructed with a plurality of perforations 68 and is preferably made of perforated panels, mesh, or a screen-like material in order to contain the food products 32 in the drum 52 while at the same time permitting the heat transfer medium 33 to enter the interior of the drum, preferably through the perforations 68, to contact the food products 32.

Each of the perforations 68 in the portion of the drum sidewall 54 shown in FIG. 2 is exaggerated for clarity. Preferably, the perforations 68 are constructed and arranged to permit heat transfer medium 33 to flow through the sidewall 52 into or out of the drum 50 while retaining the food product 42 in the drum 50. Depending on the type of food product 32 being processed, the size and shape of the perforations 68 can vary. Preferably, the size of each perforation 68 can range from as small as  $\frac{1}{6}$  of an inch, for relatively small food product, such as rice, to as large as  $\frac{1}{2}$

inch or more for larger food products, such as hot dogs or the like. The sizes of the perforations preferably are selected using routine testing and experimentation to help maximize the flow of the directed flows of fluid through the drum sidewall 54.

Particularly where the auger 48 is of coreless construction, the drum 52 can be constructed with circumferentially spaced apart elongate struts 70 that preferably extend from one end wall 56 to the other end wall 58 to help strengthen and rigidify the drum 52 and auger 48. These struts 68 can also serve as mounts to which the panels that make up the perforate drum sidewall 54 can be fastened. Preferably, the panels are removably fastened to the struts 68.

In its preferred embodiment, the cover 22 is of preferably elongate and vaulted construction so as to fit over and completely cover the tank 24 so as to provide an enclosure for receiving the heat transfer medium 33 and a food product receiving chamber for receiving the food products 32. The cover 22 has a pair of endwalls 80 and 82 and each endwall has a semi-circular opening 76. When the cover 22 is closed, one of the openings 76 is positioned above one of the openings 40 in tank endwall 34 and the other one of the openings 76 is positioned above the other one of the openings 42 in tank endwall 36. When closed, one of the drum journals 64 extends out from openings 76 and 42 and the other one of the journals 64 extends out from openings 76 and 40.

The cover 22 can be attached to the tank 24 in a manner such that it can be moved relative to the tank 24 to permit access to the interior of the blancher 20. The cover 22 can be attached to the tank 24 by one or more hinges such that it may be opened along one side of the blancher 20. If desired, the cover 22 can be attached to the tank 24 such that it can be lifted free of the tank 24 using cylinders or the like, such as in the manner disclosed in U.S. Pat. No. 4,788,476 to Zittel, the disclosure of which is hereby incorporated by reference.

The blancher 20 preferably also has an inlet 84 permitting introduction of the heat transfer medium 33 into the tank 28 and an outlet 86 through which the heat transfer medium 33 can be drained. If desired, there can be a constant flow of heat transfer medium 84 and outlet 86. The outlet 84 and 86 can also assist in cleaning the interior of the tank 24.

During operation, the auger 48 is rotated to urge the food products 32 through the blancher 20. Preferably, both the auger 48 and the drum 52 rotate. If desired, the auger 48 and drum 52 can be constructed such that the auger 48 rotates relative to or independently of the drum 52. While use of a drum 52 is preferred, depending upon the construction of the tank 24, as well as other components of the blancher 20, and the food processing application, a drum 52 may not be needed.

In one preferred embodiment, the drum 52 and auger 48 are driven by a motor (not shown) which transfers power via a geartrain, belt, or chain (also not shown) to a drive sprocket 72 carried by either of the drum journals 64. The drum 52 preferably rotates at a speed selected to achieve the desired cooking time for the type of food product 32, its weight, the amount being processed, and other factors, thereby controlling its residency time within the blancher 20 and thus its time of exposure to the heat transfer medium 33.

When one or more of the food products 32 in the blancher 20 reaches the outlet 62, each food product 32 is lifted and transferred to the outlet 62 where it is expelled out of the blancher 20. A single generally radially extending lifting



flight 74, or more than one, can be used to transfer the food products 32 to the outlet 62. Of course, other suitable arrangements can be used to remove food product 32 from the blancher 20.

Referring to FIG. 3, to help agitate food products 32 and help break up food products 32 that have clumped together, a baffle or ramp 88, carried by at least one of the auger flights 50 and/or the drum sidewall 54, can physically contact individual food products 32. In a preferred embodiment shown in FIG. 4, the baffle 88 comprises a plate 90 that extends between adjacent auger flights 50. Preferably, the baffle 88 forms an acute vee with the drum sidewall 54 that has its apex pointed in the direction of rotation of the drum 52. One end of the baffle 88 is located adjacent the drum sidewall 54 and preferably is disposed against the sidewall 54 or close enough to the sidewall 54 such that food products 32 will not get caught between the drum 52 and baffle 88. If desired, the free end of each baffle 88 can be equipped with a lip 92, preferably for preventing damage to food products 32 as they tumble off the plate 90.

In one preferred embodiment, each baffle 90 forms an acute angle of between about 5° and about 35° with the drum sidewall 54 for helping to efficiently physically contact, lift and agitate food products 32 that come into contact with the baffles. In another preferred embodiment, particularly where the food products 32 are heavy, each baffle 90 forms an acute angle of between about 30° and about 45° with the sidewall 54.

Preferably, there are between one and four circumferentially spaced apart baffles between at least one pair of adjacent flights 50. Preferably, there are between one and four baffles between each pair of adjacent auger flights 50. In the preferred embodiment shown, each baffle is of substantially flat construction. In another preferred embodiment, the baffle is of non-straight construction and preferably is curved. If desired, the baffle can further comprise bars or posts that extend outwardly from the plate.

The baffles 88 orbit the center of the drum 52 as the drum rotates. After entering the heat transfer medium 33, each baffle 88 wedges between one or more food products 32 near the drum sidewall 54 or near the bottom of the drum 52 and urges the food products 32 away from the sidewall 54. As the drum 52 further rotates, the food products 32 slide or tumble along the baffle 88 until each food product 32 falls or tumbles off of the baffle 88. In doing so, food products 32 that have gathered along the bottom of the drum 52 are lifted and mixed with the heat transfer medium. As a result of this mechanical agitation by physical contact, clumps of food products 32 are broken up and heat transfer is increased.

The blancher 20 is equipped with a plurality of pairs of orifices 94 (at least three orifices 94) from which directed flows, jets, or streams of a fluid are discharged into the tank 24 to displace food products 32 in the drum 52 to help increase heat transfer. The orifices 94 are connected to a common manifold 96 that is in turn connected to a source of fluid (not shown). In one preferred embodiment, the fluid source comprises a source of liquid, preferably a source of water. In another preferred embodiment, the fluid source comprises a source of gas, preferably a source of air.

As is depicted in FIG. 4, each orifice 94 can include a nozzle 98, if desired. In the exemplary orifice arrangement shown in FIG. 4, the orifice 94 includes a first conduit 100 connected at an angle to a second conduit 102 attached to a necked down or tapered section 104 from which the nozzle 98 extends. The orifice 94 extends through or communicates with an opening in the tank bottom 38 to enable a flow 106

of the fluid to be directed toward the drum 52 with enough force such that at least some of the fluid flow 106 passes through the perforations 68 in the drum sidewall 54 and impinges against food products 32 in the drum 52 causing at least some of the food products 32 to be displaced.

Referring to FIG. 1, the manifold 96 has a plurality of pairs of orifices 94 that each direct fluid flow 106 into the drum 52. In a preferred embodiment, there is at least one orifice 94 for each auger flight 50. In another preferred embodiment, there are at least two orifices for each auger flight 50. For example, for at least a portion of the axial length of the blancher 20 shown in FIG. 2, there are two orifices 94 for each auger flight 50. Each orifice 94 is disposed between a pair of adjacent auger flights 50. If desired, two or more orifices 94 can be disposed between a pair of adjacent auger flights 50 with one or more of the orifices 94 being directed toward one or both of the flights 50. While an orifice 94 can be located anywhere between adjacent auger flights 50, at least one orifice 94 can be located adjacent the auger flight 50 of the adjacent pair that is located closest to the blancher inlet 60 for agitating food products 32 being contacted and urged by that flight 50.

In one preferred embodiment, orifices 94 are located between the 6 o'clock and 9 o'clock position when the drum 52 is rotating in the clockwise direction, such as is the direction depicted in FIG. 3. Thus, in this preferred embodiment, orifices 94 direct flows 106 into the heat transfer medium 33 in the quadrant of the drum 52 adjacent or along where the drum sidewall 54 leaves the heat transfer medium 33 during rotation. Where rotation is opposite to that shown in FIG. 3 (i.e., counterclockwise), the orifices 94 are located between 3 o'clock and 6 o'clock.

In one preferred embodiment, orifices 94 are positioned to aim flows 106 toward the drum interior and preferably generally toward the center of the drum 52. In another preferred embodiment, at least a plurality of orifices 94 are aimed at a target point 108 where food products 32 tend to conglomerate while the drum 52 is rotating. Such a point 108 can be determined by routine testing and experimentation and its location will depend upon, among other factors, the type, size, shape, weight, and amount of the food product 32 being processed.

While the manifold 96 and at least a portion of the orifices 94 can be disposed outside the tank 24, such as in the manner depicted in FIGS. 3 and 4, the orifices 94, and if desired, the manifold 96, can be disposed inside the tank 24, such as is depicted in FIG. 5, so that fluid flows 106 are expelled from the orifices 94 more closely to the food products 32 to more vigorously displace and agitate them. Where the manifold 96 and orifices 94 are disposed outside the tank 24, the location of each orifice 94 from which the fluid flows 106 are discharged is no farther than about twelve inches away from the outside of the drum sidewall 54. Where located outside the tank 24, the discharge opening 110 (FIG. 4) of each orifice 94 can be disposed in the tank 24 and preferably is located no farther away than six inches from the sidewall 54. Where orifices 94 are disposed inside the tank 24, a discharge opening of each in-tank orifice 94 is located closer than six inches because typically there is no more than about six inches between the tank 24 and drum sidewall 54. Where orifices 94 are disposed inside the tank 24, they preferably have discharge openings 110 located between about three inches and about one inch away from the sidewall 54. In one preferred embodiment, the discharge opening 110 of each in-tank orifice 94 is located about two inches away from the sidewall 54.

Where a liquid is being expelled from the orifices 94, the liquid is expelled at a flow rate of at least 60 gpm/ft to more



## 11

vigorously agitate and displace food products **32**. Preferably, the liquid is expelled from each orifice **94** at a flow rate of at least 20 gpm. In another preferred embodiment, the liquid is expelled from each orifice **94** at a flow rate of at least 60 gpm. Preferably, the liquid is expelled from each orifice **94** at a pressure of at least about 30 psi.

In another preferred method that can be dependent upon the type of food product being processed, liquid is expelled from the orifices **94** at a pressure of at least about 40 psi at a flow rate of at least about 80 gpm/ft. Preferably, the liquid is expelled from each orifice **94** at a flow rate of at least about 80 gpm. If desired, higher-pressure water having a pressure of at least 80 psi and a flow rate of at least 20 gpm/ft can be used. Preferably, at least 20 gpm is discharged from each orifice that is discharging water.

Where a liquid is being expelled, the opening of each orifice **94** can be as large as about  $\frac{1}{2}$  inch. Where round pipe is used, the pipe opening or outlet can have as large as  $\frac{1}{2}$  inch inside diameter.

Where a gas is expelled from the orifices **94**, the gas preferably is expelled at a flow rate of at least 100 CFM/ft. Preferably, the gas is discharged at a flow rate of 60 CFM from each orifice. Preferably, the gas is discharged at a pressure of at least 2 psi. In another preferred method that can be dependent on the type of food product being processed, the gas preferably is expelled at a pressure of at least 2 psi at a flow rate of no less than about 200 CFM/ft. In a still further preferred method, higher-pressure gas having a pressure of at least 60 psi and a flow rate of 10 standard cubic feet per minute per foot (SCFM/ft) of blancher length is used. In this instance, the flow rate discharged from each orifice is at least 10 CFM.

Where a gas is being expelled, the orifice opening can be as large as about  $\frac{1}{4}$  inch. Where round pipe is used, the pipe opening or outlet can have as large as  $\frac{1}{8}$  inch inside diameter.

If desired, vapor, such as steam, can also be discharged from one or more of the orifices **94** at the above-mentioned gas flow rates and pressures. Where steam is discharged, it preferably is discharged from one or more orifices at a flow rate of at least 20 pounds per hour from each orifice discharged at a discharge flow rate of at least 15 psi.

Where water is the liquid being expelled, one or more centrifugal-type water pumps can be used to achieve the aforementioned high flow rates and high pressures. If desired, one or more positive displacement sanitary pumps or liquid-ring vacuum pumps can also be used to deliver water at these high pressures and/or at these high flow rates. More than one such device for supplying water at the desired high flow rate and/or high pressure can be used. For example, as many as three or more such devices can be used to deliver a sufficiently high flow rate of water at a sufficient pressure to a single manifold.

Where air is the gas being expelled, an air compressor can be used to achieve the aforementioned high volumes and high pressures. If desired, a squirrel cage blower, a regenerative blower, or a liquid-ring vacuum pump can be used to deliver air at these high pressures and/or at these high volumes. More than one such device for supplying air at the desired high flow rate and/or high pressure can be used. For example, as many as three or more such devices can be required to deliver a sufficient volume of air at a sufficient pressure to a single manifold.

In its preferred embodiment, the manifold **96** is a pipe from which two or more orifices **94** extend. Referring to FIG. 2, while the manifold **96** can extend axially the length

## 12

of the blancher **20**, it can be broken up into two or more smaller manifolds each having a length less than the blancher **20** that are each connected to a separate fluid delivery source, system, or device. While the manifold **96** shown in FIG. 2 has a single inlet **112** and a single outlet **114**, the manifold **96** can be equipped with more than one inlet where more than one fluid delivery source, system or device is connected to the manifold **96**. The manifold outlet **114** can be capped, such as is shown in FIG. 1, or it can have a return, if desired. Other arrangements for connecting more than one fluid delivery source, system or device can be used.

FIG. 5 depicts a preferred embodiment of the invention having at least a plurality of spaced apart banks **116** of orifices **94** disposed around the food products **32** being processed with the banks **116** located between 3 o'clock and 9 o'clock. In this preferred embodiment, the blancher **20** has seven banks **116a**, **116b**, **116c**, **116d**, **116e**, **116f**, and **116g**. Of course, a blancher can be equipped with more or less than seven banks. The banks **116a**–**116g** can be generally equi-angularly spaced apart, if desired, and are shown in FIG. 5 as being located at about 3 o'clock, 4 o'clock, 5 o'clock, 6 o'clock, 7 o'clock, 8 o'clock, and 9 o'clock positions. Preferably, bank **116a** is located between 3 o'clock and 4 o'clock, bank **116b** is located between 4 o'clock and 5 o'clock, bank **116c** is located between 5 o'clock and 6 o'clock, bank **116d** is located between 6 o'clock and 7 o'clock, bank **116e** is located between 7 o'clock and 8 o'clock, bank **116f** is located between 8 o'clock and 9 o'clock, and bank **116g** is located between 9 o'clock and 12 o'clock.

Preferably, the blancher **20** is equipped with at least two banks of orifices **94** with both banks located in the exiting quadrant **118** of the tank **24** along where the drum sidewall **54** exits the heat transfer medium **33** during rotation. In the present case, since the drum **52** is depicted rotating clockwise, the exiting quadrant **118** extends from 6 o'clock to no more than 9 o'clock or about 90° from perpendicular drum centerline **120** (extends through center of drum) in the direction of drum rotation. Where the drum **52** is rotating clockwise, the exiting quadrant extends from 6 o'clock to no more than about 3 o'clock or no more than 90° from centerline **120** in the opposite direction.

The orifices **94** in a particular bank preferably all expel the same type of fluid in flow **106**. If desired, the orifices **94** in all of the banks can all expel the same type of fluid in flow **106**. However, different types of fluid can be discharged from different orifices **94**, if desired. For example, where the food products **32** are relatively heavy, liquid can be expelled from the orifices **94** of at least one bank and gas can be expelled from orifices **94** of at least one other bank not expelling liquid. g

In one preferred arrangement, the orifices **94** of banks **116a**, **116c**, **116e**, and **116g** all expel a gas at a high volume and the orifices **94** of the remaining banks **116b**, **116d** and **116f** all expel water at a high volume. In another preferred arrangement, orifices **94** of one or more of banks **116c**, **116e**, and **116d** expel a gas, preferably air, while the orifices **94** of one or more of the remaining banks, **116a**, **116b**, **116f** and **116g**, expel a liquid that preferably is water.

In still another preferred arrangement, only banks in the exiting quadrant are used, e.g. between 6 o'clock and 9 o'clock in FIG. 5, with the orifices **94** of at least one of the banks ejecting air and the orifices **94** of at least one other of the banks ejecting water. For example, the orifices **94** of at least one of banks **116d** and **116g** eject water and the orifices **94** of at least one of banks **116e** and **116f** eject air. If desired,



## 13

the orifices **94** of at least one of banks **116d** and **116g** eject air and the orifices **94** of at least one of banks **116e** and **116f** eject water.

FIG. 6 illustrates a preferred embodiment having banks **116a**, **116b**, **116c**, **116d**, **116e**, **116f**, and **116g** of orifices **94** that discharge liquid and banks **116h**, **116i**, **116j**, **116k**, **116l**, **116m**, and **116n** of orifices **94** that discharge gas. Preferably, bank **116h** is located between 3 o'clock and 4 o'clock, bank **116i** is located between 4 o'clock and 5 o'clock, bank **116j** is located between 5 o'clock and 6 o'clock, bank **116k** is located between 5 o'clock and 7 o'clock, bank **116l** is located between 6 o'clock and 7 o'clock, bank **116m** is located between 7 o'clock and 8 o'clock, bank **116n** is located between 8 o'clock and 9 o'clock. One or more of banks **116a**–**116g** can be used and one or more of banks **116h**–**116n** can be used.

FIG. 7 illustrates one preferred arrangement for processing relatively heavy food products **32** having a density of at least 55 lb/ft<sup>3</sup>. Examples of such food products include hot dogs, hot dogs in packages or pouches, turkey breasts, chicken breasts, beef patties, and steaks. Hot dogs, turkey breasts, and other meat products, for example, have a density of about 65 lb/ft<sup>3</sup> and therefore are difficult to uniformly heat, and are difficult to quickly pasteurize. The blancher **20** has at least one bank **116e** of orifices **94** located between 6 o'clock and 8 o'clock (or between 4 o'clock and 6 o'clock where the drum **52** is rotating counterclockwise) from which air is injected into a liquid heat transfer medium that preferably is water heated to a temperature above 120° Fahrenheit. Preferably, bank **116e** is located within 65° of centerline **120** in the direction of drum rotation. Since rotation is clockwise, bank **116e** is located within 65° to the left of centerline **120**. This injected air has the desired effect of making the relatively heavy food products **32** more buoyant and therefore easier to lift off the bottom of the drum **52**. The air also impinges against at least some of the food products near the bottom of the drum **52** physically urging them away from the bank **116e** and hence the drum sidewall **54**. This also desirably agitates at least some of the food products **32** in the drum **52** and thereby also improves heat transfer.

The blancher **20** has at least one bank **116f** of orifices **94** located between 7 o'clock and 9 o'clock from which water is injected into the water heat transfer medium **33**. Preferably, bank **116f** is located within a band that extends between 45° and 85° from centerline **120** in the direction of drum rotation. This injected water has the desired effect of forcefully churning the relatively heavy food products **32**, urging them away from the bank **116f** and drum sidewall **54**, breaking them up, and agitating them.

Baffles **88** are also used to physically contact food products **32** and move food products **32** that are clumped together in a direction away from the drum sidewall **54**. Thereafter, the combination of injected air and injected water helps urge the food products **32** toward the surface of the water **33**, breaking it up, all while intensely agitating the food products **32**. As a result of breaking up food products **32** that have clumped together, heat transfer is dramatically improved because the water **32** in the tank **24** can directly contact each of the food products **32**.

Although use of baffles **88** is preferred, they are not needed for all applications. For those applications not requiring baffles, a combination of gas injection and liquid injection, such as in the manner discussed above, can be used.

Either high volume air at a pressure of at least 2 psi and a volume of at least 60 SCFM/ft or high-pressure air at a

## 14

pressure of at least 80 psi and a volume of at least 10 SCFM/ft is discharged from the orifices **94** of bank **116e**. Where the air is discharged at a pressure of less than 80 psi, at least 60 SCFM is discharged from each orifice **94** discharging air. Otherwise, at least 10 SCFM is discharged from each orifice **94** of each orifice that is discharging air. Either high volume water at a pressure of at least 30 psi and a flow rate of at least 80 gpm/ft or high-pressure water at a pressure of at least 80 psi and a flow rate of at least 20 gpm/ft is discharged from the orifices of bank **116f**. Preferably, at least 20 gpm is discharged from each orifice of each bank that is discharging water. If desired, one or more orifices **94** or banks of orifices can be employed that discharge a vapor that preferably is steam.

Because these relatively heavy food products **32** are also each relatively large in size, the drum sidewall perforations **68** each are at least 3/4 inch in width or diameter. Preferably, for such large food products **32** the drum sidewall perforations **68** each can range in size (width or diameter) from 1/2 inch or 3/4 inch.

Where the food products **32** are to be blanched and the heat transfer medium **33** in the tank **24** is water, the water **33** preferably is kept at a temperature above 185° Fahrenheit (F). Where the food products **32** are to be pasteurized, the water **33** is kept at a temperature above 120° F. and each food product **32** resides in the blancher **20** for at least 3 minutes and as long as 720 minutes. Preferably, pasteurization of these kinds of relatively heavy food products **32** at or above this temperature takes no more than about 4 minutes per food product **32**. The use of the aforementioned directed flows **106** advantageously reduces pasteurization time by as much as 25% while helping to ensure complete and uniform pasteurization of each food product.

More product can advantageously be blanched or pasteurized at one time. For example, where only a few inches of relatively heavy food product **32** can be processed in a prior art blancher at a given moment, at least double the food product depth can be processed in a blancher of this invention using a method of this invention. For example, no more than six inches depth of packaged hot dogs **32** can be blanched in a prior art 72 inch diameter blancher equipped only with baffles **88**, whereas at least eight inches and preferably at least twelve inches of depth of packaged hot dogs **32** can be blanched by a blancher **20** of the present invention that is also 72 inches in diameter. This also translates into dramatically increased throughput. More specifically, where a certain amount of food products **32** can be processed in a given hour using a prior art blancher, a blancher **20** of the present invention will process at least double that amount. For example, a 72-inch diameter blancher **20** of the present invention will process at least 6000 pounds per hour (lbs/hr) of relatively heavy food product **32** as compared to no more than 3000 lbs/hr for a prior art blancher of the same size. This is true for the processing of hot dogs or packaged hot dogs. Experiments with a prior art blancher equipped with baffles resulted in only 5000 lbs/hr of food product **32** being processed, whereas at least 10000 lbs/hr of the same food product **32** can be processed using a blancher **20** of this invention. Thus, the preferred arrangement can process at least 8000 lbs/hr of food product **32**.

FIG. 8 depicts another arrangement of the invention that is used to process food products having a density no greater than 55 lb/ft<sup>3</sup>. This arrangement is suited for processing relatively fragile food products **32** that include, for example, pasta, lasagna, and tortellini. For exemplary purposes, pasta or lasagna food products **32** are shown in FIG. 8 and have a density of about 40 lb/ft<sup>3</sup>.



## 15

The arrangement shown in FIG. 8 includes at least a plurality of pairs of spaced apart banks **116b**, **116c**, **116d**, **116e** and **116f** of orifices **94** that each deliver a fluid that preferably is a gas, namely air. Bank **116b** is disposed between 3 o'clock and 5 o'clock or lies within a band located between 45° and 65° from the perpendicular drum centerline **120** in a direction opposite the direction of drum rotation (measured from the center of the drum and line **120**). Bank **116c** is disposed between 4 o'clock and 6 o'clock or lies within a band located between 25° and 40° from the centerline **120** in a direction opposite the direction of drum rotation. Bank **116d** is disposed between 5 o'clock and 7 o'clock or lies within  $\pm 25^\circ$  of the centerline **120**. Bank **116e** is disposed between 6 o'clock and 8 o'clock or lies within a band located between 25° and 40° from the centerline **120** in a direction the same as the direction of drum rotation. Bank **116f** is disposed between 7 o'clock and 9 o'clock or lies within a band located between 45° and 65° from the centerline **120** in a direction the same as the direction of drum rotation.

Air is discharged from the orifices **94** in each bank **116b**–**116f** either generally upwardly or generally toward the food products **32** in the drum **52** causing at least some of the air to become trapped in the food products **32** thereby increasing their buoyancy. By increasing the buoyancy of the food products **32** in the drum **52**, at least some of the food products **32** begin to float and rise from the bottom of the drum **52** (where the food products **32** are shown in FIG. 8), and thereby become more directly exposed to the water heat transfer medium **33**. The discharged air also advantageously has the desired effect of churning the water **33** and also agitating the food products **32**. As a result of the high volumes and/or high pressures used, the agitation achieved is more vigorous and more forceful. All of this advantageously increases heat transfer to the food products **32** without requiring direct contact between food products **32** and mechanical agitation devices such as baffles. Thus, no baffles are needed and no baffles are shown in FIG. 8 making this arrangement particularly suitable for processing relatively fragile food products.

Either high volume air at a pressure of at least 2 psi and a volume of at least 60 SCFM/ft or high pressure air at a pressure of at least 80 psi and a volume of at least 10 SCFM/ft is discharged from the orifices **94** of each bank of one or more of banks **116b**–**116f**. Preferably, at least 10 SCFM is discharged from each orifice **94** of each bank that is discharging air. Where pasta or pasta-based products **32** are processed, the drum sidewall perforations **68** each are no greater than  $\frac{5}{32}$  inch in width or diameter. During processing of these kinds of products, the water preferably is kept at a temperature of above 190° F. and can be cooked in the manner previously described, if needed.

If desired, one or more orifices **94** or banks of orifices **94** can be employed through which water is discharged. If desired, one or more orifices **94** or banks of orifices **94** can be employed through which steam is discharged.

More product can advantageously be blanched, cooked, or pasteurized at one time. For example, where only a few inches of relatively fragile pasta or lasagna **32** can be processed in a prior art blancher at a given moment, at least double the food product depth can be processed in a blancher of this invention. For example, where no more than six inches depth of pasta or lasagna can be blanched in a prior art 72 inch diameter blancher, at least eight inches and preferably at least twelve inches of depth of pasta or lasagna **32** can be blanched by a 72 inch diameter blancher **20** of the present invention. This also translates into dramatically

## 16

increased throughput. More specifically, where a certain amount of food products **32** can be processed in a given hour using a prior art blancher, a blancher **20** of the present invention will process at least double that amount. For example, a 72-inch diameter blancher **20** of the present invention will process at least 4500 lbs/hr and preferably at least 7000 lbs/hr of pasta or lasagna **32** as compared to a prior art 72-inch diameter blancher, which can only process 3500 lbs/hr.

FIG. 9 depicts a blancher **20** of this invention having at least one orifice **94** from which a fluid is discharged into the tank **24**. The discharged fluid is drawn from within the blancher **20** by a pump **122** that delivers the fluid to the orifice **94**. Such an arrangement advantageously conserves energy because it recirculates the fluid discharged into the blancher **20** lessening heat losses.

FIG. 9 illustrates a first fluid recirculation system **124** where a liquid heat transfer medium **26** is disposed in the tank **24**. The system includes an inlet **126** through which liquid from the blancher **20** enters a conduit **128**. The liquid flows through the conduit **128** to a pump **122** that delivers the liquid via another conduit **130** to orifice **94**. The liquid is discharged through the orifice **94** into the tank **24**. In one embodiment, the orifice **94** is disposed so as to direct the liquid toward a particular location, such as the drum **52**, one or more food products **32** in the drum **52**, or a spot or region where food products **32** tend to congregate or clump. In the arrangement shown in FIG. 9, the inlet **126** is disposed below the water line of the liquid heat transfer medium **26** and above orifice **94**. If desired, the drum **52** can be equipped with one or more baffles **88**.

FIG. 9 further illustrates a second fluid recirculation system **132** where atmosphere **134** within the blancher **20** is collected and discharged into the tank **24**. The atmosphere within the blancher typically comprises gas and vapor, typically air and water vapor, but can be comprised solely of a gas or a vapor. Where a liquid heat transfer medium **26** is used, the atmosphere **134** is disposed above the liquid **26**. The system includes an inlet **136** through which atmosphere **134** in the blancher **20** is drawn into a first conduit **138**. The atmosphere **134** flows through the conduit **138** to a pump **122'** that delivers the atmosphere via a second conduit **140** to the other orifice **94**. The atmosphere **134** is then discharged through that orifice **94** into the tank.

In this manner, fluid used to move and agitate food products **32** in the blancher **20** is delivered to a single orifice **94**, a plurality of orifices **94**, a manifold **96** connected to a plurality of orifices **94**, or a plurality of manifolds **94**. One or more first and second fluid recirculation systems **124** and **132** can be used alone or in combination in a single blancher. The pump **122** preferably is a pump, a blower or a compressor capable of operating where moisture or liquid is present.

An example of a preferred pump for recirculating atmosphere is a liquid-ring vacuum pump or liquid-ring vacuum compressor. Examples of liquid-ring vacuum pumps or compressors are disclosed in U.S. Pat. Nos. 4,787,824 and 5,580,222, the disclosures of which are expressly incorporated herein. A liquid-ring vacuum pump or liquid-ring vacuum compressor is particularly preferred for pump **122'** because of its ability to suck hot air carrying water vapor from inside the blancher **20** and deliver it under pressure to an orifice **94**, a plurality of orifices **94**, and/or one or more manifolds. This type of pump is also preferred because of its ability to be able to reliably pump air containing moisture for long periods of time and over a long service life all while withstanding a rather harsh operating environment.



17

FIG. 10 illustrates first and second recirculation systems 124 and 132 each with a heater 142 that heats the fluid being recirculated. For example, the first recirculation system 124 includes a heater 142 that can be located upstream of the pump 122 to heat the liquid drawn from the blancher 20. The second recirculation system 124 can also include a heater 142 that heats the atmosphere 134 drawn from within the blancher 20. Examples of suitable fluid heaters 142 include gas fluid heaters and electric fluid heaters. Heated liquid, heated atmosphere, or heated vapor can be added to the fluid being recirculated. If desired, the heater 142 can be located downstream of the pump 122 or pump 122'.

These recirculation systems advantageously conserve energy by recirculating already hot fluid from the blancher 20 thereby preventing the heat loss that would occur if cooler ambient air outside the blancher 20 or cooler plant water was instead used. If, desired, the first fluid recirculation system 124 and/or the second fluid recirculation system 132 shown in FIGS. 9 and 10 can be used with any one of the arrangements depicted in FIGS. 1-8 and can be used to recirculate liquid at flow rates and pressures less than those discussed above in association with the arrangements depicted in FIGS. 1-8.

In use, the blancher 20 of this invention is used to process food products 32 preferably by blanching or pasteurizing the food products 32. Food product 32 that can be processed using the blancher 20 includes food product 32 in pouches that are preferably constructed of a flexible, synthetic material that typically is of laminate construction. Examples of such pouched food product include: sauces, soups, juices, catsup, fruits, certain pastas, vegetables, meats, hot dogs, and the like. Food products 32 that can be processed using the blancher 20 include food products 32 not in pouches. For example, and without limitation, pastas and vegetables like potatoes, corn, rice, beans, spinach, are but a few types of food products 32 not in pouches that can be heated, cooked or blanched by the blancher 20 of this invention.

In operation, food products 32 are introduced into the blancher 20 through the inlet 60 and preferably enter the drum 52. The food product transport mechanism 44 urges the food products 32 received in the blancher 20 toward the outlet 62 preferably by rotation.

Where the food product transport mechanism 44 is an auger 48, the rate of rotation of the auger 48 is controlled to control the residency time of the food products 32 within the blancher 20. For example, the auger 48 can be rotated as slow as one-half of a revolution per minute to as fast as ten or more revolutions per minute depending on factors such as 1) the type of food product 32, 2) the length of the blancher 20, 3) the diameter of the blancher 20, 4) whether the food product 32 is simply being blanched or pasteurized, 5) the type of heat transfer medium 33 being used, and 6) other factors. Typically, selection of a rate of rotation is based upon experience and routine testing and experimentation.

As the food products 32 travel along the blancher 20, they are immersed in the heat transfer medium 33, which heats the food products 32. Where the blancher 20 is equipped with baffles 88, the baffles 88 help scoop up at least some of the food products 32 that have fallen to the bottom. As each baffle 88 rises toward the surface of the heat transfer medium 33, typically water, food products 32 carried by the baffle 88 slide off and tumble, thereby agitating the food products 32 while also helping to break up clumps of food products 32.

Where liquid injection is used, the liquid flows 106 are directed from orifices 94 toward food products 32 in the blancher 20 displacing at least some of the food products 32

18

which helps break up any food products 32 that have clumped together, increasing heat transfer efficiency. Additionally, the liquid flows 106 directed toward the food products 32 help agitate them thereby increasing heat transfer efficiency. Where liquid, such as water, is discharged, the volumetric flow rate and pressure are selected to satisfy the following condition:

$$P \cdot V \geq 55 \frac{\text{lbs} \cdot \text{gallons}}{\text{in}^2 \cdot \text{min}} \quad (\text{Equation I})$$

where:

P is the pressure of the liquid in psi; and

V is the volumetric flow rate of liquid discharged from each orifice 94 in gpm.

Where more turbulence is desired, the volumetric flow rate and pressure are selected to provide highly turbulent flow within the blancher and satisfy the following condition:

$$P \cdot V \geq 65 \frac{\text{lbs} \cdot \text{gallons}}{\text{in}^2 \cdot \text{min}} \quad (\text{Equation II})$$

Where gas injection is used, the gas flows 106 are directed from orifices 94 toward food products 32 in the blancher 20 increasing the buoyancy of at least some of the food products 32. By increasing buoyancy, at least some of the food products 32 will float up from the bottom and thereby become more directly exposed to the heat transfer medium 33 increasing heat transfer efficiency. Depending upon the volume and pressure of gas injected, the force of the gas flows 106 impinging against food products 32 will also help agitate them which further increases heat transfer efficiency. Depending upon the force with which the gas impinges, the gas flows 106 impinging against food products 32 can also help break up clumps of food products. Where a gas, such as air, is discharged, the flow rate and pressure are selected to provide highly turbulent flow within the blancher and to satisfy the following condition:

$$P \cdot V \geq 0.1275 \frac{\text{in of H}_2\text{O}}{\text{CFM}} \quad (\text{Equation III})$$

where:

P is the pressure of the gas in inches of H<sub>2</sub>O; and

V is the volumetric flow rate of gas discharged from each orifice 94 in CFM.

Where even more flow and turbulence are desired, the gas flow rate and pressure are selected to satisfy the following condition:

$$P \cdot V \geq 0.15 \frac{\text{in of H}_2\text{O}}{\text{CFM}} \quad (\text{Equation IV})$$

Where steam is discharged, the flow rate and pressure are selected to provide highly turbulent flow within the blancher and satisfy the following condition:

$$P \cdot V \geq 300 \frac{\text{lbs}^2}{\text{in}^2 \cdot \text{hr}} \quad (\text{Equation V})$$

where:

P is the pressure of the steam in pounds per square inch; and



19

V is the volumetric flow rate of steam discharged from each orifice 94 in lbs/hr.

In some instances, it may be desirable to use gas injection alone to increase heat transfer. In other instances, it may be desirable to use gas injection in combination with baffles 88 or another direct-contact agitation device. In still other instances, it may be desirable to use a combination of gas injection and liquid injection or a combination of gas injection, liquid injection, and direct-contact agitation devices. In even other instances, it may be desirable to use liquid injection with or without direct-contact mechanical agitation devices.

Once food products 32 have completed their journey through the blancher 20, they are discharged from the outlet 62. After that, the food products 32 can be packaged and shipped, packaged and frozen, stored, or further processed.

It is also to be understood that, although the foregoing description and drawings describe and illustrate in detail one or more embodiments of the present invention, to those skilled in the art to which the present invention relates, the present disclosure will suggest many modifications and constructions as well as widely differing embodiments and applications without thereby departing from the spirit and scope of the invention. The present invention, therefore, is intended to be limited only by the scope of the appended claims.

What is claimed is:

1. A method of heating a food product comprising:

- a) providing a blancher including a *perforate* food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, and *at least one orifice bank comprised of a plurality of pairs of orifices each for introducing a [fluid] liquid into a tank disposed inside the housing in which the food product-receiving chamber is received with the orifices spaced apart in a lengthwise direction relative to the tank substantially the length of the tank;*
  - b) introducing food product into *the food product-receiving chamber into a liquid heat transfer medium within the [housing of the blancher] tank through the inlet;*
  - c) *turbulently* discharging a [fluid] liquid through [at least] each one of the plurality of pairs of orifices into the liquid heat transfer medium in the tank;
  - d) heating the food product in the food product-receiving chamber *using the liquid heat transfer medium in the tank with the liquid heat transfer medium having a temperature of at least 120 Fahrenheit;*
  - e) urging the food product in the food product-receiving chamber toward the outlet; [and]
  - f) removing the food product from the food product-receiving chamber through the outlet;
- wherein in step c) the liquid that is discharged through orifices at a flow rate of at least 20 gallons per minute per foot of tank length; and*
- wherein the orifices in the orifice bank are oriented to direct the discharged liquid into liquid heat transfer medium in an exiting quadrant of the tank generally toward an axis of rotation of the rotary food product transport medium.*

[2. The method of claim 1 wherein in step c) the fluid is a liquid that is discharged through at least one of the orifices at a flow rate of at least 20 gpm and a pressure of at least 30 psi.]

20

3. The method of claim [2] 1 wherein [there is provided at least one bank of orifices comprised of a plurality of orifices, the blancher has a length, and] in step c) the liquid is discharged from the [bank of orifices] *at least one of the orifice banks* at a flow rate of at least 20 gallons per minute per orifice or 60 [gpm] gallons per minute per foot [of length of the blancher].

4. The method of claim 3 [wherein the heat transfer medium comprises a liquid and] further comprising the additional step of withdrawing liquid heat transfer medium from the [blancher] tank and discharging the withdrawn liquid heat transfer medium *from the orifices* in step c).

5. [The] A method of [claim 1] heating a food product comprising:

- a) *providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, and a plurality of spaced apart banks of orifices each comprised of a plurality of pairs of orifices each for introducing a fluid into a tank holding a liquid heat transfer medium;*
- b) *introducing food product into the liquid heat transfer medium within the tank through the inlet;*
- c) *discharging a fluid through each one of the plurality of pairs of orifices of each one of the plurality of orifice banks into the liquid heat transfer medium within the tank;*
- d) *heating the food product in the food product-receiving chamber via heat transfer from liquid heat transfer medium having a temperature of at least 120° Fahrenheit;*
- e) *urging the food product in the food product-receiving chamber toward the outlet by rotating the food product transport mechanism; and*
- f) *removing the food product from the food product-receiving chamber through the outlet;*

*wherein in step c) the fluid [is a liquid] discharged [through at least one of] from the orifices of at least one of the plurality of orifice banks comprises a liquid at a flow rate of at least 20 [gpm] gallons per minute per foot of manifold length and at a pressure of at least [80 psi] about 30 pounds per square inch; and*

*wherein each one of the plurality of orifice banks is spaced apart and located so each one of the orifices of each one of the plurality of orifice banks directs fluid flow into liquid heat transfer medium located in an exiting quadrant of the tank.*

6. The method of claim 5 wherein [there is provided at least one bank of orifices comprised of a plurality of orifices, the blancher has a length, and] in step c) the liquid is discharged from the bank of orifices at a *pressure of at least 80 pounds per square inch or a flow rate of at least 60 [gpm] gallons per minute per foot [of length of the blancher].*

7. The method of claim 6 [wherein the heat transfer medium comprises a liquid and] further comprising the additional step of withdrawing liquid heat transfer medium from the blancher and discharging the withdrawn liquid heat transfer medium in step c) *from the orifices of the at least one of the orifice banks.*

8. [The] A method of [claim 1] heating a food product comprising:

- a) *providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a*



21

rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, and a plurality of pairs of orifices each for introducing a fluid into the housing;

- b) introducing food product into a liquid heat transfer medium within the housing of the blancher through the inlet;
- c) discharging a fluid through at least one of the plurality of pairs of orifices into the heat transfer medium;
- d) heating the food product in the food product-receiving chamber;
- e) urging the food product in the food product-receiving chamber toward the outlet; and
- f) removing the food product from the food product-receiving chamber through the outlet; and

wherein in step c) the fluid comprises a gas discharged through [at least] each one of the orifices into the liquid heat transfer medium within the housing in an exiting quadrant of the blancher toward the perforate food product-receiving chamber at a flow rate of at least 60 [CFM] cubic feet per minute and at a pressure of at least 2 [psi] pounds per square inch.

9. The method of claim 8 wherein there is a gaseous atmosphere in the blancher and further comprising the additional step of withdrawing a portion of the gaseous atmosphere from the blancher and discharging the withdrawn portion of the gaseous atmosphere in step c).

10. The method of claim 9 wherein the heat transfer medium comprises water and the gaseous atmosphere in the blancher includes water vapor.

11. The method of claim 8 wherein there is provided at least one bank of orifices comprised of a plurality of orifices, the blancher has a length, and in step c) the gas is discharged from the bank of orifices at a flow rate of at least 100 CFM per foot of length of the blancher.

12. The method of claim 8 wherein there is provided at least one bank of orifices comprised of a plurality of orifices, the blancher has a length, and in step c) the gas is discharged from the bank of orifices at a flow rate of at least 200 CFM per foot of length of the blancher.

13. [The] A method of [claim 1] heating a food product comprising:

- a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, a first bank comprised of a plurality of pairs of orifices each for introducing a fluid into a liquid heat transfer medium holding tank, and a second bank comprised of a plurality of pairs of orifices each for introducing a fluid into the liquid heat transfer medium holding tank;
- b) introducing food product into liquid heat transfer medium within the tank through the inlet;
- c) discharging a fluid through at least one of the plurality of pairs of orifices of each orifice bank into the liquid heat transfer medium within the tank;
- d) heating the food product in the food product-receiving chamber;
- e) urging the food product in the food product-receiving chamber toward the outlet; and
- f) removing the food product from the food product-receiving chamber through the outlet; and

22

wherein in step c) the fluid comprises a gas discharged through [at least] each one of the orifices [at a flow rate of at least 10 CFM and a pressure of at least 60 psi] of one of the orifice banks into liquid heat transfer medium in an exiting quadrant of the blancher; and wherein in step c) the fluid comprises a liquid discharged through each one of the orifices of the other one of the orifice banks into liquid heat transfer medium in the exiting quadrant of the blancher.

14. The method of claim 13 wherein there is a gaseous atmosphere in the blancher and further comprising the additional step of withdrawing a portion of the gaseous atmosphere from the blancher and discharging the withdrawn drawn portion of the gaseous atmosphere in step c) through the orifices of the one of the orifice banks.

15. The method of claim 14 wherein the liquid heat transfer medium comprises water and the gaseous atmosphere in the blancher includes water vapor.

16. The method of claim 13 wherein there is provided at least one bank of orifices comprised of a plurality of orifices, the blancher has a length, [and] in step c) the gas is discharged from the [bank of] orifices of the one of the orifice banks at a flow rate of at least 10 CFM per foot of length [of the blancher], and in step c) the liquid is discharged from the from the orifices of the other one of the orifice banks at a flow rate of at least 20 gpm per foot of length.

17. [The] A method of [claim 1] heating a food product comprising:

- a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, a first bank of a plurality of pairs of orifices each for introducing a fluid into the housing, and a second bank of a plurality of pairs of orifices each for introducing a fluid into the housing;
- b) introducing food product into liquid heat transfer medium within the housing of the blancher through the inlet wherein the liquid heat transfer medium has a temperature high enough to blanch the food product;
- c) discharging a fluid through each one of the plurality of pairs of orifices of each one of the orifice banks into the liquid heat transfer medium;
- d) heating the food product in the food product-receiving chamber via heat transfer from the liquid heat transfer medium;
- e) urging the food product in the food product-receiving chamber toward the outlet; and
- f) removing the food product from the food product-receiving chamber through the outlet; and

wherein the food products have a density of at least 55 lb/ft<sup>3</sup> and in step c) [there is at least one orifice through which] water is discharged from the orifices of one of the orifice banks into liquid heat transfer medium in an exiting quadrant of the blancher at a flow rate of at least 20 gpm [and a pressure of at least 30 psi] per foot of manifold length and [there is at least one orifice through which] air is discharged from the orifices of the other one of the orifice banks into liquid heat transfer medium in the exiting quadrant of the blancher at a flow rate of at least 60 SCFM [and a pressure of at least 2 psi].

18. The method of claim 17 wherein there is at least eight inches of depth of food product in the food product-receiving chamber.



## 23

19. The method of claim 17 wherein at least eight thousand pounds of food product per hour is removed in step f).

20. [The] A method of [claim 1] heating a food product comprising:

- a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, a first elongate longitudinally extending manifold comprised of a plurality of pairs of orifices each for introducing a fluid into the housing, and a second longitudinally extending manifold comprised of a plurality of pairs of orifices each for introducing a fluid into the housing;
- b) introducing food product into a water heat transfer medium within the housing of the blancher through the inlet;
- c) discharging a fluid through each one of the plurality of pairs of orifices of each one of the first and second manifolds into the water heat transfer medium;
- d) heating the food product in the food product-receiving chamber;
- e) urging the food product in the food product-receiving chamber toward the outlet; and
- f) removing the food product from the food product-receiving chamber through the outlet;

wherein the food products have a density of at least 55 lb/ft<sup>3</sup> and in step c) [there is at least one orifice through which] water is discharged at a flow rate of at least 20 gpm [and a pressure of at least 30 psi and there is at least one orifice through which air is discharged at a flow rate of at least 10 SCFM and a pressure of at least 80 psi] per foot of manifold length from the orifices of each one of the manifolds into water heat transfer medium in an exiting quadrant of the blancher and into water heat transfer medium in the perforate food product-receiving chamber so it impinges against food product in the perforate food product-receiving chamber; and

wherein the water discharged from the plurality of pairs of orifices of each one of the first and second manifolds is recirculated water heat transfer medium withdrawn from within the blancher housing.

21. The method of claim 20 wherein there is at least eight inches of depth of food product in the food product-receiving chamber.

22. The method of claim 20 wherein at least eight thousand pounds of food product per hour is removed in step f).

23. [The] A method of [claim 1] heating a food product comprising:

- a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, first manifold comprised of a plurality of pairs of orifices each for introducing a fluid into the housing, and a second manifold comprised of a plurality of pairs of orifices each for introducing a fluid into the housing;
- b) introducing food product into liquid heat transfer medium within the housing of the blancher through the inlet;

## 24

c) discharging a fluid through each one of the plurality of pairs of orifices of the first and second manifolds into the liquid heat transfer medium;

d) heating the food product in the food product-receiving chamber;

e) urging the food product in the food product-receiving chamber toward the outlet; and

f) removing the food product from the food product-receiving chamber through the outlet; and

wherein the blancher has a length, the food products being heated in the blancher have a density of at least 55 lb/ft<sup>3</sup>, and in step c) [there is at least one orifice through which] water is discharged [at a flow rate of at least 80 gpm per foot of blancher length and a pressure of at least 30 psi and there is at least one orifice through which air is discharged at a flow rate of at least 10 SCFM per foot of blancher length and a pressure of at least 80 psi] from each one of the plurality of pairs of orifices of each one of the first and second manifolds at a flow rate of at least 20 gpm per foot of manifold into liquid heat transfer medium in the blancher housing located in an exiting quadrant of the blancher toward and into the perforate food product-receiving chamber.

24. The method of claim 23 wherein each one of the first and second manifolds are spaced apart from one another, wherein each one of the first and second manifolds extend in a longitudinal direction relative to the blancher housing, and each one of the first and second manifolds are disposed outside the blancher housing, and wherein there is at least eight inches of depth of food product in the food product-receiving chamber.

25. The method of claim 23 wherein at least eight thousand pounds of food product per hour is removed in step f).

26. [The] A method of [claim 1] heating a food product comprising:

[wherein the blancher has a length, the food products have a density of at least 55 lb/ft<sup>3</sup>, and in step c) there is at least one orifice through which water is discharged at a flow rate of at least 80 gpm per foot of blancher length and a pressure of at least 30 psi and there is at least one orifice through which air is discharged at a flow rate of at least 60 SCFM per foot of blancher length and a pressure of at least 2 psi.]

- a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, and at least one manifold comprised of a plurality of pairs of orifices each for introducing a fluid into the housing;
- b) introducing food product into liquid heat transfer medium within the housing of the blancher through the inlet having a temperature high enough to blanch the food product during its residency time in the liquid heat transfer medium in the blancher housing;
- c) withdrawing liquid heat transfer medium from within the housing of the blancher;
- d) discharging the withdrawn liquid heat transfer medium through each one of the plurality of pairs of orifices of the manifold into the liquid heat transfer medium disposed in an exiting quadrant of the blancher at a flow rate of at least 20 gpm per foot of blancher length substantially along the entire length of the blancher housing;



25

- e) heating the food product in the food product-receiving chamber;
- f) urging the food product in the food product-receiving chamber toward the outlet by rotating the rotary food product transport mechanism; and
- g) removing the food product from the perforate food product-receiving chamber through the outlet.

27. The method of claim 26 wherein there are a plurality of manifolds each having a plurality of pairs of liquid heat transfer medium discharging orifices that discharge recirculated liquid heat transfer medium in step d) and wherein there is at least eight inches of depth of food product in the perforate food product-receiving chamber.

28. The method of claim 26 wherein at least eight thousand pounds of food product per hour is removed in step f).

29. [The] A method of [claim 1] heating a food product comprising:

- a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, and at least one longitudinally extending manifold disposed outside the blancher housing that is comprised of a plurality of pairs of orifices each for introducing a fluid into the housing;
- b) introducing food product into liquid heat transfer medium within the housing of the blancher through the inlet with the liquid heated to a temperature high enough to at least pasteurize the food product;
- c) discharging liquid heat transfer medium withdrawn from within the blancher housing through each one of the plurality of pairs of orifices of the at least one manifold back into the liquid heat transfer medium within the blancher housing;
- d) heating the food product in the food product-receiving chamber using the liquid heat transfer medium;
- e) urging the food product in the food product-receiving chamber toward the outlet by rotating the rotary food product transport mechanism; and
- f) removing the food product from the food product-receiving chamber through the outlet; and

wherein the blancher has a length, the food products have a density of at least 55 lb/ft<sup>3</sup>, and in step c) [there is at least one orifice through which water] liquid heat transfer medium is discharged from each one of the plurality of pairs of orifices of the at least one manifold substantially along the entire length of the blancher housing at a flow rate of at least 20 gpm per foot of blancher length and at a pressure of at least [80] about 30 psi [and there is at least one orifice through which air is discharged at a flow rate of at least 10 SCFM per foot of blancher length and a pressure of at least 80 psi] into an exiting quadrant of the blancher.

30. The method of claim 29 wherein there is at least eight inches of depth of food product in the food product-receiving chamber.

31. The method of claim 29 wherein at least eight thousand pounds of food product per hour is removed in step f).

32. [The] A method of [claim 1] heating a food product comprising:

- a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that

26

has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, and a plurality of pairs of orifices each for introducing a fluid into the housing;

- b) introducing food product into a liquid heat transfer medium within the housing of the blancher through the inlet;

- c) discharging a fluid through each one of the plurality of pairs of orifices into the heat transfer medium;

- d) heating the food product in the food product-receiving chamber;

- e) urging the food product in the food product-receiving chamber toward the outlet; and

- f) removing the food product from the food product-receiving chamber through the outlet; and

wherein the blancher has a length, the food products have a density of at least 55 lb/ft<sup>3</sup>, and in step c) there is at least one orifice through which water is discharged at a flow rate of at least [80] 20 gpm per foot of blancher length and a pressure of at least 30 psi into liquid heat transfer medium in an exiting quadrant of the blancher and there is at least one orifice through which air is discharged at a flow rate of at least 10 SCFM per foot of blancher length and a pressure of at least 80 psi into liquid heat transfer medium in the exiting quadrant of the blancher.

33. The method of claim 32 wherein there is at least eight inches of depth of food product in the food product-receiving chamber.

34. The method of claim 32 wherein at least eight thousand pounds of food product per hour is removed in step f).

35. [The] A method of [claim 1] heating a food product comprising:

- a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, and a plurality of pairs of orifices arranged in a lengthwise direction substantially the length of the blancher housing with each orifice for introducing a fluid into the housing;
- b) introducing food product into a liquid heat transfer medium within the housing of the blancher through the inlet;
- c) discharging a fluid through each one of the plurality of pairs of orifices into the liquid heat transfer medium;
- d) heating the food product in the food product-receiving chamber;
- e) urging the food product in the food product-receiving chamber toward the outlet; and
- f) removing the food product from the food product-receiving chamber through the outlet; and

wherein the blancher has a length, the food products have a density of no greater than 55 lb/ft<sup>3</sup>, and in step c) [there is at least one orifice through which] air is discharged from each one of the plurality of pairs of orifices into the liquid heat transfer medium in an exiting quadrant of the blancher at a flow rate of at least 60 SCFM per foot of blancher length and a pressure of at least 2 psi.

36. The method of claim 35 wherein there is at least eight inches of depth of food product in the food product-receiving chamber.



27

37. The method of claim 35 wherein at least four thousand five hundred pounds of food product per hour is removed in step f).

38. [The] A method of [claim 1] heating a food product comprising:

- a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, and a plurality of pairs of orifices arranged in a lengthwise direction substantially the length of the blancher housing with each orifice for introducing a fluid into the housing;
- b) introducing food product into a liquid heat transfer medium within the housing of the blancher through the inlet;
- c) discharging a fluid through each one of the plurality of pairs of orifices into the heat transfer medium;
- d) heating the food product in the food product-receiving chamber;
- e) urging the food product in the food product-receiving chamber toward the outlet; and
- f) removing the food product from the food product-receiving chamber through the outlet; and

wherein the blancher has a length, the food products have a density of no greater than 55 lb/ft<sup>3</sup>, and in step c) [there is at least one orifice through which] air is discharged from each one of the plurality of pairs of orifices into the liquid heat transfer medium in an exiting quadrant of the blancher at a flow rate of at least 10 SCFM per foot of blancher length and a pressure of at least 80 psi.

39. The method of claim 38 wherein there is at least eight inches of depth of food product in the food product-receiving chamber.

40. The method of claim 38 wherein at least four thousand five hundred pounds of food product per hour is removed in step f).

41. A method of heating a food product comprising:

- a) providing a blancher including a food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, a first manifold having a plurality of pairs of orifices each for introducing a fluid into the housing, and a second manifold having a plurality of pairs of orifices each for introducing a fluid into the housing;
- b) introducing food product into a liquid heat transfer medium within the housing of the blancher through the inlet;
- c) discharging a fluid through each one of the plurality of pairs of orifices into the heat transfer medium;
- d) heating the food product in the food product-receiving chamber;
- e) urging the food product in the food product-receiving chamber toward the outlet; and
- f) removing the food product from the food product-receiving chamber through the outlet; and

wherein each manifold is 1) oriented in a lengthwise direction relative to the food product receiving chamber with the manifold orifices directing flow of liquid heat transfer medium toward the food product receiving

28

ing chamber and 2) located outwardly of a lengthwise-extending centerline of the blancher with each one of the manifold orifices directing fluid flow into an exiting quadrant thereof defined from where the rotating food product transport mechanism emerges from the heat transfer medium to adjacent the centerline but not passing to or beyond the centerline.

42. A method of heating a food product comprising:

- a) providing a blancher including a food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging the food product toward the food product outlet, and a manifold having a plurality of pairs of orifices distributed along substantially the length of the blancher housing each for introducing a fluid into the housing;
- b) introducing food product into a liquid heat transfer medium within the housing of the blancher through the inlet;
- c) discharging a fluid through each one of the plurality of pairs of orifices into the heat transfer medium;
- d) heating the food product in the food product-receiving chamber;
- e) urging the food product in the food product-receiving chamber toward the outlet; and
- f) removing the food product from the food product-receiving chamber through the outlet;

wherein in step c) the fluid is a liquid that is discharged through the orifices at a flow rate of at least 20 gallons per minute per foot of manifold; and wherein the manifold is 1) oriented in a lengthwise direction relative to the food product receiving chamber with the manifold orifices directing flow of liquid heat transfer medium toward the food product receiving chamber and 2) located outwardly of a lengthwise-extending centerline of the blancher with each one of the manifold orifices directing fluid flow into an exiting quadrant thereof defined from where the rotating food product transport mechanism emerges from the heat transfer medium to adjacent the centerline but not passing to or beyond the centerline.

43. A method of heating a food product comprising:

- a) providing a blancher including a perforate food product-receiving and generally cylindrical drum disposed in a housing that has a food product inlet, a food product outlet, and comprises a liquid heat transfer medium holding tank, a rotary auger having a plurality of flights disposed in the drum for urging the food product toward the food product outlet, a first manifold having a plurality of pairs of orifices each for introducing a fluid into the tank and drum, and a second manifold having a plurality of pairs of orifices each for introducing a fluid into the tank and drum;
- b) introducing food product into liquid heat transfer medium disposed in the drum through the inlet with the liquid heat transfer medium having a temperature of at least 120° Fahrenheit;
- c) discharging a fluid through each one of the plurality of pairs of orifices of each one of the manifolds into the liquid heat transfer medium;
- d) heating the food product in the food product-receiving chamber;
- e) urging the food product in the food product-receiving chamber toward the outlet by rotating the auger; and



29

f) removing the food product from the drum through the outlet;

wherein in step c) the fluid is a liquid that is discharged through each one of the orifices of at least one of the manifolds at a flow rate of at least 20 gallons per minute per foot of manifold; and

wherein each manifold is 1) oriented in a lengthwise direction relative to the perforate drum with the orifices of the manifold directing flow of liquid heat transfer medium toward the perforate drum and 2) located outwardly of a lengthwise-extending generally vertical centerline of the blancher in an exiting quadrant thereof defined from where at least one of the auger flights of the rotary auger emerges from the liquid heat transfer medium to adjacent the centerline but not passing to or beyond the centerline.

44. A method of heating a food product comprising:

a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the perforate food product receiving chamber for urging the food product toward the food product outlet, a first manifold having a plurality of pairs of orifices each for introducing a fluid into the housing, and a second manifold having a plurality of pairs of orifices each for introducing a fluid into the housing;

b) introducing food product into a heated liquid heat transfer medium within the housing of the blancher through the inlet;

c) discharging a fluid through each one of the plurality of pairs of orifices into the heat transfer medium;

d) heating the food product in the perforate food product-receiving chamber using the heat transfer medium;

e) urging the food product in the perforate food product-receiving chamber toward the outlet by rotating the food product transport mechanism; and

f) removing the food product from the perforate food product-receiving chamber through the outlet;

wherein each manifold is 1) oriented in a lengthwise direction relative to the food product receiving chamber with each one of the plurality of the orifices of each manifold each directing a separate flow of fluid toward and into the perforate food product receiving chamber, and 2) located outwardly of a lengthwise-extending generally vertical centerline of the blancher with each one of the manifold orifices directing fluid flow into an exiting quadrant thereof defined from where the rotating food product transport mechanism emerges from the heat transfer medium to adjacent the centerline but not passing to or beyond the centerline; and

wherein a liquid is discharged from the orifices of one of the manifolds into heat transfer medium located in both the exiting quadrant and the perforate food product-receiving chamber and a gaseous or vaporous fluid is discharged from the orifices of the other one of the manifolds into heat transfer medium located in both the exiting quadrant and the perforate food product-receiving chamber.

45. A method of heating a food product comprising:

a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet and comprises a liquid heat transfer medium holding tank, a helical auger rotary food product transport mechanism

30

disposed in the food product-receiving chamber for urging the food product toward the food product outlet, a first manifold having a plurality of pairs of orifices each for introducing a fluid into the liquid heat transfer medium in the tank, and a second manifold having a plurality of pairs of orifices each for introducing a fluid into the liquid heat transfer medium in the tank;

b) introducing food product into a liquid heat transfer medium within the tank of the blancher by introducing the food product through the inlet into the perforate food product-receiving chamber;

c) discharging a fluid through each one of the plurality of pairs of orifices into the heat transfer medium;

d) heating the food product in the food product-receiving chamber by heat transfer from the liquid heat transfer medium to the food product;

e) urging the food product in the food product-receiving chamber toward the outlet by rotating the helical auger rotary food product transport mechanism; and

f) removing the food product from the food product-receiving chamber through the outlet;

wherein in step c) the fluid is a liquid that is discharged through the orifices of the first and second manifolds at a flow rate of at least 20 gallons per minute per foot of manifold length; and

wherein each manifold is 1) oriented in a lengthwise direction relative to the food product receiving chamber with its orifices directing flow of liquid heat transfer medium toward the perforate food product-receiving chamber and 2) located outwardly of a lengthwise-extending generally vertical centerline of the blancher with each one of the orifices directing fluid flow into an exiting quadrant of the tank defined from where the helical auger rotating food product transport mechanism emerges from the liquid heat transfer medium in the tank to adjacent the centerline but not passing to or beyond the centerline.

46. The method of claim 45 wherein in step c) the fluid is a gas that is discharged through each one of the orifices of the other one of the manifolds at a flow rate of at least 10 standard cubic feet per minute into the exiting quadrant.

47. A method of heating a food product comprising:

a) providing a blancher including a perforate food product-receiving chamber disposed in a tank of a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging food product received in the food product-receiving chamber toward the food product outlet, and a manifold having a plurality of pairs of orifices each for introducing a fluid into a liquid heat transfer medium in the tank;

b) introducing food product into the food product-receiving chamber through the inlet and into liquid heat transfer medium received in the tank extending into the food product-receiving chamber;

c) discharging a fluid through each one of the plurality of pairs of orifices into the liquid heat transfer medium;

d) heating the food product in the food product-receiving chamber;

e) urging the food product in the food product-receiving chamber toward the outlet; and

f) removing the food product from the food product-receiving chamber through the outlet;



31

wherein in step c) the fluid is a liquid that is discharged through each one of the orifices at a flow rate of at least 20 gallons per minute per foot of manifold length;

wherein the manifold is 1) oriented in a lengthwise direction relative to the food product receiving chamber with its orifices directing flow of liquid heat transfer medium toward the food product receiving chamber and 2) located outwardly of a lengthwise-extending generally vertical blancher bisecting centerline of the blancher such that each one of the manifold orifices direct fluid flow into an exiting quadrant thereof defined from where the rotating food product transport mechanism emerges from the heat transfer medium to adjacent the centerline but not passing to or beyond the centerline; and

wherein at least four thousand five hundred pounds of food product per hour is removed in step f).

48. A method of heating a food product comprising:

a) providing a blancher including a generally cylindrical perforate food product-receiving drum disposed in a housing that comprises a tank and comprises a food product inlet and a food product outlet, a rotary auger disposed in the food product receiving drum for urging food product received in the perforate food product-receiving drum toward the food product outlet, and a manifold comprising a plurality of pairs of outwardly projecting orifices each for introducing a fluid into an aqueous heat transfer medium received in the tank;

b) introducing a plurality of pairs of pieces of food product into an aqueous heat transfer medium received in the tank and disposed in the perforate food product-receiving drum via the inlet;

c) discharging a fluid through each one of the plurality of pairs of orifices of the manifold into the aqueous heat transfer medium;

d) heating the plurality of pairs of pieces of food product in the perforate food product-receiving drum via heat transfer from the aqueous heat transfer medium having been heated to a temperature of at least 120° Fahrenheit;

e) urging the plurality of pairs of pieces of food product in the perforate food product-receiving drum toward the outlet by rotation of the rotary auger; and

f) removing the plurality of pairs of pieces of food product from the perforate food product-receiving drum through the outlet;

wherein in step c) the fluid that is discharged through each one of the orifices comprises an aqueous liquid that is discharged at a flow rate and at a pressure;

wherein the manifold is 1) oriented in a lengthwise direction relative to the food product receiving chamber with the orifices of the manifold directing flow of fluid toward the perforate food product-receiving drum and 2) located outwardly of a lengthwise-extending centerline of the blancher with each one of the orifices directing fluid flow into an exiting quadrant thereof defined from where the rotating rotary auger emerges from the heat transfer medium to adjacent the centerline but not passing to or beyond the centerline;

wherein there is at least eight inches of depth of pieces of food product in the perforate food product-receiving drum; and

wherein the manifold extends substantially the length of the tank.

32

49. A method of heating a food product comprising:

a) providing a blancher including a perforate food product-receiving chamber disposed in a tank of a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging food product received in the food product-receiving chamber toward the food product outlet, and a manifold having a plurality of pairs of orifices each for introducing a fluid into a liquid heat transfer medium in the tank;

b) introducing food product into the food product-receiving chamber through the inlet and into liquid heat transfer medium received in the tank extending into the food product-receiving chamber;

c) discharging a fluid through each one of the plurality of pairs of orifices into the heat transfer medium;

d) heating the food product in the food product-receiving chamber;

e) urging the food product in the food product-receiving chamber toward the outlet; and

f) removing the food product from the food product-receiving chamber through the outlet;

wherein in step c) the fluid is a liquid that is discharged through each one of the orifices at a flow rate of at least 20 gallons per minute per foot of manifold length;

wherein the manifold is 1) oriented in a lengthwise direction relative to the food product receiving chamber with its orifices directing flow of liquid heat transfer medium toward the food product-receiving chamber and 2) located outwardly of a lengthwise-extending generally vertical blancher bisecting centerline of the blancher such that each one of the manifold orifices direct fluid flow into an exiting quadrant thereof defined from where the rotating food product transport mechanism emerges from the heat transfer medium to adjacent the centerline but not passing to or beyond the centerline; and

wherein at least eight thousand pounds of food product per hour is removed in step f).

50. A method of heating a food product comprising:

a) providing a blancher including a perforate food product-receiving chamber disposed in a tank of a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging food product inside the food product-receiving chamber toward the food product outlet, a first manifold having a plurality of pairs of orifices each for introducing a fluid into the tank and the food product receiving chamber, and a second manifold having a plurality of pairs of orifices each for introducing a fluid into the tank and the food product receiving chamber;

b) introducing food product into the food product-receiving chamber through the inlet and into a liquid heat transfer medium received in the tank and extending into the food product-receiving chamber;

c) discharging a fluid through each one of the plurality of pairs of orifices into the heat transfer medium;

d) heating the food product in the food product-receiving chamber;

e) urging the food product in the food product-receiving chamber toward the outlet; and

f) removing the food product from the food product-receiving chamber through the outlet;



33

wherein in step c) the fluid is a liquid that is discharged through each one of the orifices of at least one of the manifolds at a flow rate of at least 20 gallons per minute per foot of manifold length;

wherein each manifold is 1) oriented in a lengthwise direction relative to the food product receiving chamber with its orifices directing flow of liquid heat transfer medium toward the food product receiving chamber and 2) located outwardly of a lengthwise-extending centerline of the blancher with each one of the orifices directing fluid flow into an exiting quadrant thereof defined from where the rotating food product transport mechanism emerges from the heat transfer medium to adjacent the centerline but not passing beyond the centerline; and

wherein at least eight thousand pounds of food product having a density of at least 55 lb/ft<sup>3</sup> is removed per hour in step f).

51. A method of heating a food product comprising:

- a) providing a blancher including a perforate food product-receiving chamber disposed in a housing that has a food product inlet and a food product outlet and that is capable of holding heated water as a heat transfer medium, a rotary food product transport mechanism disposed in the food product-receiving chamber for urging food product received in the food product-receiving chamber toward the food product outlet, a first manifold having a plurality of orifices each for introducing a fluid into heat transfer medium in the housing, and a second manifold having a plurality of orifices each for introducing a fluid into heat transfer medium in the housing, and a recirculation system comprising an intake through which fluid from within the blancher can be withdrawn and delivered to at least one of the first and second manifolds, and a pump in fluid-flow communication with the intake for drawing fluid from within the blancher and communicating it to one of the first and second manifolds;
- b) introducing food product into a heat transfer medium within the housing through the inlet;
- c) withdrawing fluid from within the housing and delivering it to one of the first and second manifolds;
- d) discharging fluid through each one of the plurality of orifices of the first and second manifolds into the heat transfer medium;
- e) heating the food product in the food product-receiving chamber via heat transfer from the heat transfer medium;
- f) urging the food product in the food product-receiving chamber toward the outlet; and
- g) removing the food product from the food product-receiving chamber through the outlet;

wherein in step d) the fluid that is discharged through each one of the orifices of at least one of the manifolds comprises water; and

34

wherein the first and second manifolds are spaced apart and have each one of the plurality of orifices of each manifold oriented to direct fluid discharged from each orifice into an exiting quadrant in the housing toward the food product-receiving chamber impinging against food product disposed in heat transfer medium in the exiting quadrant.

52. A method of heating a food product comprising:

- a) providing a blancher including a perforate food product-receiving chamber disposed in a tank of a housing that has a food product inlet and a food product outlet, a rotary food product transport mechanism disposed in the food product receiving chamber for urging food product inside the food product-receiving chamber toward the food product outlet, a first manifold having a plurality of pairs of orifices each for introducing a fluid into the tank and the food product-receiving chamber, and a second manifold having a plurality of pairs of orifices each for introducing a fluid into the tank and the food product-receiving chamber;
- b) introducing food product into the food product-receiving chamber through the inlet and into a liquid heat transfer medium received in the tank and extending into the food product-receiving chamber;
- c) discharging a fluid through each one of the plurality of pairs of orifices into the heat transfer medium;
- d) heating the food product in the food product-receiving chamber;
- e) urging the food product in the food product-receiving chamber toward the outlet; and
- f) removing the food product from the food product-receiving chamber through the outlet;

wherein in step c) the fluid is a liquid that is discharged through each one of the orifices of at least one of the manifolds at a flow rate of at least 20 gallons per minute per foot of manifold length;

wherein each manifold is 1) oriented in a lengthwise direction relative to the food product receiving chamber with its orifices directing flow of liquid heat transfer medium toward the food product receiving chamber and 2) located outwardly of a lengthwise-extending centerline of the blancher with each one of the orifices directing fluid flow into an exiting quadrant thereof defined from where the rotating food product transport mechanism emerges from the heat transfer medium to adjacent the centerline but not passing to or beyond the centerline; and

wherein at least eight inches of food product depth is heated in step d) and at least eight thousand pounds of food product per hour is removed in step f).

\* \* \* \* \*



UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : RE 40,232 E  
APPLICATION NO. : 10/791694  
DATED : April 8, 2008  
INVENTOR(S) : Zittel et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Col. 19, Claim 1, line 63: the word “medium” should be --mechanism--:

...rotation of the rotary food product transport mechanism...

Col. 22, Claim 14, line 14: the word “drawn” should be removed:


...~~drawn~~ drawn portion of the gaseous atmosphere...

Col. 22, Claim 16, line 24: the words “from the” should be removed:

...charged ~~from the~~ from the orifices of the other one of the...

Signed and Sealed this

Seventh Day of October, 2008

A handwritten signature in black ink, reading "Jon W. Dudas". The signature is stylized, with a large, looped initial "J" and a cursive "Dudas".

JON W. DUDAS  
*Director of the United States Patent and Trademark Office*