

US00RE40363E

(19) **United States**
(12) **Reissued Patent**
Grim et al.

(10) **Patent Number: US RE40,363 E**
(45) **Date of Reissued Patent: Jun. 10, 2008**

(54) **FOOTGEAR WITH PRESSURE RELIEF ZONES**

(75) Inventors: **Tracy E. Grim**, Thousand Oaks, CA (US); **Kevin O'Donnell**, Santa Barbara, CA (US); **Eric G. Montag**, Van Nuys, CA (US)

(73) Assignee: **Ossur hf**, Reykjavik (IS)

(21) Appl. No.: **09/592,462**

(22) PCT Filed: **Feb. 16, 1994**

(86) PCT No.: **PCT/US94/01797**

§ 371 (c)(1),
(2), (4) Date: **Jan. 6, 1995**

(87) PCT Pub. No.: **WO94/18863**

PCT Pub. Date: **Sep. 1, 1994**

(Under 37 CFR 1.47)

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **5,761,834**
Issued: **Jun. 9, 1998**
Appl. No.: **08/360,798**
Filed: **Jan. 6, 1995**

U.S. Applications:

(63) Continuation-in-part of application No. 08/017,818, filed on Feb. 16, 1993, now Pat. No. 5,329,705.

(51) **Int. Cl.**

A43B 13/38 (2006.01)
A43B 7/20 (2006.01)
A43B 7/14 (2006.01)
A61F 5/00 (2006.01)
A61F 5/37 (2006.01)

(52) **U.S. Cl.** **36/88; 36/93; 36/95; 36/110**

(58) **Field of Classification Search** **36/43, 36/44, 71, 88, 95, 93, 110, 140, 155, 141; 602/23**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

975,576 A	*	11/1910	Sexton	36/140
2,868,191 A	*	1/1959	Juhasz	601/136
2,885,797 A	*	5/1959	Chrencik	36/91
2,909,854 A	*	10/1959	Edelstein	36/140
2,913,837 A	*	11/1959	Geuder	36/71
2,979,836 A	*	4/1961	Scholl	36/44
3,548,420 A	*	12/1970	Spence	36/71
3,859,740 A	*	1/1975	Kemp	36/71
4,095,353 A	*	6/1978	Foldes	36/11.5
4,100,686 A	*	7/1978	Sparlato et al.	36/29
4,408,402 A	*	10/1983	Looney	36/43
4,571,853 A	*	2/1986	Medrano	36/29

(Continued)

FOREIGN PATENT DOCUMENTS

FR	2681516	*	3/1993
WO	93/13685	*	7/1993


Primary Examiner—Marie Patterson

(74) *Attorney, Agent, or Firm*—Bacon & Thomas, PLLC

(57) **ABSTRACT**

Footgear with an inner sole (66) having a grid of removable resilient elements to permit removal of selected elements (68) to provide relief to ulcerated or injured areas of the foot. An air bladder (64) may underlie sole (66), preferably with additional cushioning material (40) within the air bladder. A walker (12) with a soft support (20) may be provided with the inner sole within the support. Some of the removal resilient elements may have a higher density or height than others. The footgear may include an adhesively-backed resilient pad (212) to provide additional support to a region. The footgear may include means for reducing shear stress on a bottom surface of the foot. An edema patch (240) may be provided for covering an open space (248) left after a user has removed a removable section from the grid. The edema patch applies pressure to the afflicted zone of the foot (250) preventing fluids from building up.

41 Claims, 11 Drawing Sheets



US RE40,363 E

Page 2

U.S. PATENT DOCUMENTS

4,598,484	A	*	7/1986	Ma	36/3	R	4,869,001	A	*	9/1989	Brown	
4,608,768	A	*	9/1986	Cavanagh				4,893,418	A	*	1/1990	Ogden	
4,633,598	A	*	1/1987	Moronaga et al.	36/44		5,078,128	A	*	1/1992	Grim et al. 602/23
4,689,898	A	*	9/1987	Fahey	36/43		5,154,682	A	*	10/1992	Kellerman 36/44
4,727,661	A	*	3/1988	Kuhn	36/100		5,197,942	A	*	3/1993	Brady 602/23
4,793,078	A	*	12/1988	Andrews	36/43		5,329,705	A	*	7/1994	Grim et al. 36/88

* cited by examiner




FIG. 1




FIG. 4





FIG. 2






FIG. 5




FIG. 6

FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 12







FIG. 13




FIG. 14




FIG. 23





FIG. 17




FIG. 19

FIG. 20





FIG. 16




FIG. 18




FIG. 21




FIG. 22




FIG. 24

FIG. 25





FIG. 27



FOOTGEAR WITH PRESSURE RELIEF ZONES

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

RELATED PATENT APPLICATIONS

This application is a continuation-in-part of U.S. patent application Ser. No. 08/017,818, which was filed Feb. 16, 1993 now U.S. Pat. No. 5,329,705. This invention is related to that disclosed in U.S. patent application Ser. No. 07/965,750, filed Oct. 23, 1992, (Docket No. 88-182), entitled "Orthopaedic Support and Method for Providing Semi-Permanent Relief Zones," assigned to the assignee of this invention.

FIELD OF THE INVENTION

This invention relates to footgear having orthopaedic soles providing pressure relief areas for the feet.

BACKGROUND OF THE INVENTION

The problems solved by the present invention were discussed at length in the prior patent application cited above, and the background section of that application will therefore be repeated here.

Support pads are used in a wide variety of applications to provide cushioned support to an injured or otherwise sensitive bodily appendage. Such pads have the dual purpose of (1) providing orthopaedic support to the appendage and (2) protecting the appendage from further injury or damage resulting from contact with a foreign object or hard surface.

One common use of a support pad is as a cushioned foot sole in specialized footwear such as soft boots or patient walkers. These devices generally employ some type of soft, resilient material, such as foam, to provide cushioned support of a sensitive or damaged foot.

A particular problem arises when it becomes necessary to provide uneven support across the outer surface of an appendage. For example, an ulcerated appendage, often found in diabetic patients, requires pressure relief to the ulcerated area to allow healing. In this instance, it is desirable to have a pad which will apply cushioned support to the appendage, while refraining from supporting the afflicted area. For diabetic patients, the feet are commonly beset with such ulcerations, and it is therefore desirable to provide a cushioned support sole for a shoe or walker which is capable of providing specific zones of pressure relief.

Other approaches have addressed the problem of providing cushioned foot support. U.S. Pat. No. 2,598,217 (Bronson), issued May 27, 1952, discloses as invalid's boot with a thick insole. However, these approaches require replacement of the sole for each new patient, or for each new area of the original patient's foot which must be relieved.

Andrews U.S. Pat. No. 4,793,078 discloses a footwear insole with a molded arch support. The insole has either three indentations or a single banana-shaped indentation arranged in an arc behind the toes, and another indentation at the heel. A user may adhesively fix pad inserts into one or more of the indentations to provide support to the foot. The user omits inserts from selected indentations to relieve pressure on certain area of the foot.

Unfortunately, a number of problems arise when diabetes patients, who are prone to severe foot ulcers, attempt to use

the Andrews device. Before discussing these deficiencies, however, it is useful to review the foot problem that many diabetes patients face. It is well known that diabetes patients are prone to foot ulcers. In fact, lesions of the foot are responsible for more than one-fifth of the hospitalizations of diabetic patients. More than 40% of the lower extremity amputations in the United States are performed on diabetic patients who have poor circulation in the lower limb. With reduced sensation in the foot, the patient is unlikely to feel discomfort when the skin is subject to shear forces during walking, and consequently he or she does not properly adjust his or her gait. Lesions are formed or are made worse.

Diabetes patients also experience other extreme difficulties with their feet. Diabetic patients often undergo an unfortunate evolutionary pattern of anatomical deterioration. Initially, the foot will have a normal appearance and will only have vascular or neuro-vascular deficiencies. However, the bone structure can quickly deteriorate. Charcot joints can form, and the foot becomes drastically deformed. From then on, the areas of the foot that can bear weight are abnormal, their locations are unpredictable, and custom foot accommodations will be required for the remainder of the person's ambulatory life.

The Andrews device does little to overcome these problems. Foot ulcers and bone deterioration can occur anywhere on the foot, yet Andrews provides only a few pads in very specific locations. The Andrews fixed-location pad arrangement cannot provide pressure relief to damaged areas of the foot that are located anywhere except the four specific pad locations. This makes Andrews inadequate for the majority of diabetes patients with damaged feet.

An additional drawback of the Andrews pad is that it lacks means to reduce shear forces on the skin of the foot that arise as the patient walks along. Such shear forces can further damage existing ulcers, or create new ulcers. This is particularly true where the patient walks for any distance.

Other deficiencies of Andrews are apparent. As shown in Andrews FIG. 1, the Andrews sole is limited to either a left or right foot-only sole. The same Andrews sole cannot be used on either foot because sole support 16 is built into the shoe.

U.S. Pat. No. 3,760,056 (Rudy), teaches a method for conforming a ski boot to the foot of the wearer by heating an inflatable bladder, distending it to the desired shape, and then cooling and deflating the bladder. The bladder can be subsequently be re-inflated to fit the wearer's foot. This method requires a mechanism for heating, which may be inconvenient or impractical when applied to a comfortable sole. In the method disclosed, the inflatable bladder was placed over the foot to contact opposing sides, rather than underneath it as a support. Moreover, the elastomeric materials described in the Rudy patent typically may not provide the requisite comfort and cushioning generally required in a healing device.

A further method of providing support to an injured foot is disclosed in U.S. Pat. No. 5,078,128 (Grim, et al.) in which a removable leg walker includes a plurality of inflatable and adjustable bladder members in order to provide variable amounts of pressure to an affected limb as leg swelling increases or decreases. However, the bladder members of the Grim device do not retain their shape except as restrained by the surface of the appendage itself and thus do not provide the desired semi-permanent areas of relief to an injured appendage.

Incidentally, the above-cited U.S. patent application Ser. No. 07/965,750 discloses arrangements which provide relief

3

using a pad of particulate material which is vacuum formed to the desired configuration.

From an overall standpoint, a principal object of the present invention is to provide a comfortable cushioned sole which may be conveniently modified to provide pressure relief to specific areas of the wearer's foot.

Another important object of the invention is to furnish a device which may be reused to provide relief to different areas of the patient's foot, or which may be used by other patients.

A further object is to provide a method for comforting a cushioned sole to the foot of a particular wearer, and of later reforming or returning the sole to its original shape.

SUMMARY OF THE INVENTION

In accordance with one illustrative embodiment of the invention, a walker frame, including an outer sole and side struts may be provided with an air bladder mounted above the outer sole, and a special inner sole mounted above the bladder and made up of a large number of separate resilient sections removably secured to a flexible sheet to form a substantially flat surface for engagement by the foot. In areas where the foot is ulcerated or otherwise injured, sections of the inner sole are removed to provide pressure relief.

In accordance with a broader aspect of the invention, footgear or footwear generally may be provided with an inner sole having mobile sections of the type described in the preceding paragraph.

With regard to the walker embodiment, a flexible soft goods-type support may be provided, to enclose the patient's foot, and having arrangements for securing to the walker frame. The bladder may be mounted between the outer sole and support, layered within the soft goods support, or preferably above the soft goods support. A dorsum strap may be secured to the support or the inner sole and extend around the ankle and instep, to hold the foot in place on the inner sole.

Additional features of the invention may include the following:

1. The removable sections may be held in place by pressure sensitive adhesive or preferably hook and loop type securing material of the Velcro type of permit removal and replacement of the sections.
2. The removable sections may be in a grid like configuration, using hexagonal, rectangular or square patterns.
3. The inner sole may have multiple layers, with the layer closest to the foot being softer and more resilient than other layers.
4. The inner sole may extend to the rear and upward to cushion the rear of the heel.
5. The bladder may be filled with fluid, air, other gas, liquid, or gel material.
6. The bladder may contain additional resilient material such as a layer of foam, for extra cushioning of the foot.
7. The removable sections can be arranged on a substantially indentation-free surface.
8. The removable sections may cover most or substantially all of the inner sole, or may cover selected important areas such as the heel and ball of the feet areas.
9. The removable sections may have various densities so that a user may arrange denser sections to provide additional cushioning in selected areas of the inner sole.

4

10. The removable sections may have various heights so that a user may arrange the sections to custom-fit the foot.

11. An edema patch may be provided for covering an open space left after a user has removed one or more mobile sections from the grid and for applying pressure to the afflicted zone of the foot, thereby preventing fluids from building up in the afflicted zone of the foot.

Other objects, features and advantages of the invention will become apparent from the following detailed description and from the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a walker of the type to which the present invention is applicable;

FIG. 2 is a partial exploded view of the walker of FIG. 1;

FIG. 3 is a partial cross-sectional view taken along lines 3-3 of FIG. 1;

FIG. 4 is a cross-sectional view taken along lines 4-4 of FIG. 1;

FIG. 5 is a top view of an alternative inner sole configuration;

FIG. 6 is a schematic showing of a walker system implementing the principles of the invention;

FIG. 7 is a side view of a support pad which has dense removable sections arranged underneath the arch of a user's foot;

FIG. 8 is a side view of a support pad which has dense removable sections arranged around a pressure relief area from which sections have been removed;

FIG. 9 is a side view of a support pad which has dense removable sections arranged in the heel area to absorb impact as a user steps down on the pad;

FIG. 10 is a side view of a support pad which has dense removable sections arranged in the ball region of the foot to absorb the pressure of stepping forward;

FIG. 11 is a top view showing a support pad having high density removable sections in the toe area, and less dense removable sections in the mid-foot region;

FIG. 12 is side view of a pad having taller removable members arranged underneath the arch of a foot;

FIG. 13 is a side view showing that the members of the pad of FIG. 10 custom-fit the contour of the foot when the user is standing on the pad;

FIG. 14 is a side view of a pad having taller members arranged around a pressure relief zone from which removable members have been removed;

FIG. 15 is a top view showing an additional pad applied on top of removable members;

FIG. 16 is a sectional view of the support pad of FIG. 15 taken along line 16-16 of FIG. 15 showing that the additional pad has an aperture which is positioned over a pressure relief zone from which removable members have been removed;

FIG. 17 is a side view of a support pad showing that fluids can become trapped in an injured area of the foot that is positioned over a pressure relief zone;

FIG. 18 is a perspective view of an edema patch having a stretch layer and an adhesive layer;

FIG. 19 is a side view of a support pad in which an edema patch has been applied over a relief zone area from which removable sections have been removed;

FIG. 20 is a top view of a support pad in which an edema patch has been applied over a relief zone area from which removable sections have been removed;

5

FIG. 21 is a perspective view of an edema patch having a layer of stretch material, a fluid-impermeable film, and an adhesive layer;

FIG. 22 is a perspective view of an edema patch having a fluid-impermeable film and an adhesive layer;

FIG. 23 is a side view of a support pad having an edema patch covering a pressure relief zone with the edema patch rounding the top edges of the pressure relief zone;

FIG. 24 is a partial exploded view of an alternative embodiment of a walker of the type to which the present invention applies;

FIG. 25 is a partial cross-sectional view of the alternative embodiment of FIG. 24 taken along lines 3-3 of FIG. 1;

FIG. 26 is a perspective view of a pad having inflated pneumatic members; and

FIG. 27 is a perspective view of the pad of FIG. 26, with individual members having been deflated to provide pressure relief in a specific area of the pad.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring more particularly to the drawings, FIG. 1 shows a walker 12 including a frame made up of an outer sole assembly 14 and two side struts 16 secured to the sole, and extending up on either side of the lower leg of the patient 18. Within the frame 14, 16, is a soft goods type support member 20 for enclosing the lower leg, ankle and most of the foot of the patient or user. As best shown in FIG. 4, the soft goods type body member 20 includes outer cloth material 22 and 24 separated by two layers of foam 36 and 37, which may be either foam rubber or foamed urethane, by way of examples. The soft goods type body member 20 may be held in position within the frame 14, 16, by pads of hook and loop type material on the inner surface of the struts 16, and by the straps 28 extending around the struts 16, through the D-rings 30 and then being folded back on the other portions of the straps, and held in adjustable positions by mating Velcro type hoop and loop areas on the surfaces of the straps. The straps 32 and 34 across the instep and the forward portion of the assembly, operate in similar manners to hold the foot and the soft goods type support member 20 in position within the frame 14, 16.

Incidentally, with regard to the detailed construction of the walker frame, reference is made to U.S. Pat. No. 5,078,128, granted Jan. 7, 1992, and assigned to the assignee of the present invention.

One of the straps 28 is also visible in FIG. 4 as is one of the struts 16. Between the body member 20 and the strut 16, and between the strut 16 and the strap 28, is hook and loop type material, so that various members are secured in place relative to one another.

Within the side walls of the soft goods body member 20, may be air bladders such as that shown at reference numeral 38 in FIG. 4 and preferably containing a layer of open cell foam 40. The bladder 38 may be located between one layer of foam 36 and fabric 22 and the second layer of foam 37 and fabric 24. This arrangement provides additional cushioning for the lower leg of the patient, particularly in the vicinity of the struts 16.

FIG. 2 is a partial exploded view of the walker of FIG. 1, with reference numerals employed in FIG. 1 being carried over to FIG. 2. Shown in FIG. 2 is the elongated pad 44 of hook type material. The outer cloth covering of the soft goods type body member 20 is of cloth of one of the well known types such as brushed nylon material which will

6

receive hook type securing pads, such as that sold under the trademark "Velcro" so that the front upper portion of the soft goods type support member 20 may be held in the closed position by the engagement of the pad 44 with the outer surface of the mating portion 45 of the support member 20. Similarly, the pad 46 on the inner surface of the front flap 48 of the soft goods support member 20 serves to engage the mating flat 50 on its outer surface, and holds the front portion of the soft goods member around the upper portion of the patient's foot.

The footwear of the present invention is provided with an inner sole assembly 52 which is preferably mounted within the soft goods support member 20 by a layer of hook type securing material 54 which is on the lower surface of the assembly 52, and which engages the inner surface of the soft goods type support member 20 in the area 56 as shown in FIG. 2. The rear portion 58 of the inner sole assembly 56 may extend up behind the heel of the patient to cushion this area of the foot; and the straps 60 and 62, formed of soft material and held together by hook and loop type securing arrangements, served to hold the patient's foot back into proper engagement with the inner sole assembly 52.

Inner sole assembly 52 includes a lower air bladder 64 which may contain a layer of foam material, and an upper resilient layer 66 constituting separate removable sections, also known as individually mobile resilient sections, which together form a normally substantially smooth surface for engagement by the foot. These sections are individually removable, as indicated by the sections 68 which are shown removed from the space 70 where they would normally be located to complete the smooth upper surface of the inner sole assembly 52. The concept, as mentioned in the introductory portion of the present specification, is to provide relief to ulcerated or injured portions of the foot, whereby the foot is supported on the adjacent resilient material, with relief provided in the areas where the removable sections have been taken away.

The top surface of bladder 64 may be substantially indentation-free so that the resilient sections may be removed from any location on the grid. The user is thereby not limited to removing insets only from indentations located in a limited number of positions on the side, such as in the Andrews patent discussed in the Background section. Instead, a user of the present invention may remove sections from precisely the desired location.

Note that the individual resilient sections such as the section 68, have hook or loop type securing material 72 on their lower surfaces, and the upper surface of the bladder 64 has mating hook and loop type material for removably securing sections such as section 68 in place to provide a relatively smooth upper surface. Thus, the group of sections 68 may be reinserted and re-secured into the opening 70, and other sections removed, to accommodate different needs, or the problems of another patient. Instead of using hook and loop type securing material as shown in FIG. 2, the lower surface of sections such as the sections 68 may be provided with pressure sensitive adhesive, thereby providing the removable and replaceable functions as discussed hereinabove.

FIG. 3 is a somewhat schematic cross-sectional view taken along line 3-3 of FIG. 1. More specifically, the view of FIG. 3 includes the soft goods type support member 20 which is here shown as a single layer for simplicity, but which, in reality, would be two layers of cloth and two foam layers forming a central foam core, as discussed in connection with FIG. 4. In addition, FIG. 3 shows the outer sole 14

including the lower tread portion **78**, which would normally be somewhat rough for traction, the flap **48**, the strap **62**, the bladder **64**, and the resilient inner sole **66**.

Concerning the sole **14**, in addition to the outer tread portion **78**, it may include the upper and lower high strength plastic sheet members **82** and **84** which are interconnected by appropriate ribs **85**. At the rear of the sole **14** is a cantilevered area in which resilient foam material **86** is located, so that controlled flexing of the rear heel end **88** of the lower plastic sheet member **84** provides increased cushioning for the patient, against shock to which he or she might otherwise be subjected.

Regarding the bladder assembly **64**, it may include a sealed bladder made of thin sheet urethane **92** covered with cloth material **94**, and containing an open cell foam layer **96** which may be bonded to the upper or lower surface of the bladder. Between the upper surface of the bladder assembly **64**, and the lower surface of the inner sole **66** is a suitable material **98**, for removably securing the inner sole **66** to the upper surface of the bladder **64**. Material **98** may be hook and loop type material, or pressure sensitive adhesive, as noted hereinabove. The inner sole **66** may be formed of three layers **102**, **104** and **106**, which are bonded together. These three layers **102**, **104** and **106** may be of progressively different softness and resiliency, with the softest and most resilient layer being the layer **102** closest to the foot, with layers **104** and **106** being progressively less resilient and providing somewhat greater support.

It should be noted that bladder **64** is entirely optional. Inner sole assembly **52** may alternatively include a flexible pad rather than bladder **64**. The flexible pad may be made of a material such as cloth with which a hook and loop type material can engage.

With regard to the construction of the outer sole assembly **14**, it may be formed as described hereinabove in the cited U.S. Pat. No. 5,078,128, or may be of any other desired configuration. The present invention is primarily directed to a configuration of the inner sole, and the precise configuration of the outer sole arrangements may be chosen from many alternatives.

FIG. 5 shows an alternative arrangement of the individual removable sections of the inner sole which is designated by the reference numeral **52'**. In addition to the continuous outer rim **112**, the sections are rectangular, or square, and have a closer spacing in the heel area **114**, and in the area **116** immediately behind the toes. The area **118** where the toes would be located, and the central area **120** below the instep, could have larger sections, as these areas are less likely to have ulcerations and require relief. It is noted in passing, however, that the hexagonal configuration as shown in FIG. 2, is the presently preferred embodiment.

Regarding FIG. 6, this is a schematic showing of a walker illustrating the principles of the invention and shows the soft goods type support **20**, the sole **14**, the bladder **64**, and the inner sole **66**. The bladder **64** may be a sealed bladder, preinflated, or may be provided with a pump **132**, and pressure relief arrangements **134**. The pump **132** may be manually actuated, mechanically actuated, or may be actuated by a walking or running action of the user. The pressure relief arrangements **134** may involve a simple adjustable spring and ball type controlled pressure relief valve, or may involve more complex pressure sensing and valve actuation arrangements controlled by the sensing of the pressure.

Regarding FIGS. 7-11, one alternate embodiment of the present invention employs separate removable resilient sections having different material densities. Some of the resil-

ient sections are lower density sections and some are higher density sections, so that a user may arrange the higher density sections to create at least one zone of additional support for a foot. The zone or zones of higher density sections serve to selectively absorb energy during portions of the walking gait.

For instance, concentrating resilient sections made of dense material in the midfoot region will help distribute force throughout the surface of the plantar pad during the gait. As with the other embodiments of the present invention, the removable resilient sections are arranged in a grid. The user removes selected resilient sections in order to create a customized pressure relief zone of desired location and dimensions.

Dense material may also be added to specific regions of the foot to absorb energy where needed, such as the heel region or the instep region. These areas may experience high stress and therefore require additional padding.

Alternatively, the midfoot region of the planar pad may be of a denser material than the heel or the forefoot region. Body weight then shifts onto the middle foot area and off of the front and heel portions of the foot. In other words, during the gait the denser material will support the midfoot region, while the heel and forefoot sink into the less dense material. It should be emphasized, however, that the less dense material must be sufficiently dense so as to prevent the foot from hitting the bottom of the pad, which is known as "bottoming out".

There are at least two other uses for resilient sections having increased density. First, dense resilient sections may be arranged around the perimeter of a pressure-relief area where resilient sections have been removed. The denser sections provide additional support, and serve to prevent the ulcerated area of the foot from bottoming out in the unsupported area.

Second, dense resilient sections may be used to prevent "compression set", which is a permanent reduction in cross-section arising from constantly stepping down on the material. A denser material is stronger and more durable, and is less likely to become permanently deformed than a less dense material. Consequently, use of resilient sections having increased density can result in increased durability and product life.

FIGS. 7-11 illustrate some of the various ways that a user or physician might arrange resilient sections of different densities on the pad. FIG. 7 illustrates an inner sole **166**, also known as a plantar pad, having removable resilient sections of different densities. A region **168** of high-density removable sections supports the arch section of foot **170**. As the user steps down on plantar pad **166**, high density region **168** reduces the load that lower density regions **172** would otherwise carry. Consequently, high density region **168** reduces pressure from ulcerated area **174** of foot **170**.

FIG. 8 illustrates an alternative distribution of high density removable sections on an inner sole or plantar pad **180**. Most of the surface area of plantar pad **180** is covered with normal density removable pads **182**. However, higher density removable pad **184** surround pressure relief area **186** where pads have been removed. These dense pads **184** provide additional support in the area immediately adjacent to ulcerated area **174**. In particular, these dense pads serve to reduce the chance that ulcerated area **174** will "bottom out" or displace vertically below the bottom of pad **180** during walking and running, which would impact ulcerated area **174** and potentially further injure the foot.

FIG. 9 shows that dense sections **192** are arranged in a rear portion of plantar pad **190**. These dense sections **192** can

absorb shock better than normal density pads **196** and, in this instance, help compensate for the “heel strike” that occurs as the user steps down onto heel **194** of the foot **170**. It should be noted that many diabetic patients are obese, and that the heel may be subjected to significant loading while the user walks around. The arrangement of dense sections **192** of FIG. **9** reduces the risk of heel injury from such significant heel loading.

FIG. **10** shows that dense sections **169** may be arranged in a front portion of a plantar pad **167** in the area of the ball and toes of foot **170**. This arrangement of dense sections **169** provides support during the “push-off” part of the walk when the person pushes hard against the forward portion of the foot to move the body forward. Dense sections **169** absorb this “push-off” pressure, and protect the ball and toes **179** of foot **170** from bottoming out against a support layer below plantar pad **167**.

FIG. **11** illustrates a plantar pad **210** having three different densities of removable resilient pads. High density pads **212** are arranged in the heel area of the plantar pad. These pads compensate for the significant shock loading of heel strike. Medium density pads **214** are arranged to correspond to the toe and ball areas of the foot to provide support during pushoff loading. Lower density pads **216** support the rest of the foot.

Another alternative embodiment uses some separate resilient sections that are taller than other sections. A user may arrange the taller sections to custom fit a foot. FIG. **12** shows that tall removable sections **200** have been arranged underneath the arch of a user’s foot **202**. Regular height sections **204** support the other areas of the foot. When the user steps onto the pad **206** as in FIG. **13**, the taller sections **200** fully support the arch of the foot. In addition, the taller sections **200** carry more of the user’s body weight than would regular-height sections.

Taller sections can be arranged around an area of pressure relief, as in FIG. **14**. This region of taller sections **208** serves two purposes. First, the taller sections raise the foot in the region of the pressure relief area, thereby reducing the chances that the injured area will “bottom out” against the bottom of the pad when the user steps down on the foot. Second, the taller sections carry more weight around the pressure relief area than would shorter sections. Consequently, the region of tall sections **208** of FIG. **14** provides greater pressure relief to the injured area. It should be noted that the taller sections **200** in FIG. **12** may be rearranged to form the configuration of the pad in FIG. **14**.

As noted above, a heavy patient or a patient with a particularly large ulcer may “bottom out” the afflicted area against the bottom of the pad during walking. To prevent “bottoming out”, the user may apply an additional resilient pad having an aperture and an adhesively-backed lower surface. The lower surface adheres to the upper surface of resilient sections surrounding a pressure relief zone. The additional pad provides extra support around the pressure relief area.

FIG. **15** shows an additional pad **212** applied on top of resilient sections **214**. Pad **212** has an aperture **216** to provide pressure relief to an ulcer. FIG. **16** shows that aperture **216** is positioned immediately adjacent to pressure relief zone **218**, from which removable sections have been removed to create an area of low or no pressure. The bottom surface of additional pad **212** is provided with an adhesive layer **220** to attach the pad to the top surface of resilient sections **214**. Any of a variety of commercial adhesives may be used, such as the 921 High Tech Adhesive manufactured by the 3M Company of St. Paul, Minn.

The additional pad may have any of a variety of sizes and shapes to accommodate a variety of different ulcer sizes and user weights. The pad may be made of a single-density material, or may have a multi-density layered arrangement consisting of a supple top layer for comfort and a dense lower layer to support body weight. The pad may also be cut into a grid pattern in order to reduce the shear forces on the foot during walking.

Furthermore, the user may choose to apply the additional pad to the plantar surface without removing any removable sections from the pad. For a particularly heavy user, leaving the removable sections in place provides padding beneath the injured area of the foot to further prevent the “bottoming out” that might otherwise occur as the user transfers weight to the injured area of the foot.

With regard to an alternative feature of the present invention, a problem called “window edema” occurs when an area of the body under low pressure is surrounded by an area of higher pressure. Body fluids tend to build up and become trapped in the area of lower pressure. Distal parts of the body, such as the hands and feet, are particularly prone to window edema because the cardio-vascular system typically does not do a good job of retrieving fluids that are far from the heart. The trapped fluids become excellent media for bacteria to grow, thereby causing infections.

Window edema may be a problem for some users of the present invention. FIG. **17** show that fluids **226** may build up and become trapped in a pressure relief zone such as **228** under foot **230**. Since foot **230** is far from the user’s heart, the cardio-vascular system has trouble carrying away the fluids **226** that build up in relief zone **228**. As bacteria grows in fluids **226**, the user may be subject to a dangerous infection that can threaten the well-being of the foot.

In order to prevent window edema in the present invention, an edema patch may be provided in the relief area. FIG. **18** shows that an edema patch **240** may comprise a patch of stretch material **242** with an adhesive backing **244**. Stretch material **242** may be the material sold under the trademark “LYCRA” or a similar material elastic properties. Adhesive **244** may be any of a variety of commercial adhesives, such as the 921 High Tech Adhesive manufactured by the 3M Company of St. Paul, Minn.

FIGS. **19** and **20** show an edema patch **240** applied to the plantar relief pad **246** to cover the opening of relief zone **248**. The edema patch **240** adheres to a top surface of removable sections surrounding a relief zone from which a user has removed other sections, such that the edema patch covers the relief zone. Edema patch **240** applies some pressure to afflicted regions **250** of foot **230**, thereby reducing the pressure difference between the afflicted area **250** and the area immediately surrounding relief zone **248**. However, edema patch **240** generally applies less pressure to afflicted region **250** than would removable sections if inserted to fill relief zone **248**. Nevertheless, edema patch **240** applies sufficient pressure to afflicted region of the foot **250** in order to reduce the likelihood of window edema.

The edema patch may be provided with a variety of features, and may be used in ways other than that shown in FIGS. **19** and **20**. The patch may be of various sizes, shapes and stretch to accommodate particular sizes and shapes of afflicted areas. The patch may be applied to any area of the plantar pad where sections have been removed to create a pressure relief zone. If a user has created multiple pressure relief zones to accommodate multiple ulcers, the user may place an edema patch over each pressure relief zone.

As FIG. **21** shows, the edema patch may further include a fluid-impermeable film layer **256** underlying the stretch

material **242** in order to prevent fluid transmission from the foot into the area from which sections have been removed. Adhesive **244** is applied to the lower surface of film **256**. Any of a variety of materials may be selected for the underlying film, including but not limited to urethane. The film thickness may be chosen to have substantial thickness, thereby limiting its stretchability and enabling it to give substantial support to the afflicted area of the foot. Alternatively, the film may have minimal thickness, which makes the film highly stretchable but limits the support that the film can give the foot.

As an additional alternative, film **256** may overlie stretch material **242**, with adhesive **244** being on the lower surface of stretch material **242**. Film **256** and stretch material **242** may be bonded by pressing the film and stretch material together under high pressure. Alternatively, they may be bonded using any of a variety of commercial adhesives. Additionally, FIG. **22** shows that the patch may comprise a film layer **256** with adhesive layer **244** without any stretch material at all.

The edema patch provides another benefit to the user. The relief zone has edges that provide a "window" around the afflicted area. The foot may be subject to increased pressure at these edges, which physicians must often scythe to prevent skin irritation. However, as FIG. **23** shows, when an edema patch **240** is applied to the plantar pad to cover the pressure relief zone, the pad covers and smooths the edges of relief zone **248**. There is then no need for a physician to scythe the edges.

FIG. **24** and **25** illustrate an additional alternative embodiment of a walker that incorporates the present invention. FIG. **24** is a partial exploded view of an alternative embodiment of a walker of the type illustrated in FIG. **1**. A feature of this embodiment is the inner booty **357**, which holds the foot firmly in place within the walker.

FIG. **24** shows a walker including a frame made up of an outer sole assembly **314** and two side struts **316** secured to the sole, and extending up on either side of the lower leg of a patient. Within the frame **314**, **316**, is a soft goods type support member **320** for enclosing the lower leg, ankle and most of the foot of the patient or user. The soft goods member, which is of the type described previously in conjunction with FIG. **4**, includes outer layers of cloth material separated by two layers of foam and bladders **338**.

The soft goods body member **320** may be held in position within the frame **314**, **316**, by pads of hook and loop type material on the inner surface of the struts **316**. Additionally, straps such as **28** of FIG. **1** may extend around the struts **316**, through D-rings such as **30** in FIG. **1** and then fold back to be held in place by mating hook and loop areas on the surfaces of the straps. The straps **332** and **334** across the instep and the forward portion of the assembly, operate in similar manners to hold the foot and the soft goods type support member **320** in position within the frame **314**, **316**.

Elongated pad **344** is a strip of hook type material. As in the embodiment of FIG. **2**, the outer cloth covering of the soft goods type body member **320** is of one of many well-known types cloth that will receive hook type securing pads such as that sold under the trademark "Velcro". The front upper portion of the soft goods type support member **320** may be held in the closed position by the engagement of the pad **344** with the outer surface of the mating portion **345** of the support member **320**. Similarly, the pad **346** on the inner surface of the front flap **348** of the soft goods support member **320** serves to engage the mating flat **350** on its outer surface, and holds the front portion of the soft goods member around the upper portion of the patient's foot.

The present embodiment is provided with an inner booty **357** to provide additional means for retaining the foot within the walker. Inner booty **357** is sewn to soft goods body members **320** along seam **351**. Elongated hook type pads **347** and **349** engage the inner surfaces of flaps **359** and **361**, respectively, to adjustably hold the inner body about the patient's ankle and foot.

The footgear of the present embodiment is provided with an inner sole assembly **352** which is preferably mounted within the soft goods support member **320** by a layer of hook type securing material **354** which is on the lower surface of the assembly **352**, and which engages the inner surface of the soft goods type support member **320** in the area **356** and in the area **390** on inner booty **357**.

Inner sole assembly **352** includes a lower cloth pad **364** and an upper resilient layer **366** constituting separate removable sections, also known as individually mobile resilient sections, which together form a normally substantially smooth surface for engagement by the foot. These sections are individually removable, as indicated by the sections **368** which are shown removed from the space **370** where they would normally be located to complete the smooth upper surface of the inner sole assembly **352**.

Cloth pad **364** may be substantially indentation-free so that the resilient sections may be removed from any location on the grid. The user is thereby not limited to removing insets only from indentations located in a limited number of positions on the sole. Instead, a user may remove sections from precisely the desired location.

The individual resilient sections such as the section **368**, have hook or loop type securing material **372** on their lower surfaces, and the upper surface of the bladder **364** has mating hook and loop type material for removably securing sections such as section **368** in place to provide a relatively smooth upper surface. Thus, the group of sections **368** may be reinserted and re-secured into opening **370**, and other sections removed, to accommodate different patient needs.

FIG. **25** is a somewhat schematic cross-sectional view of the present embodiment taken along line **3-3** of FIG. **1**. Soft goods type support member **320** is shown here as a single layer for simplicity but which would actually be two layers of cloth and two foam layers forming a central foam core, as discussed in connection with FIG. **4**. FIG. **25** also shows outer sole **314** including the lower tread portion **378**, which would normally be somewhat rough for traction, the flap **348**, the cloth pad **364**, and the resilient inner sole **366**. The sole **314** may include tread portion **378**, and upper and lower high strength plastic sheet members **382** and **384** interconnected by appropriate ribs **385**. Resilient foam material **386** controls flexing of the rear heel end **388** of lower plastic sheet member **384** provides increased cushioning for the patient.

Between the upper surface of cloth pad **364**, and the lower surface of the inner sole **366** is a suitable material **398**, for removably securing the inner sole **366** to the upper surface of the cloth pad **364**. Material **398** may be hook and loop type material, or pressure sensitive adhesive, as noted hereinabove. The inner sole **366** may be formed of three layers **302**, **304** and **306**, which may be of progressively different softness and resiliency, with the softest and most resilient layer being the layer **302** closest to the foot, with layers **304** and **306** being progressively less resilient and providing somewhat greater support.

Another alternative embodiment of the present invention includes an inner sole having a plurality of independently vertically movable sections arranged in a grid pattern.

13

Means are provided for independently and adjustably modifying the support of the foot at each section location. Referring to FIG. 26, the modifying means may include independent pneumatic sections 468 which a user may puncture to a partially or fully deflat, as illustrated in FIG. 27. The modifying means could alternatively include independent mechanical retention elements which a user would push down and which would then stay in place at a position below the surface of the sections that the user has not pushed down.

It should be noted that the various embodiments of the present invention provide means to reduce shear forces on the sole of the foot. The grid pattern of resilient sections creates a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot. Typical soles simply resist lateral foot motion, thereby including shear stresses on the bottom of the foot which may cause or aggravate ulcers. Thus, in contrast to typical soles, the grid pattern of independently mobile resilient sections of the present invention constitutes means for reducing shear stresses on the bottom of a foot as the user walks along.

It should also be noted that inner sole assembly 52 may be worn interchangeably with either the right or left foot. So, for instance, a user may use the inner sole assembly to pad the left foot for a time, then later use it to pad the right foot. Likewise, the entire walker 12 may be designed to be worn interchangeably on either the right or left leg.

Concerning the dimensions of the removable sections, one operative and presently preferred embodiment of the invention employs hexagonal removable elements of the type shown in FIG. 2, with the hexagons having a distance between opposing faces of approximately $\frac{1}{2}$ ". Larger or smaller removable sections could be employed; however, it is preferred that the sections have a linear extent less than $\frac{3}{4}$ ". In the presently preferred embodiment, the removable sections are resilient and each have a height that is greater than its width and depth.

In conclusion, a number of illustrative embodiments of the invention have been discussed hereinabove. However, it is to be understood that various changes and modifications may be made without departing from the spirit and scope of the invention. Thus, by way of example and not of limitation, the air bladder under the sole may be embedded in the soft goods member or may be located under it, between the soft goods support member 20 and the outer sole assembly 14. In addition, the optional bladder may be filled with a variety of fluids other than air, such as gel or water. The invention is, of course, applicable to other types of footwear, in addition to walkers, for example, athletic shoes or normal walking shoes. Accordingly, the present invention is not limited to the precise embodiments described hereinabove.

What is claimed is:

[1. A walker with pressure relief areas for the foot of a user, said walker having a sole area extending substantially for the entire area underlying the foot of a user, comprising:
 a walker frame including an outer sole and struts extending from said sole upward;
 a soft goods support for enclosing the ankle, lower leg and at least a portion of the foot, said support being secured to said frame;
 an inner sole mounted in said soft good support, said inner sole including an underlying flexible sheet extending substantially over the entire sole area; and an upper resilient inner sole member extending over and being removably secured to said underlying flexible sheet,

14

said upper resilient inner sole member having a substantially uniform thickness and extending substantially over the entire sole area;

said upper resilient inner sole portion being composed of a plurality of at least 50 separate resilient sections arranged in a grid pattern, said sections being removably secured on their lower surfaces to said underlying flexible sheet and said sections together forming a substantially smooth surface for engagement by the foot, said sections being individually removable to provide localized pressure relief to selected areas of the foot; and

said sections being directly adjacent one another to form said grid;

said grid pattern extending over substantially all of said upper inner sole member;

whereby one or a plurality of said sections may be removed at any desired area of the inner sole member to provide a relief zone corresponding to an afflicted zone of a foot.]

[2. A walker with pressure relief areas for the foot of a user, as defined in claim 1 wherein said upper resilient sole member includes at least 80 separate resilient sections.]

[3. A walker as defined in claim 1 wherein the inner sole portion has a central longitudinal axis, and wherein the inner sole portion is substantially symmetrical about said axis so that the walker may be used for either the left or the right foot and ankle of the user.]

[4. A walker as defined in claim 1 wherein said resilient sections are removably secured to said flexible sheet by hook and loop material; whereby said resilient sections may be easily removed and replaced.]

[5. A walker as defined in claim 4 wherein some of said separate resilient sections are taller than other of said sections so that a user may arrange said taller sections to custom fit a foot.]

[6. A walker as defined in claim 1 wherein said underlying flexible sheet is substantially indentation-free.]

[7. A walker as defined in claim 1 wherein some of said separate resilient sections are lower density sections and some are higher density sections so that a user may arrange said higher density sections to create at least one zone of additional support for a foot.]

[8. A walker as defined in claim 1 wherein said walker further comprises an additional resilient pad having an aperture and an adhesively-backed lower surface for attaching said additional pad to the upper surface of a plurality of said removable sections, said additional pad providing a region of additional support for a foot.]

[9. A walker as defined in claim 1 wherein said walker further includes an edema patch comprising a patch of stretch material having an adhesive layer on a lower surface thereof for adhering the edema patch to a top surface of removable sections surrounding a relief zone from which a user has removed other sections, such that the edema patch covers the relief zone.]

[10. A walker as defined in claim 9 wherein said edema patch further includes a fluid-impermeable film layer overlying said stretch material for preventing transmission of fluids through said edema patch.]

[11. A walker as defined in claim 1 wherein said walker further includes an edema patch comprising a patch of fluid-impermeable film having an adhesive layer on a lower surface thereof for adhering the edema patch to a top surface of sections surrounding a relief zone from which a user has removed other sections, such that the edema patch covers the relief zone.]

15

[12. A walker as defined in claim 11 wherein said edema patch further includes a layer of stretch material overlying said film patch.]

[13. A walker as defined in claim 1 wherein said separate resilient sections are hexagonal.]

[14. A walker as defined in claim 1 wherein said inner sole includes a plurality of layers, with the layer closest to the foot being substantially softer and more resilient than other layers.]

[15. A walker as defined in claim 1 further comprising means connected to said support for extending around the instep to hold the foot back into said support and in engagement with said inner sole.]

[16. A walker as defined in claim 1 wherein said inner sole extends to the rear beyond the heel of a patient and upward along and to the rear of the foot of the user.]

[17. A walker as defined in claim 1 wherein hook and loop type fabric holds the support to the walker frame.]

[18. A walker as defined in claim 1 wherein said walker further comprises a bladder for containing air which is mounted in said walker above said outer sole, and wherein said inner sole is mounted above said bladder.]

[19. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole extending substantially over the entire sole area mounted in said footgear above said outer sole, said inner sole having a plurality of independently vertically movable sections arranged in a grid pattern, said independently vertically movable sections having lower surfaces which are mounted within said footgear and said sections together form a substantially smooth surface for engagement by the foot;

means for independently modifying support of the foot provided at each section location;

said resilient sections being directly adjacent one another to form said grid; and

said grid of resilient sections comprising substantially all of said inner sole and extending over substantially all of said sole area;

wherein said resilient sections have a height, a width and a depth, said height being greater than said width and depth.]

[20. Footgear as defined in claim 19 wherein said means for independently modifying the support of the foot comprises independent mechanical retention elements.]

[21. Footgear with pressure relief areas for the foot, comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner having a plurality of independently vertically movable sections arranged in a grid pattern, said independently vertically movable sections having lower surfaces which are mounted within said footgear and together form a substantially smooth surface for engagement by the foot;

means for independently modifying the support of the foot provided at each section location;

said resilient sections being directly adjacent one another to form said grid; and

said grid of resilient sections comprising substantially all of said inner sole;

wherein said resilient sections have a height, a width and a depth, said height being greater than said width and depth; and

16

said means for independently modifying the support of the foot comprising independent pneumatic sections which a user may puncture to deflate.]

[22. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user, comprising:

an outer sole;

an inner sole extending substantially over the entire sole area mounted in said footgear above said outer sole, said inner sole having a plurality of removable sections that are removable mounted in said footgear and that are arranged in a grid pattern said removable sections having lower surfaces which are removable secured within said footgear and said sections together forming a substantially smooth surface for engagement by the foot said sections being individually removable from said footgear to provide localized relief to selected areas of the foot;

said resilient sections being directly adjacent to one another to form said grid, with substantially no space in between said sections except when at least one of said sections has been removed; and

said grid of resilient sections comprising substantially all of said inner sole and extending substantially over the entire sole area;

wherein said footgear further comprises a bladder for containing fluid, mounted in said footgear above said outer sole, and said removable sections are mounted in said footgear above said bladder.]

[23. Footgear with pressure relief zones for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user, comprising:

an outer sole;

an inner sole extending substantially over the entire sole area mounted in said footgear above said outer sole, said inner sole having a plurality of separate individually mobile resilient sections arranged in a grid pattern, said sections being removable secured on each of their lower surfaces to an underlying flexible sheet such that a user may disengage a lower surface of one or more of said sections from said flexible sheet for removal from said footgear, said resilient sections forming a surface for engagement by a foot;

said resilient sections being directly adjacent one another to form said grid and extending over substantially all of said sole area; and

an edema patch for covering an open space left after a user has removed at least one mobile section from said grid, said edema patch comprising an upper patch body having a lower surface and an adhesive layer on said lower surface for adhering said patch to mobile resilient sections surrounding the open space;

wherein said footgear further comprises a bladder for containing fluid, mounted in said footgear above said outer sole, and said resilient sections are mounted in said footgear above said bladder;

whereby one or a plurality of said adjacent sections may be removed at any desired area of the inner sole to provide relief corresponding to an afflicted zone of the foot, said edema patch being placed over the removed sections to apply pressure to the afflicted zone of the foot, thereby preventing fluids from building up therein.]

[24. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;
 an inner sole extending substantially over the entire sole area mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said resilient sections having lower surfaces which are mounted within said footgear and said sections together form a substantially smooth surface for engagement by the foot, and having upper surfaces which are independently vertically movable;
 means for independently modifying support of the foot provided at each section location;
 said resilient sections being directly adjacent one another to form said grid; and
 said grid of resilient sections comprising substantially all of said inner sole and extending over substantially all of said sole area;
 wherein said resilient sections each comprise at least three layers of progressively different softness and resiliency, with the softest and most resilient layer being closest to the foot; and
 said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway to a substantial extent laterally independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along.

25. Footgear as defined in claim 24 wherein said footgear is a shoe.

26. Footgear as defined in claim 24 wherein said footgear further comprises a heel portion that extends partially up the heel and ankle area of the user.

27. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user, comprising:
 an outer sole;
 an inner sole extending substantially over the entire sole area mounted in said footgear above said outer sole, said inner sole having a plurality of removable resilient sections that are removably mounted in said footgear and that are arranged in a grid pattern, said removable sections having lower surfaces which are removably secured within said footgear and said sections together forming a substantially smooth surface for engagement by the foot said sections being individually removable from said footgear to provide localized relief to selected areas of the foot;
 said resilient sections being directly adjacent to one another to form said grid, with substantially no space in between said sections except when at least one of said sections has been removed;
 said grid of resilient sections comprising substantially all of said inner sole and extending substantially over the entire sole area;
 wherein said resilient sections each comprise at least three layers of progressively different softness and resiliency, with the softest and most resilient layer being closest to the foot; and
 said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally to a substantial extent independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along.

28. A pad for footgear with pressure relief areas for the foot, said pad having a sole area extending for substantially the entire area underlying the foot of a user, comprising:

an underlying flexible sheet and an upper resilient inner sole member extending over and being removably secure to said underlying flexible sheet, said upper resilient inner sole member having a substantially uniform thickness and extending substantially over the entire sole area;
 said upper resilient inner sole portion being composed of a plurality of resilient sections, said sections being removably secured on their lower surfaces to said underlying flexible sheet and said sections together forming a grid having a substantially smooth upper surface for engagement by the foot, said sections being individually removable to provide localized pressure relief to selected areas of the foot;
 said grid comprising substantially all of said inner sole and extending substantially over the entire sole area; wherein said resilient sections each comprise at least three layers of progressively different softness and resiliency, with the softest and most resilient layer being closest to the foot;
 whereby a relief zone corresponding to an afflicted zone of a foot is provided when one or more of said sections is removed; and
 said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along.

29. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:
 an outer sole;
 an inner sole extending substantially over the entire sole area mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are mounted within said footgear and said sections together form a substantially smooth surface for engagement by the foot, and having upper surfaces which are independently vertically movable;
 means for independently modifying support of the foot provided at exact section location;
 said resilient sections being directly adjacent one another to form said grid;
 said grid of resilient sections comprising substantially all of said inner sole and extending over substantially all of said sole area;
 wherein said resilient sections comprise a material that resists compression-set; and
 said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally to a substantial extent independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along.

30. Footgear with pressure relief areas for the foot, comprising:
 an outer sole;
 an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably mounted within said footgear, and said sections having upper surfaces which together form a substantially continuous upper surface for engagement by the foot and which are independently vertically movable;

19

said resilient sections being directly adjacent one another to form said grid; and

said grid of resilient sections extending over substantially all of said inner sole;

said sections having a height and width, with the height of said sections being at least equal to the width thereof, to permit swaying of said sections, thereby reducing shear forces on the lower surface of the foot;

said footgear having a heel/ankle portion that extends partially up the heel and ankle area of the user;

said footgear including flaps for holding the foot into the footgear, said flaps extending over at least a portion of the upper surface of the foot from both sides of the foot;

arrangements for holding said flaps together to hold the user's foot into the footgear;

said flaps leaving an opening at the front of the footgear so that the toes of the user may extend out beyond the flaps while still resting on said inner sole;

said upper surface of said sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user; and

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally to a substantial extent independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along.

31. Footgear with pressure relief areas for the foot as defined in claim 30 wherein said inner sole includes an underlying flexible sheet to which said sections are removably secured; and said sections being secured to said sheet, and said inner sole being secured into said shoe by hook and loop type fastening arrangements.

32. Footgear with pressure relief areas for the foot as defined in claim 30 wherein said sections are softer and more resilient adjacent said upper surface as compared with the lower portion of said sections adjacent said lower surfaces.

33. Footgear with pressure relief areas for the foot, comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably mounted within said footgear and said sections having upper surfaces which together form a substantially smooth and continuous upper surface for engagement by the foot; and which are independently vertically movable;

said resilient sections being directly adjacent one another to form said grid;

said grid of resilient sections extending over substantially all of said inner sole;

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally to a substantial extent independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along;

said footgear having a closed heel/ankle portion;

said footgear including upper footgear parts for holding the foot into the footgear, said upper footgear parts extending over at least a portion of the upper surface of the foot from both sides of the foot; and

20

said upper surface of said resilient sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user.

34. Footgear with pressure relief areas for the foot said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably mounted within said footgear, and said sections having upper surfaces which together form a substantially smooth and continuous upper surface for engagement by the foot; and which are independently vertically movable;

said resilient sections being directly adjacent one another to form said grid; and

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

said footgear having a closed heel/ankle portion;

said footgear including upper footgear parts for holding the foot into the footgear, said upper footgear parts extending over at least a portion of the upper surface of the foot;

arrangements for engaging said upper footgear parts to hold the user's foot into the footgear;

said upper surface of said resilient sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user; and

said grid pattern of resilient sections constituting means for enabling said sections to sway laterally to a substantial extent independently of one another in response to forces applied by the foot and for reducing shear stresses on the bottom of a foot as the user walks along.

35. Footgear with pressure relief areas for the foot said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably mounted within said footgear, and said sections having upper surfaces which together form a substantially smooth and continuous upper surface for engagement by the foot, and which are independently vertically movable;

said resilient sections being directly adjacent one another to form a grid; and

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

said footgear having a closed heel/ankle portion;

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally to a substantial extent independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along; and

said upper surface of said sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user.

36. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably, 5 mounted within said footgear and said sections having upper surfaces which together form a substantially smooth and continuous upper surface for engagement by the foot, and which are independently vertically movable;

said resilient sections being directly adjacent one another to form a grid; and

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

said upper surface of said sections being directly exposed 15 for direct engagement with the foot of the user or a sock or stocking on the foot of the user; and

said grid pattern of resilient sections constituting means for providing a multiplicity of section that sway laterally to a substantial extent independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along.

37. Footgear with pressure relief areas for the foot as defined in claim 36 wherein said inner sole includes an underlying flexible sheet to which said sections are removably secured; and said sections being secured to said sheet, and said inner sole being secured into said shoe by hook and loop type fastening arrangements.

38. Footgear with pressure relief areas for the foot as defined in claim 36 wherein said sections are softer and more resilient adjacent said upper surface as compared with the lower portion of said sections adjacent said lower surfaces.

39. Footgear with pressure relief areas for the foot, comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfacers which are separately removably, mounted within said footgear and said sections having upper surfaces which together form a substantially continuous upper surface for engagement by the foot, and which are independently vertically movable;

said resilient sections being directly adjacent one another to form said grid; and

said grid of resilient sections extending over substantially all of said inner sole;

said upper surface of said sections being of soft resilient material and being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user;

said inner sole including at least 80 of said resilient sections;

said sections being hexagonal in shape and having a linear extent less than $\frac{3}{4}$ inch; and

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another to a substantial extent in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along.

40. Footgear with pressure relief areas for the foot, comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably, mounted within said footgear and said sections having upper surfaces which together form a substantially continuous upper surface for engagement by the foot, and which are independently vertically movable;

said resilient sections being directly adjacent one another to form a grid; and

said upper surface of said sections being of soft resilient materials and being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user;

said inner sole including at least 80 of said resilient sections; and

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another to a substantial extent in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along.

41. Orthopaedic footgear with resilient support for the foot, comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of compressible resilient sections arranged in a grid pattern, said sections having upper surfaces which are independently vertically movable and which together form a substantially smooth and continuous upper surface for engagement by the foot; said inner sole extending for substantially the entire area underlying the foot of the user;

said resilient sections being directly adjacent one another to form said grid;

said grid of resilient sections extending over substantially all of said inner sole;

said upper surface of said sections being of soft resilient material and being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user; and

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another to a substantial extent in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along.

42. Orthopaedic footgear as defined in claim 41 wherein said sections are hexagonal in cross section.

43. Orthopaedic footgear as defined in claim 41 wherein said inner sole includes at least 80 sections.

44. Orthopaedic footgear as defined in claim 41 wherein said sections are less than $\frac{3}{4}$ inch in transverse extent.

45. Orthopaedic footgear as defined in claim 41 wherein said sections are individually removably secured within said footgear.

46. Orthopaedic footgear with resilient support for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of compressible

23

resilient sections arranged in a grid pattern, said sections having upper surfaces which are independently vertically movable and which together form a substantially smooth and continuous upper surface for engagement by the foot;

5 said resilient sections being directly adjacent one another to form a grid;

said upper surface of said sections being of soft resilient material and being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user;

10 said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along;

15 said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

said sections having a height and a transverse extent, with the height being greater than said transverse extent.

47. Footgear with pressure relief areas for the foot, comprising:

an outer sole;

25 an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably mounted within said footgear and said sections having upper surfaces which are independently vertically movable and which together form a substantially smooth and continuous upper surface for engagement by the foot;

30 said resilient sections being directly adjacent one another to form a grid; and

said grid of resilient sections extending over substantially all of said inner sole;

said upper surface of said sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user;

40 said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent; and

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another to a substantial extent in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along.

45 48. An orthopaedic footgear as defined in claim 47 wherein the sections are in contact with one-another.

49. Footgear with pressure relief areas for the foot, comprising:

50 an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably mounted within said footgear and said sections having upper surfaces which are independently vertically movable and which together form a substantially smooth and continuous upper surface for engagement by the foot;

60 said resilient sections being directly adjacent one another to form said grid;

24

said grid of resilient sections extending over substantially all of said inner sole;

said upper surface of said sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user; and

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally to a substantial extent independently of one another in response to forces applied by the foot, for reducing shear stresses on the bottom of a foot as the user walks along.

50. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

15 an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably mounted within said footgear and said sections having upper surfaces which are independently vertically movable and which together form a substantially smooth and continuous upper surface for engagement by the foot;

25 said resilient sections being directly adjacent one another to form said grid;

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

30 said upper surface of said sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user; and

said grid pattern of resilient sections constituting means for providing a multiplicity of sections of substantial height that sway laterally to a substantial extent independently of one another in response to forces applied by the foot, and providing means for reducing shear stresses on the bottom of a foot as the user walks along.

51. Orthopaedic footgear with resilient support for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

40 an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having upper surfaces which together form a substantially continuous upper surface for engagement by the foot; and which are independently vertically movable;

45 said resilient sections being directly adjacent one another to form said grid;

said upper surface of said sections being of soft resilient material and being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user;

50 said resilient sections being removable from the footgear;

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

60 said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot, and constituting means for reducing shear stresses on the bottom of a foot as the user walks along; and

65 said sections having a height and a transverse extent, with the height being greater than said transverse extent.

52. Orthopaedic footgear with resilient support for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having upper surfaces which together form a substantially continuous upper surface for engagement by the foot and which are independently vertically movable; said resilient sections being directly adjacent one another to form a grid;

said upper surface of said sections being of soft resilient material and being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user;

said resilient sections being removable from the footgear;

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot, further constituting means for reducing shear stresses on the bottom of a foot as the user walks along; and

said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent.

53. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole extending substantially over the entire sole area mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said resilient sections having lower surfaces which are mounted within said footgear and said sections together form a substantially smooth surface for engagement by the foot; and having upper surfaces which are independently vertically movable;

means for independently modifying support of the foot provided at each section location;

said resilient sections being directly adjacent one another to form said grid; and

said grid of resilient sections comprising substantially all of said inner sole and extending over substantially all of said sole area;

wherein said resilient sections each comprise at least three layers of progressively different softness and resiliency, with the softest and most resilient layer being closest to the foot;

said grid pattern of resilient sections constituting a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along, and

said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent.

54. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user, comprising:

an outer sole;

an inner sole extending substantially over the entire sole area mounted in said footgear above said outer sole, said inner sole having a plurality of removable resilient sections that are removable mounted in said footgear and that are arranged in a grid pattern said removable sections having lower surfaces which are removable secured within said footgear and said sections together forming a substantially smooth surface for engagement by the foot said sections being individually removable from said footgear to provide localized relief to selected areas of the foot;

said resilient sections being directly adjacent to one another to form said grid, with substantially no space in between said sections except when at least one of said sections has been removed;

said grid of resilient sections comprising substantially all of said inner sole and extending substantially over the entire sole area;

wherein said resilient sections each comprise at least three layer of progressively different softness and resiliency, with the softest and most resilient layer being closest to the foot;

said grid pattern of resilient sections constituting a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along;

said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent.

55. A pad for footgear with pressure relief areas for the foot, said pad having a sole area extending for substantially the entire area underlying the foot of a user, comprising:

an underlying flexible sheet and an upper resilient inner sole member extending over and being removably secured to said underlying flexible sheet, said upper resilient inner sole member having a substantially uniform thickness and extending substantially over the entire sole area;

said upper resilient inner sole portion being composed of a plurality of resilient sections, said sections being removably secured on their lower surfaces to said underlying flexible sheet and said sections together forming a substantially smooth surface for engagement by the foot, said sections being individually removable to provide localized pressure relief to selected areas of the foot;

wherein said resilient sections each comprise at least three layers of progressively different softness and resiliency, with the softest and most resilient layer being closest to the foot;

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

whereby a relief zone corresponding to an afflicted zone of a foot is provided when one or more of said sections is removed;

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along; and

said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent.

27

56. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole extending substantially over the entire sole area mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are mounted within said footgear and said sections together form a substantially smooth surface for engagement by the foot; and having upper surfaces which are independently vertically movable;

means for independently modifying support of the foot provided at each section location;

said resilient sections being directly adjacent one another to form said grid;

said grid of resilient sections comprising substantially all of said inner sole and extending over substantially all of said sole area;

wherein said resilient sections comprise a material that resists compression-set; and

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally to a substantial extent independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along; and

said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent.

57. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said section having lower surfaces which are separately removably mounted within said footgear, and said sections having upper surfaces which together form a substantially continuous upper surface for engagement by the foot; and which are independently vertically movable;

said resilient sections being directly adjacent one another to form a grid; and

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

said sections having a height and width, with the height of said sections being at least equal to the width thereof, to permit swaying of said sections, thereby reducing shear forces on the lower surface of the foot;

said footgear having a heel/ankle portion that extends partially [only part way] up the heel and ankle area of the user;

said footgear including flaps for holding the foot into the footgear, said flaps extending over at least a portion of the upper surface of the foot from both sides of the foot;

arrangements for holding said flaps together to hold the user's foot into the footgear;

said flaps leaving an opening at the front of the footgear so that the toes of the user may extend out beyond the flaps while still resting on said inner sole;

said upper surface of said sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user;

28

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally to a substantial extent independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along; and

said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent.

58. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably mounted within said footgear and said sections having upper surfaces which together form a substantially smooth and continuous upper surface for engagement by the foot, and which are independently vertically movable;

said resilient sections being directly adjacent one another to form said grid;

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

said grid pattern of resilient sections constituting a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along;

said footgear having a closed heel/ankle portion;

said footgear including upper footgear parts for holding the foot into the footgear, said upper footgear parts extending over at least a portion of the upper surface of the foot from both sides of the foot;

said upper surface of said resilient sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user; and

said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent.

59. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably mounted within said footgear, and said sections having upper surfaces which together form a substantially smooth and continuous upper surface for engagement by the foot; and which are independently vertically movable;

said resilient sections being directly adjacent one another to form said grid; and

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

said footgear having a closed heel/ankle portion;

said footgear including upper footgear parts for holding the foot into the footgear, said upper footgear parts extending over at least a portion of the upper surface of the foot;

29

arrangements for engaging said upper footgear parts to hold the user's foot into the footgear;

said upper surface of said resilient sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user; and

said grid pattern of resilient sections constituting a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot thereby reducing shear stresses on the bottom of a foot as the user walks along; and

said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent.

60. Footgear with pressure relief areas for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said section having lower surfaces which are separately removably mounted within said footgear, and said sections having upper surfaces which together form a substantially smoothed and continuous upper surface for engagement by the foot; and which are independently vertically movable;

said resilient sections being directly adjacent one another to form a grid;

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along;

said upper surface of said sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user; and

said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent.

61. Footgear as defined in claim 60 wherein said means for independently modifying support of the foot at each section location includes the removable fastening of each resilient section into the footgear.

62. Orthopaedic footgear with resilient support for the foot, said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of compressible resilient sections arranged in a grid pattern, said sections having upper surfaces which are independently vertically movable and which together form a substantially smooth and continuous upper surface for engagement by the foot;

said resilient sections being directly adjacent one another to form a grid;

said upper surface of said sections being of soft resilient material and being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user;

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

30

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along; and

said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent.

63. Footgear with pressure relief areas for the foot said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said sections having lower surfaces which are separately removably mounted within said footgear and said sections having upper surfaces which are independently vertically movable and which together form a substantially smooth and continuous upper surface for engagement by the foot;

said resilient sections being directly adjacent one another to form a grid; and

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

said upper surface of said sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user;

said sections having a height and a transverse extent, with the height being substantially equal to or greater than said transverse extent; and

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally independently of one another to a substantial extent in response to forces applied by the foot, thereby reducing shear stresses on the bottom of a foot as the user walks along.

64. Footgear with pressure relief areas for the foot said footgear having a sole area extending substantially for the entire area underlying the foot of a user comprising:

an outer sole;

an inner sole mounted in said footgear above said outer sole, said inner sole having a plurality of resilient sections arranged in a grid pattern, said section having lower surfaces which are separately removably mounted within said footgear and said sections having upper surfaces which are independently vertically movable and which together form a substantially smooth and continuous upper surface for engagement by the foot;

said resilient sections being directly adjacent one another to form said grid;

said grid comprising substantially all of said inner sole and extending substantially over the entire sole area;

said upper surface of said sections being directly exposed for direct engagement with the foot of the user or a sock or stocking on the foot of the user; and

said grid pattern of resilient sections constituting means for providing a multiplicity of sections that sway laterally to a substantial extent independently of one another in response to forces applied by the foot, for reducing shear stresses on the bottom of a foot as the user walks along.