

(19) **United States**
 (12) **Reissued Patent**
Asbach et al.

(10) **Patent Number:** **US RE41,121 E**
 (45) **Date of Reissued Patent:** **Feb. 16, 2010**

(54) **INFANT SUPPORT WITH ENTERTAINMENT DEVICE**
 (75) Inventors: **Ronald M. Asbach**, Grand Island, NY (US); **Curt Jonathan Mahlstedt**, Duxbury, MA (US)
 (73) Assignee: **Mattel, Inc.**, El Segundo, CA (US)
 (21) Appl. No.: **11/244,408**
 (22) Filed: **Oct. 6, 2005**

(Under 37 CFR 1.47)

Related U.S. Patent Documents

Reissue of:
 (64) Patent No.: **6,629,727**
 Issued: **Oct. 7, 2003**
 Appl. No.: **09/971,003**
 Filed: **Oct. 5, 2001**
 (51) **Int. Cl.**
A47C 7/62 (2006.01)
A63H 33/00 (2006.01)
 (52) **U.S. Cl.** **297/188.21**; 297/DIG. 11; 297/188.2; 297/188.06; 446/227
 (58) **Field of Classification Search** 297/188.06, 297/188.2, 188.21, DIG. 11; 248/227.4, 230.5, 248/231.61; 446/227, 228, 229; 5/658
 See application file for complete search history.

References Cited

U.S. PATENT DOCUMENTS

355,663 A 1/1887 Price
 442,629 A 12/1890 Lipscomb
 546,333 A 9/1895 Kell
 659,487 A 10/1900 McMurdy

810,900 A 1/1906 Bartlett
 1,265,682 A 5/1918 Larson
 1,390,502 A 9/1921 Clouser
 1,404,894 A 1/1922 Rollins
 1,436,367 A 11/1922 Sullivan
 1,548,617 A 8/1925 La Belle
 1,574,226 A 2/1926 Ackermann
 1,634,162 A 6/1927 Tesk
 1,671,085 A * 5/1928 Nuernberg 248/103
 1,806,773 A 5/1931 Waters
 1,965,236 A 7/1934 Hall

(Continued)

FOREIGN PATENT DOCUMENTS



GB 2 216 428 A * 10/1989
 GB 2 279 265 A * 1/1995
 GB 2279265 A 1/1995
 GB 2280616 A 2/1995
 WO 0205917 A1 1/2002

Primary Examiner—Sarah B McPartlin
 (74) *Attorney, Agent, or Firm*—Edell, Shapiro & Finnan, LLC

(57) **ABSTRACT**

The present invention provides support assembly having a resilient support frame having a ground engaging portion and an upper portion. The upper portion is moveable with respect to the ground engaging portion. A suspension assembly is coupled to the upper portion of the support frame such that motion of the upper portion imparts motion to the suspension assembly. In another aspect of the invention, the invention includes a seat supported on a resilient support frame having a ground engaging portion and an upper portion moveable with respect to the ground engaging portion. A mobile is coupled to the upper portion such that motion of the upper portion imparts a corresponding motion to the mobile.

51 Claims, 4 Drawing Sheets




US RE41,121 E

Page 2

U.S. PATENT DOCUMENTS						
2,252,224 A	8/1941	Welsh	5,480,340 A	1/1996	Bogar	
2,282,881 A	5/1942	Ostrow	5,487,705 A	1/1996	Clarke	
2,402,861 A	6/1946	Winnick	5,509,721 A	4/1996	Huang	
2,452,749 A *	11/1948	Guden 248/104	5,533,936 A	7/1996	Julien et al.	
D156,293 S	11/1949	Tharler	5,553,337 A	9/1996	Lin	
2,490,230 A	12/1949	Riegel	D374,691 S	10/1996	Chow et al.	
2,506,001 A	5/1950	Sturman	D374,692 S	10/1996	Stroud et al.	
2,567,418 A	9/1951	Barker	5,584,531 A	12/1996	Bowman	
2,628,666 A	2/1953	Hall	5,620,274 A	4/1997	Wear	
2,686,030 A	8/1954	Johnson	5,628,689 A	5/1997	Saint et al.	
2,723,856 A	11/1955	Thomson	5,634,796 A	6/1997	Dollar	
2,769,276 A	11/1956	Steiner	5,664,746 A	9/1997	Benzakarya	
2,858,641 A	11/1958	Trimble	5,672,088 A	9/1997	Chininis	
3,014,307 A	12/1961	Dupuis	5,702,039 A	12/1997	Olaiz	
D193,093 S	6/1962	Wiele	5,709,582 A	1/1998	O'Donnell	
3,060,628 A	10/1962	Palmer	D392,126 S	3/1998	Sack	
3,116,493 A	1/1964	Gerds et al.	5,788,014 A	8/1998	Saint et al.	
3,180,600 A	4/1965	Kopec	5,797,785 A	8/1998	Silberstein	
3,204,367 A	9/1965	Stubbmann	5,803,786 A	9/1998	McCormick	
3,564,759 A	2/1971	Buttermore	D403,719 S	1/1999	Smith, II et al.	
3,779,124 A	12/1973	Chistensen	5,887,945 A	3/1999	Sedlack	
3,954,240 A	5/1976	Schmidt, III et al.	5,928,054 A	7/1999	Mast	
3,978,610 A	9/1976	Stubbmann	5,930,854 A	8/1999	O'Neill	
4,014,540 A	3/1977	Caulkins	5,939,995 A	8/1999	Phillips	
D248,518 S	7/1978	Huff	D413,940 S	9/1999	Yip	
D250,861 S	1/1979	Boudreau et al.	5,951,360 A	9/1999	Fearon et al.	
4,188,745 A	2/1980	Harvey et al.	6,016,926 A	1/2000	Smith, II et al.	
4,207,696 A	6/1980	Hyman et al.	6,056,246 A	5/2000	Argy, II	
4,321,660 A	3/1982	Sokol	6,068,285 A	5/2000	Jackson et al.	
4,335,538 A	6/1982	Greenberg	6,099,377 A	8/2000	Pridemore	
4,449,321 A	5/1984	Reiling	6,113,455 A	9/2000	Whelan et al.	
4,540,219 A	9/1985	Klinger	6,129,418 A	10/2000	Bergh et al.	
4,553,786 A	11/1985	Lockett, III et al.	6,149,489 A	11/2000	Johnson	
D282,791 S	3/1986	Lockett, III et al.	6,170,910 B1	1/2001	Bapst	
4,573,654 A	3/1986	Nottingham	6,213,547 B1	4/2001	Bowe et al.	
4,627,588 A	12/1986	Block	6,250,526 B1	6/2001	Bess	
4,640,034 A	2/1987	Zisholtz	6,283,870 B1	9/2001	Saint et al.	
4,664,640 A	5/1987	Shindo et al.	6,343,994 B1	2/2002	Clarke	
4,702,719 A	10/1987	Lapid	6,386,490 B1 *	5/2002	Suh 248/104	
4,722,713 A	2/1988	Williams et al.	6,386,986 B1	5/2002	Sonner et al.	
D295,198 S	4/1988	Williams et al.	D461,854 S	8/2002	Myers	
4,756,109 A	7/1988	Marcus	6,447,362 B2	9/2002	Khamphilavong et al.	
4,841,911 A	6/1989	Houghton	6,464,594 B1	10/2002	Canna et al.	
D302,988 S	8/1989	Zinter-Chahin	6,475,057 B1	11/2002	Norman	
4,865,380 A	9/1989	Heitzman-Powell et al.	D468,544 S	1/2003	Myers	
4,880,197 A	11/1989	Wsyzynski	6,520,862 B1	2/2003	Armbruster et al.	
4,904,220 A	2/1990	Williams et al.	6,561,915 B2	5/2003	Kelly et al.	
4,973,286 A	11/1990	Davison	6,592,425 B2	7/2003	Bapst et al.	
4,984,380 A	1/1991	Anderson	6,594,840 B2	7/2003	Tomas et al.	
5,076,520 A	12/1991	Bro	6,616,237 B2	9/2003	Sonner et al.	
D328,927 S	8/1992	Hines	6,656,009 B1	12/2003	Epping	
5,135,233 A	8/1992	Leas et al.	6,682,389 B2	1/2004	Wells	
5,187,826 A	2/1993	Mariol	6,705,950 B2	3/2004	Wood et al.	
5,195,918 A	3/1993	Mozes	6,739,649 B2	5/2004	Kelly et al.	
D342,117 S	12/1993	Nolan	6,860,786 B2	3/2005	Oren et al.	
5,301,999 A	4/1994	Thompson et al.	2001/0003695 A1	6/2001	Tell et al.	
5,352,145 A	10/1994	Raiffe et al.	2001/0028184 A1	10/2001	Sitarski et al.	
5,360,258 A	11/1994	Alivizatos	2002/0002741 A1 *	1/2002	Tomas et al. 5/101	
5,370,570 A	12/1994	Harris	2002/0077020 A1	6/2002	Graf et al.	
5,393,075 A	2/1995	Harber	2003/0020317 A1 *	1/2003	Keegan et al. 297/446.2	
D356,346 S	3/1995	Yip	2003/0171065 A1 *	9/2003	Greenberg 446/226	
5,411,315 A	5/1995	Greenwood	2003/0199329 A1	10/2003	Wood et al.	
D362,346 S	9/1995	Clarke	2004/0198513 A1	10/2004	Wood et al.	
5,451,095 A	9/1995	Riback	2004/0198515 A1	10/2004	Wood et al.	
5,478,268 A	12/1995	Au				

* cited by examiner

25



151




FIG. 3




FIG. 4




FIG. 5





FIG. 6



INFANT SUPPORT WITH ENTERTAINMENT DEVICE

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

BACKGROUND

1. Field of the Invention

The present invention relates generally to infant support seats, and more particularly to an infant support seat with an attached mobile.

2. Discussion of the Related Art

Conventional infant support seats provide support for infants who are unable to support themselves in an upright position. Typically, the support seats provide some sort of stimulation for the infant in the form of vibration or music. Many infant support seats are also supported by resilient frames that flex under an infant's weight and provide soothing bouncing or rocking motion with the infant in the seat.

Additionally, there are infant seats that incorporate a bar or similar structure that arches over the seat and is configured to suspend toys to stimulate the infant in the seat. Such toy bars are typically removably coupled to opposite sides of the support seat frame. With the toy bar in place, it is difficult to place an infant in the seat, and likewise, difficult to remove the infant from the seat. Removal and replacement of the toy bar can be burdensome, especially when holding an infant.

Thus, there is a need for an infant seat that includes an entertainment device, such as a mobile, that is selectively positioned above the infant seat so that an infant may be easily placed in and removed from the seat without detaching the entertainment device.

SUMMARY OF THE INVENTION

The present invention solves the problems with, and overcomes the disadvantages of, conventional infant seats. In particular, the present invention relates to an infant seat that has an attached entertainment device that is selectively positionable above the seat.

The invention includes a resilient support frame having a ground engaging portion and an upper portion. The upper portion is moveable with respect to the ground engaging portion. A suspension assembly is coupled to the upper portion of the support frame such that motion of the upper portion imparts motion to the suspension assembly.

In another aspect of the invention, the invention includes a seat supported on a resilient support frame having a ground engaging portion and an upper portion moveable with respect to the ground engaging portion. A mobile is coupled to the upper portion such that motion of the upper portion imparts a corresponding motion to the mobile.

These and other aspects of the present invention will become apparent from the following drawings and description.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is described with reference to the accompanying drawings. In the drawings, like reference numbers indicate identical or functionally similar elements.

FIG. 1 is a perspective view of one embodiment of a support assembly with an attached entertainment device embodying the principles of the present invention.

FIG. 2 is a perspective view of the support assembly illustrated in FIG. 1 with the entertainment device positioned away from the support assembly.

FIG. 3 is an exploded view of detail A in FIG. 1.

FIG. 4 is a top plan view of a socket of the mounting bracket of the suspension assembly embodying the principles of the present invention.

FIG. 5 is a bottom plan view of an end post of the support arm of suspension assembly embodying the principles of the present invention.

FIG. 6 is an exploded view of detail B in FIG. 1.

DETAILED DESCRIPTION

FIGS. 1–6 illustrate one embodiment of an infant support assembly 100. The infant support assembly 100 includes a support frame 110, a seat 240, a suspension assembly 300, and an entertainment device 500.

The support frame 110 is a generally peripheral frame and includes a ground-engaging base member 112 that is configured to elevate the seat 240 above a supporting surface. An upper portion 114 is coupled to the base member 112 and is configured to support the seat 240 in an inclined position relative to the supporting surface. The upper portion 114 includes a leg support 116 that is coupled above the base member 112 and is configured to support a portion of the seat 240 in a forwardly extended position. The upper portion 114 of the frame 110, including leg support 116, is movable with respect to the ground engaging portion or base 112 to provide a bouncing or rocking motion to soothe the infant positioned in the seat 240.

A stimulation device 119 may be attached to the leg support 116 to provide stimulation for an infant in the seat. The stimulation device 119 may include a vibrator or music producing apparatus or any combination thereof as would be known to the skilled artisan.

The support frame 110 can include feet 111 located on the base member 112 to engage the supporting surface to inhibit the support assembly 100 from sliding.

The seat 240 is substantially elliptical or oval in plan view and includes an upper seating surface 242 upon which an infant can be positioned and a lower foot portion 244 adjacent the upper seating surface 242. The foot portion 244 and the seating surface 242 may be integrally formed or removably coupled. The seat 240 is coupled to the frame 110 according to conventional methods known to the skilled artisan.

To maintain the infant securely in seat 240, a belt 270 is coupled to the seat 240. The belt 270 is provided with separable buckles for easy operation. Any infant restraint device known to the skilled artisan may be utilized with the seat 240 without departing from the scope of the invention.

A suspension assembly 300 is coupled to the upper portion 114 of the frame 110 such that motion of the upper portion 114 imparts a motion to the suspension assembly 300. As will be apparent, the configuration of the support assembly 300 (described in detail below) allows the translating motion of the support assembly 300 to result in a rotating motion of the entertainment device 500.

The suspension assembly 300 is coupled to one of a pair of opposing sides of the unshaped upper portion 114 of frame 110. The suspension assembly 300 includes a mount or mounting bracket 400 that is coupleable to the upper portion 114 of the support frame 110 and a support arm 310 pivotably coupled to the mount 400. As best seen in FIG. 3, mount 400 includes a first side 401 and a second side 402,

which together form a channel 420 for receiving the upper portion 114 of the frame 110. The first and second sides of mounting bracket 400 include openings 422 that receive nuts and bolts 440 to maintain the position of the mount 400 on the support frame 110. Similarly, upper portion 114 and lower portion 112 of the frame 110 include openings 108, 118 respectively that are in registry with openings 422 when the infant support assembly 100 is in the assembled configuration. As can be appreciated, the nuts and bolts 440 can be utilized to secure the upper and lower portion of the frame 110 regardless of whether the mounting bracket 400 is attached. Any other suitable fastener may be used to couple the upper and lower portion of frame 110 and/or to couple mounting bracket 400 to upper portion 114.

The suspension assembly 300 is movable with respect to the mounting bracket between a first position in which the entertainment device 500 is disposed above an infant positioned on the upper seating surface 242, (as illustrated in FIG. 1) and a second position in which the entertainment device 500 is disposed away from the infant (as illustrated in FIG. 2).

The mounting bracket 400 includes a body 408 that extends from the frame 110 and terminates in a socket 410 that receives support arm 310. As best seen in FIG. 4, socket 410 includes a post 420 to guide the support arm 310 into position. The mounting bracket 400 includes a face 430 that is adjacent a face 315 of the support arm 310 when in the assembled configuration. As best seen in FIG. 5, support arm 310 includes a post 370 that mates with socket 410 to maintain the support arm in an upright configuration. The post 370 is able to rotate within socket 410 along an arc defined by stop surfaces 470 in the socket 410 and stop surfaces 390 on the post 370.

In the illustrated embodiment, the mounting bracket 400 is positioned on the upper portion 114 of the frame 110 adjacent the seat 240, between the upper seating surface 242 and the lower foot portion 244. It will be appreciated that the mounting bracket can be positioned at any point along the upper portion 114 of the frame 110 provided that motion of the upper portion 114 imparts a motion to the support arm 310 of the suspension assembly 300. Alternatively, mounting bracket 400 could be coupled to leg support 116.

Further, in the illustrated embodiment, the support arm 310 is pivotally connected with respect to the mounting bracket 400 about an axis disposed at an acute angle with respect to the upper portion of the frame engaged by the connector 400. Accordingly, the support arm 310 extends upwardly in a direction perpendicular to the supporting surface, in a position best viewed by the infant positioned in the seat 240.

The support arm 310 is able to suspend an entertainment device 500 above an infant positioned on the seat 240. As best illustrated in FIG. 6, the support arm 310 terminates at its uppermost end in a post 330 that mates with an opening 525 of a collar on the entertainment device 500. In the illustrated embodiment, the entertainment device 500 is configured as a mobile that rotates about post 330 when the upper portion 114 of the frame 110 is moved with respect to the ground engaging portion 112 of the frame 110. The mobile 500 includes fasteners 530 which support articles 535 that are pleasing and/or soothing to an infant positioned in the seat.

In the illustrated embodiment, support arm 310 extends upwardly from connector or mounting bracket 400 and terminates in a downward direction facing the seat 240. This configuration, along with the flexibility of the support arm 310, allows the desired movement of the entertainment device 500.

As described above, articles 535 are suspended from fasteners 530. The articles may be fixedly coupled to fasteners 530 or may be removably attached by hook and loop type fasteners, mating rings, loops, snaps, buckles, etc.

In use, when an adult user desires to position an infant in the seat 240 or remove an infant from the seat 240, the support arm 310 may be pivoted to its second position as illustrated in FIG. 2. When an infant is positioned in the seat 240, the adult user can pivot the support arm 310 such that entertainment device 500 is positioned above the infant positioned in the seat.

While particular, illustrative embodiments of the invention have been described, numerous variations and modifications exist that would not depart from the scope of the invention. For example, mount 400, as described above, can be attached to the frame by screws as illustrated. However, any connector that enables the support arm 310 to be pivotally coupled to the frame 110 would be appropriate.

The attachment of the entertainment device 500 is described above as being rotatably coupled to the support arm. Alternatively, the entertainment device 500 may be fixedly coupled or coupled to a swivel connector. Additionally, entertainment device 500 need not be configured as a mobile. Entertainment device 500 may take many configurations known to those skilled in the art that are soothing and/or entertaining to children. For example, entertainment device may be a static figure that produces lights and/or sounds.

The various features of the invention have been described in relation to an infant bouncer seat. However it will be appreciated that many of the features, such as the connector and the entertainment device may also be implemented on various infant support devices including car seats, swings, high chairs, etc. Moreover, variations and modifications exist that would not depart from the scope of the invention. A number of these variations have been set forth above.

CONCLUSION

While various embodiments of the present invention have been described above, it should be understood that they have been presented by way of example only, and not limitation. Thus, the breadth and scope of the present invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

The previous description of the preferred embodiments is provided to enable any person skilled in the art to make or use the present invention. While the invention has been particularly shown and described with reference to preferred embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention.

What is claimed is:

1. A support assembly for an infant, comprising:

a resilient support frame having a ground engaging portion and an upper portion, said upper portion including a u-shaped member having two opposing sides and being moveable with respect to the ground engaging portion; [and]

a suspension assembly being coupled to only one of the opposing sides and having a mount coupled to said upper portion of said support frame; [and]

a support arm pivotally coupled to said mount, such that motion of said upper portion imparts motion to said suspension assembly; and

5

an entertainment device suspended from said support arm, the entertainment device comprising a collar, wherein the support arm comprises a post that mates with the collar of the entertainment device and the entertainment device is configured to rotate about the post when the upper portion of the support frame is moved with respect ground engaging portion.

2. The support assembly of claim 1, wherein said mount includes a first portion and a second portion, together defining a channel configured to receive said upper portion of said support frame.

3. The support assembly of claim 2, said mount further including a socket defined by said first portion and said second portion and configured to receive said support arm.

4. The support assembly of claim 1, further comprising an entertainment device suspended from said support arm.]

5. The support assembly of claim 1, further comprising an entertainment device coupled to said suspension assembly, said suspension assembly moveable between a first position disposed above said support frame and a second position disposed away from said support frame;

said entertainment device being positioned over said support frame when said suspension assembly is in said first position.

6. A seat and mobile combination, comprising:

a seat supported on a resilient support frame, said frame having a ground engaging portion and an upper portion, said upper portion including a u-shaped member having two opposing sides and being moveable with respect to the ground engaging portion; [and]

a mobile coupled to only one of the opposing sides of the upper portion by a pivotable connector such that motion of said upper portion imparts a corresponding motion to said mobile, the pivotable connector having a mounting bracket configured to be rigidly coupled to said upper portion of said support frame; and

a support arm pivotally coupled to said mounting bracket, wherein the mounting bracket further includes a socket, the support arm further includes a post that mates with the socket, and the post is configured to rotate within the socket along an arc defined by stop surfaces disposed on at least one of the socket and the post.

7. The seat and mobile combination of claim 6, wherein said mounting bracket includes a first portion and a second portion, together defining a channel configured to receive said upper portion of said support frame.

8. The seat and mobile combination of claim 7, said mounting bracket further including a socket defined by said first portion and said second portion and configured to receive said support arm.

9. The seat and mobile combination of claim 6, further comprising an entertainment device suspended from said support arm.

10. The seat and mobile combination of claim 6, wherein said mobile is moveable between a first position disposed above said support frame and a second position disposed away from said support frame.

11. A support assembly for an infant, comprising:

a support frame;

a seat supported on the support frame and having an upper seating surface upon which an infant can be positioned and a lower foot portion adjacent the upper seating surface; and

a mobile pivotally coupled to the support frame via a mounting bracket including a socket with stop surfaces, said mobile being coupled between the upper seating

6

surface and the lower foot portion, said mobile being pivotable about a vertical axis between a first position disposed above the upper seating surface and a second position disposed away from, and coupled to, the upper seating surface,

wherein the mobile includes a post that mates with the socket, and wherein the stop surfaces define a rotational arc between the first mobile position and the second mobile position.

12. The support assembly of claim 11, wherein said mobile is pivotally coupled to the support frame by a connector having

a mounting bracket; and

a support arm pivotally coupled to said mounting bracket.

13. An apparatus, comprising:

a connector configured to receive a portion of a frame of a support assembly for an infant;

a support arm pivotally coupleable to said connector to extend upwardly from said connector, said support arm being pivotable with respect to said connector about an axis disposed at an acute angle with respect to the portion of the frame received by the connector; and

a mobile coupled to said support arm to be suspended from said support arm,

wherein the connector further includes a socket, the support arm further includes a post that mates with the socket, and the post is configured to rotate within the socket along an arc defined by stop surfaces disposed on at least one of the socket and the post.

14. The apparatus of claim 13, wherein said support arm is moveable between a first orientation disposed opposite the frame and a second orientation disposed away from the frame, said mobile being positioned opposite the frame when the support arm is in said first position.

15. The apparatus of claim 13, wherein said support arm is pivotable about a vertical axis with respect to said connector.

16. The support assembly of claim 1, wherein said support arm is pivotable about a vertical axis with respect to said mount.

17. The seat and mobile combination of claim 6, wherein said support arm is pivotable about a vertical axis with respect to said mounting bracket.

18. An infant swing comprising:

an infant support assembly including a support frame; and

a suspension assembly including:

a support arm coupled to only one side of the support frame, and

an entertainment device coupled to the support arm, wherein the entertainment device comprises a mobile,

wherein motion of the suspension assembly imparts motion to the entertainment device such that the mobile moves relative to the infant support, and wherein the entertainment device is configured such that translational motion of the suspension assembly imparts rotational motion to the mobile.

19. The infant swing of claim 18 further comprising a seat secured to the support frame.

20. The infant swing of claim 18, wherein the motion of the infant support assembly imparts the motion to the suspension assembly.

21. The infant swing of claim 18, wherein the mobile includes articles suspended therefrom.

22. The infant swing of claim 18, wherein the support arm further includes a post coupled to the mobile such that the motion of the infant support assembly rotates the mobile about the post.

7

23. The infant swing of claim 18, wherein the support arm is pivotally coupled to the support frame.

24. The infant swing of claim 19, wherein the support arm is pivotable from a first position, in which the entertainment device is positioned over the seat, to a second position, in which the entertainment device is positioned away from the seat.

25. A suspension assembly for an entertainment device comprising:

a support arm including a first end and a second end;
a mount connected to the first end of the support arm, the mount operable to couple the support arm to a frame portion of an infant support; and

an entertainment device coupled to the second end of the support arm, wherein the suspension assembly is configured such that motion imparted to the suspension assembly imparts a rotating motion to the entertainment device,

wherein the support arm is capable of moving about an axis disposed at an acute angle with respect to the frame portion of the infant support, and wherein the entertainment device comprises a collar, the second end of the support arm comprises a post that mates with the collar, and the entertainment device rotates about the post.

26. The suspension assembly of claim 25, wherein the infant support comprises a swing.

27. The suspension assembly of claim 25, wherein the entertainment device is rotatably coupled to the support arm.

28. The suspension assembly of claim 25, wherein the configuration of the suspension assembly allows translating motion of the suspension assembly to result in the rotating motion of the entertainment device.

29. The suspension assembly of claim 25, wherein:

the mount includes a socket; and
the support arm is pivotally coupled to the socket.

30. The suspension assembly of claim 25, wherein the infant support includes a seat and the support arm is operable to pivot from a first position, in which the entertainment device is positioned over the seat, to a second position, in which the entertainment device is positioned away from the seat.

31. An infant support comprising:

a frame having opposing sides, the frame including:
a base member, and

a movable portion configured to support a seat, wherein the movable portion is configured to move in a translating motion;

a suspension assembly including a support arm coupled to only one of the opposing sides of the frame infant support; and

an entertainment device coupled to the suspension assembly,

wherein the translating motion of the movable portion with respect to the base results in a rotational motion of the entertainment device.

32. The infant support of claim 31, wherein:

the movable portion defines the opposing sides; and

the suspension assembly is coupled to the movable portion.

33. The infant support of claim 32, wherein the motion of the movable portion imparts the motion to the suspension assembly.

34. The infant support of claim 31, wherein the entertainment device comprises a mobile including articles suspended therefrom.

8

35. The infant support of claim 31, wherein the support arm is pivotally coupled to the infant support.

36. The infant support of claim 35, wherein the moveable portion supports a seat, and the support arm is pivotable from a first position, in which the entertainment device is positioned over the seat, to a second position, in which the entertainment device is positioned away from the seat.

37. The infant swing of claim 18, wherein:

the support arm is coupled to the support frame via a mount, and

the support arm is movably coupled to the mount.

38. The infant swing of claim 37, wherein the support arm is pivotally coupled to the mount.

39. The infant swing of claim 38, wherein the support arm is pivotable about a vertical axis.

40. The suspension assembly of claim 25, wherein the support arm moves about a vertical axis.

41. The infant support of claim 32, wherein the support arm is movable with respect to the movable portion.

42. The infant support of claim 41, wherein the support arm is:

coupled to the movable portion via a mount; and

capable of pivoting with respect to the mount.

43. The infant support of claim 42, wherein:

the mount receives a section of the movable portion; and

the support arm pivots about an axis disposed at an acute angle with respect to the section of the movable portion received by the mount.

44. A support assembly for an infant comprising:

an infant swing comprising opposing sides; and

a suspension assembly including:

a support arm coupled to only one of the opposing sides of the swing, and

an entertainment device coupled to the support arm, the entertainment device comprising a collar,

wherein motion of the suspension assembly imparts rotary motion to the entertainment device, and wherein the support arm comprises a post that mates with the collar of the entertainment device and the motion of the suspension assembly rotates the collar about the post.

45. The support assembly of claim 44, wherein:

the support arm is coupled to the swing via a mount; and

the support arm is movably coupled to the mount.

46. The support assembly of claim 45, wherein the support arm pivots with respect to the mount.

47. The support assembly of claim 46, wherein the support arm pivots about a vertical axis.

48. The support assembly of claim 44, wherein the support assembly is configured such that motion of the swing imparts the rotary motion to the suspension assembly.

49. The support assembly of 44, wherein:

the infant swing comprises a support frame defining the opposing sides; and

the suspension assembly is coupled to only one side of the opposing sides of the support frame.

50. The apparatus of claim 13, wherein:

the support arm comprises a second post; and

the mobile is configured to rotate about the second post.

51. The infant support of claim 31, wherein:

the entertainment device comprises a collar;

the support arm comprises a post that mates with the collar; and

the entertainment device rotates about the post as the movable portion moves in the translating motion.

9

52. A suspension assembly for an entertainment device comprising:

a support arm including a first end and a second end;

a mount connected to the first end of the support arm, the mount operable to couple the support arm to a frame portion of an infant support; and

an entertainment device coupled to the second end of the support arm,

wherein the suspension assembly is configured such that motion imparted to the suspension assembly imparts a

10

rotating motion to the entertainment device, and wherein the configuration of the suspension assembly allows translating motion of the suspension assembly to result in the rotating motion of the entertainment device,

wherein the support arm is capable of moving about an axis disposed at an acute angle with respect to the frame portion of the infant support.

* * * * *