

US00RE41175E

(19) **United States**
(12) **Reissued Patent**
Vashisth et al.

(10) **Patent Number:** **US RE41,175 E**
(45) **Date of Reissued Patent:** **Mar. 30, 2010**

(54) **GPS-ENHANCED SYSTEM AND METHOD FOR AUTOMATICALLY CAPTURING AND CO-REGISTERING VIRTUAL MODELS OF A SITE**

(75) Inventors: **Robert M. Vashisth**, Salt Lake City, UT (US); **James U. Jensen**, Salt Lake City, UT (US); **James W. Bunger**, Salt Lake City, UT (US)

(73) Assignee: **Intelisum, Inc.**, Salt Lake City, UT (US)

(21) Appl. No.: **11/480,248**

(22) Filed: **Jun. 30, 2006**

6,307,556	B1	10/2001	Ellenby et al.
6,330,523	B1	12/2001	Kacyra et al.
6,420,698	B1	7/2002	Dimsdale
6,473,079	B1	10/2002	Kacyra et al.
6,526,352	B1	2/2003	Breed et al.
6,664,529	B2 *	12/2003	Pack et al. 250/208.1
6,759,979	B2	7/2004	Vashisth et al.
2001/0010546	A1	8/2001	Chen
2002/0060784	A1	5/2002	Pack et al.
2003/0090415	A1	5/2003	Miyasaka et al.
2004/0105573	A1	6/2004	Neumann et al.
2005/0057745	A1	3/2005	Bontje

FOREIGN PATENT DOCUMENTS

WO	WO97/40342	A2 *	10/1997
WO	WO 01/04576		1/2001
WO	WO 01/88565		11/2001
WO	WO 01/88566		11/2001
WO	WO 01/88741		11/2001
WO	WO 01/88849		11/2001
WO	WO 02/16865		2/2002
WO	WO 97/40342		10/2006

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,759,979**
Issued: **Jul. 6, 2004**
Appl. No.: **10/348,275**
Filed: **Jan. 21, 2003**

U.S. Applications:

(60) Provisional application No. 60/350,860, filed on Jan. 22, 2002.

(51) **Int. Cl.**
G01S 5/14 (2006.01)
G06T 15/00 (2006.01)
G09G 5/00 (2006.01)
H04N 5/225 (2006.01)

(52) **U.S. Cl.** **342/357.13; 345/419; 345/629; 348/218.1**

(58) **Field of Classification Search** **342/357.13; 345/419, 629; 348/218.1**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,337,149	A	8/1994	Kozah et al.
5,988,862	A	11/1999	Kacyra et al.
6,166,744	A	12/2000	Jaszlics et al.
6,246,468	B1	6/2001	Dimsdale
6,249,600	B1	6/2001	Reed et al.
6,292,215	B1	9/2001	Vincent

OTHER PUBLICATIONS

Allen, P. et al, Avenue: automated site modeling in urban environments—3-D Digital Imaging and Modeling, 2001. Proceedings. Third International Conference on, 2001, pp. 357–364.*


(Continued)

Primary Examiner—Gregory C Issing
(74) *Attorney, Agent, or Firm*—Austin Rapp & Hardman

(57) **ABSTRACT**

A system for capturing a virtual model of a site includes a range scanner for scanning the site to generate range data indicating distances from the range scanner to real-world objects. The system also includes a global positioning system (GPS) receiver coupled to the range scanner for acquiring GPS data for the range scanner at a scanning location. In addition, the system includes a communication interface for outputting a virtual model comprising the range data and the GPS data.

43 Claims, 11 Drawing Sheets



OTHER PUBLICATIONS

- Gueorguiev, A. et al, "Design, architecture and control of a mobile site-modeling robot"—Robotics and Automation, 2000. Proceedings. ICRA '00. IEEE International Conference on, pp. 3266–3271.*
- Besl, Paul, "Geometric modeling and computer vision"—Proceedings of the IEEE, vol. 76, No. 8, Aug. 1988, pp. 936–958.*
- Kropp, A. et al, OMNIVIS'00: "Acquiring and Rendering High-Resolution Spherical Mosaics", pp. 1–7.*
- Berladin, J.-A. et al, "Object Model Creation From Multiple Range Images: Acquisition, Calibration, Model Building And Verification," 3-D Digital Imaging and Modeling, 1997. Proceedings., International Conference on Recent Advances, pp. 326–333.*
- Beraldin, J.-A. et al, "Portable Digital 3-d Imaging System For Remote Sites"—Circuits and Systems, 1998. ISCAS '98. Proceedings of the 1998 IEEE International Symposium on, pp. V488–V493.*
- Li, Rongxing, "Mobile Mapping—An Emerging Technology For Spatial Data Acquisition," Dept. of Civil and Environmental Engineering and Geodetic Science, The Ohio State University, 2000, pp. 1–23.*
- Kamgar-Parsi et al, "Registration Algorithms For Geophysical Maps"—Oceans '97, MTS/IEEE Conference Proceedings, pp. 974–980.*
- Soucy, M. et al, "A general surface approach to the integration of a set of range views"—Pattern Analysis and Machine Intelligence, vol. 17, No. 4,, IEEE Transactions on, Apr. 1995, pp. 34–358.*
- Hans J. Johnson, et al., "Consistent Landmark and Intensity-based Image Registration," IEEE Transactions on Medical Imaging, p. 126, 2002.
- David T. Gering, et al., An Integrated Visualization System for Surgical Planning and Guidance using Image Fusion and Interventional Imaging, MIT AI Laboratory, 1999.
- Yu Lifeng, et al., "Multi-Modality Medical Image Fusion Based on Wavelet Pyramid and Evaluation," Peking University, Beijing China, 1994.
- Faysal Boughorbal, et al., "Registration and Integration of Multi-Sensor Data for Photo-realistic Scene Reconstruction," Applied Imagery Pattern Recognition, Sponsored by SPIE, Washington, DC, Oct. 13–15, 1999.
- Nathaniel Williams, et al., "Automatic Image Alignment for 3D Environment Modeling," Department of Computer Science, University of North Carolina at Chapel Hill, 2004.
- D. Akca, "Registration of Point Clouds Using Range and Intensity Information," International Workshop on Recording, Modeling and Visualization of Cultural Heritage, 2005.
- Kia Ng, et al., "An Integrated Multi-Sensory System for photo-Realistic 3D Scene Reconstruction," ISPRS Comm, p. 356–363, 1998.
- Fiorella Sgallari, "Numerical Solution of Inverse Problems in Image Processing," University of Bologna, Presented at Association for Computing Machinery Conference, Jan. 13, 2006.
- Paul Rademacher, "Ray Tracing: Graphics for the Masses," ACM, New York, vol. 3, Issue 4, p. 3–7, 1997.
- "Open Scene Graph Home Page," <http://www.openscenegraph.org/osgwiki/pmwiki.php/Home/HomePage>, Jan. 25, 2007.
- Geoff Jacobs, "Field Productivity Factors in Laser Scanning, Part 1," Professional Surveyor Magazine, Jan. 2007.
- Naser El-Sheimy, et al., "Digital Terrain Modeling, Acquisition, Manipulation, and Applications," Artech House, Inc., p. 117–119, 184–186, 2005.
- Google Search, "Medical Image Fusion," <http://www.google.com/search?hl=cn&q=medical+image+fusion&btnG...>, Jul. 7, 2006.
- "Image Guidance Laboratories," Complete Laboratory Publications, <http://www-igl.stanford.edu/papers.php?pg=main...>, Jul. 7, 2006.
- "Keith Price Bibliography Fusion of Medical Data," <http://iris.usc.edu/Vision-Notes/bibliography/match-p1504.html>, Jul. 7, 2006.
- "iPhotoMeasure—The Contractors Photo Measuring Tool," <http://www.iphotomeasure.com/faq.asp>, Jan. 25, 2007.
- "Selected Papers on Image Registration, Image Fusion Systems Research," http://www.imgfsr.com/ifsr_irb.html, Jul. 7, 2006.
- Nhat Xuan Nguyen, "Numerical Algorithms for Image Supreresolution," <http://citeseer.ist.psu.edu/nguyen00numerical.html>, 2000.
- Andrew Johnson, et al. "Registration and Integration of Textured 3-D Data," Bibliography, 1996.
- Nathaniel Williams, et al., "Automatic Image Alignment for 3D Environment Modeling," Bibliography, Presented at the Siggraph conference, Aug. 11, 2004.
- Richard A. Robb, et al., "Adaptive Piece-wise. Registration for Automated Fusion of Point Cloud Coordinates and Anatomic Volume Images," <http://www.mayoclinictechnology.com/tc/software/MMV-04-247-565.html>, 2004.
- Armin Gruen, et al., "Least Squares 3D Surface and Curve Matching," Elsevier, ISPRS Journal of Photogrammetry & Remote Sensing 59, Feb. 16, 2005.
- "Automated Registration and Evaluation of Laser Scanner Point Clouds and Images, Automatic Point Cloud Registration Using Template Shaped Targets," <http://www.photogrammetry.ethz.ch/research/pointcloud/withtargets.html>, Aug. 25, 2004.
- "Automated Registration, 3DD Optix 400 Series," 3D Digital Corp., Apr. 2004.
- "Leica Cyclone 5.6 Register," Leica Geosystems, Heerbrugg, Switzerland, 2006.
- S.T. Dijkman, et al., "Semi Automatic Registration of Laser Scanner Data," International Archives of Photogrammetry Remote Sensing and Spatial Information Sciences, Natural Resources, Canada, vol. 34, Part 5, . 12–17, 2002.
- Christoph Dold, "Extended Gaussian Images for the Registration of Terrestrial Scan Data," Institute of Cartography and Geoinformatics, Workshop "Laser Scanning 2005," Sep. 1214, 2005.
- Natasha Gelfand, et al., "Robust Global Registration," Eurographics Symposium on Geometry Processing, 2005.
- Christoph Dold, et al., "Automatic Matching of Terrestrial Scan Data as a Basis for the Generation of Detailed 3D City Models," International Archives of Phtotogrammetry Remote Sensing and Spatial Information Sciences, vol. 35, Part 3, p. 1091–1096, 2004.
- Kwang-Ho Bae, et al., "Automated registration of Unorganised Point Clouds from Terrestrial Laser Scanners," Department of Spatial Sciences, Curtin University of Technology, Perth, Australia, 2004.
- Ameesh Makadia, et al., "Fully Automatic Registration of 3D Point Clouds," Proceedings of the 2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, 2006.

- Pedro F. Felzenswalb, et al., "Pictorial Structures for Object Recognition," Artificial Intelligence Lab, Massachusetts Institute of Technology, Computer Science Department, Cornell University, 2003.
- Helmut Pottmann, et al., "Registration without ICP," Geometric Modeling and Industrial Geometry Group, Vienna University of Technology, Mar. 5, 2004.
- Matthew P. Tait, "Point Cloud registration: Current State of the Science," Schulich School of Engineering, University of Calgary, Mar. 27, 2006.
- Steven Alexander Sablerolle, "Automatic Registration of Laser Scanning Data and Colour Images," TUDelft, Oct. 2006.
- Ayman F. Habib, et al., "Automatic Surface Matching for the Registration of LIDAR Data and MR Imagery," ETRI Journal, vol. 28, No. 2, Apr. 2006.
- Peter K. Allen, et al., "3D Modeling of Historic Sites Using Range and Image Data," Dept. of Computer Science, Columbia University, Dept. of Computer Science, Hunger College, May 16, 2008.
- Steven Alexander Sablerolle, "Automatic Registration of Laser Scanning Data and Colour Images," TU Delft, Faculty of Civil Engineering, Final Presentation Msc. Geomatics, Oct. 31, 2006.
- Steven Sablerolle, "Graduation Research Report," TU Delft, Sep. 2006.
- Mehdi Bouroumand, et al., "The Fusion of Laser Scanning and Close Range Photogrammetry in Bam Laser-Photogrammetric Mapping of Bam Citadel (Arg-E-Bam)/Iran," KNT University in Tehran, 2004.
- Isi-Gi, Dec. 21, 2006.
- "HLODs: Hierarchical Levels of Detail, hierarchical Simplification for Faster Display of Massive Geometric environments," Department of Computer Science, University of North Carolina at Chapel Hill, Feb. 2004.
- Wikipedia, the free encyclopedia, "Level of Detail," [http://en.wikipedia.org/wiki/Level_of_detail_\(programming\)](http://en.wikipedia.org/wiki/Level_of_detail_(programming)), May 23, 2008.
- Tahir Rabbani Shah, "Automatic Reconstruction of Industrial Installations Using Point Clouds and Images," Geodesy 6.2, Nederlandse Commissie voor Geodesie Netherlands Geodetic Commission, Delft, May 2006.
- T. Rabbani, et al., "Segmentation of Point clouds Using Smoothness Constraint," ISPRS Commission V Symposium 'Image Engineering and Vision Metrology,' 2006.
- Tahir Rabbani, et al., "Efficient Hough Transform for Automatic detection of Cylinders in Point Clouds," Workshop "Laser Scanning 2005," Enschede, the Netherlands, Sep. 12-14, 2005.
- B. Vangelder, et al., "Modern Technologies for Design Data Collection." Civil Engineering, Joint Transportation Research Program, Purdue Libraries, 2005.
- Dinesh Manadhar, "Extraction of linear features from vehicle-borne laser data," Remote Sensing, Singapore, vol. 2, p. 113-1118, Nov. 5-9, 2001.
- Hendrik P. A. Lensch, et al., "Automated Texture Registration and Stitching for Real World Models," Max-Planck-Institute for Computer Science, Saarbrücken, Germany, 2000.
- "A Point-and-Shoot Color 3D Camera," Askold V. Strat, Manuel M. Oliveira, Proceedings of the Fourth International Conference on 3-D Digital Imaging and Modeling, 2003, pp. 1-8.
- "Adaptive Enhancement of 3D Scenes using Hierarchical Registration of Texture-Mapped 3D models," Srikumar Ramalingam and Suresh K. Lodha, Proceedings of the Fourth International Conference on 3-D Digital Imaging and Modeling, 2003, pp. 1-8.
- "Automatic Registration of Range Images Based on Correspondence of Complete Plane Patches," Wenfeng He, Wei Ma, Hongbin Zha, Proceedings of the Fifth International Conference on 3-D Digital Imaging and Modeling, 2005, pp. 1-6.
- "A Multi-Resolution ICP with Heuristic Closest Point Search for Fast and Robust 3D Registration of Range Images," Timothée Jost and Heinz Hügli, Proceedings of the Fourth International Conference on 3-D Digital Imaging and Modeling, 2003, pp. 1-7.
- "Effective Nearest Neighbor Search for Aligning and Merging Range Images," Ryusuke Sagawa et al., Proceedings of the Fourth International Conference on 3-D Digital Imaging and Modeling, 2003, pp. 1-8.
- "Enhanced, Robust Genetic Algorithms for Multiview Range Image Registration," Luciano Silva et al., Proceedings of the Fourth International Conference on 3-D Digital Imaging and Modeling, 2003, pp. 1-8.
- "Non-parametric 3D Surface Completion," Toby P. Breckon, Robert B. Fisher, Proceedings of the Fifth International Conference on 3-D Digital Imaging and Modeling, 2005, pp. 1-8.
- "Projective Surface Matching of Colored 3D Scans," Kari Pulli et al., Proceedings of the Fifth International Conference on 3-D Digital Imaging and Modeling, 2005, pp. 1-8.
- "Combining texture and shape for automatic crude patch registration," Joris Vanden Wyngaerd et al., Proceedings of the Fourth International Conference on 3-D Digital Imaging and Modeling, 2003, pp. 1-8.
- "Automated reconstruction of 3D models from real environments," V. Sequeira, K. Ng, E. Wolfart, J.G.M. Gonçalves, D. Hogg, ISPRS Journal of Photogrammetry & Remote Sensing 54, 1999, pp. 1-22.
- "3D Reality Modelling: Photo-Realistic 3D Models of Real World Scenes," Vitor Sequeira, João G.M. Gonçalves, Proceedings of the First International Symposium on 3D Data Processing Visualization and Transmission, 2002, pp. 1-8.
- "An Integrated Multi-Sensory System for Photo-Realistic 3D Scene Reconstruction," Kia Ng et al., School of Computer Studies, University of Leeds, European Commission—Joint Research Centre, pp. 1-9.
- "Lecture Notes In Computer Science," <http://portal.acm.org/toc.cfm?id=645595&type=proceeding&coll=GUI...>, Jul. 6, 2006, pp. 1-6.
- "2-D and 3-D Image Registration: A Tutorial," http://www.cs.wright.edu/~agoshtas/CVPR04_Registration_Tutorial.html, Jul. 7, 2006, pp. 1-3.
- "Medical Image Processing," <http://www.sce.carleton.ca/faculty/adler/elg7173/elg7173.html>, Jul. 7, 2006, pp. 1-5.
- "Gaussian Random Fields on Sub-Manifolds for Characterizing Brain Surfaces," <http://portal.acm.org/citation.cfm?id=645595.660540&coll=GUIDE&d...>, Jul. 6, 2006, pp. 1-3.
- "Image Image-Guided Interventions Workshop Guided Interventions Workshop," John Haller, National Institute of Biomedical Imaging and Bioengineering, May 13, 2004-May 14, 2004, pp. 2-11.
- "Workshop on symmetries, inverse problems and image processing," <http://www.indmath.uni-linz.ac.at/people/bila/Workshop.html>, Jan. 12, 2005, pp. 1-4.

- “Automatic” Multimodal Medical Image Fusion,” <http://csdl2.computer.org/persagen/DLAbsToc.jsp>, Jul. 7, 2006, pp. 1.
- “Consistent Linear–Elastic Transformations for Image Matching,” Gary E. Christensen, A. Kuba et al. (Eds.): IPIM’99, LNCS 1613, 1999, pp. 224–237.
- “Edge and Line Detection Image Fusion Systems Research,” http://www.imgfsr.com/ifsr_is_ed.html, Jul. 7, 2006, pp. 1–8.
- “Fast Normalized Cross–Correlation,” <http://www.idiom.com/~zilla/Work/nvisionInterface/nip.htm>, Jul. 7, 2006, pp. 1–11.
- “A simple MATLAB interface to FireWire cameras,” F. Wörnle, May 2006, pp. 1–25.
- “Fusion and interpretation of medical images,” <http://www.research.ibm.com/hc/VISUALIZE/visualize.html>, Jul. 7, 2006, pp. 1–3.
- “Project: Fully Automated Registration and Composite Generation of Multisensor and Multidate Satellite Image Data,” <http://vision.ece.ucsb.edu/registration/satellite/>, Jul. 7, 2006, pp. 1–2.
- “Infrastructure for Image Guided Surgery,” John W. Haller, Timothy C. Ryken, Thomas A. Gallagher and Michael W. Vannier, National Institute of Neurological Disease and Stroke, Jun. 28, 2001, pp. 1–6.
- “Reliability of Functional MRI for Motor and Language Cortex Activation,” http://dolphin.radiology.uiowa.edu/ge/BME/public_html/projects/project, Jul. 6, 2006, pp. 1.
- “Investigations of Image Fusion,” http://www.ece.lehigh.edu/SPCRL/IF/image_fusion.htm, Jul. 7, 2006, pp. 1–13.
- “Image Registration and Mosaicking,” <http://prettyview.com/mtch/mtch.shtml>, Jul. 7, 2006, pp. 1.
- “Image Fusion Systems Research,” <http://www.imgfsr.com/>, Jul. 7, 2006, pp. 1–2.
- “Medical image fusion by wavelet transform modulus maxima,” Guihong Qu, Dali Zhang and Pingfan Yan, Department of Automation, Tsinghua University, Beijing 100084, China, May 10, 2001, pp. 184–190.
- “Multi–modality image registration using mutual information based on gradient vector flow,” Yujun Guo, May 1, 2006, pp. 1–31.
- “Medical Image Fusion,” <http://www.uihealthcare.com/news/currents/vol1issue1/figimfus.html>, Jul. 6, 2006, pp. 1–4.
- “Image Fusion—a new era in diagnosis,” Dr Michael Kitchener, Imaging Update, Issue 8, Apr. 2002, pp. 1–4.
- “Future standard,” http://www.medicalimagingmag.com/issues/articles/2000-08_01.asp, Jul. 7, 2006, pp. 1.
- “A Contour–Based Approach to Multisensor Image Registration,” Hui Li, B. S. Manjunath, Sanjit K. Mitra, IEEE Transactions On Image Processing, vol. 4, No. 3, Mar. 1995, pp. 320–334.
- “Multi–Sensor Image Fusion Using the Wavelet Transform,” Hui Li, B.S. Manjunath, Sanjit K. Mitra, IEEE, 1994, pp. 51–55.
- “Advanced Nonrigid Registration Algorithms for Image Fusion,” Simon K. Warfield et al., Brain Mapping: The Methods, Second Edition, 2002, pp. 661–690.
- “Robust Detection of Significant Points in Multiframe Images,” <http://staff.utia.cas.cz/zitova/corners.htm>, Jul. 7, 2006, pp. 1–5.
- “A Survey of Medical Image Registration,” J. B. Antoine Maintz and Max A. Viergever, Image Sciences Institute, Utrecht University Hospital, Utrecht, the Netherlands, Oct. 16, 1997, pp. 1–37.
- “The Registration of Three Dimensional Images from one or more Imaging Modalities,” <http://www.biomed.abdn.ac.uk/Abstracts/A00331/>, Jul. 7, 2006, pp. 1–11.
- “Inverse Problems: Image Restoration and Parameter Identification,” <http://www.mit.jyu.fi/majkir/tutkimus/index.html>, Tommi Kärkkäinen and Kirsi Majava, University of Jyväskylä Dept. of Mathematical Information Technology, Aug. 2, 2004, pp. 1–3.
- “Registration and Integration of Textured 3–D Data,” Andrew Johnson and Sing Bing Kang, Digital Equipment Corporation Cambridge Research Lab, Sep. 1996, pp. 1–48.
- “Alignment by Maximization of Mutual Information,” Paul A. Viola, Massachusetts Institute of Technology, 1995, pp. 1–156.
- “Feature point detection in multiframe images,” Barbara Zitova et al., Czech Pattern Recognition Workshop 2000, Feb. 2, 2000–Feb. 4, 2000, pp. 1–6.
- “Image registration methods: a survey,” Barbara Zitova et al., Department of Image Processing, Institute of Information Theory and Automation, Academy of Sciences of the Czech Republic, Jun. 26, 2003, pp. 977–1000.
- “Image–Based Registration of 3D–Range Data Using Feature Surface Elements,” Gerhard Heinrich Bendels et al., Institute for Computer Science II—Computer Graphics, University of Bonn, Germany, 2004, pp. 1–10.
- “Fully automatic registration of multiple 3D data sets,” Daniel F. Huber, Martial Hebert, Image and Vision Computing 21, 2003, pp. 637–650.
- “Least Squares 3D Surfaces Matching,” Armin Gruen, Devrim Akca, Geospatial Goes Global: From Your Neighborhood to the Whole Planet, ASPRS 2005 Annual Conference, Mar. 7, 2005–Mar. 11, 2005, pp. 1–13.
- “A flexible mathematical model for matching of 3D surfaces and attributes,” Devrim Akca, Armin Gruen, Electronic Imaging, SPIE vol. 5665, 2005, pp. 184–195.
- “3D Modeling of Outdoor Environments by Integrating Omnidirectional Range and Color Images,” Toshihiro ASAI et al., Proceedings of the Fifth International Conference on 3–D Digital Imaging and Modeling, 2005, pp. 1–8.
- “Correction of color information of a 3D model using a range intensity image,” Kazunori Umeda et al., Proceedings of the Fifth International Conference on 3–D Digital Imaging and Modeling, 2005, pp. 1–8.
- “Registration and Fusion of Intensity and Range Data for 3D Modelling of Real World Scenes,” Paulo Dias et al., Proceedings of the Fourth International Conference on 3–D Digital Imaging and Modeling, 2003, pp. 1–8.
- “Construction of Large–Scale Virtual Environment by Fusing Range Data, Texture Images, and Airborne Altimetry Data,” Conny Riani Gunadi et al., Proceedings of the First International Symposium on 3–D Data Processing Visualization and Transmission, 2002 pp. 1.
- “Semi–automatic range to range registration: a feature–based method,” Chen Chao et al., Proceedings of the Fifth International Conference on 3–D Digital Imaging and Modeling, 2005, pp. 1–8.
- “Fast Alignment of 3D Geometrical Models and 2D Color Images using 2D Distance Maps,” Yumi Iwashita et al., Proceedings of the Fifth International Conference on 3–D Digital Imaging and Modeling, 2005, pp. 1–8.

“Evaluating Collinearity Constraint for Automatic Range Image Registration,” Yonghuai Liu et al., Proceedings of the Fifth International Conference on 3-D Digital Imaging and Modeling, 2005, pp. 1–8.

“Image-Based Object Editing,” Holly Rushmeier et al., Proceedings of the Fourth International Conference on 3-D Digital Imaging and Modeling, 2003, pp. 1–8.

“Construction of Large-Scale Virtual Environment by Fusing Range Data, Texture Images, and Airborne Altimetry Data,” Conny Riani Gunadi et al., Proceedings of the First International Symposium on 3-D Data Processing Visualization and Transmission, 2002, pp. 1–4.

Klein, Konrad et al, “View Planning for the 3D Modelling of Real World Scenes,” Proc. of the 2000 IEEE/RSJ International Co on Intelligent Robots and Systems, pp. 943–948.*

Sato, Yukio et al, “Three-Dimensional Shape Reconstruction by Active Rangefinder,” Proc. CVPR., IEEE Computer Society Conf. on Computer Vision and Pattern Recognition, Jun. 1993, pp. 142–147.*

Modeling and Rendering of Real Environments by Wagner T. Correa et al.; RITA, vol. IX, Numero 1, Aug. 2002; pp. 1–32.*

Scanalyze: a system for aligning and merging range data; <http://graphics.stanford.edu/software/scanalyze>; dated Dec. 9, 2002; pp. 1–7.*

Zippered Polygon Meshes from Range Images by Greg Turk et al.; Proc. SIGGRAPH '94, Jul. 1994; pp. 1–8.*

A Volumetric Method for Building Complex Models from Range Images by Brian Curless et al.; Proc. SIGGRAPH '96, Aug. 1995; pp. 1–10.*

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

**GPS-ENHANCED SYSTEM AND METHOD
FOR AUTOMATICALLY CAPTURING AND
CO-REGISTERING VIRTUAL MODELS OF A
SITE**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

CROSS REFERENCE TO RELATED
APPLICATIONS

[The application] *Notice: More than one reissue application has been filed for the reissue of Pat. No. 6,759,979. The reissue applications are application No. 11/480,248 (the present application filed on Jun. 30, 2006) and application No. 12/362,954 (filed on Jan. 30, 2009), all of which are reissue or divisional reissue applications of Pat. No. 6,759,979. The present application is a reissue application of U.S. Pat. No. 6,759,979 (application No. 10/348,275), which claims the benefit of U.S. Provisional Application No. 60/350,860, filed on Jan. 22, 2002, for "System and Method for Generating 3-D Topographical Visualizations," with inventors Munish Vashisth and James U. Jensen, [which] each application [is] identified above being incorporated herein by this reference in its entirety.*

BACKGROUND

1. Field of the Invention

The present invention relates generally to three-dimensional modeling. More specifically, the present invention relates to a system and method for capturing three-dimensional virtual models of a site that can be co-registered and visualized within a computer system.

2. Description of Related Background Art

Lidar (light detection and ranging) uses laser technology to make precise distance measurements over long or short distances. One application of lidar is the range scanner, or scanning lidar. In a typical range scanner, a lidar is mounted on a tripod equipped with a servo mechanism that continuously pans and tilts the lidar to scan a three-dimensional area. During the scanning process, the lidar makes repeated range measurements to objects in its path. The resulting range data may be collected and serve as a rough model of the scanned area.

Physical limitations of the range scanner constrain the maximum resolution of the range data, which decreases with distance from the range scanner. At large distances, the range scanner may not be able to discern surface details of an object. A lack of continuous spatial data (gaps between points) and a lack of color attributes are significant limitations of conventional range scanners. Furthermore, a range scanner only scans objects within the lidar's line-of-sight. As a result, no data is collected for the side of an object opposite to the lidar or for objects obscured by other objects ("occlusions").

To obtain a more complete and accurate model, the range scanner can be moved to other scanning locations in order to scan the same area from different perspectives and thereby obtain range data for obscured objects. Thereafter, the resulting sets of range data can be merged into a single model.

Unfortunately, the merging of sets of range data is not automatic. Human decision-making is generally required at several steps in the merging process. For instance, a human surveyor is typically needed to determine the relative dis-

tances between the range scanning locations and the scanned area. Furthermore, a human operator must manually identify points in common ("fiducials") between multiple sets of range data in order to align and merge the sets into a single model. Such identification is by no means easy, particularly in the case of curved surfaces. The need for human decision-making increases the cost of modeling and the likelihood of error in the process.

SUMMARY OF THE INVENTION

A system for capturing a virtual model of a site includes a range scanner for scanning the site to generate range data indicating distances from the range scanner to real-world objects. The system also includes a global positioning system (GPS) receiver coupled to the range scanner for acquiring GPS data for the range scanner at a scanning location. In addition, the system includes a communication interface for outputting a virtual model comprising the range data and the GPS data.

The system may further include a transformation module for using the GPS data with orientation information, such as bearing, for the range scanner to automatically transform the range data from a scanning coordinate system to a modeling coordinate system, where the modeling coordinate system is independent of the scanning location. A co-registration module may then combine the transformed range data with a second set of transformed range data for the same site generated at a second scanning location.

The system also includes a digital camera coupled to the range scanner for obtaining digital images of the real-world objects scanned by the range scanner. The system may associate the digital images of the real-world objects with the corresponding range data in the virtual model.

A system for building a virtual model of a site includes a communication interface for receiving a first set of range data indicating distances from a range scanner at a first location to real-world objects. The communication interface also receives a first set of GPS data for the range scanner at the first location. The system further includes a transformation module for using the first set of GPS data with orientation information for the range scanner to automatically transform the first set of range data from a first local coordinate system to a modeling coordinate system.

A system for modeling an object includes a range scanner for scanning an object from a first vantage point to generate a first range image. The system further includes a GPS receiver for obtaining GPS readings for the first vantage point, as well as a storage medium for associating the first range image and the GPS readings within a first virtual model.

The range scanner may re-scan the object from a second vantage point to generate a second range image. Likewise, the GPS receiver may acquire updated GPS readings for the second vantage point, after which the storage medium associates the second range image and the updated GPS readings within a second virtual model. A transformation module then employs the GPS readings of the virtual models with orientation information for the range scanner at each location to automatically transform the associated range images from local coordinate systems referenced to the vantage points to a single coordinate system independent of the vantage points.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-exhaustive embodiments of the invention are described with reference to the figures, in which:

3

FIG. 1 is a high-level overview of a system for capturing and co-registering virtual models;

FIG. 2 is a detailed block diagram of the system of FIG. 1;

FIG. 3 is a schematic illustration of capturing one or more virtual models of a site at each of a number of positions or vantage points;

FIG. 4 is a schematic illustration of three sets of range data;

FIG. 5 is a representation of a scanning coordinate system;

FIG. 6 is a schematic illustration of transforming range data from various scanning coordinate systems to a single modeling coordinate system;

FIG. 7 is a schematic illustration of generating a combined or transformed virtual model;

FIG. 8 is a schematic illustration of generating a merged virtual model;

FIG. 9 is a schematic illustration of generating an interactive, three-dimensional visualization;

FIG. 10 is a flowchart of a method for capturing and co-registering virtual models of a site; and

FIG. 11 is a schematic illustration of generating an area model based on scans of multiple sites.

DETAILED DESCRIPTION

Reference is now made to the figures in which like reference numerals refer to like elements. For clarity, the first digit of a reference numeral indicates the figure number in which the corresponding element is first used.

In the following description, numerous specific details of programming, software modules, user selections, network transactions, database queries, database structures, etc., are provided for a thorough understanding of the embodiments of the invention. However, those skilled in the art will recognize that the invention can be practiced without one or more of the specific details, or with other methods, components, materials, etc. In some cases, well-known structures, materials, or operations are not shown or not described in detail to avoid obscuring aspects of the invention. Furthermore, the described features, structures, or characteristics may be combined in any suitable manner in one or more embodiments.

FIG. 1 is a high-level overview of a modeling system 100 according to an embodiment of the invention. A range scanner 102 includes a lidar 103 for scanning a site 104 to generate range data, i.e., distance measurements from the range scanner 102 to real-world objects within the site 104. The site 104 may be any indoor or outdoor three-dimensional region that includes one or more objects to which distance measurements can be made using the lidar 103.

The location and dimensions of the site 104 may be defined by an operator 105 using a control device, such as a personal data assistant (PDA) 106, computer 108, or the like, which may communicate with the range scanner 102 using any wired or wireless method. The operator 105 may specify, for instance, the degree to which the range scanner 102 pans and tilts during scanning, effectively determining the dimensions of the site 104.

In one embodiment, the range scanner 102 is equipped with a high-resolution, high-speed digital camera 110 for obtaining digital images of the site 104 during the scanning process. As explained more fully below, the digital images may be later used to apply textures to a polygon mesh created from the range data, providing a highly realistic three-

4

dimensional visualization 112 of the site 104 for display on a computer monitor 114 or other display device.

The range scanner 102 also includes a global positioning system (GPS) receiver 116 for acquiring GPS data relative to the range scanner 102 at the location of scanning. The GPS data may include, for example, the latitude, longitude, and altitude of the range scanner 102. In other embodiments, the GPS data may include Universal Transverse Mercator (UTM) coordinates, Earth-Centered/Earth-Fixed (ECEF) coordinates, or other Earth-based locators. A GPS receiver 116 relies on three or more orbiting satellites 118 for triangulation and, in some configurations, can provide readings accurate to within a few centimeters.

In one embodiment, the range scanner 102 sends the range data, digital images, and GPS data to a computer 108, where they are used to create the visualization 112. The visualization 112 may be interactive, e.g., a user may "walk through" the site 104 depicted in the visualization 112. In addition, the user may delete or move objects depicted in the visualization 112 or modify the visualization 112 in other ways. Such visualizations 112 are highly beneficial in the fields of architecture, landscape design, land use, erosion control, etc.

FIG. 2 is a detailed block diagram of the system 100 of FIG. 1. As noted above, the range scanner 102 includes a lidar 103, a digital camera 110, and a GPS receiver 116. The lidar 103 may be embodied, for instance, as an LMS 291, available SICK AG of Waldkirch, Germany, although various other models are contemplated.

The digital camera 110 may include a PowerShot G2™ camera available from Canon, Inc. In one configuration, the digital camera 110 is capable of capturing images with a resolution of 2272×1704 pixels at a rate of approximately 2.5 images per second. The digital camera 110 may be included within, attached to, or otherwise integrated with the range scanner 102. In alternative embodiments, the range scanner 102 includes multiple digital cameras 110.

The GPS receiver 116 may be embodied as a standard mapping-grade receiver, which may support L-band differential GPS (DGPS). Where higher accuracy is needed, survey-grade receivers may be used, such as a carrier phase (CPH) or real-time kinematic (RTK) GPS. In such embodiments, a base station (not shown) having a known Earth location broadcasts an error correction signal that is used by the GPS receiver 116 to achieve accuracy to within a few centimeters. An example of a suitable GPS receiver 116 is the ProMark2™ survey system available from Ashtech, Inc. of Santa Clara, Calif. Like the digital camera 110, the GPS receiver 116 may be included within, attached to, or otherwise integrated with the range scanner 102.

The range scanner 102 may also include one or more orientation indicator(s) 202 for providing information about the orientation of the range scanner 102 with respect to the Earth. For example, one indicator 202 may provide a bearing or heading (azimuth) of the range scanner 102. Azimuth is typically expressed as a horizontal angle of the observer's bearing, measured clockwise from a referent direction, such as North. A bearing indicator 202 may be embodied, for instance, as a high-accuracy compass capable of digital output.

Some GPS receivers 116 may include compasses, gyroscopes, inertial navigation systems, etc., for providing highly accurate bearing and/or other orientation information. For example, the ProMark2™ survey system described above provides an azimuth reading. Similarly, a bearing may be obtained indirectly from GPS readings, since two precise GPS coordinates define a bearing. Thus, the orientation indicator 202 need not be separate component.

In certain implementations, an indicator **202** may provide the tilt or inclination of the range scanner **102** with respect to the Earth's surface. For example, the range scanner **102** may be tilted with respect to one or two axes. For simplicity, however, the following exemplary embodiments assume that the range scanner **102** is level prior to scanning.

As depicted, the range scanner **102** further includes a servo **203** for continuously changing the bearing and/or tilt of the range scanner **102** to scan a selected site **104**. The servo **203** may include high-accuracy theodolite-type optical or electronic encoders to facilitate high-resolution scanning.

In one embodiment, the servo **203** only tilts the range scanner **102**, while a continuously rotating prism or mirror performs the panning or rotation function. Alternatively, the range scanner **102** could be mounted at a 90° angle, in which case the servo **203** is used for panning. Thus, any appropriate mechanical and/or electronic means, such as stepper motors, diode arrays, etc., may be used to control the bearing and/or tilt of the range scanner **102** within the scope of the invention.

In one embodiment, the servo **203**, as well as the other components of the range scanner **102**, are directed by a controller **204**. The controller **204** may be embodied as a microprocessor, microcontroller, digital signal processor (DSP), or other control device known in the art.

The controller **204** is coupled to a memory **206**, such as a random access memory (RAM), read-only memory (ROM), or the like. In one configuration, the memory **206** is used to buffer the range data, digital images, and GPS data during the scanning process. The memory device **206** may also be used to store parameters and program code for operation of the range scanner **102**.

In addition, the controller **204** is coupled to a control interface **208**, such as an infrared (IR) receiver, for receiving IR-encoded commands from the PDA **106**. Various other control interfaces **208** may be used, however, such as an 802.11b interface, an RS-232 interface, a universal serial bus (USB) interface, or the like. As previously noted, the PDA **106** is used to program the range scanner **102**. For example, the PDA **106** may specify the size of the site **104** to be scanned, the resolution of the range data and digital images to be collected, etc.

The controller **204** is also coupled to a communication interface **210** for sending the captured range data, digital images, and GPS data to the computer **108** for further processing. The communication interface **210** may include, for instance, an Ethernet adaptor, a IEEE 1349 (Firewire) adaptor, a USB adaptor, or other high-speed communication interface.

The communication interface **210** of the range scanner **102** is coupled to, or in communication with, a similar communication interface **212** within the computer **108**. The computer **108** may be embodied as a standard IBM-PC™ compatible computer running a widely-available operating system (OS) such as Windows XP™ or Linux™.

The computer **108** also includes a central processing unit (CPU) **214**, such as an Intel™ x86 processor. The CPU **214** is coupled to a standard display interface **216** for displaying text and graphics, including the visualization **112**, on the monitor **114**. The CPU **214** is further coupled to an input interface **218** for receiving data from a standard input device, such as a keyboard **220** or mouse **222**.

The CPU **214** is coupled to a memory **224**, such as a RAM, ROM, or the like. As described in greater detail hereafter, the memory **224** includes various software modules or components, including a co-registration module **228**, transformation module **229**, a merging module **230**, and a visualization module **232**. The memory **224** may further include various data structures, such as a number of virtual models **234**.

Briefly, the co-registration module **228** automatically co-registers sets of range data from different views (e.g., collected from different vantage points) using the GPS data and orientation information. Co-registration places the sets of range data **302** within the same coordinate system and combining the sets into a single virtual model **234**. In addition, co-registration may require specific calibration of instruments for parallax and other idiosyncrasies.

The transformation module **229** performs the necessary transformations to convert each set of range data from a local scanning coordinate system referenced to a particular scanning location to a modeling coordinate system that is independent of the scanning location. Since transformation is typically part of co-registration, the transformation module **229** may be embodied as a component of the co-registration module **228** in one embodiment.

The merging module **230** analyzes the range data **302** to correct for errors in the scanning process, eliminating gaps, overlapping points, and other incongruities. Thereafter, the visualization module **232** produces the interactive, three-dimensional visualization **112**, as explained in greater detail below.

In alternative embodiments, one or more of the described modules may be implemented using hardware or firmware, and may even reside within the range scanner **102**. Thus, the invention should not be construed as requiring a separate computer **108**.

In one configuration, the computer **108** includes a mass storage device **236**, such as a hard disk drive, optical storage device (e.g., DVD-RW), or the like, which may be used to store any of the above-described modules or data structures. Hence, references herein to "memory" or "storage media" should be construed to include any combination of volatile, non-volatile, magnetic, or optical storage media.

Referring to FIG. 3, one or more virtual models **234** of a site **104** may be captured at each of a number of positions or vantage points. At each position, the range scanner **102** generates range data **302** indicating distances to objects (e.g., a tree) within the site **104**. A set of range data **302** is sometimes referred to as a "range image," although the range data **302** need not be stored or presented in a conventional image format. The terms "range data" and "range image" are used herein interchangeably.

The pattern of marks depicted within the range data **302** represents sample points, i.e., points at which a range measurement has been taken. The density or resolution of the range data **302** depends on the distance of the object from the range scanner **102**, as well as the precision and accuracy of the lidar **103** and the mechanism for panning and/or tilting the lidar **103** relative to its platform. Although FIG. 3 suggests a horizontal scanning pattern, the range data **302** could also be generated using a vertical or spiral scanning pattern.

As previously noted, the GPS receiver **116** associated with the range scanner **102** obtains GPS data **304** (e.g., latitude, longitude, altitude) relative to the range scanner **102** at the scanning position. Additionally, the orientation indicator(s) **202** may provide orientation information **305**, e.g., bearing, tilt.

The camera **110** associated with the range scanner **102** obtains one or more high-resolution digital images **306** of the site **104**. The resolution of the digital images **306** will typically far exceed the resolution of the range data **302**.

The range data **302**, GPS data **304**, orientation information **305**, and digital images **306** are collected at each scanning position or location and represent a virtual model **234** of the site **104**. Separate virtual models **234** are generated from the perspective of each of the scanning positions. Of course, any number of virtual models **234** of the site **104** can be made within the scope of the invention.

In certain instances, a data structure lacking one or more of the above-described elements may still be referred to as a “virtual model.” For example, a virtual model **234** may not include the digital images **306** or certain orientation information **305** (such as tilt data where the range scanner **102** is level during scanning).

FIG. **4** depicts the three sets of range data **302a–c** from top-down views rather than the side views of FIG. **3**. As shown, each set represents only a portion of the site **104**, since the range scanner **102** is not able to “see” behind objects.

In general, each of the sets of range data **302a–c** have separate scanning coordinate systems **402a–c** that are referenced to the scanning positions. Typically, the range data **302** is initially captured in a polar (or polar-like) coordinate system. For example, as shown in FIG. **5**, an individual range measurement may be represented by $P(R, \phi, \theta)$, where R is the range (distance) from the range scanner **102**, ϕ is the degree of tilt, and θ is the degree of panning.

Converting polar range-data **304** into the depicted Cartesian coordinates may be done using standard transformations, as shown below.

$$X=R \cos \phi \cos \theta \quad \text{Eq. 1}$$

$$Y=R \sin \phi \quad \text{Eq. 2}$$

$$Z=R \cos \phi \sin \theta \quad \text{Eq. 3}$$

In certain embodiments, the geometry of the range scanner **102** (e.g., the axis of rotation, offset, etc.) may result in a polar-like coordinate system that requires different transformations, as will be known to those of skill in the art. In general, the origin of each of the scanning coordinate systems **402a–c** is the light-reception point of the lidar **103**.

Referring to FIG. **6**, in order to combine or “co-register” the virtual models **234** from the various scanning positions, the transformation module **229** transforms the range data **302a–c** from their respective scanning coordinate systems **402a–c** to a single modeling coordinate system **602** that is independent of the scanning positions and the orientation of the range scanner **102**.

In one embodiment, the modeling coordinate system **602** is based on a geographic coordinate system, such as Universal Transverse Mercator (UTM), Earth-Centered/Earth-Fixed (ECEF), or longitude/latitude/altitude (LLA). GPS receivers **104** are typically able to display Earth-location information in one or more of these coordinate systems. UTM is used in the following examples because it provides convenient Cartesian coordinates in meters. In the following examples, the UTM zone is not shown since the range data **302** will typically be located within a single zone.

As depicted in FIG. **6**, the transformation module **229** initially rotates each set of range data **302a–c** by the bearing of the range scanner **102** obtained from the orientation information **305**. After a set of range data **302** has been converted into Cartesian coordinates, each point may be rotated around the origin by the following transformation, where b is the bearing.

$$X_1=X \cos (b)-Z \sin (b) \quad \text{Eq. 4}$$

$$Z_1=Z \cos (b)+X \sin (b) \quad \text{Eq. 5}$$

These equations assume that the range scanner **102** was level at the time of scanning, such that the XZ planes of the scanning coordinate system **402** and modeling coordinate system

602 are essentially co-planer. If, however, the range scanner **102** was tilted with respect to the X and/or Z axes, the transformations could be modified by one of skill in the art.

Next, as shown in FIG. **7**, the transformation module **229** uses the GPS data **304** to translate the range data **302** to the correct location within the modeling coordinate system **602**. In one embodiment, this is done by adding the coordinates from the GPS data **304** to each of the range data coordinates, as shown below.

$$X_2=X_1+GPS_E \quad \text{Eq. 6}$$

$$Y_2=Y_1+GPS_H \quad \text{Eq. 7}$$

$$Z_2=Z_1+GPS_N \quad \text{Eq. 8}$$

where

GPS_E is the UTM “easting,”

GPS_H is the altitude (typically the height above the reference ellipsoid), and

GPS_N is the UTM “northing.”

The UTM easting and northing for a number of points in the modeling coordinate system **602** are shown in FIG. **7**, and are typically represented on maps using the “mE” (meters East) and “mN” (meters North) labels.

Those of skill in the art will recognize that the invention is not limited to UTM coordinates and that transformations exist for other coordinate systems, such as ECEF and LLA. In certain embodiments, the modeling coordinate system **602** may actually be referenced to a local landmark or a point closer to the range data **302**, but will still be geographically oriented.

In the preceding example, the units of the range data **302** and GPS data **304** are both in meters. For embodiments in which the units differ, a scaling transformation will be needed. Furthermore, while FIGS. **6** and **7** show particular types of transformations, those of skill in the art will recognize that different transformations may be required based on the geometry of the range scanner **102**, whether the range scanner **102** was tilted with respect to the XZ plane, and the like.

When the transformation is complete, the co-registration module **228** co-registers or [combine] *combines* the range data **302a–c** from the various views into a co-registered model **702** of the entire site **104**. This may involve, for example, combining the sets of range data **302a–c** into a single data structure, while still preserving the ability to access the individual sets.

In one embodiment, the co-registered model **702** includes GPS data **304** for at least one point. This allows the origin of the modeling coordinate system **602** to be changed to any convenient location, while still preserving a geographic reference.

As illustrated in FIG. **7**, a co-registered model **702** is not perfect. Noise and other sources of error may result in various gaps, incongruities, regions of overlap, etc. Thus, while the co-registration module **228** automatically places the range data **302a–c** within close proximity to their expected locations, eliminating the need for human decision-making, the range data **302a–c** are not truly merged. For example, two separate points may exist within the co-registered model **702** that should actually refer to the same physical location in the site **104**.

Referring to FIG. **8**, a merging module **230** addresses this problem by merging the range data **302a–c** from the co-registered model **702** into a single merged model **802**. The merging module **230** makes fine adjustments to the

transformed range data **302a**—**c**, eliminating the gaps, incongruities, and regions of overlap. In addition, *the* merging module **230** may eliminate redundancy by merging points from the transformed range data **302a** that represent the same physical location. This is accomplished, in one embodiment, using an iterative closest point (ICP) algorithm, as known to those of skill in the art.

In one embodiment, the merging module **230** incorporates the Scanalyze™ product available from Stanford University. Scanalyze™ is an interactive computer graphics application for viewing, editing, aligning, and merging range images to produce dense polygon meshes.

Scanalyze™ processes three kinds of files: triangle-mesh PLY files (extension .ply), range-grid PLY files (also with extension .ply), and SD files (extension .sd). Triangle-mesh PLY files encode general triangle meshes as lists of arbitrarily connected 3D vertices, whereas range-grid PLY files and SD files encode range images as rectangular arrays of points. SD files also contain metadata that describe the geometry of the range scanner **102** used to acquire the data. This geometry is used by Scanalyze™ to derive line-of-sight information for various algorithms. PLY files may also encode range images (in polygon mesh form), but they do not include metadata about the range scanner and thus do not provide line-of-sight information.

Once the PLY or SD files have been loaded, they can be pairwise aligned using a variety of techniques—some manual (i.e. pointing and clicking) and some automatic (using a variant of the ICP algorithm).

Pairs of scans can be selected for alignment either automatically (so-called all-pairs alignment) or manually, by choosing two scans from a list. These pairwise alignments can optionally be followed by a global registration step whose purpose is to spread the alignment error evenly across the available pairs. The new positions and orientations of each PLY or SD file can be stored as a transform file (extension .xf) containing a 4×4 matrix.

Referring to FIG. 9, the visualization module **232** uses the merged model **802** of FIG. 8 to create an interactive, three-dimensional visualization **112** of the site **104**. To accomplish this, the visualization module **232** may convert the transformed/merged range data **302** into a polygon mesh **902**. Various known software applications are capable of producing a polygon mesh **902** from range data **302**, such as the Volumetric Range Image Processing Package (VripPack), available from Stanford University. VripPack is a set of source code, scripts, and binaries for creating surface reconstructions from range images. For example, the Vrip-Pack merges range images into a compressed volumetric grid, extracts a surface from the compressed volumetric grid, fills holes in the reconstruction by carving out empty space, removes small triangles from the reconstruction, and performs a simple 4-level decimation for interactive rendering.

The visualization module **232** also decomposes the digital images **306** into textures **904**, which are then applied to the polygon mesh **902**. In essence, the digital images **306** are “draped” upon the polygon mesh **902**. Due to the relatively higher resolution of the digital images **306**, the textures **904** add a high degree of realism to the visualization **112**. Techniques and code for applying textures **904** to polygon meshes **902** are known to those of skill in the art.

In one embodiment, the mesh **902** and textures **904** are used to create the visualization **112** of the site **104** using a standard modeling representation, such as the virtual reality modeling language (VRML). Thereafter, the visualization **112** can be viewed using a standard VRML browser, or a browser equipped with a VRML plugin, such as the

Microsoft™ VRML Viewer. Of course, the visualization **112** could also be created using a proprietary representation and viewed using a proprietary viewer.

As depicted in FIG. 9, the browser may provide navigation controls **906** to allow the user to “walk through” the visualization **112**. In addition, the user may delete or move objects shown in the visualization **112** or modify the visualization **112** in other ways. As noted, such visualization **112** are highly beneficial in the fields of architecture, landscape design, land use, erosion control, and the like.

FIG. 10 is a flowchart of a method **1000** for capturing and co-registering virtual models **234** of a site **104**. Initially, the site **104** is scanned **1002** to generate a first set of range data **302** indicating distances from a range scanner **102** at a first location to real-world objects in the site **104**. A GPS receiver then acquires **1004** GPS data **304** relative to the range scanner **102** at the first location, after which the range scanner **102** outputs **1006** a first virtual model **234** comprising the first sets of range data **302** and GPS data **304**.

After then range scanner **102** is moved to a second location, the method **1000** continues by scanning **1008** the site **104** to generate a second set of range data **302** indicating distances from the range scanner **102** at the second location to real-world objects in the site **104**. In addition, the GPS receiver **116** acquires **1010** a second set of GPS data **304** relative to the range scanner **102** at the second location, after which the range scanner **102** outputs **1012** a second virtual model **234** comprising the second sets of range data **302** and GPS data **304**.

In one configuration, a transformation module **229** then uses **1014** the sets of GPS data **304** to transform the sets of range data **302** from scanning coordinate systems **402** to a single modeling coordinate system **602**. Thereafter, the transformed range data **302** can be merged and visualized using standard applications.

As illustrated in FIG. 11, a range scanner **102** may be used to scan multiple sites **104a**–**b** within a particular area **1102** to create multiple site models **1104a**–**b** using the techniques discussed above. The sites **104a**–**b** may or may not be contiguous, although they are typically in close proximity or related in some manner. For instance, the area **1102** may [represents] *represent* a town, campus, golf course, etc., while the sites **104a**–**b** may correspond to different buildings or structures.

The site models **1104a**–**b** may be co-registered models **702** or merged models **802**, as previously shown and described. Furthermore, as previously noted, a site model **1104a**–**b** may include GPS data **304**.

In one embodiment, the transformation module **229** uses the sets of GPS data **304a**–**b** to combine the individual site models **1104a**–**b** into a single area model **1106**. This may be done in the same manner as the virtual models **302a**–**c** of FIG. 6 were transformed and combined into the co-registered model **702**. Specifically, the GPS data **304** provides a common reference point for each site model **1104a**–**b**, allowing the co-registration and/or transformation modules **228**, **229** to make any necessary transformations.

The resulting area model **1106** may then be used to produce an interactive, three-dimensional visualization **112** of the entire area **1102** that may be used for many purposes. For example, a user may navigate from one site **104** to another within the area **1102**. Also, when needed, a user may remove any of the site models **1104** from the area model **1106** to visualize the area **1102** within the objects from the removed site model **1104**. This may be helpful in the context of architectural or land-use planning.

While specific embodiments and applications of the present invention have been illustrated and described, it is to

11

be understood that the invention is not limited to the precise configuration and components disclosed herein. Various modifications, changes, and variations apparent to those skilled in the art may be made in the arrangement, operation, and details of the methods and systems of the present invention disclosed herein without departing from the spirit and scope of the invention.

What is claimed is:

1. A system for capturing a virtual model of a site including one or more occluded surfaces when viewed from any given perspective, the system comprising:

a range scanner for automatically scanning a site from a plurality of different fixed locations to generate a separate set of range data at each scanning location indicating distances from the range scanner to real-world objects within the site, each set of range data comprising a three-dimensional model of the same site from a different perspective, wherein at least one set of range data includes a surface of a real-world object that is occluded in at least one other set of range data;

a digital camera coupled to the range scanner for obtaining digital images of the real-world objects scanned by the range scanner at each location;

a global positioning system (GPS) receiver [coupled to the range scanner] for acquiring GPS data for the range scanner at [a] each scanning location, wherein the GPS receiver interacts with a separate base station to achieve sub-meter accuracy;

an orientation indicator [coupled to the range scanner] for indicating an orientation of the range scanner at each scanner location;

a transformation module for using the GPS data with orientation [data] *information* for the range scanner at each scanning location to automatically transform the sets of range data from individual scanning coordinate systems based on the scanning locations to a single modeling coordinate system; and

a co-registration module for automatically co-registering the transformed sets of range data into a single virtual model of the site that includes the one or more occluded surfaces.

2. The system of claim 1, further comprising:

a visualization module for converting the co-registered virtual model of the site into a polygon mesh and for applying textures to the polygon mesh [derived from the digital imagery] to create [an] a visualization of the site that is substantially free of occlusions, *the textures being derived from the digital images*.

3. The system of claim 1, further comprising:

a merging module for merging at least two points represented within the co-registered virtual model that correspond to the same physical location within the site.

4. The system of claim 1, wherein the modeling coordinate system is a geographic coordinate system.

5. The system of claim 2, wherein the orientation indicator comprises a bearing indicator for indicating the bearing of the range scanner.

6. The system of claim 1, wherein the GPS data is selected from the group consisting of longitude, latitude, altitude, Universal Transverse Mercator (UTM) coordinates, and Earth-Centered/Earth-Fixed (ECEF) coordinates.

7. The system of claim 1, wherein at least two of the sets of range data indicate a distance from the range scanner to the same physical location within the site.

8. The system of claim 1, wherein the virtual model associates the digital images of the real-world objects with the corresponding range data.

12

9. The system of claim 1, wherein the range scanner comprises:

a servo for continuously changing an orientation of the range scanner with respect to a fixed location to scan the site; and

a lidar to obtain range measurements to real-world objects along a changing path of the range scanner responsive to the servo.

10. A system for capturing a virtual model of a site including one or more occluded surfaces when viewed from any given perspective, the system comprising:

a range scanner for automatically scanning the site to generate a first set of range data indicating distances from the range scanner at a first location to real-world objects in the site, wherein the range scanner is to automatically re-scan the site to generate a second set of range data indicating distances from the range scanner at a second scanning location to real-world objects in the site, each set of range data comprising a three-dimensional model of the same site from a different perspective, wherein the second set of range data includes a surface of a real-world object that is occluded in the first set of range data;

a digital camera coupled to the range scanner for obtaining digital images of the real-world objects scanned by the range scanner at each location;

a global positioning system (GPS) receiver [coupled to the range scanner] for acquiring a first set of GPS data for the range scanner at the first scanning location and a second set of GPS data for the range scanner at the second location, wherein the GPS receiver interacts with a separate base station to achieve sub-meter accuracy;

an orientation indicator for indicating an orientation of the range scanner at each scanning location;

a transformation module for using the first and second sets of GPS data with orientation [data] *information* for the range scanner at the scanning locations to automatically transform the first and second sets of range data from local coordinate systems referenced to the scanning locations to a single coordinate system independent of the scanning locations;

a co-registration module for automatically co-registering the first and second sets of range data into a single virtual model of the site that includes the one or more occluded surfaces; and

a merging module for merging at least two points represented within the co-registered virtual model that correspond to the same physical location within the site.

11. The system of claim 10, further comprising:

a visualization module for converting the co-registered virtual model of the site into a polygon mesh and for applying textures to the polygon mesh [derived from the digital imagery] to create [an] a visualization of the site that is substantially free of occlusions, *the textures being derived from the digital images*.

12. A system for modeling an object including one or more occluded surfaces when viewed from any vantage point, the system comprising:

a range scanner for automatically scanning an object from a plurality of fixed vantage points to generate a plurality of separate range images, each range image comprising a three-dimensional model of the object from a different perspective, wherein at least one range image includes a surface of the object that is occluded in at least one other range image;

13

a digital camera coupled to the range scanner for obtaining digital images of the object from each vantage point;

a global positioning system (GPS) receiver for obtaining GPS readings for the range scanner at each vantage point, wherein the GPS receiver interacts with a separate base station to achieve sub-meter accuracy;

[an] a bearing indicator [coupled to the range scanner] for indicating a bearing of the range scanner at each scanning location;

a transformation module for using the GPS readings associated with each range image, as well as information about the range scanner's bearing at each vantage point, to automatically transform the range images from local coordinate systems relative to the vantage points to a single coordinate system independent of the vantage points; and

a co-registration module for automatically co-registering the transformed range images into a single virtual model of the object that includes the one or more occluded surfaces.

13. The system of claim 12, further comprising:

a visualization module for converting the co-registered virtual model of the object into a polygon mesh and for applying textures to the polygon mesh [derived from the digital imagery] to create [an] a visualization of the object that is substantially free of occlusions, *the textures being derived from the digital images*.

14. The system of claim 12, wherein the range scanner comprises

a servo for continuously changing an orientation of the range scanner with respect to a fixed location to scan the object; and

a lidar to obtain range measurements of the object along a changing path of the range scanner responsive to the servo.

15. The system of claim 12, wherein the virtual model is to associate the digital [imagery] images and the corresponding range images within the virtual model.

16. The system of claim 12, further comprising:

a merging module for merging at least two points represented within the co-registered range images that correspond to the same physical location on the object.

17. A method for capturing a virtual model of a site including one or more occluded surfaces when viewed from any given perspective, the method comprising:

automatically scanning a site from a plurality of different fixed locations to generate a separate set of range data at each scanning location indicating distances from a range scanner to real-world objects within the site, each set of range data comprising a three-dimensional model of the same site from a different perspective, wherein at least one set of range data includes a surface of a real-world object that is occluded in at least one other set of range data;

obtaining digital images of the real-world objects scanned by the range scanner at each location;

acquiring global positioning system (GPS) data for the range scanner at each scanning location using a GPS receiver that interacts with a separate base station to achieve sub-meter accuracy;

obtaining orientation [data] information for the scanner at each scanning location;

automatically transforming the separate sets of range data from individual scanning coordinate systems to a mod-

14

eling coordinate system using the GPS data with the orientation [data] information for the range scanner at each scanning location; and

automatically co-registering the transformed sets of range data into a single virtual model of the site that includes the one or more occluded surfaces.

18. The method of claim 17, further comprising:

converting the co-registered virtual model of the site into a polygon mesh; and

applying textures to the polygon mesh [derived from the digital imagery] to create [an] a visualization of the site that is substantially free of occlusions, *the textures being derived from the digital images*.

19. The method of claim 17, further comprising:

merging at least two points represented within the co-registered virtual model that correspond to the same physical location within the site.

20. The method of claim 17, wherein the modeling coordinate system is a geographic coordinate system.

21. The method of claim 17, wherein the orientation information includes a bearing of the range scanner, the method further comprising:

determining the bearing of the range scanner.

22. The [system] method of claim 17, wherein the GPS data is selected from the group consisting of longitude, latitude, altitude, Universal Transverse Mercator (UTM) coordinates, and Earth-Centered/Earth-Fixed (ECEF) coordinates.

23. The method of claim 17, wherein at least two of the sets of range data indicate a distance from the range scanner to the same physical location within the site.

24. The method of claim 17, further comprising:

associating the digital images of the real-world objects with the corresponding range data.

25. The method of claim 17, wherein scanning comprises:

continuously changing an orientation of the range scanner with respect to a fixed location to scan the site; and

obtaining range measurements to real-world objects along a changing path of the range scanner.

26. A method for capturing a virtual model of a site including one or more occluded surfaces when viewed from any given perspective, the method comprising:

automatically scanning the site to generate a first set of range data indicating distances from a range scanner at a first location to real-world objects in the site, wherein the first set of range data comprises a three-dimensional model of the site from a first perspective;

obtaining digital images of the real-world objects scanned by the range scanner at the first location;

acquiring a first set of global positioning system (GPS) data for the range scanner at the first location using a GPS receiver that interacts with a base station to achieve sub-meter accuracy;

determining orientation information for the range scanner at the first location;

scanning the same site from a second perspective to generate a second set of range data indicating distances from the range scanner at a second location to real-world objects in the site, wherein the second set of range data comprises a three-dimensional model of the site from a second perspective, wherein the second set of range data includes a surface of a real-world object that is occluded in the first set of range data;

obtaining digital images of the real-world objects scanned by the range scanner at the second location;

15

acquiring a second set of GPS data for the range scanner at the second location;

determining orientation information for the range scanner at the second location;

automatically transforming the first and second sets of range data from individual local coordinate systems to a single coordinate system independent of the range scanner locations using the first and second sets of GPS data with the orientation information;

automatically co-registering the first and second sets of range data into a single virtual model of the site that includes the one or more occluded surfaces;

converting the co-registered virtual model of the site into a polygon mesh; and

applying textures to the polygon mesh [derived from the digital imagery] to create [an] a visualization of the site that is substantially free of occlusions, *the textures being derived from the digital images.*

27. A method for modeling an object including one or more occluded surfaces when viewed from any vantage point, the method comprising:

automatically scanning an object from a plurality of fixed vantage points to generate a plurality of separate range images, each range image comprising a three-dimensional model of the object from a different perspective, wherein at least one range image includes a surface of the object that is occluded in at least one other range image;

obtaining digital images of the object from each vantage point;

obtaining a bearing of the scanner at each vantage point;

acquiring global position system (GPS) readings for the range scanner at each vantage point using a GPS receiver that accesses a separate base station to achieve sub-meter accuracy;

transforming the range images from local coordinate systems relative to the vantage points to a single coordinate system independent of the vantage points using the GPS readings associated with each range image, as well as information about the range scanner's bearing at each vantage point; and

automatically co-registering the transformed range images into a single virtual model of the object that includes the one or more occluded surfaces.

28. The method of claim, 27, further comprising:

converting the co-registered virtual model of the object into a polygon mesh; and

applying textures to the polygon mesh [derived from the digital imagery] to create [an] a visualization of the object that is substantially free of occlusions, *the textures being derived from the digital images.*

29. The [system] method of claim 27, wherein scanning comprises:

continuously changing an orientation of the range scanner with respect to a fixed location to scan the object; and

obtaining range measurements of the object along a changing path of the range scanner responsive to the servo.

30. The [system] method of claim 27, wherein the GPS data is selected from the group consisting of longitude, latitude, uniform, altitude, Universal Transverse Mercator (UTM) coordinates, and Earth-Centered/Earth-Fixed (ECEF) coordinates.

16

31. The method of claim 27, further comprising:
 associating the digital [imagery] images with the corresponding range images within the virtual model.

32. The method of claim 27,
 wherein at least two of the range images depict the same physical location within the site.

[33. The system of claim 27, wherein the GPS data is selected from the group consisting of longitude, latitude, altitude, Universal Transverse Mercator (UTM) coordinates, and Earth-Centered/Earth-Fixed (ECEF) coordinates.]

34. The [system] method of claim 27,
 wherein at least two of the range images depict the same physical location on the object.

35. An apparatus for capturing a virtual model of a site including one or more occluded surfaces when viewed from any given perspective, the [system] apparatus comprising:
 scanning means for automatically scanning a site from a plurality of different fixed locations to generate a separate set of range data at each scanning location indicating distances from the scanning means to real-world objects within the site, each set of range data comprising a three-dimensional model of the same site from a different perspective, wherein at least one set of range data includes a surface of a real-world object that is occluded in at least one other set of range data;

camera means coupled to the scanning means for obtaining digital images of the real-world objects scanned by the scanning means at each location;

position detection means [coupled to the scanning means] for acquiring global positioning system (GPS) data for the scanning means at [a] each scanning location, wherein the position detection means interacts with a separate base station to achieve sub-meter accuracy;

an orientation detection means [coupled to the scanning means] for indicating an orientation of the scanning means at each scanning location;

transformation means for using the GPS data with orientation [data] information for the scanning means at each scanning location to automatically transform the sets of range data from individual scanning coordinate systems based on the scanning locations to a single modeling coordinate system; and

co-registration means for automatically co-registering the transformed sets of range data into a single virtual model of the site that includes the one or more occluded surfaces.

36. A computer program product comprising program code for performing a method for capturing a virtual model of a site including one or more occluded surfaces when viewed from any given perspective, the computer program product comprising:
 program code for automatically scanning a site from a plurality of different fixed locations to generate a separate set of range data at each scanning location indicating distances from a range scanner to real-world objects within the site, each set of range data comprising a three-dimensional model of the same site from a different perspective, wherein at least one set of range data includes a surface of a real-world object that is occluded in at least one other set of range data;

program code for obtaining digital images of the real-world objects scanned by the range scanner at each location;

program code for acquiring global positioning system (GPS) data for the range scanner at each scanning loca-

17

tion using a GPS receiver that interacts with a separate base station to achieve sub-meter accuracy;
 program code for obtaining orientation [data] information for the scanner at each scanning location;
 program code for automatically transforming the separate
 sets of range data from individual scanning coordinate
 systems to a modeling coordinate system using the GPS
 data with the orientation [data] information for the
 range scanner at each scanning location; and
 program code for automatically co-registering the trans-
 formed sets of range data into a single virtual model of
 the site that includes the one or more occluded surfaces.

37. *The system of claim 1, wherein the GPS receiver achieves sub-centimeter accuracy.*

38. *The system of claim 1, wherein the orientation indicator comprises a compass capable of digital output.*

39. *The system of claim 1, wherein the orientation indicator comprises at least two GPS readings to indicate the orientation of the range scanner at each location.*

40. *The system of claim 1, further comprising a second digital camera for obtaining digital images of the real-world*

18

objects scanned by the range scanner at each location, wherein the digital camera and the second digital camera are set to focus in a stereo vision arrangement.

41. *The method of claim 17, wherein the GPS receiver achieves sub-centimeter accuracy.*

42. *The method of claim 17, wherein the orientation information comprises data from a compass capable of digital output.*

43. *The method of claim 17, wherein the orientation information comprises at least two GPS readings to indicate an orientation of the range scanner at each location.*

44. *The method of claim 17, further comprising obtaining digital images of the real-world objects scanned by the range scanner at each location using a second digital camera, wherein the digital camera and the second digital camera are set to focus in a stereo vision arrangement.*

* * * * *