

US00RE41261E

(19) **United States**
(12) **Reissued Patent**
Forbes et al.

(10) **Patent Number:** **US RE41,261 E**
(45) **Date of Reissued Patent:** **Apr. 27, 2010**

(54) **CENTER BEAM CAR WITH DEEP UPPER BEAM STRUCTURE**

(75) Inventors: **James W. Forbes**, Campbellville (CA);
Alistair Wilson, Brantford (CA)

(73) Assignee: **National Steel Car Limited (CA)**

(21) Appl. No.: **11/202,398**

(22) Filed: **Aug. 11, 2005**

2,724,611 A	11/1955	Robertson
2,759,737 A	8/1956	Manning
2,768,004 A	10/1956	Wagner
2,801,597 A	8/1957	Ecoff
2,803,201 A	8/1957	Johnson et al.
2,810,602 A	10/1957	Abrams
2,839,328 A	6/1958	Prickett et al.
2,851,301 A	9/1958	Jagsch
2,883,945 A	4/1959	Walker
2,904,340 A	9/1959	Simpson

(Continued)

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,604,470**
 Issued: **Aug. 12, 2003**
 Appl. No.: **09/621,304**
 Filed: **Jul. 20, 2000**

U.S. Applications:

(63) Continuation of application No. 09/457,615, filed on Dec. 8, 1999, now Pat. No. 6,237,506.

(51) **Int. Cl.**
B61D 17/00 (2006.01)

(52) **U.S. Cl.** **105/355; 105/404; 410/31**

(58) **Field of Classification Search** **410/12, 410/100, 97, 103, 106; 242/401; 254/380; 105/355, 404, 396, 411, 414**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

190,542 A	5/1877	Brooks
401,528 A	4/1889	Zurcher
831,648 A	9/1906	Dodds
831,654 A	9/1906	Dodds
934,578 A	9/1909	Stoller
975,861 A	11/1910	Harrigan
2,061,673 A	11/1936	Robinson
2,167,427 A	7/1939	Tatum
2,650,856 A	9/1953	Mashburn, Jr. et al.
2,710,221 A	6/1955	Hinners

FOREIGN PATENT DOCUMENTS

CA	1265388	2/1990
CA	2313834	1/2002
EP	0306584	3/1989
NL	37659	1/1933

OTHER PUBLICATIONS

Car Builders' Cyclopedia of American Practice, 14th ed., Simmons-Boardman Publishing Corporation, New York, NY, 1937, pp. 209-214.

(Continued)



Primary Examiner—Mark T Le

(74) *Attorney, Agent, or Firm*—Hahn Loeser & Parker LLP; Michael H. Minns

(57) **ABSTRACT**

A center beam car has a main deck structure extending laterally from a main center sill, a laterally extending top truss structure, and a central vertically oriented web work structure for carrying vertical shear loads. The center beam so formed defines bunks upon in which to carry cargo. The upper region of the web-work structure includes a deep upper beam structure that has downwardly extending planar surfaces. The surfaces provide a bearing area against which bundled loads can be secured. The surfaces are inwardly reinforced to discourage deflection between adjacent upright members of the vertical web work.

50 Claims, 16 Drawing Sheets



U.S. PATENT DOCUMENTS

2,940,402 A 6/1960 Hansen et al.
 2,996,020 A * 8/1961 Udstad 410/43
 3,009,426 A 11/1961 Nampa
 3,028,191 A 4/1962 Magor
 3,079,874 A 3/1963 Hansen et al.
 3,159,112 A 12/1964 Tomlinson
 3,240,168 A 3/1966 Charles et al.
 3,244,120 A 4/1966 Taylor
 3,357,371 A 12/1967 Guttridge
 3,485,184 A 12/1969 Berry
 3,509,829 A 5/1970 Henriksson et al.
 3,659,724 A 5/1972 Miller et al.
 3,675,592 A 7/1972 Bateson et al.
 3,677,193 A 7/1972 Pringle
 3,713,400 A 1/1973 Teoli
 3,724,394 A 4/1973 Pringle
 3,734,031 A 5/1973 Wagner
 3,751,102 A 8/1973 Stoneburner
 3,774,554 A 11/1973 O'Neill et al.
 3,777,671 A 12/1973 Miller et al.
 3,779,411 A 12/1973 Moretti, Jr.
 3,788,702 A 1/1974 Toboll
 3,806,182 A 4/1974 Bateson et al.
 3,814,028 A 6/1974 Adler
 3,818,843 A 6/1974 Lee
 3,820,476 A 6/1974 Harter et al.
 3,820,747 A 6/1974 Bateson et al.
 3,841,236 A 10/1974 Hammonds et al.
 3,885,506 A 5/1975 Mundinger et al.
 3,964,399 A 6/1976 Miller et al.
 4,024,821 A 5/1977 Yang
 4,079,676 A 3/1978 Miller
 4,082,045 A 4/1978 McNally et al.
 4,091,742 A 5/1978 Cordani
 4,092,039 A 5/1978 Lutkenhouse
 4,128,062 A 12/1978 Roberts
 4,194,451 A 3/1980 Dehner
 RE30,388 E 9/1980 Mundinger et al.
 4,221,427 A 9/1980 Sentle, Jr. et al.
 4,236,459 A 12/1980 Teoli
 4,254,714 A 3/1981 Heap
 4,331,083 A 5/1982 Landregan et al.
 4,348,963 A 9/1982 Dancy
 4,361,097 A 11/1982 Jones et al.
 4,373,447 A 2/1983 Pfister
 4,385,856 A 5/1983 O'Neal
 4,408,542 A 10/1983 Heap
 4,452,150 A 6/1984 Dominguez
 4,478,155 A 10/1984 Cena et al.
 4,543,887 A 10/1985 Baker
 4,569,289 A 2/1986 Gielow et al.
 4,580,844 A 4/1986 Farmer
 4,626,017 A 12/1986 Robertson
 4,633,787 A 1/1987 Przybylinski et al.
 4,637,320 A 1/1987 Paton et al.
 4,646,653 A 3/1987 Balbi et al.
 4,681,041 A 7/1987 Harris et al.
 4,686,907 A 8/1987 Woollam et al.
 4,688,976 A 8/1987 Rowley et al.
 4,690,072 A 9/1987 Wille et al.
 4,738,203 A 4/1988 Gielow et al.
 4,751,882 A 6/1988 Wheatley et al.
 4,753,175 A 6/1988 Harris et al.
 4,756,256 A 7/1988 Rains et al.
 4,770,578 A 9/1988 Coleman
 4,771,705 A 9/1988 Przybylinski et al.
 4,771,706 A 9/1988 Lindauer et al.
 4,784,067 A 11/1988 Harris et al.
 4,802,420 A 2/1989 Butcher et al.
 4,805,539 A 2/1989 Ferris et al.

4,807,722 A 2/1989 Jamrozy et al.
 4,876,968 A 10/1989 Lindauer et al.
 4,889,055 A 12/1989 Jamrozy et al.
 4,901,649 A 2/1990 Fehrenbach et al.
 4,911,082 A 3/1990 Richmond
 4,944,232 A 7/1990 Schlaeger
 4,951,575 A 8/1990 Dominguez et al.
 4,966,081 A 10/1990 Dominquez et al.
 5,024,567 A 6/1991 Dominguez et al.
 5,088,417 A 2/1992 Richmond et al.
 5,159,882 A 11/1992 Krug et al.
 5,259,322 A 11/1993 Dominguez et al.
 5,271,336 A 12/1993 Willetts
 5,410,970 A 5/1995 Stephenson, Jr.
 5,520,489 A 5/1996 Butcher et al.
 5,582,495 A 12/1996 Schroeder
 5,626,083 A 5/1997 Saxton
 5,692,792 A 12/1997 Klar
 5,758,584 A 6/1998 Saxton
 5,878,548 A 3/1999 Sauer et al.
 5,899,646 A 5/1999 Tatina et al.
 5,943,963 A 8/1999 Beals
 6,050,202 A 4/2000 Thompson
 6,183,176 B1 2/2001 Weiner
 6,199,486 B1 3/2001 Landrum et al.
 6,237,506 B1 5/2001 Forbes
 6,431,085 B1 8/2002 Saxton et al.
 6,470,808 B1 10/2002 Clark et al.
 2002/0073885 A1 6/2002 Saxton et al.
 2002/0073890 A1 6/2002 Saxton et al.
 2002/0124767 A1 9/2002 Forbes

OTHER PUBLICATIONS

Car Builders' Cyclopeda of American Practice, 18th ed.,
 Simmons-Boardman Publishing Corporation, New York,
 NY, 1949-51, pp. 155.
 Car Builders' Cyclopeda of American Practice, 19th ed.,
 Simmons-Boardman Publishing Corporation, New York,
 NY, 1953, pp. 284-285.
 Railway Age Weekly, Simmons-Boardman Publishing Cor-
 poration, Boston, Conn., Jan. 5, 1959, p. 19.
 Car Builders' Cyclopeda of American Practice, 21st ed.,
 Simmons-Boardman Publishing Corporation, New York,
 NY, 1961, pp. 168-172.
 Car Builders' Cyclopeda of American Practice, 21st ed.,
 Simmons-Boardman Publishing Corporation, New York,
 NY, 1961, pp. 447-448.
 Railway Age Weekly, Simmons-Boardman Publishing Cor-
 poration, Boston, Conn., 1965, pp. 22-23.
 Blodgett, Omer W., "Rigid-Frame Knees (Elastic Design)"
 in Design of Welded Structures, James F. Lincoln Arc Weld-
 ing Foundation, Jun. 1966, pp. 5.11-1 to 5.11-20.
 Railway Age Weekly, Simmons-Boardman Publishing Cor-
 poration, Boston, Conn., Mar. 20, 1967, p. 15.
 Railway Age Weekly, Simmons-Boardman Publishing Cor-
 poration, Boston, Conn., Dec. 18, 1967, p. 58.
 Railway Age Weekly, Simmons-Boardman Publishing Cor-
 poration, Boston, Conn., Feb. 19, 1968. "RSP Carbuilding
 Shop Adds Repair Facility", 1 page.
 Railway Age Weekly, Simmons-Boardman Publishing Cor-
 poration, Boston, Conn., Apr. 28, 1969. "Meet the Convert-
 ibles!", 1 page.
 Car and Locomotive Cyclopeda of American Practice, 2nd
 ed., Simmons-Boardman Publishing Corporation, New
 York, NY, 1970, p. 126.

Car and Locomotive Cyclopedia of American Practice, 2nd ed., Simmons–Boardman Publishing Corporation, New York, NY, 1970, pp. 287 + 289.

Car and Locomotive Cyclopedia of American Practice, 3rd ed., Simmons–Boardman Publishing Corporation, New York, NY, 1974, pp. S3–165 + S3–173 to S3–176.

Car and Locomotive Cyclopedia of American Practice, 3rd ed., Simmons–Boardman Publishing Corporation, Omaha, Nebraska, copyright 1974, pp. 73 + 76.

The Car and Locomotive Cyclopedia of American Practice, 4th ed., Simmons–Boardman Publishing Corporation, Omaha, Nebraska, copyright 1980, pp. 242, 243 + 256 .

The Car and Locomotive Cyclopedia of American Practice, 5th ed., Simmons–Boardman Publishing Corporation, Omaha, Nebraska, copyright 1984, p. 169.

Various photographs showing a dropped deck center beam car bearing model No. THRX 3001 manufactured by Thrall (date and location unknown).

Photographs showing a flatcar bearing model No. BCOL 866688 (date and location unknown).

Various photographs showing a center beam car bearing model No. BNSF 564124 (date and location unknown).

Illustration showing a model of a car built for Pulpwood Service in 1963.

Various photographs taken on Sep. 19, 2000, Chicago, Illinois, USA, showing a dropped deck center beam car bearing model No. THRX 3001 manufactured by Thrall.

Various photographs taken on Sep. 27, 2000, Campbellville, Ontario, Canada, showing a flatcar bearing model No. CN 602376.

Various photographs taken on Sep. 27, 2000, Milton, Ontario, Canada, showing a flatcar bearing model No. BCOL 52098.

Railway Age Weekly, Simmons–Boardman Publishing Corporation, Boston, Conn., Jul. 29, 1968, p. 42D.

Various photographs taken on Apr. 24, 2001 at the Frid Street Yard, Hamilton, Ontario, Canada, showing a dropped deck center beam car bearing model No. GCFX 1002 manufactured by Alstrom..

Various photographs taken on Sep. 4, 2001 at the Frid Street Yard, Hamilton, Ontario, Canada, showing a dropped deck center beam car bearing model No. GBRX 20003 manufactured by Gunderson.

Various photographs taken on Oct. 31, 2001 at the Frid Street Yard, Hamilton, Ontario, Canada, showing a dropped deck center beam car bearing model No. GBRX 20003 manufactured by Gunderson.

Various photographs taken on May 17, 2001 at the Savage Reload Facility, Chicago, Illinois, USA, showing a dropped deck center beam car bearing model No. GBRX 20003 manufactured by Gunderson.

* cited by examiner




Figure 1




Figure 2




Figure 3b

Figure 3a




Figure 4b

Figure 4a




Figure 5a

Figure 5b




Figure 6b




Figure 6a




Figure 7b




Figure 7a




Figure 8b

Figure 8a




Figure 9a

Figure 9b




Figure 10




Figure 11




Figure 12a




Figure 12b




Figure 12c




Figure 12e




Figure 12d




Figure 12f




Figure 13






Figure 14



CENTER BEAM CAR WITH DEEP UPPER BEAM STRUCTURE

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

This application is a continuation of U.S. patent application Ser. No. 09/457,615 filed Dec. 8, 1999.

FIELD OF THE INVENTION

This invention relates generally to center beam rail road cars, and, in particular, to center beam cars having a deepened upper beam structure.

BACKGROUND OF THE INVENTION

Center beam railroad cars have a pair of end structures mounted on railroad car trucks. A center sill extends the length of the car between the end structures. A deck extends laterally outward from the center sill above, and between, the end structures. A pair of end bulkheads stand at the ends of the car and extend transversely of the rolling direction of the car. A center beam structure, typically in the nature of a truss, stands upright from the deck and runs along the longitudinal centerline of the car between the end bulkheads. The center beam is a deep girder beam whose bottom flange is the center sill, and whose top flange is the top truss (or analogous structure) of the car. Typically, a web work structure for carrying vertical shear loads, such as an open framework of posts and diagonal braces, extends between the center sill and the top truss. An upper beam assembly, that is, the upper or top flange end of the center beam, is usually manufactured as a wide flange, or flange-simulating truss, both to co-operate with the center sill to resist vertical bending, and also to resist bending due to horizontal loading of the car while travelling on a curve. Center beam cars are commonly used to transport packaged bundles of lumber, although other loads such as pipe, steel, engineered wood products, or other goods can also be carried.

The space above the deck on each side of the center beam forms a bunk upon which bundles of wood can be loaded. The base of the bunk has risers that are mounted to slant inward, and the center beam itself is tapered from bottom to top, such that when the bundles are stacked, the overall stack leans inward toward the longitudinal centerline of the car. The load is most typically secured in place using straps or cables. The straps extend from a winch device at deck level, upward outside the bundles, to a top fitting. The top fitting can be located at one of several intermediate heights for partially loaded cars. Most typically the cars are fully loaded and the strap terminates at a fitting mounted to the outboard portion of the upper beam assembly. In as much as the upper beam assembly is narrower than the bundles, when the strap is drawn taut by tightening the pawl, it binds on the upper outer corner of the topmost bundle and exerts a force inwardly and downwardly, tending thereby to hold the stack in place tight against the web of the center beam.

Each bundle typically contains a number of pieces of lumber, commonly 2×4, 2×6, 2×8 or other standard size. The lengths of the bundles vary, typically ranging from 8' to 24', in 2' increments. The most common bundle size is nominally 32 inches deep by 49 inches wide, although 24 inch deep bundles are also used, and 16 inch deep bundles can be used, although these latter are generally less common. A 32 inch nominal bundle may contain stacks of 21 boards, each 1½ inch thick, making 31½ inches, and may include a further

1½ inches of dunnage for a total of 33 inches. The bundles are loaded such that the longitudinal axes of the boards are parallel to the longitudinal, or rolling, axis of the car generally. The bundles are often wrapped in a plastic sheeting to provide some protection from rain and snow, and also to discourage embedment of abrasive materials such as sand, in the boards. The bundles are stacked on the car bunks with the dunnage located between the bundles such that a fork-lift can be used for loading and unloading.

It has been observed that when the straps are tightened, the innermost, uppermost boards of the topmost bundle bear the greatest portion of the lateral reaction force against the center beam due to the tension in the straps or cables. It has also been observed that when these bundles bear against the vertical posts of the center beam, the force is borne over only a small area. As the car travels it is subject to vibration and longitudinal inertia loads. Consequently the plastic sheeting may tend to be torn or damaged in the vicinity of the vertical posts, and the innermost, uppermost boards can be damaged.

The physical damage to these boards may tend to make them less readily saleable. Further, whether or not the boards are damaged, if the plastic is ripped, moisture can collect inside the sheeting. This may lead to the growth of molds, and may cause discoloration of the boards. In some markets the aesthetic appearance of the wood is critical to its saleability, and it would be advantageous to avoid this discoloration.

In part, the difficulty arises because the bearing area may be too small. Further, the join between the upstanding web portion of the center beam and the upper beam assembly can coincide with the height of the topmost boards. This join is not always smooth. Further still, when the posts are fabricated, the flanges of the posts may not stand perfectly perpendicular to the webs of the respective posts. That is, the post flanges may not be co-planar with the side webs, or legs, of the adjoining top chord, such that one edge of the flange may be twisted so that it bears harder against the bundles than another.

It is also desirable that the bundles stack squarely one upon another. Although it is possible to use wooden battens at the top end of the center beam, this will tend to cause the top bundle to sit outwardly of its neighbours. It has been observed that a thin wooden batten, of ¾" thickness may tend to bow inwardly between adjacent posts, and may not spread the wear load as much as may be desired. A 1½ inch thick wooden batten may have a greater ability to resist this bowing effect. However, the space available for employing a batten may tend to be limited by the design envelope of the car. In as much as is advantageous to load the car as fully as possible, and given that the design of the car may usually reflect a desire to maximize loading within the permissible operational envelope according to the applicable AAR standard, the use of a relatively thick wooden batten may tend to push the outside edge of the top bundle outside the permissible operational envelope. Wooden battens may also be prone to rotting if subject to excessive exposure to moisture, or may be consumable wear items that may require relatively frequent periodic replacement.

It would be desirable to have an upper beam assembly that is integrated into the structure, that is formed to spread the bearing load across a larger area, that would tend to resist the bowing phenomenon, that would tend not to require frequent replacement, and that would tend not to be prone to rotting.

SUMMARY OF THE INVENTION

In an aspect of the invention there is a center beam railroad car having a longitudinal centerline. The railroad car is

supported by rail car trucks at either end thereof. The railroad car comprises a cargo support structure borne between the trucks, upon which cargo can be carried. There is a web work assembly including an array of posts mounted along the longitudinal centerline of the railroad car. The array extends upwardly of the cargo support structure, and the array is braced longitudinally. An upper beam assembly surmounts the web work assembly. The upper beam assembly has cantilevered wings extending laterally of the longitudinal centerline. The railroad car has a load limit height defined at a level measured upwardly from the cargo support structure, and has a nominal load height that is less than the load limit height. The nominal load height is at least as great as 32 inches multiplied by Q, where Q is the integer quotient obtained by dividing the load limit height by 32 inches. The web work assembly has at least one skirt member mounted thereto to define a longitudinally extending face against which loads placed laterally outward thereof can bear. The skirt member extends from a first height that is at least as high as the nominal load height to a second height that is at least six inches below the nominal load height.

In another feature of that aspect of the invention the first height is at least 2 inches above the nominal load height. In an additional feature of that aspect of the invention the first height is at least as high as the load limit height. In another additional feature of that aspect of the invention the distance between the first and second heights is at least 12 inches. In still another additional feature of that aspect of the invention the distance between the first and second heights is at least 24 inches. In yet another additional feature of that aspect of the invention the distance between the first and second heights is at least 30 inches. In a further additional feature of that aspect of the invention the skirt member extends between two posts of the array.

In a still further additional feature of that aspect of the invention each of the posts is located at a longitudinal station along the longitudinal centerline. The skirt member extends longitudinally over a range of distance that includes the longitudinal station of at least one of the posts. The skirt member has a portion that is longitudinally distant from one of the posts, and the reinforcement stiffens the longitudinally distant portion.

In yet another additional feature of that aspect of the invention the center beam car has a first skirt member and a second skirt member. The first skirt member has a first face for engaging loads placed laterally to one side of the web work assembly, and the second skirt member has a second face for engaging loads placed laterally to the other side of the web work assembly. In still another additional feature of that aspect, the reinforcement is a web extending between the first skirt member and the second skirt member.

In another aspect of the invention there is a center beam railroad car having a longitudinal centerline. The center beam car is supported by rail car trucks at either end thereof. The center beam railroad car has a center sill extending between the trucks. There is a decking structure extending laterally of the center sill upon which loads can be placed. An open truss assembly extends upwardly from the center sill. An upper beam assembly is mounted upon the open truss assembly. The upper beam structure includes laterally extending wing portions and a vertical stem portion. The stem portion is mounted to the open truss assembly at a joining interface, and the laterally extending wing portions are mounted to the stem. The stem includes a pair of longitudinally extending, laterally spaced apart, first and second skirt members. The first skirt member has a first outwardly facing surface against which cargo placed laterally outboard

thereof can bear. The second skirt member has a second outwardly facing surface against which cargo placed laterally outboard thereof can bear. The center beam car has an upper load limit height defined at a level between the decking structure and the laterally extending wings. The first and second skirt members are located to overlap the load limit height. The outside lateral dimension of the stem matches the overall outside dimension of the open truss assembly at the joining interface.

In an additional feature of that aspect of the invention the stem and the open truss assembly have slope continuity at the joining interface. In still another additional feature of that aspect of the invention the open truss assembly has a taper from bottom to top and the first and second skirt members are angled to match the taper of the truss assembly. In still yet another additional feature of that aspect of the invention the car conforms to AAR plate C, and 49 inches is at least as great as the distance from the first outwardly facing surface of the first skirt member to the limit of the AAR plate 'C' profile, measured along the load limit height boundary. In a further additional feature of that aspect of the invention the open truss assembly includes an array of upright posts spaced along the longitudinal centerline and bracing. The posts have notched upper ends; and the stem includes a longitudinally extending top chord member formed to seat in the notched upper ends of the posts. In still a further additional feature of that aspect of the invention the top chord member includes a U-shaped pressing. The first and second skirt members are formed integrally therewith. In still yet a further additional feature of that aspect of the invention the U-shaped pressing has a back and the first and second skirt members have an inwardly stepped shoulder extending there along for seating in the notches of the posts.

In an additional feature of that aspect of the invention the longitudinally extending top chord member is a channel having a back and legs. The back is of a width to seat in the notches of the posts, and the first and second skirt members are mounted to the legs. In another additional feature of that aspect of the invention the longitudinally extending top chord member is a tube. The first and second skirt members are mounted to sides of the tube to leave a portion of the tube extending downwardly beyond the first and second skirt members. The notches of the posts are formed to engage the downwardly extending portion of the tube.

In still another additional feature of that aspect of the invention the open truss assembly includes a plurality of upright posts spaced along the longitudinal centerline of the railroad car and diagonal bracing mounted thereto. Each of the posts has a width transverse to the longitudinal centerline of the railroad car. The posts taper from a wider portion adjacent to the decking structure to a narrower portion at a top end adjacent to the upper beam assembly. Each of the posts has a notch defined in the top and thereof. The stem is a top chord assembly having a first U-shaped formed member seated in the notch. The first U-shaped member has a back and upstanding legs. A second U-shaped, formed member has a back and downwardly extending legs. The legs of the first and second U-shaped members co-operate to define the skirt members. The legs of the first and second U-shaped members are formed at an angle matching the taper of the tapered posts.

In another aspect of the invention there is a center beam rail car having a longitudinal centerline. The center beam rail car is supported by rail car trucks at either end thereof. The center beam railroad car has a center sill extending between the trucks, a decking structure extending laterally of the center sill upon which loads can be placed, an open truss struc-

5

ture extending upwardly from the center sill and an upper beam assembly mounted upon the open truss structure. The upper beam structure includes laterally extending wing portions. The open truss structure has a pair of longitudinally extending, laterally spaced apart, first and second skirt members mounted thereto. The first and second skirt members each have an outwardly facing surface against which cargo placed laterally outboard thereof can bear. The center beam car has an upper load limit height defined at a level between the decking structure and the laterally extending wings. The first and second skirt members are located to overlap the load limit height. The first and second skirt members have at least one reinforcement mounted laterally inboard thereof to discourage lateral deflection of the faces when cargo placed laterally outward thereof bears against the first and second skirt members.

In a further aspect of the invention, there is a rail road car having a longitudinal centerline. It comprises a pair of rail car trucks and a center beam assembly carried thereupon. The center beam assembly has a lower flange assembly, an upper flange assembly, and a web assembly extending between the upper and lower flange assemblies. The web assembly has a plurality of upwardly extending posts. The posts have a lower region and an upper region. The web assembly has a non-consumable skirt mounted to the upper region of the posts. The skirt presents a bearing surface. The bearing surface faces laterally outward relative to the longitudinal centerline of said rail road car. Cargo can bear against the bearing surface.

In an additional feature of that aspect, the posts have a laterally outwardly facing flange, and the laterally outwardly facing skirt is mounted flush with the flange. In another alternative additional feature of that aspect of the invention, the posts have a laterally outwardly facing flange, and the skirt stands proud of said outwardly facing flange a distance less than $\frac{3}{4}$ inches. In still another additional feature of that aspect of the invention, the skirt is formed of a hollow cell material having an outwardly facing skin. In another alternative additional feature, the skirt is formed of a corrugated section with an outer skin against which objects may bear. In a further additional feature of that aspect of the invention, the skirt is laterally inwardly reinforced to discourage bowing thereof between adjacent pairs of posts.

In another aspect of the invention there is a center beam rail road car having a longitudinal centerline, the rail road car being supported by rail car trucks at either end thereof. The railroad car has a cargo support structure borne between the trucks, upon which cargo can be carried. The cargo support structure includes decking having a first end, a second end, and upstanding bulkheads mounted at each of the first and second ends. Each of the bulkheads has a base adjoining the decking and an upper end upwardly distant therefrom. A web work assembly including an array of posts is mounted along the longitudinal centerline of the railroad car, the array extending upwardly of the cargo support structure. The web work assembly has a lower region adjacent to the cargo support structure, and an upper region distant from the cargo support structure. An upper beam is located above the web work assembly. The upper beam runs between the upper ends of the bulkheads. The upper beam member has at least one structural member mounted to the upper region of the web work, the structural member having a longitudinally extending face against which lading placed laterally outward of the posts can bear. A reinforcement member extends laterally inward of the face to discourage lateral deflection of the longitudinally extending face.

In still another aspect of the invention there is a center beam railroad car having a longitudinal centerline. The cen-

6

ter beam railroad car is supported by rail car trucks at either end thereof. The center beam railroad car has a center sill extending between the trucks; a decking structure extending laterally of the center sill, upon which loads can be placed; an open web work structure extending upwardly from the center sill; and an upper beam mounted upon the open web work structure. The upper beam is mounted to the open web work structure at a joining interface. The upper beam has a pair of longitudinally extending, laterally spaced apart, planar members, the planar members each having a smooth outwardly facing surface against which cargo placed laterally outboard thereof can bear. The upper beam planar members have an outside lateral dimension matching the open web work structure at the joining interface.

In a further aspect of the invention, there is a center beam car having a longitudinal centerline, the center beam car being supported by rail car trucks at either end thereof. The center beam rail car includes a center sill extending between the trucks; a decking structure extending laterally of the center sill upon which loads can be placed; and an open truss structure extending upwardly from the center sill. The open truss structure includes an upper beam assembly mounted upwardly of, and parallel to, the center sill. The open truss structure includes an array of posts extending between the center sill and the upper beam assembly. The upper beam assembly has a pair of longitudinally extending, laterally spaced apart, planar members. The planar members each have an outwardly facing surface against which cargo placed laterally outboard thereof can bear. The outwardly facing surfaces stand proud of the posts. The planar members each have a longitudinally extending reinforcement mounted laterally inboard thereof to discourage lateral deflection of the faces when cargo placed laterally outward thereof bears there against.

In still another aspect of the invention, there is a railroad car having a longitudinal centerline. The railroad car has a pair of rail car trucks and a center beam assembly carried thereupon. The center beam assembly has a center sill; a cargo support structure extending laterally of the center sill assembly; and a plurality of posts extending upwardly from the center sill. The cargo support structure includes decking having a first end, a second end, and upstanding bulkheads mounted at each of the first and second ends. Each of the bulkheads has a base adjoining the decking and an upper end upwardly distant therefrom. The posts have a lower region adjacent the center sill and an upper region distant from the center sill. A non-consumable, longitudinally extending upper beam assembly is mounted to the upper region of the posts and runs between the upper ends of the bulkheads. The upper beam assembly includes a longitudinally extending structural member presenting a bearing surface facing laterally outward, against which cargo can bear, the bearing surface being reinforced to discourage lateral deflection thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows an isometric, general arrangement view of a center beam car according to the present invention;

FIG. 2 shows a side view of one half of the center beam car of FIG. 1;

FIG. 3a shows a cross-section of the car of FIG. 2 taken on section '3a—3a';

FIG. 3b shows a cross-section of the car of FIG. 2 taken on section '3b—3b';

FIG. 4a shows a detail of the section of FIG. 3;

FIG. 4b shows a side sectional view of the detail of FIG. 4a;

7

FIG. 5a shows a alternate detail to that of FIG. 4a;
 FIG. 5b shows a side sectional view of the detail of FIG. 5a;
 FIG. 6a alternate detail to that of FIG. 4a;
 FIG. 6b shows a side sectional view of the detail of FIG. 6a;
 FIG. 7a shows an alternate detail to that of FIG. 4a;
 FIG. 7b shows a side sectional view of the detail of FIG. 7a;
 FIG. 8a shows an alternate detail to that of FIG. 4a;
 FIG. 8b shows a side sectional view of the detail of FIG. 8a;
 FIG. 9a shows an alternate detail to that of FIG. 4a;
 FIG. 9b shows a side sectional view of the detail of FIG. 9a;
 FIG. 10 shows an alternate detail to that of FIG. 4a;
 FIG. 11 shows an alternate detail to that of FIG. 4a;
 FIG. 12a shows an alternate detail to that of FIG. 4a;
 FIG. 12b shows an alternate detail to that of FIG. 12a;
 FIG. 12c shows an alternate detail to that of FIG. 12a;
 FIG. 12d shows an alternate detail to that of FIG. 12c;
 FIG. 12e shows an alternate detail to that of FIG. 12c;
 FIG. 12f shows an alternate detail to that of FIG. 12d;
 FIG. 13 shows an alternate detail to that of FIG. 4a;
 FIG. 14 shows an alternate detail to that of FIG. 4a;
 FIG. 15 shows an alternate detail to that of FIG. 4a; and
 FIG. 16 shows an alternate detail to that of FIG. 4a.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The description which follows, and the embodiments described therein, are provided by way of illustration of an example, or examples of particular embodiments of the principles of the present invention. These examples are provided for the purposes of explanation, and not of limitation, of those principles and of the invention. In the description which follows, like parts are marked throughout the specification and the drawings with the same respective reference numerals. The drawings are not necessarily to scale and in some instances proportions may have been exaggerated in order more clearly to depict certain features of the invention.

A center beam railroad car is indicated in FIG. 1 generally as 20. It is carried on railroad car trucks 22 and 24 in a rolling direction along rails in the generally understood manner of railcars. Car 20 has a longitudinal centerline 25 lying in a longitudinal plane of symmetry, indicated generally as 26 which intersects the kingpin connections of trucks 22 and 24. It will be appreciated that aside from fittings such as hand grabs, ladders, brake fittings, and couplers, the structure of car 20 is symmetrical about the longitudinal plane of symmetry, and also about a transverse plane of symmetry 28 at the mid-length station of the car. In that light, a structural description of one half of the car will serve to describe the other half as well.

The structure of a center beam car is analogous to a deep beam having a tall central structure to approximate the web of a beam, or a web-like structure or truss assembly, a wide flange at the bottom, and a wide flange at the top. In the case of railroad car 20, the central web-work assembly is indicated generally as 30 and runs in the longitudinal direction (that is, the rolling direction of the car), the top flange function is served by a top truss assembly 32, and the lower

8

flange function is performed by a lower flange assembly in the nature of a lateral support structure 34, upon which cargo can be placed, and that extends laterally outward to either side of a main center sill 36.

In detail, as shown in FIGS. 2, 3a and 3b, car 20 has at its lowest extremity main center sill 36, in the nature of a fabricated steel box beam that extends longitudinally along the centerline of car 20 throughout its length, having couplers 38 mounted at either end. Cross bearers 40 extend outwardly from center sill 36 to terminate at a pair of longitudinal left and right hand side sills 42, 44 that also run the length of the car. In the car illustrated, alternating cross-bearers 40 and crossties 41 extend laterally outward from center sill 36 on approximately 4 ft centers. Decking 46 is mounted to extend between cross-bearers 40, and crossties 41 providing a shear connection between adjacent cross-bearers when side loads are imposed on the car. Tapered risers 48 are mounted above the cross-bearers to form the base of a bunk for carrying loads. Risers 48 are tapered so that loads stacked thereupon will tend to lean inwardly toward the centerline of car 20. The combined structure of center sill 36, cross-bearers 40, and side sills 42, 44 and decking 46 provides a wide, lower beam or lower flange assembly extending laterally outward from the longitudinal centerline of car 20.

At either end of car 20 there are vertically upstanding fore and aft end bulkheads 50 and 52 which extend from side to side, perpendicular to the central longitudinal plane 26 of car 20. Each of bulkheads 50 and 52 has a base portion 53 adjoining decking 46, and an upper end 51 located upwardly away from decking 46. Running the full length of car 20 between end bulkheads 50 and 52 is an array 54 of upright posts 56, 57. Array 54 is reinforced by diagonal braces 58, 59, that provide a sheer path for vertical loads.

As also shown in FIGS. 3a and 3b, the array 54 of posts 56 (and 57) is surmounted by an upper beam assembly 60 that runs between the upper ends 51 of bulkheads 50 and 52. A deep beam top chord assembly is identified as 62. An open framework top truss 64 is mounted above, and connected to deep beam top chord assembly 62. Truss 64 has lateral wings 65 and 67 that are mounted to extend outboard from the central plane 26 of car 20 in a cantilevered manner. Truss 64 has longitudinal stringers 66, cross members 68, and web members 70 and 72.

Each of posts 56 has a central web 74 that lies in a vertical plane perpendicular to the plane 26 of car 20. Web 74 is tapered from a wide bottom adjacent main center sill 36 to a narrow top. The wide bottom portion is about 13½ inches wide, and at the top portion the inward taper is such as to yield a 6 inch width of section at the junction of top chord assembly 62 and top truss 64. At the outboard extremities of web 74 there are left and right hand flanges 76 and 78 that each lie in a longitudinal plane inclined at an angle α defined (from the vertical) by the slope of the taper of web 74. In the preferred embodiment, α is roughly 1.450°. At the top of each post 56, 57 web 74 has been trimmed back to a pair of tabs 80, 82 at the ends of flanges 76, 78. This yields a seat, socket, relief, or rebate in the nature of a generally U-shaped notch or slot 84 into which top chord assembly 62 can seat.

A horizontal cross-section of post 56 will generally have an H-shape, with web 74 lying centrally relative to flanges 76 and 78. Post 57, by contrast, although tapered in a similar manner to post 56, has a horizontal cross-section of a U-shaped channel, with its web being the back of the U, and the flanges being a pair of legs extending away from the back. Each diagonal member 58 (or 59) has a first end rooted at a lower lug 86 welded at the juncture of the base of one of

the posts **56** and decking **46** and main center sill **36**, and a second diagonal end rooted in an upper lug **88** at the juncture of another adjacent post **56** and top chord assembly **62**. Midway along its length, diagonal beam **58** (or **59**) passes through a post **57** intermediate the posts **56** to which diagonal **58** (or **59**) is mounted. It is intended that the respective flanges of the various posts **56** and **57** lie in the same planes on either side of the central plane **26** of car **20** to present an aligned set of bearing surfaces against which lading can be placed.

The incline of flanges **76** and **78** is such that they lie at roughly a right angle to the inward taper of risers **48** so that generally square or rectangular bundles can be stacked neatly in the clearance openings of the bunk defined between the underside of the top truss **64** and risers **48**.

In the preferred embodiment of FIGS. **2**, **3a**, **3b**, **4a** and **4b**, upper beam assembly **60** can be defined as the combination of top chord assembly **62** and top truss **64**. It has a cross section in the shape, generally, of a 'T', with the cross-bar of the T being defined by wings **65** and **67** of top truss **64**, and the stem **69** of the 'T' being defined by top chord assembly **62**, described more fully below.

Straps **92** are provided to attach to the out board, distal extremities of wings **65** and **67** of top truss **64**, to be wrapped outboard of the load, and to be tightened by a come-along, a winch, a pawl-and-ratchet type of mechanism, indicated generally as **94**, or similar tightening device mounted to the respective side sill **42** or **44**. An operator turns mechanism **94** with the aid of an extension bar or handle (not shown). When tightened, straps **92** bear against the outboard, upper corners of bundles indicated as **96**, tending to force their inboard, upper regions, indicated generally as **98**, most tightly against the upright car structure that extends along plane of symmetry **26**, namely array **54** and the outer shank, or skirt of stem **69** of upper beam assembly **60**.

The preferred embodiment illustrated in FIGS. **2**, **3a**, **3b**, **4a** and **4b** has an inside loading clearance indicated as 'A' of $137\frac{3}{16}$ inches perpendicular to rungs **48**. It also has a loading limit indicated as 'B' extending perpendicular to the slope of web **74**, at a height $132\frac{1}{2}$ inches above, and measured perpendicular to, risers **48**. The nominal load height is then 132 inches for 4 bundles at 33 inches each, including dunnage. The nominal load height, in general, for $31\frac{1}{2}$ inch bundles of kiln dried lumber is thus the largest integer multiple of 33 inches that is less than the load limit height. In the illustrations of FIGS. **2**, **3a**, **3b**, **4a** and **4b**, this loading limit permits 49 inch wide bundles to fall within the loading envelope **39** defined by AAR plate 'C' as shown by dimension 'D' in FIG. **3b**. Dimension 'D' also permits a load 131 inches high and 51 inches wide to fall within the desired loading envelope **39** of AAR plate C.

Deep beam section **90** is shown in cross-section in FIG. **4a**. It includes a first, or upper formed section **120** in the shape of an inverted U, having a back **122** and left and right hand legs **124**, **126**. Legs **124**, **126** are splayed outwardly relative to the vertical at angle α to match the angle of the taper of the flanges of posts **56** and **57**. Upper-formed section **120** also has inwardly stepped shoulders **121** and **123** to accommodate the mating ears of gusset plates **125** and **127** which join top truss **64** to top chord assembly **62**. Deep beam section **90** also includes a second formed section **130** that is generally U-shaped, having a back **132**, and a pair of left and right hand legs **134** and **135**. Legs **134** and **135** each have a proximal region **138**, **139** relative to back **132** that is stepped inwardly to form a shoulder **140** and a neck **142** of a size to nest between tabs **80**, **82** of post **56** (or **57**). Tabs **80**, **82** are

formed by trimming back web **74** locally to conform to the depth of shoulder **140**. Legs **134**, **135** also each have an inwardly stepped toe **148**, **149** stepped inward a distance equal to the wall thickness of legs **134**, **135** such that toes **150**, **151** of legs **124**, **126** of member **120** can overlap, and seat outside of, outside toes **148**, **149** respectively, and be fillet welded in place. Legs **134** and **135** are angled inward to yield slope continuity with both legs **124** and **126** and also with flanges **76** and **78** of post **56** (or the corresponding flanges of post **57** as the case may be). That is, legs **134** and **135** are toed inward at the same angle from the vertical at which legs **124**, **126** are splayed outward such that the exterior surfaces are flush with, and lying in the planes of, the respective flanges of posts **56** and **57**. The exterior surfaces so defined can be termed skirts.

Gussets **152** and **154** are welded inside formed section **120** and **130** respectively at longitudinal stations along the length of car **20** corresponding to the various longitudinal stations of the webs of posts **56** and **57** respectively, thus providing a substantially continuous web from main sill **36** to top truss **64**. There is, however, a web discontinuity between gusset **152** and gusset **154** indicated by gap 'G', seen in FIG. **4b**. In light of this discontinuity, gussets **152** and **154** have a main web leg **156**, **157** that, when installed, lies in the vertical plane of web **74** and a toe **158**, **159** extending at a right angle therefrom, lying in a horizontal plane. The lateral edges of toes **158** and **159** are welded along the inside faces of toes **148**, **149** and **150**, **151** respectively and extend a distance comparable to the width between the respective toes at that point. In the preferred embodiment the overall height of top chord assembly **64** is 27 inches, with $\frac{1}{4}$ inch wall thickness on legs **156**, **157**, **134** and **135**. In the preferred embodiment the length of legs **134**, **135** is 13.5 inches, and the overall length of legs **156**, **157** is 14.5 inches. Nominally, shoulder **140** overlaps tabs **80** and **82** by 2 inches. That is, tabs **80**, **82** extend 2 inches beyond web **74**. Toes **158** and **159** are both 6 inches long, and the nominal width of gap 'G' is about 6.75 inches.

In this way, when assembled, legs **134**, **135** and **156**, **157** form respective left and right hand outwardly facing bearing surfaces against which a load may bear, and over which a reaction force to tension in the tightening straps can be spread. In the span between the stations of adjacent posts **56** and **57**, the skirts, or bearing surfaces, formed in this way are reinforced by the laterally inward web, (that is, back **132**) which connects both skirts (that is, legs **124** and **134**, and legs **126** and **135**). The laterally inward reinforcement need not be immediately behind the respective skirt or facing, but rather can be offset, as illustrated in FIG. **4a**, with the influence of the web stiffening the face some distance away. The web is "inward" of the skirts in the sense of lying behind, or shy of, the profile of the contact interface with the wood bundles, since the reinforcement lies toward the centerline of the rail car, rather than proud of, the respective skirt faces. In this way an inwardly disposed stiffener will not protrude and rub against an object bearing against the outwardly facing surface of the respective skirt.

In an alternative embodiment shown in FIGS. **5a** and **5b** a deep beam section **170** has left and right hand formed sections **172**, **174** surmounted by a rectangular tube **176**, upon which top truss **64** is mounted. Each of sections **172**, **174** has a main sheet **180**, an inwardly stepped shoulder **182**, an inwardly extending leg **184** and an upturned toe **186**. In place of gussets **152** and **154**, section **170** has gussets **188**, **190** having a main, vertical leg **192**, **193** and a horizontal leg **194**, **195**. Vertical legs **192**, **193** are contoured to match the inside wall shape of formed sections **172**, **174** respectively,

and are located at longitudinal stations to correspond to the longitudinal stations of the webs of posts **56**, **57**, as above. Vertical legs **192**, **193** are separated by a vertically extending gap having a width 'H'. Once gussets **188**, **190** are welded in place, formed sections **172**, **174** are welded along the seam where legs **184** of sections **172**, **174** abut along the centerline of car **20**. As above, the step in sections **172**, **174** is of a size to seat between tabs **80**, **82** of posts **56** (or **57**), and the distal tips of main sheets **180** are fillet welded to the side faces of tube **176**. As above, there is slope continuity between main sheets **180** and the corresponding flanges **76**, **78** of posts **56**, **57**.

In the alternative embodiment of FIGS. **6a** and **6b**, a deep upper beam assembly **200** has a pair of angle irons **202** and **204** welded longitudinally inside tabs **80** and **82** of posts **56** and **57**. Angle irons **202** and **204** each have an inwardly extending toe **206**, **207** which bottoms on the cut edge of web **74**, and an upwardly extending leg bent to conform to the slope of flanges **76** and **78** of posts **56** and **57**. Beam **200** also has a pair of left and right formed sections **208**, **209** each having a main sheet portion **210**, **211**, an inwardly extending leg **212**, **213** and a re-entrant toe **214**, **215**.

On assembly, L-shaped gussets **216**, **217** are welded in each of sections **208**, **209**. Gussets **216** and **217** each have a profile to match the inside profile of the upper regions of main sheet portions **210**, **211**, legs **212**, **213** and toe **214**, **215**. The toes of gussets **216** and **217** are welded along their outboard edges to the inside face of main sheet portions **210**, **211**. Sections **208** and **209** are welded along the centerline seam between abutting toes **214** and **215**. A further, main, gusset **220** is trimmed to a shape to permit welding of its top edge to the underside of the toes **218**, **219** of gussets **216**, **217**, its side edges to the inner face of the lower regions of main sheet portions **210** and **211**; once welded in this manner, the base leg **222** of gusset **220** can be welded to toes **206** and **207** of angle irons **202** and **204**, with a plug weld **223** formed to fill the longitudinal gap therebetween. Gusset **220** is also trimmed to have reliefs **224**, **225** to permit entry between the upwardly extending legs of angle irons **202**, **204**. Gussets **216**, **217** and **220** are located at longitudinal stations that correspond generally to the longitudinal stations of posts **56** and **57** as the case may be. Legs **212**, **213** of sections **208**, **209** form, ideally, a flat surface to weld to top truss assembly **62**, as before. Similarly, when installed, main sheet portions **210**, **211** have slope continuity with flanges **76** and **78** of posts **56** and **57**.

In the alternative embodiment of FIGS. **7a** and **7b**, a deep upper beam **230** has a pair of formed sections **232**, **234**, a rectangular steel tube **236**, a main gusset **238** and minor gussets **240** and **242**. On assembly, minor gussets **240** and **242** are welded inside the lower regions of formed section **232** and **234**, being shaped to conform to the shape of the lower region of outer main sheets **246**, **248**, inwardly stepped shoulder **250**, **252**, and inwardly extending legs **254**, **256**. A gap 'P' is left between the respective inboard edges of gussets **240** and **242**, and their outboard edges are welded to the inner face of main sheets **246**, **248**. Gussets **240**, **242** are trimmed to be clear of re-entrant toes **258**, **260**. Main gusset **238** is welded upon minor gussets **240**, **242**, with its lateral edges welded to the inside face of main sheets **232** and **234**. Tabs **262**, **264** at the distal ends of main sheets **246**, **248** embrace the outer side faces of steel tube **234**.

In the alternative embodiment of FIGS. **8a** and **8b**, a deep upper beam assembly **270** has a longitudinally extending inverted C-channel **272** upon which is welded a generally U-shaped formed section **274** having a back **276** and upwardly extending legs **278**, **280** bent to lie on the slopes of

the flanges of posts **56** and **57**, as above. The distal ends of legs **278** and **280** abut the lower edges of a pair of skirt plates **282** and **284**. A weld is formed along the abutting edges of the legs and skirts. At their furthest ends, skirt plates **282**, **284** are welded to the outside faces of a 4"x6" steel tube **290**. Top truss assembly **62** surmounts assembly **270**. Minor gussets **286** are welded inside C-channel **272** at the longitudinal stations of posts **56** and **57**, as above, and gussets **288** are welded inside legs **278**, **280** and plates **282**, **284** thereby providing a form to define the angular profile upon which they lie. As before, that profile is such as to yield a surface lying flush with the outer surfaces of posts **56** and **57**.

The alternate embodiment of deep beam **300** of FIGS. **9a** and **9b** is similar to that of FIGS. **8a** and **8b**, but differs insofar as C-channel **272** and formed section **274** have been combined into a singular formed section **302** having inwardly stepped shoulders **304** to yield a plug shaped head **306**, similar to that described in the context of FIGS. **4a**. Further, rather than straight legs **278** and **280**, formed section **302** has inwardly stepped toes **308** and **310**, again, similar to those shown in FIG. **4a**. Skirt plates **312** and **314**, similar to skirt plates **282** and **284**, again extend between toes **308** and **310** to terminate on the outer side faces of a rectangular steel tube **316**.

In this instance a large gusset **318** is welded inside section **302**, and plates **312** and **314**. Gusset **318** has a vertical leg **320** having a profile cut to yield the desired slope continuity with the flanges of posts **56** and **57**.

The alternate embodiment of deep beam **330** of FIG. **10** is similar to that of FIG. **8a**. However, as in FIG. **9a**, C-channel **272** and formed section **274** have been supplanted by a single formed section **332** having a back **334**, a pair of legs **336**, **338** having inwardly stepped shoulders **337**, **339** and a pair of distal toes. A gusset **340** is mounted within formed section **332** at each of the longitudinal stations of car **20** corresponding to the longitudinal stations of the webs of posts **56** and **57**, as described above. However, gussets **340** terminate in a horizontal leg lying shy of the tips of the distal toes of legs **336** and **338** such that another formed section **342** can seat between them. Formed section **342** has a back **344**, legs **346**, **348** and shoulders **350**, **352**. An internal stiffener in the nature of a gusset **354** is located at each of the longitudinal post stations. Back **344** provides a horizontal web sufficiently close to top truss assembly **62** that no rectangular steel tube is employed. As before, the outer faces of legs **346**, **348** and legs **334**, **336** are intended to lie in the same planes as the flanges of posts **56** and **57**. The external faces of each of formed sections **332** and **342** each extend about a foot in depth, relative to top truss assembly **62**, and present, more or less, a 2 foot wide skirt, or band, that overlaps the load limit, and the maximum loading height.

In the embodiment of FIG. **11**, a deep beam assembly **360** is generally similar to deep beam assembly **330**, but rather than have step-shouldered formed sections it has a C-channel **362** for mounting between tabs **80** and **82** as in FIG. **8a** above, with gussets **364** mounted as described in FIG. **8a**. Above this is a first pair of angle irons **366**, **368**, bent to present outer faces lying on the desired slope of the flanges of posts **56** and **57**. Angle irons **366**, **368** are welded on a series of lateral gussets **370**, again, at the longitudinal stations of vertical posts **56** and **57**. Angle irons **366** and **368** are also welded along the tips of their inwardly extending toes **372**, **374**. Another pair of angle irons **380**, **382** are welded on an array of gussets **384**, and along a seam at their inwardly extending toes **385**, **386**, and mounted above angle irons **366** and **368**, as shown, such that their generally upwardly extending legs, and the consequent skirt-like sur-

13

face they present, lie flush with, and on the same slopes as, the respective flanges of posts **56** and **57**.

The embodiment of FIG. **12a** shows a half view of a retrofit installation. (As the section is symmetrical about the centerline of the car, only one half is illustrated.) An existing center beam post is shown as **400**. It has a web **402** trimmed down to leave tabs **404** and **405** which lie to either side of, and are welded to, a rectangular steel tube **406** upon which a top truss assembly **408** is mounted. A skirt panel **410** is formed with a stiffener in the nature of an inwardly bent toe **412**. The length of main leg **414** is roughly 2 feet, such that its outer face overlaps both the maximum load height and the load limit height. Toe **412** is trimmed to accommodate the flanges of post **400** (analogous to posts **56** or **57**). An additional reinforcement, or longitudinal stiffener, in the nature of angle **416** of a length to lie between successive posts **400**, is welded to the inner face of main leg **414** at an intermediate level roughly halfway between top truss assembly **408** and toe **412**. Angle **416** will tend to cause main leg **414** to resist lateral deflection between adjacent posts **400**, thereby tending to assist in maintaining main leg **414** in a position to spread loads placed against it. It is preferred that panel **410** be $\frac{3}{16}$ inches thick, but could be as thick as $\frac{1}{2}$ or $\frac{5}{8}$ inches. Although panel **410** is preferably a metal sheet welded to posts **400**, a different fastening means, such as rivets, bolts or the like, could be used. A smooth steel face is preferred, but other metals, such as aluminum, could be used, or a suitable, rot resistant, UV resistant polymer could be selected, either as a solid sheet or as a face coating or layer, or sheet, upon a metal substrate. It is preferred that the material chosen be a non-consumable material, that is, one that may tend not to be prone to require frequent replacement such as may be required if softwood lumber battens are used, and also one that has little or no tendency to develop wood rot or to support the growth of molds.

Panel **410** need not be integrally formed with bent toe **412**, but could be fabricated by using a flat sheet **420** as the external face plate, with an angle iron **422**, or similar stiffener, welded along the inward facing bottom edge of the face plate between pairs of posts **400**, as indicated in the other half view shown in FIG. **12b**.

FIG. **12c** is again a half section, showing a hollow cell panel **424** in place of panel **410**. Hollow cell panel **424** has an external skin **426**, an internal skin **428**, and an intermediate hollow cell core **427** for carrying shear between skins **426** and **428**. The hollow cells usually have a hexagonal columnar shape, the columns running perpendicular to the skins. The thickness of hollow cell panel **424** has been exaggerated for the purposes of illustration. Although skins **426** and **428** may be made of steel, they may also be made of other substances, such as structural polymers, reinforced polymers, aluminum, or other suitable material.

FIG. **12d** is similar to FIG. **12c**, but web **430** of post **432** has been trimmed back to permit outwardly facing external face **434** of hollow cell panel **436** to lie flush with flange **438** of post **432**. Hollow cell panel **436** is similar in construction to hollow cell panel **424**, having a pair of skins and a hollow core.

FIGS. **12c** and **12f** correspond to FIGS. **12c** and **12d** respectively, and illustrate the use of a corrugated core sandwich, either standing proud of the flange of the post, as illustrated by sandwich **429** in FIG. **12e**, or flush with a trimmed down flange **431** as shown by sandwich **433** in FIG. **12f**. The corrugated sandwiches have inner and outer metal skins, with a reverse folded, corrugated core maintaining the skins in a spaced apart, parallel planar relationship.

14

In each of the embodiments illustrated in FIGS. **12a**, **12b**, **12c**, **12d**, **12e** and **12f** the vertical extent of the skirt can be chosen according to the lading customarily carried by the car. As noted above, in general the skirt overlaps the nominal loading height, and extends a modest distance below the nominal loading height, whether 6 inches, 12 inches, 18 inches, 24 inches, 30 inches, or 36 inches. The skirt may also tend to overlap the maximum load limit height, and, further still, to be joined at a welded lap joint to the top chord, or top chord assembly.

The embodiment of FIG. **13** shows a deep beam assembly **440** that is similar to deep beam assembly **360** of FIG. **11** but does not have slope continuity with the flanges of posts **56** and **57**. Rather, the sides **442** and **444** of deep beam assembly **440** are parallel, and rise generally vertically.

The embodiment of FIG. **14** is similar to the embodiment of FIG. **13**, except insofar as it has a single formed section **446** with shoulders **448** in lieu of a C-channel **450** and section **452**. Similarly, its upper formed section **454** also has shoulders **456**, in contrast to upper section **458** of assembly **440**.

In the embodiment of FIG. **15** deep beam assembly **470** has an inverted U-shaped formed section **472** having parallel legs **474**, **476**. A notch has been cut in web **478** of post **480** such that a longitudinally extending rectangular steel tube **482** can seat between tabs **484** and **486** of flanges **488** and **490**. The distal tips **492** and **494** of legs **474** and **476** are welded along the side faces of tube **482**. In the embodiment of FIG. **16** a formed section **500** is used in place of rectangular steel tube **482**. In the cases of both FIG. **15** and FIG. **16**, the overall depth of the side skirts defined by legs **474**, **476** or **502**, **504**, is roughly half that of the embodiments of FIGS. **4a**, **5a**, **6a**, **7a**, and **8a**, being roughly 1 foot. This width overlaps both the load limit height and the maximum load height.

In the preferred embodiment of FIGS. **2**, **3a**, **3b**, **4a** and **4b**, legs **76** and **78** extend from a root at the join to top truss **64** to a level below the upper load limit. Although other cargoes can be carried, the 132 and $\frac{1}{2}$ inch load limit corresponds to a stack of 4 bundles of sawn lumber, each bundle being 32 inches thick and 49 inches wide for a total of 128 inches, with 1 and $\frac{1}{2}$ inch thick dunnage between the bundles, for an additional 4 and $\frac{1}{2}$ inches, legs **76** and **78** are roughly 24 inches long so that the bottom edge of legs **76** and **78** will extend down half the height of the top bundle to act as a skirt against which a larger bearing area of the bundle can bear, as compared to the width of the flanges of posts **56** by themselves. The skirt has a mid level reinforcement between its upper and lower extremities, namely web stiffener **84** to discourage lateral deflection of the skirt, or bowing inward.

In alternative embodiments, the level of the bottom edge of the legs could be as little as one board (1 and $\frac{1}{2}$ inches, kiln dried wood) below the top edge of the design bundle height, but is expected to be most commonly 12 inches, 24 inches (as in the preferred embodiment) or 30 inches deep when measured from the join to the top truss.

It is possible to manufacture a generally similar center beam car to fall within the loading profile defined by AAR plate 'F', or some other height. In that case, the desired load limit height is the height that is the largest integer multiple of 33 that is less than the clearance opening. The minimum height of the bottom edge of the leg, or skirt, is desirably 1 and $\frac{1}{2}$ inches or more below the nominal load height, typically such that the overall height of the skirt is, nominally, an integer multiple of 6 that is at least 12 inches. Preferably, the skirt extends to a height that is at least half way down the top

bundle of the nominal design load, and possibly to a height that is the full depth of the top bundle.

Although the main deck could be a continuous decking structure, this need not necessarily be so. The main deck, or lower beam structure could be in the form of an open truss, or grid work. Car **20**, is preferably a car of all-steel construction. However, although the web work assembly of the center beam, and the top truss section is preferably a welded steel fabricated structure, it could be made of aluminum.

Various embodiments of the invention have now been described in detail. Since changes in and or additions to the above-described best mode may be made without departing from the nature, spirit or scope of the invention, the invention is not to be limited to those details, but only by the appended claims.

I claim:

1. A center beam rail road car having a longitudinal centerline, the rail road car being supported by rail car trucks at either end thereof, said railroad car comprising: a cargo support structure borne between the trucks, upon which cargo can be carried; said cargo support structure including decking having a first end, a second end, and upstanding bulkheads mounted at each of said first and second ends; each of said bulkheads having a base adjoining said decking and an upper end upwardly distant therefrom; a web work assembly including an array of posts mounted along the longitudinal centerline of the rail road car, said array extending upwardly of said cargo support structure; said web work assembly having a lower region adjacent to said cargo support structure, and an upper region distant from said cargo support structure; an upper beam located above said web work assembly, said upper beam running between said upper ends of said bulkheads; said upper beam having at least one structural member mounted to said upper region of said web work assembly, said structural member having a longitudinally extending face against which lading *in the form of bundles of forest products having a length of at least 8 ft, and a depth of at least 16 inches* placed laterally outward of said posts can bear, *said bundles of forest products being oriented such that the longitudinal axes of the bundles are parallel to the longitudinal centerline of the rail road car*; and a reinforcement member extending laterally inward of said face to discourage lateral deflection of said longitudinally extending face.

2. The railroad car of claim **1** wherein said longitudinally extending structural member and said reinforcement member are portions of a longitudinally extending, formed structural section.

3. The center beam car of claim **1** wherein said car has a load limit height lying at a distance measured upwardly of said cargo support structure, and said face extends from a first height that is at least as high as said load limit height to a second height that is lower than said load limit height.

4. The center beam car of claim **3** wherein the distance between said first and second heights is at least 12 inches.

5. The center beam car of claim **3** wherein the distance between said first and second heights is at least 24 inches.

6. The center beam car of claim **3** wherein the distance between said first and second heights is at least 30 inches.

7. The center beam car of claim **1** wherein said face extends between two posts of said array.

8. The center beam car of claim **1** wherein:

said face extends longitudinally past at least one of said posts;

said face has a portion that is longitudinally distant from said one of said posts; and

said reinforcement stiffens said longitudinally distant portion.

9. The center beam car of claim **1** wherein said center beam car has a pair of said faces, one of said faces being located to engage loads placed laterally to one side of said web work assembly, and the other of said faces being located to engage loads placed laterally to the other side of said web work assembly.

10. The center beam assembly of claim **9** wherein said reinforcement is a web extending between said pair of faces.

11. A center beam rail road car having a longitudinal centerline, the center beam rail road car being supported by rail car trucks at either end thereof, said center beam rail road car comprising: a center sill extending between said trucks; a decking structure extending laterally of said center sill, upon which loads can be placed; an open web work structure extending upwardly from said center sill; an upper beam mounted upon said open web work structure, said upper beam being mounted to said open web work structure at a joining interface; said upper beam having a pair of longitudinally extending, laterally spaced apart, planar members, said planar members each having a smooth outwardly facing surface against which *[cargo] lading in the form of bundles of forest products having a length of at least 8 ft and a depth of at least 16 inches* placed laterally outboard thereof can bear, *said bundles of forest products being oriented such that the longitudinal axes of the bundles are parallel to the longitudinal centerline of the rail road car*; and said upper beam planar members having an outside lateral dimension matching said open web work structure at said joining interface.

12. The center beam rail road car of claim **11** wherein said upper beam and said open web work structure have slope continuity at said joining interface.

13. The center beam rail road car of claim **12** wherein said open web work structure has a taper from bottom to top and said planar members are angled to match the taper of said web work structure.

14. The center beam rail road car of claim **11** wherein:

said open web work structure includes an array of upright posts spaced along said longitudinal centerline;

said posts have notched upper ends; and

said upper beam has a longitudinally extending chord member formed to seat in said notched upper ends of said posts.

15. The center beam railroad car of claim **14** wherein said chord member includes a U-shaped pressing, said planar members being formed integrally therewith.

16. The center beam rail road car of claim **15** when said U-shaped pressing has a back and said planar members have an inwardly stepped shoulder extending therealong for seating in said notches of said posts.

17. The center beam rail road car of claim **14** wherein said longitudinally extending chord member is a channel having a back and legs, said back being of a width to seat in said notches of said posts, and said planar members being mounted to said legs.

18. The center beam rail road car of claim **14** wherein said longitudinally extending top chord member is a tube, and said planar members are side portions of said tube.

19. The center beam railroad car of claim **11** wherein:

said web work structure includes a plurality of upright posts spaced along the longitudinal centerline of said railroad car and diagonal bracing mounted thereto;

each of said posts has a tapering width transverse to said longitudinal centerline of said rail road car, said posts tapering from a wider position adjacent to said decking structure to narrower portion at a top end adjacent to said upper beam;

17

each of said posts has a notch defined in said top end thereof;

said upper beam has

a first U-shaped formed member seated in said notch, said first U-shaped member having a back and upstanding legs;

a second U-shaped, formed member having a back and downwardly extending legs;

said legs of said first and second U-shaped members co-operate to define said planar members; and

said legs of said first and second U-shaped members are formed at an angle matching the taper of said posts.

20. The center beam rail road car of claim 11 wherein:

said posts have notched upper ends; and

said upper beam assembly has a longitudinally extending chord member formed to seat in said notched upper ends of said posts.

21. The railroad car of claim 11 wherein said planar members are each formed of a hollow cell material.

22. The railroad car of claim 11 wherein said planar members are each formed of a corrugated section with an outer skin, said outer skin defining said smooth, outwardly facing surface.

23. The railroad car of claim 11 wherein said planar members are laterally inwardly reinforced to discourage bowing thereof.

24. The railroad car of claim 11 wherein said upper beam includes a longitudinally extending tube.

25. A center beam car having a longitudinal centerline, the center beam car being supported by rail car trucks at either end thereof, said center beam rail car comprising: a center sill extending between said trucks; a decking structure extending laterally of said center sill upon which loads can be placed; an open truss structure extending upwardly from said center sill; said open truss structure including an upper beam assembly mounted upwardly of, and parallel to, said center sill; said open truss structure including an array of posts extending between said center sill and said upper beam assembly; said upper beam assembly having a pair of longitudinally extending, laterally spaced apart, planar members, said planar members each having an outwardly facing surface against which [cargo] *lading in the form of bundles of forest products having a length of at least 8 ft and a depth of at least 16 inches* placed laterally outboard thereof can bear, said bundles of forest products being oriented such that the longitudinal axes of the bundles are parallel to the longitudinal centerline of the rail road car; said outwardly facing surfaces standing proud of said posts; and said planar members each having a longitudinally extending reinforcement mounted laterally inboard thereof to discourage lateral deflection of said faces when cargo placed laterally outward thereof bears there against.

26. The center beam railroad car of claim 25 wherein said longitudinally extending structural member and said reinforcement member are portions of a longitudinally extending, formed structural section.

27. The center beam car of claim 25 wherein said car has a load limit height lying at a distance measured upwardly of said cargo support structure, and said face extends from a first height that is at least as high as said load limit height to, a second height that is lower than said load limit height.

28. The center beam car of claim 27 wherein the distance between said first and second heights is at least 24 inches.

29. The center beam car of claim 27 wherein the distance between said first and second heights is at least 12 inches.

30. The center beam car of claim 27 wherein the distance between said first and second heights is at least 30 inches.

18

31. The center beam car of claim 25 wherein said center beam car has a pair of said surfaces, one of said outwardly facing surfaces is located to engage lading placed laterally to one side of said posts, and the other of said outwardly facing surfaces is located to engage lading placed laterally to the other side of said posts. between said surfaces.

32. The center beam car of claim 31 wherein said reinforcement is a web extending.

33. The center beam railroad car of claim 25 wherein said posts have outwardly facing flanges, and said flanges and said surfaces lie in parallel planes.

34. The center beam rail road car of claim 25 wherein said posts have a taper from bottom to top and said surfaces are angled to match the taper of said posts.

35. The center beam railroad car of claim 25 wherein said upper beam assembly includes a U-shaped pressing, said surfaces being formed integrally therewith.

36. The center beam rail road car of claim 35 wherein said U-shaped pressing has a back and an inwardly stepped shoulder for seating in said notches of said posts.

37. The center beam rail road car of claim 25 wherein said upper beam assembly includes a channel having a back and legs, said back being of a width to seat in said notches of said posts, and said legs defining said surfaces.

38. The center beam rail road car of claim 25 wherein said upper beam assembly includes a longitudinally extending top chord member, said top chord member is a tube, said tube has side portions, and said surfaces are defined by said side portions of said tube.

39. The railroad car of claim 25 wherein said posts have a laterally outwardly facing flange, and said surface stands proud thereof a distance less than $\frac{3}{4}$ inches.

40. The railroad car of claim 25 wherein said planar members are each formed of a hollow cell material having an outwardly facing skin.

41. The railroad car of claim 25 wherein said upper beam assembly includes a tube, said laterally spaced apart planar members being sides of said tube.

42. A rail road car having a longitudinal centerline, comprising: a pair of rail car trucks and a center beam assembly carried thereupon; said center beam assembly having a center sill; a cargo support structure extending laterally of said center sill assembly; and a plurality of posts extending upwardly from said center sill, said cargo support structure including decking having a first end, a second end, and upstanding bulkheads mounted at each of said first and second ends; each of said bulkheads having a base adjoining said decking and an upper end upwardly distant therefrom; said posts having a lower region adjacent said center sill and an upper region distant from said center sill; a non-consumable, longitudinally extending upper beam assembly mounted to said upper region of said posts and running between said upper ends of said bulkheads, said upper beam assembly including a longitudinally extending structural member presenting a bearing surface facing laterally outward, against which [cargo] *lading in the form of bundles of forest products having a length of at least 8 ft and a depth of at least 16 inches* can bear, said bundles of forest products being oriented such that the longitudinal axes of the bundles are parallel to the longitudinal centerline of the rail road car; said bearing surface being reinforced to discourage lateral deflection thereof.

43. The railroad car of claim 42 wherein said posts have a laterally outwardly facing flange and said laterally outwardly facing bearing surface is mounted flush with said flange.

44. The railroad car of claim 42 wherein said posts have a laterally outwardly facing flange, and said bearing surface stands proud thereof a distance less than $\frac{3}{4}$ inches.

19

45. The rail road car of claim **42** wherein said longitudinally reinforced structural member is formed of a hollow cell material having an outwardly facing skin.

46. The rail road car of claim **42** wherein said longitudinally reinforced structural member is formed of a corrugated section with an outer skin against which objects may bear.

47. The rail road car of claim **42** wherein said longitudinally reinforced structural member is laterally inwardly reinforced to discourage bowing thereof between adjacent pairs of said posts.

20

48. The rail road car of claim **42** wherein said longitudinally reinforced structural member is a tube.

49. The rail road car of claim **42** wherein said posts have a laterally outwardly facing flange, and said bearing surface stands proud thereof.

50. The railroad car of claim **42** wherein said planar members are each formed of a corrugated section with an outer skin against which objects may bear.

* * * * *