

US00RE41283E

(19) **United States**  
(12) **Reissued Patent**  
**Evans et al.**

(10) **Patent Number:** **US RE41,283 E**  
(45) **Date of Reissued Patent:** **Apr. 27, 2010**

(54) **POWER CONNECTOR WITH SAFETY FEATURE**

(75) Inventors: **Robert F. Evans**, Bedford, NH (US);  
**Jeffrey W. Allison**, Etters, PA (US);  
**Brian M. Rohrbaugh**, Glen Rock, PA (US)

(73) Assignee: **FCI Americas Technology, Inc.**, Carson City, NV (US)

(21) Appl. No.: **11/862,464**

(22) Filed: **Sep. 27, 2007**

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **7,037,142**  
Issued: **May 2, 2006**  
Appl. No.: **11/227,666**  
Filed: **Sep. 15, 2005**

U.S. Applications:

(63) Continuation of application No. 10/352,531, filed on Jan. 28, 2003, now abandoned.

(51) **Int. Cl.**  
**H01R 13/64** (2006.01)

(52) **U.S. Cl.** ..... **439/680**; 439/79; 439/633

(58) **Field of Classification Search** ..... 439/680,  
439/681, 682, 677, 633, 79  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,430,011 A 11/1947 Gillentine ..... 173/361

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE 23 50 834 4/1975  
DE 34 41 416 A1 5/1986  
DE 40 01 104 A1 7/1991

EP	0 465 013	1/1992
EP	0 724 313	7/1996
EP	0 951 102 A2	10/1999
EP	1091449	9/2004
FR	2 699 744	6/1994
GB	2 168 550	6/1986
JP	05344728	12/1993
JP	06068943	3/1994
JP	07169523	7/1995
JP	08096918	4/1996
JP	09 055 245	2/1997
JP	09199215	7/1997
JP	13135388	5/2001
JP	2003217785	7/2003
KR	100517561 B1	9/2005
WO	WO 200016445	3/2000
WO	WO 2002103847	12/2002
WO	WO 2005065254	7/2005
WO	WO 2007064632	6/2007

**OTHER PUBLICATIONS**

U.S. Appl. No. 12/317,366, filed Dec. 22, 2008, Minich.  
Metral 1000 Series, PCB Mounted Receptacle Assembly,  
FCI Web Site page, 2001, 1 p.

(Continued)


*Primary Examiner*—Brigitte R Hammond

(74) *Attorney, Agent, or Firm*—Woodcock Washburn LLP

(57) **ABSTRACT**

Electrical receptacle connectors are provided including an insulative housing and AC power contacts disposed therein that are configured for engaging an external power supply. The receptacle connectors are employed with a safety guard for restricting operator access to hot AC power contacts when disconnected from complementary header connectors. Preferred safety guards include projections extending along at least a portion of perimeter areas surrounding housing apertures that provide access to engaging portions of the AC power contacts. The projections define a safety gap between human digits directed toward the housing apertures and the AC power contacts.

**7 Claims, 5 Drawing Sheets**



# US RE41,283 E

Page 2

## U.S. PATENT DOCUMENTS

3,208,030 A	9/1965	Evans et al.	4,979,074 A	12/1990	Morley
3,286,220 A	11/1966	Marley et al. .... 439/680	4,990,099 A	2/1991	Marin et al. .... 439/284
3,497,850 A	2/1970	Gallo, Sr. .... 337/197	5,016,968 A	5/1991	Hammond et al.
3,538,486 A	11/1970	Shlesinger, Jr. .... 439/268	5,024,610 A	6/1991	French et al. .... 439/857
3,596,235 A	7/1971	Teurlings .... 439/907	5,046,960 A	9/1991	Fedder et al.
3,669,054 A	6/1972	Desso et al. .... 113/119	5,052,953 A	10/1991	Weber .... 439/857
3,748,633 A	7/1973	Lundergan .... 339/217	5,066,236 A	11/1991	Broeksteeg .... 439/79
3,750,092 A	7/1973	Bury .... 339/192 RL	5,077,893 A	1/1992	Mosquera et al. .... 29/882
3,789,348 A	1/1974	Lenaerts et al. .... 339/198 R	5,082,459 A	1/1992	Billman et al. .... 439/637
3,871,015 A	3/1975	Lin et al. .... 357/67	5,094,634 A	3/1992	Dixon et al. .... 431/751
3,910,671 A	10/1975	Townsend .... 339/97 R	5,107,328 A	4/1992	Kinsman .... 357/74
3,942,856 A	3/1976	Mindheim et al. .... 339/74	5,108,301 A	4/1992	Torok .... 439/263
3,944,312 A	3/1976	Koenig .... 339/59 R	5,137,959 A	8/1992	Block et al.
4,005,923 A	2/1977	Davis, Jr. .... 339/157	5,139,426 A	8/1992	Barkus et al.
4,073,564 A	2/1978	Davis, Jr. .... 339/157	5,151,056 A	9/1992	McClune
4,076,362 A	2/1978	Ichimura .... 339/75	5,152,700 A	10/1992	Bogursky et al.
4,082,407 A	4/1978	Smorzaniuk et al.	5,158,471 A	10/1992	Fedder et al. .... 439/80
4,136,919 A	1/1979	Howard et al. .... 339/75	5,173,063 A	12/1992	Barkus et al. .... 439/681
4,159,861 A	7/1979	Anhalt .... 339/75	5,174,770 A	12/1992	Sasaki et al. .... 439/108
4,224,486 A	9/1980	Zimmerman, Jr. et al. . 200/51.1	5,194,480 A	3/1993	Block et al.
4,227,762 A	10/1980	Scheiner .... 339/91 R	5,207,591 A	5/1993	Ozaki et al. .... 439/212
4,260,212 A	4/1981	Ritchie et al. .... 339/97	5,213,868 A	5/1993	Liberty et al.
4,288,139 A	9/1981	Cobaugh et al. .... 339/74	5,214,308 A	5/1993	Nishiguchi et al.
4,322,120 A	3/1982	Rilling .... 439/907	5,238,414 A	8/1993	Yaegashi et al. .... 439/108
4,371,912 A	2/1983	Guzik .... 361/417	5,238,416 A	8/1993	Dickie .... 439/148
4,383,724 A	5/1983	Verhoeven .... 439/510	5,254,012 A	10/1993	Wang .... 439/263
4,402,563 A	9/1983	Sinclair .... 339/75	5,274,918 A	1/1994	Reed .... 29/882
4,473,113 A	9/1984	Whitfield et al.	5,281,168 A	1/1994	Krehbiel et al. .... 435/595
4,500,160 A	2/1985	Bertsch .... 339/166	5,286,212 A	2/1994	Broeksteeg
4,505,529 A	3/1985	Barkus .... 339/17	5,295,843 A	3/1994	Davis et al.
4,533,187 A	8/1985	Kirkman	5,298,791 A	3/1994	Liberty et al.
4,536,955 A	8/1985	Gudgeon .... 29/840	5,302,135 A	4/1994	Lee .... 439/263
4,545,610 A	10/1985	Lakritz et al. .... 29/589	5,321,582 A	6/1994	Casperson
4,560,222 A	12/1985	Dambach .... 339/75	5,358,422 A	10/1994	Schaffer et al. .... 439/346
4,626,637 A	12/1986	Olsson et al. .... 200/284	5,362,249 A	11/1994	Carter .... 439/357
4,659,158 A	4/1987	Sakamoto et al. .... 339/19	5,376,012 A	12/1994	Clark .... 439/80
4,669,801 A	6/1987	Worth .... 439/404	5,400,949 A	3/1995	Hirvonen et al. .... 228/180
4,685,886 A	8/1987	Denlinger et al. .... 439/55	5,403,206 A	4/1995	McNamara et al. .... 439/608
4,709,976 A	12/1987	Nakama et al. .... 439/350	5,427,543 A	6/1995	Dynia .... 439/346
4,717,360 A	1/1988	Czaja .... 439/710	5,431,578 A	7/1995	Wayne .... 439/259
4,767,344 A	8/1988	Noschese .... 439/83	5,435,876 A	7/1995	Alfaro et al. .... 156/247
4,776,803 A	10/1988	Pretchel et al. .... 439/59	5,457,342 A	10/1995	Herbst, II .... 257/712
4,780,088 A	10/1988	Means .... 439/107	5,458,426 A	10/1995	Ito
4,782,893 A	11/1988	Thomas	5,475,922 A	12/1995	Tamura et al. .... 29/881
4,790,763 A	12/1988	Weber et al.	5,481,442 A	1/1996	Dickie et al. .... 362/95
4,790,764 A	12/1988	Kawaguchi et al. .... 439/78	5,490,040 A	2/1996	Gaudenzi et al. .... 361/773
4,801,271 A	1/1989	Piper .... 439/148	5,511,987 A	4/1996	Shinchi
4,815,987 A	3/1989	Kawano et al. .... 439/263	5,512,519 A	4/1996	Hwang
4,818,237 A	4/1989	Weber	5,533,915 A	7/1996	Deans .... 439/678
4,820,169 A	4/1989	Weber et al.	5,549,480 A	8/1996	Cheng .... 439/79
4,820,175 A	4/1989	Hasegawa et al. .... 439/98	5,558,542 A	9/1996	O'Sullivan et al. .... 439/682
4,838,809 A	6/1989	Mouissie .... 439/155	5,564,952 A	10/1996	Davis et al.
4,845,592 A	7/1989	Himes, Jr. et al. .... 361/407	5,582,519 A	12/1996	Buchter
4,867,713 A	9/1989	Ozu et al. .... 439/833	5,588,852 A	12/1996	Puerner .... 439/135
4,875,865 A	10/1989	Demler, Jr. et al. .... 439/101	5,590,463 A	1/1997	Feldman et al. .... 29/844
4,878,611 A	11/1989	LoVasco et al. .... 228/180.2	5,605,489 A	2/1997	Gale et al. .... 451/28
4,881,905 A	11/1989	Demler, Jr. et al. .... 439/79	5,609,502 A	3/1997	Thumma .... 439/747
4,900,271 A	2/1990	Colleran et al. .... 439/595	5,618,187 A	4/1997	Goto .... 439/79
4,907,990 A	3/1990	Bertho et al. .... 439/851	5,622,511 A	4/1997	Jarrett .... 439/248
4,915,641 A	4/1990	Miskin et al.	5,637,008 A	6/1997	Kozel .... 439/342
4,917,625 A	4/1990	Haile .... 439/358	5,643,013 A	7/1997	Weidler et al. .... 439/660
4,941,830 A	7/1990	Tkazyik et al. .... 439/59	5,664,968 A	9/1997	Mickiewicz
4,950,186 A	8/1990	Kaley et al. .... 439/882	5,667,392 A	9/1997	Kocher et al.
4,954,090 A	9/1990	Shimochi .... 439/76	5,691,041 A	11/1997	Frankeny et al.
4,963,102 A	10/1990	Gettig et al. .... 439/291	5,702,255 A	12/1997	Murphy et al.
4,965,699 A	10/1990	Jorden et al.	5,716,234 A	2/1998	Phillips .... 439/595
4,968,263 A	11/1990	Silbernagel et al. .... 439/246	5,727,963 A	3/1998	LeMaster
4,973,271 A	11/1990	Ishizuka et al. .... 439/839	5,730,609 A	3/1998	Harwath .... 439/108
4,974,119 A	11/1990	Martin	5,741,144 A	4/1998	Elco et al. .... 439/101
4,975,084 A	12/1990	Fedder et al.	5,741,161 A	4/1998	Cahaly et al. .... 439/709
			5,742,484 A	4/1998	Gillette et al.

# US RE41,283 E

5,743,009 A	4/1998	Matsui et al.	6,220,895 B1	4/2001	Lin
5,745,349 A	4/1998	Lemke ..... 361/818	6,220,896 B1	4/2001	Bertoncini et al. .... 439/608
5,746,608 A	5/1998	Taylor ..... 439/70	6,238,225 B1	5/2001	Middlehurst et al.
5,749,746 A	5/1998	Tan et al.	6,257,478 B1	7/2001	Straub
5,755,595 A	5/1998	Davis et al. .... 439/607	6,259,039 B1	7/2001	Chroneos, Jr. et al.
5,772,452 A	6/1998	Aoyama ..... 439/79	6,261,132 B1	7/2001	Koseki et al.
5,782,644 A	7/1998	Kiat	6,269,539 B1	8/2001	Takahashi et al. .... 29/883
5,785,557 A	7/1998	Davis ..... 439/660	6,272,474 B1	8/2001	Garcia
5,787,971 A	8/1998	Dodson ..... 165/121	6,280,230 B1	8/2001	Takase et al.
5,795,191 A	8/1998	Preputnick et al. .... 439/608	6,293,827 B1	9/2001	Stokoe ..... 439/608
5,810,607 A	9/1998	Shih et al. .... 439/66	6,299,492 B1	10/2001	Pierini et al.
5,817,973 A	10/1998	Elco et al. .... 174/32	6,319,075 B1	11/2001	Clark et al. .... 439/825
5,827,094 A	10/1998	Aizawa et al.	6,322,377 B2	11/2001	Middlehurst et al.
5,831,314 A	11/1998	Wen ..... 257/391	6,328,602 B1	12/2001	Yamasaki et al. .... 439/608
5,865,651 A	2/1999	Dague et al. .... 439/680	6,335,224 B1	1/2002	Peterson et al. .... 438/114
5,872,046 A	2/1999	Kaeriyama et al. .... 438/465	6,347,952 B1	2/2002	Hasegawa et al.
5,874,776 A	2/1999	Kresge et al. .... 257/747	6,350,134 B1	2/2002	Fogg et al. .... 439/79
5,876,219 A	3/1999	Taylor et al.	6,358,094 B1	3/2002	Belopolsky et al. .... 439/637
5,876,248 A	3/1999	Brunker	6,359,783 B1	3/2002	Noble
5,879,198 A	3/1999	Sekimori et al. .... 439/700	6,360,940 B1	3/2002	Bolde et al. .... 228/264
5,882,214 A	3/1999	Hillbish et al.	6,362,961 B1	3/2002	Chiou ..... 361/704
5,883,782 A	3/1999	Thurston et al. .... 364/704	6,363,607 B1	4/2002	Chen et al. .... 29/883
5,888,884 A	3/1999	Wojnarowski ..... 438/462	6,371,773 B1	4/2002	Crofoot et al. .... 439/79
5,904,594 A	5/1999	Longueville et al. .... 439/608	6,379,188 B1	4/2002	Cohen et al. .... 439/608
5,908,333 A	6/1999	Perino et al. .... 439/631	6,386,924 B2	5/2002	Long ..... 439/701
5,919,050 A	7/1999	Kehley et al. .... 439/71	6,394,818 B1	5/2002	Smalley, Jr.
5,923,995 A	7/1999	Kao et al. .... 438/460	6,402,566 B1	6/2002	Middlehurst et al.
5,924,899 A	7/1999	Paagman ..... 439/701	6,409,543 B1	6/2002	Astbury, Jr. et al. .... 439/608
5,930,114 A	7/1999	Kuzmin et al. .... 361/704	6,431,914 B1	8/2002	Billman ..... 439/608
5,937,140 A	8/1999	Leonard et al. .... 392/392	6,435,914 B1	8/2002	Billman ..... 439/608
5,955,888 A	9/1999	Frederickson et al. .... 324/761	6,450,029 B1	9/2002	Sakai et al.
5,961,355 A	10/1999	Morlion et al. .... 439/686	6,461,183 B1	10/2002	Ohkita et al.
5,971,817 A	10/1999	Longueville ..... 439/857	6,461,202 B2	10/2002	Kline ..... 439/701
5,975,921 A	11/1999	Shuey ..... 439/83	6,471,523 B1	10/2002	Shuey ..... 439/63
5,980,321 A	11/1999	Cohen et al. .... 439/608	6,471,548 B2	10/2002	Bertoncini et al. .... 439/608
5,984,726 A	11/1999	Wu ..... 439/607	6,472,474 B2	10/2002	Burkhardt et al.
5,993,259 A	11/1999	Stokoe et al. .... 439/608	6,488,549 B1	12/2002	Weller et al.
6,012,948 A	1/2000	Wu ..... 439/567	6,489,567 B2	12/2002	Zachrai
6,027,360 A	2/2000	Jenkins ..... 439/364	6,506,081 B2	1/2003	Blanchfield et al. .... 439/682
6,036,549 A	3/2000	Wulff	6,511,329 B2	1/2003	Yi-Tsung ..... 439/76.1
6,041,498 A	3/2000	Hillbish et al.	6,514,103 B2	2/2003	Pape et al.
6,050,862 A	4/2000	Ishii ..... 439/843	6,537,111 B2	3/2003	Brammer et al. .... 439/857
6,059,170 A	5/2000	Jimarez et al. .... 228/119	6,551,112 B1	4/2003	Li et al. .... 439/66
6,062,911 A	5/2000	Davis et al. .... 439/630	6,554,046 B1	4/2003	Bryan et al. .... 156/584
6,063,696 A	5/2000	Brenner et al. .... 438/465	6,554,647 B1	4/2003	Cohen et al. .... 439/607
6,066,048 A	5/2000	Lees	6,572,410 B1	6/2003	Volstorf et al. .... 439/608
6,068,520 A	5/2000	Winings et al. .... 439/676	6,575,774 B2	6/2003	Ling et al.
6,071,152 A	6/2000	Achammer et al. .... 439/733.1	6,575,776 B1	6/2003	Conner et al.
6,089,878 A	7/2000	Meng ..... 439/79	6,592,381 B2	7/2003	Cohen et al. .... 439/80
6,095,827 A	8/2000	Dutkowsky et al. .... 439/83	6,604,967 B2	8/2003	Middlehurst et al.
6,123,554 A	9/2000	Ortega et al. .... 439/79	6,629,854 B2	10/2003	Murakami
6,125,535 A	10/2000	Chiou et al. .... 29/883	6,652,318 B1	11/2003	Winings et al. .... 439/608
6,139,336 A	10/2000	Olson ..... 439/83	6,663,426 B2	12/2003	Hasireoglu et al. .... 439/608
6,146,157 A	11/2000	Lenoir et al. .... 439/101	6,665,189 B1	12/2003	Lebo ..... 361/730
6,146,202 A	11/2000	Ramey et al. .... 439/608	6,669,514 B2	12/2003	Wiebking et al. .... 439/701
6,146,203 A	11/2000	Elco et al. .... 439/608	6,672,884 B1	1/2004	Toh et al.
6,152,756 A	11/2000	Huang et al. .... 439/342	6,672,907 B2	1/2004	Azuma ..... 439/682
6,174,198 B1	1/2001	Wu et al. .... 439/541.5	6,692,272 B2	2/2004	Lemke et al. .... 439/108
6,178,106 B1	1/2001	Umemoto et al. .... 363/146	6,702,594 B2	3/2004	Lee et al. .... 439/83
6,180,891 B1	1/2001	Murdeshwar ..... 174/260	6,705,902 B1	3/2004	Yi et al. .... 439/678
6,183,301 B1	2/2001	Paagman ..... 439/608	6,712,621 B2	3/2004	Li et al. .... 439/65
6,190,213 B1	2/2001	Reichart et al. .... 439/736	6,716,068 B2	4/2004	Wu ..... 439/733.1
6,190,215 B1	2/2001	Pendleton et al. .... 439/853	6,740,820 B2	5/2004	Cheng ..... 174/260
6,196,871 B1	3/2001	Szu ..... 439/571	6,743,037 B2	6/2004	Kassa et al. .... 439/342
6,202,916 B1	3/2001	Updike et al.	6,746,278 B2	6/2004	Nelson et al. .... 439/608
6,206,722 B1	3/2001	Ko et al.	6,769,935 B2	8/2004	Stokoe et al.
6,210,197 B1	4/2001	Yu	6,776,635 B2	8/2004	Blanchfield et al. .... 439/181
6,212,755 B1	4/2001	Shimada et al. .... 29/527.1	6,776,649 B2	8/2004	Pape et al. .... 439/485
6,215,180 B1	4/2001	Chen et al.	6,780,027 B2	8/2004	Allison
6,219,913 B1	4/2001	Uchiyama ..... 29/883	6,790,088 B2	9/2004	Ono et al. .... 439/607
6,220,884 B1	4/2001	Lin	6,796,831 B1	9/2004	Yasufuku et al. .... 439/485

6,810,783 B1 11/2004 Larose  
 6,811,440 B1 11/2004 Rothermel et al. .... 439/608  
 6,814,590 B2 11/2004 Minich et al.  
 6,829,143 B2 12/2004 Russell et al. .... 361/704  
 6,835,103 B2 12/2004 Middlehurst et al. .... 439/699.1  
 6,843,687 B2 1/2005 McGowan et al. .... 439/608  
 6,848,886 B2 2/2005 Schmaling et al. .... 416/134  
 6,848,950 B2 2/2005 Allison et al. .... 439/682  
 6,869,294 B2 3/2005 Clark et al.  
 6,884,117 B2 4/2005 Korsunsky et al. .... 439/607  
 6,890,221 B2 5/2005 Wagner ..... 439/855  
 6,905,367 B2 6/2005 Crane, Jr. et al. .... 439/608  
 6,947,012 B2 9/2005 Aisenbrey ..... 343/906  
 6,975,511 B1 12/2005 Lebo et al. .... 361/703  
 6,994,569 B2 2/2006 Minich et al. .... 439/79  
 7,001,189 B1 2/2006 McGowan et al. .... 439/79  
 7,059,892 B1 6/2006 Trout  
 7,059,919 B2 6/2006 Clark et al.  
 7,065,871 B2 6/2006 Minich et al.  
 7,070,464 B2 7/2006 Clark et al.  
 7,097,465 B1 8/2006 Korsunsky et al.  
 7,101,228 B2 9/2006 Hamner et al. .... 439/637  
 7,104,812 B1 9/2006 Bogiel et al. .... 439/79  
 7,114,963 B2 10/2006 Shuey et al. .... 439/79  
 RE39,380 E 11/2006 Davis  
 7,137,848 B1 11/2006 Trout et al.  
 7,168,963 B2 1/2007 Minich et al. .... 439/79  
 7,182,642 B2 2/2007 Ngo et al. .... 439/608  
 7,204,699 B2 4/2007 Stoner  
 D542,736 S 5/2007 Rico ..... D13/147  
 7,220,141 B2 5/2007 Daily et al.  
 7,258,562 B2 8/2007 Daily et al.  
 7,273,382 B2 9/2007 Igarashi et al.  
 7,303,427 B2 12/2007 Swain  
 7,335,043 B2 2/2008 Hgo et al.  
 7,384,289 B2 6/2008 Minich  
 7,425,145 B2 9/2008 Ngo  
 7,458,839 B2 12/2008 Ngo  
 7,476,108 B2 5/2009 Swain et al.  
 2001/0000498 A1 4/2001 Watanabe et al. .... 439/507  
 2001/0003685 A1 6/2001 Aritani ..... 439/485  
 2001/0049229 A1 12/2001 Pape et al.  
 2002/0106930 A1 8/2002 Pape et al. .... 439/485  
 2002/0142676 A1 10/2002 Hosaka et al. .... 439/874  
 2002/0159235 A1 10/2002 Miller et al. .... 361/704  
 2002/0193019 A1 12/2002 Blanchfield et al. .... 439/857  
 2003/0013330 A1 1/2003 Takeuchi ..... 439/83  
 2003/0119378 A1 6/2003 Avery  
 2003/0143894 A1 7/2003 Kline et al. .... 439/608  
 2003/0219999 A1 11/2003 Minich et al. .... 439/79  
 2003/0220021 A1 11/2003 Whiteman, Jr. et al. .... 439/608  
 2003/0236035 A1 12/2003 Kuroda et al. .... 439/857  
 2004/0147177 A1 7/2004 Wagner  
 2004/0183094 A1 9/2004 Caletka et al. .... 257/178

2005/0112952 A1 5/2005 Wang et al. .... 439/660  
 2006/0003620 A1 1/2006 Daily et al. .... 439/295  
 2006/0128197 A1 6/2006 McGowan et al.  
 2006/0228927 A1 10/2006 Daily  
 2006/0228948 A1 10/2006 Swain  
 2006/0281354 A1 12/2006 Ngo et al. .... 439/290  
 2007/0197063 A1 8/2007 Ngo  
 2007/0202748 A1 8/2007 Daily  
 2007/0275586 A1 11/2007 Hgo  
 2007/0293084 A1 12/2007 Ngo  
 2008/0038956 A1 2/2008 Swain  
 2008/0248670 A1 10/2008 Daily et al.

OTHER PUBLICATIONS

Power TwinBlade™ I/O Cable Connector RA–North–South, No. GS–20\_072, Aug. 6, 2007, 11 pages.  
 Product Datasheets, 10 Bgit/s XENPAK 850 nm Transponder (TRP10GVP2045), Copyright 2005, MergeOptics GmbH, 13 pages.  
 Product Datasheets, Welcome to XENPAK.org., Copyright 2001, <http://www.xenpak.org>, 1 page.  
 FCI, “PwrBlade® Power Distribution Connector System,” 2003, [www.fciconnect.com](http://www.fciconnect.com), 2 pages.  
 FCI, “PwrBlade® Power Distribution Connector System,” *Technology Innovation Service*, 2003, 2–3.  
 FCI, “PwrBlade™, new Power Distribution connector for electronic applications,” *Product News*, 2003, [www.fciconnect.com](http://www.fciconnect.com), 1 page.  
 FCI, “Act Connectors in action,” *Panorama*, 2003, 1 page.  
 In the United States Patent and Trademark Office, Notice of Allowance and Fee(s) Due in re: U.S. Appl. No. 10/352,584, filed Jan. 28, 2003, 4 pages.  
 In the United States Patent and Trademark Office, Office Action Final Rejection in re: U.S. Appl. No. 10/352,584, filed Jan. 28, 2003, 7 pages.  
 In the United States Patent and Trademark Office, Non Final Office Action in re: U.S. Appl. No. 10/352,584, filed Jan. 28, 2003, 14 pages.  
 Finan, J.M., “Thermally Conductive Thermoplastics”, LNP Engineering Plastics, Inc., *Plastics Engineering* 2000, [www.4spe.org](http://www.4spe.org), 4 pages.  
 Sherman, L.M., “Plastics that Conduct Heat”, *Plastics Technology Online*, Jun. 2001, <http://www.plasticstechnology.com>, 4 pages.  
 Ogando, J., “And now—An Injection–Molded Heat Exchanger”, Sure, plastics are thermal insulators, but additive packages allow them to conduct heat instead, *Global Design News*, Nov. 1, 2000, 4 pages.  
 U.S. Appl. No. 09/944,266, filed Aug. 31, 2001, Schell.




FIG. 1




FIG. 2




FIG. 3




FIG. 4

FIG. 5






FIG. 6




FIG. 7

## POWER CONNECTOR WITH SAFETY FEATURE

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.**

### CROSS-REFERENCE TO RELATED APPLICATION

This is a continuation of U.S. patent application Ser. No. 10/352,531 filed Jan. 28, 2003, now abandoned the contents of which is incorporated by reference herein in its entirety.

### FIELD OF THE INVENTION

The present invention relates to electrical power connectors that are useful in circuit board or backplane interconnection systems. Connectors of the present invention include a safety feature that restricts access to hot AC power contacts housed within the connectors.

### BACKGROUND OF THE INVENTION

There has been significant evolution in the area of electrical connectors, with improvements including multi-function consolidation within a single connector housing, and employment of features for effective heat dissipation generated from electrical power transmission. For example, Clark et al., in U.S. Pat. No. 6,319,075, discloses an electrical connector including both power and signal contacts within a single insulative housing, thereby eliminating the need for two separate connectors. Preferred power contacts disclosed in the '075 patent employ a "dual-mass" principle that provides a greater surface area available for heat dissipation, as compared to "single-mass" designed contacts, such as, for example, those having a circular or pin-like cross section.

Electrical connectors similar to those above may further comprise an AC power cable port and AC power contacts for direct connection with an external power supply. Examples of such connectors are commercially available from FCI Electronics, Inc. FCI's PWRBLADE brand connector series includes a receptacle connector that consists of AC power contacts, DC power contacts, signal contacts, and a shrouded AC cable port. Each of the power contacts includes two contact walls with a space therebetween to facilitate heat dissipation. Two patent applications owned by the assignee of the instant application and generally related to power distribution connectors, U.S. patent application Ser. No. 09/160,900 filed Sep. 25, 1998 and Ser. No. 09/944,266 filed Aug. 31, 2001, are currently pending in the U.S. Patent & Trademark Office, and are incorporated by reference herein.

Power distribution connectors that are engaged with an AC power cable plug when the mating face is unconnected to a complementary connector, may provide access of foreign objects to engaging portions of the hot AC power contacts. Accordingly, there is room for improvement in the art.

### SUMMARY OF THE PRESENT INVENTION

The present invention is related to electrical connectors having contacts for transmitting electrical power and electrical signals in a single connector. In accordance with a preferred embodiment of the present invention, there has now been provided an electrical connector comprising an insulative housing including a connector mating face, and an AC power contact disposed in the insulative housing. The connector mating face comprises an aperture to provide access

to an engaging portion of the AC power contact, and a guard for preventing direct human touching of the engaging portion.

In accordance with another preferred embodiment of the present invention, there has now been provided an electrical connector comprising an insulative housing, and an AC power contact disposed in the insulative housing. The power contact includes an engaging portion comprising two spaced apart contact walls. The insulative housing includes a mating face having an aperture therein to provide access to the AC power contact, and a guard proximate a perimeter of the aperture to define an electrical shock safety gap of at least about 5 mm between a human digit that is directed towards the aperture and the engaging portion of the AC power contact.

In accordance with yet another preferred embodiment of the present invention, there has now been provided an electrical connector comprising an insulative housing having a mating face, a plurality of AC power contacts, a plurality of DC power contacts, and a plurality of signal contacts. The mating face comprises a plurality of spaced apart apertures to provide access to a mating portion of a power or signal contact, and at least one outwardly directed projection extending along at least a portion of a perimeter defined by each of the apertures corresponding to the plurality of AC power contacts.

These and various other features of novelty, and their respective advantages, are pointed out with particularity in the claims annexed hereto and forming a part hereof. However, for a better understanding of aspects of the invention, reference should be made to the drawings which form a further part hereof, and to the accompanying descriptive matter, in which there is illustrated preferred embodiments.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an electrical connector embodiment provided by the present invention including anti-shock guard projections extending from its mating face.

FIG. 2 is a partial front view of the electrical connector embodiment shown in FIG. 1.

FIG. 3 is a perspective view of another electrical connector embodiment provided by the present invention including beam and hood projections extending from its mating face.

FIG. 4 is a partial perspective view of the electrical connector embodiment shown in FIG. 3, and including a simulated human digit directed towards an aperture providing access to an AC power contact.

FIG. 5 is a partial cutaway view of the electrical connector embodiment shown in FIG. 3, illustrating a safety gap between a simulated human digit and a power contact housed with the connector.

FIG. 6 is a perspective view of an AC power contact embodiment comprising two spaced apart contact walls and a tab extending from one of the contact walls.

FIG. 7 is a perspective view of a DC power contact embodiment comprising two spaced apart contact walls and a plurality of terminals extending from each of the contact walls.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention is believed to be best understood through the following detailed description of preferred embodiments and the accompanying drawings wherein like

reference numbers indicate like features. Referring to FIG. 1, an electrical receptacle connector 10 is shown including an insulative housing 12 having a mating face 20 for receiving a complimentary header connector (not shown). Mating face 20 contains a plurality of apertures that provide access to electrical contacts disposed in insulative housing 12. Apertures 30 provide access to engaging portions of signal contacts 100, apertures 31 provide access to engaging portions of DC power contacts 80 (shown in FIG. 7), and apertures 32 provide access to engaging portions of AC power contacts 70 (shown in FIG. 6). Although the number and arrangement of the various apertures is identical in all of the figures herein, connectors covered by the appended claims may have any number of contacts and corresponding apertures that are arranged in various configurations.

A shrouded AC cable port 40 extends from a top portion 21 of housing 12. An external power supply is provided by way of an AC power cable plug 41, which is shown partially inserted within AC cable port 40. Preferred connectors may alternatively be configured so that AC cable port 40 extends from a bottom portion or rear portion of housing 12. AC power cable plug 41 engages vertically-oriented AC power contacts 70 (shown in FIG. 6). An anti-shock guard 50 is employed to restrict direct operator access (that is, direct human touching without the aid of a tool) to the hot AC power contacts 70 during times when AC power cable plug 41 is engaged and receptacle connector 10 is disconnected from a complementary header connector.

Preferred exemplary embodiments of anti-shock guard 50 will be described with reference to FIGS. 2–5. Mating face 20 includes a perimeter area 35 associated with each of apertures 32 that provide access to AC power contacts 70. Perimeter area 35 is shown as a dotted line in FIG. 2; however, the perimeter area as included in the preferred embodiments and appended claims should not be construed as a fixed area limited to contact with or within a certain distance of apertures 32, but rather is the area generally surrounding apertures 32. Anti-shock guard 50 may comprise one or more projections extending outwardly along at least a portion of perimeter area 35. By way of example and as shown in FIGS. 2–4, two spaced apart beams 51 and 52 are disposed on one side of perimeter area 35 and two additional spaced apart beams 53 and 54 are disposed on the opposing side. A space exists between each pair of beams 51, 52 and 53, 54 to provide room for structural features employed on a complementary header connector. The space may for example, support and insulate electrical contacts extending from the header connector, or provide a latching feature. Alternative embodiments (not shown) contemplated and covered by the appended claims include, but are not limited to, a single projection disposed on opposing sides of perimeter area 35, and a single projection extending along a sufficient portion of perimeter area 35 to encompass opposing sides thereof. Connector 10 is shown having two apertures 32, with beams 53 and 54 serving as joint anti-shock guard projections on one side of the adjacent perimeter areas 35 of the two apertures. Individual, side-by-side beams could alternatively be employed that extend from the adjacent perimeter areas. Since beams 53 and 54 collectively restrict operator access to two adjacent apertures, they are preferably slightly larger than beams 51 and 52.

Now referring to FIG. 3, another projection in the form of a hood 56 preferably extends from a top position of perimeter area 35 and in between opposing beams 51 and 53. Hood 56 restricts operator access to apertures 32 from a position above connector 10. Hood 56 is shown as a single projection extending over two adjacent apertures 32;

however, hood 56 could alternatively comprise multiple individual projections associated with the individual apertures. As illustrated by comparing FIGS. 1 and 3, preferred connectors may include an anti-shock guard 50 having one type of projection discussed above (beam and hood) and not the other.

As can be seen in FIGS. 4 and 5, a simulated human digit 90 directed towards an aperture 32 is restricted from touching the hot AC power contact 70 accessible via aperture 32. A safety gap 91 of at least 5 mm is provided between simulated human digit 90 and an engaging portion of the AC power contact.

Housing 12, AC cable port 40, and anti-shock guard 50 are preferably molded or formed from a glass-filled high temperature nylon or other materials known to one having ordinary skill in the art. AC cable port 40 and anti-shock guard 50 may be integrally molded with housing 12, or alternatively, be manufactured separately and then coupled to housing 12.

Power circuits can undergo changes in electrical properties because of the relatively high current flows, for example, on the order of 30 amps or more in certain electronic equipment. Preferred power contacts are designed to dissipate heat generated from power transmission so that changes in circuit characteristics are minimized. A preferred AC power contact 70 is shown in FIG. 6, comprising an engaging portion 71 having two spaced apart contact walls 72 and 73 connected by a bridging element 74. Employing two contact walls increases the electrical integrity of the connector. Also, the two contact walls in conjunction with intermediate space 75 increases the ability and rate of heat dissipation. A tab 76 extends from contact wall 72 for engaging AC power cable plug 41. Although not shown, both contact walls 72 and 73 may include a tab for engaging an external power supply.

Referring now to FIG. 7, a preferred DC power contact 80 is shown, similar to the preferred AC power contact 70, comprising an engaging portion 81 having two spaced apart contact walls 82 and 83 connected by a bridging element 84. One or both, as shown in FIG. 7, of contact walls 82 and 83 have terminals 86 for connection with a circuit board (not shown).

Power contacts 70 and 80 are preferably loaded into housing 12 from the rear. The contact walls and/or bridging element of the AC and DC power contacts 70, 80 may contain notches or other female elements, and/or tangs or other male elements for retaining the power contacts in housing 12. Preferred power contacts 70 and 80 are stamped or otherwise formed as single piece from suitable materials such as phosphor bronze alloys or beryllium copper alloys. Signal contacts 100 (shown in FIG. 1 disposed in housing 12) are preferably “pin-type” contacts that include tail portions for connection with a circuit board, and are made from suitable materials, such as, for example, copper alloys. The power and signal contacts may be plated with gold, or a combination of gold and nickel.

It is to be understood that even though numerous characteristics and advantages of the present invention have been set forth in the foregoing description, together with details of the structure and function of the invention, the disclosure is illustrative only. Accordingly, changes may be made in detail, especially in matters of shape, size and arrangement of features within the principles of the invention to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed.

5

What is claimed is:

1. An electrical connector, comprising:  
 an insulative housing including a connector mating face;  
 a DC power contact disposed in said insulative housing,  
 said DC power contact comprising a pair of opposed  
 and spaced apart contact walls, and one or more terminals  
 extending from one of the contact walls for engaging  
 a circuit board;  
 an AC power contact disposed in said insulative housing;  
 and  
 a shrouded AC cable port extending from said insulative  
 housing at a location that is different from that of said  
 connector mating face;  
 wherein said connector mating face comprises:  
 an aperture therein to provide access to a engaging por-  
 tion of said AC power contact;  
 a perimeter area adjacent said aperture; and  
 a guard proximate said perimeter area for preventing  
 direct human touching of said engaging portion of  
 said AC power contact.
2. The electrical connector according to claim 1, wherein  
 said AC power contact comprises a pair of opposed and  
 spaced apart contact walls, and a tab extending from at least  
 one of the contact walls.
3. The electrical connector according to claim 1, further  
 comprising a plurality of signal contacts disposed in said  
 insulative housing.
4. The electrical connector according to claim 1, wherein  
 said guard comprises at least one projection extending out-  
 wardly from opposing sides of said perimeter area.

6

5. The electrical connector according to claim 4, wherein  
 said guard comprises two spaced apart projections extending  
 outwardly from each of the opposing sides of said perimeter  
 area.
6. The electrical connector according to claim [3] 5,  
 wherein said two spaced apart projections are dissimilar.
7. An electrical connector, comprising:  
 an insulative housing including a connector mating face  
 including first and second apertures formed therein;  
 a first type of power contact disposed in said insulative  
 housing and accessible through said first aperture;  
 a second type of power contact disposed in said insulative  
 housing, said second type of power contact being  
 accessible through said second aperture and having a  
 different configuration than that of said first type of  
 power contact; and  
 at least one projection extending outwardly from said con-  
 nector mating face and along at least a portion of a  
 perimeter of said first aperture to inhibit entry of a  
 human digit into said first aperture,  
 wherein said first type of power contact comprises a pair  
 of opposed and spaced apart walls, at least one of which  
 includes a tab for engaging an AC power cable plug;  
 and wherein said second type of power contact com-  
 prises a second pair of opposed and spaced apart walls  
 including a plurality of terminals extending therefrom  
 for engaging a printed circuit board.

\* \* \* \* \*