

US00RE41808E

(19) **United States**  
(12) **Reissued Patent**  
**Feder**

(10) **Patent Number:** **US RE41,808 E**  
(45) **Date of Reissued Patent:** **Oct. 5, 2010**

(54) **INTERNET SERVER APPARATUS, METHOD AND DEVICE FOR IMPLEMENTING EMERGENCY INFORMATION INSTRUCTIONS**  
(75) Inventor: **David L. Feder**, Los Angeles, CA (US)  
(73) Assignee: **Safetymate, Inc.**, Irvine, CA (US)  
(21) Appl. No.: **11/347,789**  
(22) Filed: **Feb. 3, 2006**

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **6,758,811**  
Issued: **Jul. 6, 2004**  
Appl. No.: **09/805,339**  
Filed: **Mar. 12, 2001**

U.S. Applications:

(60) Provisional application No. 60/188,641, filed on Mar. 10, 2000.

(51) **Int. Cl.**  
**A61B 5/00** (2006.01)

(52) **U.S. Cl.** ..... **600/300; 128/920; 705/3**

(58) **Field of Classification Search** ..... 358/1.15, 358/1.16, 1.17; 379/88.17; 434/265, 321, 434/322, 323; 128/920; 369/32.01, 41.01; 705/3; 600/300

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,845,250 A 10/1974 O'Brien  
4,303,395 A 12/1981 Bower  
4,569,026 A 2/1986 Best  
4,583,524 A 4/1986 Hutchins

4,588,383 A \* 5/1986 Parker et al. .... 434/265  
4,677,552 A 6/1987 Sibley, Jr.  
5,025,374 A 6/1991 Roizen et al.  
5,059,126 A 10/1991 Kimball  
5,086,391 A 2/1992 Chambers  
5,088,037 A 2/1992 Battaglia  
5,106,097 A 4/1992 Levine  
5,185,857 A 2/1993 Rozmanith et al.  
5,274,560 A 12/1993 LaRue  
5,521,812 A 5/1996 Feder et al.  
5,668,954 A \* 9/1997 Feder et al. .... 369/30.24  
6,304,788 B1 10/2001 Eady et al. .... 600/300  
6,319,207 B1 11/2001 Naidoo ..... 600/300  
6,375,038 B1 4/2002 Hock et al.  
6,398,729 B1 6/2002 Levinson ..... 600/300  
6,443,890 B1 9/2002 Schulze et al. .... 600/300  
6,544,198 B2 4/2003 Chong et al. .... 600/300  
6,602,181 B2 8/2003 Quy ..... 600/300  
6,721,415 B1 \* 4/2004 Gilbert ..... 379/221.09  
2003/0163784 A1 8/2003 Daniel et al.

\* cited by examiner


*Primary Examiner*—Houshang Safaipoor

(74) *Attorney, Agent, or Firm*—Orrick, Herrington & Sutcliffe LLP

(57) **ABSTRACT**

There is disclosed herein an Internet server apparatus, method and device for implementing emergency information instructions. The instructions comprise a program of a plurality of steps and can be in the form of a virtual implementation through use of a web page that includes representations of a virtual emergency information apparatus or, alternatively, in the form of a physical portable device. Indicators are provided in the form of lights or a numerical display to indicate the completion of sequential steps in the program so as to aid the user in knowing how many steps will be necessary and to indicate the completion of each step.

**11 Claims, 6 Drawing Sheets**






FIG. 1 PRIOR ART




Figure 2




Figure 3






FIG. 4




Figure 5




FIG. 6

\* This row of LED's will functionally represent the user's location in the audio sequence. I.E., during the 5th step of the instructions, LED's 1 through 5 will illuminate.



**INTERNET SERVER APPARATUS, METHOD  
AND DEVICE FOR IMPLEMENTING  
EMERGENCY INFORMATION  
INSTRUCTIONS**

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.**

This application claims the benefit of Provisional application Ser. No. 60/188,641, filed Mar. 10, 2000.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to the Internet and related devices and, more particularly, to an Internet web server that provides web documents, or a physical device, that relate to the interactive provision of instructional information particularly in medical and other emergency situations.

2. Description of Related Art

In any emergency operation, such as in the rescue of an unconscious victim, it is of paramount importance for the individuals involved to take the proper actions as soon as possible. Normally, if proper rescue operations are applied to a victim, the chance of survival or recovery of the victim are much improved. In order to carry out many rescue operations effectively, the rescuer must follow the steps set forth in any of the standard medical rescue manuals. The proper procedure is generally based upon the particular condition of the victim.

Standard rescue procedures are well developed in the medical field and are beyond the scope of this disclosure, except so far as may be necessary to explain the nature and applications of the present concepts. Studies have shown that even amongst professional rescue operators such as paramedic, firemen and nurses, relatively few people can remember the proper rescue sequence or procedure precisely. This is further complicated because the "standard" procedures frequently change as they are refined and new methodologies are introduced.

Even more importantly, a paramedic, fireman, nurse or other emergency medical technician is generally not available in the critical initial moments of an emergency. Rather, lay rescuers, i.e., ordinary individuals, generally discover emergencies, and these people are responsible for both initiating the proper procedures and determining whether additional assistance from professionals is necessary.

In general, the standard procedures have become more complex, and more procedures have been created for a growing number of emergencies. As procedures become more and more complex, potential rescuers have more and more difficulty in obtaining familiarity with them and memorizing them.

Moreover, the ability of a rescuer to recall and employ the proper emergency procedure is further hampered by the chaotic circumstances typically surrounding an emergency situation.

The prior art has seen varied approaches to the handling of emergency instructions or to the use of audible instructions. The prior art systems have included use of instruction booklets having indices in which the particular emergency has to be located; then pages flipped to locate the emergency; and read step by step while trying to perform the emergency with

one hand and constantly going back to reread the instructions. The prior art also has included sophisticated computer instructions that are activated by a particular code on a telephone to give a caller instructions as to how to fill out a bank deposit, how to call a particular bit of information regarding insurance policies or the like.

Attempts have been made to provide devices to assist in providing emergency information to ensure that a rescuer performs the rescue operation properly. However, most of these have been devices dedicated to just one type of emergency—cardiopulmonary resuscitation (CPR). One of such devices is shown in U.S. Pat. No. 4,451,158 to Selwyn et al. Selwyn's device is in the form of a timer with various coded pattern displays at predetermined time intervals to indicate various stages in the rescue operation. The main drawback of the device is that confusion may still arise for the rescuer to memorize which procedural step is related to which code.

Another device, such as that shown in U.S. Pat. No. 4,588,383 to Parker et al., provides voice instructions solely for the rescuer to carry out the CPR rescue operation. Other portable CPR-prompting devices have been disclosed in U.S. Pat. No. 4,588,383 to Parker et al., U.S. Pat. No. 4,583,524 to Hutchins and U.S. Pat. No. 5,088,037 to Battaglia.

An emergency audible instruction apparatus for a fire extinguisher is disclosed in U.S. Pat. No. 4,303,395 to Bower. Such a device provides audible instructions which instruct a user in handling a fire emergency. The device is activated automatically when the fire extinguisher is removed from its base. Bower suggests that a device embodiment storing multiple instructions may be included with a dial selector for selecting a particular emergency. However, unlike the CPR-prompting devices, the Bower device is not portable and suggests purely mechanical means for providing a portable solution.

A generalized manual key operated message generator is described in U.S. Pat. No. 3,845,250 to O'Brien. However, this device is not portable nor adapted for emergency use. To retrieve a message, the user presses a series of keys to assemble a complete message upon prerecorded parts.

U.S. Pat. No. 5,086,391 describes a medical alert system for domestic use comprising two major components, a device worn about the neck and a home computer. The device worn about the neck and the home computer reciprocally communicate with one another to provide the wearer of the device, as well as an attendant of the device, both instructions for care and a method to call for emergency help. The home computer contains an audio synthesizer and a voice amplification device to communicate verbally to the individual. The device may be used to summon an ambulance from a remote location if the injured person is unable to reach a telephone.

As can be seen, most of the known devices are bulky in size, not portable to be located conveniently beside the victim at the rescue site, provide very limited information and are complex to operate.

Other prior devices have been developed in the past and include the Emergency Information Apparatus and Methods of U.S. Pat. No. 5,521,812 and the Instructional CD Player for providing emergency information of U.S. Pat. No. 5,668,954, the disclosures of each of which are fully incorporated herein by this reference.

SUMMARY OF THE INVENTION

A principal object of the present invention is to provide an Internet web server and method for an interactive virtual



implementation and provision of instructional information in medical and other emergency situations. Another object is to provide a new form of a portable device which can be conveniently located beside a victim or near an emergency site to assist the rescuer to carry out the rescue operation. Either implementation provides step by step instructions sequentially in response to the condition of the victim.

A particularly important aspect of the present invention, whether implemented via an Internet web server, or a physical device, is the provision of a plurality of step indicators to assist the user in determining progress with respect to completion of the instructional program. Preferably, a separate indicator such as a light, is provided for each step in the program, and as steps are completed, the corresponding indicator light is either extinguished or illuminated in a manner to provide the user with an indication that the step has been completed. During a crisis, such as a medical emergency, the persons involved can be nervous, the situation can be chaotic, there can be uncertainty as to the steps to be taken. Therefore, it is important to have something to indicate the status of the beginning and ending of the procedure as well as each step of the procedure. Such step indicators provide this important feature. Alternatively, a display of numbers (e.g., 1 through 8) can be provided with the display stepping through the numbers as steps are completed.

These objects and features are provided in the emergency information concepts of the present invention.

#### BRIEF DESCRIPTION OF THE DRAWINGS

These and other advantages of the present invention are best understood with reference to the drawings in which:

FIG. 1 is a partial elevation of an emergency information apparatus of the prior art.

FIG. 2 is a block diagram of a network data distribution system,

FIG. 3 shows an Internet browser window,

FIG. 4 shows an exemplary web page that includes a virtual representation of an information apparatus,

FIG. 5 is a flow chart that describes a method of providing instructional programs over the Internet in connection with a virtual information apparatus, and

FIG. 6 is a block diagram of a hardware implementation device according to the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring first to FIG. 1, there is shown a partial elevation of an emergency information apparatus of the type disclosed in U.S. Pat. No. 5,521,812 and No. 5,668,954. The external portion of the apparatus is comprised primarily of a casing 100. The casing 100 is preferably of a rigid material, such as hard plastic, PVC, or the like. In addition, the casing and the items disposed in and within the casing 100 are, together, water resistant, such that water will not seep into the internal portion of the apparatus and induce electrical shorts or corrosion. This is beneficial so that the apparatus may be used, for example, in the rain, or during fire emergencies when water is being used to douse the fire. The bottom of the casing 100 (not shown) preferably includes shock absorbing pads, such as rubber pads embedded within the casing 100 and exposed at the outer edge of the casing 100 to reduce shock and vibration when the apparatus is set down.

On the left side of the apparatus there is a hinged compartment 180. The compartment 180 is in a closed and locked position, as shown. The compartment 180 may be opened

through a release (not shown), which may be on the side or top of the apparatus as known in the art. The compartment 180 is adapted for receiving a program medium such as a compact disc (CD) (not shown). When open, the compartment 180 may receive a CD, and when closed, the compartment 180 holds the CD within the apparatus.

While a CD is one form of the program medium, other media are generally suitable. These media preferably are of a standard form and storage format, such as Data Play CD, micro cassette, floppy disk, DAT, flash memory or ROMs on a PCMCIA card.

As shown in FIG. 1, there are provided five rows of three program selectors 110. The program selectors 110 are used for selecting and thereby starting the playback of programs stored therein. The number of program selectors 110 is not critical, although several should be provided so that several emergencies may be addressed. To further control playback, there are also provided several playback selectors 160, including a pause key 160H, a reverse key 160R, a forward key 160F and a continued play key 160P. The program selectors 110 and the playback selectors 160 are preferably push buttons. The program selectors 110 and playback selectors 160 preferably are backlit.

A nearly limitless number of programs may be used with the apparatus. To accommodate this flexibility, the program selectors 110 are preferably labeled with numbers 1–15, and these numbers correspond to stored programs. Programs may include instructions relating to AIDS/HIV, bloody nose, bumps and bruises, burns, choking, CPR, dental injuries, drowning, earthquakes, electric shock, external bleeding, eye injuries, fires, fractures and dislocations, frostbite and hypothermia, heart attack, heat emergencies, insect stings and bites, internal injuries, muscle cramps, poisoning, rescue breathing, seizures and shock, stroke, spinal injuries, sprains and strains, and emergency action principles.

With each start program, there can be provided a removable overlay 115. The overlay 115 is adapted to be placed over and around the program selectors 110. The overlay 115 labels the program selectors 110 in accordance with the stored programs. Thus, by scanning the overlay 115, the user can determine which program selector 110 to press to begin a playback of a desired program. The overlay 115 is preferably a thin piece of plastic, with the labels being resistant to erasure from typical use of the apparatus. The apparatus further includes a speaker 120 for playing back the audio portion of the programs stored.

Once a program selector 110 has been pressed and the selected program has begun to play, the number of the program as associated with the program selector 110 and the name of the program is displayed on a display 160. In FIG. 1, it is shown that the program number 5 related to “bleeding” has begun playback. The programs may be in multilingual audio. Preferably there is a language selector 185 in the casing.

#### Virtual Implementation of Information Apparatus

Turning now to FIG. 2, there is shown a network data distribution system in which a preferred embodiment of the invention is implemented. The data distribution system includes a local device 600, a data access network 620, and a web server 650. The local device 600, the data access network 620 and the monitoring server 630 comprise the network data distribution system.

The local device 600 preferably comprises a client computer which is configured to access the web server 650 via the local access network 120. The client computer may be,



## 5

for example, a PC running a Microsoft Windows operating system. The local device **600** preferably includes an output device, such as display **601**, and an input device, such as keyboard **602** and/or pointing device **603** (e.g., mouse, track ball, light pen, or data glove). The local device **600** also includes a docking station **611** that allows a data access device, such as a PDA to interface with the local device **600** and exchange data.

Furthermore, the local device **100** may be any device that provides some measure of individual user interactivity with a source of web pages. For example, the local device could be an Internet appliance, network computer (NC, or an appropriately Internet-enabled device such as a PDA, mobile phone, etc.

The data access network **620** provides lower layer network support for the local device **100** to interact with the web server **650**. The data access network **620** preferably comprises a common or private bi-directional telecommunications network (e.g., a public switched telephone network (PSTN), a cable-based telecommunication network, a LAN, a WAN, a wireless network), coupled with or overlaid by a TCP/IP network (e.g., the Internet or an intranet).

The web server **650** may be of the type known in the art and has the ability to serve web pages to the local device **600**, as requested in the manner known in the art. It should be appreciated that the web server **650** is generic for any source of web pages available to the local device **100**. Thus, for example, the web server **650** could be accessible from the Internet, or it could be a part of an intranet and represents any number of web servers.

A browser application, such as, Microsoft Internet Explorer or Netscape Navigator is preferably installed on the local device **600**. When the local device **100** is connected to the web server **650** through the data access network **620**, the user of the local device browses the web server **650** from the local device **600** using the browser application. The browser application itself need not be stored on the local device **600**.

Referring now to FIG. **3**, there is shown a browser window **700** generated by a browser application, here Microsoft Internet Explorer. The browser window **700** is familiar to those skilled in the art, so the particulars are not described further herein. Further information regarding the use of most browser applications and their technical specifications is abundantly available.

Several aspects of the browser window **700** are identified for further reference below. These aspects include a display pane **710**, an address bar **720** and a title bar **730**. The display pane **710** is a region of the browser window **700** wherein the browser application causes web pages received by the browser application to be displayed. The address bar **720** is another region of the browser window **700** and the browser application displays URLs in the address bay **720** corresponding to the web page currently displayed in the display pane **710**. The user can also enter a URL into the address bar **720**, and the browser application will attempt to load the web page or other object to which the entered URL points. The primary feature of the title bar **730** is that it displays the title of the browser application.

The web server **650** preferably includes a memory that includes one or more web pages that are associated with a virtual representation of the emergency information apparatus described above. The web server **650** downloads the web pages to the local device **600** so that a representation of the emergency information apparatus is displayed on the display device **601** within the browser display pane **710**.

FIG. **4** shows an embodiment of a web page that includes a representation of a virtual emergency information appara-

## 6

tus **800**. The virtual information apparatus **800** is preferably configured to simulate the operation of the physical apparatus described above with respect to FIG. **1**. According, the web page includes several hypertext program keys **810**, wherein each program key **810** is associated with a program that is stored in the web server **650**. By clicking on any of the program keys **810**, a user of the local device **600** causes the web server to load and initiate a program associated with the particular key **810**. In a preferred embodiment, each program is associated with a set of instructions relating to an emergency medical scenario, although the programs could vary.

The virtual information apparatus **800** also includes one or more operational keys **812** that allow a user using the local device **600** to perform functions relating to the program, such as start, stop, pause, etc. In addition, the apparatus **800** includes step indicator **814** that provide a representation of the status with respect to the number of completed steps in the program, and which are described in more detail later.

With reference to FIG. **4**, the virtual information apparatus also includes a representation of one or more acknowledgement keys **816** that allow a user of the local device **600** to acknowledge the completion of steps associated with a program.

FIG. **5** shows a flow chart that describes process in web pages associated with the virtual emergency information apparatus are downloaded to the local device **600**. The process begins when a user accesses the web server **650** using the local device **600** (step **910**). In step **920**, the web server **650** downloads one or more web pages to the local device **600**. The web pages preferably include one or more introductory pages that allow a user to select a particular instructional template for the virtual information apparatus **800** from a list of options (step **930**). For example, the user could select an instructional template associated with the provision of emergency services or provision of some category of emergency services. The templates could also be associated with other subject matter.

In any event, in step **940**, after the user selects the instructional template, the web server downloads a web page in which is displayed a representation of the information apparatus **800** configured in accordance with the selected instructional template. For example, FIG. **8** shows the web page associated with the information apparatus **800** being configured to implement emergency medical instructions. The program keys **810** each include a label that indicates the particular instructional set that will be implemented when the respective key **810** is selected.

In step **950**, the instruction program is initiated. The web server **650** preferably issues instructions that causes the local device **600** to play the particular program in the manner described above with respect to the physical emergency information apparatus. The user can pause, stop, play or interact with the program using the acknowledgement keys **812** and the operational keys **810**.

Each program preferably comprises plural audio instruction messages that relate to steps in a procedure. In one embodiment, the procedure relates to instructional steps for dealing with an emergency medical situation. However, the procedure could also relate to instructional steps for any other type of situations for which instructional steps are appropriate. The program further comprises playback control information for directing playback of the audio step message in a predefined pattern and in accordance with operation of the operational keys **810** and acknowledgement keys **812**.



In a preferred embodiment, the acknowledgement keys **812** are used interactively in response to the audio instructional steps. The user preferably selects an appropriate acknowledgement key **812** to acknowledge an audio instruction. Preferably, the program includes predetermined stop points where the program either pauses for a predetermined time or repeats an instruction until the user acknowledges completion of a step using one or more of the acknowledgement keys **812**. The apparatus is preferably configured to respond to voice acknowledgements. The apparatus could be equipped with voice activation software that recognizes and responds to the voice of a user.

For example, in an emergency medical instruction program, the audio instruction may instruct the user to check a person's breathing. The program could repeat the instruction or pause playing of the next instruction until the user acknowledges that this step has been completed. Once an acknowledgment has been received, the program would then continue.

The step indicators **814** preferably assist the user in determining progress with respect to completion of the instructional program. Preferably, a separate indicator, such as a light, is provided for each step in the program. Any given program (e.g., category of medical emergency, such as bleeding, burns, seizure, etc.). For example, a "bleeding" program may involve four steps, a "seizure" program eight steps, and the like. When one of the programs is selected, all of the lights can be illuminated, such as illuminated green, so that the operator can readily see that there are four, five, six or more steps as the case may be. As the steps are completed, the corresponding indicator light is either extinguished or illuminated, or illuminated in a different color, to provide the user an indication that the step has been completed. The indicator could also blink or flash during the pendency of a particular step. The step indicators **814** thus provide the user with a visual status and summary relating to the progress of the particular program that is being played.

In a preferred embodiment, the docking station **611** can be used to transfer one or more programs and virtual representations of the information apparatus to a PDA, such as a Palm Pilot. The PDA may then be used to implement the instructional program. For example, the user could dock the PDA to the docking station **611** and then download a virtual information apparatus into the memory of the PDA. Thereafter, the functionally provided in the web page representation of the virtual information apparatus would be available directly on the PDA, preferably via a touch screen on the PDA. Preferably, audio files in the form of voice instructions are downloaded to the PDA as part of the instructional program and virtual information apparatus. The PDA is also configured to accept voice instructions from the user from a microphone positioned on the PDA. Alternatively, the programs can be stored or embedded in the computer (e.g., in the hard drive) or PDA memory and be accessible via an emergency icon.

#### Physical Device

The virtual apparatus of the present invention as shown in FIG. 4 also can be implemented in a physical device of the nature earlier described in connection with FIG. 1, but further includes the step indicators **814** in the physical device operating in the same manner as described above and for the same purposes. Thus, the concepts of the present invention can be implemented in the form of a virtual device through a network data distribution system and the Internet, or via other communications systems, and can as well be implemented in a physical device like that shown in FIG. 4.

This device typically is battery powered and includes a speaker **820** (FIG. 4) for providing audible instructions and includes an internal system as shown in FIG. 6 with a microcontroller interconnected with the keypad **810** and the step indicators **812** to appropriately cause illumination or extinguishing of the lights (e.g., LED's). The programs preferably are stored in a flash memory, and the other components of the system shown in FIG. 6 provide the audio information.

As noted earlier, the steps can be indicated via a display of numbers which are stepped through as program steps are completed, for either or both of the virtual system or portable device.

While embodiments of the present invention have been shown and described, various modifications may be made without departing from the scope of the present invention, and all such modifications and equivalents are intended to be covered.

What is claimed is:

1. [Computer readable software code stored on a web document server, the web server being part of a client server network, the computer readable software code including a set of instructions for causing the web server to] *A computer-readable storage medium with an executable program stored thereon, wherein the program instructs a microprocessor to:*

download a web document to a client device, the web document including a virtual representation of an emergency information apparatus including one or more individually selectable program selectors for selecting a specific program to be played, wherein each program comprises plural audio instruction messages comprising steps in a procedure, and playback control information for directing playback of the audio step messages in a predefined pattern and in accordance with operation of the playback selectors, the playback control information including the location of each audio instruction message on the web server and the order of playback of the audio instructions within the program.

2. [Software code as claimed in] *The computer-readable storage medium of claim 1 wherein the virtual representation includes a series of step indicators to assist the user in determining progress with respect to completion of an instructional program.*

3. [A software code as in] *The computer-readable storage medium of claim 2 wherein the series of step indicators [are all illuminated at the commencement of the program and change as each step in the program is complete] comprise auditory indicators.*

4. [A software code as in] *The computer-readable storage medium of claim 2 wherein the step [instructions] indicators comprise numbers provided on a display.*

5. [A compact portable information apparatus comprising a plurality of program keys, each key being associated with an instructional program, such as an emergency medical scenario, and wherein depression of a key initiates a series of steps of the program, and

a plurality of step indicators to assist the program user in determining progress of completion of the instructional program and steps thereof, the step indicators comprising a plurality of illumination members which change in illumination as each step in the program is completed.]

6. [Apparatus as in claim 5 wherein the plurality of step indicators are all illuminated upon initiation of a program, and sequentially changed as respective steps of the program are completed.]

7. [Apparatus as in claim 5 wherein the apparatus further includes acknowledgement keys to allow the user to acknowledge completion of steps associated with a program.]







11

lights that are all illuminated upon initiation of a program, and sequentially changed as respective steps of the program are completed.]

[26. A virtual information method using a plurality of program keys, each key being associated with an instructional program, such as an emergency medical scenario, and wherein use of a key initiates a series of steps of the program, and

generating a plurality of step indicators to assist the program user in determining progress of completion of the instructional program and steps thereof, the step indicators comprising a display of a plurality of illumination members which change as each step in the program is completed, and wherein the steps indicators comprise a display of sequential members indicating each respective step.]

[27. An information method using a plurality of program keys, each key being associated with an instructional program, such as an emergency medical scenario, and wherein use of a key initiates a series of steps of the program,

generating a plurality of step indicators to assist the program user in determining progress of completion of the instructional program and steps thereof, the step indicators comprising a display of a plurality of illumination members which change as each step in the program is completed, and wherein the step indicators comprise lights that are all illuminated upon initiation of a program, and sequentially changed as respective steps of the program are completed.]

[28. An information method using a plurality of program keys, each key being associated with an instructional program, such as an emergency medical scenario, and wherein use of a key initiates a series of steps of the program,

generating a plurality of step indicators to assist the program user in determining progress of completion of the instructional program and steps thereof, the step indicators comprising a display of a plurality of illumination members which change as each step in the program is completed, and wherein the step indicators comprise a display of sequential members indicating each respective step.]

29. [Computer] *A general purpose computer configured to execute computer readable software code stored on [a web document server] the computer, the [web server] computer being part of a client server network, the computer readable software code including a set of instructions for causing the [web server] computer to*

download a web document to a client device, the web document including interactive instructional informa-

12

tion and including one or more individually selectable program selectors for selecting a specific program to be played, wherein each program comprises plural audio instruction messages comprising steps in a procedure, and playback control information for directing playback of the audio step messages in a predefined pattern and in accordance with operation of the playback selectors, the playback control information including the location of each audio instruction message on the [web server] computer and the order of playback of the audio instruction within the program.

30. [Software code as claimed in] *The computer of claim 29 wherein the virtual representation includes a series of step indicators to assist the user in determining progress with respect to completion of an instructional program.*

31. [A software code as in] *The computer of claim 30 wherein the step indicators are [all illuminated at the commencement of the program and change as each step in the program is complete] visual indicators.*

32. [Computer readable software code stored on a web document server, the web server being part of a client server network, the computer readable software code including a set of instructions for causing the web server to] *A computer-readable storage medium with an executable program stored thereon, wherein the program instructs a microprocessor to:*

download a web document to a client device, the web document including situations for which instructional steps are appropriate and including one or more individually selectable program selectors for selecting a specific program to be played, wherein each program comprises plural-audio instruction messages comprising steps in a procedure, and playback control information for directing playback of the audio step messages in a predefined pattern and in accordance with operation of the playback selectors, the playback control information including the location of each audio instruction message on the web server and the order of playback of the audio instructions within the program.

33. [Software code as claimed in] *The computer-readable storage medium of claim 32 wherein the virtual representation includes a series of step indicators to assist the user in determining progress with respect to completion of an instructional program.*

[34. A software code as in claim 33 wherein the step indicators are all illuminated at the commencement of the program and change as each step in the program is complete.]

35. *The computer-readable storage medium of claim 33 wherein the step indicators are auditory indicators.*

36. *The computer-readable storage medium of claim 33 wherein the step indicators comprise a display of sequential numbers indicating each respective step.*

\* \* \* \* \*