



US00RE41812E

(19) **United States**
(12) **Reissued Patent**
Taylor et al.

(10) **Patent Number:** **US RE41,812 E**
(45) **Date of Reissued Patent:** **Oct. 12, 2010**

(54) **ELECTRO-KINETIC AIR TRANSPORTER-CONDITIONER**

1,869,335 A 7/1932 Day
1,882,949 A 10/1932 Ruder
2,129,783 A 9/1938 Penney

(75) Inventors: **Charles E. Taylor**, Punta Gorda, FL (US); **Shek Fai Lau**, Foster City, CA (US)

(Continued)

(73) Assignee: **Sharper Image Acquisition LLC**, New York, NY (US)

CN 2111112 U 7/1972

(Continued)

(21) Appl. No.: **11/041,926**

OTHER PUBLICATIONS

(22) Filed: **Jan. 21, 2005**

European Search Report, mailed Feb. 6, 2006.

U.S. Appl. No. 60/104,573, filed Oct. 16, 1998, Krichtafovitch.

(Continued)

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,713,026**
Issued: **Mar. 30, 2004**
Appl. No.: **09/730,499**
Filed: **Dec. 5, 2000**

U.S. Applications:

(63) Continuation of application No. 09/186,471, filed on Nov. 5, 1998, now Pat. No. 6,176,977.

(51) **Int. Cl.**
B01J 19/08 (2006.01)
B03C 3/45 (2006.01)

(52) **U.S. Cl.** **96/89**; 96/95; 422/186.04; 422/186

(58) **Field of Classification Search** 422/186, 422/186.04; 204/286; 96/29, 39, 40, 83, 95, 96/98

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

653,421 A 7/1900 Lorey
895,729 A 8/1908 Carlborg
995,958 A 6/1911 Goldberg
1,791,338 A 2/1931 Wintermute


Primary Examiner—Thao T. Tran

(74) *Attorney, Agent, or Firm*—Arent Fox LLP

(57) **ABSTRACT**

An electro-kinetic electro-static air conditioner includes a self-contained ion generator that provides electro-kinetically moved air with ions and safe amounts of ozone. The ion generator includes a high voltage pulse generator whose output pulses are coupled between first and second electrode arrays. Preferably the first array comprises one or more wire electrodes spaced staggeringly apart from a second array comprising hollow “U”-shaped electrodes. Preferably a ratio between effective area of an electrode in the second array compared to effective area of an electrode in the first array exceeds about 15:1 and preferably is about 20:1. An electric field produced by the high voltage pulses between the arrays produces an electrostatic flow of ionized air containing safe amounts of ozone. A bias electrode, electrically coupled to the second array electrodes, affects net polarity of ions generated. The outflow of ionized air and ozone is thus conditioned.

23 Claims, 12 Drawing Sheets



US RE41,812 E

Page 2

U.S. PATENT DOCUMENTS					
2,327,588 A	8/1943	Bennett	4,363,072 A	12/1982	Coggins
2,359,057 A	9/1944	Skinner	4,366,525 A	12/1982	Baumgartner
2,509,548 A	5/1950	White	4,369,776 A	1/1983	Roberts
2,590,447 A	3/1952	Nord et al.	4,375,364 A	3/1983	Van Hoesen et al.
2,949,550 A	8/1960	Brown	4,380,900 A	4/1983	Linder et al.
3,018,394 A	1/1962	Brown	4,386,395 A	5/1983	Francis, Jr.
3,026,964 A	3/1962	Penney	4,391,614 A	7/1983	Rozmus
3,374,941 A	3/1968	Okress	4,394,239 A	7/1983	Kitzelmann et al.
3,518,462 A	6/1970	Brown	4,405,342 A	9/1983	Bergman
3,540,191 A	11/1970	Herman	4,406,671 A	9/1983	Rozmus
3,581,470 A	6/1971	Aitkenhead et al.	4,412,850 A	11/1983	Kurata et al.
3,638,058 A	1/1972	Fritzius	4,413,225 A	11/1983	Donig et al.
3,744,216 A	7/1973	Halloran	4,414,603 A	11/1983	Masuda
3,803,808 A	4/1974	Shibuya et al.	4,435,190 A	3/1984	Taillet et al.
3,806,763 A	4/1974	Masuda	4,440,552 A	4/1984	Uchiya et al.
3,892,927 A	7/1975	Lindenberg	4,443,234 A	4/1984	Carlsson
3,945,813 A	3/1976	Iinoya et al.	4,445,911 A	5/1984	Lind
3,958,960 A	5/1976	Bakke	4,477,263 A	10/1984	Shaver et al.
3,958,961 A	5/1976	Bakke	4,477,268 A	10/1984	Kalt
3,958,962 A	5/1976	Hayashi	4,481,017 A	11/1984	Furlong
3,981,695 A	9/1976	Fuchs	4,496,375 A	1/1985	Levantine
3,984,215 A	10/1976	Zucker	4,502,002 A	2/1985	Ando
3,988,131 A	10/1976	Kanazawa et al.	4,505,724 A	3/1985	Baab
4,007,024 A	2/1977	Sallee et al.	4,509,958 A	4/1985	Masuda et al.
4,052,177 A	10/1977	Kide	4,514,780 A	4/1985	Brussee et al.
4,056,372 A	11/1977	Hayashi	4,515,982 A	5/1985	Lechtken et al.
4,070,163 A	1/1978	Kolb et al.	4,516,991 A	5/1985	Kawashima
4,074,983 A	2/1978	Bakke	4,521,229 A	6/1985	Baker et al.
4,092,134 A	5/1978	Kikuchi	4,522,634 A	6/1985	Frank
4,097,252 A	6/1978	Kirchhoff et al.	4,534,776 A	8/1985	Mammel et al.
4,102,654 A	7/1978	Pellin	4,536,698 A	8/1985	Shevalenko et al.
4,104,042 A	8/1978	Brozenick	4,544,382 A	10/1985	Taillet et al.
4,110,086 A	8/1978	Schwab et al.	4,555,252 A	11/1985	Eckstein
4,119,415 A	10/1978	Hayashi et al.	4,569,684 A	2/1986	Ibbott
4,126,434 A	11/1978	Keiichi	4,582,961 A	4/1986	Frederiksen
4,138,233 A	2/1979	Masuda	4,587,475 A	5/1986	Finney, Jr. et al.
4,147,522 A	4/1979	Gonas et al.	4,588,423 A	5/1986	Gillingham et al.
4,155,792 A	5/1979	Gelhaar et al.	4,590,042 A	5/1986	Drage
4,171,975 A	10/1979	Kato et al.	4,597,780 A	7/1986	Reif
4,185,971 A	1/1980	Isahaya	4,597,781 A	7/1986	Spector
4,189,308 A	2/1980	Feldman	4,600,411 A	7/1986	Santamaria
4,205,969 A	6/1980	Matsumoto	4,601,733 A	7/1986	Ordines et al.
4,209,306 A	6/1980	Feldman et al.	4,604,174 A	8/1986	Bollinger et al.
4,218,225 A	8/1980	Kirchhoff et al.	4,614,573 A	9/1986	Masuda
4,225,323 A	9/1980	Zarchy et al.	4,623,365 A	11/1986	Bergman
4,227,894 A	10/1980	Proynoff	4,626,261 A	12/1986	Jorgensen
4,231,766 A	11/1980	Spurgin	4,632,135 A	12/1986	Lenting et al.
4,232,355 A	11/1980	Finger et al.	4,632,746 A	12/1986	Bergman
4,244,710 A	1/1981	Burger	4,636,981 A	1/1987	Ogura
4,244,712 A	1/1981	Tongret	4,643,744 A	2/1987	Brooks
4,251,234 A	2/1981	Chang	4,643,745 A	2/1987	Sakakibara et al.
4,253,852 A	3/1981	Adams	4,647,836 A	3/1987	Olsen
4,259,093 A	3/1981	Vlastos et al.	4,650,648 A	3/1987	Beer et al.
4,259,452 A	3/1981	Yukuta et al.	4,656,010 A	4/1987	Leitzke et al.
4,259,707 A	3/1981	Penney	4,657,738 A	4/1987	Kanter et al.
4,266,948 A	5/1981	Teague et al.	4,659,342 A	4/1987	Lind
4,282,014 A	8/1981	Winkler et al.	4,662,903 A	5/1987	Yanagawa
4,284,420 A	8/1981	Borysiak	4,666,474 A	5/1987	Cook
4,289,504 A	9/1981	Scholes	4,668,479 A	5/1987	Manabe et al.
4,293,319 A	10/1981	Claassen, Jr.	4,670,026 A	6/1987	Hoenig
4,308,036 A	12/1981	Zahedi et al.	4,674,003 A	6/1987	Zylka
4,315,188 A	2/1982	Cerny et al.	4,680,496 A	7/1987	Letournel et al.
4,318,718 A	3/1982	Utsumi et al.	4,686,370 A	8/1987	Blach
4,338,560 A	7/1982	Lemley	4,689,056 A	8/1987	Noguchi et al.
4,342,571 A	8/1982	Hayashi	4,691,829 A	9/1987	Auer
4,349,359 A	9/1982	Fitch et al.	4,692,174 A	9/1987	Gelfand et al.
4,351,648 A	9/1982	Penney	4,693,869 A	9/1987	Pfaff
4,354,861 A	10/1982	Kalt	4,694,376 A	9/1987	Gesslauer
4,357,150 A	11/1982	Masuda et al.	4,702,752 A	10/1987	Yanagawa
4,362,632 A	12/1982	Jacob	4,713,092 A	12/1987	Kikuchi et al.
			4,713,093 A	12/1987	Hansson

US RE41,812 E

Page 3

4,713,724 A	12/1987	Voelkel	5,180,404 A	1/1993	Loreth et al.
4,715,870 A	12/1987	Masuda et al.	5,183,480 A	2/1993	Raterman et al.
4,725,289 A	2/1988	Quintilian	5,196,171 A	3/1993	Peltier
4,726,812 A	2/1988	Hirth	5,198,003 A	3/1993	Haynes
4,726,814 A	2/1988	Weitman	5,199,257 A	4/1993	Colletta et al.
4,736,127 A	4/1988	Jacobsen	5,210,678 A	5/1993	Lain et al.
4,743,275 A	5/1988	Flanagan	5,215,558 A	6/1993	Moon
4,749,390 A	6/1988	Burnett et al.	5,217,504 A	6/1993	Johansson
4,750,921 A	6/1988	Sugita et al.	5,217,511 A	6/1993	Plaks et al.
4,760,302 A	7/1988	Jacobsen	5,234,555 A	8/1993	Ibbott
4,760,303 A	7/1988	Miyake	5,248,324 A	9/1993	Hara
4,765,802 A	8/1988	Gombos et al.	5,250,267 A	10/1993	Johnson et al.
4,771,361 A	9/1988	Varga	5,254,155 A	10/1993	Mensi
4,772,297 A	9/1988	Anzai	5,266,004 A	11/1993	Tsumurai et al.
4,779,182 A	10/1988	Mickal et al.	5,271,763 A	12/1993	Jang
4,781,736 A	11/1988	Cheney et al.	5,282,891 A	2/1994	Durham
4,786,844 A	11/1988	Farrell et al.	5,290,343 A	3/1994	Morita et al.
4,789,801 A	12/1988	Lee	5,296,019 A	3/1994	Oakley et al.
4,808,200 A	2/1989	Dallhammer et al.	5,302,190 A	4/1994	Williams
4,811,159 A	3/1989	Foster, Jr.	5,308,586 A	5/1994	Fritsche et al.
4,822,381 A	4/1989	Mosley et al.	5,315,838 A	5/1994	Thompson
4,853,005 A	8/1989	Jaisinghani et al.	5,316,741 A	5/1994	Sewell et al.
4,869,736 A	9/1989	Ivester et al.	5,330,559 A	7/1994	Cheney et al.
4,892,713 A	1/1990	Newman	5,348,571 A	9/1994	Weber
4,929,139 A	5/1990	Vorreiter et al.	5,376,168 A	12/1994	Inculet
4,940,470 A	7/1990	Jaisinghani et al.	5,378,978 A	1/1995	Gallo et al.
4,940,894 A	7/1990	Morters	5,386,839 A	2/1995	Chen
4,941,068 A	7/1990	Hofmann	5,395,430 A	3/1995	Lundgren et al.
4,941,224 A	7/1990	Saeki et al.	5,401,301 A	3/1995	Schulmerich et al.
4,944,778 A	7/1990	Yanagawa	5,401,302 A	3/1995	Schulmerich et al.
4,954,320 A	9/1990	Birmingham et al.	5,403,383 A	4/1995	Jaisinghani
4,955,991 A	9/1990	Torok et al.	5,405,434 A	4/1995	Inculet
4,966,666 A	10/1990	Waltonen	5,407,469 A	4/1995	Sun
4,967,119 A	10/1990	Torok et al.	5,407,639 A	4/1995	Watanabe et al.
4,976,752 A	12/1990	Torok et al.	5,417,936 A	5/1995	Suzuki et al.
4,978,372 A	12/1990	Pick	5,419,953 A	5/1995	Chapman
D315,598 S	3/1991	Yamamoto et al.	5,433,772 A	7/1995	Sikora
5,003,774 A	4/1991	Leonard	5,435,817 A	7/1995	Davis et al.
5,006,761 A	4/1991	Torok et al.	5,435,978 A	7/1995	Yokomi
5,010,869 A	4/1991	Lee	5,437,713 A	8/1995	Chang
5,012,093 A	4/1991	Shimizu	5,437,843 A	8/1995	Kuan
5,012,094 A	4/1991	Hamade	5,445,798 A	8/1995	Ikeda et al.
5,012,159 A	4/1991	Torok et al.	5,466,279 A	11/1995	Hattori et al.
5,022,979 A	6/1991	Hijikata et al.	5,468,454 A	11/1995	Kim
5,024,685 A	6/1991	Torok et al.	5,474,599 A	12/1995	Cheney et al.
5,030,254 A	7/1991	Heyen et al.	5,484,472 A	1/1996	Weinberg
5,034,033 A	7/1991	Alsup et al.	5,484,473 A	1/1996	Bontempi
5,037,456 A	8/1991	Yu	5,492,678 A	2/1996	Ota et al.
5,045,095 A	9/1991	You	5,501,844 A	3/1996	Kasting, Jr. et al.
5,053,912 A	10/1991	Loreth et al.	5,503,808 A	4/1996	Garbutt et al.
5,059,219 A	10/1991	Plaks et al.	5,503,809 A	4/1996	Coate et al.
5,061,462 A	10/1991	Suzuki	5,505,914 A	4/1996	Tona-Serra
5,066,313 A	11/1991	Mallory, Sr.	5,508,008 A	4/1996	Wasser
5,072,746 A	12/1991	Kantor	5,514,345 A	5/1996	Garbutt et al.
5,076,820 A	12/1991	Gurvitz	5,516,493 A	5/1996	Bell et al.
5,077,468 A	12/1991	Hamade	5,518,531 A	5/1996	Joannu
5,077,500 A	12/1991	Torok et al.	5,520,887 A	5/1996	Shimizu et al.
5,100,440 A	3/1992	Stahel et al.	5,525,310 A	6/1996	Decker et al.
RE33,927 E	5/1992	Fuzimura	5,529,613 A	6/1996	Yavnieli
D326,514 S	5/1992	Alsup et al.	5,529,760 A	6/1996	Burris
5,118,942 A	6/1992	Hamade	5,532,798 A	7/1996	Nakagami et al.
5,125,936 A	6/1992	Johansson	5,535,089 A	7/1996	Ford et al.
5,136,461 A	8/1992	Zellweger	5,536,477 A	7/1996	Cha et al.
5,137,546 A	8/1992	Steinbacher et al.	5,538,695 A	7/1996	Shinjo et al.
5,141,529 A	8/1992	Oakley et al.	5,540,761 A	7/1996	Yamamoto
5,141,715 A	8/1992	Sackinger et al.	5,542,967 A	8/1996	Ponizovsky et al.
D329,284 S	9/1992	Patton	5,545,379 A	8/1996	Gray
5,147,429 A	9/1992	Bartholomew et al.	5,545,380 A	8/1996	Gray
5,154,733 A	10/1992	Fujii et al.	5,547,643 A	8/1996	Nomoto et al.
5,158,580 A	10/1992	Chang	5,549,874 A	8/1996	Kamiya et al.
D332,655 S	1/1993	Lytte et al.	5,554,344 A	9/1996	Duarte

US RE41,812 E

Page 4

5,554,345	A	9/1996	Kitchenman	6,212,883	B1	4/2001	Kang
5,569,368	A	10/1996	Larsky et al.	6,228,149	B1	5/2001	Alenichev et al.
5,569,437	A	10/1996	Stiehl et al.	6,252,012	B1	6/2001	Egitto et al.
D375,546	S	11/1996	Lee	6,270,733	B1	8/2001	Rodden
5,571,483	A	11/1996	Pfingstl et al.	6,277,248	B1	8/2001	Ishioka et al.
5,573,577	A	11/1996	Joannou	6,282,106	B2	8/2001	Grass
5,573,730	A	11/1996	Gillum	D449,097	S	10/2001	Smith et al.
5,578,112	A	11/1996	Krause	D449,679	S	10/2001	Smith et al.
5,578,280	A	11/1996	Kazi et al.	6,296,692	B1	10/2001	Gutmann
5,582,632	A	12/1996	Nohr et al.	6,302,944	B1	10/2001	Hoenig
5,587,131	A	12/1996	Malkin et al.	6,309,514	B1	10/2001	Conrad et al.
D377,523	S	1/1997	Marvin et al.	6,312,507	B1	11/2001	Taylor et al.
5,591,253	A	1/1997	Altman et al.	6,315,821	B1	11/2001	Pillion et al.
5,591,334	A	1/1997	Shimizu et al.	6,328,791	B1	12/2001	Pillion et al.
5,591,412	A	1/1997	Jones et al.	6,348,103	B1	2/2002	Ahlborn et al.
5,593,476	A	1/1997	Coppom	6,350,417	B1	2/2002	Lau et al.
5,601,636	A	2/1997	Glucksman	6,362,604	B1	3/2002	Cravey
5,603,752	A	2/1997	Hara	6,372,097	B1	4/2002	Chen
5,603,893	A	2/1997	Gundersen et al.	6,373,723	B1	4/2002	Wallgren et al.
5,614,002	A	3/1997	Chen	6,379,427	B1	4/2002	Siess
5,624,476	A	4/1997	Eyraud	6,391,259	B1	5/2002	Malkin et al.
5,630,866	A	5/1997	Gregg	6,398,852	B1	6/2002	Loreth
5,630,990	A	5/1997	Conrad et al.	6,447,587	B1	9/2002	Pillion et al.
5,637,198	A	6/1997	Breault	6,451,266	B1	9/2002	Lau et al.
5,637,279	A	6/1997	Besen et al.	6,464,754	B1	10/2002	Ford
5,641,342	A	6/1997	Smith et al.	6,471,753	B1	10/2002	Ahn et al.
5,641,461	A	6/1997	Ferone	6,494,940	B1	12/2002	Hak
5,647,890	A	7/1997	Yamamoto	6,504,308	B1	1/2003	Krichtafovitch et al.
5,648,049	A	7/1997	Jones et al.	6,508,982	B1	1/2003	Shoji
5,655,210	A	8/1997	Gregoire et al.	6,544,485	B1	4/2003	Taylor
5,656,063	A	8/1997	Hsu	6,585,935	B1	7/2003	Taylor et al.
5,665,147	A	9/1997	Taylor et al.	6,588,434	B2	7/2003	Taylor et al.
5,667,563	A	9/1997	Silva, Jr.	6,603,268	B2	8/2003	Lee
5,667,564	A	9/1997	Weinberg	6,613,277	B1	9/2003	Monagan
5,667,565	A	9/1997	Gondar	6,632,407	B1	10/2003	Lau et al.
5,667,756	A	9/1997	Ho	6,635,105	B2	10/2003	Ahlborn et al.
5,669,963	A	9/1997	Horton et al.	6,672,315	B2	1/2004	Taylor et al.
5,678,237	A	10/1997	Powell et al.	6,709,484	B2	3/2004	Lau et al.
5,681,434	A	10/1997	Eastlund	6,713,026	B2	3/2004	Taylor et al.
5,681,533	A	10/1997	Hiromi	6,735,830	B1	5/2004	Merciel
5,698,164	A	12/1997	Kishioka et al.	6,749,667	B2	6/2004	Reeves et al.
5,702,507	A	12/1997	Wang	6,753,652	B2	6/2004	Kim
D389,567	S	1/1998	Gudefin	6,761,796	B2	7/2004	Srivastava et al.
5,766,318	A	6/1998	Loreth et al.	6,768,108	B2	7/2004	Hirano et al.
5,779,769	A	7/1998	Jiang	6,768,110	B2	7/2004	Alani
5,814,135	A	9/1998	Weinberg	6,768,120	B2	7/2004	Leung et al.
5,879,435	A	3/1999	Satyapal et al.	6,768,121	B2	7/2004	Horskey
5,893,977	A	4/1999	Pucci	6,770,878	B2	8/2004	Uhlemann et al.
5,911,957	A	6/1999	Khatchatrian et al.	6,774,359	B1	8/2004	Hirabayashi et al.
5,972,076	A	10/1999	Nichols et al.	6,777,686	B2	8/2004	Olson et al.
5,975,090	A	11/1999	Taylor et al.	6,777,699	B1	8/2004	Miley et al.
5,980,614	A	11/1999	Loreth et al.	6,777,882	B2	8/2004	Goldberg et al.
5,993,521	A	11/1999	Loreth et al.	6,781,136	B1	8/2004	Kato
5,997,619	A	12/1999	Knuth et al.	6,785,912	B1	9/2004	Julio
6,019,815	A	2/2000	Satyapal et al.	6,791,814	B2	9/2004	Adachi et al.
6,042,637	A	3/2000	Weinberg	6,794,661	B2	9/2004	Tsukihara et al.
6,063,168	A	5/2000	Nichols et al.	6,797,339	B2	9/2004	Akizuki et al.
6,086,657	A	7/2000	Freije	6,797,964	B2	9/2004	Yamashita
6,117,216	A	9/2000	Loreth	6,799,068	B1	9/2004	Hartmann et al.
6,118,645	A	9/2000	Partridge	6,800,862	B2	10/2004	Matsumoto et al.
6,126,722	A	10/2000	Mitchell et al.	6,803,585	B2	10/2004	Glukhoy
6,126,727	A	10/2000	Lo	6,805,916	B2	10/2004	Cadieu
6,149,717	A	11/2000	Satyapal et al.	6,806,035	B1	10/2004	Atireklapvarodom et al.
6,149,815	A	11/2000	Sauter	6,806,163	B2	10/2004	Wu et al.
6,152,146	A	11/2000	Taylor et al.	6,806,468	B2	10/2004	Laiko et al.
6,163,098	A	12/2000	Taylor et al.	6,808,606	B2	10/2004	Thomsen et al.
6,176,977	B1	1/2001	Taylor et al.	6,809,310	B2	10/2004	Chen
6,182,461	B1	2/2001	Washburn et al.	6,809,312	B1	10/2004	Park et al.
6,182,671	B1	2/2001	Taylor et al.	6,809,325	B2	10/2004	Dahl et al.
6,193,852	B1	2/2001	Caracciolo et al.	6,812,647	B2	11/2004	Cornelius
6,203,600	B1	3/2001	Loreth	6,815,690	B2	11/2004	Veerasamy et al.

6,818,257	B2	11/2004	Amann et al.
6,818,909	B2	11/2004	Murrell et al.
6,819,053	B2	11/2004	Johnson
2001/0048906	A1	12/2001	Lau et al.
2002/0069760	A1	6/2002	Pruette et al.
2002/0079212	A1	6/2002	Taylor et al.
2002/0098131	A1	7/2002	Taylor et al.
2002/0122751	A1	9/2002	Sinaiko et al.
2002/0122752	A1	9/2002	Taylor et al.
2002/0127156	A1	9/2002	Taylor
2002/0134664	A1	9/2002	Taylor et al.
2002/0134665	A1	9/2002	Taylor et al.
2002/0141914	A1	10/2002	Lau et al.
2002/0144601	A1	10/2002	Palestro et al.
2002/0146356	A1	10/2002	Sinai ko et al.
2002/0150520	A1	10/2002	Taylor et al.
2002/0152890	A1	10/2002	Leiser
2002/0155041	A1	10/2002	McKinney, Jr. et al.
2002/0170435	A1	11/2002	Joannou
2002/0190658	A1	12/2002	Lee
2002/0195951	A1	12/2002	Lee
2003/0005824	A1	1/2003	Katou et al.
2003/0206837	A1	11/2003	Taylor et al.
2003/0206839	A1	11/2003	Taylor et al.
2003/0206840	A1	11/2003	Taylor et al.
2004/0033176	A1	2/2004	Lee et al.
2004/0052700	A1	3/2004	Kotlyar et al.
2004/0065202	A1	4/2004	Gatchell et al.
2004/0136863	A1	7/2004	Yates et al.
2004/0166037	A1	8/2004	Youdell et al.
2004/0226447	A1	11/2004	Lau et al.
2004/0234431	A1	11/2004	Taylor et al.
2004/0237787	A1	12/2004	Reeves et al.
2004/0251124	A1	12/2004	Lau
2004/0251909	A1	12/2004	Taylor et al.
2005/0000793	A1	1/2005	Taylor et al.

FOREIGN PATENT DOCUMENTS

CN	87210843	U	7/1988
CN	2138764	Y	6/1993
CN	2153231	Y	12/1993
DE	2206057		8/1973
DE	197 41 621	C1	6/1999
EP	0433152	A1	12/1990
EP	0332624	B1	1/1992
FR	2690509		10/1993
GB	643363		9/1950
JP	S51-90077		8/1976
JP	S62-20653		2/1987
JP	S63-164948		10/1988
JP	10137007		5/1998
JP	11104223		4/1999
JP	2000236914		9/2000
WO	WO92/05875	A1	4/1992
WO	WO96/04703	A1	2/1996
WO	WO99/07474	A1	2/1999
WO	WO00/10713	A1	3/2000
WO	WO01/47803	A1	7/2001
WO	WO01/48781	A1	7/2001
WO	WO01/64349	A1	9/2001
WO	WO01/85348	A2	11/2001
WO	WO02/20162	A2	3/2002
WO	WO02/20163	A2	3/2002
WO	WO02/30574	A1	4/2002
WO	WO02/32578	A1	4/2002
WO	WO02/42003	A1	5/2002
WO	WO02/066167	A1	8/2002
WO	WO03/009944	A1	2/2003
WO	WO03/013620	A1	2/2003
WO	WO03/013734	AA	2/2003

OTHER PUBLICATIONS

“Zenion Elf Device,” drawing, prior art.

Electrical schematic and promotional material available from Zenion Industries, 7 pages, Aug. 1990.

Promotional material available from Zenion Industries for the Plasma–Pure 100/200/300, 2 pages, Aug. 1990.

Promotional material available from Zenion Industries for the Plasma–Tron, 2 pages, Aug. 1990.

LENTEK Sila™ Plug–In Air Purifier/Deodorizer product box copyrighted 1999, 13 pages.

Trion Console 250 Electronic Air Cleaner, Model Series 442857 and 445600, Manual for Installation Operation Maintenance, Trion Inc., 7 pp., believed to be at least one year prior to Nov. 5, 1998.

Trion 350 Air Purifier, Model 450111–010, <http://www.feddersoutlet.com/trion350.html>, 12 pp., believed to be at least one year prior to Nov. 5, 1998.

LENTEY Sila™ Plug–In Air Purifier/Deodorizer product box copyrighted 1999.

Trion 150 Air Purifier, Model 45000–002, <http://www.feddersoutlet.com/trion150.html>, 11 pp., believed to be at least one year prior to Nov. 5, 1998.

Trion 120 Air Purifier, Model 442501–025, <http://www.feddersoutlet.com/trion120.html>, 16 pp., believed to be at least one year prior to Nov. 5, 1998.

Friedrich C–90A Electronic Air Cleaner, Service Information, Friedrich Air Conditioning Co., 12 pp., 1985.

LakeAir Excel and Maxum Portable Electronic Air Cleaners, Operating and Service Manual, LakeAir International, Inc., 11 pp., 1971.

Blueair AV 402 Air Purifier, http://www.air-purifiers-usa.biz/Blueair_AV402.htm, 4 pp., 1996.

Blueair AV 501 Air Purifier, http://www.air-purifiers-usa.biz/Blueair_AV501.htm, 15 pp., 1997.

ConsumerReports.org, “Air Cleaners: Behind the Hype,” http://www.consumerreports.org/main/content/printable.jsp?FOLDER%3C%3EFOLDER_id, Oct. 2003, 6 pp.

“Household Air Cleaners,” Consumer Reports Magazine, Oct. 1992, 6 pp.

Court Docket for *Sharper Image Corporation v. Honeywell International Inc. and Kaz, Inc.*, Case No. 02–4860 CW (Consolidated), United States District Court, Northern District of California, Oakland Division.

Defendant Honeywell International Inc.’s Answer and Counterclaim to Plaintiff’s Consolidated Amended Complaint, Dated: May 5, 2003.

Defendant Kaz, Inc.’s Answer and Counterclaim to Plaintiff’s Consolidated Amended Complaint, Dated: May 5, 2003.

Defendants’ Second Preliminary Invalidity Contentions Relating to U.S. Patents Nos. 6,713,026 and 6,709,484 and Attached Exhibits A and B, Dated: Jun. 1, 2004.

Exhibit A: Charts of Preliminary Invalidity Contentions for U.S. Patent No. 6,713,026.

Exhibit B: Charts of Preliminary Invalidity Contentions for U.S. Patent No. 6,709,484.

Defendants Honeywell and Kaz, Inc.'s Preliminary Invalidity Contentions Relating to U.S. Patent No. 4,789,801, U.S. Patent No. 6,176,977, and U.S. Patent No. 6,350,417 and Attached Exhibits A, B, and C, Dated: Apr. 28, 2003. The analysis and all references from this Document have been incorporated by reference to Defendants' Second Preliminary Invalidity Contentions Relating to U.S. Patent Nos. 6,713,026 and 6,709,484 (Document 521) Exhibit A: List of Cited Prior Art of Record for Asserted U.S. Patent Nos. 6,176,977; 4,789,801; 6,350,417 Exhibit B: Supplemental List of the Following U.S. Patent Cited as Prior Art by Defendants: Exhibit C: Charts Preliminary Invalidity Contentions for U.S. Patent Nos. 6,176,977; 4,789,801; 6,350,417.

Exhibit C: Charts Preliminary Invalidity Contentions for U.S. Patent Nos. 6,176,977; 4,789,801; 6,350,417.

Exhibit A: List of Cited Prior Art of Record for Asserted U.S. Patent Nos. 6,176,977; 4,789,801; 6,350,417.

Exhibit B: Supplemental List of the Following U.S. Patent Cited as Prior Art by Defendants.

Exhibit C: Charts Preliminary Invalidity Contentions for U.S. Patent Nos. 6,176,977; 4,789,801; 6,350,417.

Defendants Honeywell and Kaz, Inc.'s Final Invalidity Contentions and Attached Exhibits A, B, and C, Dated: Mar. 24, 2004.

Exhibit A: Defendants' Charts of Final Invalidity Contentions Relating to Claim 24 of U.S. Patent No. 4,789,801.

Exhibit B: Defendants' Charts of Final Invalidity Contentions Relating to the Claims of U.S. Patent No. 6,176,977.

Exhibit C: Defendants' Charts of Final Invalidity Contentions Relating to Claim 16 of U.S. Patent No. 6,350,417.

Kaz's Responsive Claim Construction Brief, Dated: Sep. 30, 2004.

Court Docket for *Sharper Image Corporation v. Target Corporation, Ionic Pro, LLC, Sylmark, Inc., Sylmark LLC, Qwik Cook, Inc., Home Trends, Factories2U, LLC, and Chaim Mark Bess*, Case No. 04-0824 CW, United States District Court, Northern District of California, Oakland Division.

Defendants Target Corporation's, Ionic Pro, LLC's, Qwik Cook, Inc.'s, and Factories2U, LLC's Answer and Counterclaim to Plaintiff Sharper Image Corporation's Second Amended Complaint, Dated: May 27, 2004.

Defendants Ideal Products, LLC's, Sylmark, Inc.'s, Sylmark LLC's, and Chaim Mark Bess's Answer to Second Amended Complaint, Dated: May 24, 2004.

Defendants' L.R. 3-3 Preliminary Invalidity Contentions and Attached Exhibits A, B, and C, Dated: Jun. 1, 2004. Exhibit A: Charts of Preliminary Invalidity Contentions for U.S. Patent No. 6,709,484. Exhibit B: Charts of Preliminary Invalidity Contentions for U.S. Patent No. 6,713,026.

Defendants' Supplemental Patent L.R. 3-3 Preliminary Invalidity Contentions, Dated: Jun. 25, 2004.

Defendants' Opposition to Plaintiff Sharper Image Corporation's Motion for a Preliminary Injunction, Dated: Jul. 23, 2004.

Declaration of Peter Spiegel in Support of Defendants' Opposition to Plaintiff Sharper Image Corp.'s Motion for a Preliminary Injunction (Document 530) and Attached Exhibits A-H, Dated Jul. 21, 2004.

Exhibit A: Ed Leiber, "Air Purifiers: Growth of Iconic Cleaners Refuels Overall High-End Segment," *Homeworld Business Magazine*, *Home Health Care Report*, 2004, 1 page.

Exhibit B: ConsumerReports.org, "Air Cleaners: Behind the Hype," http://www.consumerreports.org/main/content/printable.jsp?FOLDER%3C%EFOLDER_id, Oct. 2003, 6 pp.

Exhibit C: "Household Air Cleaners," *Consumer Reports Magazine*, Oct. 1992, 6 pp.

Exhibit D: Friedrich C-90A, "How the C-90A Works," *BestAirCleaner.com*, <http://www.bestaircleaner.com/faq/c90works.asp>, 1 page.

Exhibit E: Service Information for the Friedrich C-90A Electronic Air Cleaner, 2003. 12 pp.

Exhibit F: Information on the Ionic Breeze Quadra Silent Air Purifier, *Sharperimage.com* <http://www.sharperimage.com/us/en/catalog/productview/sku=SI637SNX/hppos=1>, 2 pp.

Exhibit G: Richard Thalheimer, "The 7 Reasons Why IBQ is the Best Air Cleaner for Your Home," <http://www.sharperimage.com/us/en/templates/products/pipmorework1printable.jhtml>, 3 pp.

Exhibit H: Ionic Pro Ionic Air Purifier Owner's Guide, No date. 19 pp.

Exhibit G: Richard Thalheimer, "The 7 Reasons Why IBQ is the Best Air Cleaner for Your Home," <http://www.sharperimage.com/us/en/templates/products/pipmorework1printable.jhtml>, 3 pp.

Exhibit H: Ionic Pro Air Purifier Owner's Guide, No date. 19 pp.

Declaration of Jonathan Kagan in Support of Defendants' Opposition to Plaintiff Sharper Image Corp.'s Motion for a Preliminary Injunction (Document 530) and Attached Exhibits A-B, Dated: Jul. 23, 2004.

Exhibit A: U.S. Patent No. D 389,567; Inventor: Gudefin; Issued: Jan. 10, 1998; filed Nov. 14, 1996.

Exhibit B: U.S. Patent No. 6,296,692 B1; Inventor: Gutmann; Issued: Oct. 2, 2001; filed May 8, 1996.

Miscellaneous Administrative Request to File Sur-Reply in Opposition to Plaintiff's Motion for Preliminary Injunction, Dated: Aug. 4, 2004.

Defendants' Opening Claim Construction Brief, Dated: Sep. 30, 2004.

Declaration of Jonathan Kagan in Support of Defendants' Opening Claim Construction Brief (Document 534) and Attached Exhibits G-N, Dated: Sep. 30, 2004.

Exhibit G: Plaintiff Sharper Image Corporation's Preliminary Claim Constructions and Extrinsic Evidence Pursuant to Patent Local Rule 4-2, Dated: Jul. 6, 2004, 6 pp.

Exhibit H: Excerpts from Webster's Third New International Dictionary of the English Language, p. 1097.

Exhibit I: Excerpts from Webster's Third New International Dictionary of the English Language, p. 737.

Exhibit J: Excerpts from Webster's Third New International Dictionary of the English Language, p. 2546.

Exhibit K: Excerpts from Webster's Third New International Dictionary of the English Language, p. 132. Exhibit L:

Excerpts from Webster's Third New International Dictionary of the English Language, p. 99 and 1079. Exhibit M:

Office Action for Plaintiff's '026 Patent, Feb. 27, 2003. 11 pp. Exhibit N: Amendment and Response to Office Action for Plaintiff's '026 Patent, Jun. 18, 2003. 19 pp.

Exhibit L: Excerpts from Webster's Third New International Dictionary of the English Language, p. 99 and 1079.

Exhibit M: Office Action for Plaintiff's '026 Patent, Feb. 27, 2003, 11 pp.

Exhibit N: Amendment N: Amendment and Response to Office Action for Plaintiff's '026 Patent, Jun. 18, 2003. 19 pp.

Miscellaneous Administrative Request to File Sur-Reply Re: Claim Construction, Dated: Oct. 12, 2004.

Defendants' Second Amended L.R. 3-3 Preliminary Invalidity Contentions, Dated: Nov. 29, 2004, and Attached Exhibits A, B, and C:

Exhibit A: Charts of Invalidity Contentions for U.S. Patent No. 6,709,484.

Exhibit B: Charts of Invalidity Contentions for U.S. Patent No. 6,713,026.

Exhibit C: Copy of the Following References Cited by Defendants as Prior Art: U.S. Patent D 326,514, Inventor: Alsup et al.; Issued May 26, 1992; filed Feb. 27, 1990 U.S. Patent 5,043,033 (Friedrich Unit); Inventor: Alsup et al.; Issued Jul. 23, 1991, filed Jul. 13, 1990 Consumer Reports.org, "Air Cleaners: Behind the Hype," http://www.consumerreports.org/main/content/printable.jsp?FOLDER%3C%3EFOLDER_id, Oct. 2003, 6 pp. "Household Air Cleaners," Consumer Reports Magazine, Oct. 1992, 6 pp.

Court Docket for *Sharper Image Corporation v. Brookstone Company, Inc.*, Case No. 04-1572 MMC, United States District Court, Northern District of California, San Francisco Division.

Answer and Counterclaim in *Sharper Image Corporation v. Brookstone, Inc.*, Case No. 04-1572 MMC, dated: Jun. 3, 2004.

Brookstone's Preliminary Invalidity Contentions and Attached Exhibits A-N, Dated: Nov. 5, 2004.

Exhibit A: English Translation of Japanese Unexamined Utility Model Application No. S62-20653; Publication Date: Feb. 7, 1987.

Exhibit B: Japanese Unexamined Utility Model Application No. S62-20653; Publication Date: Feb. 7, 1987.

Exhibit C: English Translation of Japanese Unexamined Patent Application Bulletin No. S51-90077; Publication Date: Aug. 6, 1976.

Exhibit D: Japanese Unexamined Patent Application Bulletin No. S51-90077; Publication Date: Aug. 6, 1976.

Exhibit E: English Translation of German Published Patent Application 2206057; Publication Date: Aug. 16, 1973.

Exhibit F: German Published Patent Application 2206057; Publication Date: Aug. 16, 1973.

Exhibit G: English Translation of Japanese Unexamined Utility Model Application No. S63-164948; Publication Date: Oct. 27, 1988.

Exhibit H: Japanese Unexamined Utility Model Application No. S63-164948; Publication Date: Oct. 27, 1988.

Exhibit I: English Translation of German Patent Document DE 197 41 621 C1; Publication Date: Jun. 10, 1999.

Exhibit J: German Patent Document DE 197 41 621 C1; Publication Date: Jun. 10, 1999.

Exhibit K: Charts of Preliminary Invalidity Contentions for U.S. Patent No. 6,713,026.

Exhibit L: Charts of Preliminary Invalidity Contentions for U.S. Patent No. 6,713,026.

Exhibit M: Charts of Preliminary Invalidity Contentions for U.S. Patent No. 6,713,026.

Exhibit N: The Pure Ion UV Air Purifier Sales Guide, No date.

Brookstone's Proposed Terms and Claim Elements for Construction; Correction of Errata in Invalidity Contentions, Dated: Nov. 15, 2004.

Brookstone's Preliminary Claim Construction and Extrinsic Evidence Under Patent Local Rule 4-2 Disclosure and Attached Exhibits A-L, Dated: Dec. 6, 2004.

Exhibit A: Excerpts from Webster's Third New International Dictionary (Unabridged) (Merriam Webster, Inc. 1989) pp. 732, 737, 742, 1027, 1097, 1192, 1768, 1936, 2053, 2409-2410, 2518, 2541, 2546, and 2627.

Exhibit B: Excerpts from VanNorstrand's Scientific Encyclopedia.

Exhibit C: Excerpts from the McGraw-Hill Dictionary of Engineering (2d Ed. 2002).

Exhibit D: Excerpts from Old English Dictionary (on-line version)

Exhibit E: 1) U.S. Patent No. 4,227,894 (Proynoff) 2) U.S. Patent No. 4,253,852 (Adams) 3) U.S. Patent No. 4,772,297 (Anzai) 4) U.S. Patent No. 4,789,801 (Lee) 5) U.S. Patent No. 4,496,375 (Levantine) 6) U.S. Patent No. 5,386,839 (Chen) 7) U.S. Patent No. 4,231,766 (Spurgin)

Exhibit F: Brief Description of the Substance of Expert's Proposed Testimony—Summary of Expert Testimony Pursuant to Local Rule 4-2(b).

Exhibit G: Final Transcript of SHRP Q4 Sharper Image Corporation's Earning Conference Call, Mar. 25, 2004

Exhibit H: Sharper Image Web Page for Deluxe Spire Feel-Good Fan

Exhibit I: Transcript of the Markman Hearing, Oct. 22, 2004

Exhibit J: Hearing Transcript of Defendant's Motion to Strike, from *Sharper Image Corporation v. Consumer's Union of United States, Incorporated*, Case No. C03-4094 MMC, N. Dist. California, San Francisco Division.

Exhibit K: Photograph of Installed Honeywell Electrostatic Precipitator

Exhibit L: List of the Following U.S. Patents Cited as Prior Art by Defendants:

Exhibit H: Sharper Image Web Page for Deluxe Spire Feel-Good Fan.

Exhibit I: Transcript of the Markman Hearing, Oct. 22, 2004.

Exhibit J: Hearing Transcript of Defendant's Motion to Strike, from *Sharper Image Corporation v. Consumer's Union of United States, Incorporated*, Case No. C03-4094 MMC, N. Dist. California, San Francisco Division.

Exhibit K: Photograph of Installed Honeywell Electrostatic Precipitator.

Exhibit L: List of U.S. Patents Cited as Prior Art by Defendants.

Claim Construction Order for Case No.'s C 02-4860 and C 04-0824, Issued by Claudia Wilken, United States District Judge, Dated: Mar. 21, 2005.

Kaz's Final Invalidity Contentions, Dated: Apr. 11, 2005.

Letter From Mr. Alan Barry, Counsel for Sharper Image, to Mr. Pierre Yanney, Counsel for Kaz, Inc., Dated: Mar. 25, 2005.

Letter from Mr. Pierre Yanney to Mr. Alan Barry, Dated: Mar. 22, 2005.

U.S. Appl. No. 10/023,197, Taylor et al., filed Dec. 13, 2001.

U.S. Appl. No. 10/023,460, Taylor et al., filed Dec. 13, 2001.

U.S. Appl. No. 10/074,209, Taylor et al., filed Feb. 12, 2002.

U.S. Appl. No. 10/074,207, Taylor et al., filed Feb. 12, 2002.

U.S. Appl. No. 10/074,208, Taylor, filed Feb. 12, 2002.

U.S. Appl. No. 10/074,339, Taylor et al., filed Feb. 12, 2002.

U.S. Appl. No. 10/074,827, McKinney, Jr. et al., filed Feb. 12, 2002.

U.S. Appl. No. 10/074,549, Sinaiko et al., filed Feb. 12, 2002.

U.S. Appl. No. 10/074,103, Sinaiko et al., filed Feb. 12, 2002.

U.S. Appl. No. 10/074,096, Taylor et al., filed Feb. 12, 2002.

U.S. Appl. No. 10/074,347, Taylor et al., filed Feb. 12, 2002.

U.S. Appl. No. 10/074,379, Taylor et al., filed Feb. 12, 2002.
Copending U.S. Appl. No. 09/924,624; 10/074,082; 10/074,207; 10/074,208; 10/074,209; 10/074,339; 10/074,549.*

* cited by examiner




FIG. 1A (PRIOR ART)




FIG. 1B (PRIOR ART)




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 4F




FIG. 4G




FIG. 4H




FIG. 4I




FIG. 4J




FIG. 4K

ELECTRO-KINETIC AIR TRANSPORTER-CONDITIONER

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

This is a continuation of application Ser. No. 09/186,471 filed Nov. 5, 1998 now U.S. Pat. No. 6,176,977.

FIELD OF THE INVENTION

This invention relates to electro-kinetic conversion of electrical energy into fluid flow of an ionizable dielectric medium, and more specifically to methods and devices for electro-kinetically producing a flow of air from which particulate matter has been substantially removed. Preferably the air flow should contain safe amounts of ozone (O₃).

BACKGROUND OF THE INVENTION

The use of an electric motor to rotate a fan blade to create an air flow has long been known in the art. Unfortunately, such fans produce substantial noise, and can present a hazard to children who may be tempted to poke a finger or a pencil into the moving fan blade. Although such fans can produce substantial air flow, e.g., 1,000 ft³/minute or more, substantial electrical power is required to operate the motor, and essentially no conditioning of the flowing air occurs.

It is known to provide such fans with a HEPA-compliant filter element to remove particulate matter larger than perhaps 0.3 μm. Unfortunately, the resistance to air flow presented by the filter element may require doubling the electric motor size to maintain a desired level of airflow. Further, HEPA-compliant filter elements are expensive, and can represent a substantial portion of the sale price of a HEPA-compliant filter-fan unit. While such filter-fan units can condition the air by removing large particles, particulate matter small enough to pass through the filter element is not removed, including bacteria, for example.

It is also known in the art to produce an air flow using electro-kinetic techniques, by which electrical power is directly converted into a flow of air without mechanically moving components. One such system is described in U.S. Pat. No. 4,789,801 to Lee (1988), depicted herein in simplified form as FIGS. 1A and 1B. Lee's system 10 includes an array of small area ("minisectional") electrodes 20 that is spaced-apart symmetrically from an array of larger area ("maxisectional") electrodes 30. The positive terminal of a pulse generator 40 that outputs a train of high voltage pulses (e.g., 0 to perhaps +5 KV) is coupled to the minisectional array, and the negative pulse generator terminal is coupled to the maxisectional array.

The high voltage pulses ionize the air between the arrays, and an air flow 50 from the minisectional array toward the maxisectional array results, without requiring any moving parts. Particulate matter 60 in the air is entrained within the airflow 50 and also moves towards the maxisectional electrodes 30. Much of the particulate matter is electrostatically attracted to the surface of the maxisectional electrode array, where it remains, thus conditioning the flow of air exiting system 10. Further, the high voltage field present between the electrode arrays can release ozone into the ambient environment, which appears to destroy or at least alter whatever is entrained in the airflow, including for example, bacteria.

In the embodiment of FIG. 1A, minisectional electrodes 20 are circular in cross-section, having a diameter of about

0.003" (0.08 mm), whereas the maxisectional electrodes 30 are substantially larger in area and define a "teardrop" shape in cross-section. The ratio of cross-sectional areas between the maxisectional and minisectional electrodes is not explicitly stated, but from Lee's figures appears to exceed 10:1. As shown in FIG. 1A herein, the bulbous front surfaces of the maxisectional electrodes face the minisectional electrodes, and the somewhat sharp trailing edges face the exit direction of the air flow. The "sharpened" trailing edges on the maxisectional electrodes apparently promote good electrostatic attachment of particulate matter entrained in the airflow. Lee does not disclose how the teardrop shaped maxisectional electrodes are fabricated, but presumably they are produced using a relatively expensive mold-casting or an extrusion process.

In another embodiment shown herein as FIG. 1B, Lee's maxisectional electrodes 30 are symmetrical and elongated in cross-section. The elongated trailing edges on the maxisectional electrodes provide increased area upon which particulate matter entrained in the airflow can attach. Lee states that precipitation efficiency and desired reduction of anion release into the environment can result from including a passive third array of electrodes 70. Understandably, increasing efficiency by adding a third array of electrodes will contribute to the cost of manufacturing and maintaining the resultant system.

While the electrostatic techniques disclosed by Lee are advantageous to conventional electric fan-filter units, Lee's maxisectional electrodes are relatively expensive to fabricate. Further, increased filter efficiency beyond what Lee's embodiments can produce would be advantageous, especially without including a third array of electrodes.

Thus, there is a need for an electro-kinetic air transporter-conditioner that provides improved efficiency over Lee-type systems, without requiring expensive production techniques to fabricate the electrodes. Preferably such a conditioner should function efficiently without requiring a third array of electrodes. Further, such a conditioner should permit user-selection of safe amounts of ozone to be generated, for example to remove odor from the ambient environment.

The present invention provides a method and apparatus for electro-kinetically transporting and conditioning air.

SUMMARY OF THE PRESENT INVENTION

The present invention provides an electro-kinetic system for transporting and conditioning air without moving parts. The air is conditioned in the sense that it is ionized and contains safe amounts of ozone.

Applicants' electro-kinetic air transporter-conditioner includes a louvered or gridded body that houses an ionizer unit. The ionizer unit includes a high voltage DC inverter that boosts common 110 VAC to high voltage, and a generator that receives the high voltage DC and outputs high voltage pulses of perhaps 10 KV peak-to-peak, although an essentially 100% duty cycle (e.g., high voltage DC) output could be used instead of pulses. The unit also includes an electrode assembly unit comprising first and second spaced-apart arrays of conducting electrodes, the first array and second array being coupled, respectively, preferably to the positive and negative output ports of the high voltage generator.

The electrode assembly preferably is formed using first and second arrays of readily manufacturable electrode types. In one embodiment, the first array comprises wire-like electrodes and the second array comprises "U"-shaped electrodes having one or two trailing surfaces. In an even more efficient embodiment, the first array includes at least one pin

3

or cone-like electrode and the second array is an annular washer-like electrode. The electrode assembly may comprise various combinations of the described first and second array electrodes. In the various embodiments, the ratio between effective area of the second array electrodes to the first array electrodes is at least about 20:1.

The high voltage pulses create an electric field between the first and second electrode arrays. This field produces an electro-kinetic airflow going from the first array toward the second array, the airflow being rich in preferably a net surplus of negative ions and in ozone. Ambient air including dust particles and other undesired components (germs, perhaps) enter the housing through the grill or louver openings, and ionized clean air (with ozone) exits through openings on the downstream side of the housing.

The dust and other particulate matter attaches electrostatically to the second array (or collector) electrodes, and the output air is substantially clean of such particulate matter. Further, ozone generated by the present invention can kill certain types of germs and the like, and also eliminates odors in the output air. Preferably the transporter operates in periodic bursts, and a control permits the user to temporarily increase the high voltage pulse generator output, e.g., to more rapidly eliminate odors in the environment.

Other features and advantages of the invention will appear from the following description in which the preferred embodiments have been set forth in detail, in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a plan, cross-sectional view, of a first embodiment of a prior art electro-kinetic air transporter-conditioner system, according to the prior art;

FIG. 1B is a plan, cross-sectional view, of a second embodiment of a prior art electro-kinetic air transporter-conditioner system, according to the prior art;

FIG. 2A is a perspective view of a preferred embodiment of the present invention;

FIG. 2B is a perspective view of the embodiment of FIG. 2A, with the electrode assembly partially withdrawn, according to the present invention;

FIG. 3 is an electrical block diagram of the present invention;

FIG. 4A is a perspective block diagram showing a first embodiment for an electrode assembly, according to the present invention;

FIG. 4B is a plan block diagram of the embodiment of FIG. 4A;

FIG. 4C is a perspective block diagram showing a second embodiment for an electrode assembly, according to the present invention;

FIG. 4D is a plan block diagram of a modified version of the embodiment of FIG. 4C;

FIG. 4E is a perspective block diagram showing a third embodiment for an electrode assembly, according to the present invention;

FIG. 4F is a plan block diagram of the embodiment of FIG. 4E;

FIG. 4G is a perspective block diagram showing a fourth embodiment for an electrode assembly, according to the present invention;

FIG. 4H is a plan block diagram of the embodiment of FIG. 4G;

FIG. 4I is a perspective block diagram showing a fifth embodiment for an electrode assembly, according to the present invention;

4

FIG. 4J is a detailed cross-sectional view of a portion of the embodiment of FIG. 4I;

FIG. 4K is a detailed cross-sectional view of a portion of an alternative to the embodiment of FIG. 4I.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIGS. 2A and 2B depict an electro-kinetic air transporter-conditioner system **100** whose housing **102** includes preferably rear-located intake vents or louvers **104** and preferably front and side-located exhaust vents **106**, and a base pedestal **108**. Internal to the transporter housing is an ion generating unit **160**, preferably powered by an AC:DC power supply that is energizable using switch **S1**. Ion generating unit **160** is self-contained in that other than ambient air, nothing is required from beyond the transporter housing, save external operating potential, for operation of the present invention.

The upper surface of housing **102** includes a user-liftable handle **112** to which is affixed an electrode assembly **220** that comprises a first array **230** of electrodes **232** and a second array **240** of electrodes **242**. The first and second arrays of electrodes are coupled in series between the output terminals of ion generating unit **160**, as best seen in FIG. 3. The ability to lift handle **112** provides ready access to the electrodes comprising the electrode assembly, for purposes of cleaning and, if necessary, replacement.

The general shape of the invention shown in FIGS. 2A and 2B is not critical. The top-to-bottom height of the preferred embodiment is perhaps 1 m, with a left-to-right width of perhaps 15 cm, and a front-to-back depth of perhaps 10 cm, although other dimensions and shapes may of course be used. A louvered construction provides ample inlet and outlet venting in an economical housing configuration. There need be no real distinction between vents **104** and **106**, except their location relative to the second array electrodes, and indeed a common vent could be used. These vents serve to ensure that an adequate flow of ambient air may be drawn into or made available to the present invention, and that an adequate flow of ionized air that includes safe amounts of O_3 flows out from unit **130**.

As will be described, when unit **100** is energized with **S1**, high voltage output by ion generator **160** produces ions at the first electrode array, which ions are attracted to the second electrode array. The movement of the ions in an "IN" to "OUT" direction carries with them air molecules, thus electrokinetically producing an outflow of ionized air. The "IN" notion in FIGS. 2A and 2B denote the intake of ambient air with particulate matter **60**. The "OUT" notation in the figures denotes the outflow of cleaned air substantially devoid of the particulate matter, which adheres electrostatically to the surface of the second array electrodes. In the process of generating the ionized air flow, safe amounts of ozone (O_3) are beneficially produced. It may be desired to provide the inner surface of housing **102** with an electrostatic shield to reduce detectable electromagnetic radiation. For example, a metal shield could be disposed within the housing, or portions of the interior of the housing could be coated with a metallic paint to reduce such radiation.

As best seen in FIG. 3, ion generating unit **160** includes a high voltage generator unit **170** and circuitry **180** for converting raw alternating voltage (e.g., 117 VAC) into direct current ("DC") voltage. Circuitry **180** preferably includes circuitry controlling the shape and/or duty cycle of the generator unit output voltage (which control is altered with user switch **S2**). Circuitry **180** preferably also includes a pulse mode component, coupled to switch **S3**, to temporarily pro-

5

vide a burst of increased output ozone. Circuitry **180** can also include a timer circuit and a visual indicator such as a light emitting diode ("LED"). The LED or other indicator (including, if desired, audible indicator) signals when ion generation is occurring. The timer can automatically halt generation of ions and/or ozone after some predetermined time, e.g., 30 minutes, indicator(s), and/or audible indicator(s).

As shown in FIG. 3, high voltage generator unit **170** preferably comprises a low voltage oscillator circuit **190** of perhaps 20 KHz frequency, that outputs low voltage pulses to an electronic switch **200**, e.g., a thyristor or the like. Switch **200** switchably couples the low voltage pulses to the input winding of a step-up transformer T1. The secondary winding of T1 is coupled to a high voltage multiplier circuit **210** that outputs high voltage pulses. Preferably the circuitry and components comprising high voltage pulse generator **170** and circuit **180** are fabricated on a printed circuit board that is mounted within housing **102**. If desired, external audio input (e.g., from a stereo tuner) could be suitably coupled to oscillator **190** to acoustically modulate the kinetic airflow produced by unit **160**. The result would be an electrostatic loudspeaker, whose output air flow is audible to the human ear in accordance with the audio input signal. Further, the output air stream would still include ions and ozone.

Output pulses from high voltage generator **170** preferably are at least 10 KV peak-to-peak with an effective DC offset of perhaps half the peak-to-peak voltage, and have a frequency of perhaps 20 KHz. The pulse train output preferably has a duty cycle of perhaps 10%, which will promote battery lifetime. Of course, different peak-peak amplitudes, DC offsets, pulse train waveshapes, duty cycle, and/or repetition frequencies may instead be used. Indeed, a 100% pulse train (e.g., an essentially DC high voltage) may be used, albeit with shorter battery life-time. Thus, generator unit **170** may (but need not) be referred to as a high voltage pulse generator.

Frequency of oscillation is not especially critical but frequency of at least about 20 KHz is preferred as being inaudible to humans. If pets will be in the same room as the present invention, it may be desired to utilize an even higher operating frequency, to prevent pet discomfort and/or howling by the pet.

The output from high voltage pulse generator unit **170** is coupled to an electrode assembly **220** that comprises a first electrode array **230** and a second electrode array **240**. Unit **170** functions as a DC:DC high voltage generator, and could be implemented using other circuitry and/or techniques to output high voltage pulses that are input to electrode assembly **220**.

In the embodiment of FIG. 3, the positive output terminal of unit **170** is coupled to first electrode array **230**, and the negative output terminal is coupled to second electrode array **240**. This coupling polarity has been found to work well, including minimizing unwanted audible electrode vibration or hum. An electrostatic flow of air is created, going from the first electrode array towards the second electrode array. (This flow is denoted "OUT" in the figures.) Accordingly electrode assembly **220** is mounted within transporter system **100** such that second electrode array **240** is closer to the OUT vents and first electrode array **230** is closer to the IN vents.

When voltage or pulses from high voltage pulse generator **170** are coupled across first and second electrode arrays **230** and **240**, it is believed that a plasma-like field is created surrounding electrodes **232** in first array **230**. This electric

6

field ionizes the ambient air between the first and second electrode arrays and establishes an "OUT" airflow that moves towards the second array. It is understood that the IN flow enters via vent(s) **104**, and that the OUT flow exits via vent(s) **106**.

It is believed that ozone and ions are generated simultaneously by the first array electrode(s) **232**, essentially as a function of the potential from generator **170** coupled to the first array. Ozone generation may be increased or decreased by increasing or decreasing the potential at the first array. Coupling an opposite polarity potential to the second array electrode(s) **242** essentially accelerates the motion of ions generated at the first array, producing the air flow denoted as "OUT" in the figures. As the ions move toward the second array, it is believed that they push or move air molecules toward the second array. The relative velocity of this motion may be increased by decreasing the potential at the second array relative to the potential at the first array.

For example, if +10 KV were applied to the first array electrode(s), and no potential were applied to the second array electrode(s), a cloud of ions (whose net charge is positive) would form adjacent the first electrode array. Further, the relatively high 10 KV potential would generate substantial ozone. By coupling a relatively negative potential to the second array electrode(s), the velocity of the air mass moved by the net emitted ions increases, as momentum of the moving ions is conserved.

On the other hand, if it were desired to maintain the same effective outflow (OUT) velocity but to generate less ozone, the exemplary 10 KV potential could be divided between the electrode arrays. For example, generator **170** could provide +4 KV (or some other fraction) to the first array electrode(s) and -6 KV (or some other fraction) to the second array electrode(s). In this example, it is understood that the +4 KV and the -6 KV are measured relative to ground. Understandably it is desired that the present invention operate to output safe amounts of ozone. Accordingly, the high voltage is preferably fractionalized with about +4 KV applied to the first array electrode(s) and about -6 KV applied to the second array electrodes.

As noted, outflow (OUT) preferably includes safe amounts of O₃ that can destroy or at least substantially alter bacteria, germs, and other living (or quasi-living) matter subjected to the outflow. Thus, when switch S1 is closed and B1 has sufficient operating potential, pulses from high voltage pulse generator unit **170** create an outflow (OUT) of ionized air and O₃. When S1 is closed, LED will visually signal when ionization is occurring.

Preferably operating parameters of the present invention are set during manufacture and are not user-adjustable. For example, increasing the peak-to-peak output voltage and/or duty cycle in the high voltage pulses generated by unit **170** can increase air flowrate, ion content, and ozone content. In the preferred embodiment, output flowrate is about 200 feet/minute, ion content is about 2,000,000/cc and ozone content is about 40 ppb (over ambient) to perhaps 2,000 ppb (over ambient). Decreasing the R2/R1 ratio below about 20:1 will decrease flow rate, as will decreasing the peak-to-peak voltage and/or duty cycle of the high voltage pulses coupled between the first and second electrode arrays.

In practice, unit **100** is placed in a room and connected to an appropriate source of operating potential, typically 117 VAC. With S1 energized, ionization unit **160** emits ionized air and preferably some ozone (O₃) via outlet vents **150**. The air flow, coupled with the ions and ozone freshens the air in the room, and the ozone can beneficially destroy or at least

diminish the undesired effects of certain odors, bacteria, germs, and the like. The air flow is indeed electro-kinetically produced, in that there are no intentionally moving parts within the present invention. (As noted, some mechanical vibration may occur within the electrodes.) As will be described with respect to FIG. 4A, it is desirable that the present invention actually output a net surplus of negative ions, as these ions are deemed more beneficial to health than are positive ions.

Having described various aspects of the invention in general, preferred embodiments of electrode assembly 220 will now be described. In the various embodiments, electrode assembly 220 will comprise a first array 230 of at least one electrode 232, and will further comprise a second array 240 of preferably at least one electrode 242. Understandably material(s) for electrodes 232 and 242 should conduct electricity, be resilient to corrosive effects from the application of high voltage, yet be strong enough to be cleaned.

In the various electrode assemblies to be described herein, electrode(s) 232 in the first electrode array 230 are preferably fabricated from tungsten. Tungsten is sufficiently robust to withstand cleaning, has a high melting point to retard breakdown due to ionization, and has a rough exterior surface that seems to promote efficient ionization. On the other hand, electrodes 242 preferably will have a highly polished exterior surface to minimize unwanted point-to-point radiation. As such, electrodes 242 preferably are fabricated from stainless steel, brass, among other materials. The polished surface of electrodes 232 also promotes ease of electrode cleaning.

In contrast to the prior art electrodes disclosed by Lee, electrodes 232 and 242 according to the present invention are lightweight, easy to fabricate, and lend themselves to mass production. Further, electrodes 232 and 242 described herein promote more efficient generation of ionized air, and production of safe amounts of ozone, O₃.

In the present invention, a high voltage pulse generator 170 is coupled between the first electrode array 230 and the second electrode array 240. The high voltage pulses produce a flow of ionized air that travels in the direction from the first array towards the second array (indicated herein by hollow arrows denoted "OUT"). As such, electrode(s) 232 may be referred to as an emitting electrode, and electrodes 242 may be referred to as collector electrodes. This outflow advantageously contains safe amounts of O₃, and exits the present invention from vent(s) 106.

According to the present invention, it is preferred that the positive output terminal or port of the high voltage pulse generator be coupled to electrodes 232, and that the negative output terminal or port be coupled to electrodes 242. It is believed that the net polarity of the emitted ions is positive, e.g., more positive ions than negative ions are emitted. In any event, the preferred electrode assembly electrical coupling minimizes audible hum from electrodes 232 contrasted with reverse polarity (e.g., interchanging the positive and negative output port connections).

However, while generation of positive ions is conducive to a relatively silent air flow, from a health standpoint, it is desired that the output air flow be richer in negative ions, not positive ions. It is noted that in some embodiments, however, one port (preferably the negative port) of the high voltage pulse generator may in fact be the ambient air. Thus, electrodes in the second array need not be connected to the high voltage pulse generator using wire. Nonetheless, there will be an "effective connection" between the second array electrodes and one output port of the high voltage pulse generator, in this instance, via ambient air.

Turning now to the embodiments of FIGS. 4A and 4B, electrode assembly 220 comprises a first array 230 of wire electrodes 232, and a second array 240 of generally "U"-shaped electrodes 242. In preferred embodiments, the number N1 of electrodes comprising the first array will preferably differ by one relative to the number N2 of electrodes comprising the second array. In many of the embodiments shown, N2>N1. However, if desired, in FIG. 4A, additional first electrodes 232 could be added at the out ends of array 230 such that N1>N2, e.g., five electrodes 232 compared to four electrodes 242.

Electrodes 232 are preferably lengths of tungsten wire, whereas electrodes 242 are formed from sheet metal, preferably stainless steel, although brass or other sheet metal could be used. The sheet metal is readily formed to define side regions 244 and bulbous nose region 246 for hollow elongated "U" shaped electrodes 242. While FIG. 4A depicts four electrodes 242 in second array 240 and three electrodes 232 in first array 230, as noted, other numbers of electrodes in each array could be used, preferably retaining a symmetrically staggered configuration as shown. It is seen in FIG. 4A that while particulate matter 60 is present in the incoming (IN) air, the outflow (OUT) air is substantially devoid of particulate matter, which adheres to the preferably large surface area provided by the second array electrodes (see FIG. 4B).

As best seen in FIG. 4B, the spaced-apart configuration between the arrays is staggered such that each first array electrode 232 is substantially equidistant from two second array electrodes 242. This symmetrical staggering has been found to be an especially efficient electrode placement. Preferably the staggering geometry is symmetrical in that adjacent electrodes 232 or adjacent electrodes 242 are spaced apart a constant distance, Y1 and Y2 respectively. However, a non-symmetrical configuration could also be used, although ion emission and air flow would likely be diminished. Also, it is understood that the number of electrodes 232 and 242 may differ from what is shown.

In FIG. 4A, typically dimensions are as follows: diameter of electrodes 232 is about 0.08 mm, distances Y1 and Y2 are each about 16 mm, distance X1 is about 16 mm, distance L is about 20 mm, and electrode heights Z1 and Z2 are each about 1 m. The width W of electrodes 242 is preferably about 4 mm, and the thickness of the material from which electrodes 242 are formed is about 0.5 mm. Of course other dimensions and shapes could be used. It is preferred that electrodes 232 be small in diameter to help establish a desired high voltage field. On the other hand, it is desired that electrodes 232 (as well as electrodes 242) be sufficiently robust to withstand occasional cleaning.

Electrodes 232 in first array 230 are coupled by a conductor 234 to a first (preferably positive) output port of high voltage pulse generator 170, and electrodes 242 in second array 240 are coupled by a conductor 244 to a second (preferably negative) output port of generator 170. It is relatively unimportant where on the various electrodes electrical connection is made to conductors 234 or 244. Thus, by way of example FIG. 4B depicts conductor 244 making connection with some electrodes 242 internal to bulbous end 246, while other electrodes 242 make electrical connection to conductor 244 elsewhere on the electrode. Electrical connection to the various electrodes 242 could also be made on the electrode external surface providing no substantial impairment of the outflow airstream results.

To facilitate removing the electrode assembly from unit 100 (as shown in FIG. 2B), it is preferred that the lower end

of the various electrodes fit against mating portions of wire or other conductors **234** or **244**. For example, "cup-like" members can be affixed to wires **234** and **244** into which the free ends of the various electrodes fit when electrode array **220** is inserted completely into housing **102** of unit **100**.

The ratio of the effective electric field emanating area of electrode **232** to the nearest effective area of electrodes **242** is at least about 15:1, and preferably is at least 20:1. Thus, in the embodiment of FIG. 4A and FIG. 4B, the ratio $R2/R1 \approx 2 \text{ mm}/0.04 \text{ mm} \approx 50:1$.

In this and the other embodiments to be described herein, ionization appears to occur at the smaller electrode(s) **232** in the first electrode array **230**, with ozone production occurring as a function of high voltage arcing. For example, increasing the peak-to-peak voltage amplitude and/or duty cycle of the pulses from the high voltage pulse generator **170** can increase ozone content in the output flow of ionized air. If desired, user-control **S2** can be used to somewhat vary ozone content by varying (in a safe manner) amplitude and/or duty cycle. Specific circuitry for achieving such control is known in the art and need not be described in detail herein.

Note the inclusion in FIGS. 4A and 4B of at least one output controlling electrode **243**, preferably electrically coupled to the same potential as the second array electrodes. Electrode **243** preferably defines a pointed shape in side profile, e.g., a triangle. The sharp point on electrode(s) **243** causes generation of substantial negative ions (since the electrode is coupled to relatively negative high potential). These negative ions neutralize excess positive ions otherwise present in the output air flow, such that the OUT flow has a net negative charge. Electrode(s) **243** preferably are stainless steel, copper, or other conductor, and are perhaps 20 mm high and about 12 mm wide at the base.

Another advantage of including pointed electrodes **243** is that they may be stationarily mounted within the housing of unit **100**, and thus are not readily reached by human hands when cleaning the unit. Were it otherwise, the sharp point on electrode(s) **243** could easily cause cuts. The inclusion of one electrode **243** has been found sufficient to provide a sufficient number of output negative ions, but more such electrodes may be included.

In the embodiment of FIGS. 4A and 4C, each "U"-shaped electrode **242** has two trailing edges that promote efficient kinetic transport of the outflow of ionized air and O_3 . Note the inclusion on at least one portion of a trailing edge of a pointed electrode region **243'**. Electrode region **243'** helps promote output of negative ions, in the same fashion as was described with respect to FIGS. 4A and 4B. Note, however, the higher likelihood of a user cutting himself or herself when wiping electrodes **242** with a cloth or the like to remove particulate matter deposited thereon. In FIG. 4C and the figures to follow, the particulate matter is omitted for ease of illustration. However, from what was shown in FIGS. 2A-4B, particulate matter will be present in the incoming air, and will be substantially absent from the outgoing air. As has been described, particulate matter **60** typically will be electrostatically precipitated upon the surface area of electrodes **242**.

Note that the embodiments of FIGS. 4C and 4D depict somewhat truncated versions of electrodes **242**. Whereas dimension **L** in the embodiment of FIGS. 4A and 4B was about 20 mm, in FIGS. 4C and 4D, **L** has been shortened to about 8 mm. Other dimensions in FIG. 4C preferably are similar to those stated for FIGS. 4A and 4B. In FIGS. 4C and 4D, the inclusion of point-like regions **246** on the trailing edge of electrodes **242** seems to promote more efficient gen-

eration of ionized air flow. It will be appreciated that the configuration of second electrode array **240** in FIG. 4C can be more robust than the configuration of FIGS. 4A and 4B, by virtue of the shorter trailing edge geometry. As noted earlier, a symmetrical staggered geometry for the first and second electrode arrays is preferred for the configuration of FIG. 4C.

In the embodiment of FIG. 4D, the outermost second electrodes, denoted **242-1** and **242-2**, have substantially no outermost trailing edges. Dimension **L** in FIG. 4D is preferably about 3 mm, and other dimensions may be as stated for the configuration of FIGS. 4A and 4B. Again, the $R2/R1$ ratio for the embodiment of FIG. 4D preferably exceeds about 20:1.

FIGS. 4E and 4F depict another embodiment of electrode assembly **220**, in which the first electrode array comprises a single wire electrode **232**, and the second electrode array comprises a single pair of curved "L"-shaped electrodes **242**, in cross-section. Typical dimensions, where different than what has been stated for earlier-described embodiments, are $X1 \approx 12 \text{ mm}$, $Y1 \approx 6 \text{ mm}$, $Y2 \approx 5 \text{ mm}$, and $L1 \approx 3 \text{ mm}$. The effective $R2/R1$ ratio is again greater than about 20:1. The fewer electrodes comprising assembly **220** in FIGS. 4E and 4F promote economy of construction, and ease of cleaning, although more than one electrode **232**, and more than two electrodes **242** could of course be employed. This embodiment again incorporates the staggered symmetry described earlier, in which electrode **232** is equidistant from two electrodes **242**.

FIGS. 4G and 4H show yet another embodiment for electrode assembly **220**. In this embodiment, first electrode array **230** is a length of wire **232**, while the second electrode array **240** comprises a pair of rod or columnar electrodes **242**. As in embodiments described earlier herein, it is preferred that electrode **232** be symmetrically equidistant from electrodes **242**. Wire electrode **232** is preferably perhaps 0.08 mm tungsten, whereas columnar electrodes **242** are perhaps 2 mm diameter stainless steel. Thus, in this embodiment the $R2/R1$ ratio is about 25:1. Other dimensions may be similar to other configurations, e.g., FIGS. 4E, 4F. Of course electrode assembly **220** may comprise more than one electrode **232**, and more than two electrodes **242**.

An especially preferred embodiment is shown in FIG. 4I and FIG. 4J. In these figures, the first electrode assembly comprises a single pin-like element **232** disposed coaxially with a second electrode array that comprises a single ring-like electrode **242** having a rounded inner opening **246**. However, as indicated by phantom elements **232'**, **242'**, electrode assembly **220** may comprise a plurality of such pin-like and ring-like elements. Preferably electrode **232** is tungsten, and electrode **242** is stainless steel.

Typical dimensions for the embodiment of FIG. 4I and FIG. 4J are $L1 \approx 10 \text{ mm}$, $X1 \approx 9.5 \text{ mm}$, $T \approx 0.5 \text{ mm}$, and the diameter of opening **246** is about 12 mm. Dimension **L1** preferably is sufficiently long that upstream portions of electrode **232** (e.g., portions to the left in FIG. 4I) do not interfere with the electrical field between electrode **232** and the collector electrode **242**. However, as shown in FIG. 4J, the effect $R2/R1$ ratio is governed by the tip geometry of electrode **232**. Again, in the preferred embodiment, this ratio exceeds about 20:1. Lines drawn in phantom in FIG. 4J depict theoretical electric force field lines, emanating from emitter electrode **232**, and terminating on the curved surface of collector electrode **246**. Preferably the bulk of the field emanates within about $\pm 45^\circ$ of coaxial axis between electrode **232** and electrode **242**. On the other hand, if the open-

11

ing in electrode **242** and/or electrode **232** and **242** geometry is such that too narrow an angle about the coaxial axis exists, air flow will be unduly restricted.

One advantage of the ring-pin electrode assembly configuration shown in FIG. **4I** is that the flat regions of ring-like electrode **242** provide sufficient surface area to which particulate matter **60** entrained in the moving air stream can attach, yet be readily cleaned.

Further, the ring-pin configuration advantageously generates more ozone than prior art configurations, or the configurations of FIGS. **4A–4H**. For example, whereas the configurations of FIGS. **4A–4H** may generate perhaps 50 ppb ozone, the configuration of FIG. **4I** can generate about 2,000 ppb ozone.

Nonetheless it will be appreciated that applicants' first array pin electrodes may be utilized with the second array electrodes of FIGS. **4A–4H**. Further, applicants' second array ring electrodes may be utilized with the first array electrodes of FIGS. **4A–4H**. For example, in modifications of the embodiments of FIGS. **4A–4H**, each wire or columnar electrode **232** is replaced by a column of electrically series-connected pin electrodes (e.g., as shown in FIGS. **4I–4K**), while retaining the second electrode arrays as depicted in these figures. By the same token, in other modifications of the embodiments of FIGS. **4A–4H**, the first array electrodes can remain as depicted, but each of the second array electrodes **242** is replaced by a column of electrically series-connected ring electrodes (e.g., as shown in FIGS. **4I–4K**).

In FIG. **4J**, a detailed cross-sectional view of the central portion of electrode **242** in FIG. **4I** is shown. As best seen in FIG. **4J**, curved region **246** adjacent the central opening in electrode **242** appears to provide an acceptably large surface area to which many ionization paths from the distal tip of electrode **232** have substantially equal path length. Thus, while the distal tip (or emitting tip) of electrode **232** is advantageously small to concentrate the electric field between the electrode arrays, the adjacent regions of electrode **242** preferably provide many equidistant interelectrode array paths. A high exit flowrate of perhaps 90 feet/minute and 2,000 ppb range ozone emission attainable with this configuration confirm a high operating efficiency.

In FIG. **4K**, one or more electrodes **232** is replaced by a conductive block **232"** of carbon fibers, the block having a distal surface in which projecting fibers **233-1**, . . . **233-N** take on the appearance of a "bed of nails". The projecting fibers can each act as an emitting electrode and provide a plurality of emitting surfaces. Over a period of time, some or all of the electrodes will literally be consumed, whereupon graphite block **232"** will be replaced. Materials other than graphite may be used for block **232"** providing the material has a surface with projecting conductive fibers such as **233-N**.

As described, the net output of ions is influenced by placing a bias element (e.g., element **243**) near the output stream and preferably near the downstream side of the second array electrodes. If no ion output were desired, such an element could achieve substantial neutralization. It will also be appreciated that the present invention could be adjusted to produce ions without producing ozone, if desired.

Modifications and variations may be made to the disclosed embodiments without departing from the subject and spirit of the invention as defined by the following claims.

What is claimed is:

1. An air conditioner system, comprising:

an upstanding, elongated housing having a top surface, an inlet and an outlet; and

12

an ion generating unit positioned in said housing, including:

a first electrode;

a second electrode; and

a high voltage generator that provides a potential difference between said first electrode and said second electrode;

wherein said second electrode is removable, through said top surface of said housing, from a resting position within said housing to a location external to the housing, to thereby allow said second electrode to be cleaned; and

wherein said second electrode is returnable through said top surface of the housing such that gravity will assist with return of the second electrode to the resting position within said housing.

2. The system as recited in claim 1, wherein said top surface of said housing further includes a user control.

3. The system as recited in claim 1, wherein said first electrode is located proximate to the inlet, and the second removable electrode is located closer to the outlet than said first electrode.

4. The system as recited in claim 1, wherein a user-liftable handle is attached to said second removable electrode, said use-liftable handle accessible through an opening in said top surface of said housing.

5. The system as recited in claim 1, wherein said second removable electrode is elongated along a direction of said elongated housing.

6. An air conditioner system, comprising:

an upstanding, elongated housing having a top surface, an air inlet vent, and an air outlet vent;

an ion generating unit positioned in said housing, for creating an airflow from said inlet vent to said outlet vent, including:

a first emitter electrode;

a second removable collector electrode, elongated along the direction of elongation of said housing, and removable through an opening in the top surface of said housing; and

a user-liftable handle secured to said second removable collector electrode, said handle accessible through said opening in said top surface of said housing, to assist a user with lifting said second removable collector electrode out of said housing from a resting position within said housing; and

wherein said second removable electrode is returnable through said opening in said top surface of said housing such that gravity will assist with return of said second removable collector electrode to the resting position within said housing.

7. The system as recited in claim 6, wherein said second removable collector electrode is hollow.

8. The system as recited in claim 6, wherein said second removable collector electrode is "U"-shaped.

9. The system as recited in claim 6, wherein said second removable collector electrode is located proximate to said air outlet vent.

10. The system of claim 6, further comprising: a user operable control located on said top surface of said housing.

11. An ion producing system, comprising:

a housing that is vertically elongated, said housing including at least one vent;

an emitter electrode within said housing;

a collector electrode that is vertically elongated when in a resting position within said housing;

13

a high voltage generator to provide a potential difference between said emitter electrode and said collector electrode when said collector electrode is in the resting position within said housing; and
 a handle secured to said collector electrode, said handle to assist a user with vertically lifting said collector electrode out of said housing;
 wherein said collector electrode is vertically returnable with the assistance of gravity, through an opening in an upper portion of said housing, to the resting position within said housing.

12. The system of claim 11, further comprising:
 an opening in a top of said housing; and
 wherein said handle assists a user with vertically lifting said collector electrode out through said opening in said top of said housing.

13. The system of claim 11, wherein the high voltage generator comprises a first terminal at a first potential and a second terminal at a second potential that enable the high voltage generator to provide the potential difference between said emitter electrode and said collector electrode; and wherein a lower end of said collector electrode mates with said second terminal when in the resting position within said housing; and wherein said collector electrode disengages from said second terminal when vertically lifted out of said housing.

14. The system of claim 13, wherein gravity causes said lower end of said collector electrode to mate with said second terminal when said collector electrode is in the resting position within said housing.

15. An ion producing system, comprising:
 an upstanding, elongated housing having a top surface, an inlet and an outlet; and
 an ion generating unit positioned in said housing, including:
 a first electrode;
 a second electrode; and
 a high voltage generator that provides a potential difference between said first electrode and said second electrode;

wherein said second electrode is removable, through said top surface of said housing, from a resting position within said housing to a location external to the housing, to thereby allow said second electrode to be cleaned; and
 wherein said second electrode is returnable through said top surface of the housing such that gravity will assist with return of the second electrode to the resting position within said housing.

16. An ion producing system, comprising:
 an upstanding, elongated housing having an inlet and an outlet; and
 an ion generating unit positioned in said housing, including:
 a first electrode;
 a second electrode; and
 a high voltage generator that provides a potential difference between said first electrode and said second electrode;

wherein said second electrode is vertically removable, through an opening in an upper portion of said housing, from a resting position within said housing to a location external to the housing, to thereby allow said second electrode to be cleaned; and

wherein said second electrode is vertically returnable through said opening such that gravity will assist with

14

return of the second electrode to the resting position within said housing.

17. An ion producing system, comprising:
 an upstanding, vertically elongated housing having at least one air vent;
 an ion generating unit positioned in said housing, including:
 a first emitter electrode;
 a second removable collector electrode, elongated along a direction of elongation of said vertically elongated housing, and vertically removable through an opening through a top portion of said housing; and

a handle secured to said second removable collector electrode, said handle accessible through said opening to assist a user with vertically lifting said second removable collector electrode out of said housing from a resting position within said housing; and

wherein said second removable electrode is vertically returnable through said opening such that gravity will assist with return of said second removable collector electrode to the resting position within said housing.

18. An ion producing air conditioning system, comprising:

an upstanding, vertically elongated housing having at least one air vent;

an ion generating unit positioned in said housing, including:

an emitter electrode;
 a removable collector electrode, elongated along a direction of elongation of said vertically elongated housing, and vertically removable through an opening through a top portion of said housing such that a user can vertically lift said removable collector electrode out of said housing from a resting position within said housing; and

wherein said removable electrode is vertically returnable through said opening such that gravity will assist with return of said removable collector electrode to the resting position within said housing.

19. An ion producing system, comprising:

an upstanding, vertically elongated housing containing an ion generating unit;

at least one air vent in said housing;

the ion generating unit including:

an emitter electrode;
 a removable collector electrode elongated along a direction of elongation of said vertically elongated housing when in a resting position within said housing; and
 a handle attached to said removable collector electrode such that said handle extends in an upward direction from said collector electrode and isolates said ion generating unit from a user when said removable collector electrode is in the resting position within said housing;

wherein said handle is adapted to assist a user with vertically lifting said removable collector electrode out of said housing from the resting position within said housing; and

wherein said removable collector electrode is vertically returnable into said housing such that gravity will assist with return of said removable collector electrode to the resting position within said housing.

15

20. An ion producing system, comprising:
 an upstanding, vertically elongated housing containing
 an ion generating unit;
 at least one air vent in said housing;
 the ion generating unit including a removable electrode 5
 elongated along a direction of elongation of said verti-
 cally elongated housing when in a resting position
 within said housing; and
 a handle attached to said removable electrode such that 10
 said handle extends in an upward direction from said
 electrode and isolates said ion generating unit from a
 user when said removable electrode is in the resting
 position within said housing;
 wherein said handle is adapted to assist a user with verti- 15
 cally lifting said removable electrode out of said hous-
 ing from the resting position within said housing; and
 wherein said removable electrode is vertically returnable
 into said housing such that gravity will assist with
 return of said removable electrode to the resting posi- 20
 tion within said housing.

21. An ion producing system, comprising:
 an upstanding, vertically elongated housing containing
 an ion generating unit;
 at least one air vent in said housing; 25
 the ion generating unit including:
 an emitter electrode;
 a removable collector electrode elongated along a
 direction of elongation of said vertically elongated
 housing when in a resting position within said hous- 30
 ing; and
 a handle attached to said collector electrode such that
 said handle extends in an upward direction from said
 collector electrode and isolates said ion generating
 unit from a user, when said collector electrode is in 35
 the resting position within said housing;
 wherein said handle is adapted to assist a user with verti-
 cally lifting said removable collector electrode out of
 said housing from the resting position within said hous- 40
 ing; and
 wherein said removable collector electrode is vertically
 returnable into said housing such that gravity will
 assist with return of the second electrode to the resting
 position within the housing.

16

22. An ion producing system, comprising:
 an upstanding, vertically elongated housing containing
 an ion generating unit;
 the ion generating unit including a removable electrode
 elongated along a direction of elongation of said verti-
 cally elongated housing when in a resting position
 within said housing; and
 a handle attached to said removable electrode such that
 said handle extends in an upward direction from said
 electrode and isolates said ion generating unit from a
 user, when said removable electrode is in the resting
 position within said housing;
 wherein said handle is adapted to assist a user with verti-
 cally lifting said removable electrode out of said hous-
 ing from the resting position within said housing; and
 wherein said removable electrode is vertically returnable
 into said housing such that gravity will assist with
 return of the second electrode to the resting position
 within the housing.

23. An ion producing system, comprising:
 an upstanding, vertically elongated housing containing
 an ion generating unit;
 a high voltage generator that provides a potential differ-
 ence in the ion generating unit;
 the ion generating unit including a removable electrode
 elongated along a direction of elongation of said verti-
 cally elongated housing when in a resting position
 within said housing; and
 a handle fixedly attached to said removable electrode such
 that said handle extends in an upward direction from
 said electrode and isolates said ion generating unit
 from a user, when said removable electrode is in the
 resting position within said housing;
 wherein said handle is adapted to assist a user with verti-
 cally lifting said removable electrode out of said hous-
 ing from the resting position within said housing; and
 wherein said removable electrode is vertically returnable
 into said housing such that gravity will assist with
 return of the second electrode to the resting position
 within the housing.

* * * * *