



US00RE42090E

(19) **United States**
(12) **Reissued Patent**
Bruner et al.

(10) **Patent Number:** **US RE42,090 E**
(45) **Date of Reissued Patent:** **Feb. 1, 2011**

(54) **METHOD OF SORTING WASTE PAPER**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Russell S. Bruner**, Franklin, TN (US);
David R. Morgan, Hardin, KY (US);
Garry R. Kenny, Nashville, TN (US);
Paul G. Gaddis, Seattle, WA (US);
David Lee, Tacoma, WA (US); **James**
M. Roggow, Puyallup, WA (US)

CA 2109021 4/1994

(Continued)

OTHER PUBLICATIONS

Exhibit A: U.S. Appl. No. 09/516,257, filed Feb. 29, 2000
(now U.S. Patent No. 7,019,822) and its file history.

(Continued)

Primary Examiner—F. L. Evans

(74) Attorney, Agent, or Firm—Waddey & Patterson, P.C.;
Lucian Wayne Beavers

(73) Assignee: **MSS, Inc.**, Nashville, TN (US)

(21) Appl. No.: **11/139,005**

(22) Filed: **May 26, 2005**

(57) **ABSTRACT**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,570,653**
Issued: **May 27, 2003**
Appl. No.: **10/004,690**
Filed: **Dec. 4, 2001**

U.S. Applications:

(63) Continuation of application No. 09/301,715, filed on Apr.
29, 1999, now Pat. No. 6,369,882.

(51) **Int. Cl.**
G01N 21/64 (2006.01)

(52) **U.S. Cl.** **356/417**; 356/317; 250/459.1;
250/461.1; 209/577

(58) **Field of Classification Search** 356/317,
356/417; 250/458.1, 459.1, 461.1, 461.2;
209/577

See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

1,035,345 A 8/1912 Heess

(Continued)

[Apparatus and methods are provided for sensing the presence of bright white paper on a conveyor of a paper sorting system. The conveyor is constantly illuminated with ultraviolet light. When bright white paper is present in the inspection zone of the conveyor, it will re-radiate fluorescent light energy as a result of the ultraviolet light. Periodically, the inspection zone of the conveyor is illuminated with a second light source in the visible light spectrum. Light is collected from the inspection zone of the conveyor, including reflected light from the secondary source and including emitted fluorescent light energy as a result of the ultraviolet light falling on bright white paper. Periodically a microprocessor associated with the sensor senses reflected light from the second source to determine whether any object is present on the conveyor. The microprocessor then senses the level of fluorescent light energy being emitted from any object on the conveyor. The system determines first whether any object is present on the conveyor, as a result of the reflected secondary light, and then determines whether that object is bright white paper depending upon the measured level of emitted fluorescent light energy. Based upon these determinations, the stream of waste paper on the conveyor can be sorted into two fractions, one of which is the bright white paper.] *A method of sorting waste paper includes spreading waste paper out into a layer that is substantially one unit thick; detecting the presence or absence of a predetermined optical characteristic as the layer of paper is passed by a sensor; and controlling one or more actuators that direct a sheet of paper based on the presence or absence of the predetermined optical characteristic.*

30 Claims, 8 Drawing Sheets



US RE42,090 E

Page 2

U.S. PATENT DOCUMENTS

1,547,743 A	7/1925	Fowler	5,209,355 A	5/1993	Mindermann	209/3.1
1,847,263 A	3/1932	Sandberg	5,242,059 A	9/1993	Low et al.	
1,847,265 A	3/1932	Sandberg	5,257,577 A	11/1993	Clark	100/99
2,897,952 A	8/1959	Buccicone	5,260,576 A	11/1993	Sommer, Jr. et al.	
3,101,832 A	8/1963	Wyle et al.	5,297,667 A	3/1994	Hoffman et al.	198/492
3,185,286 A	5/1965	Koplin	5,299,693 A	4/1994	Ubaldi et al.	209/3.3
3,198,352 A	8/1965	Puechberty	5,301,816 A	4/1994	Weber et al.	209/616
3,227,263 A	1/1966	Kastenbein	5,314,072 A	5/1994	Frankel et al.	209/44.1
3,352,404 A	11/1967	Settembrini	5,315,384 A	5/1994	Heffington et al.	
3,471,013 A	10/1969	Haver	5,318,172 A	6/1994	Kenny et al.	209/524
3,606,645 A	9/1971	Hardy	5,318,173 A	6/1994	Datari	
3,650,369 A	3/1972	Vergobbi	5,322,152 A	6/1994	Tommila et al.	194/212
3,747,755 A	7/1973	Senturia et al.	5,333,739 A	8/1994	Stelte	
3,800,936 A	4/1974	Anfossi	5,333,797 A	8/1994	Becker et al.	241/19
3,908,814 A	9/1975	Hieronimus	5,335,791 A	8/1994	Eason	
4,069,145 A	1/1978	Sommer, Jr. et al.	5,339,962 A	8/1994	Sommer, Jr. et al.	209/576
4,093,062 A	6/1978	Sjögren	5,339,963 A	8/1994	Tao	
4,094,772 A	6/1978	Hillekamp et al.	5,344,026 A	9/1994	Booth et al.	
4,102,056 A	7/1978	Angelo et al.	5,348,136 A	9/1994	Kenny et al.	198/443
4,124,168 A	11/1978	Bialski et al.	5,348,162 A	9/1994	Wroblewski	209/35
4,131,540 A	12/1978	Husome et al.	5,361,913 A	11/1994	Melchionna	209/583
4,176,750 A	12/1979	Holmes	5,398,818 A	3/1995	McGarvey	
4,207,177 A	6/1980	Block	5,402,264 A	3/1995	Wilbur et al.	
4,225,427 A	9/1980	Schnell	5,419,438 A	5/1995	Squyres et al.	
4,231,526 A	11/1980	Ortner et al.	5,419,498 A	5/1995	Rasmussen et al.	241/280
4,352,430 A	10/1982	Maier et al.	5,423,431 A	6/1995	Westin	
4,440,284 A	4/1984	DeWolfson	5,440,127 A	8/1995	Squyres	
4,505,371 A	3/1985	Krueger et al.	5,443,164 A	8/1995	Walsh et al.	
4,533,053 A	8/1985	Kenny et al.	5,460,271 A	10/1995	Kenny et al.	209/576
4,533,054 A	8/1985	Sommer, Jr. et al.	5,464,981 A	11/1995	Squyres et al.	
4,541,530 A	9/1985	Kenny et al.	5,469,973 A	11/1995	Booth et al.	
4,542,689 A	9/1985	Trolle	5,481,864 A	1/1996	Wright	
4,609,108 A	9/1986	Hristozov et al.	5,497,871 A	3/1996	Ciolkevich	198/443
4,632,320 A	12/1986	Holz et al.	5,501,344 A	3/1996	Kaiser et al.	
4,657,144 A	4/1987	Martin et al.	5,512,758 A	4/1996	Kobayashi et al.	250/461.1
4,686,371 A	8/1987	Birch et al.	5,520,290 A	5/1996	Kumar et al.	
4,699,510 A	10/1987	Alguard	5,531,331 A	7/1996	Barnett	
4,718,558 A	1/1988	Castaneda	5,533,628 A	7/1996	Tao	
4,718,559 A	1/1988	Kenny et al.	5,555,984 A	9/1996	Sommer, Jr. et al.	
4,741,042 A	4/1988	Throop et al.	5,581,353 A	12/1996	Taylor	
4,760,925 A	8/1988	Stehle et al.	5,615,778 A	4/1997	Kaiser et al.	
4,830,501 A	5/1989	Terashita	5,632,381 A	5/1997	Thust et al.	
4,844,351 A	7/1989	Holloway	5,675,416 A	10/1997	Campbell et al.	
4,909,930 A	3/1990	Cole	5,676,256 A	10/1997	Kumar et al.	
4,919,534 A	4/1990	Reed	5,689,757 A	11/1997	Ferrante et al.	
4,929,342 A	5/1990	Johnston	5,695,035 A	12/1997	Fukushima et al.	
4,945,253 A	7/1990	Frohardt	5,703,784 A	12/1997	Pearson	364/478.11
5,022,644 A	6/1991	Burge	5,770,864 A	6/1998	Dlugos	
5,024,335 A	6/1991	Lundell	5,789,741 A	8/1998	Kinter et al.	
5,048,674 A	9/1991	Wilbur et al.	5,794,788 A	8/1998	Massen	
5,060,870 A	10/1991	Trezek et al.	5,797,327 A	8/1998	Gieser et al.	
5,085,325 A	2/1992	Jones et al.	5,799,105 A	8/1998	Tao	
5,091,077 A	2/1992	Williams	5,799,801 A	9/1998	Clark et al.	209/667
5,092,526 A	3/1992	Takata	5,813,542 A	9/1998	Cohn	
5,100,005 A	3/1992	Noble et al.	5,813,543 A	9/1998	Gesing et al.	
5,100,537 A	3/1992	Krause	5,848,706 A	12/1998	Harris	
5,101,977 A	4/1992	Roman	5,861,919 A	1/1999	Perkins et al.	
5,111,927 A	5/1992	Schulze, Jr.	5,862,919 A	1/1999	Eason	
5,115,144 A	5/1992	Konishi et al.	5,884,775 A	3/1999	Campbell	
5,115,987 A	5/1992	Mithal	5,900,943 A	5/1999	Owen	356/406
5,134,291 A	7/1992	Ruhl, Jr. et al.	5,901,856 A	5/1999	Brantley, Jr. et al.	209/672
5,139,339 A	8/1992	Courtney et al.	5,917,585 A	6/1999	Roe et al.	356/73
5,143,308 A	9/1992	Hally et al.	5,954,206 A	9/1999	Mallon et al.	
5,150,307 A	9/1992	McCourt et al.	5,955,741 A	9/1999	Kayani	
5,165,676 A	11/1992	Blessing et al.	5,960,964 A	10/1999	Austin et al.	209/672
5,169,588 A	12/1992	Estep	5,966,217 A	10/1999	Roe et al.	
5,183,251 A	2/1993	Sardella	5,979,240 A	11/1999	Rix et al.	
5,190,165 A	3/1993	Garfield, Jr.	6,022,017 A	2/2000	Cummings et al.	
5,197,678 A	3/1993	Trezek et al.	6,060,677 A	5/2000	Ulrichsen et al.	
5,201,921 A	4/1993	Luttermann et al.	6,064,056 A	5/2000	Doak	250/223
			6,068,106 A	5/2000	Brizzi et al.	

US RE42,090 E

Page 3

6,076,684	A	6/2000	Bollegraaf	209/668
6,137,074	A	10/2000	Doak	209/581
6,263,291	B1	7/2001	Shakespeare et al.	702/85
6,303,925	B1 *	10/2001	Edmonds	250/223 R
6,335,501	B1	1/2002	Khalfan	209/582
6,353,197	B1	3/2002	Ulrichsen et al.	
6,369,882	B1	4/2002	Bruner et al.	356/73
6,373,575	B1	4/2002	Takayama et al.	356/445
6,509,537	B1	1/2003	Krieg et al.	
6,778,276	B2	8/2004	Bruner et al.	
7,262,380	B1	8/2007	Ulrichsen et al.	
2002/0017445	A1	2/2002	Mukai	

FOREIGN PATENT DOCUMENTS

CA	2235665	10/1998
DE	3615644A 1	11/1987
DE	3828067 A1	3/1990
DE	3926641 A1	2/1991
DE	3926641	2/1991
DE	4125045 A1	2/1993
DE	4135394 A1	4/1993
DE	4305006 A1	9/1993
DE	44 17 357 A1	11/1995
DE	PCT/DE95/00966	11/1995
DE	4241990 C2	2/1997
EP	291 959 A2	11/1988
EP	0484221 A2	5/1992
EP	0873797 A2 *	10/1998
EP	873797	10/1998
JP	9314070 A	12/1997
JP	11-084745	3/1999
RU	1411228	7/1988

SU	1050992	10/1983
WO	WO 96/06690	3/1996

OTHER PUBLICATIONS

Exhibit B: U.S. Appl. No. 11/325,835, filed Jan. 5, 2006 (now U.S. Patent No. 7,173,709) and its file history.

Exhibit C: U.S. Appl. No. 11/514,449, filed Sep. 1, 2006 (now U.S. Patent No. 7,499,172) and its file history.

Exhibit D: U.S. Appl. No. 12/252,909, filed Oct. 16, 2008 (still pending) and its file history.

U.S. Appl. No. 09/301,715, filed Apr. 29, 1999, and issued as U.S. Patent No. 6,369,882 on Apr. 9, 2002.

U.S. Appl. No. 10/428,311, filed May 2, 2003, and issued as U.S. Patent No. 6,778,276 on Aug. 17, 2004.

PCT Patent Application No. US/00/11761, filed Apr. 28, 2000.

Catalog of Magnetic Separation Systems, Inc. entitled "Systems for Separation and Sensing"(undated).

Brochure entitled "MSS Pen Binary Bottlesort®" (Undated).

Brochure entitled "MSS Plasticsort™" (Undated).

Brochure entitled "Machinefabriek Lubo® Mobile Systems" (Undated) discloses a screening unit having rotating disc on parallel shafts.

Brochure entitled "Machinefabriek Lubo® Projects" (Undated) discloses a screening unit having rotating disc on parallel shafts.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5a




FIG. 5b




FIG. 5c




FIG. 6a




FIG. 6b




FIG. 6c




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

METHOD OF SORTING WASTE PAPER

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

This application is a continuation of our pending application Ser. No. 09/301,715 filed Apr. 29, 1999, now U.S. Pat. No. 6,369,882 B1.

Be it known that I, Russell S. Bruner, a citizen of the United States residing at 726 Poplar Avenue, Mt. Juliet, Tenn. 37122 and I, David R. Morgan, a citizen of the United States residing at 9921 U.S. Highway 68 East, Benton, Ky. 42025, and I, Garry R. Kenny, a citizen of the United States residing at 6299 McDaniel Rd., College Grove, Tenn. 37046, and I, Paul G. Gaddis, a citizen of the United States residing at 2000 Alaska Way #156, Seattle, Wash. 98121, and I, David Lee, a citizen of the United States residing at 3614 North 30th Street, Tacoma, Wash. 98407, and I, James M. Roggow, a citizen of the United States residing at 14526 26th Avenue, Court East, Puyallup, Wash. 98374, have invented a new and useful **["System and Method For Sensing White Paper."]** *"Method of Sorting Waste Paper."*

BACKGROUND OF THE INVENTION

The present invention relates to a system and method for sorting mass recyclables and more particularly to a system for sensing and sorting white paper from other objects.

It will be appreciated by those skilled in the art that society desires to recycle as much of its waste materials as possible. For example, aluminum cans, plastic bottles, and other items have been the source of mixed recyclable efforts in the past. The assignee of the present application, Magnetic Separation Systems, Inc. (MSS) is a world leader in mixed recyclables. MSS is also the owner of many patents disclosing technologies for sorting and concentrating aluminum and sorting plastics.

One other type of mixed recyclable is paper. In the past, recyclable efforts have been dominated by hand sorting of paper by type. One common effort is curbside recycling. Other efforts have been to sort paper from other types of materials. Unfortunately, as with any other procedure, any type of hand sorting requires an intensive use of labor that is not always efficient.

What is needed, then, is a method and system that can sort white paper from a stream of other paper. This needed system must also be capable of sorting a stream of material from white paper in case the stream is dominated by materials other than white paper. The system must decrease the amount of labor presently being used. The system must be economical. The system must be effective. The system is presently lacking in prior art.

SUMMARY OF THE INVENTION

The present invention discloses a method of sorting waste paper, comprising spreading waste paper out into a layer that is substantially one unit thick; detecting the presence or absence of a predetermined optical characteristic as the layer of paper is passed by a sensor; and controlling one or more actuators that direct a sheet of paper based on the presence or absence of the predetermined optical characteristic.

The present invention discloses a system and method for sorting white paper, and especially a type of white paper commonly referred to as bright white paper, from other objects. One reason that recycling of bright white paper is

very desirable is that the fluorescent chemicals added to such papers are expensive plus the bright white paper tends to be a very high quality paper fiber. Thus, this is a premium paper fraction for recycling. The system may also sort other objects from white paper.

The present invention uses an energy source that is preferably an ultraviolet light that is concentrated in some manner onto an object. The energy is focused on the paper. If the paper is bright white paper, the ultraviolet radiation will cause the brightening agents in the white paper to fluoresce into an energy having a different and longer wavelength. The fluorescence is then measured.

The system and method of the present invention is particularly adapted for use in sensing the presence of bright white paper that flows past the sensor on a conveyor. The conveyor is constantly illuminated with the ultraviolet light. Also, a second light source is provided which periodically illuminates an inspection zone of the conveyor with a second light which is in the visible light spectrum, and preferably in the blue-green portion of the visible light spectrum.

A sensor located above the inspection zone of the conveyor collects light from the inspection zone of the conveyor. The collected light includes both emitted fluorescence from bright white paper located in the inspection zone and reflected light from the second light source reflected off of objects in the inspection zone.

Periodically, the sensing system senses first and second parameters of the light collected from the inspection zone. The first parameter is the level of reflection of the second light source in order to determine whether any object is present on the conveyor in the inspection zone. The second parameter sensed is the level of fluorescent light to determine whether an object present in the inspection zone is bright white paper.

Thus, if the sensed level of the reflected light from the second light source is below a certain threshold, the system will determine that no object is present in the inspection zone on the conveyor. If the sensed level of reflected light from the second light source is above a threshold level, the system will sense that some object is present in the inspection zone on the conveyor, but the identification of that object will depend upon the sensed level of fluorescent energy coming from that object. If the sensed level of fluorescent energy from the object is below a threshold level, the system will determine that the object is something other than bright white paper. If the sensed level of fluorescent energy is above a predetermined threshold, the system will determine that the sensed object is bright white paper.

The system may then send control signals to an ejection means which will eject either the bright white paper fraction or the non-bright white paper fraction from the paper stream flowing across the conveyor.

Accordingly one object of the present invention is to provide a system and method for sensing and sorting bright white paper from other objects.

Another object of the present invention is to provide a system that allows someone to sort bright white paper from other objects that is not labor intensive.

Another object of the present invention is to provide a system that can sort both bright white paper from other objects and other objects from bright white paper.

Still a further object of the present invention is to provide an accurate system for sensing bright white paper.

And another object of the present invention is to provide improved methods of sorting waste paper.

Other and further objects features and advantages of the present invention will be readily apparent to those skilled in the art upon a reading of the following disclosure when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of the system and method of the present invention.

FIG. 2 is an optical diagram of the system and method of the present invention.

FIG. 3 is a block diagram of the secondary light source of the present invention.

FIG. 4 is an elevation view of one half of the reflector of the present invention as viewed from the side of the conveyor.

FIG. 5a is a plan view of a lens of a sensor element.

FIG. 5b is an elevation view of the lens of FIG. 5a.

FIG. 5c is a schematic elevation partly sectioned view of a sensing element showing the lens in place within a collimator tube which, in turn, is in place within a lens housing.

FIG. 6a is a bottom view of a sensor housing, showing the layout of an array of lens cavities and cavities for receiving the second light sources.

FIG. 6b is an elevation sectioned view of the sensor housing, taken along line 6b—6b of FIG. 6a. FIG. 6b shows the cavity in which the lens is received.

FIG. 6c is another elevation sectioned view through the sensor housing, taken along line 6c—6c of FIG. 6a. FIG. 6c illustrates cavities in which the second light source elements are placed.

FIG. 7 is an elevation view of the sensor of the present invention as viewed from the side of the conveyor.

FIG. 8 is a schematic plan view of the conveyor showing the inspection zone.

FIG. 9 is a schematic side elevation view of the sensor in place above a conveyor, and also shows an associated ejection system for ejecting a fraction of the flowing paper stream in response to signals from the sensor.

FIG. 10 is a graph illustrating the wavelength of the ultraviolet energy source and of the emitted fluorescent energy from bright white paper. Also shown is a high frequency cut-off of a filter.

FIG. 11 is a block diagram of the electrical control system.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now the drawings, and particularly to FIG. 1, the system of the present invention is shown and generally designated by the numeral 10. The system 10 includes a first light source 12 which preferably is an ultraviolet light source 12. Ultraviolet light energy emitted from source 12 travels along paths 13 to a concentrator means 14 which then directs the light along paths 15 so as to focus the ultraviolet light energy on an inspection zone or focal zone 19 on a conveyor 100 located below the apparatus 10. A portion of any light energy reflected from or emitted from any objects within the inspection zone 19 will travel upward as indicated by path 17 to a sensor 16. If an object such as 102 is located in the inspection zone 19, the light reflected from and/or emitted from the object 102 in inspection zone 109 and received by sensor 16 can be examined to determine the nature of the object 102, and particularly to determine whether the object 102 is bright white paper. Other objects 101, 104 and 106 are also schematically illustrated in place upon the conveyor belt 100.

The system 10 is particularly designed to determine whether an object in the inspection zone 19 is bright white paper. Bright white paper is a common name for a type of high quality paper commonly used in offices for printers and copiers. Bright white paper is typically a high quality paper fiber which has been treated with brighteners which cause the paper to fluoresce in the presence of ultraviolet light. When ultraviolet light energy falls upon bright white paper, the brighteners in the object will fluoresce and will emit light energy having a wavelength in the range of from about 400 to about 550 nanometers, which is in the visible light spectrum. The fluorescent energy emitted from bright white paper when an ultraviolet light is shown on it is great when compared to the amount of fluorescent energy that will be emitted from objects other than bright white paper.

FIG. 3 schematically illustrates a second feature of the system 10 which includes a second light source 20. As will be further described below, the second light source 20 is contained within a common housing with the sensor 16. The second light source 20 is preferably a source of visible light energy. One preferred second light source 20 is a blue light emitting diode which emits light energy having a wavelength of approximately 480 nanometers. Light from the second light source 20 travels downward along path 21 and is reflected off an object such as object 102 located within the inspection zone 19. The reflected light energy travels back upward along path 23 where it is also received by the sensor 16.

As will be further described below, the general purpose of the second light source 20 is to provide a means for detecting whether any object is present on the conveyor belt 100 within the inspection zone 19. The sensor 16 and its associated control apparatus will be calibrated so that when the reflected light 23 exceeds a certain threshold, it will provide a determination that some object other than the black conveyor belt 100 is located within the inspection zone 19. A second determination will then be made as to the level of fluorescent energy traveling upward along path 17 to the sensor 16. If an object is present in the inspection zone 19, but the level of fluorescent energy is below a predetermined threshold, the system 10 will determine that the object is not the desired bright white paper. On the other hand, if an object is determined to be present, and the amount of fluorescent energy 17 emitted by that object is above the predetermined threshold, the system 10 will determine that the object is bright white paper.

FIG. 10 is a graphical illustration of the electromagnetic radiation energy which might be picked up by sensor 16. The horizontal axis represents the wavelength of the electromagnetic radiation, and the vertical axis represents the relative intensity of radiation.

There is a peak at approximately 360 nanometers in FIG. 10 which represents the frequency of the ultraviolet light energy radiating from source 12. To the extent that ultraviolet energy is merely reflected off of the focal zone 19 and received by sensor 16, it would create a spike as shown in FIG. 10.

As previously noted, when ultraviolet light energy falls upon a piece of bright white paper containing fluorescing additives, the additives fluoresce, thus converting some of the ultraviolet light energy into visible light energy having a longer wavelength (and thus lower frequency). In FIG. 10, a hump in the detected energy generally designated at 118 is representative of the fluorescent energy emitted from a piece of bright white paper. As is apparent in FIG. 10, the hump 118 begins at a wavelength of approximately 400

5

nanometers, peaks at about 440 nanometers, then drops off and is essentially absent at about 550 nanometers wavelength.

In order to isolate the fluorescent energy emitted from bright white paper, the sensor **16** preferably has a filtering means associated therewith. Preferably the filtering means is a band pass filter which will allow light energy only within the range of from 400 to 500 nanometers length to pass therethrough. The details of construction of this filtering means are further described below. In FIG. **10**, the high frequency, and thus short wavelength, cut off of the filter is indicated by the curve **120**. Since this high frequency cut off is at a lower frequency than the ultraviolet light source, reflected ultraviolet light energy will not be sensed by sensor **16**.

The secondary light source **20** previously described operates at a wavelength of 480 nanometers, so that when the secondary light source reflects off of an object within the inspection zone **19** that reflected light **23** can pass through the filter means.

FIG. **7** is an elevation sectioned view of the sensing system **10** in place over the conveyor **100**.

The first light source **12** is a light module **46** which includes four parallel elongated tubular ultraviolet light bulbs **48** which are seen in cross-section in FIG. **7**. The light bulbs **48** extend transversally across the width of the conveyor **100** perpendicular to the direction of paper flow indicated by the arrow **110**. The bulbs **48** are contained within a housing **52**. Electronic starters **50** are associated with the bulbs **48** and cause the same to turn on and off when electrical power is directed thereto in a well known manner. A glass panel **54** covers the lower side of module **46**.

Thus, most of the ultraviolet light energy from bulbs **48** is emitted laterally as along the paths **13** previously noted, where it falls upon the concentrators **14**. The concentrators **14** are preferably curved reflectors formed in the shape of an arc of an ellipse so that all light falling thereon will be reflected toward a focal point **58** lying in the center of the inspection zone **19** on the conveyor **100**. The ultraviolet light energy reflected from concentrators **14** follows paths generally designated as **15** to the focal point **58**.

The geometric layout of the concentrator **14** is best illustrated in the schematic representation shown in FIG. **2**. As indicated in FIG. **2**, the light source **12** has a central point **112** which is generally coincident with the upper focal point **114** of an ellipse **114** upon which the reflecting walls of concentrator **14** lie. The lower focal point **58** of the ellipse **114** falls upon the conveyor **100** in the center of the inspection zone **19**.

Referring now to FIGS. **4** and **7**, the concentrator **14** is constructed from first and second reflecting walls **24** and **25** which are supported within a housing **60** of the apparatus **10** by a plurality of brackets such as **26** and **27**. The reflector walls **24** and **25** are preferably polished stainless steel. The brackets such as bracket **26** shown in FIG. **4** may also be manufactured from stainless steel.

The lower end of the housing **60** of apparatus **10** is closed by a transparent glass shield **116** which allows the light energy to pass therethrough while preventing dirt, paper and debris from entering the apparatus **10**.

The reflecting walls **24** and **25** may be generally described as an elliptical reflecting lens having focal point **58** within the inspection zone **19**.

Referring now to FIGS. **6a**, **6b** and **6c**, a sensor housing or lens housing is shown and generally designated by the

6

numeral **124**. The sensor housing **124** is an elongated housing which lies across the width of the conveyor **100** and can be described as being transverse to and is perpendicular to the direction of travel **110** along the conveyor belt **100**.

The sensor housing **124** has a plurality of lens cavities **42** and a plurality of secondary light source cavities **126** defined therein. An array of sensor elements are carried by housing **124**.

FIG. **6b** is a sectioned view taken along lines **6b—6b** of FIG. **6a**, showing the details of construction of one of the lens cavities **42**.

FIG. **6c** is a sectioned view taken along lines **6c—6c** of FIG. **6a**, showing the details of construction of two secondary light source cavities **126**.

The sensor housing is held in place by a bracket **56** as shown in FIG. **7**.

Turning now to FIGS. **5a—5c**, the details of construction of one of the sensing elements of sensor **16** will be described.

FIG. **5c** is a schematic elevation cross-section view similar to FIG. **6b** and schematically illustrating the components of one sensing element **128** of sensor **16**. Each sensing element such as **128** is associated with one of the lens cavities **42**.

A collimator tube **40** is received in each lens cavity **42** and held in place therein by set screws received through threaded holes **130** (See FIG. **6b**). In one preferred embodiment each collimator tube is approximately 4" long, 1" outside diameter and $\frac{3}{4}$ " inside diameter. The collimator tube **40** may be an aluminum tube having a matte black finish. The collimator tube **40** ensures that the light being collected by the sensing element **128** is substantially only light traveling directly upward from an object immediately below sensing element **128** in the focal zone **19**.

Located at the upper end of each collimator tube **40** is a semi-spherical lens **32**. Plan and side elevation views of one lens **32** are shown in FIGS. **5a** and **5b**, respectively.

Located immediately above the lens **32** is the filtering means **122** which includes first and second optical filter plates **34** and **36**. The first optical filter plate is a high frequency pass filter **34**, and the second optical filter plate **36** is a low frequency pass plate **36**. As will be understood by those skilled in the art, the filter plates **34** and **36** can be selected to determine the frequencies of light energy which really will not pass therethrough. Filter plates **34** and **36** are standard optical filters which are available from Edmund Scientific.

The light energy which passes through the lens **32** is focused within a cone having outer boundaries along the dashed arrows **132** and **134** which focuses that energy upon a photo electric detector **38**. The photo electric detector **38** is a silicone photo diode.

Thus, the band pass filter means **122** will pass fluorescent energy having a wavelength longer than a lower limit of about 400 nanometers, which lower limit is longer than the wavelength of the ultraviolet light from source **12**. The filtering means **122** will further block fluorescent energy having a wavelength longer than an upper limit, which in the illustrated embodiment is preferably about 500 nanometers. The range of light energy having wavelength from 400 to 500 nanometers can be described as being in the blue-green portion of the visible light spectrum.

As previously noted, the light emitted from second light source **20** has a wavelength of approximately 480 nanometers, which will be passed by the filtering means **122** when said light is reflected from an object in the inspection zone **19**.

Referring now to FIG. 9, a general layout of the system 10 and associated conveyor apparatus is shown, whereby the sensor system 10 may be utilized to detect bright white paper on the conveyor 100 and to send control signals to an ejector mechanism 70 which uses air jets 80 to eject paper from the conveyor 100.

The conveyor 100, ejector system 70 and associated apparatus are shown in detail in an application of Michael R. Grubbs et al, entitled PAPER SORTING SYSTEM, U.S. patent application Ser. No. 09/301,992, filed Apr. 29, 1999, now U.S. Pat. No. 6,250,472 issued Jun. 26, 2001, and assigned to the assignee of the present invention. The details of construction of the system shown in the Grubbs et al. patent are incorporated herein by reference as if the same were fully set forth herein.

FIG. 8 is a schematic plan view of the conveyor 100 illustrating an elongated strip shaped inspection zone 19 lying across a width 142 of the conveyor belt 100. The focal point 58 previously described with regard to the side elevation view of the ellipse is in fact a focal line 58 which defines the center line of the inspection zone 19.

In the system shown in FIG. 9 the first conveyor 100 conveys the paper objects 102 from right to left so that they pass under the sensor 16. The conveyor 100 is traveling at a very great rate of speed (as much as 1200 ft/min), and as the objects reach the left hand end of conveyor 100 they are launched off of the conveyor 100 and fly through the air across an ejection gap 136 toward a product conveyor 138.

Signals from the photo electric detector 38 are converted into digital signals which are directed to a microprocessor 140 which performs the measuring, sensing, comparing and evaluating functions. The microprocessor 140 will go through the evaluation steps described below, and at appropriate times will send a control signal to the ejector system 70 to direct compressed air to jet 80 so that the air jet 80 will be directed against an object which at that time is passing across the ejection gap 136. Any object impacted by an air jet as it crosses the gap 136 will be blown downward between the two conveyors 100 and 138 and will be part of an ejected paper stream fraction. Non-ejected paper will flow across the gap 136 and fall onto the conveyor 138 which will take it to another location.

FIG. 11 is a schematic block diagram of the control system of the apparatus 10.

The microprocessor 140 may be a XYCOM model PCD1048 microprocessor available from XYCOM Automation, Inc. The microprocessor 140 preferably has touch screen operated control station 144 which allows system variables to be changed and the sort selection to be changed. The system provides the ability to perform a positive sort where non-bright white paper is ejected or a reverse sort where the bright white paper is ejected when the concentration of the targeted paper is less than that of the non-targeted paper.

The microprocessor 140 is connected by interface 146 to power supply ballasts 148 and then to the ultraviolet light source 12.

The microprocessor 140 is connected by a ribbon cable 150 to a rear receiver board 152 which is in turn connected by a ribbon cable 154 to the sensor unit 16 and the secondary light sources 20 contained in the sensor housing.

A power supply 156 is connected to the rear receiver board 152.

An LED power supply 158 is connected to the secondary light source 20.

The rear receiver board 152 includes amplifiers and analog to digital converters. Signals from the sensor 16 are communicated over cable 154 to the rear receiver board 152 where they are amplified and digitized before being passed over cable 150 to the microprocessor 140.

The microprocessor 140 also communicates over cable 160 to the ejector control system 70 which includes a plurality of solenoid driver boards 162 and an array of solenoid valves 164 which control the flow of air to the air jets 80. A solenoid power supply 166 is connected to the driver boards 162.

Methods of Operation

The methods of operation of the present invention will now be described with reference to FIGS. 7 and 9.

The system 10 provides an apparatus and method for sensing the presence of bright white paper on the conveyor 100 of the paper sorting system like that described in the Grubbs et al. application which has been incorporated herein by reference.

The conveyor 100 is directing a stream of waste paper from right to left as seen in FIG. 8 at a very high speed below the sensor 16.

The ultraviolet light source 12 is constantly on and constantly illuminates the inspection zone 19 on the conveyor belt 100 immediately below the sensor 16. As previously described, that ultraviolet light energy is focused on the inspection zone 19 by means of the elliptical shaped walls 24 and 25.

When a piece of paper such as 102 passes through the inspection zone 19, if the paper 102 is bright white paper, it will fluoresce and will re-radiate fluorescent light energy from the bright white paper. As previously described with reference to FIG. 1, a portion of that fluorescent energy will travel directly upward along the path 17 to the sensor 16.

Throughout this process, the inspection zone 19 will also be periodically illuminated with light from the second light source 20, which as previously noted is preferably a blue light emitting diode. In a preferred embodiment, the secondary light source 20 illuminates the inspection zone 19 every 3 milliseconds.

Light from the inspection zone 19, including both reflected light and emitted fluorescent light, is collected by the collimator tube 40 and passes through the lens 32 and the filtering means 122 to the photo electric detector 38. The photo electric detector 38 will convert the light energy into an electrical signal, which, in turn, is converted into a digital electric signal which is directed to the microprocessor 140.

A first measuring step or sensing step is performed by microprocessor 12 when the secondary light source 20 is on. This first sensed parameter will thus indicate the level of reflected light from secondary source 20, and if that level of reflected secondary light exceeds a predetermined threshold, the microprocessor 140 will determine that some object is present in the inspection zone 19 on the conveyor 100. Then, when the secondary light source 20 is off, the microprocessor 140 will perform a second measuring or sensing step while only the ultraviolet light illuminates the inspection zone 19. In this second step, the sensed light energy will be compared to the predetermined threshold for fluorescent energy, and if that threshold is exceeded, the microprocessor 140 will determine that an object present in the inspection zone 19 is bright white paper.

The microprocessor 140 can be described as periodically sensing first and second parameters of the light collected by

the sensing element. The first parameter is the level of reflection from the inspection zone **19** of light originating with the secondary light source **20**. If this first parameter exceeds a certain threshold, an indication is generated indicating that some object is present in the inspection zone **19** other than the conveyor belt **100** itself.

The second parameter sensed by the microprocessor **14** is the level of fluorescent light energy which has been radiated from an object within the inspection zone **19**. If this level of fluorescent light energy exceeds a predetermined threshold, this will generate an indication that an object which is present in the inspection zone **19** is, in fact, bright white paper.

If the first parameter indicates that an object is present, but the second parameter indicates that the object is not bright white paper, then it is known that the object is one which should be separated from the bright white paper.

Depending upon the signals generated by the microprocessor **140**, a control signal is then sent to the ejection system **70** to direct compressed air to air jets **80** to eject a selected fraction of the stream of paper which is moving along the conveyor **100**. It will be appreciated that the microprocessor **140** can be programmed to either eject the bright white paper or to eject the non-bright white paper. Preferably, whichever type of paper comprises the smaller portion of the stream of paper flowing across conveyor **100** will be ejected, whereas the major portion will be allowed to flow across to the product conveyor **138**.

The periodic illumination by secondary source **100** is preferably performed approximately every 3 milliseconds. In general, it may be described as being performed in excess of 100 times per second. Preferably the microprocessor **140** periodically senses the light being collected from the inspection zone **19** at the same periodic rate at which the secondary light source **20** is illuminating the inspection zone **19**.

The paper objects will be traveling on the conveyor **100** at a speed of approximately 1200 feet per minute or 20 feet per second, thus by strobing every 3 milliseconds, a piece of letter size paper, 8½" wide would be strobed at least 10 times as it passed under the sensor **16**.

The sensor **16** and associated microprocessor **140** can be described as an evaluating means for evaluating the level of fluorescent energy detected by each of the sensing elements to determine whether bright white paper is located below each sensing element.

As previously noted, there is preferably a linear array of sensing elements arranged across the width of the conveyor belt. For example, for a 48" wide conveyor, there may be 32 sensor elements. Signals from each of the sensing elements are separately analyzed, and control signals are separately sent to an array of 32 air jets **80**, so that there is an ejection air jet **80** associated with each of the sensing elements. Thus, a paper object may be located toward one edge of the conveyor belt and its location will be determined by the identification of the sensing elements which sense the presence of that object therebelow. Then the associated air jets can be activated at the proper time to blow the sensed object through the ejection gap **136** if desired.

Thus, it is seen that the apparatus and methods of the present invention readily achieve the ends and advantages mentioned, as well as those inherent therein. While certain preferred embodiments of the invention have been illustrated and described for purposes of the present disclosure, numerous changes in the arrangement and construction of parts and steps may be made by those skilled in the art, which changes are encompassed within the scope and spirit of the present invention as defined by the appended claims.

What is claimed is:

1. A method of sorting waste paper, comprising:
 - spreading waste paper out into a layer that is substantially one unit thick;
 - detecting the presence or absence of a predetermined optical characteristic as the layer of paper is passed by a sensor; and
 - controlling one or more actuators that direct a sheet of paper based on the presence or absence of the predetermined optical characteristic.
2. The method of claim 1, wherein the predetermined optical characteristic is fluorescence caused by optical brighteners in the paper, and wherein the presence or absence of the fluorescence is detected by:
 - applying ultraviolet light on a sheet of waste paper;
 - detecting light received from the paper in response to the ultraviolet light applied; and
 - comparing the level of light received from the paper with a threshold to detect the presence or absence of optical brighteners in the paper.
3. *The method of claim 1, wherein:*
 - said spreading step includes carrying said layer on a conveyor having a width; and*
 - in said detecting step, said sensor includes an array of sensor elements spaced across the width of the conveyor.*
4. *The method of claim 3, wherein:*
 - in said controlling step, said one or more actuators include one or more air jets.*
5. *The method of claim 4, wherein:*
 - in said controlling step, said one or more air jets include an array of air jets spaced across the width of the conveyor, and said controlling step includes actuating an appropriate number of said air jets at an appropriate time to direct the sheet of paper.*
6. *The method of claim 5, wherein:*
 - in said controlling step, each one of said air jets is associated with one of said sensing elements.*
7. *The method of claim 1, wherein:*
 - in said controlling step, each of said actuators includes an air jet.*
8. *The method of claim 7, wherein:*
 - said spreading step includes spreading said layer on a conveyor having a width; and*
 - in said controlling step, said air jets comprise an array of air jets spaced across the width of the conveyor.*
9. *The method of claim 7, wherein:*
 - said detecting step includes communicating sensor signals from the sensor to a microprocessor; and*
 - said controlling step comprises communicating control signals from the microprocessor to an array of solenoid valves associated with the air jets and thereby controlling a flow of air to the air jets.*
10. *The method of claim 1, further comprising:*
 - conveying the layer of waste paper on a first conveyor and launching the layer of waste paper off the first conveyor across a gap to a second conveyor; and*
 - wherein said controlling step includes controlling said one or more actuators to deflect a portion of the paper away from said second conveyor in an ejected paper stream.*
11. *The method of claim 1, being further characterized as a method of sorting waste paper objects, wherein:*
 - in said spreading step said one unit thick layer is substantially one paper object thick;*

11

in said detecting step said layer of paper is a layer of paper objects; and

in said controlling step said sheet of paper is a paper object.

12. The method of claim 1, wherein:

the waste paper is provided in a stream including white paper and materials other than white paper; and

the controlling step includes controlling one or more actuators that direct the materials other than white paper out of the stream.

13. The method of claim 12, wherein:

said spreading step includes carrying the stream on a conveyor having a width; and

in the controlling step, said one or more actuators include an array of air jets spaced across the width of the conveyor, and said controlling step includes actuating an appropriate number of said air jets at an appropriate time to direct the materials other than white paper out of the stream.

14. The method of claim 1, wherein:

the waste paper is provided in a stream including white paper and materials other than white paper, wherein the stream is dominated by the materials other than white paper; and

the controlling step includes controlling one or more actuators that direct the white paper out of the stream.

15. The method of claim 14, wherein:

said spreading step includes carrying the stream on a conveyor having a width; and

in the controlling step, said one or more actuators include an array of air jets spaced across the width of the conveyor, and said controlling step includes actuating an appropriate number of said air jets at an appropriate time to direct the white paper out of the stream.

16. A method of sorting waste paper, comprising:

spreading waste paper out into a layer that is substantially one unit thick;

detecting the presence or absence of a predetermined optical characteristic as the layer of paper is passed by a sensor; and

controlling one or more actuators that direct a paper object based on the presence or absence of the predetermined optical characteristic.

17. A method of sorting waste paper objects, comprising: spreading waste paper objects out into a layer that is substantially one waste paper object thick;

detecting the presence or absence of a predetermined optical characteristic as the layer of waste paper objects is passed by a sensor; and

controlling one or more actuators that direct the waste paper object based on the presence or absence of the predetermined optical characteristic.

18. The method of claim 17, further comprising:

providing the waste paper objects in a stream including white paper and materials other than white paper; and

wherein the controlling step includes controlling one or more actuators that direct the materials other than white paper out of the stream.

19. The method of claim 18, wherein:

said spreading step includes carrying the stream on a conveyor having a width; and

in the controlling step, said one or more actuators include an array of air jets spaced across the width of the conveyor, and said controlling step includes actuating

12

an appropriate number of said air jets at an appropriate time to direct the materials other than white paper out of the stream.

20. The method of claim 17, further comprising:

providing the waste paper objects in a stream including white paper and materials other than white paper, wherein the stream is dominated by the materials other than white paper; and

wherein the controlling step includes controlling one or more actuators that direct the white paper out of the stream.

21. The method of claim 20, wherein:

said spreading step includes carrying the stream on a conveyor having a width; and

in the controlling step, said one or more actuators include an array of air jets spaced across the width of the conveyor, and said controlling step includes actuating an appropriate number of said air jets at an appropriate time to direct the white paper out of the stream.

22. A method of sorting waste paper objects, comprising: providing a stream of waste paper objects in a layer that is substantially one waste paper object thick;

detecting the presence or absence of a predetermined optical characteristic as the layer of waste paper objects is passed by a sensor; and

controlling one or more actuators that direct the waste paper object based on the presence or absence of the predetermined optical characteristic.

23. The method of claim 22, wherein:

in said controlling step, each of said actuators includes an air jet.

24. The method of claim 23, wherein:

said providing step includes providing said layer on a conveyor having a width; and

in said controlling step, said air jets comprise an array of air jets spaced across the width of the conveyor.

25. The method of claim 23, wherein:

said detecting step includes communicating sensor signals from the sensor to a microprocessor; and

said controlling step comprises communicating control signals from the microprocessor to an array of solenoid valves associated with the air jets and thereby controlling a flow of air to the air jets.

26. The method of claim 22, further comprising:

conveying the layer of waste paper objects on a first conveyor and launching the layer of waste paper objects off the first conveyor across a gap to a second conveyor; and

wherein said controlling step includes controlling said one or more actuators to deflect a portion of the paper objects away from said second conveyor in an ejected paper object stream.

27. The method of claim 22, wherein:

in the providing step the stream includes white paper and materials other than white paper; and

the controlling step includes controlling one or more actuators that direct the materials other than white paper out of the stream.

28. The method of claim 27, wherein:

said providing step includes carrying the stream on a conveyor having a width; and

13

in the controlling step, said one or more actuators include an array of air jets spaced across the width of the conveyor, and said controlling step includes actuating an appropriate number of said air jets at an appropriate time to direct the materials other than white paper out of the stream. 5

29. *The method of claim 22, wherein:*

in the providing step the stream includes white paper and materials other than white paper, and the stream is dominated by the materials other than white paper; and 10
the controlling step includes controlling one or more actuators that direct the white paper out of the stream.

14

30. *The method of claim 29, wherein:*

said providing step includes carrying the stream on a conveyor having a width; and

in the controlling step, said one or more actuators include an array of air jets spaced across the width of the conveyor, and said controlling step includes actuating an appropriate number of said air jets at an appropriate time to direct the white paper out of the stream.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : RE42,090 E
APPLICATION NO. : 11/139005
DATED : February 1, 2011
INVENTOR(S) : Bruner et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In column 1, line 13, in the specification, replace "Slates" with --States--.

In column 7, line 43, in the specification, replace "lake" with --take--.

In column 10, line 6, in claim 1, 5th line thereof, before "paper" insert --waste--.

In column 10, line 8, in claim 1, 7th line thereof, after "a sheet of" insert --the waste paper from the layer of waste--.

In column 11, line 41, in claim 16, 5th line thereof, after "the layer of" insert --waste--.

In column 11, line 44, in claim 16, 8th line thereof, after "object" insert --from the layer of waste paper--.

In column 11, line 53, in claim 17, 8th line thereof, replace "object" with --objects--.

In column 12, line 30, in claim 22, 8th line thereof, replace "object" with --objects--.

Signed and Sealed this
Fifteenth Day of March, 2011

A handwritten signature in black ink that reads "David J. Kappos". The signature is written in a cursive, slightly slanted style.

David J. Kappos
Director of the United States Patent and Trademark Office