

US00RE42304E

(19) **United States**
(12) **Reissued Patent**
Frank et al.

(10) **Patent Number:** **US RE42,304 E**
(45) **Date of Reissued Patent:** **Apr. 26, 2011**

(54) **LOCK OUT TAG**

(75) Inventors: **Carl Frank**, Mt. Pleasant, IA (US);
Virgil Allen Watson, Salem, IA (US);
Jason Bender, Mt. Pleasant, IA (US)

(73) Assignee: **Lomont Molding, Inc.**, Mount Pleasant, IA (US)

(21) Appl. No.: **12/796,815**

(22) Filed: **Jun. 9, 2010**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,624,525**
Issued: **Dec. 1, 2009**
Appl. No.: **11/277,007**
Filed: **Mar. 20, 2006**

(51) **Int. Cl.**
G09F 3/14 (2006.01)

(52) **U.S. Cl.** **40/664; 40/5**

(58) **Field of Classification Search** **40/664,**
40/330, 630, 631, 6, 661.12, 655
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

262,696 A * 8/1882 Russell 40/6
736,299 A 11/1903 Rose

1,089,956 A *	3/1914	Polyanich	40/665
2,571,349 A	10/1951	Eckles		
2,811,797 A *	11/1957	Teetor	40/653
3,581,347 A	6/1971	Verspieren		
3,913,179 A *	10/1975	Rhee	24/16 PB
4,570,368 A *	2/1986	Stover	40/645
4,807,379 A *	2/1989	Blumhof	40/653
5,189,761 A	3/1993	Chisholm		
5,381,617 A *	1/1995	Schwartztol et al.	40/6
5,581,850 A	12/1996	Acker		
5,687,455 A	11/1997	Alexander		
5,692,268 A	12/1997	Case		
5,765,885 A	6/1998	Netto		
5,881,582 A	3/1999	Monaco		
6,226,839 B1	5/2001	Sayegh		
6,276,029 B1	8/2001	Buettell		
6,513,349 B1	2/2003	Miao		
6,671,984 B2 *	1/2004	Larson	37/404
6,694,655 B2 *	2/2004	Redburn et al.	40/664
2003/0182766 A1	10/2003	Avinger		
2005/0268509 A1	12/2005	Lewis		

* cited by examiner


Primary Examiner — Lesley Morris

Assistant Examiner — Shin Kim

(57) **ABSTRACT**

A tag has an in-mold graphic plate portion with a slot therein. Extending outwardly from the plate portion is an extension or tongue that has a neck and locking tip. The locking tip has an aperture adapted to receive a lock. The neck of the tongue is flexible such that the locking tip is received by and extends through the slot.

1 Claim, 2 Drawing Sheets






Fig. 1




Fig. 2

1
LOCK OUT TAG

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

BACKGROUND OF THE INVENTION

This invention is directed toward a tag, and more specifically a lock out tag for complying with OSHA regulations.

Lock out tags are known in the art to provide notice and authorization to specific individuals permitting removal of a lock from a secured area, such as an electrical switch/breaker box. Standard lock out tags are sold having separate pieces. Presently, a need exists for an all-in-one tag having a strap that conveniently receives a lock and provides an in-mold graphic.

An object of the present invention is to provide a tag that is easy to use.

A further object of the present invention is to provide a tag that is economical to manufacture.

These and other objects will be apparent to those skilled in the art based on the following written description.

BRIEF SUMMARY OF THE INVENTION

A tag has an in-mold graphic plate portion with a slot therein. Extending outwardly from the plate portion is an extension or tongue that has a neck and locking tip. The locking tip has an aperture adapted to receive a lock. The neck of the tongue is flexible such that the locking tip is received by and extends through the slot.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a tag and a lock; and FIG. 2 is a top plan view of a tag.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to the figures, a tag **10** has a plate portion **12**. Molded within the plate portion **12** is a sheet **13** having a

2

graphics and printed indicia **15**. The graphics and indicia **15** may include a warning as well as information indicating the individual authorized to remove the tag **10**.

Extending through the plate **12** is a slot **14**. While the slot is of any shape and size, preferred is a T-shaped slot. Extending outwardly from the plate portion **12** is an extension or tongue **16**. The tongue **16** has a neck portion **18** and a locking tip **20**. The locking tip **20** is formed to be received within the slot **14** such that once the tip **20** passes through the slot and is twisted the tip **20** is retained by the tip **20** engaging a surface of the plate portion **12**. The neck **18** is made of a flexible material such that the neck **18** may be bent to permit the tip **20** to be received by and pass through the slot **14**. The locking tip **20** has an aperture **22** adapted to receive a lock **23**, such as a conventional padlock.

In use, a tag **10** is provided and the tongue **16** is bent around an object so that the locking tip **20** is received by and passes through the slot **14**. In the embodiment shown in the drawings, the neck **18** is bent and twisted such that the tip **20** slides through the narrow section **24** of the T-shaped slot **14**. Once through the slot **14**, when the neck **18** is permitted to untwist, the neck **18** is received in the transverse section **26** of the slot **14**, such that an edge of the tip engages a surface of the plate portion **12**. Once the tip **20** is retained, the lock **23** is inserted through aperture **22** and locked in place.

From the foregoing, a tag has been shown that meets at least all the state objectives.

What is claimed is:

1. A method of securing an object, comprising the steps of:
 - providing a tag having an elongate, in-mold plastic plate portion, a slot, and a flexible tongue wherein the tongue further comprises a neck portion that extends outwardly from the plate portion and a locking tip extending from the neck portion; wherein the neck portion is narrower than the tongue and locking tip and wherein the locking tip has a centrally located aperture adapted to receive a lock;
 - bending the tongue around an object to be secured;
 - engaging the locking tip and the slot;
 - twisting the tongue so that the locking tip is received by and passes through the slot; and inserting a lock through the aperture.

* * * * *