

US00RE42381E

(19) United States

(12) Reissued Patent

Gildenberg

(10) Patent Number:

US RE42,381 E

(45) Date of Reissued Patent:

May 17, 2011

(54) HAIR TRANSPLANTATION METHOD AND APPARATUS

(75) Inventor: **Philip L. Gildenberg**, Houston, TX

(US)

(73) Assignee: Restoration Robotics, Inc., Mountain

View, CA (US)

(*) Notice: This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 12/259,482

(22) Filed: Oct. 28, 2008

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: 7,130,717
Issued: Oct. 31, 2006
Appl. No.: 10/354,836
Filed: Jan. 30, 2003

U.S. Applications:

(63) Continuation of application No. 09/774,154, filed on Jan. 30, 2001, now Pat. No. 6,585,746.

(51) **Int. Cl.**

A61B 17/00 (2006.01)

(52) **U.S. Cl.** **700/245**; 700/213; 700/219; 700/220; 700/250; 700/251; 700/252; 700/253; 700/257; 700/259; 901/1; 901/8; 901/14; 606/133; 606/187; 112/470.12; 112/470.13

700/251–253, 213, 219, 220; 901/1, 8, 14; 602/540; 606/133, 187

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,867,942 A	2/1975	Bellantoni et al.	
4,004,592 A	1/1977	Yamada	
4,160,453 A	7/1979	Miller	
4,451,254 A	5/1984	Dinius et al.	
4,476,864 A	10/1984	Tezel	
4,479,291 A	10/1984	Yamada	
4,716,901 A	1/1988	Jackson et al.	
4,751,927 A	6/1988	Yamada	
4,768,517 A	9/1988	Joachim	
4,807,163 A	2/1989	Gibbons	
4,969,903 A	11/1990	Valle	
5,036,860 A	8/1991	Leigh et al.	
5,050,608 A	9/1991	Watanabe et al.	
5,078,140 A	1/1992	Kwoh	
5,183,053 A	2/1993	Yeh et al.	
	(Continued)		
	(001		

FOREIGN PATENT DOCUMENTS

JP 10-000210 1/1998

(Continued)

OTHER PUBLICATIONS

Computerworld, Dispatches & Images from the Fringes of the Electronic Frontier, Mar. 30, 1998, Nexis, p. 1.*


(Continued)

Primary Examiner — Khoi Tran Assistant Examiner — Nikhil Sriraman (74) Attorney, Agent, or Firm — Lena I. Vinitskaya; Sharon Upham

(57) ABSTRACT

A hair transplantation method and apparatus utilizes a robot, which includes a robotic arm, having a hair follicle effector associated with the robotic arm.

26 Claims, 4 Drawing Sheets



U.S. PATENT DOCUMENTS

5,251,127	Λ	10/1993	Raah
5,331,472			Rassman 359/894
5,381,743		1/1995	
5,395,368			Ellman et al.
5,417,683		5/1995	
5,439,475			Bennett
5,483,961			Kelly et al.
, ,			Ellman et al.
5,490,850			
5,562,613			Kaldany
5,578,054		11/1996	
5,584,841			Rassman
5,584,851			Banuchi Amaldat at
5,611,810			Arnold et al.
5,611,811			Goldberg
5,662,661			Boudjema
5,693,064		12/1997	
5,733,278			Slatkine et al.
5,782,843			Aasberg
5,782,851			Rassman
5,782,853			Zeevi et al.
5,792,163		8/1998	•
5,792,169			Markman
5,817,105			Van Der Brug
5,817,120			Rassman
5,827,217			Silver et al.
5,827,297			Boudjema
5,858,019			Ashraf
5,865,744			Lemelson
5,873,888	\mathbf{A}	2/1999	Costanzo
5,893,853	\mathbf{A}	4/1999	Arnold
5,895,403	\mathbf{A}	4/1999	Collinsworth
5,899,916	\mathbf{A}	5/1999	Casparian
5,951,572	\mathbf{A}	9/1999	Markman
5,961,529	\mathbf{A}	10/1999	Arnold
5,984,936	\mathbf{A}	11/1999	Mangubat et al.
5,989,273	\mathbf{A}	11/1999	Arnold
5,989,279	\mathbf{A}	11/1999	Rassman
5,997,550	\mathbf{A}	12/1999	Russell
6,013,087	\mathbf{A}	1/2000	Adams et al.
6,027,512		2/2000	Bridges
6,056,736	\mathbf{A}	5/2000	Markman
6,059,807	\mathbf{A}	5/2000	Boudjema
6,110,189			Markman
6,120,521	\mathbf{A}	9/2000	Casparian
6,341,831			Weber et al.
6,434,416			Mizoguchi et al.
6,445,943			Ferre et al.
6,461,369		10/2002	
6,547,782		4/2003	
6,572,625			Rassman 606/133
6,694,167			Ferre et al.
6,973,931			
6,986,739			Warren et al 600/159
7,806,121			Bodduluri
2001/0034534		10/2001	
2001/0055807			Vournakis et al 435/366
2002/0050518			
2002/0030310		5/2002	110 motuvi

FOREIGN PATENT DOCUMENTS

WO	WO -98/25666	6/1998
WO	WO 98/25666	6/1998
WO	WO -00/64379	11/2000
WO	WO 00/64379	11/2000

OTHER PUBLICATIONS

Robert M. Bernstein, MD; William R. Rassman, MD; Wojciech Szaniawski, MD and Alan J. Halperin, MD. "Follicular Tranplantation" Int. Journal of Aesthetic and Restoration Surgery, vol. 3, No. 2, 1995, pp. 119-132.

Robert M. Bernstein, MD and William R. Rassman, MD. "The Logic of Follicular Unit Transplantation". Dermatologic Clinics, vol. 17, No. 2, Apr. 1999.

Francsico Jimenez, MD and Jose M. Ruifernandez, PhD. Distribution of Human Hair in Follicular Units. Dermatologic Surgery 1999; 25: pp. 294-298.

William R. Rassman, MD and Sharon Carson, BA. "Micrografting in Extensive Quantities". http://www.newhair.com/resources/mp-1995-micrografting.asp (7 pages).

"Mini and Micrograft Megasession" advertising sheet, undated, Alfonso Barrera MD, Houston, TX.

"M.D. News" Feb. 1996; Article entitled "West Houston Plastic Surgery Clinic . . . Houston Physician Transplants . . . Hair . . . ". Hair Transplantation, Third Edition, pp. 60-63.

"Neuro Mate—The Stereotactic Robot"; Advertising brochure, undated.

Annex to form PCT/ISA/206, Communication Relating to the Results of the Partial International Search, attached to PCT Invitation to Pay Additional Fees, PCT/ISA/206, for PCT/US2006/0038002, Applicant Restoration Robotics, Inc., dated Jan. 25, 2007 (5 pages). Japanese office action mailed May 20, 2008 in the corresponding Japanese application No. 2000-613372 together with Attorney's English translation (5 pages).

Web site, http://www.medicamat.com/materiel/hair-transplant/punchhairmatic.html?L=1, Medicamat, Medical and Surgical Devices, Cosmetic Products, Hair Transplant/Punch Hair Matic®, accessed on Aug. 8, 2007 (1 page).

Web site, http://www.medicamat.com/materiel/hair-transplant/punchhairmatic/case-study.html?L=1, Medicamat, Medical and Surgical Devices, Cosmetic Products, Hair Transplant/Punch Hair Matic®/ Case Study, accessed on Aug. 8, 2007 (3 pages).

Brochure, "Punch-Hair-Matic® A New Robot to Fight Baldness", Medicamat, (3 pages).

Web site, http://www.medicamat.com/materiel/hair-transplant/omnigraft.html?L=1, Medicamat, Medical and Surgical Devices, Cosmetic Products, Hair Transplant/Omnigraft®, accessed on Aug. 8, 2007 (1 page).

Web site, http://www.medicamat.com/materiel/hair-transplant/omnigraft/case-study.html?L=1, Omnigraft®, Medicamat, Medical and Surgical Devices, Cosmetic Products, Hair Transplant/Omnigraft®/Case Study, accessed on Aug. 8, 2007 (4 pages).

Brochure, Automated Hair Restoration System, OmniGraftTM, Medicamat S.A. (4 pages).

M. Inaba and Y Inaba, "Androgenetic Alopecia, Modern Concepts of Pathogenesis and Treatment" pp. 238-244, 309, Springer-Verlag, published 1996 (9 pages).

PCT International Search Report for PCT/US00/10596, PCT/ISA forms 210 and 220, dated Aug. 16, 2000, Applicant: Philip L. Gildenberg, (7pages).

PCT International Preliminary Examination Report for PCT/US00/10596, form PCT/IPEA/409 and 406, Applicant: Philip L. Gildenberg, (7 pages).

EPO Communication pursuant to Article 96(2) EPC,dated Dec. 2, 2004, for Application No. 00 926 161.1-2310, Applicant Houston Stereotactic Concepts, Inc., (3 pages).

Examiner's Report for Canadian Application No. 2,368,254, Restoration Robotics, dated Aug. 14, 2006, (3 pages).

Hill et al., Telepresence Surgery Demonstration System, 1994, IEEE, pp. 3202-3207.

Marshall, Semiconductor-Based Lasers in Medicine, 1998, IEEE, p. 1

Non-final Office Action Mailed Oct. 3, 2008 in relation to U.S. Appl. No. 11/702,485 (6 pages).

Response to Non-final Office Action submitted Nov. 3, 2008 in relation to U.S. Appl. No. 11/702,485, (26 pages).

Supplemental Response submitted Apr. 30, 2009 in relation to U.S. Appl. No. 11/702,485. (9 pages).

Non-final Office Action Mailed Jul. 21, 2009 in relation to U.S. Appl. No. 11/702,485. (13 pages).

Response to Non-final Office Action submitted Jul. 30, 2009 in relation to U.S. Appl. No. 11/702,485, together with Exhibits 1, 2 and 3. (21 pages).

Amendment after Final Rejection & Supplemental Reissue Declaration, submitted Mar. 12, 2010, in relation to U.S. Appl. No. 11/702,485.

Supplemental Amendment after Final Rejection, submitted May 28, 2010, in relation to U.S. Appl. No. 11/702,485.

Non-Final Office Action mailed Jul. 2, 2010 in relation to U.S. Appl. No. 11/702,485.

Examiner Interview Summary Record, mailed Jun. 14, 2010, in relation to U.S. Appl. No. 11/702,485.

Examiner Interview Summary Record, mailed Apr. 5, 2010, in relation to U.S. Appl. No. 12/259,434.

Response after Non-Final Action, submitted Apr. 15, 2010, in relation to U.S. Appl. No. 12/259,434.

Final Rejection mailed Jun. 30, 2010, in relation to U.S. Appl. No. 12/259,434.

Pre-Appeals Conference Decision mailed Jan. 26, 2010, in relation to U.S. Appl. No. 12/259,456.

Appeal Brief submitted Mar. 25, 2010, in relation to U.S. Appl. No. 12/259,456, including Appendices 1, 2 & 3.

Examiner's Answer to Appeal Brief mailed Jun. 22, 2010, in relation to U.S. Appl. No. 12/259,456, including Exhibits A, B, C and D. Reply Brief submitted Aug. 20, 2010, in relation to U.S. Appl. No. 12/259,456.

P.L. Gleason, Ron Kikinis, David Altobelli, William Wells, Eben Alexander III, Peter MCL. Black, Ferenc Jolesz. "Video Registration Virtual Reality for Nonlinkage Stereotactic Surgery". Stereotact Funct Neurosurg 1994; 63:pp. 139-143.

FDA Correspondence and 510(k) Summary of Safety and Effectiveness for CyberKnife System for Stereotactic Radiosurgery/Radiotherapy, date stamped Jul. 14, 1999. (5 Pages).

FDA Correspondence and 510(k) Premarket Notification Summary for "CyberKnife System", date stamped Aug. 10, 2001. (4 Pages). Supplemental Response to Office Action filed Oct. 23, 2009 in relation to U.S. Appl. No. 11/702,485. (9 Pages).

Final Office Action mailed Dec. 15, 200 in relation to U.S. Appl. No. 11/702,485, (14 pages).

STIC, Search Report, Dialog, Internet and EBSCO Host, 2009, pp. 1-71—provided with Final Office Action mailed Dec. 15, 200 in relation to U.S. Appl. No. 11/702,485, (71 pages).

Office Action mailed May 13, 2009 in relation to U.S. Appl. No. 12/259,456 (18 pages).

Interview Summary mailed Jul. 1, 2009 in relation to U.S. Appl. No. 12/259,456—without attachments (2 pages).

Response filed Jul. 2, 2009 in relation to U.S. Appl. No. 12/259,456, (9 pages).

Final Office Action mailed Sep. 16, 2009 in relation to U.S. Appl. No. 12/259,456, (15 pages).

Pre-Appeal Brief Request for Review filed Dec. 14, 2009 in relation to U.S. Appl. No. 12/259,456, (6 pages).

Office Action mailed May 14, 2009 in relation to U.S. Appl. No. 12/259,434 (21 pages).

Interview Summary mailed Jul. 1, 2009 in relation to U.S. Appl. No. 12/259,434—without attachments (3 pages).

Response filed Jul. 2, 2009 in relation to U.S. Appl. No. 12/259,434, (11 pages).

Final Office Action mailed Sep. 11, 2009 in relation to U.S. Appl. No. 12/259,434, (17 pages).

RCE, Amendment and Response filed Nov. 13, 2009 in relation to U.S. Appl. No. 12/259,434, (14 pages).


Office Action mailed Jan. 15, 2010 in relation to U.S. Appl. No. 12/259,434 (20 pages).


McInerney, James; Frameless Sterotaxy of the Brain; Sep. 2000; The Mount Sinai Journal of Medicine; vol. 67 No. 4; pp. 300-310.


Kwoh Ysi; A Robot with Improved Absolute Positioning Accuracy for CT Guided Stereotactic Brain Surgery; 1998; IEE Trans Biomed Eng; pp. 153-160.


BPAI Decision on Appeal mailed Jan. 28, 2011, in relation to commonly assigned Divisional Reissue U.S. Appl. No. 12/259,456, (15 pages).

* cited by examiner









HAIR TRANSPLANTATION METHOD AND APPARATUS

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

RELATED APPLICATION DATA

[This application] More than one reissue application has been filed for the reissue of U.S. Pat. No. 7,130,717. The reissue applications are application Ser. No. 11/702,485 filed on Feb. 5, 2007, and divisional application Ser. Nos. 12/259, 15 434, 12/259,456, and 12/259,482 (the present application), all filed on Oct. 28, 2008. U.S. Pat. No. 7,130,717 is a continuation of application Ser. No. 09/774,154, filed Jan. 30, 2001, now U.S. Pat. No. [6,58,746] 6,585,746 which claims the benefit [of U.S. Provisional Application No. 60/130,877 20 filed Apr. 23, 1999] under 35 U.S.C. §119 to PCT Application PCT/00/10596, filed Apr. 20, 2000. [application] Application Ser. No. 09/774,154 is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates generally to a method and apparatus for hair transplantation, and, more particularly, to a method and apparatus for hair transplantation which utilize a robot.

2. Description of the Related Art

Hair transplantation is presently a widely-performed procedure. Typically, it involves implanting many individual hair grafts. The individual grafts may be micrografts or minigrafts. In a "Megasession", or hair transplantation session, a large number of grafts, usually from 1000 to 2000 grafts, are implanted. Micrografts may contain one to two hair follicles and minigrafts may contain from three to five hair follicles Generally, the number of grafts done depends on the degree of baldness and density of hair desired for the transplantation.

The transplantation technique generally requires removal of an elliptical-shaped flap of scalp from the occiput, or back of the patient's head. The tiny micro and/or minigrafts may be removed from the flap of the patient's scalp which has been removed. The incision made to remove the flap is stitched 45 together, and normally leaves a well-concealed scar. The new grafts, which might be micro or mini-grafts are then inserted in very small slits, or openings, formed in the patient's scalp where it is desired to have the grafts implanted. Usually, the grafts are implanted approximately 1.5 mm. from each other 50 into the bald area of the patient's scalp to be treated. Generally, the slits, or small openings, formed in the patient's scalp to receive the grafts, heal very well, normally without leaving any scars.

The Megasession procedure generally takes a complete sworkday of from five to eight hours to complete, depending upon the number of grafts to be transplanted. Normally, one team of physicians and/or physicians assistants and/or nurses work together form the micro and/or minigrafts from the flap of removed scalp. They carefully trim the flap of scalp into the desired number of micro and/or minigrafts, each micro and/or minigraft containing at least one hair follicle. This step is generally referred to as the harvesting step and requires the use of very sharp, fine knives, or scalpels, and the use of magnification devices, such as magnifying loops, by the first surgical team. Generally, a second surgical team forms the slits, or openings in the patient's scalp which are to receive the

2

hair grafts, and each hair graft, or plug, is individually placed within each incision, or opening, by the second surgical team. The angle of insertion and the distribution of the recipient sites generally reflects the experience and art of the individual surgeon performing the procedure.

The disadvantages associated with the foregoing described Megasession hair transplantation technique, are that it is a long, laborious, and tedious procedure, which may begin at 7:30 am and not be completed until 2:00 pm to 5:00 pm, dependent upon the number of grafts, or plugs, to be transplanted and the efficiency of the teams. Furthermore, because of the labor intensiveness of the procedure, and the fact that all the individuals involved in the procedure are highly skilled and well trained and experienced, the procedure can be a very expensive procedure, the cost varying from \$2000 to \$12,000 dollars or more, dependent upon the number of hair grafts, or plugs, to be implanted.

Accordingly, prior to the development of the present method and apparatus for hair transplantation, there has been no hair transplantation technique which is not a long, laborious, tedious, uneconomical procedure, and is not overly labor intensive. Therefore, the art has sought a hair transplantation technique which is less long, laborious, tedious, and more economical, and which technique is less labor intensive.

The present invention is directed to overcoming, or at least reducing the effects of, one or more of the problems set forth above.

SUMMARY OF THE INVENTION

In accordance with the invention, the foregoing advantages have been achieved through the present hair transplantation method and apparatus for implanting at least one hair follicle into a portion of a patient's scalp. The hair transplantation apparatus of the present invention includes: a robot, including at least one robotic arm having a first end adapted to be disposed adjacent the patient's scalp; a hair follicle effector associated with the first end of the robotic arm, the robotic arm being adjustably maneuverable so that the hair follicle effector is capable of being selectably placed proximate the patient's scalp and operated to implant the at least one hair follicle into a portion of the patient's scalp; and the hair follicle effector being moved and operated to implant the at least one hair follicle into a portion of the patient's scalp. A feature of the present invention is that the hair follicle effector may be either a single hair follicle insertion device which includes a needle, or a multiple hair follicle insertion device which includes multiple needles.

Another feature of the present invention is that the apparatus may include a video system adapted to be associated with the patient's scalp and adapted to identify at least one location on the scalp where the at least one hair follicle is to be implanted. The video system may include a camera and a distance measuring device to measure the distance from the patient's scalp to the camera. Another feature of the present invention is that a plug cutting device may be associated with the first end of the at least one robotic arm, the plug cutting device being adapted to remove a plug of the patient's scalp, the plug containing at least one hair follicle. The plug cutting device may be a single hair follicle insertion device which includes a needle. Another feature of the present invention is that a plug trimming device may be associated with the first end of the at least one robotic arm, the plug trimming device being adapted to trim a portion of a flap, removed from the patient's scalp, into a plurality of plugs of the patient's scalp, each plug containing at least one hair follicle. An additional feature of the present invention includes a stereotactic frame, adapted to be releaseably secured to the patient's head, for restraining the patient's head with respect to a stereotactic robot.

In accordance with the invention, the foregoing advantages have also been achieved through the present method for transplanting hair by implanting at least one hair follicle into a portion of a patient's scalp, the patient's scalp having a plurality of existing hair follicles. This aspect of the present 5 invention includes the steps of: providing a robot, the robot including at least one robotic arm, the at least one robotic arm having a first end; associating a hair follicle effector with the first end of the robotic arm, the robotic arm being adjustably maneuverable so that the hair follicle effector is capable of 10 being selectably placed proximate the patient's scalp; loading the hair follicle effector with at least one existing hair follicle; disposing the first end of the robotic arm adjacent to the patient's scalp; moving the hair follicle effector toward the patient's scalp; and operating the hair follicle effector to 15 implant the at least one existing hair follicle into a portion of the patient's scalp.

Another feature of this aspect of the present invention may include the step of utilizing as the hair follicle effector either a single hair follicle insertion device which includes a needle, or a multiple hair follicle insertion device which includes multiple needles. A further feature of this aspect of the present invention may include, prior to implanting the at least one existing hair follicle, the steps of: providing a video system; associating the video system with the patient's scalp; scanning the patient's scalp with the video system to determine the 25 locations of the existing hair follicles and the location of the patient's scalp in three dimensions. An additional feature of the present invention may include the steps of: utilizing a stereotactic video system which includes a camera and a distance measuring sensor; and measuring the distance from 30 the patient's scalp to the camera while the patient's scalp is being scanned.

An additional feature of this aspect of the present invention may include the step of determining the angular disposition of the existing hair follicles with respect to the patient's scalp.

Another feature of this aspect of the present invention may include the step of utilizing a single hair follicle insertion device, which includes a needle, as the plug cutting device.

Another feature of this aspect of the present invention, prior to the implantation of the at least one existing hair follicle, may include the steps of: providing a plug trimming device; associating the plug trimming device with the first end of the at least one robotic arm; disposing a flap containing a plurality of existing hair follicles, previously removed from the patient's scalp, upon a support surface; and trimming the flap into a plurality of plugs of the patient's scalp, each plug containing at least one existing hair follicle. An additional feature of this aspect of the present invention may include the steps of releaseably securing a stereotactic frame to the patient's head and restraining the patient's head with respect to a stereotactic robot.

The hair transplantation method and apparatus of the present invention, when compared to previously proposed operating the hair follicle effector to implant the at least one existing hair follicle into a portion of the patient's scalp hair transplantation methods and apparatus, are believed to have the advantages of providing a shorter, less laborious, less tedious, more economical, and less labor intensive hair transplantation procedure.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention may be best understood by reference to the following description taken in conjunction with the accompanying drawings, in which like reference numerals identify like elements, and in which:

FIG. 1 is a rear view of a patient's head illustrating an 65 elliptical-shaped piece of scalp having been removed from the occiput, or back of the patient's head;

4

FIG. 2 is a perspective view of the flap of scalp removed from the patient's head of FIG. 1, and illustrating its division into a plurality of micrografts and minigrafts;

FIG. 3 is a rear view of a patient's head after the elliptical shaped incision has been sutured;

FIG. 4 is a side view of the patient's head of FIG. 1 with a plurality of hair follicles having been implanted in the patient's scalp;

FIG. 5 is a side view of a hair follicle introducer;

FIG. 6 is a perspective view of a stereotactic robot, in accordance with one embodiment of the present invention, implanting a hair follicle into the scalp of the patient of FIG. 1:

FIG. 7 is a perspective view of the patient of FIG. 1 with a stereotactic video system associated with the patient's scalp; and

FIG. 8 is a perspective view of a plug cutting device for use in the present invention.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof have been shown by way of example in the drawings and are herein described in detail. It should be understood, however, that the description herein of specific embodiments is not intended to limit the invention to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

Illustrative embodiments of the invention are described below. In the interest of clarity, not all features of an actual implementation are described in this specification. It will of course be appreciated that in the development of any such actual embodiment, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which will vary from one implementation to another. Moreover, it will be appreciated that such a development effort might be complex and time-consuming, but would nevertheless be a routine undertaking for those of ordinary skill in the art having the benefit of this disclosure.

With reference to FIGS. 1-4, the prior art "Megasession" hair transplantation technique is illustrated. As seen in FIG. 1, patient 100 has hair, or hair follicles, 101, disposed upon the scalp 102 of patient 100. In order to obtain the hair follicles 101 for transplantation into the bald portion 103 of the scalp 102 of patient 100, a surgeon typically removes a elliptical-shaped flap 104 from the patient's scalp 102, the flap 104 containing a plurality of existing hair follicles 101. As to hair follicles 101, throughout this written description and the claims appended hereto, the use of the term "hair follicle" encompasses both the follicle and the hair shaft disposed within the follicle.

With reference to FIG. 2, a team of technicians, typically cleans the flap 104 and divides flap 104 into a plurality of smaller pieces 105, each piece 105 containing a plurality of hair follicles 101. The team of technicians would then trim and divide the smaller pieces 105 into a plurality of grafts, or small plugs, 106. Generally, the grafts, or small plugs, 106, are referred to as micrografts, 107 when they contain one to two hair follicles 101 and are referred to as "minigrafts" 108 when they contain from three to five hair follicles 101. As illustrated in FIG. 3, the elliptical-shaped incision 110 (FIG.

1) is sutured by the surgeon in a conventional manner leaving a very fine scar, or no scar, in the back of the head of patient 100.

With reference to FIG. 4, the transplantation of a plurality of micrografts 107, and minigrafts 108, is illustrated as having been transplanted upon the bald portion 103 of the scalp 102 of patient 100. The spacing depicted between the various grafts, or small plugs, is greatly exaggerated, for ease of illustration. Typically, the grafts 107, 108 are spaced approximately 1.5 mm. from each other. As previously discussed, a surgical team performs the transplantation of the grafts 107, 108 into the scalp 102 of patient 100. Typically, the surgeon makes a small incision in the desired location in the bald portion 103 of the patient's scalp 102, and each graft, or plug, 107, 108 is inserted into the incision. The angle of insertion and the distribution and location of the incisions normally reflects the experience and art of the individual surgeon. Typically, the foregoing procedure is performed under a local anesthetic, and hemostasis, or the prevention and/or stopping 20 of bleeding, is obtained by adding epinephrine to the local anesthetic, as well as by applying manual pressure following the transplantation, or insertion, of the grafts, or plugs, 107, 108 into the scalp 102. As previously described, from 1000 to 2000 grafts 107, 108 may be transplanted in one surgical 25 session or Megasession.

With reference to FIG. 5, a hair follicle introducer 115 is illustrated. Hair follicle introducer 115 may be a single hair follicle insertion device 116, such as that known as a Choi single hair insertion instrument, or similar instrument, as is 30 known in the art. As will be hereinafter described in greater detail, the present invention may utilize the hair follicle hair introducer 115 of FIG. 5. The single hair follicle insertion device 116 of FIG. 5 could also be used by the surgeon in the Megasession transplantation technique illustrated in FIGS. 35 1-4. The single hair follicle insertion device 116 typically includes a needle 117, as is known in the art, into which is loaded the hair follicle, as is known in the art.

With reference to FIG. 6, the hair transplantation apparatus **200** of the present invention for implanting at least one hair 40 follicle 101 into a portion of a patient's scalp 102 is illustrated. The hair transplantation apparatus 200 generally includes: a stereotactic robot 201, having at least one robotic arm 202 and a hair follicle introducer 115. Stereotactic robot 201 may be a commercially available stereotactic robot, such 45 as the NeuroMate Stereotactic Robot manufactured by Immi Medical Robots of Grenoble, France and sold in the United States by its subsidiary Innovative Medical Machines International of Wellesley, Mass. Another commercially available stereotactic robot which may be utilized in the present inven- 50 tion is that designed by Tsubikawa. The NeuroMate Stereotactic Robot is illustrated in FIG. 6. Stereotactic robot 201 is a computer-controlled, image-directed robotic assistant which includes robotic arm 202 which has a first end 203 adapted to be disposed adjacent the patient's scalp 102. The robotic arm 202 may have a plurality of axes of rotation, associated therewith, robotic arm 202 having five axes of rotation, or rotatable joints 205-209. As illustrated, robotic arm 202 includes two arms members 210, 211, rotatably journaled to each other about rotational axis 206. The first end 203 of robotic arm 202 includes an instrument holder 212 which is rotatably mounted about axis of rotation 205. The stereotactic robot 201 may include a PC compatible work station and image work station 215, which may illustrate the location of the hair follicle introducer 115 with respect to the 65 patient's scalp 102 on the screen 216 of the image work station 215. The movements of robotic arm 202 and the opera6

tion of hair follicle introducer 115 may be controlled by any suitable computer software program.

As in the case of any stereotactic procedure, the head of the patient 100 must be fixed, or restrained. A conventional stereotactic frame, or a conventional head holder, such as one which makes three point contact with the patient's head, 220, adapted to be releaseably secured to the patient's head, for restraining the patient's head with respect to the stereotactic robot 201 may be utilized. In this regard, the stereotactic frame, or head holder, 220 is typically fixedly secured to the operating room table 221, and as known in the art, the location and disposition of the stereotactic robot 201 with respect to the operating room table 221 and frame 220, in three-dimensional space, may be readily determined. Optionally, if desired for increasing the accuracy of apparatus 200, a plurality of fiducial marks may be disposed on the stereotactic frame 220, as well as on the patient's head. The location of the patient's head with respect to the stereotactic frame, or head holder, 220, as well as the orientation of the stereotactic robot 201 with respect to the stereotactic frame, or head holder, 220 may then be readily determined, as is known in the art. It should be noted that, alternatively, the patient's head could be releaseably secured directly to the operating room table 221, without the use of a stereotactic frame. So long as there is a fixed, known relationship in three-dimensional space between stereotactic robot 201 and the patient's head, apparatus 200 of the present invention may be used.

Still with reference to FIG. 6, the hair follicle introducer 115 may be a single hair follicle insertion device 116 including a single needle 117. The hair follicle introducer 115 may be modified to permit it to be operated by stereotactic robot 201, such as by including a piston device, or other operating mechanism (not shown) to operate the plunger 118 (FIG. 5) of hair follicle introducer 115, device, a plurality of hair follicles 101 could be simultaneously implanted into the patient's scalp 102. Alternatively, the individual hair follicle insertion devices, such as hair follicle introducer 115, which are combined to form the multiple hair follicle insertion device, may be actuated sequentially by the stereotactic robot 201, as desired. If single hair follicle insertion devices 116 are utilized, it would be necessary to reload the single hair follicle insertion device with a new hair follicle 101 after each use of the hair follicle introducer 115, or alternatively, a loaded hair follicle introducer 115 could be associated, or loaded into the tool, or instrument, holder 212 at the first end 203 of the robotic arm 202. By using a multiple hair follicle insertion device, including multiple needles, loaded with a plurality of hair follicles, set up, or down, time associated with the use of stereotactic robot 201 is decreased. As will be hereinafter described in greater detail, the apparatus 200 illustrated in FIG. 6 would be utilized in the present invention when it is desired to utilize stereotactic robot 201 to implant at least one hair follicle 101 into the patient's scalp 102.

Turning now to FIG. 7, a stereotactic video system 300 for use in the present invention is illustrated. A portion of the stereotactic video system 300 is adapted to be associated with the patient's scalp 102, or head, and is adapted to identify at least one location on the scalp 102 where the at least one hair follicle, or graft, 107, 108 containing the at least one hair follicle 101, is to be implanted. Stereotactic video system 300 preferably includes a video camera 301 and a distance measuring device 302, for measuring the distance from the patient's scalp 102 to the camera 301. The stereotactic video system 300 is used in connection with the stereotactic frame 220 which has been releaseably secured to the patient's head. The camera 301 is mounted for rotation about the patient's head via a stereotactic arm 303 having a length which can be

varied and predetermined. The stereotactic video system may include suitable wiring 304 and circuitry contained within a housing 305, which is in a signal transmitting relationship with a display device 306. An example of a suitable stereotactic video system 300 for use in the present invention is that 5 known as the Exoscope, as described in Chapter 23 of Advanced Neurosurgical Navigation published in 1999 by Thieme Medical Publishers, Inc. Whereas the Exoscope is used to view an intracerebral mass, or tumor, located within the patient's head, it can be modified as hereinafter described, 10 to function with the present invention. The viewing equipment, or display device, 306 can include images of the patient's scalp as shown at 307, and a graphic depiction of the distance to the patient's scalp 102, as shown at 308.

Stereotactic video system 300 is used in the following 15 manner. Camera **301** is moved in controlled arcs across the patient's scalp 102 to map the location of existing hair follicles 101 (FIG. 1) on the patients' scalp 102. The distance measuring device 302 may be an infrared measuring device 305, or any other suitable device which permits the distance 20 from the patient's scalp 102 to the camera 301 to be measured. Since the radius of the stereotactic arc being scanned by the movement of the stereotactic arm 303 and the distance from the video camera 301 to the patient's scalp 102 are known, it is possible to calculate the position in three-dimensional 25 space of each point on the surface of the patient's scalp 102 in three-dimensional space, including the location and threedimensional coordinates of each existing hair follicle 101 on the patient's scalp 102 with respect to the stereotactic frame **220**. A three-dimensional virtual image of the patient's scalp 30 and the location of each hair follicle may be reconstructed in the computer (not shown) associated with stereotactic video system 300 and the stereotactic robot 201 (FIG. 6). For example, the image of the scalp and the hair follicles 101 may be viewed as shown at **309**. The contour of the patient's scalp 35 102 with respect to the stereotactic frame 220 in three-dimensional space is thus determined, as well as the location of existing hair follicles 101. The three-dimensional virtual image of the patient's scalp 102 may then be utilized to plan at what locations upon scalp 102, the various grafts, or plugs, 40 107, 108, will be implanted upon scalp 102 of the patient 100 by the stereotactic robot **201**.

If desired, the scanning of the patient's scalp 102 and existing hair follicles 101 may also be performed so as to determine the angular disposition of each hair follicle 101 45 with respect to the patient's scalp 102, including the vector the existing hair follicle 101 is oriented in relation to the patient's scalp 102. This information could be utilized, as will be hereinafter described in greater detail, when the present invention is utilized to also remove, or harvest, existing hair 50 follicles from the patient's scalp 102, or from flap 104. In this regard, it is desirable to remove the entire hair follicle, including the hair shaft disposed above the patient's scalp 102, as well as that portion of the hair shaft and follicle disposed beneath the surface of the patient's scalp **102**. To accomplish 55 this, it is preferable to know at what angle the hair follicle, including its hair shaft, is disposed and oriented, both above and below the patient's scalp 102.

With reference to FIG. 8, a graft, or plug, cutting device 400 is illustrated. Plug cutting device 400 may be associated 60 with the first end 203 of robotic arm 202 of stereotactic robot 201, and is adapted to remove a plug, or graft, 107, 108, of the patient's scalp 102, the plug, or graft, 107, 108 containing at least one hair follicle 101. Plug cutting device 400 may be received within the instrument holder 212 of stereotactic 65 robot 201. Plug cutting device 400 may include a plurality of cutting heads 401 associated with the housing 402 and the

8

movement of which are powered by a motor 403. As will be hereinafter described in greater detail, plug cutting device 400 may be used to remove a plug, or graft, 107, 108 directly from patient's scalp 102. An example of such a plug cutting device 400 may be found in U.S. Pat. No. 4,476,864, issued Oct. 16, 1984, which patent is incorporated herein by reference. Alternatively, a single hair follicle insertion device 116, including a needle 117, could be utilized as the plug cutting device.

As will be described in greater detail, the stereotactic robot 201 may be provided with a plug trimming device, or fine scalpel (not shown), which could be mounted, or associated, with the first end 203 of robotic arm 202 of stereotactic robot 201. After the flap 104 (FIG. 2) of the patient's scalp 102 has been surgically removed, the flap 104 could be positioned upon a suitable support surface, or table, or similar device. The stereotactic video system 300 of FIG. 7 could be utilized to scan the flap 104 and determine the three-dimensional location of the hair follicles 101 disposed upon and within flap 104 in three-dimensional space with respect to a set of predetermined markers, such as fiducial markers, associated with the support surface. The plug trimming device, or scalpel, associated with stereotactic robot 201 could then be utilized to trim the flap 104 into a plurality of plugs, or graft, 107, 108, each graft containing at least one existing hair follicle 101. The grafts would then later be inserted into a hair follicle introducer, such as hair follicle introducer 115, for implantation into the patient's scalp 102.

With reference to FIG. 6, the method of the present invention for transplanting hair will be described. In accordance with one aspect of the present invention, the stereotactic robot 201 may be used only to implant at least one hair follicle 101 contained within a graft 107, 108 into a portion of the patient's scalp 102. In this aspect of the present invention, the hair follicle introducer 115, as previously described, is loaded with the graft 107, 108 and the hair follicle introducer 115 disposed at the first end 203 of the robotic arm 202 of stereotactic robot 201 is moved toward the patient's scalp 102. The hair follicle introducer 115 is then operated to implant the at least one existing hair follicle 101 contained in the graft 107, 108 into the patient's scalp 102. Preferably, the particular location where the hair follicle, or graft 107, 108 is implanted within scalp 102, and the control of stereotactic robot 201 is determined by the stereotactic video system 300 which has previously computed the three-dimensional virtual image of the patients's scalp and the location and three-dimensional spacing of the existing hair follicles 101 and the desired location of the hair follicles to be implanted in scalp 102. The surgeon plans on the virtual three-dimensional image of the patient's scalp where each of the grafts 107, 108 is to be implanted. Several methods of planning may used individually or in combination. For example, the graft insertion site on the patient's scalp, and the angle of each of the hair follicles 101 contained within grafts 107, 108, may be manually plotted individually. The planning can be computerized either all, or in part. In either case, the new hair line, formed by the transplantation of the hair follicles, is determined by the surgeon. The computer (not shown) associated with stereotactic robot 201 and stereotactic video system 300, can distribute the grafts 107, 108, evenly throughout the bald portion 103 of the patient's scalp 102, and can plot the individual implantation sites, or locations, according to selected degrees of randomness. The angle of insertion of each hair follicle 101 may be determined for each region of the bald portion 103 of the patient's scalp 102, and/or the angle of insertion can be gradually adjusted from one region of the patient's scalp to another. Optionally, the computer (not shown) can display the

intended distribution of the existing and transplanted hair follicles as a three-dimensional rendering for final approval of the surgeon and the patient.

As to the robotic insertion of the grafts 107, 108, into the patient's scalp 102, the hair follicle introducer 115 may be 5 used to simultaneously make the necessary slit, or short incision, into the patient's scalp 102, by use of the needle 117 associated with the hair follicle introducer. Alternatively, a separate device, such as a suitable scalpel, or laser, could be associated with the stereotactic robot **201** to make the necessary small opening, incision, or slit in the patient's scalp which is to receive the graft 107, 108.

Hemostasis, or cessation of bleeding, may be necessary, as in the prior Megasession procedure, and hemostasis may provided such as by injecting a vasoconstrictor along with the 15 local anesthetic at the beginning of the procedure, and/or by applying local pressure for several seconds or minutes after the graft 107, 108 is inserted in the patient's scalp. In order to minimize bleeding even more, a pneumatic band (not shown) can be placed around the patient's scalp at the beginning of 20 the procedure. As previously discussed, single hair follicle insertion devices 115 or multiple hair follicle insertions devices could be utilized as previously described. As will be hereinafter discussed, the apparatus 200 of the present invention in addition to performing the hair transplantation method 25 previously described may also be used, if desired, to perform additional functions; however, whether or not the following described additional functions are also performed by apparatus 200 does not detract from the usefulness of apparatus 200.

If desired, the apparatus **200** of the present invention could 30 also be utilized to trim the flap 104 of the patient's scalp which has been previously removed from the patient. As previously described, a plug trimming device, or suitable scalpel, can be associated with the first end 203 of the robotic arm 202 of the stereotactic robot 201. The surgeon could 35 mount the flap 104 containing the hair follicles 101 upon a suitable support surface. As previously described, after the location of the existing hair follicles 101 is determined and mapped by the stereotactic video system 300, the plug trimming device, or scalpel, could be operated and controlled by 40 the stereotactic robot 201 to cut the grafts 107, 108 from the flap 104. Preferably, each graft 107, 108 would be cut along the longitudinal axis of the hair shaft of each hair follicle to minimize damage to the hair shaft and hair follicle. As previously described, if the angular disposition between the hair 45 follicle and the patient's scalp has been determined the stereotactic video system 300, the stereotactic robot 201 may be programmed to operate the plug trimming device along the longitudinal axis of each hair follicle 101. Alternatively, a single hair follicle insertion device, such as device 116 of 50 ing: FIG. 5, could be utilized as the plug cutting device, whereby the needle 117 would be inserted within flap 104 to retrieve a single hair follicle 101, thus simultaneously loading the hair follicle to be implanted into the single hair follicle insertion device 116.

Alternatively, if desired, the apparatus 200 of the present invention may be utilized to also directly obtain the grafts 107, 108 directly from the patient's scalp 102 without surgically removing flap 104. In this regard, as previously described, a plug cutting device 400 (FIG. 8) could be associated with stereotactic robot 201 and the plug cutting device 400 could directly remove the grafts 107, 108, from the patient's scalp 102. Alternatively, plug cutting device 400 could be a single hair follicle insertion device **116** (FIG. **5**) which includes a needle 117, which could be used to remove 65 the grafts 107, 108, directly from the patient's scalp 102. As previously described, the patient's scalp is scanned roboti**10**

cally to identify the position of each hair follicle 101 and the plug cutting device 400 could be operated to select only every nth hair follicle 101, rather than removing all the hair from a given location, which is comparable to the surgical removal of a flap **104**.

As to the transplantation of grafts 107, 108, into the patient's scalp 102, it should be noted that the bald portion of the patient's scalp 102, or recipient space, 103, can be divided into any number of individual areas, each of which can be programmed individually. The recipient space, or bald area, 103 can overlap areas of existing hair in order to insert hair follicles **101** to increase the density of hair in those areas. The density of the transplanted hair follicles can be calculated, depending upon the number of hair follicles to be implanted. The spacing between hair follicles can be done either manually, or the computer can generate a random distribution. The angle of insertion may be determined for each area individually, or the computer can generate a plan to vary the angle of insertion progressively from one side of an area to the other. If some of the hair follicles to be transplanted are finer than the other hair follicles, they can be individually identified and reserved for insertion at the hair line. A three-dimensional rendered image simulating the post-operative appearance of the patient's scalp can be presented prior to hair follicle insertion for approval of the surgeon and possibly the patient.

Although the instrument holder 112 illustrated in FIG. 6 is shown to only hold a single tool, or instrument, such as hair follicle introducer 115, it should be noted that a rotating head (not shown) may be utilized in connection with robotic arm 202 to hold all the desired tools, or instruments such as scalpel, plug cutting devices, plug trimming devices, and hair follicle insertion devices, the rotating head being sequentially moved, or rotated, to permit the desired tool, or instrument to be mounted at the first end 203 of robotic arm 202.

The particular embodiments disclosed above are illustrative only, as the invention may be modified and practiced in different but equivalent manners apparent to those skilled in the art having the benefit of the teachings herein. Furthermore, no limitations are intended to the details of construction or design herein shown, other than as described in the claims below. It is therefore evident that the particular embodiments disclosed above may be altered or modified and all such variations are considered within the scope and spirit of the invention. Accordingly, the protection sought herein is as set forth in the claims below.

What is claimed:

55

[1. A hair transplantation apparatus for harvesting at least one hair follicle from a portion of a patient's scalp compris-

- a robot, including at least one robotic arm having a first end adapted to be disposed adjacent the patient's scalp;
- a hair follicle plug cutting device associated with the first end of the robotic arm, the robotic arm being adjustably maneuverable so that the plug cutting device is capable of being selectably placed proximate the patient's scalp; and
- the plug cutting device being operated using a substantially automated process to harvest the at least one hair follicle.
- [2. The hair transplantation apparatus of claim 1, wherein the robot is at least a partially automated robot, and the robotic arm is moved to place the plug cutting device proximate the patient's scalp using a substantially automated process.
- [3. The hair transplantation apparatus of claim 1, wherein the portion of the patient's scalp under consideration is a flap that has been removed from the patient's scalp.

- [4. The hair transplantation apparatus of claim 1, wherein the robot is a stereotactic robot.]
- [5. The hair transplantation apparatus of claim 4, further comprising a plurality of fiducial marks strategically positioned in relation to the stereotactic robot so that the position of the robotic arm is known in relation to the patient's scalp.]
- [6. The hair transplantation apparatus of claim 1, further comprising a video system that includes a camera and a monitor for displaying an image of the portion of patient's scalp under consideration.]
- [7. The hair transplantation apparatus of claim 6, wherein the video system is used for mapping locations of existing hair follicles on the portion of the patient's scalp under consideration.]
- [8. The hair transplantation apparatus of claim 7, wherein 15 the video system is used to determine an angular disposition of the at least one hair follicle with respect to the patient's scalp.]
- [9. The hair transplantation apparatus of claim 6, wherein the video system is used to create a virtual image of the 20 portion of the patient's scalp under consideration.]
- [10. The hair transplantation apparatus of claim 9, wherein the video system includes a stereo pair of video cameras, and the virtual image is created by scanning the patient's scalp using the stereo pair of video cameras.]
- [11. The hair transplantation apparatus of claim 9, wherein the video system includes a video camera and a range finder, and the virtual image is created by scanning the patient's scalp using the video camera and the range finder.]
- [12. The hair transplantation apparatus of claim 9, wherein 30 the video system includes at least one camera, and the virtual image is acquired from a series of still images taken by the at least one camera at different perspectives.]
- [13. The hair transplantation apparatus of claim 9, wherein the virtual image of the portion of the patient's scalp under 35 consideration includes a location and three-dimensional spacing of the at least one hair follicle to be harvested.]

 disposition of the patient's scalp under 35 patient's scalp.]
- [14. The hair transplantation apparatus of claim 13, wherein the robot is at least a partially automated robot, and the virtual image of the portion of the patient's scalp under 40 consideration is used to move the robotic arm and place the plug cutting device proximate the patient's scalp using a substantially automated process.]
- [15. The hair transplantation apparatus of claim 13, wherein the video system is used to simultaneously display 45 the virtual image and a real-time image of the portion of the patient's scalp under consideration.]
- [16. The hair transplantation apparatus of claim 1, wherein the hair follicle plug cutting device is operated to harvest a follicular unit.]
- [17. The hair transplantation apparatus of claim 16, wherein the follicular unit includes a single hair follicle.]
- [18. The hair transplantation apparatus of claim 16, wherein the follicular unit includes a plurality of hair follicles.]
- [19. A hair transplantation apparatus for implanting at least one hair follicle into a portion of a patient's scalp comprising: a robot, including at least one robotic arm having a first end adapted to be disposed adjacent the patient's scalp;
 - a hair follicle introducer associated with the first end of the robotic arm, the robotic arm being adjustably maneuverable so that the hair follicle introducer is capable of being selectably placed proximate the patient's scalp; and
 - the hair follicle introducer is loaded with the at least one hair follicle and then operated using a substantially automated process to implant the at least one hair follicle.

12

- [20. The hair transplantation apparatus of claim 19, wherein the at least one hair follicle is loaded into the hair follicle introducer using a substantially automated process.]
- [21. The hair transplantation apparatus of claim 19, wherein the robot is at least a partially automated robot, and the robotic arm is moved to place the introducer proximate the patient's scalp using a substantially automated process.]
- [22. The hair transplantation apparatus of claim 19, wherein the robot is a stereotactic robot.]
- [23. The hair transplantation apparatus of claim 22, further comprising a plurality of fiducial marks strategically positioned in relation to the stereotactic robot so that the position of the robotic arm is known in relation to the patient's scalp.]
- [24. The hair transplantation apparatus of claim 19, further comprising a video system that includes a camera and a monitor for displaying an image of the portion of patient's scalp under consideration.]
- [25. The hair transplantation apparatus of claim 24, wherein the video system is used for planning a desired location for the at least one hair follicle to be implanted in the portion of the patient's scalp under consideration.]
- [26. The hair transplantation apparatus of claim 25, wherein, in planning the desired location for the at least one hair follicle, the video system is used to calculate a distance between a plurality of hair follicles to be implanted in the portion of the patient's scalp under consideration.]
 - [27. The hair transplantation apparatus of claim 25, wherein, in planning the desired location for the at least one hair follicle, the video system is used to plan a random distribution of a plurality of hair follicles.]
 - [28. The hair transplantation apparatus of claim 24, wherein the video system is used to determine an angular disposition of the at least one hair follicle with respect to the patient's scalp.]
 - [29. The hair transplantation apparatus of claim 24, wherein the video system is used to create a virtual image of the portion of the patient's scalp under consideration.]
 - [30. The hair transplantation apparatus of claim 29, wherein the video system includes a stereo pair of video cameras, and the virtual image is created by scanning the patient's scalp using the stereo pair of video cameras.]
 - [31. The hair transplantation apparatus of claim 29, wherein the video system includes a video camera and a range finder, and the virtual image is created by scanning the patient's scalp using the video camera and the range finder.]
- [32. The hair transplantation apparatus of claim 29, wherein the video system includes at least one camera, and the virtual image is acquired from a series of still images taken by the at least one camera at different perspectives.]
 - [33. The hair transplantation apparatus of claim 29, wherein the virtual image of the portion of the patient's scalp under consideration includes a three-dimensional spacing of a location the at least one hair follicle is to be implanted.]
 - [34. The hair transplantation apparatus of claim 33, wherein the robot is at least a partially automated robot, and the virtual image of the portion of the patient's scalp under consideration is used to move the robotic arm and place the introducer proximate the patient's scalp using a substantially automated process.]
 - [35. The hair transplantation apparatus of claim 29, wherein the video system is used to simultaneously display the virtual image and a real-time image of the portion of the patient's scalp under consideration.]
 - [36. The hair transplantation apparatus of claim 19, wherein the at least one hair follicle is implanted in the patient's scalp at a predetermined depth, and the robot deter-

mines when the predetermined depth is attained using the substantially automated process.

[37. A hair transplantation apparatus for implanting at least one hair follicle into a portion of a patient's scalp comprising: a robot, including at least one robotic arm having a first end adapted to be disposed adjacent the patient's scalp;

a hair follicle introducer associated with the first end of the robotic arm, the robot being capable of registering a position of the introducer with at least a portion of the patient's scalp under consideration so that the position of the introducer is known in three-dimensional space with respect to the portion of the patient's scalp under consideration, and the robotic arm is moved to place the introducer proximate the patient's scalp using a substantially automated process; and

the hair follicle introducer is loaded with the at least one hair follicle and then operated using a substantially automated process to implant the at least one hair follicle.]

[38. The hair transplantation apparatus of claim 37, wherein the at least one hair follicle is loaded into the hair 20 follicle introducer using a substantially automated process.]

[39. The hair transplantation apparatus of claim 37, wherein the robot is a stereotactic robot.]

[40. The hair transplantation apparatus of claim 39, further comprising a plurality of fiducial marks strategically positioned in relation to the stereotactic robot so that the position of the robotic arm is known in relation to the patient's scalp.]

[41. The hair transplantation apparatus of claim 37, further comprising a video system that includes a camera and a monitor for displaying an image of the portion of patient's 30 scalp under consideration.]

[42. The hair transplantation apparatus of claim 41, wherein the video system is used for planning a desired location for the at least one hair follicle to be implanted in the portion of the patient's scalp under consideration.]

[43. The hair transplantation apparatus of claim 42, wherein, in planning the desired location of the at least one hair follicle, the video system is used to calculate a distance between a plurality of hair follicles to be implanted in the portion of the patient's scalp under consideration.]

[44. The hair transplantation apparatus of claim 42, wherein, in planning the desired location of the at least one hair follicle, the video system is used to plan a random distribution of a plurality of hair follicles.]

[45. The hair transplantation apparatus of claim 41, 45 wherein the video system is used to create a virtual image of the portion of the patient's scalp under consideration.]

[46. The hair transplantation apparatus of claim 45, wherein the video system includes a stereo pair of video cameras, and the virtual image is created by scanning the 50 patient's scalp using the stereo pair of video cameras.]

[47. The hair transplantation apparatus of claim 45, wherein the video system includes a video camera and a range finder, and the virtual image is created by scanning the patient's scalp using the video camera and the range finder.] 55

[48. The hair transplantation apparatus of claim 45, wherein the video system includes at least one camera, and the virtual image is acquired from a series of still images taken by the at least one camera at different perspectives.]

[49. The hair transplantation apparatus of claim 45, 60 wherein the virtual image of the portion of the patient's scalp under consideration includes a three-dimensional spacing of a location the at least one hair follicle is to be implanted.]

[50. The hair transplantation apparatus of claim 45, wherein the video system is used to simultaneously display 65 the virtual image and a real-time image of the portion of the patient's scalp under consideration.]

14

[51. The hair transplantation apparatus of claim 37, wherein the at least one hair follicle is implanted in the patient's scalp at a predetermined depth, and the robot determines when the predetermined depth is attained using the substantially automated process.]

[52. A hair transplantation apparatus for harvesting at least one hair follicle from a portion of a patient's scalp comprising:

a robot, including at least one robotic arm having a first end adapted to be disposed adjacent the patient's scalp;

a hair follicle plug cutting device associated with the first end of the robotic arm, the robot being capable of registering a position of the plug cutting device with at least a portion of the patient's scalp under consideration so that the position of the plug cutting device is known in three-dimensional space with respect to the portion of the patient's scalp under consideration, and the robotic arm is moved to place the plug cutting device proximate the patient's scalp using a substantially automated process; and

the plug cutting device being operated using a substantially automated process to harvest the at least one hair follicle.

[53. The hair transplantation apparatus of claim 52, wherein the portion of the patient's scalp under consideration is a flap that has been removed from the patient's scalp.

[54. The hair transplantation apparatus of claim 52, wherein the robot is a stereotactic robot.]

[55. The hair transplantation apparatus of claim 54, further comprising a plurality of fiducial marks strategically positioned in relation to the stereotactic robot so that the position of the robotic arm is known in relation to the patient's scalp.]

[56. The hair transplantation apparatus of claim 52, further comprising a video system that includes a camera and a monitor for displaying an image of the portion of patient's scalp under consideration.]

[57. The hair transplantation apparatus of claim 56, wherein the video system is used for mapping locations of existing hair follicles on the portion of the patient's scalp under consideration.]

[58. The hair transplantation apparatus of claim 57, wherein the video system is used to determine the angular disposition of the at least one hair follicle with respect to the patient's scalp.]

[59. The hair transplantation apparatus of claim 56, wherein the video system is used to create a virtual image of the portion of the patient's scalp under consideration.]

[60. The hair transplantation apparatus of claim 59, wherein the video system includes a stereo pair of video cameras, and the virtual image is created by scanning the patient's scalp using the stereo pair of video cameras.]

[61. The hair transplantation apparatus of claim 59, wherein the video system includes a video camera and a range finder, and the virtual image is created by scanning the patient's scalp using the video camera and the range finder.]

[62. The hair transplantation apparatus of claim 59, wherein the video system includes at least one camera, and the virtual image is acquired from a series of still images taken by the at least one camera at different perspectives.]

[63. The hair transplantation apparatus of claim 59, wherein the virtual image of the portion of the patient's scalp under consideration includes a location and three-dimensional spacing of the at least one hair follicle to be harvested.]

[64. The hair transplantation apparatus of claim 59, wherein the video system is used to simultaneously display the virtual image and a real-time image of the portion of the patient's scalp under consideration.]

- [65. The hair transplantation apparatus of claim 52, wherein the hair follicle plug cutting device is operated to harvest a follicular unit.
- [66. The hair transplantation apparatus of claim 65, wherein the follicular unit includes a single hair follicle.
- [67. The hair transplantation apparatus of claim 65, wherein the follicular unit includes a plurality of hair follicles.
- [68. A hair transplantation apparatus for harvesting at least one hair follicle and implanting the at least one hair follicle 10 from/into a portion of a patient's scalp comprising:
 - a robot, including at least one robotic arm having a first end adapted to be disposed adjacent the patient's scalp;
 - an instrument holder associated with the first end of the robotic arm;
 - a hair plug cutting device associated with the instrument holder, the robot being adjustably maneuverable so that the plug cutting device is capable of being selectably placed proximate the patient's scalp;
 - the plug cutting device being operated using a substantially 20 automated process to harvest the at least one hair follicle from a first location of the patient's scalp;
 - a hair follicle introducer associated with the instrument holder, the robot being adjustably maneuverable so that the introducer is capable of being selectably placed 25 proximate the patient's scalp; and
 - the hair follicle introducer being operated using a substantially automated process to implant the at least one hair follicle into a second location of the patient's scalp.
- [69. The hair transplantation apparatus of claim 68, 30] wherein the plug cutting device and the hair follicle introducer are the same device.
- [70. The hair transplantation apparatus of claim 68, wherein the robot is at least a partially automated robot, and the introducer proximate the patient's scalp using a substantially automated process.
- [71. The hair transplantation apparatus of claim 68, wherein the robot is a stereotactic robot.
- [72. The hair transplantation apparatus of claim 71, further 40] comprising a plurality of fiducial marks strategically positioned in relation to the stereotactic robot so that the position of the robotic arm is known in relation to the patient's scalp.
- [73. The hair transplantation apparatus of claim 68, further comprising a video system that includes a camera and a 45 licles. monitor for displaying an image of the portion of patient's scalp under consideration.
- [74. The hair transplantation apparatus of claim 73, wherein the video system is used for mapping the first location of the patient's scalp.
- [75. The hair transplantation apparatus of claim 74, wherein the video system is used to determine the angular disposition of the at least one hair follicle with respect to the patient's scalp.
- [76. The hair transplantation apparatus of claim 73, 55] wherein the video system is used for planning the second location of the patient's scalp.
- [77. The hair transplantation apparatus of claim 76, wherein, in planning the second location, the video system is used to calculate a distance between the second location and 60 a plurality of additional locations hair follicles are to be implanted in the patient's scalp.
- [78. The hair transplantation apparatus of claim 73, wherein the video system is used to create a virtual image of the portion of the patient's scalp under consideration.
- [79. The hair transplantation apparatus of claim 78, wherein the video system includes a stereo pair of video

16

cameras, and the virtual image is created by scanning the patient's scalp using the stereo pair of video cameras.

- [80. The hair transplantation apparatus of claim 78, wherein the video system includes a video camera and a range finder, and the virtual image is created by scanning the patient's scalp using the video camera and the range finder.
- [81. The hair transplantation apparatus of claim 78, wherein the video system includes at least one camera, and the virtual image is acquired from a series of still images taken by the at least one camera at different perspectives.
- [82. The hair transplantation apparatus of claim 78, wherein the virtual image of the portion of the patient's scalp under consideration includes a three-dimensional image of the first location of the patient's scalp.
- [83. The hair transplantation apparatus of claim 82, wherein the robot is at least a partially automated robot, and the virtual image of the first location is used to move the robotic arm and place the plug cutting device proximate the patient's scalp using a substantially automated process.
- **[84.** The hair transplantation apparatus of claim **78**, wherein the virtual image of the portion of the patient's scalp under consideration includes a three-dimensional image of the second location of the patient's scalp.
- [85. The hair transplantation apparatus of claim 84, wherein the robot is at least a partially automated robot, and the virtual image of the second location is used to move the robotic arm and place the introducer proximate the patient's scalp using a substantially automated process.
- **[86.** The hair transplantation apparatus of claim **78**, wherein the video system is used to simultaneously display the virtual image and a real-time image of the portion of the patient's scalp under consideration.
- [87. The hair transplantation apparatus of claim 68, wherein the at least one hair follicle is implanted in the the robotic arm is moved to place the plug cutting device and 35 patient's scalp at a predetermined depth, and the robot determines when the predetermined depth is attained using the substantially automated process.
 - [88. The hair transplantation apparatus of claim 68, wherein the hair follicle plug cutting device is operated to harvest a follicular unit.
 - [89. The hair transplantation apparatus of claim 88, wherein the follicular unit includes a single hair follicle.
 - [90. The hair transplantation apparatus of claim 88, wherein the follicular unit includes a plurality of hair fol-
 - [91. A hair transplantation apparatus for harvesting at least one hair follicle and implanting the at least one hair follicle from/into a portion of a patient's scalp comprising:
 - a robot, including at least one robotic arm having a first end adapted to be disposed adjacent the patient's scalp;
 - an instrument holder associated with the first end of the robotic arm;
 - a hair follicle plug cutting device associated with the instrument holder, the robot being capable of registering a position of the plug cutting device with a first location of the patient's scalp so that the position of the plug cutting device is known in three-dimensional space with respect to the first location, and the robotic arm is moved to place the plug cutting device proximate the first location using a substantially automated process;
 - the plug cutting device being operated using a substantially automated process to harvest the at least one hair follicle;
 - a hair follicle introducer associated with the instrument holder, the robot being capable of registering a position of the introducer with a second location of the patient's scalp so that the position of the introducer is known in

three-dimensional space with respect to the second location, and the robotic arm is moved to place the introducer proximate the second location using a substantially automated process; and

the hair follicle introducer is loaded with the at least one 5 hair follicle and then operated using a substantially automated process to implant the at least one hair follicle.

- [92. The hair transplantation apparatus of claim 91, wherein the plug cutting device and the hair follicle introducer are the same device.
- [93. The hair transplantation apparatus of claim 91, wherein the robot is a stereotactic robot.
- [94. The hair transplantation apparatus of claim 93, further comprising a plurality of fiducial marks strategically positioned in relation to the stereotactic robot so that the position of the robotic arm is known in relation to the patient's scalp.
- [95. The hair transplantation apparatus of claim 91, further comprising a video system that includes a camera and a monitor for displaying an image of the portion of patient's 20 scalp under consideration.
- [96. The hair transplantation apparatus of claim 95, wherein the video system is used for mapping the first location of the patient's scalp.
- [97. The hair transplantation apparatus of claim 95, 25 partially computer controlled. wherein the video system is used for planning the second location of the patient's scalp.
- [98. The hair transplantation apparatus of claim 95, wherein the video system is used to create a virtual image of the portion of the patient's scalp under consideration.
- [99. The hair transplantation apparatus of claim 98, wherein the video system includes a stereo pair of video cameras, and the virtual image is created by scanning the patient's scalp using the stereo pair of video cameras.
- [100. The hair transplantation apparatus of claim 98, 35] wherein the video system includes a video camera and a range finder, and the virtual image is created by scanning the patient's scalp using the video camera and the range finder.
- [101. The hair transplantation apparatus of claim 98, wherein the video system includes at least one camera, and 40 the virtual image is acquired from a series of still images taken by the at least one camera at different perspectives.
- [102. The hair transplantation apparatus of claim 98, wherein the virtual image of the portion of the patient's scalp under consideration includes a three-dimensional image of 45 the first location of the patient's scalp.]
- [103. The hair transplantation apparatus of claim 98, wherein the virtual image of the portion of the patient's scalp under consideration includes a three-dimensional image of the second location of the patient's scalp.
- [104. The hair transplantation apparatus of claim 98, wherein the video system simultaneously displays the virtual image and a real-time image of the portion of the patient's scalp under consideration.
- wherein the at least one hair follicle is loaded into the hair follicle introducer using a substantially automated process.]
- [106. The hair transplantation apparatus of claim 91, wherein the at least one hair follicle is implanted in the patient's scalp at a predetermined depth, and the robot deter- 60 mines when the predetermined depth is attained using the substantially automated process.
- [107. The hair transplantation apparatus of claim 91, wherein the hair follicle plug cutting device is operated to harvest a follicular unit.
- [108. The hair transplantation apparatus of claim 107, wherein the follicular unit includes a single hair follicle.

18

- [109. The hair transplantation apparatus of claim 107, wherein the follicular unit includes a plurality of hair follicles.
- 110. A method of planning transplantation of hair grafts, comprising:
 - using an imaging system to identify a location of individual hair follicles on a surface containing hair follicles; and selecting from the identified hair follicles a hair graft for harvesting based on a user-specified parameter, wherein selecting is accomplished at least in part with the use of a computer program.
- 111. The method of claim 110, wherein the user-specified parameter is every Nth hair follicle.
- 112. The method of claim 110, wherein the user-specified parameter comprises reserving hair follicles that are within a user-specified region of interest.
- 113. The method of claim 110, wherein identifying and selecting hair follicles are computer implemented.
- 114. The method of claim 110, further comprising acquiring one or more images of the location from which hair follicles are to be harvested.
- 115. The method of claim 110, further comprising harvesting the selected hair graft wherein harvesting is at least
- 116. A system for planning transplantation of hair grafts, comprising:

a computer programmed to

- receive an image of a surface containing hair follicles, the image being acquired by an image acquisition device;
- record locations of individual hair follicles in the image, the hair follicles being previously identified; and
- carry out selection of one or more of the identified hair follicles for harvesting based on a user-specified parameter.
- 117. The system of claim 116, further comprising a display coupled to the computer for displaying the locations and/or intended distribution of hair follicles.
- 118. The system of claim 116, wherein the computer is further programmed to assist in planning implantation locations and display an image simulating an appearance of hair follicles being implanted in the implantation locations.
- 119. The system of claim 116, further comprising an image acquisition device, including a camera.
- 120. The system of claim 116, wherein the computer is associated with a robotic hair transplantation system.
- 121. The system of claim 118, wherein the computer is further programmed to determine an angle of insertion of a 50 hair follicle to be implanted.
 - 122. The system of claim 121, wherein the computer is programmed to gradually adjust the angle of insertion from one region to another.
- 123. The method of claim 110, wherein said using an imag-[105. The hair transplantation apparatus of claim 91, 55 ing system to identify a location of individual hair follicles comprises determining three-dimensional coordinates of the hair follicles.
 - 124. The method of claim 110, wherein the method is used in conjunction with a robotic hair transplantation procedure.
 - 125. The method of claim 110, further comprising determining an angular disposition of the hair follicles.
 - 126. The method of claim 110, further comprising plotting hair graft implantation locations based upon the location of the hair follicles.
 - 127. The method of claim 126, further comprising displaying an image simulating a distribution of the hair follicles and plotted hair grafts.

- 128. A method of planning transplantation of hair grafts, comprising:
 - identifying a plurality of individual hair follicles from data obtained by an imaging system; and
 - selecting from the plurality of hair follicles based on a suser-specified parameter an individual hair graft to be harvested, wherein selecting is accomplished at least in part using a processor programmed to carry out a user-specified selection.
- 129. The method of claim 128, wherein the user-specified 10 parameter is every Nth hair follicle.
- 130. The method of claim 128, wherein the user-specified parameter comprises reserving hair follicles that are within a user-specified region of interest.

- 131. The method of claim 128, wherein identifying and selecting are computer implemented.
- 132. The method of claim 128, further comprising acquiring one or more images of a location from which hair grafts are to be harvested.
- 133. The method of claim 128, further comprising harvesting the selected hair grafts.
- 134. The method of claim 128, further comprising mapping locations and three-dimensional coordinates of the plurality of hair follicles.
- 135. The method of claim 128, wherein the method is used in conjunction with a robotic hair transplantation procedure.

* * * *