

US00RE42996E

(19) **United States**
(12) **Reissued Patent**
Hyun et al.

(10) **Patent Number:** **US RE42,996 E**
(45) **Date of Reissued Patent:** **Dec. 6, 2011**

(54) **SIP-BASED USER MOBILITY PROVIDING APPARATUS AND METHOD**

2003/0154293 A1 8/2003 Zmolek
2004/0218605 A1 11/2004 Gustafsson et al.
2005/0021976 A1 1/2005 Trossen

(75) Inventors: **Eun-Hee Hyun**, Daejeon (KR);
Young-Jick Bahg, Daejeon (KR)

FOREIGN PATENT DOCUMENTS

KR 100179510 11/1998
KR 100179510 B1 11/1998
KR 1020030001672 1/2003
KR 1020030001672 A 1/2003

(73) Assignee: **Pantech Co., Ltd.**, Seoul (KR)

(21) Appl. No.: **12/612,327**

OTHER PUBLICATIONS

(22) Filed: **Nov. 4, 2009**

Ubiquitous Computing Using SIP, 8 pages.
Ubiquitous Computing Using SIP, 8 pages, no date provided.

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,292,561**
Issued: **Nov. 6, 2007**
Appl. No.: **10/882,604**
Filed: **Jun. 30, 2004**

* cited by examiner

Primary Examiner — Erika Gary

(74) *Attorney, Agent, or Firm* — H.C. Park & Associates, PLC

(30) **Foreign Application Priority Data**

Dec. 5, 2003 (KR) 10-2003-0087886

(57) **ABSTRACT**

(51) **Int. Cl.**
H04W 4/00 (2009.01)

(52) **U.S. Cl.** **370/338; 370/395.2**

(58) **Field of Classification Search** None
See application file for complete search history.

Disclosed are an SIP-based user mobility service providing apparatus and method using user position information obtained by a sensing apparatus. When a user enters a specific region, a gateway including a sensing management module carries out SIP registration for several terminals existing in the specific region in place of user agents of the terminals. The sensing management module transmits an SIP registration message to an SIP proxy server and notifies the terminals of the completion of SIP registration. Then, the user receives a call using the same kind of a terminal as a specific terminal previously set on the basis of a user's preferences among the terminals in the specific region.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,395,336 B1 * 7/2008 Santharam et al. 709/227
2003/0048195 A1 3/2003 Trossen

32 Claims, 4 Drawing Sheets




Fig. 1




Fig. 2




Fig. 3




Fig. 4





Fig. 5



**SIP-BASED USER MOBILITY PROVIDING
APPARATUS AND METHOD**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

CROSS REFERENCE TO RELATED
APPLICATION

This application is based on Korea Patent Application No. 2003-87886 filed on Dec. 5, 2003 in the Korean Intellectual Property Office, the content of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

(a) Field of the Invention

The present invention relates to an SIP-based user mobility providing apparatus and method using user location information obtained by a sensing apparatus.

(b) Description of the Related Art

There are a variety of networks having different performances and applications for communication services. Users are provided with the communication services using various kinds of terminals. With the development of wired and wireless communication techniques, the users want to select communication infrastructures providing the communication services according to their preferences.

The development of wired and wireless communication networks and a user's desire for being provided with the communication services whenever and wherever the user wants, creates a service environment in which various communication networks coexist in an arbitrary place. In this service environment, the user can use various network services depending on a place where the user uses the services, a moving speed, the kind of information the user wants to use, a performance level, and costs. Furthermore, a user terminal used for communications can have various forms and a choice of a terminal may affect a choice of a communication network. The user has an inclination in utilization of communication services in the aforementioned service environment.

A session initiation protocol (SIP) is a call signaling protocol of an application layer, which provides multimedia session initiation, exchange of session information, and cancellation of session. The SIP allows a user to be provided with communication services using a uniform resource identifier (URI) irrespective of a physical position of a user or a user terminal. That is, a service based on a user's preferences can be provided by several service features in an SIP-based multimedia service environment. Furthermore, services that allow a user to select a communication terminal according to his/her taste are proposed. For example, a receiving terminal for the wired/wireless telephone, E-mail, facsimile, and SMS service can be chosen according to a condition designated by a user. For this, an SIP service network has a separate database that stores user's preferences using for initiation of a communication session.

However, the above-described service can be provided only when the user has a designated terminal or he/she is in a place where the terminal exists. That is, if an arbitrary user provides his/her preferences for services to the SIP service network, a call is accomplished only when the user is located

beside a terminal that is designated such that it receives the call at the instant of time when someone attempts to make the call.

Accordingly, there has been proposed a ubiquitous service by which users can be provided with information or services they want in any place using various devices having a computing function that exist in any space. For the ubiquitous service, it is required to collect various contexts of users in order to conjecture psychological states and thoughts of the users and provide services they need.

To grasp the states of the users, various sensing apparatuses are required. There are various sensing apparatuses depending on kinds of information the apparatuses should collect.

Current selective services based on a user's preferences are provided depending on only preference information that has been designated by the user. Thus, the information can designate a terminal for receiving a call only when a designated condition, such as a condition that 'a call is received by a specific terminal at a specific time zone' or a condition that 'a call satisfying a specific condition is sent to voice mail', is satisfied. However, the call does not arrive at a corresponding user when the user is not located near the terminal.

Furthermore, terminals to be used for services using the SIP must be registered before a communication session is initiated. The SIP Registration cannot be spontaneously carried out when there is no user's intention. In particular, when many unspecified persons share one terminal, it is impossible to conjecture users and carry out the SIP registration. In the case of originating a call, the SIP registration is performed at the instant of time when a user signifies his/her intention to make a call using a terminal, such that he/she uses the terminal, clicks a button or a mouse, or uses a keyboard, and then a session is initiated. In the case of terminating a call, however, when the SIP registration has not been carried out by SIP user agent, any attempt to execute a communication is not received. Thus, a terminating part cannot carry out the SIP registration in time because the terminating part cannot be aware of the time when the terminating part is requested to receive a call. When the terminating part uses his/her own terminal, the SIP registration can be performed when the terminal is turned on or the terminating part previously sets the SIP registration. However, when many persons share one terminal or a user uses an arbitrary terminal in an arbitrary place, the user should carry out the registration using the several terminals. This considerably restricts the communication service using the SIP.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an SIP-based user mobility providing apparatus and method for supporting user mobility such that a user can receive a call in any place he/she exists using an arbitrary terminal existing in the place by using an SIP service network and a sensing apparatus in an environment where a variety of communication infrastructures coexist.

In one aspect of the present invention, an SIP-based user mobility service providing apparatus is connected to an SIP-based IP multimedia service network in an environment where various communication infrastructures coexist, and transmits an SIP message to an SIP terminal and an SIP proxy server through a gateway to provide a mobile user with an SIP service.

The SIP-based user mobility service providing apparatus comprises a sensing part that detects an event that the user enters a specific region or goes out of the specific region, to grasp a position of the user, and a sensing management mod-

ule that receives information on the position of the user in the specific region from the sensing part and carries out SIP registration for several terminal existing in the specific region in place of the user, to allow the user to receive a call using a specific terminal among the plurality of terminals.

The specific terminal has the same capability as that of a terminal selected on the basis of a predetermined terminal priority order depending on a user's preferences among the several terminals existing in the specific region.

The sensing part includes a marker that transmits specific information in response to the user's position, and a receiver that receives the specific information from the marker to detect the event that the user enters the specific region or goes out of the specific region and transmits the detected information to the sensing management module. The sensing management module can be mounted in the gateway or constructed in a separate machine having computing capability.

The sensing management module comprises an interface unit for communicating with the receiver of the sensing unit, the SIP proxy server, the SIP terminal, and an operator terminal that manages the receiver of the sensing unit and controls the sensing management unit; an information managing unit that manages the user information and information on the terminals in the specific region; and an SIP service supporting unit that carries out SIP registration for the several terminals existing in the specific region and notification of the completion of SIP registration such that the user is provided with the SIP service.

The operator terminal determines a range of the specific region on the basis of a marker detection allowable limit of the receiver. In addition, the operator terminal determines a marker monitoring period to determine whether the user exists in the specific region.

The sensing management module further comprises a user authentication unit that determines whether the user in the specific region uses the several terminals existing in the specific region and whether the user subscribes to an SIP service provider. The sensing management module further comprises a management information database for storing SIP registration related information including the user information and the information on the terminals in the specific region.

The information managing unit comprises a user/marker mapping manager for managing mapping information of an ID of the marker and a URI of the user; a terminal information manager for managing the information on the terminals existing in the specific region; and an active user manager for managing information of the user activation in the specific region;

The SIP service supporting unit comprises an SIP user registration/cancellation proxy unit that generates an SIP registration message for each of the several terminals in the specific region according and transmits the SIP registration message to the SIP proxy server to perform SIP registration; and an SIP user registration/cancellation notifying unit that notifies the SIP terminal of the completion of SIP user registration when SIP registration has been completed through the SIP user registration/cancellation proxy unit.

The interface unit comprises a sensing receiver interface that provides an interface for transmitting information on the result of the detection of the event that the user enters the specific region or goes out of the region from the sensing part to the sensing management module; an SIP proxy server interface that provides an interface for transmitting the SIP registration message for each of the terminals to the SIP proxy server; an SIP terminal interface that provides an interface for transmitting the SIP registration completion notification to the SIP terminal; and an operator interface that provides an

interface for operating and controlling the sensing management module by the operator terminal.

The present invention also provides an SIP-based user mobility service providing method using an SIP-based user mobility providing apparatus that is connected to an SIP-based IP multimedia service network in an environment where various communication infrastructures coexist, and transmits an SIP message to an SIP terminal and an SIP proxy server through a gateway to provide a mobile user with an SIP service.

The SIP-based user mobility service providing method comprises converting each terminals existing in a specific region to an available state when a user who is authorized to use the SIP service enters the specific region; and receiving a call using a specific terminal having the same capability as that of a terminal previously set on the basis of a user's preferences among the plurality of terminals in the available state.

The SIP-based user mobility service providing method further comprising performing user authentication for determining whether the user is authorized to use the terminals existing in the specific region and whether the user is authorized to use the SIP service when the user enters the specific region before the converting the terminals existing in the specific region to the available state when the user who is authorized to use the SIP service enters the specific region.

The converting the each terminals existing in the specific region to the available state when the user who is authorized to use the SIP service enters the specific region comprises detecting the event that the user enters the specific region; generating an SIP registration message for the each terminals in the specific region and transmitting the SIP registration message to the SIP proxy server to carry out SIP registration; and notifying the SIP terminal of the completion of SIP registration when SIP registration has been completed.

The converting the each terminals existing in the specific region to the available state when the user who is authorized to use the SIP service enters the specific region further comprises periodically confirming whether the user exists in the specific region after the notifying the SIP terminal of the completion of SIP registration when SIP registration has been completed.

The converting the each terminals existing in the specific region to the available state when the user who is authorized to use the SIP service enters the specific region further comprises, when it is confirmed that the user does not exist in the specific region, generating an SIP registration cancellation message for the plurality of terminals in the specific region and transmitting the SIP registration cancellation message to the SIP proxy server, to carry out cancellation of SIP registration; and notifying the SIP terminal of the completion of SIP registration cancellation when the cancellation of SIP registration has been completed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate an embodiment of the invention, and, together with the description, serve to explain the principles of the invention:

FIG. 1 illustrates a service environment where various communication networks coexist, to which the present invention is applied;

FIG. 2 illustrates a mobile multimedia service environment for supporting user mobility according to an embodiment of the present invention;

5

FIG. 3 illustrates an SIP-based mobile multimedia service network in connection with a sensing apparatus according to an embodiment of the present invention;

FIG. 4 is a block diagram of a sensor management module of an SIP-based user mobility providing apparatus according to an embodiment of the present invention; and

FIG. 5 is a flow chart illustrating an SIP-based user mobility providing method according to an embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the following detailed description, only the preferred embodiment of the invention has been shown and described, simply by way of illustration of the best mode contemplated by the inventor(s) of carrying out the invention. As will be realized, the invention is capable of modification in various obvious respects, all without departing from the invention. Accordingly, the drawings and description are to be regarded as illustrative in nature, and not restrictive.

FIG. 1 illustrates a service environment where a variety of communication networks coexist, to which the present invention is applied.

As shown in FIG. 1, the service environment 100 includes a wireless LAN (WLAN) environment 101 having access points which are equipped in a campus or an office building, which is used for walking speed; a cellular or personal mobile communication environment 102 usable for a moving speed higher than a certain level, such as in a car; a Bluetooth environment 103 for communications through radio apparatuses or Internet access in the home or office; a conventional fixed network environment 104; and any other network environments 105.

The above-described communication infrastructures provide communication services while being overlapped in an arbitrary region, and they can be classified depending on a method of providing a physical communication path. Furthermore, the communication infrastructures can include networks of different telecommunication operators using the same communication method. Users select communication infrastructures or terminals used for communications on the basis of various and complicate factors including costs, environmental factors, personal tastes, and so on. For example, the users can select communication infrastructures or terminals on the basis of capability of currently usable terminals, a billing policy of a communication infrastructure, service quality, importance of a communication counterpart, an emergency degree, and so on. These factors are combined with information on a specific time zone or a place where the users exist, and are applied to the selection of the communication infrastructures or terminals.

A system and a method for providing user mobility in a ubiquitous environment will now be explained.

FIG. 2 illustrates a mobile multimedia service environment for supporting user mobility according to an embodiment of the present invention. FIG. 2 shows a mobile multimedia service environment supporting user mobility, to which a moving user's preferences can be applied, in an environment where various communication infrastructures coexist.

The mobile multimedia service environment for supporting user mobility includes an SIP service network 200 that provides a mobile multimedia service using an SIP on the basis of various communication infrastructures 100 having different transmission methods.

The environment having the various communication infrastructures includes a service environment having a sensing

6

region 300 where a user who has been moved from a region where his/her terminal exists to the sensing region 300 can originate or terminate a call using a terminal existing in the sensing region. In the sensing region 300, communication services are provided to the user through a terminal resource existing in the area where the user is located on the basis of a user's preferences previously registered without having the user's intentional intervention in cooperation with the SIP service network 200 that is a service control network. FIG. 3 illustrates the SIP service network (SIP-based mobile multimedia service network) in connection with a sensing apparatus in the sensing region according to an embodiment of the present invention.

According to the present invention, the sensing apparatus 310 is installed in the sensing region 300 in order for the SIP service network 200 to support user mobility. The sensing apparatus 310 manages the sensing region 300 and includes a receiver 312 and markers 314. Various kinds of sensing apparatuses can be utilized depending on a sensing method and physical structural characteristics of an environment where the sensing apparatus is installed.

The sensing region 300 is a space where an arbitrary user selects one of terminals 320 existing therein to use the selected terminal for communications. The sensing region 300 is formed by installing the sensing apparatus and defining a sensing diameter.

Furthermore, the sensing region 300 means an area where the receiver 312 can recognize signals of the markers 314. The range of the sensing region 300 can be varied according to a selected sensing apparatus. The sensing region 300 can be intentionally formed to be small or large in order to define a personal space within the capability of the sensing apparatus 310.

Each of the markers 314 transmits unique information such as an ID to the receiver 312 such that the receiver 312 knows the existence of the marker 314. The marker 314 has a small size and low power consumption such that a user uses it conveniently. The user should carry the marker 314. The receiver 312 receives the ID of the marker 314 using a predetermined method to detect a movement of the user carrying the marker 314.

The SIP service network 200 includes an SIP proxy server 210, an SIP registration server 220, an SIP redirect server 230, an SIP presence server 240, and an SIP application server 250. The SIP service network 200 uses functions of a conventional SIP service network so that detailed explanation thereof is omitted.

To transmit information on the movement of the user who carries the marker 314 to the SIP service network 200, which is obtained from the identification of the marker 314 by the receiver 312, a sensing management module having sensing management and transmission functions of storing or processing the user movement information is required.

FIG. 4 is a block diagram of the sensing management module of the SIP-based user mobility providing apparatus according to an embodiment of the present invention. Here, the sensing management module is mounted in a gateway 330 (shown in FIG. 3).

Referring to FIG. 4, the sensing management module 400 includes an interface unit 410, an information management unit 420, a management information database 430, a user authentication unit 440, and an SIP service supporting unit 450. The interface unit 410 includes a sensing receiver interface 412, an SIP proxy server interface 414, an SIP terminal interface 416, and an operator interface 418.

The sensing receiver interface 412 receives the identifier of the marker 314 whose movement is recognized. In addition,

the sensing receiver interface **412** depends on a hardware connection of the receiver **312** and the computer (gateway) **330** in order to obtain information on a user who enters a corresponding region.

The SIP proxy server interface **414** is connected with an SIP user registration/cancellation proxy unit **452** to transmit/receive an SIP message to/from the SIP proxy server **210**. The SIP terminal interface **416** is connected with an SIP user registration/cancellation notifying unit **454** to enable communication between the SIP terminal **320** and the computer (gateway) **330** on the basis of a communication method of the SIP terminal **320** existing in the sensing region **300** and the gateway **330**. The communication method is determined on the basis of a wired or wireless communication standard or mode. Accordingly, the SIP terminal interface **416** is operated on the basis of information required for the interface **416** to be connected with the SIP terminal **320**. This information can be stored in the management information database **430** and managed by it.

The operator interface **418** interfaces an operator terminal **270**, the information management unit **420**, and the SIP service supporting unit **450** with one another to allow an operator to search or change parameters for a rule that the operator should observe when he/she controls environmental variables, adds or deletes information, and carries out real-time operation through the operator terminal **270**.

The operator terminal **270** controls reference values for procedures processed by various data tables and the components of the sensing management module **400** while the sensing management module **400** is operated. Furthermore, the operator terminal **270** determines a range of the sensing region **300** where the sensing apparatus **310** is installed to provide the service. In addition, the operator terminal **270** determines a monitoring period of the marker **314** for confirming whether a user continuously exists in the corresponding sensing region **300**.

The information management unit **420** includes a user/marker mapping manager **422**, a terminal information manager **424**, and an active user manager **407**. The user/marker mapping manager **422** maps the ID of the marker **314** with a URI that means a specific user when the sensing apparatus **310** receives the Identifier of the marker **314**. The user/marker mapping manager **422** is operated by a table that manages mapping of the marker ID and the user URI. The table is stored in the separate database **430** and managed by the database.

In the case that there are multiple sensing regions and users want to be provided with user mobility service while moving in these sensing regions, all information on mapping between the users and markers can be stored in sensing management modules corresponding to the respective sensing regions when the number of the users is small. When the number of the users is not small, a separate database can be used. Here, the sensor management module **400** can have a function of executing a separate communication with the separate database in order to obtain a URI of a user having a specific marker ID.

The terminal information manager **424** manages information on terminals existing in a specific region. Here, the information on the terminals includes information on characteristics of each terminal, which is required for the SIP service supporting unit **450** to carry out SIP registration in place of a user agent UA of the terminal, and information required for the user agent UA to perform SIP registration in the SIP service network **200**. The information on the terminals is stored in the separate database **430**.

The active user manager **426** manages active information on whether a user exists in the corresponding sensing region **300**. In addition, the active user manager **426** manages information on active users through the database **430**.

The user authentication unit **440** authenticates whether a user who has moved to the corresponding sensing region **300** is authorized to use the terminals **320** existing in the sensing region or to use the mobile multimedia service. Information required for the authentication is stored in the database **430** and managed by the database **430**. The user authentication unit **440** can be operated by a separate authentication server such that multiple sensing regions can commonly access the user authentication unit **440**.

The SIP service supporting unit **450** includes the SIP user registration/cancellation proxy unit **452** and the SIP user registration/cancellation notifying unit **454**. The SIP user registration/cancellation proxy unit **452** carries out SIP registration for a corresponding user in place of user agents of the SIP terminals.

The SIP user registration/cancellation notifying unit **454** notifies the user agents of the SIP terminals that SIP user registration has been completed when the gateway finishes SIP registration. Here, information required for operating a service session for a corresponding SIP terminal is transmitted.

The sensing management module **400** constructed as above carries out SIP registration of a corresponding terminal in place of a user such that the user can be provided with the SIP service using the terminal in a specific region. By doing so, the sensing management module **400** can manage the terminals existing in the sensing region **300** in order to select a terminal used for a communication session on the basis of a predetermined user's preferences in a specific region, and to control the terminals to be available when the user enters the sensing region **300**.

An SIP-based user mobility providing method using user position information obtained by the sensing apparatus will now be explained in detail with reference to FIG. 5. FIG. 5 is a flow chart showing the SIP-based user mobility providing method according to an embodiment of the present invention.

When a user enters the sensing region **300**, the receiver **312** receives the ID of the marker **314** using a predetermined method to detect a movement of the user in step **S502**. For example, the receiver **312** carries out a separate procedure of confirming the existence of the marker **314** periodically to detect a movement of a person or an object carrying the marker **314** when the marker **314** is passive. When the marker **314** is active, the receiver **312** detects a movement of the person or object carrying the marker **314** through information received from the marker **314**.

The receiver **312** that has detected a motion of the user transmits the ID of the marker to the sensing management module **400** through the receiver interface **412**. That is, the receiver **312** recognizes whether the user enters a specific area defined as the sensing region **300** or goes out of the area in step **S502**, and controls information on the marker **314** and processes the received identification information of the marker to transmit it to the gateway in step **504**, to support user mobility.

Then, the user/marker mapping manager **422** of the sensing management module **400** maps the marker ID with a URI of the user to determine that the user has entered the sensing region **300** in step **S506**. Mapping information on the marker ID and user's URI is managed by a corresponding service provider when the user subscribes to the service provider to be provided with the marker. That is, the mapping information on all users who can be provided with the service in the

sensing region 300 is managed irrespective of whether the users exist in the sensing region.

When the existence of the marker is recognized through the sensing receiver interface 412, the user authentication unit 440 of the sensing management module 400 determines whether the user carrying the marker is authorized to use a terminal existing in the sensing region 300 to authenticate the user in step S508.

When it is confirmed that the user entering the sensing region 300 subscribes to an SIP service provider, the SIP user registration/cancellation proxy unit 452 of the sensing management module 400 generates an SIP registration message in place of a user agent UA of each terminal 320 existing in the sensing region 300 in step S510, and transmits the SIP registration message to the SIP proxy server 210 through the SIP proxy server interface 414 in step S512. When the SIP proxy server 210 receives the SIP registration message from the SIP user registration/cancellation proxy unit 452, the SIP proxy server 210 transmits an acknowledge signal SIP OK in response to the received result in step S514.

At the instant of time when the sensing management module 400 completes the SIP registration, the SIP user registration/cancellation notifying unit 454 of the sensing management module 400 generates SIP registration completion messages for all of the SIP terminals existing in the sensing region 300 in step S516, and notifies the user agents of the SIP terminals that the SIP user registration has been completed in step S518. When each of the SIP terminals receives the notification, it transmits an acknowledge signal to the sensing management module 400 in step S520. Then, the user agent UA of each SIP terminal becomes an available state for transmitting or receiving an INVITE message capable of carrying out the service after SIP registration is finished.

The sensing management module 400 periodically sends a confirmation signal to the receiver 312 with respect to the user existing in the sensing region 300 to confirm whether the marker IDs recognized by the receiver 312 still exist in step S522. The receiver 312 that has received the 15 confirmation signal from the sensing management module 400 transmits IDs of markers existing in the sensing region 300. When there is no ID of the marker that previously entered the sensing region 300 among the marker IDs transmitted from the receiver, a user carrying the corresponding marker is considered to have gone out of the sensing region 300. These operations are performed by the active user manager 426.

When the active user manager 426 of the sensing management module 400 determines that the corresponding user has gone out of the sensing region 300 in step S525, the SIP user registration/cancellation proxy unit 452 generates an SIP deregistration message in step S526, to cancel the SIP registration for the corresponding SIP terminal 320. Then, the SIP user registration/cancellation proxy unit 452 transmits the SIP deregistration message to the SIP proxy server 210 through the SIP proxy interface 414 in step S528. The SIP proxy server 210 receives the SIP deregistration message and transmits an acknowledge signal SIP OK to the sensing management module 400 in step S530.

At the instant of time when the sensing management module 400 completes the cancellation of SIP registration, the SIP user registration/cancellation notifying unit 454 of the sensing management module 400 generates an SIP deregistration completion message for all the SIP terminals existing in the sensing region 300 in step S532, to notify the user agents UA of the SIP terminals that the SIP deregistration has been cancelled in step S534. Each the SIP terminals that has

received the notification transmits an acknowledgement signal ACK to the sensing management module 400 in step S536.

While the separate computer (gateway) 330 having software functioning as the sensing management module is connected with the sensing apparatus 310 in the aforementioned embodiment of the present invention, it is not restricted thereto. For example, the sensing apparatus 310 may not be connected to the gateway 330 and the receiver 312 of the sensing apparatus 310 may be constructed such that it has computing capability. Otherwise, the sensing management module can be inserted into a separate device having computing capability and being operated through an internal interface of the sensing apparatus 310.

The components of the sensing management module are required to manage an arbitrary sensing region. When a management region of a gateway existing for a specific purpose on a home network or an office network or agents, which are included in a physical network environment having unique characteristics, corresponds to the sensing region, the components of the sensing management module can be mounted on the same platform as the platform of the gateway or agents.

While this invention has been described in connection with what is presently considered to be the most practical and preferred embodiment, it is to be understood that the invention is not limited to the disclosed embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

According to the present invention, a user can use a terminal existing in an arbitrary area to originate a call or receive a call when the user has moved to the area from an area where his/her terminal exists in an environment where various communication terminals and communication infrastructures for supporting the terminals coexist. Furthermore, even when the user is located in an area where his/her terminal does not exist, the user can be provided with a desired communication service using a terminal having the same capability and characteristics as those of his/her terminal if the terminal exists in the area.

Moreover, the present invention can support user mobility such that a user can be provided with the user mobility services using various terminals. Furthermore, according to the present invention, the user does not have to intentionally carry out SIP user registration using a terminal he/she wants to use. In addition, since an arbitrary terminal can provide a ubiquitous service for an arbitrary user in a ubiquitous service environment, the user can receive a call using the same kind of terminal as his/her own terminal among terminals existing in the area where the user is currently located.

What is claimed is:

1. An SIP (Session Initiation protocol)-based user mobility service providing apparatus that is connected to an SIP-based IP multimedia service network in an environment where various communication infrastructures coexist and transmits an SIP message to an SIP terminal and an SIP proxy server through a gateway to provide a mobile user with an SIP service, comprising:

a sensing part that detects an event that the user enters a specific region or goes out of the specific region based on signals from at least one marker, to obtain a position of the user; and

a sensing management module that receives information on the position of the user in the specific region from the sensing part and carries out SIP registration for terminals in the specific region when it is confirmed that the user[,] enters the specific region, and carries out SIP

11

cancellation of SIP registration for terminals in the specific region when it is confirmed that the user goes out of the specific region.

2. The SIP-based user mobility service providing apparatus as claimed in claim 1, wherein the specific terminal has the same capability as that of a terminal selected on the basis of a predetermined terminal priority order depending on a user's preferences among the several of terminals existing in the specific region.

3. The SIP-based user mobility service providing apparatus as claimed in claim 1, wherein the at least one marker transmits specific information in the signals in response to the user's position, and the sensing part includes a receiver that receives signals with the specific information from the at least one marker to detect the event that the user enters the specific region or goes out of the specific region and transmits the detected information to the sensing management unit.

4. The SIP-based user mobility service providing apparatus as claimed in claim 1, wherein the sensing management module is mounted in the gateway.

5. The SIP-based user mobility service providing apparatus as claimed in claim 1, wherein the sensing management module is constructed in a separate machine having computing capability.

6. The SIP-based user mobility service providing apparatus as claimed in claim 1, wherein the sensing management module comprises:

- an interface unit for communicating with the receiver of the sensing unit, the SIP proxy server, the SIP terminal, and an operator terminal that manages the receiver of the sensing unit and controls the sensing management unit;
- an information managing unit that manages the user information and information on the terminals in the specific region; and
- an SIP service supporting unit that carries out SIP registration for the each terminals existing in the specific region and notification of the completion of SIP registration such that the user is provided with the SIP service.

7. The SIP-based user mobility service providing apparatus as claimed in claim 6, wherein the operator terminal determines a range of the specific region on the basis of a marker detection allowable limit of the receiver.

8. The SIP-based user mobility service providing apparatus as claimed in claim 6, wherein the operator terminal determines a marker monitoring period to determine whether the user exists in the specific region.

9. The SIP-based user mobility service providing apparatus as claimed in claim 6, wherein the sensing management module further comprises a user authentication unit that determines whether the user in the specific region uses the several terminals existing in the specific region and whether the user subscribes to an SIP service provider.

10. The SIP-based user mobility service providing apparatus as claimed in claim 6, wherein the sensing management module further comprises a management information database for storing SIP registration related information including the user information and the information on the terminals in the specific region.

11. The SIP-based user mobility service providing apparatus as claimed in claim 6, wherein the information managing unit comprises:

- a user/marker mapping manager for managing mapping information of an ID of the at least one marker and a URI (uniform resource identifier) of the user;
- a terminal information manager for managing the information on the terminals existing in the specific region; and

12

an active user manager for managing active information of the user in the specific region.

12. The SIP-based user mobility service providing apparatus as claimed in claim 6, wherein the SIP service supporting unit comprises:

- an SIP user registration/cancellation proxy unit that generates an SIP registration message for each of the several terminals in the specific region according to the SIP registration related information and transmits the SIP registration message to the SIP proxy server to perform SIP registration; and
- an SIP user registration/cancellation notifying unit that notifies the SIP terminal of the completion of SIP user registration when SIP registration has been completed through the SIP user registration/cancellation proxy unit.

13. The SIP-based user mobility service providing apparatus as claimed in claim 6, wherein the interface unit comprises:

- a sensing receiver interface that provides an interface for transmitting information on the result of the detection of the event that the user enters the specific region or goes out of the region from the sensing part to the sensing management module;
- an SIP proxy server interface that provides an interface for transmitting the SIP registration message for each of the terminals to the SIP proxy server;
- an SIP terminal interface that provides an interface for transmitting the SIP registration completion notification to the SIP terminal; and
- an operator interface that provides an interface for operating and controlling the sensing management module by the operator terminal.

14. An SIP-based user mobility service providing method using an SIP (session initiation protocol)-based user mobility providing apparatus that is connected to an SIP-based IP multimedia service network in an environment where various communication infrastructures coexist, and transmits an SIP message to an SIP terminal and an SIP proxy server through a gateway to provide a mobile user with an SIP service, comprising:

- a) converting each [terminals] *terminal* existing in a specific region to an available state when a user who is authorized to use the SIP service enters the specific region; and
- b) receiving a call using a specific terminal having the same capability as that of a terminal previously set on the basis of a user's preferences among the several terminals in the available state,

wherein converting each terminal further comprises:
 detecting an event that the user enters the specific region based on signals from at least one marker;
 generating an SIP registration message for terminals in the specific region and transmitting the SIP registration message to the SIP proxy server to carry out SIP registration when it is confirmed that the user enters the specific region; and
 generating an SIP deregistration message for the terminals in the specific region and transmitting the SIP deregistration message to the SIP proxy server, to carry out cancellation of SIP registration when it is confirmed that the user goes out of the specific region.

15. The SIP-based user mobility service providing method as claimed in claim 14, further comprising performing user authentication for determining whether the user is authorized to use the terminals existing in the specific region and whether the user is authorized to use the SIP service when the user

enters the specific region before the converting the each terminals existing in the specific region to the available state when the user who is authorized to use the SIP service enters the specific region.

16. The SIP-based user mobility service providing method as claimed in claim 15, wherein step a) further comprises periodically confirming whether the user exists in the specific region after the notifying the SIP terminal of the completion of SIP registration when SIP registration has been completed.

17. An SIP (Session Initiation protocol)-based user mobility service providing apparatus that is connected to an SIP-based IP multimedia service network to transmit an SIP message to an SIP terminal and an SIP proxy server through a gateway to provide a mobile user with an SIP service, comprising:

a sensing part to determine if the mobile user enters a sensing region based on a recognition of a first marker corresponding to the mobile user; and

a sensing management module to receive identification information corresponding to the first marker from the sensing part, and to carry out SIP registration for a first SIP terminal in the sensing region if the mobile user enters the sensing region,

wherein the sensing part determines if the mobile user departs the sensing region, and the sensing management module carries out SIP cancellation of SIP registration for the first SIP terminal in the sensing region if the mobile user departs the sensing region.

18. The SIP-based user mobility service providing apparatus of claim 17, wherein the first SIP terminal has the same capability as a previously set second SIP terminal and is selected on the basis of a predetermined terminal priority order depending on a preference of the mobile user among several SIP terminals in the sensing region.

19. The SIP-based user mobility service providing apparatus of claim 17, wherein the first marker transmits identification information corresponding to the first marker, and the sensing part comprises a receiver to receive the identification information from the first marker, and to transmit the identification information to the sensing management unit.

20. The SIP-based user mobility service providing apparatus of claim 17, wherein the sensing management module is arranged in the gateway.

21. The SIP-based user mobility service providing apparatus of claim 17,

wherein the sensing management module is arranged in a separate machine having computing capability.

22. An SIP (Session Initiation protocol)-based user mobility service providing apparatus that is connected to an SIP-based IP multimedia service network to transmit an SIP message to an SIP terminal and an SIP proxy server through a gateway to provide a mobile user with an SIP service, comprising:

a sensing part to determine if the mobile user enters a sensing region based on a recognition of a first marker corresponding to the mobile user; and

a sensing management module to receive identification information corresponding to the first marker from the sensing part, and to carry out SIP registration for a first SIP terminal in the sensing region if the mobile user enters the sensing region, wherein the sensing management module comprises:

an interface unit to communicate with the receiver of the sensing unit, the SIP proxy server, the SIP terminal, and an operator terminal that manages a receiver of the sensing part and controls the sensing management module;

an information managing unit to manage position information identifying a position of the mobile user; and an SIP service supporting unit to carry out SIP registration for the first SIP terminal in the sensing region and to notify the first SIP terminal if SIP registration is complete.

23. The SIP-based user mobility service providing apparatus of claim 22, wherein the operator terminal determines a range of the sensing region on the basis of a marker detection allowable limit of the receiver of the sensing part.

24. The SIP-based user mobility service providing apparatus of claim 22, wherein the operator terminal determines a marker monitoring period to determine whether the mobile user is in the sensing region.

25. The SIP-based user mobility service providing apparatus of claim 22, wherein the sensing management module further comprises:

a user authentication unit to determine whether the mobile user in the sensing region is authorized to use the first SIP terminal in the sensing region and whether the mobile user subscribes to an SIP service provider.

26. The SIP-based user mobility service providing apparatus of claim 22, wherein the sensing management module further comprises:

a management information database to store SIP registration related information including mobile user information and information on the first SIP terminal.

27. The SIP-based user mobility service providing apparatus of claim 22, wherein the information managing unit comprises:

a user/marker mapping manager to manage mapping an ID of the first marker to a URI (uniform resource identifier) of the mobile user;

a terminal information manager to manage information on the first SIP terminal in the sensing region; and an active user manager to manage active information of the mobile user in the specific region.

28. The SIP-based user mobility service providing apparatus of claim 22, wherein the SIP service supporting unit comprises:

an SIP user registration/cancellation proxy unit to generate an SIP registration message for the first SIP terminal in the sensing region according to SIP registration related information, and to transmit the SIP registration message to the SIP proxy server to perform SIP registration; and

an SIP user registration/cancellation notifying unit to notify the first SIP terminal if SIP registration is complete through the SIP user registration/cancellation proxy unit.

29. The SIP-based user mobility service providing apparatus of claim 22, wherein the interface unit comprises:

a sensing receiver interface to provide an interface with the sensing part;

an SIP proxy server interface to provide an interface with the SIP proxy server;

an SIP terminal interface to provide an interface with the first SIP terminal; and

an operator interface to provide an interface with the operator terminal.

30. An SIP (session initiation protocol)-based user mobility service providing method using an SIP -based user mobility providing apparatus that is connected to an SIP-based IP multimedia service network to provide a mobile user with an SIP service, the method comprising:

15

- a) converting a first SIP terminal in a sensing region to an available state if a mobile user who is authorized to use the SIP service enters the sensing region;
- b) receiving a call using the first SIP terminal having the same capability as a previously set second SIP terminal on the basis of a preference of the mobile user among several SIP terminals in an available state in the sensing region; and
- generating an SIP deregistration message for the first SIP terminal, and transmitting the SIP deregistration message to the SIP proxy server to cancel SIP registration if the mobile user departs the sensing region, wherein converting the first SIP terminal further comprises:
- determining that the mobile user enters the sensing region based on a recognition of a first marker corresponding to the mobile user; and
- generating an SIP registration message for the first SIP terminal in the sensing region, and transmitting the SIP registration message to an SIP proxy server to carry out SIP registration for the first SIP terminal if the mobile user enters the sensing region.
31. An SIP (session initiation protocol)-based user mobility service providing method using an SIP-based user mobility providing apparatus that is connected to an SIP-based IP multimedia service network to provide a mobile user with an SIP service, the method comprising:
- a) converting a first SIP terminal in a sensing region to an available state if a mobile user who is authorized to use the SIP service enters the sensing region;

16

- b) receiving a call using the first SIP terminal having the same capability as a previously set second SIP terminal on the basis of a preference of the mobile user among several SIP terminals in an available state in the sensing region; and
- determining whether the mobile user is authorized to use the first SIP terminal in the sensing region and whether the mobile user is authorized to use the SIP service if the mobile user enters the specific region before converting the first SIP terminal in the sensing region to the available state,
- wherein converting the first SIP terminal further comprises:
- determining that the mobile user enters the sensing region based on a recognition of a first marker corresponding to the mobile user; and
- generating an SIP registration message for the first SIP terminal in the sensing region, and transmitting the SIP registration message to an SIP proxy server to carry out SIP registration for the first SIP terminal if the mobile user enters the sensing region.
32. The SIP-based user mobility service providing method of claim 31, further comprising:
- periodically determining whether the mobile user is arranged in the sensing region after SIP registration is complete.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : RE42,996 E
APPLICATION NO. : 12/612327
DATED : December 6, 2011
INVENTOR(S) : Eun-Hee Hyun et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 1, line 16, insert -- More than one reissue application has been filed for the reissue of Patent No. 7,292,561. The reissue applications include application number 12/612,327, filed on November 4, 2009 and issued as RE42,966 (the present application), and application number 13/300,799, filed on November 21, 2011, which is a continuation reissue application of Patent No. 7,292,561. --.

Signed and Sealed this
Fourteenth Day of February, 2012

A handwritten signature in black ink that reads "David J. Kappos". The signature is written in a cursive, slightly slanted style.

David J. Kappos
Director of the United States Patent and Trademark Office