

US00RE43070E

(19) **United States**
(12) **Reissued Patent**
Henrie

(10) **Patent Number: US RE43,070 E**
(45) **Date of Reissued Patent: Jan. 3, 2012**

(54) **IDENTIFYING AND LOCATING LOST OR STOLEN PERSONAL DIGITAL ASSISTANT DEVICES VIA A LANDLINE- OR WIRELESS-CONNECTED WEB SERVER**

FOREIGN PATENT DOCUMENTS

EP 1130512 1/2001
(Continued)

(75) Inventor: **James B. Henrie**, Schaumburg, IL (US)

OTHER PUBLICATIONS

(73) Assignee: **Hewlett-Packard Development Company, L.P.**, Houston, TX (US)

US Office Action for U.S. Appl. No. 11/560,040, mail date Jan. 8, 2010, 20 pages.

(21) Appl. No.: **11/546,488**

(Continued)

(22) Filed: **Oct. 10, 2006**

Primary Examiner — Phuoc Nguyen
Assistant Examiner — Adam Cooney

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,804,699**
Issued: **Oct. 12, 2004**
Appl. No.: **09/618,406**
Filed: **Jul. 18, 2000**

(57) **ABSTRACT**

A system and method for preventing unauthorized use of a device (e.g., a portable computer system) and for recovering the device when, for example, the device has been lost or stolen and an attempt to use it is made by someone other than an authorized user. The authorized user registers the device in a database at a central site (e.g., a Web site) using a unique identifier such as the device's serial number. If the device is lost or stolen, this information is entered into the Web site database by the authorized user. When the device is connected to the Internet using either a wireless or a landline connection, the device automatically communicates its unique identity to the Web site. The Web site performs a lookup and, if the database indicates that the device is lost or stolen, the device is so notified. In response, the device disables normal operation and instead will display, for example, the name and address of the authorized user. Other security measures can be used depending on the preferences of the authorized user; for example, the Web site can initiate a trace to locate the device. Thus, when a device is lost or stolen, it can be more readily recovered and, in the meantime, unauthorized use is prevented.

(51) **Int. Cl.**
G06F 15/16 (2006.01)

(52) **U.S. Cl.** **709/224; 709/203; 726/2; 455/410**

(58) **Field of Classification Search** **709/203, 709/224; 726/4; 455/410**

See application file for complete search history.


(56) **References Cited**

U.S. PATENT DOCUMENTS

4,956,769	A	9/1990	Smith
5,010,547	A	4/1991	Johnson et al.
5,012,219	A	4/1991	Henry
5,075,684	A	12/1991	DeLuca
5,359,317	A	10/1994	Gomez et al.
5,394,140	A	2/1995	Wong et al.
5,430,436	A	7/1995	Fennell
5,561,836	A	10/1996	Sowles et al.
5,612,682	A	3/1997	DeLuca et al.
5,640,452	A	6/1997	Murphy

(Continued)

2 Claims, 14 Drawing Sheets



US RE43,070 E

Page 2

U.S. PATENT DOCUMENTS			FOREIGN PATENT DOCUMENTS		
5,650,776	A	7/1997 Mitchell et al.	2003/0061166	A1	3/2003 Saito et al.
5,705,995	A	1/1998 Laffin et al.	2003/0084005	A1	5/2003 Wong et al.
5,757,271	A	5/1998 Andrews	2003/0097586	A1	5/2003 Mok
5,809,413	A *	9/1998 Meche et al. 455/411	2003/0103464	A1	6/2003 Wong et al.
5,898,783	A *	4/1999 Rohrbach 340/5.31	2003/0139175	A1	7/2003 Kim
5,903,852	A	5/1999 Schaupp, Jr. et al.	2003/0157947	A1	8/2003 Fiatal et al.
5,922,073	A	7/1999 Shimada	2004/0003266	A1	1/2004 Moshir et al.
5,930,801	A	7/1999 Falkenhainer et al.	2004/0044791	A1	3/2004 Pouzzner
5,958,006	A	9/1999 Eggleston et al.	2004/0250069	A1	12/2004 Kosamo
5,961,590	A	10/1999 Mendez et al.	2005/0005131	A1	1/2005 Yoshida et al.
5,968,131	A	10/1999 Mendez et al.	2005/0073389	A1	4/2005 Chandley
5,991,405	A	11/1999 Mills	2005/0102257	A1	5/2005 Onyon et al.
6,023,708	A	2/2000 Mendez et al.	2005/0191998	A1	9/2005 Onyon et al.
6,084,968	A	7/2000 Kennedy et al.	2006/0025071	A1	2/2006 Yamazaki et al.
6,085,192	A	7/2000 Mendez et al.	2006/0031541	A1	2/2006 Koch et al.
6,130,947	A	10/2000 Mizobe et al.	2006/0059253	A1	3/2006 Goodman et al.
6,131,096	A	10/2000 Ng et al.	2006/0084410	A1	4/2006 Sutaria et al.
6,131,116	A	10/2000 Riggins et al.	2006/0149794	A1	7/2006 Ylinen
6,151,606	A	11/2000 Mendez	2006/0173954	A1	8/2006 Maeda et al.
6,157,630	A	12/2000 Adler et al.	2006/0184591	A1	8/2006 Backholm et al.
6,202,070	B1	3/2001 Nguyen et al.	2006/0234679	A1	10/2006 Matsumoto et al.
6,208,991	B1	3/2001 French et al.	2007/0129058	A1	6/2007 Landschaft et al.
6,233,341	B1	5/2001 Riggins	2007/0157319	A1	7/2007 Kammer et al.
6,246,376	B1	6/2001 Bark et al.	2007/0238443	A1	10/2007 Richardson
6,269,456	B1	7/2001 Hodges et al.	2008/0114855	A1	5/2008 Welingkar et al.
6,300,863	B1	10/2001 Cotichini et al.	2008/0115152	A1	5/2008 Welingkar et al.
6,308,273	B1	10/2001 Goertzel et al.	2008/0115226	A1	5/2008 Welingkar et al.
6,327,584	B1	12/2001 Xian et al.	2008/0125102	A1	5/2008 Abel et al.
6,333,684	B1	12/2001 Kang			
6,360,252	B1	3/2002 Rudy et al.	EP	1130511	9/2001
6,362,736	B1	3/2002 Gehlot	EP	1130513	9/2001
6,366,912	B1	4/2002 Wallent et al.	EP	1158438	11/2001
6,370,629	B1	4/2002 Hastings et al.	EP	1180890	2/2002
6,504,480	B1	1/2003 Magnuson et al.	EP	1187421	3/2002
6,542,729	B1	4/2003 Chmaytelli et al.	EP	1215597	6/2002
6,587,684	B1	7/2003 Hsu et al.	EP	0996905	5/2006
6,636,175	B2	10/2003 Russell et al.	EP	1667042	6/2006
6,662,023	B1 *	12/2003 Helle 455/558	JP	2000-89995	10/2001
6,671,757	B1	12/2003 Multer et al.	JP	2001-356948	12/2001
6,677,858	B1 *	1/2004 Faris et al. 709/203	JP	2001-356949	12/2001
6,694,336	B1	2/2004 Multer et al.	JP	2001-356950	12/2001
6,708,221	B1	3/2004 Mendez et al.	JP	2002-149464	5/2002
6,732,176	B1	5/2004 Stewart et al.	JP	2002-163137	6/2002
6,738,789	B2	5/2004 Multer et al.	JP	2003-006074	1/2003
6,757,696	B2	6/2004 Multer et al.	JP	2002-49515	9/2003
6,766,454	B1	7/2004 Riggins	WO	WO 98/26344	6/1998
6,778,837	B2	8/2004 Bade et al.	WO	WO 99/05620	2/1999
6,801,777	B2	10/2004 Rusch	WO	WO 99/05813	2/1999
6,804,699	B1	10/2004 Henrie	WO	WO 99/06900	2/1999
6,813,503	B1	11/2004 Zillikens et al.	WO	WO 99/36870	7/1999
6,842,695	B1	1/2005 Tu	WO	WO 00/11567	3/2000
6,892,225	B1	5/2005 Tu et al.	WO	WO 00/11832	3/2000
6,898,628	B2	5/2005 Bade et al.	WO	WO 00/20994	4/2000
6,925,476	B1	8/2005 Multer et al.	WO	WO 01/13572	2/2001
6,931,130	B1	8/2005 Kraft et al.	WO	WO 01/22259	3/2001
6,934,767	B1	8/2005 Jellinek	WO	WO 01/22288	3/2001
6,944,651	B2	9/2005 Onyon et al.	WO	WO 01/22290	3/2001
6,961,567	B1	11/2005 Kuhn	WO	WO 01/22291	3/2001
6,970,418	B1	11/2005 Skinner	WO	WO 01/71539	9/2001
6,970,927	B1	11/2005 Stewart et al.	WO	WO 02/06963	1/2002
7,003,668	B2	2/2006 Berson et al.	WO	WO 02/06964	1/2002
7,007,041	B2	2/2006 Multer et al.	WO	WO 02/06970	1/2002
7,035,878	B1	4/2006 Multer et al.	WO	WO 02/37728	5/2002
7,039,679	B2	5/2006 Mendez et al.	WO	WO 02/37749	5/2002
7,051,196	B2	5/2006 Angelo et al.	WO	WO 03/036520	5/2003
7,080,402	B2	7/2006 Bates et al.	WO	WO 03/044698	5/2003
7,116,977	B1	10/2006 Moton et al.	WO	WO 03/058483	7/2003
7,239,346	B1 *	7/2007 Priddy 348/220.1	WO	WO 03/058879	7/2003
7,343,165	B2	3/2008 Obradovich	WO	WO 2004/015576	2/2004
7,591,020	B2	9/2009 Kammer et al.	WO	WO 2004/095796	11/2004
7,603,435	B2	10/2009 Welingkar et al.	WO	WO 2004/095806	11/2004
2001/0013098	A1 *	8/2001 Angelo et al. 713/200	WO	WO 2005/010715	2/2005
2001/0047272	A1	11/2001 Frietas et al.	WO	WO 2005/048038	5/2005
2002/0065074	A1	5/2002 Cohn et al.	WO	WO 2005/086662	9/2005
2002/0138632	A1	9/2002 Bade et al.	WO	WO 2005/112586	12/2005
2002/0141095	A1	10/2002 Yahiro	WO	WO 2006/045005	4/2006
2002/0176579	A1	11/2002 Deshpande et al.	WO	WO 2006/045102	4/2006
2002/0183038	A1	12/2002 Comstock et al.	WO	WO 2006/053952	5/2006

US RE43,070 E

Page 3

WO	WO 2006/053954	5/2006
WO	WO 2006/058967	6/2006
WO	WO 2006/061463	6/2006
WO	WO 2006/070071	7/2006
WO	WO 2008/060920	5/2008

OTHER PUBLICATIONS

U.S. Appl. No. 11/635,062, filed Dec. 5, 2006, Henrie.
International Search Report and Written Opinion for International Application No. PCT/US2007/083943, mail date Aug. 19, 2008, 7 pages.
Office Action for U.S. Appl. No. 11/560,048, date mailed Mar. 6, 2009, 9 pages.
Response to Office Action for U.S. Appl. No. 11/635,062, date mailed Dec. 5, 2006, 7 pages.
Response to Office Action for U.S. Appl. No. 11/560,048, date mailed Jun. 8, 2009, 11 pages.

US Notice of Allowance for U.S. Appl. No. 11/560,048, mail date Jul. 28, 2009, 4 pages.
US Office Action for U.S. Appl. No. 11/560,040, mail date May 8, 2009, 24 pages.
Office Action for U.S. Appl. No. 11/634,371, mail date Sep. 16, 2009, 17 pages.
Advisory Action for U.S. Appl. No. 11/634,371, mail date Jun. 18, 2010, 4 pages.
Office Action for U.S. Appl. No. 11/634,371, mail date Mar. 25, 2010, 16 pages.
Office Action for U.S. Appl. No. 11/635,062, mail date Apr. 22, 2010, 6 pages.
Office Action for U.S. Appl. No. 11/560,040, mail date May 24, 2010, 24 pages.

* cited by examiner




FIGURE 1A




FIGURE 1B




FIGURE 1C




FIGURE 1D




FIGURE 1E




FIGURE 1F

100a




FIGURE 2

100b




FIGURE 3




FIGURE 4

100

100




FIGURE 5

60




FIGURE 6

342




FIGURE 7

340




FIGURE 8




FIGURE 9

100




FIGURE 10

**IDENTIFYING AND LOCATING LOST OR
STOLEN PERSONAL DIGITAL ASSISTANT
DEVICES VIA A LANDLINE- OR
WIRELESS-CONNECTED WEB SERVER**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

Notice: More than one reissue application has been filed for the reissue of U.S. Pat. No. 6,804,699. The reissue applications are application Ser. No. 11/546,488 (the present application), filed Oct. 10, 2006, which is a reissue application of U.S. Pat. No. 6,804,699; and application Ser. No. 11/635,062, filed Dec. 5, 2006, which is a reissue application of U.S. Pat. No. 6,804,699 and a continuation reissue application of application Ser. No. 11/546,488.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to the field of portable devices such as personal digital assistants or palmtop computer systems. Specifically, the present invention relates to a method and system for preventing unauthorized use of a portable device and for facilitating recovery of the portable device if it is lost or stolen.

2. Related Art

As the components required to build a computer system have reduced in size, new categories of computer systems have emerged. One of the more recent categories of computer systems is the portable or "palmtop" computer system, or personal digital assistant (PDA). A palmtop computer system is a computer that is small enough to be held in the hand of a user and is thus "palm-sized." As a result, palmtops are readily carried about in a briefcase or purse, and some palmtops are compact enough to fit into a person's pocket. By virtue of their size, palmtop computer systems are also lightweight and so are exceptionally portable and convenient.

On the other hand, because they are relatively small, palmtop computer systems can be easily lost or stolen. Although they are not extremely expensive, palmtops are expensive enough to make them attractive to thieves. To the owner of a palmtop, not only is there a monetary loss if the device is lost or stolen, but the information stored on the palmtop may be very valuable and possibly irreplaceable. Consequently, it is desirable to discourage theft of palmtop computer systems and to encourage their return to their rightful owners when they are lost or stolen.

In addition, it is desirable to prevent use of the palmtop if it is not in the possession of an authorized user. Importantly, this may discourage deliberate acts such as theft if it is known beforehand that the palmtop can only be used by an authorized user. Of further importance, this can prevent information stored on the palmtop from being accessed by someone other than an authorized user.

In the prior art, one method for protecting against unauthorized use of a computer system or against unauthorized access to information stored in a computer system is to use a password. However, passwords are considered by many users to be vexing and inconvenient, passwords can lock out even an authorized user, and experience shows that passwords can be defeated by unauthorized users. In addition, while a password may prevent access to applications and information already

existing on the palmtop, it will generally not prevent an unauthorized user from adding new applications and information. Thus, an unauthorized user can simply assume ownership of the palmtop and ignore the password-protected information.

SUMMARY OF THE INVENTION

Accordingly, what is needed is a system and/or method that can discourage theft of a device such as a palmtop computer system or personal digital assistant (PDA), and that can encourage return of the device to the rightful owner if it is lost or stolen. What is also needed is a system and/or method that can satisfy the above need and that can prevent use of the device and unauthorized access to information stored on the device if it is not in the possession of an authorized user. In addition, what is needed is a system and/or method that can satisfy the above needs and that is user-friendly and convenient. The present invention provides these advantages and others not specifically mentioned above but described in the sections to follow.

A method and system are described for preventing unauthorized use of a device (e.g., a palmtop computer system or PDA) and for facilitating recovery of the device when, for example, the device has been lost or stolen and an attempt to use it is made by someone other than an authorized user. The authorized user registers the device in a database at a central site using a unique identifier for the device. If the device is lost or stolen, the authorized user records this in the central site database. When the device is connected to the central site using either a wireless or a landline connection, the device automatically communicates its unique identity to the site. The central site performs a lookup based on the unique identity and, if the database indicates that the device is lost or stolen, the device is so notified. In response, the device automatically disables normal operation.

In another embodiment, instead of notifying the device that it is lost or stolen, the device is notified that it is not lost or stolen and its use is authorized. In this embodiment, operation of the device is automatically enabled when the central site indicates that use of the device is authorized. This feature can also be used to re-enable a device that was reported as lost or stolen and disabled as a result, and then was recovered by its authorized user.

In one embodiment, the central site is a World Wide Web site residing on a server computer system in a computer system network (e.g., the Internet).

In one embodiment, when disabled, the device displays information that can be used to identify and contact the authorized user, such as the user's name and address. In other embodiments, other security measures can be used depending on the preferences of the authorized user. In one of these embodiments, the Web site can initiate a trace to locate the device. In another embodiment, if the device does not make contact with the central site for a specified period of time, operation of the device is automatically disabled.

Thus, in accordance with the present invention, when a device is lost or stolen, it can be more readily recovered and, in the meantime, unauthorized use of the device is prevented. Each time the device is connected to the Internet, the device automatically checks a Web site to determine if it is lost or stolen. If the device is reported as lost or stolen, the device will be disabled to prevent normal operation. While in the disabled mode, the device can display information on how to contact the authorized user, or the Web site can initiate a trace to find the location of the device.

In accordance with the present embodiment of the present invention, these security measures can be automatically

implemented in the background without a user knowing they are occurring, and thus they are convenient and user-friendly. In addition, once it is understood that unauthorized use will cause the device to be disabled and thus of little use to an unauthorized user, the likelihood of theft of the device is expected to decrease, and the likelihood of its return to the rightful owner is expected to increase.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a block diagram of an exemplary network environment including a portable computer system in accordance with one embodiment of the present invention.

FIGS. 1B, 1C, 1D, 1E and 1F are block diagrams showing various embodiments for coupling a portable computer system to other computer systems and to the Internet in accordance with the present invention.

FIG. 2 is a top side perspective view of a portable computer system in accordance with one embodiment of the present invention.

FIG. 3 is a bottom side perspective view of the portable computer system of FIG. 2.

FIG. 4 is an exploded view of the components of the portable computer system of FIG. 2.

FIG. 5 is a block diagram of one embodiment of a portable computer system in accordance with the present invention.

FIG. 6 is a perspective view of the cradle device for connecting the portable computer system to other systems via a communication interface in accordance with one embodiment of the present invention.

FIG. 7 is a block diagram of one embodiment of a server, desktop or laptop computer system in accordance with the present invention.

FIG. 8 is a block diagram of a one embodiment of a system for allowing a portable computer system and another computer system to share information in accordance with the present invention.

FIG. 9 is a flowchart showing the steps in a process for preventing unauthorized use of a portable device and for facilitating recovery of a portable device in accordance with one embodiment of the present invention.

FIG. 10 illustrates an exemplary display of contact information in a portable computer system in accordance with one embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description of the present invention, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be recognized by one skilled in the art that the present invention may be practiced without these specific details or with equivalents thereof. In other instances, well known methods, procedures, components, and circuits have not been described in detail as not to unnecessarily obscure aspects of the present invention.

Notation and Nomenclature

Some portions of the detailed descriptions, which follow, are presented in terms of procedures, steps, logic blocks, processing, and other symbolic representations of operations on data bits that can be performed on computer memory. These descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. A procedure, computer executed step, logic block, process,

etc., is here, and generally, conceived to be a self-consistent sequence of steps or instructions leading to a desired result. The steps are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated in a computer system. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the following discussions, it is appreciated that throughout the present invention, discussions utilizing terms such as “determining” or “indicating” or “indexing” or “receiving” or “performing” or “initiating” or “sending” or “implementing” or “disabling” or “enabling” or “displaying” or the like, refer to the action and processes of a computer system (e.g., process 900 of FIG. 9), or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

The present invention is discussed primarily in the context of a portable computer system, such as a palmtop or personal digital assistant, with the capability to access via the Internet a World Wide Web (“Web”) site residing on a server computer system. However, it is appreciated that the present invention can be used with other types of devices that have the capability to access some type of central device or central site, including but not limited to laptop computer systems.

Exemplary Palmtop Platform

FIG. 1A is a block diagram of an exemplary network environment 50 including a portable computer system 100 in accordance with one embodiment of the present invention. Portable computer system 100 is also known as a palmtop or palm-sized computer system or as a personal digital assistant (PDA). In one embodiment, portable computer system 100 has the ability to transmit and receive data and information over a wireless communication interface (e.g., a radio interface). In one embodiment, the wireless communication interface is integrated into portable computer system 100; in another embodiment, the wireless communication interface is accomplished with a wireless modem attachment (not shown).

In the present embodiment, base station 32 is both a transmitter and receiver base station, which can be implemented by coupling it into an existing public telephone network 34. Implemented in this manner, base station 32 enables portable computer system 100 to communicate with a proxy server computer system 36, which is coupled by wire to the existing public telephone network 34. Furthermore, proxy server computer system 36 is coupled to the Internet 52, thereby enabling portable computer system 100 to communicate with the Internet 52.

Coupled with Internet 52 are multiple servers exemplified by server 30. Residing on server 30 is a Web site 40. When communicating with a Web site over Internet 52, protocols such as CTP (Compact Transport Protocol) and CML (Compact Markup Language) can be used by portable computer system 100 in the present embodiment.

5

It should be appreciated that within the present embodiment, one of the functions of proxy server 36 is to perform operations over the Internet 52 on behalf of portable computer system 100. For example, proxy server 36 has a particular Internet address and acts as a proxy device for portable computer system 100 over the Internet 52.

It should be further appreciated that other embodiments of a communications network, planned or envisioned, may be utilized in accordance with the present invention. For example, a wireless connection may be made from portable computer system 100 directly to the Internet 52.

The data and information which are communicated between base station 32 and portable computer system 100 are the same type of information and data that can conventionally be transferred and received over a public telephone wire network system. However, a wireless communication interface is utilized to communicate data and information between portable computer system 100 and base station 32. It should be appreciated that one embodiment of a wireless communication system in accordance with the present invention is the Mobitex wireless communication system.

FIGS. 1B, 1C, 1D, 1E and 1F are block diagrams showing various embodiments of a system 51 for coupling a portable computer system 100 to other computer systems and to the Internet 52 in accordance with the present invention. System 51 is described in the context of wired connections between its various devices and components; however, it is appreciated that wireless connections (such as but not limited to Bluetooth wireless connections) can also be used.

With reference first to FIG. 1B, system 51 comprises a host computer system 56 which can either be a desktop unit as shown, or, alternatively, can be a laptop system 58. Optionally, one or more host computer systems can be used within system 51. Host computer systems 58 and 56 are shown connected to a communication bus 54 such as an Ethernet Local Area Network (LAN), but which can instead be any of a number of other types. Bus 54 can provide communication with the Internet 52 using a number of well-known protocols. Coupled with Internet 52 are multiple servers exemplified by server 30. Residing on server 30 is a Web site 40.

Importantly, in the present embodiment, host computer system 56 is also coupled via connector cable 68 to a cradle 60 for receiving and initiating communication with portable computer system 100 ("handheld computer") of the present invention. Connector cable 68 can be a serial bus (e.g., RS232), a parallel bus, a Universal Serial Bus (USB), or any other type of workable connection. Cradle 60 provides an electrical and mechanical communication interface between connector cable 68 and portable computer system 100 for two-way communications with host computer system 56. Portable computer system 100 also contains a wireless infrared communication mechanism 64 for sending and receiving information from other devices.

With reference next to FIG. 1C, in this embodiment, laptop system 58 is coupled via connector cable 68 to cradle 60. As described above, connector cable 68 can be a serial bus (e.g., RS232), a parallel bus, a USB, or any other type of workable connection for enabling two-way communication between portable computer system 100 and laptop system 58.

FIG. 1D shows another embodiment of system 51 in accordance with the present invention. In this embodiment, host computer system 56 is coupled via connector cable 68 to cradle 60. Host computer system 56 is also coupled to a modem 76 via another connector cable 78. Connector cable 78 can be a serial bus, a parallel bus, a USB, or any other type of workable connection that can be used for allowing two-way communication between host computer system 56 and

6

the Internet 52. In this embodiment, connector cable 78 is coupled with a wire line 74 to a central office (or cable office, etc.) 81 via modem 76. Modem 76 can be internal to or external to host computer system 56. Modem 76 can be an analog modem, a cable modem, an ADSL (Asymmetric Digital Subscriber Line) modem, or any other such device. Central office 81 in turn is communicatively coupled to the Internet 52 via some type of well-known communication line 84.

FIG. 1E shows another embodiment of system 51 in accordance with the present invention. In this embodiment, laptop system 58 is coupled via connector cable 68 to cradle 60. Laptop system 58 is also coupled to modem 76 via connector cable 78. In this embodiment, connector cable 78 is coupled with wire line 74 to central office 81 via modem 76. Central office 81 in turn is communicatively coupled to the Internet 52 via communication line 84.

FIG. 1F shows another embodiment of system 51 in accordance with the present invention. In this embodiment, portable computer system 100 is coupled with wire line 74 via a modem 82. In one embodiment, portable computer system 100 is a Palm V or other such PDA, and modem 82 is a Palm V modem or PDA modem. Wire line 74 is communicatively coupled to central office 81 which in turn is communicatively coupled to the Internet 52 via communication line 84.

With reference to FIGS. 1A through 1F, it is appreciated that portable computer system 100 can be used in a network environment combining elements of networks 50 and 51. That is, as will be seen below, portable computer system 100 can include both a wireless infrared communication mechanism and a signal (e.g., radio) receiver/transmitter device.

FIG. 2 is a perspective illustration of the top face 100a of one embodiment of the palmtop computer system 100 of the present invention. The top face 100a contains a display screen 105 surrounded by a bezel or cover. A removable stylus 80 is also shown. The display screen 105 is a touch screen able to register contact between the screen and the tip of the stylus 80. The stylus 80 can be of any material to make contact with the screen 105. The top face 100a also contains one or more dedicated and/or programmable buttons 75 for selecting information and causing the computer system to implement functions. The on/off button 95 is also shown.

FIG. 2 also illustrates a handwriting recognition pad or "digitizer" containing two regions 106a and 106b. Region 106a is for the drawing of alphabetic characters therein (and not for numeric characters) for automatic recognition, and region 106b is for the drawing of numeric characters therein (and not for alphabetic characters) for automatic recognition. The stylus 80 is used for stroking a character within one of the regions 106a and 106b. The stroke information is then fed to an internal processor for automatic character recognition. Once characters are recognized, they are typically displayed on the screen 105 for verification and/or modification.

FIG. 3 illustrates the bottom side 100b of one embodiment of the palmtop computer system that can be used in accordance with various embodiments of the present invention. An extendible antenna 85 is shown, and also a battery storage compartment door 90 is shown. A communication interface 180 is also shown. In one embodiment of the present invention, the communication interface 180 is a serial communication port, but could also alternatively be of any of a number of well-known communication standards and protocols, e.g., parallel, SCSI (small computer system interface), Firewire (IEEE 1394), Ethernet, etc.

FIG. 4 is an exploded view of the palmtop computer system 100 in accordance with one implementation. Computer system 100 contains a back cover 245, and a front cover 210 having an outline of region 106 and holes 75a for receiving

buttons 75b. A flat panel display 105 (both liquid crystal display and touch screen) fits into front cover 210. Any of a number of display technologies can be used, e.g., liquid crystal display (LCD), field emission display (FED), plasma, etc., for the flat panel display 105. A battery 215 provides electrical power. A contrast adjustment (potentiometer) 220 is also shown, as well as an on/off button 95. A flex circuit 230 is shown along with a printed circuit (PC) board 225 containing electronics and logic (e.g., memory, communication bus, processor, etc.) for implementing computer system functionality. The digitizer pad is also included in PC board 225. A mid-frame 235 is shown along with stylus 80. Position-adjustable antenna 85 is shown.

Infrared communication mechanism 64 (e.g., an infrared emitter and detector device) is for sending and receiving information from other similarly equipped devices (see FIG. 1B). A signal (e.g., radio) receiver/transmitter device 108 is also shown. The receiver/transmitter device 108 is coupled to the antenna 85 and also coupled to communicate with the PC board 225. In one implementation the Mobitex wireless communication system is used to provide two-way communication between computer system 100 and other networked computers and/or the Internet via a proxy server (see FIG. 1A).

FIG. 5 illustrates circuitry of computer system 100, some of which can be implemented on PC board 225 (FIG. 4). Computer system 100 includes an address/data bus 110 for communicating information, a central processor 101 coupled with the bus for processing information and instructions, a volatile memory 102 (e.g., random access memory, RAM) coupled with the bus 110 for storing information and instructions for the central processor 101 and a non-volatile memory 103 (e.g., read only memory, ROM) coupled with the bus 110 for storing static information and instructions for the processor 101. Computer system 100 also includes an optional data storage device 104 (e.g., memory stick) coupled with the bus 110 for storing information and instructions. Device 104 can be removable. As described above, computer system 100 also contains a display device 105 coupled to the bus 110 for displaying information to the computer user. PC board 225 can contain the processor 101, the bus 110, the ROM 103 and the RAM 102.

With reference still to FIG. 5, computer system 100 also includes a signal transmitter/receiver device 108, which is coupled to bus 110 for providing a physical communication link between computer system 100, and a network environment (e.g., network environments 50 and 51 of FIGS. 1A through 1F). As such, signal transmitter/receiver device 108 enables central processor unit 101 to communicate wirelessly with other electronic systems coupled to the network. It should be appreciated that within the present embodiment, signal transmitter/receiver device 108 is coupled to antenna 85 (FIG. 4) and provides the functionality to transmit and receive information over a wireless communication interface. It should be further appreciated that the present embodiment of signal transmitter/receiver device 108 is well suited to be implemented in a wide variety of ways. For example, signal transmitter/receiver device 108 could be implemented as a modem.

In one embodiment, computer system 100 includes a communication circuit 109 coupled to bus 110. Communication circuit 109 includes an optional digital signal processor (DSP) 120 for processing data to be transmitted or data that are received via signal transmitter/receiver device 108. Alternatively, processor 101 can perform some or all of the functions performed by DSP 120.

Also included in computer system 100 of FIG. 5 is an optional alphanumeric input device 106 that in one imple-

mentation is a handwriting recognition pad ("digitizer") having regions 106a and 106b (FIG. 2), for instance. Alphanumeric input device 106 can communicate information and command selections to processor 101. Computer system 100 also includes an optional cursor control or directing device (on-screen cursor control 107) coupled to bus 110 for communicating user input information and command selections to processor 101. In one implementation, on-screen cursor control device 107 is a touch screen device incorporated with display device 105. On-screen cursor control device 107 is capable of registering a position on display device 105 where the stylus makes contact. The display device 105 utilized with computer system 100 may be a liquid crystal display device, a cathode ray tube (CRT), a field emission display device (also called a flat panel CRT) or other display device suitable for generating graphic images and alphanumeric characters recognizable to the user. In the preferred embodiment, display device 105 is a flat panel display.

FIG. 6 is a perspective illustration of one embodiment of the cradle 60 for receiving the palmtop computer system 100. Cradle 60 contains a mechanical and electrical interface 260 for interfacing with communication interface 108 (FIG. 3) of computer system 100 when system 100 is slid into the cradle 60 in an upright position. Once inserted, button 270 can be pressed to initiate two-way communication (e.g., a communication session) between computer system 100 and other computer systems coupled to serial communication 265.

Exemplary Desktop/Laptop/Server Platform

Refer now to FIG. 7 which illustrates an exemplary computer system 342 with which embodiments of the present invention may be practiced. Computer system 342 exemplifies desktop computer system 56 or laptop computer system 58 of FIG. 1B. Computer system 342 also exemplifies a server computer system in a computer system network (such as server 30 in FIGS. 1A through 1F) or a proxy server computer (e.g., proxy server 36 of FIG. 1A).

Continuing with reference to FIG. 7, in general, computer system 342 comprises bus 700 for communicating information, processor 701 coupled with bus 700 for processing information and instructions, random access (volatile) memory (RAM) 702 coupled with bus 700 for storing information and instructions for processor 701, read-only (non-volatile) memory (ROM) 703 coupled with bus 700 for storing static information and instructions for processor 701, data storage device 704 such as a magnetic or optical disk and disk drive coupled with bus 700 for storing information and instructions, an optional user output device such as display device 705 coupled to bus 700 for displaying information to the computer user, an optional user input device such as alphanumeric input device 706 including alphanumeric and function keys coupled to bus 700 for communicating information and command selections to processor 701, and an optional user input device such as cursor control device 707 coupled to bus 100 for communicating user input information and command selections to processor 701. Furthermore, an optional input/output (I/O) device 708 is used to couple computer system 342 to, for example, a communication bus (e.g., communication bus 54 of FIG. 1B).

Continuing with reference to FIG. 7, display device 705 utilized with computer system 342 may be a liquid crystal device, cathode ray tube, or other display device suitable for creating graphic images and alphanumeric characters recognizable to the user. Cursor control device 707 allows the computer user to dynamically signal the two-dimensional movement of a visible symbol (pointer) on a display screen of

display device **705**. Many implementations of the cursor control device are known in the art including a trackball, mouse, joystick or special keys on alphanumeric input device **706** capable of signaling movement of a given direction or manner of displacement. It is to be appreciated that the cursor control **707** also may be directed and/or activated via input from the keyboard using special keys and key sequence commands. Alternatively, the cursor may be directed and/or activated via input from a number of specially adapted cursor directing devices.

FIG. **8** illustrates a system **340** (also referred to as an "installer") in accordance with one embodiment of the present invention for allowing a portable computer system **100** (e.g., a palmtop or any portable computer system) to share information with another computer, e.g., a host computer system (e.g., desktop computer system **56** or laptop computer system **58** of FIG. **1B**). System **340** contains database **326**, a software file sharing manager **322** (e.g., a hot-sync software manager), a file link configuration database **324**, and a software conduit **320**. The file link configuration database **324** is linked to the file sharing manager **322** and specifies, for a particular database, its source file, category information, and the frequency of update for the database. Conduit **320** outlines the manner in which records are to be synchronized between databases under control of file sharing manager **322**. This process, including the file sharing manager and the conduit, is described in U.S. Pat. No. 5,884,323 by Hawkins et al., issued Mar. 16, 1999, assigned to the assignee of the present invention and hereby incorporated by reference.

With reference still to FIG. **8**, portable computer system **100** is interfaced with system **340** using cradle **60** (FIG. **1B**). Alternatively, portable computer system **100** can be interfaced with system **340** using a wireless (e.g., radio) connection. During synchronization between portable computer system **100** and database **326**, delta records **330a** and **330b** are passed through conduit **320** between database **326** and a database of portable computer system **100** under control of the file sharing manager **322**. Delta records **330a** and **330b** represent changes (including additions) that occurred on either portable computer system **100** or system **340**. After synchronization, these two databases will contain the same information. Namely, records updated on portable computer system **100** are reflected in database **326** and vice versa. The synchronization process (including the file sharing manager) is described in U.S. Pat. No. 6,006,274 by Hawkins et al., issued Dec. 21, 1999, assigned to the assignee of the present invention and hereby incorporated by reference. Synchronization is also described in U.S. Pat. No. 5,727,202 by Kucala, issued Mar. 10, 1998, assigned to the assignee of the present invention and hereby incorporated by reference, and also in U.S. Pat. No. 5,832,489 by Kucala, issued Nov. 3, 1998, assigned to the assignee of the present invention and hereby incorporated by reference.

Identifying and Locating Lost or Stolen Personal Digital Assistant Devices Viava Landline- or Wireless-connected Web Server

FIG. **9** is a flowchart showing the steps in a process **900** for preventing unauthorized use of a portable device (e.g., portable computer system **100** of FIGS. **1A** through **1F**) and for facilitating recovery of the portable device in accordance with one embodiment of the present invention.

In step **910** of FIG. **9**, in the present embodiment, the owner or an authorized user registers portable computer system **100** at a Web site on the Internet (e.g., Web site **40** on Internet **52** of FIGS. **1A** through **1F**). Web site **40** typically resides on a

server computer system (e.g., a "central device") as exemplified by server **30** of FIGS. **1A** through **1F**.

With reference still to FIG. **9**, portable computer system **100** can be registered in any number of ways using any Web site supporting the features of the present invention. In one embodiment, at about the time that portable computer system **100** is first acquired by the authorized user, the user can log onto Web site **40** and set up an account for portable computer system **100**. The account can be password-protected. The user logs onto the account using the password and enters a unique identifier for portable computer system **100**, such as the device's serial number.

In the present embodiment, the account is indexed using the unique identifier so that the account can be readily accessed using the unique identifier. The user can then enter preferences into the account pertaining to the security features of the present invention. For example, the security features can be enabled or disabled depending on user preferences.

In one embodiment, the user accesses Web site **40** to set up the account using portable computer system **100**. For example, portable computer system **100** can be registered using the synchronization process described in conjunction with FIG. **8**. In another embodiment, the user accesses Web site **40** using another device such as a personal computer. Web site **40** could also be configured to set up an account and receive information from the user via an automated telephone answering service.

In the present embodiment, Web site **40** is set up to support the features of the present invention. In one embodiment, in which portable computer system **100** is a palmtop computer such as a Palm III, a Palm V, or a Palm VII (or other such devices), Web site **40** can be a site such as Palm.net. In another embodiment, Web site **40** can be an Internet access conduit that is commonly available to users of portable devices, such as the AvantGo site. It is appreciated that the security features of the present invention will be desirable to users of portable devices, and as such a number of Web sites may find it advantageous to add such security features to the services they provide.

In step **915** of FIG. **9**, if there is a change in device status, then the user reports this to Web site **40** (step **920**). For example, if portable computer system **100** is lost or stolen, the user reports this to Web site **40**. Similarly, if the user has previously reported the device as lost or stolen, and it has since been recovered, the user can report this to Web site **40**. The user can report the loss or recovery to Web site **40** using a variety of methods, as described above.

In one embodiment, when the device is lost or stolen, the user accesses the account set up for portable computer system **100** at Web site **40** and enables the security features of the present invention by clicking on an input box to indicate that portable computer system **100** is lost or stolen. When the device is recovered, the user accesses the account at Web site **40** and disables the security features of the present invention by clicking on the input box, thereby indicating that portable computer system **100** is no longer lost or stolen.

In step **930** of FIG. **9**, when portable computer system **100** is connected to Internet **52** (FIGS. **1A** through **1F**), it automatically connects to Web site **40**. In the present embodiment, portable computer system **100** sends a signal to Web site **40** containing its unique identity (e.g., its serial number), thereby identifying itself to Web site **40**. In one embodiment, this connection is made in the background so that the user is not aware of the connection. As described above in conjunction with FIGS. **1A** through **1F**, the connection to Web site **40** can be via a wireless connection (including a wireless modem

11

attachment) or via a landline (wired) connection. In one embodiment, the connection to Web site 40 can be accomplished during the synchronization process described in conjunction with FIG. 8.

In step 940 of FIG. 9, in the present embodiment, a lookup is performed based on the unique identity received in step 930. That is, using the unique identity, the account information for portable computer system 100 is accessed at Web site 40. The lookup is performed to determine if the device is or is not lost or stolen, based on the user input (account information) provided in step 920 above.

In step 945, based on the account information, a determination is made with regard to whether or not portable computer system 100 is lost or stolen (based on the user input provided in step 920). If portable computer system 100 is not reported as lost or stolen, then Web site 40 sends a signal to the device indicating normal operation of the device is enabled (step 950), and normal operation of the device continues (step 955). It is understood that enabling normal operation can be a default setting such that, if no response is received to the signal of step 930, then portable computer system 100 will continue to operate normally.

Alternatively, Web site 40 can respond to portable computer system 100 with an indication that the device is not lost or stolen, where this indication is necessary in order for portable computer system 100 to operate normally. In one embodiment, the user can configure portable computer system 100 such that it is necessary for the device to make contact with Web site 40 on a periodic basis, at an interval specified according to user preferences. If the specified time period expires before portable computer system 100 connects with Web site 40, then the device is automatically disabled. For example, the authorized user could specify that portable computer system 100 is to connect with Web site 40 once per week, and if a week goes by without such a connection, then portable computer system 100 is disabled. If, at a later time, the authorized user attempts to use portable computer system 100, then portable computer system 100 can still be connected to Web site 40 (this capability remains even if the device is in the disabled or locked mode). After looking up the account information based on the unique identity of portable computer system 100 (step 945) to determine whether the device has been lost or stolen, Web site 40 sends a signal to the device that unlocks the device and enables normal operation. It is appreciated that other actions may need to be performed in order to re-enable operation of the device.

In step 960, if portable computer system 100 is reported as lost or stolen, then Web site 40 sends a signal to the device indicating that normal operation of the device is disabled. As described above, disabling operability of the device can be the result of a signal received from Web site 40 or it can be a default setting if no response is received to the signal of step 930. In addition, if portable computer system 100 has been reported as lost or stolen and has already been disabled in accordance with the present invention, it will continue to remain disabled as a result of this step. For example, if portable computer system 100 is in the locked mode, and no response is received in step 960, then it will continue to remain in the locked mode.

In step 965, in the disabled mode of operation (e.g. a locked mode), many (almost all) functions of portable computer system 100 cannot be used. In one embodiment, portable computer system 100 changes the configuration stored in flash memory (e.g., ROM 103 of FIG. 5) from normal operation to the disabled mode to prevent unauthorized use. By storing the configuration information for the locked mode in

12

flash memory, portable computer system 100 will remain locked even if its batteries are removed.

In one embodiment, information for identifying and contacting the authorized owner or user is displayed on display device 105 (FIG. 5) of portable computer system 100 when the device is in the disabled (locked) mode of operation; refer to FIG. 10. In other embodiments, other security measures can be implemented. For example, Web site 40 can initiate a trace in order to identify the location of portable computer system 100 or the phone number being used to connect with the Internet 52.

Once portable computer system 100 is recovered by the authorized user or rightful owner, it can be reset for normal operation. In one embodiment, a bootstrap reset would be required in order to allow the flash memory to be overwritten with the normal configuration information. In another embodiment, as described in conjunction with step 915, the authorized user can change the account information to indicate that the device is no longer lost or stolen. Accordingly, when portable computer system 100 is subsequently synchronized (per FIG. 8) and connected to Web site 40, operation can be enabled. It is appreciated that other actions may need to be performed in order to re-enable operation of the device.

FIG. 10 illustrates an exemplary display of contact information on display device 105 of portable computer system 100 (FIGS. 1A through 1F) in accordance with one embodiment of the present invention. In the present embodiment, the contact information is automatically displayed when portable computer system 100 is in the disabled mode as a result of being identified as lost or stolen. It is appreciated that the type and level of detail of the contact information displayed is input by the authorized user. It is further appreciated that the contact information can specify a central physical location to which portable computer system 100 can be returned, from which the device is forwarded to the authorized user.

In summary, in accordance with the present invention, when a device (e.g., a portable device such as portable computer system 100) is lost or stolen, it can be more readily recovered and, in the meantime, unauthorized use of the device is prevented. Each time the device is connected to the Internet, the device automatically checks a Web site to determine if it is lost or stolen. If the device is reported as lost or stolen, the device will be disabled to prevent normal operation. While in the disabled mode, the device can display contact information for the authorized user, or the Web site can initiate a trace to find the location of the device.

In accordance with the present embodiment of the present invention, these security measures can be automatically implemented in the background without a user knowing they are occurring, and thus they are convenient and user-friendly. In addition, once it is understood that unauthorized use will cause the device to be disabled and thus of little use to an unauthorized user, the likelihood of theft will probably decrease and the likelihood of return to the rightful owner will probably increase.

Thus, the present invention provides a system and method that can discourage theft of a device such as a portable (palm-top) computer system, PDA, laptop or other types of device, and that can encourage return of the device to the rightful owner if it is lost or stolen. The present invention also provides a system and method that can prevent use of the device if it is not in the possession of an authorized user and that can prevent unauthorized access to information stored on the device. In addition, the present invention provides a system and method that is user-friendly and convenient.

The preferred embodiment of the present invention, identifying and locating lost or stolen personal digital assistant

13

devices via a landline- or wireless-connected web server, is thus described. While the present invention has been described in particular embodiments, it should be appreciated that the present invention should not be construed as limited by such embodiments, but rather construed according to the below claims.

What is claimed is:

[1. A method for preventing unauthorized use of a device, said method comprising:

- a) receiving registration information for said device, wherein said registration information comprises a unique identity for said device;
- b) receiving a signal upon use of said device, wherein said signal comprises said unique identity;
- c) determining whether said use of said device is authorized based on said registration information and said unique identity; and
- d) sending a signal to said device to enable operation of said device provided said use is authorized, wherein absent said signal at least a portion of said device is disabled.]

[2. The method as recited in claim 1, wherein said method is implemented using a server computer system communicatively coupled to said device via the World Wide Web.]

[3. The method as recited in claim 1, wherein said device is a palmtop computer system.]

[4. The method as recited in claim 1 wherein said step a) comprises:

- receiving an indication that said device is to be disabled when said signal of said step b) is received; and
- indexing said indication using said unique identity for said device.]

5. [The method as recited in claim 1] *A method for preventing unauthorized use of a device, said method comprising:*

- a) receiving registration information for said device, wherein said registration information comprises a unique identity for said device;*
- b) receiving a signal upon use of said device, wherein said signal comprises said unique identity;*
- c) determining whether said use of said device is authorized based on said registration information and said unique identity; and*
- d) sending a signal to said device to enable operation of said device provided said use is authorized, wherein absent said sent signal at least a portion of said device is disabled,*

wherein said step a) *further* comprises:

- receiving an indication that said device is to be enabled when said signal of said step b) is received; and
- indexing said indication using said unique identity for said device.

6. [The method as recited in claim 1] *A method for preventing unauthorized use of a device, said method comprising:*

- a) receiving registration information for said device, wherein said registration information comprises a unique identity for said device;*
- b) receiving a signal upon use of said device, wherein said signal comprises said unique identity;*
- c) determining whether said use of said device is authorized based on said registration information and said unique identity; and*
- d) sending a signal to said device to enable operation of said device provided said use is authorized, wherein absent said sent signal at least a portion of said device is disabled,*

14

wherein said step c) *further* comprises:

- c1) indexing said registration information using said unique identity; and
- c2) performing a lookup of said registration information using said unique identity.

[7. The method as recited in claim 1 further comprising: e) initiating a trace to determine a location of said device.]

[8. In a portable device, a method for preventing unauthorized use of said portable device, said method comprising:

- a) sending a signal to a central device having a database comprising registration information for said portable device, wherein said signal comprises a unique identity for said portable device;
- b) receiving in response an indication of whether use of said portable device is authorized, wherein authorization is determined based on said registration information and said unique identity; and
- c) implementing an operating mode in response to said indication, wherein said step c) comprises:
 - c1) enabling operation of said portable device provided said use is authorized; and
 - c2) disabling operation of at least a portion of said portable device provided said use is not authorized.]

[9. The method as recited in claim 8 wherein said portable device is a palmtop computer system.]

[10. The method as recited in claim 8 wherein said central device is a server computer system communicatively coupled to said portable device via the World Wide Web.]

[11. The method as recited in claim 8 wherein said step c2) comprises:

- displaying information for identifying and contacting an authorized user.]

[12. The method as recited in claim 8 wherein said registration information is indexed using said unique identity and wherein said step b) comprises:

- performing a lookup of said registration information in said database using said unique identity.]

[13. The method as recited in claim 8 wherein further comprising the step of:

- d) disabling operation of said portable device when said signal of said step a) is not sent to said central device before a specified time period expires.]

[14. A system for preventing unauthorized use of a device, said system comprising:

- a central device having a database comprising registration information for said device; and
- a device communicatively coupled to said central device; wherein upon use of said device, said device operable to send to said central device a signal comprising a unique identity for said device;

wherein said central device is operable to determine whether said use of said device is authorized based on said registration information and said unique identity, and wherein said central device indicates to said device whether said use is authorized; and

wherein operation of said device is enabled provided said use is authorized and wherein at least a portion of said device is disabled provided said use is not authorized.]

[15. The system of claim 14 wherein said device is a palmtop computer system.]

[16. The system of claim 14 wherein said central device is a server computer system communicatively coupled to said device via the World Wide Web.]

[17. The system of claim 14 wherein said registration information comprises an indication that said device is to be disabled when said signal is received by said central device from said device.]

15

[18. The system of claim **14** wherein said registration information comprises an indication that said device is to be enabled when said signal is received by said central device from said device.]

[19. The system of claim **14** wherein said registration information is indexed using said unique identity.]

[20. The system of claim **14** wherein said device comprises a display device for displaying information for identifying and contacting an authorized user.]

16

[21. The system of claim **14** wherein operation of said device is disabled when said signal is not communicated by said device to said central device before a specified time period expires.]

[22. The system of claim **14** wherein said central device initiates a trace to determine a location of said device.]

* * * * *