

US00RE43139E

(19) **United States**  
(12) **Reissued Patent**  
**Lee**

(10) **Patent Number:** **US RE43,139 E**  
(45) **Date of Reissued Patent:** **Jan. 24, 2012**

(54) **APPARATUS AND METHOD OF INTERACTING WITH A MOBILE PHONE USING A TV SYSTEM**

6,781,635 B1 8/2004 Takeda  
6,825,858 B2 11/2004 Sato  
2002/0077143 A1 6/2002 Sharif et al.

**OTHER PUBLICATIONS**

(75) Inventor: **Jae Kyung Lee**, Daegu (KR)  
(73) Assignee: **LG Electronics Inc.**, Seoul (KR)  
(21) Appl. No.: **12/784,281**  
(22) Filed: **May 20, 2010**

Office Action dated Feb. 9, 2005.  
Office Action dated Oct. 6, 2005.  
Office Action dated Jun. 16, 2006.  
Office Action dated Jun. 13, 2007.  
U.S. Office Action for U.S. Appl. No. 12/882,954 dated Feb. 28, 2011.  
U.S. Office Action for U.S. Appl. No. 12/882,908 dated Feb. 28, 2011.  
U.S. Office Action for U.S. Appl. No. 12/882,821 dated Feb. 28, 2011.

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **7,376,441**  
Issued: **May 20, 2008**  
Appl. No.: **10/225,352**  
Filed: **Aug. 22, 2002**

\* cited by examiner

*Primary Examiner* — Wen Huang  
(74) *Attorney, Agent, or Firm* — KED & Associates LLP

(51) **Int. Cl.**  
*H04M 1/00* (2006.01)  
*H04B 1/38* (2006.01)  
*H04B 7/00* (2006.01)  
(52) **U.S. Cl.** ..... **455/556.1**; 455/557; 455/556.2;  
455/66.1; 455/334; 455/550.1; 341/176; 348/552  
(58) **Field of Classification Search** ..... 455/557,  
455/556, 66, 556.1, 556.2, 66.1, 334, 550.1;  
348/552; 341/176

(57) **ABSTRACT**  
An apparatus and a method for interacting with a mobile telephone are provided. A remote control unit receives a user command and transmits it to a TV system which recognizes the user command as a telephone function command and transmits the function command to the mobile telephone if the TV system is set to Telephone Mode. The TV system may also output data received from the mobile telephone in response to the transmitted function command. Thus, a user may interact with a mobile telephone using an interactive TV system by displaying text/image data received from the telephone and by inputting various telephone function commands using a remote control unit. Upon receiving a function command from the TV system, the mobile telephone generates output data in response to the function command and transmits it to the TV system. A display unit of the TV system displays the text/image data, and a speaker outputs the sound data. As a result, a user may conveniently interact with a mobile telephone using a display unit and a speaker of an interactive TV system with a remote control unit.

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,338,492 A 7/1982 Snopko  
4,356,509 A 10/1982 Skerlos et al.  
4,855,746 A 8/1989 Stacy  
5,920,806 A 7/1999 Gouessant  
6,166,778 A 12/2000 Yamamoto et al.  
6,459,906 B1 \* 10/2002 Yang ..... 455/556.1  
6,529,742 B1 \* 3/2003 Yang ..... 455/556.1  
6,584,613 B1 6/2003 Dunn et al.

**78 Claims, 5 Drawing Sheets**




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B





FIG. 4



**APPARATUS AND METHOD OF  
INTERACTING WITH A MOBILE PHONE  
USING A TV SYSTEM**

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

[This application claims the benefit of Korean Patent Application No. P2001-51342, filed on Aug. 24, 2001, which is hereby incorporated by reference as if fully set forth herein.] *This application is a Reissue of U.S. Pat. No. 7,376,441, filed on Aug. 22, 2002, and issued on May 20, 2008. Also, the following continuations of the present reissue application have been filed: U.S. Continuation Reissue application Ser. No. 12/882,954, U.S. Continuation Reissue application Ser. No. 12/882,908, and U.S. Continuation Reissue application Ser. No. 12/882,821.*

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a system for a mobile telephone, and more particularly, to apparatus and method of interacting with a mobile telephone using an interactive television system with a remote control unit.

2. Discussion of the Related Art

As there have been high demands from many mobile telephone users, many mobile communication service providers have recently started to provide not only a simple telephonic communication service, but also various supplemental communication services such as an Internet service, text/voice/image message service, and electronic mailing service. In order for a user to use any one of the various supplement services mentioned above, the user must be able to view images that are displayed on a display unit of a mobile telephone and to input one or more desired commands into the mobile telephone by pressing one or more buttons provided on the mobile telephone.

However, the sizes of the key buttons and display units of many existing mobile telephones are significantly limited due to the current trend toward smaller dimensions of the mobile telephones, and this create great inconveniences to many users for properly viewing the image and/or text data and inputting the desired commands by pressing the key buttons provided on the mobile telephones.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to apparatus and method of interacting with a mobile telephone using an interactive television system that substantially obviates one or more problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide a method of interacting with a mobile telephone using an interactive television system that provides a significantly improved way of interacting with the mobile telephone.

Another object of the present invention is to provide an apparatus of interacting with a mobile telephone using an interactive television system that provides a significantly improved way of interacting with the mobile telephone.

Additional advantages, objects, and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention. The objectives and other advantages of the invention may be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these objects and other advantages and in accordance with the purpose of the invention, as embodied and broadly described herein, an apparatus of interacting with a mobile telephone according to the present invention includes a remote control unit receiving a user command from a user and remotely transmitting the user command, and a TV system connected to the mobile telephone. The TV system recognizes the user command remotely received from the remote control unit as a telephone function command and transmits the function command to the mobile telephone if the TV system is set to a telephone mode by the user. The TV system further outputs an output data set received from the mobile telephone in response to the transmitted function command.

The mobile telephone of the apparatus includes a TV interface unit interfacing with the television system for receiving the function command from the TV system and transmitting the output data set to the TV system, and a controller generating a control signal for generating the output data set in response to the function command and transmitting the generated output data set to the TV system.

On the other hand, the TV system of the apparatus includes a remote-control interface unit receiving the user command from the remote control unit, a telephone interface unit interfacing with the mobile telephone for transmitting the function command to the mobile telephone and receiving the output data set from the mobile telephone, a microcomputer generating a control signal for outputting the output data set received from the mobile telephone, a video/audio signal processor combining text or image data included in the output data set with an original image data according to the control signal, and a display unit displaying the combined data.

In another aspect of the present invention, a method of interacting with a mobile telephone using a TV system with a remote control unit includes the steps of (a) displaying a telephone key index on a TV display unit of the TV system if the TV system is set to a telephone mode by a user, (b) receiving a first user command from the user through the remote control unit, (c) recognizing the first user command as a telephone function command and transmitting the function command to the mobile telephone, and (d) receiving an output data set that the mobile telephone generates in response to the transmitted function command and displaying image or text data included in the output data set on the TV display unit.

In another aspect of the present invention, a method of interacting with a TV system with a remote control unit for a mobile telephone includes the steps of (a) checking whether the mobile telephone is connected to the TV system, (b) receiving a telephone function command that the TV system generates in response to a user command received from a user through the remote control unit, and (c) generating an output data set in response to the received function command and transmitting the output data set to the TV system.

It is to be understood that both the foregoing general description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiment(s) of the invention and together with the description serve to explain the principle of the invention. In the drawings;

FIG. 1 illustrates an apparatus of interacting with a mobile telephone using an interactive TV system in accordance with the present invention;

FIG. 2 illustrates is a flow chart illustrating a method of interacting with a mobile telephone using an interactive television system according to the present invention;

FIG. 3A illustrates a telephone key index that gets displayed on a display unit of the TV system according to the present invention;

FIG. 3B illustrates a TV key index that gets displayed on a display unit of the TV system according to the present invention; and

FIG. 4 illustrates a flow chart illustrating a method of interacting with a TV system for a mobile telephone in accordance with the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

FIG. 1 illustrates an apparatus of interacting with a mobile telephone using an interactive television system (TV system) with a remote control unit in accordance with the present invention. As it can be seen from FIG. 1, the apparatus includes a mobile telephone 100 being able to receive or transmit various communication data including text, image, and/or voice data from a sender or to a receiver; an interactive television system 300 that is connected to the mobile telephone 100 and is able to display various data received from the mobile telephone 100; and a remote control unit 200 for enabling a user to set the interactive television system 300 to TV Mode or Telephone Mode. The television system 300 receives the output data from the mobile telephone 100 and displays the image/text data if the user has set the television system 300 to Telephone Mode.

The mobile telephone 100 includes a TV interface unit 110 for interfacing with the interactive television system 300 and further includes a controller (not illustrated) that gives a command for transmitting the output data corresponding to a telephone function command received from the television system 300. A user sets the television system 300 to Telephone Mode for interacting with the mobile telephone 100 or to TV Mode for performing various TV-related functions such as channel up/down and volume up/down functions.

The interactive television system 300 shown in FIG. 1 includes a remote-control interface unit 313 for receiving one or more user commands from the remote control unit 200; a telephone interface unit 319 connected to the mobile telephone 100 through a connection unit 320 for transmitting the user commands to the mobile telephone 100 and receiving the corresponding output data from the mobile telephone 100; a microcomputer 314 generating a control signal for displaying a key index corresponding to Telephone Mode or TV Mode and for outputting the output data received from the mobile telephone 100; a video/audio data processor 315 combining an original image signal with the key index and/or image/text

data included in the output data received from the telephone 100; and a display unit 317 displaying the combined data.

In addition, the interactive television system 300 further includes a tuner 310 receiving a broadcasting signal; an A/D converter 311 converting the analog broadcasting signal to a digital broadcasting signal; a link 312 checking and correcting any error included in the converted digital signal; a speaker 318 outputting a sound signal processed in the video/audio data processor 315 according to the control signal of the microcomputer 314; and a memory 316 storing the program information of the microcomputer 314 or other information. The interactive television system 300 may provide not only the video/audio data of the digital broadcasting signal, but also various supplemental program information.

The general functions of the components of the television system 300 will now be described in detail. First, the tuner 310 receives various broadcasting signals including satellite, terrestrial, and cable broadcasting signals. Then the A/D converter 311 converts the broadcasting signals to digital signals and outputs the converted digital signals to the link 312. The link 312 performs error checking and correcting functions and outputs compressed video/audio data streams. In accordance with a control signal generated by the microcomputer 314, the video/audio data processor 315 performs a compensation function on the compressed data streams and converts the compensated data streams to analog image/voice signals. Then the video and audio signals are outputted through the display unit 317 and the speaker 318, respectively.

In addition, when a user inputs a user command by pressing one or more key buttons provided on the remote control unit 200, the remote-control interface unit 313 transmits the user command to the microcomputer 314. Then the microcomputer 314 outputs a control signal for performing a desired function in response to the user command. Any graphic information generated by the microcomputer 314 upon receiving the user command from the remote control unit 200 or other graphic information related to the supplemental program information are transmitted to the video/audio data processing unit 315 via a data bus and are added to the original image signals in accordance with the control signal of the microcomputer 314.

The apparatus according to the present invention enables a user to interact with a mobile telephone 100 by displaying the output data received from the telephone 100 on the display unit 317 of the television system 300 and inputting any telephone function command into the mobile telephone 100 using the remote control unit 200.

The steps showing how the apparatus shown in FIG. 1 actually operates will now be described in detail. First of all, a user connects the mobile telephone 100 with the interactive television system 300 and sets the television system 300 to Telephone Mode or TV Mode by pressing a corresponding mode key button provided on the remote control unit 200 or on a key panel of the television system 300.

When the microcomputer 314 receives a command setting the mode of the television system 300, it generates a corresponding control signal in order for the video/audio data processor 315 to display a corresponding key index on the display unit 317 using an OSD function.

When the television system 300 is set to Telephone Mode, the microcomputer 314 checks whether the mobile telephone 100 is connected to the television system 300. Thereafter, when a user inputs a user command through the remote control unit 200 for controlling the mobile telephone 100, the microcomputer 314 transmits a corresponding telephone function command to the mobile telephone 100. Upon receiving the function command from the television system 300, a



## 5

controller of the telephone **100** generates a control signal in order to perform a corresponding telephone function such as viewing the phone numbers stored in the telephone **100** or viewing one of the text messages previously received.

Then the mobile telephone **100** transmits any data generated upon performing the function or any text/voice/image data received from an external source to the television system **300** via the TV interface unit **110**. Next, the television system **300** outputs the output data or text/voice/image data through the speaker **318** and/or the display unit **317**.

The display unit **317** may display the text/image data received from the mobile telephone **100** in a predetermined portion of the display unit **317** with or without the regular images of the broadcasting signal. On the other hand, when the television system **300** being initially set to TV Mode receives a user command from the remote control unit **200** for performing a general TV function such as a power on/off, channel switching, and volume adjusting function, the microcomputer **314** generates a corresponding control signal so that the television system performs the desired TV function.

FIG. 2 is a flow chart illustrating a method of interacting with a mobile telephone **100** using an interactive television system **300** according to the present invention. As shown in the figure, the microcomputer **314** included in the television system **300** initially checks whether the mobile telephone **100** is connected to the television system **300** through a connecting unit **320** (S100). If it is confirmed in the step S100 that the mobile telephone **100** is connected to the television system **300**, the microcomputer **314** further checks whether a user has inputted a first command for Telephone Mode by pressing a Telephone Mode button provided on a remote control unit **200** or a key panel of the television system **300** (S110).

If it is confirmed that the first command for Telephone Mode is received, the microcomputer **314** sets the television system **300** to Telephone Mode. Subsequently, a first key index corresponding to Telephone Mode is displayed on a predetermined portion of the display unit **317** of the television system **300** (S120). An example of the first key index that gets displayed on the display unit **317** as the television system **300** is set to Telephone Mode is illustrated in FIG. 3A. The first key index is an On Screen Display (OSD) type index indicating what each key button of the remote control unit **200** represents in Telephone Mode. For example, it includes a mode indicator indicating that the TV system is currently set to Telephone Mode.

On the other hand, if it is found in the step S110 that the first command for Telephone Mode is not inputted by the user, the microcomputer **314** checks whether the user has inputted a second command for TV Mode by pressing a TV Mode key button provided on the remote control unit **200** or the key panel of the television system **300** (S130). If it is confirmed in the step S130 that the second command for TV Mode is received, the microcomputer **314** sets the television system **300** to TV Mode. Subsequently, a second key index corresponding to TV Mode gets displayed on a predetermined portion of a display unit **317** (S140). An example of the second key index that gets displayed on the display unit **317** as the television system **300** is set to TV Mode is illustrated in FIG. 3B. The second key index is also an On Screen Display (OSD) type index indicating what each key button of the remote control unit **200** represents in TV Mode. For example, it includes a mode indicator indicating that the TV system is currently set to TV mode.

After the television system **300** is set to either one of Telephone Mode or TV Mode, the microcomputer **314** further checks whether the user has inputted a user command by pressing any key button of the remote control unit other than

## 6

the Telephone or TV Mode key button (S150). If it is found in the step S150 that such user command is received from the remotely control unit **200**, the microcomputer **314** further checks whether the television system **300** is currently set to Telephone Mode or TV Mode (S160). If the present mode is Telephone Mode, the user command is recognized as a telephone function command, and a corresponding key code gets transmitted to the mobile telephone **100** through a telephone interface unit **319** (S170). On the other hand, if the present mode is found to be TV Mode, the user command is recognized as an ordinary TV function command, and the television system **300** performs a TV function corresponding to the TV function command (S180).

Finally, the microcomputer **314** further checks whether any output data has been received from the mobile telephone **100** (S190). If it is confirmed that the output data has been received, the television system **300** performs a corresponding function according to the data received (S200). For example, it will display the text/image data included in the output data received from the mobile telephone **100** on the display unit **317** and output the sound data through the speaker **318**. The steps of S150 to S200 may be repeated until the user inputs no further user command. In addition, the first or second key index displayed in the step S120 or S140 may be undisplayed if it is determined that the user inputs no further user command.

FIG. 4 is a flow chart illustrating the steps carrying out a method of interacting with a mobile telephone **100** using an interactive television system **300** according to the present invention. As shown in FIG. 4, first of all, the controller (not illustrated) of the mobile telephone **100** checks whether the interactive television system **300** is connected to the mobile telephone **100** (S300). Next, if it is confirmed in the step S300 that the television system **300** is connected to the mobile telephone **100**, it further checks whether any one of text, image, and voice messages is received from a message sender (S310). If the mobile telephone **100** has received such message, it transmits the message to the television system **300** (S320). Then the television system **300** displays the image or text message on the display unit **317** and outputs the voice message through the speaker **318**.

On the other hand, if it is found in the step S310 that there is no data received, the controller of the mobile telephone **100** further checks whether any key code is received from the television system **300** (S330). If it is found in the step S330 that the mobile telephone **100** received a key code from the television system **300**, then the mobile telephone performs a corresponding function and transmits output data that it generates upon performing the function to the television system (S340). Subsequently, the display unit **317** of the television system **300** displays the text/image data and outputs the sound data included in the output data through the speaker **318**.

According to the method of the present invention described above, a user is able to interact with a mobile telephone using an interactive television system by displaying the text/image data received from the telephone and by inputting various telephone function commands using a remote control unit. Upon receiving a function command from the television system that the user has inputted through the remote control unit, the output data that the mobile telephone generates in response to the function command is transmitted to television system. Finally the text/image data of the output data is displayed on a display unit of the television system and the sound data is outputted through a speaker. As a result, a user may conveniently interact with the mobile telephone using the display unit and speaker of the television system and a remote control unit.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the inventions. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

**[1.** An apparatus for interacting with a mobile telephone, the apparatus comprising:

a TV remote control unit configured to receive a command and to transmit said command, the TV remote control unit including one or more channel-changing keys and one or more volume-changing keys; and

a TV system coupled to a mobile telephone, wherein said TV system is configured to receive said command from said TV remote control unit, to recognize said command as a telephone function command, and to transmit said telephone function command to said mobile telephone if said TV system is set to a telephone mode,

wherein said telephone function command includes information related to a voice call processing capability or at least one of an electronic mail capability or a text message capability of said mobile telephone,

wherein said TV system is further configured to output an output data set transmitted to said TV system from said mobile telephone in response to said transmitted telephone function command, and

wherein the TV system displays a first on-screen display (OSD) guide containing an image of keys of the TV remote control unit, said first OSD guide mapping one or more keys of the TV remote control unit to one or more telephone functions when the TV system is set in said telephone mode, the telephone function command being generated based on the mapping in said first OSD of the one or more keys of the TV remote control unit to said one or more telephone functions, and

wherein the TV system further displays a second OSD guide mapping one or more keys of the TV remote control unit to one or more television functions when the TV system is set in a television mode, said TV remote control further including one or more keys for allowing a user to switch the TV system between said television mode and said telephone mode.]

**[2.** The apparatus of claim 1, wherein said TV system includes a display unit configured to display text or image data included in said output data set.]

**[3.** The apparatus of claim 2, wherein said TV system further comprises a speaker configured to output sound data included in said output data set.]

**[4.** The apparatus of claim 1, wherein said mobile telephone comprises:

a TV interface unit configured to interface with said TV system so as to receive said function command from said TV system and to transmit said output data set to said TV system; and

a controller configured to generate a control signal including said output data set in response to said function command and to transmit said output data set to said TV system.]

**[5.** The apparatus of claim 1, wherein said TV system comprises:

a remote-control interface circuit configured to receive said command from said remote control unit;

a telephone interface circuit configured to interface with said mobile telephone so as to transmit said function

command to said mobile telephone and to receive said output data set from said mobile telephone;

a microcomputer configured to generate a control signal including said output data set received from said mobile telephone;

a video/audio signal processor configured to combine text and image data included in said output data set with original image data according to said control signal; and a display unit configured to display said combined data.]

**[6.** The apparatus of claim 1, wherein the output data set comprises data related to a web browsing capability of the mobile telephone.]

**[7.** The apparatus of claim 1, wherein the output data set comprises data related to a text messaging capability of the mobile telephone.]

**[8.** The apparatus of claim 1, wherein the output data set comprises data related to an electronic mail capability of the mobile telephone.]

**[9.** The apparatus of claim 1, wherein the output data set comprises data related to photographs provided by the mobile telephone.]

**[10.** The apparatus of claim 1, wherein said TV system is directly connected to said mobile telephone so as to allow a user to receive incoming telephone calls and to place outgoing telephone calls.]

**[11.** A method for interacting with a mobile telephone using a TV system with a TV remote control unit, the method comprising:

(a) displaying a first on-screen display (OSD) guide on a screen of said TV system if said TV system is set to a telephone mode, the first OSD guide mapping one or more keys of a TV remote control unit to one or more telephone functions when the TV system is set in said telephone mode;

(b) receiving a first command from said TV remote control unit by said TV system, said first command generated based on the mapping in said first OSD of the one or more keys of the TV remote control unit to said one or more telephone functions;

(c) recognizing said first user command as a telephone function command and transmitting said function command to said mobile telephone, wherein said telephone function command includes information related to a voice call processing capability or at least one of an electronic mail capability or a text message capability of said mobile telephone; and

(d) receiving an output data set generated by said mobile telephone in response to said transmitted function command and displaying image or text data included in said output data set on said TV display unit, said method further comprising:

(e) receiving signals from the TV remote control unit, resulting from activation of one or more keys of the TV remote control unit, to switch the TV system between a television mode and said telephone mode; and

(f) displaying a second OSD guide mapping one or more keys of the TV remote control unit to one or more television functions when the TV system is set in said television mode.]

**[12.** The method of claim 11, further comprising outputting sound data included in said output data set through a speaker of said TV system.]

**[13.** The method of claim 12, wherein outputting sound data comprises outputting messages provided by a voice mail capability of the mobile telephone.]

**[14.** The method of claim 11, further comprising repeating steps (b) through (d) until no further commands are received.]

**[15.** The method of claim 11, further comprising:  
receiving a second command from said TV remote control unit; and  
recognizing said second user command as a TV function command and performing a corresponding TV function.]

**[16.** The method of claim 11, wherein displaying images or text data comprise displaying data related to a web browsing capability of the mobile telephone.]

**[17.** The method of claim 11, wherein displaying image or text data comprises displaying data related to a text messaging capability of the mobile telephone.]

**[18.** The method of claim 11, wherein displaying image or text data comprises displaying data related to an electronic mail capability of the mobile telephone.]

**[19.** The method of claim 11, wherein displaying image or text data comprises displaying data related to photographs provided by the mobile telephone.]

**[20.** The method of claim 11, further comprising using said TV system and said mobile telephone connected directly thereto to connect incoming and outgoing telephone calls.]

**21.** A method which allows a mobile telephone to interact with a TV system including a TV remote control unit, the method comprising:

checking whether said mobile telephone is connected to a TV system;

receiving signals from the TV remote control unit designating an operating mode of the television, wherein a first signal results from activation of a telephone mode key on the TV remote control unit to place the TV system in a telephone mode and a second signal results from activation of a television mode key on the TV remote control unit to place the TV system in a television mode, wherein the phone mode key and the television key are different keys on the TV remote control unit;

receiving a telephone function command generated by said TV system in response to a command received from said TV remote control unit while in said telephone mode, wherein said telephone function command includes information related to a voice call processing capability or at least one of an electronic mail capability or a text message capability of said mobile telephone; and

generating an output data set in response to said received function command and transmitting said output data set to said TV system, wherein said method further comprises:

displaying a first on-screen display (OSD) guide on a screen of said TV system if said TV system is set to a telephone mode, the first OSD guide mapping one or more keys of a TV remote control unit to one or more telephone functions when the TV system is set in said telephone mode, the telephone function command being generated based on the mapping in said first OSD of the one or more keys of the TV remote control unit to said one or more telephone functions; and

displaying a second OSD guide mapping one or more keys of the TV remote control unit to one or more television functions when the TV system is set in said television mode.

**22.** The method of claim 21, wherein said output data set includes at least one of text, image, or sound data generated by said mobile telephone in response to said function command received from said TV system.

**23.** The method of claim 21, further comprising:  
checking whether any one of text, voice, or image messages is newly received; and

transmitting said newly received message to said TV system.

**24.** A digital television system for interacting with a mobile telephone connected to the digital television system, the digital television system comprising:

a microcomputer for receiving a first key code, for generating a television key index according to a setting of a television mode and a telephone key index according to a setting of a telephone mode, and for determining whether the digital television system is set to the telephone mode, and

a TV remote control unit including one or more channel-changing keys and one or more volume-changing keys, at least one of the keys on the TV remote control unit causing the microcomputer to generate the television key index which includes an on-screen display (OSD) guide mapping keys on the remote control unit to corresponding television functions in a television mode, said microcomputer displaying another OSD guide mapping keys on the remote control unit to one or more corresponding telephone functions in a telephone mode in response to another key on the TV remote control unit; wherein said microcomputer is configured to recognize the input first key code as a telephone function command according to the set mode, to transmit the recognized telephone function command from the digital television system to the mobile telephone if the digital television system is set to the telephone mode, the telephone function command including information related to at least one of an electronic mail capability or a text message capability of said mobile telephone, to receive from the mobile telephone a set of output data generated according to the telephone function command, and to output the generated output data, and wherein the telephone function command is generated based on the mapping in said another OSD of at least one key of the TV remote control unit to said one or more corresponding telephone functions.

**25.** A method for using a digital television system to interact with a mobile telephone connected to the digital television system, the method comprising:

(a) assigning a television key index corresponding to a television mode and a telephone key index corresponding to a telephone mode, the television key index including a first on-screen display (OSD) guide mapping one or more keys of a TV remote control unit to one or more television functions when the digital television system is in said television mode, and the telephone key index including a second OSD guide mapping one or more keys of the TV remote control unit to one or more telephone functions when the digital television system is in said telephone mode;

(b) setting the digital television system to one of the television mode and the telephone mode, the digital television system set to said television mode when a first key of the TV remote control unit is activated and to a telephone mode when a second key of the TV remote control unit is activated;

(c) determining whether the digital television system is set to the telephone mode;

(d) displaying the telephone key index using the first OSD displayed on the digital television system, if the digital television system is set to the telephone mode;

(e) selecting a first key code using the first OSD displayed telephone key index, the selected first key code being recognized as a telephone function command according to the set mode, the telephone function command includ-

## 11

ing data related to at least one of an electronic mail capability or a text message capability of said mobile telephone;

- (f) transmitting the recognized telephone function command from the digital television system to the mobile telephone;
- (g) generating, using the mobile telephone, a set of output data according to the telephone function command;
- (h) transmitting the generated set of output data to the digital television system; and
- (i) outputting the output data using the digital television system.

26. The method as claimed in claim 25, wherein selecting a first key code comprises inputting to the digital television system a plurality of key codes in a sequence, each key code corresponding to a telephone function command.

27. The method as claimed in claim 26, further comprising: repeating steps (e) through (i) for each of the plurality of key codes.

28. The method as claimed in claim 26, further comprising: determining whether the key code sequence is completed; and discontinuing said telephone key index displaying if the key code sequence is completed.

29. The method as claimed in claim 25, wherein the displayed telephone key index includes at least one icon for selecting the mode of the digital television system.

30. The method as claimed in claim 25, wherein the displayed telephone key index includes at least one icon indicative of the set mode of the digital television system.

31. The method as claimed in claim 30, wherein one of the at least one icon indicates the set mode of the digital television system to be the television mode.

32. The method as claimed in claim 30, wherein one of the at least one icon indicates the set mode of the digital television system to be the telephone mode.

33. The method as claimed in claim 25, further comprising: (j) determining whether the digital television system is set to the television mode;

(k) displaying the television key index using the digital television system, if the digital television system is set to the television mode;

(l) selecting a second key code using the displayed television key index, the selected second key code being recognized as a television function command according to the set mode; and

(m) performing a television function corresponding to the television function command.

34. The method as claimed in claim 33, wherein selecting a second key code comprises inputting to the digital television system a plurality of key codes in a sequence, each key code corresponding to a television function command.

35. The method as claimed in claim 34, further comprising: repeating steps (1) and (in) for each of the plurality of key codes.

36. The method as claimed in claim 34, further comprising: determining whether the key code sequence is completed; and discontinuing said television key index displaying, if the key code sequence is completed.

37. A method for controlling display of information on a display device based on a mobile phone, comprising:

receiving, by the display device, broadcasting data;

displaying a first on-screen display (OSD) guide on a screen of the display device, the first OSD guide showing one or more items to switch the display device between a first mode and a second mode, wherein the one or more

## 12

items are to be selected in response to activation of one or more keys of a remote controller;

receiving a first command from the remote controller to set the display device to the first mode where a key code is to be generated and transmitted to the mobile phone, wherein the first command is generated based on mapping the one or more items in the first OSD guide to activation of said one or more keys of the remote controller;

recognizing the first command as a phone function command, wherein the phone function command relates to a voice call processing capability or at least one of an electronic mail capability or a text message capability of the mobile phone;

after a message is received at the mobile phone, receiving message information from the mobile phone corresponding to the message and displaying the message information on the screen of the display device;

receiving a second command from the remote controller to set the display device to the second mode, wherein the second command is generated based on mapping the one or more items in the first OSD guide to activation of said one or more keys of the remote controller; and

displaying a second OSD guide mapping one or more keys of the remote controller to one or more display device functions when the display device is set in the second mode, wherein the first OSD guide is displayed to select either the first mode for displaying the received message information with the broadcasting data on the screen of the display device or the second mode for displaying the broadcasting data without displaying the message information on the screen of the display device.

38. The method of claim 37, further comprising: establishing communication with the mobile phone.

39. The method of claim 37, wherein the message includes at least one of a text message, an image message, or a voice message.

40. The method of claim 37, wherein the display device automatically receives the information corresponding to the message from the mobile phone after the message is received by the mobile phone and without transmitting any key code to the mobile phone to initiate reception of the message.

41. The method of claim 37, further comprising: receiving a third command from the remote controller when the display device is set to the second mode; and recognizing the third command as a display device function command and performing a corresponding display device function.

42. The method of claim 41, wherein the display device function is a TV function.

43. The method of claim 37, wherein the information provides notification of the message.

44. The method of claim 43, wherein the information provides notification of a type or content of the message.

45. The method of claim 44, wherein the notification of the type or content of the message is based on display of the received message.

46. The method of claim 44, wherein the content of the message includes an attachment to the message or information included within the message.

47. The method of claim 46, wherein the attachment to the message includes image data.

48. The method of claim 46, wherein the information included within the message includes text.

49. The method of claim 37, wherein the information provides notification of a voice call or voice message received by the mobile phone.

50. The method of claim 37, wherein during the first mode, a television program is displayed on the screen of the display device.

51. The method of claim 37, wherein the display device is a television.

52. A display device comprising:

a tuner configured to receive broadcasting data;

a remote control interface configured to receive a command from a remote controller;

a mobile phone interface configured to transmit the command to the mobile phone and receive corresponding data from the mobile phone;

a display configured to display a graphic; and

a microcomputer configured to:

display an first on-screen display (OSD) guide on the display, the first OSD guide showing one or more items to switch the display device between a first mode and a second mode, wherein the one or more items are to be selected in response to activation of one or more keys of the remote controller;

receive a first command from the remote controller to set the display device to the first mode where a key code is to be generated and transmitted to the mobile phone, wherein the first command is generated based on mapping the one or more items in the first OSD guide to activation of one or more keys of the remote controller; recognize the first command as a phone function command, wherein the phone function command relates to a voice call processing capability or at least one of an electronic mail capability or a text message capability of the mobile phone;

after a message is received at the mobile phone, receive message information corresponding to the message from the mobile phone and display the message information on the display;

receive a second command from the remote controller to set the display device to the second mode, wherein the second command is generated based on mapping the one or more items in the first OSD guide to activation of one or more keys of the remote controller; and

display a second OSD guide mapping one or more keys of the remote controller to one or more display device functions when the display device is set in the second mode;

wherein the first OSD guide is displayed to select either the first mode for displaying the received message information with the broadcasting data on the display device or the second mode for displaying the broadcasting data without displaying the message information on the display device.

53. The display device of claim 52, wherein the microcomputer is further configured to establish communication with the mobile phone via the mobile phone interface unit.

54. The display device of claim 52, wherein the message includes at least one of a text message, an image message, or a voice message.

55. The display device of claim 52, wherein the microcomputer is further configured to automatically receive the information corresponding to the message from the mobile phone after the message is received by the mobile phone, the message received without transmitting any key code to the mobile phone to confirm reception of the message.

56. The display device of claim 52, wherein the microcomputer is further configured to receive a third command from the remote controller when the display device is set to the

second mode, recognize the third command as a display device function command, and perform a corresponding display device function.

57. The display device of claim 56, wherein the display device function is a TV function.

58. The display device of claim 52, wherein the information provides notification of the message.

59. The display device of claim 58, wherein the information provides notification of a type or content of the message.

60. The display device of claim 59, wherein the notification of the type or content of the message is based on display of the received message.

61. The display device of claim 56, wherein the content of the message includes an attachment to the message or information included within the message.

62. The display device of claim 61, wherein the attachment to the message includes image data.

63. The display device of 61, wherein the information included within the message includes text.

64. The display device of claim 52, wherein the information provides notification of a voice call or voice message received by the mobile phone.

65. The display device of claim 52, wherein during the first mode, a television program is displayed on the screen of the display device.

66. The display device of claim 52, wherein the display device is a television.

67. The display device of claim 52, wherein the mobile phone interface is adapted to receive signals from a wire line coupled to the mobile phone.

68. A method for controlling display of information on a display device, comprising:

receiving, by the display device, broadcasting data;

displaying a first on-screen display (OSD) guide on a screen of the display device, the first OSD guide showing one or more items to switch the display device between a first mode and a second mode, wherein the one or more items are to be selected in response to activation of one or more keys of the remote controller;

receiving a first command from the remote controller when the display device is set to the first mode where a key code is to be generated and transmitted to the mobile phone, wherein the first command is generated based on mapping the one or more items in the first OSD guide to activation of one or more keys of the remote controller; recognizing the first command as a phone function command and transmitting the phone function command to the mobile phone, wherein the phone function command relates to a voice call processing capability or at least one of an electronic mail capability or a text message capability of the mobile phone; and

receiving an output data set generated by the mobile phone in response to the transmitted function command and displaying image or text data included in the output data set on the screen of the display device; and

displaying a second OSD guide mapping one or more keys of the remote controller to one or more display device functions when the display device is set in the second mode, wherein the first OSD guide is displayed to select either the first mode for displaying the received output data set with the broadcasting data on the screen of the display device or the second mode for displaying the broadcasting data without displaying the output data set on the screen of the display device.

69. The method of claim 68, further comprising receiving a mode setting command from the remote controller to set the display device to either the first mode or the second mode, wherein the mode setting command is generated by selecting the one or more items.

70. The method of claim 68, wherein the message includes at least one of a text message, an image message, or a voice message.

71. The method of claim 70, further comprising: checking whether any one of the text, voice or image messages is newly received at the mobile phone; and receiving the newly received message from the mobile phone.

72. The method of claim 68, further comprising: receiving a second command from the remote controller when the display device is set to the second mode; and recognizing the second command as a display device function command and performing a corresponding display device function.

73. The method of claim 72, wherein the display device function is a TV function.

74. The method of claim 68, further comprising: receiving information providing notification of the output data; and displaying said information on the screen of the display device.

75. The method of claim 74, wherein the information providing notification of the output data includes the output data.

76. The method of claim 74, wherein the notification information provides notification of a type or content of the output data.

77. The method of claim 76, wherein the notification of the type or content of the message is based on display of the output data.

78. The method of claim 76, wherein the content of the output data includes an attachment to a message corresponding to the output data or information included within a message corresponding to the output data.

79. The method of claim 78, wherein the attachment to the message includes image data.

80. The method of 78, wherein the information included within the message includes text.

81. The method of claim 68, wherein during the first mode, a television program is displayed on the screen of the display device.

82. The method of claim 68, wherein the display device is a television.

83. A display device comprising:  
a tuner configured to receive broadcasting data;  
a remote control interface configured to receive the command from a remote controller;  
a mobile phone interface configured to transmit the command to the mobile phone and receive corresponding data from the mobile phone;  
a display configured to display a graphic; and  
a microcomputer configured to:

display a first on-screen display (OSD) guide, the first OSD guide showing one or more items to switch the display device between a first mode and a second mode, wherein the one or more items are to be selected in response to activation of one or more keys of the remote controller;  
receive a first command from the remote controller when the display device is set to the first mode where a key code is to be generated and transmitted to the mobile phone, wherein the first command is generated based on mapping the one or more items in the first OSD guide to activation of one or more keys of the remote controller;  
recognize the first command as a phone function command and transmit the phone function command to the mobile phone, wherein the phone function command relates to a voice call processing capability or at least one of an electronic mail capability or a text message capability of the mobile phone;

receive an output data set generated by the mobile phone in response to the transmitted function command and display image or text data included in the output data set on the display; and

display a second OSD guide mapping one or more keys of the remote controller to one or more display device functions when the display device is set in the second mode,

wherein the first OSD guide is displayed to select either the first mode for displaying the received output data set with the broadcasting data on the display device or the second mode for displaying the broadcasting data without displaying the output data set on the display device.

84. The display device of claim 83, wherein the microcomputer is further configured to receive a mode setting command from the remote controller to set the display device to either the first mode or the second mode, wherein the mode setting command is generated by selecting the one or more items.

85. The display device of claim 83, wherein the message includes at least one of a text message, an image message, or a voice message.

86. The display device of claim 85, wherein the microcomputer is further configured to:

check whether any one of the text, voice or image messages is newly received at the mobile phone; and receive the newly received message from the mobile phone.

87. The display device of claim 83, wherein the microcomputer is further configured to:

receive a second command from the remote controller when the display device is set to the second mode; and recognize the second command as a display device function command and performing a corresponding display device function.

88. The display device of claim 87, wherein the display device function is a TV function.

89. The display device of claim 83, wherein the microcomputer:

receives information providing notification of the output data; and displays said information on the screen of the display device.

90. The display device of claim 89, wherein the information providing notification of the output data includes the output data.

91. The display device of claim 89, wherein the notification information provides notification of a type or content of the output data.

92. The display device of claim 91, wherein the notification of the type or content of the message is based on display of the output data.

93. The display device of claim 91, wherein the content of the output data includes an attachment to a message corresponding to the output data or information included within a message corresponding to the output data.

94. The display device of claim 93, wherein the attachment to the message includes image data.

95. The display device of 93, wherein the information included within the message includes text.

96. The display device of claim 83, wherein during the first mode, a television program is displayed on the screen of the display device.

97. The display device of claim 83, wherein the display device is a television.

98. The display device of claim 83, wherein the mobile phone interface is adapted to receive signals from a wire line coupled to the mobile phone.

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : RE43,139 E  
APPLICATION NO. : 12/784281  
DATED : January 24, 2012  
INVENTOR(S) : Jae Kyung Lee

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title page, item [30] should read;

**(30) Foreign Application Priority Data**

**Aug. 24, 2001 (KR) 10-2001-51342**

Signed and Sealed this  
Eighteenth Day of December, 2012



David J. Kappos  
*Director of the United States Patent and Trademark Office*