

#### US00RE43183E

# (19) United States

# (12) Reissued Patent

Blair et al.

# (10) Patent Number: US RE43,183 E

## (45) Date of Reissued Patent: Feb. 14, 2012

#### (54) SIGNAL MONITORING APPARATUS ANALYZING VOICE COMMUNICATION CONTENT

(75) Inventors: Christopher Douglas Blair, South

Chailey (GB); Roger Louis Keenan,

London (GB)

(73) Assignee: Cerint Americas, Inc., Roswell, GA

(US)

(21) Appl. No.: 11/477,124

(22) Filed: Jun. 28, 2006

# Related U.S. Patent Documents

Reissue of:

(64) Patent No.: 6,757,361
Issued: Jun. 29, 2004
Appl. No.: 10/073,966
Filed: Feb. 14, 2002

U.S. Applications:

(62) Division of application No. 09/500,800, filed on Feb. 10, 2000, now Pat. No. 6,404,857, which is a division of application No. 08/936,428, filed on Sep. 24, 1997, now abandoned.

#### (30) Foreign Application Priority Data

- (51) Int. Cl.

  H04M 3/51 (2006.01)

  H04M 3/36 (2006.01)

  H04M 3/50 (2006.01)

  H04M 3/42 (2006.01)

  H04M 7/12 (2006.01)

See application file for complete search history.

## (56) References Cited

#### U.S. PATENT DOCUMENTS

3,855,418 A	*	12/1974	Fuller	704/272	
4,093,821 A		6/1978	Williamson		
4,142,067 A		2/1979	Williamson		
4,567,512 A		1/1986	Abraham		
4,837,804 A		6/1989	Akita		
4,856,066 A	*	8/1989	Lemelson	704/275	
(Continued)					

#### FOREIGN PATENT DOCUMENTS

EP 0 510 412 10/1992

(Continued)

#### OTHER PUBLICATIONS

Lieberman et al., "Some Aspects of Fundamental Frequency and Envelope Amplitude as Related to the Emotional Content of Speech", The Journal of the Acoustical Society of America, vol. 34, previously presented. 922-927 (Jul. 1962).


#### (Continued)

Primary Examiner — William D Cumming
(74) Attorney, Agent, or Firm — McKeon, Meunier, Carlin & Curfman

#### (57) ABSTRACT

A signal monitoring apparatus and method involving devices for monitoring signals representing communications traffic, devices for identifying at least one predetermined parameter by analyzing the context of the at least one monitoring signal, a device for recording the occurrence of the identified parameter, a device for identifying the traffic stream associated with the identified parameter, a device for analyzing the recorded data relating to the occurrence, and a device, responsive to the analysis of the recorded data, for controlling the handling of communications traffic within the apparatus.

#### 30 Claims, 4 Drawing Sheets



# US RE43,183 E Page 2

LLC DATENI	E DOCLIMENTS	6,233,256 B1 5/2001 Dieterich et al.	
	Γ DOCUMENTS _	6,233,256 B1 5/2001 Dieterich et al. 6,246,752 B1 6/2001 Bscheider et al.	
·	Bergman	6,246,759 B1 6/2001 Greene et al.	
	Nicholas Swinehart et al.	6,249,570 B1 6/2001 Glowny et al.	
	Kosich	6,252,946 B1 6/2001 Glowny et al.	
	Brown et al.	6,252,947 B1 6/2001 Diamond et al. 6,282,269 B1 8/2001 Bowater et al.	
	Chamberlin et al.	6,288,739 B1 9/2001 Hales et al.	
, ,	Brown et al.	6,320,588 B1 11/2001 Palmer et al.	
	D'Agosto, III et al. Wrench, Jr. et al.	6,330,025 B1 12/2001 Arazi et al.	
5,070,526 A 12/1991		6,351,762 B1 2/2002 Ludwig et al.	
	Chiu et al.	6,356,294 B1 3/2002 Martin et al. 6,370,574 B1 4/2002 House et al.	
5,166,971 A 11/1992		6,404,857 B1 6/2002 Blair et al.	
	Comroe et al.	6,411,683 B1* 6/2002 Goldberg et al 379/88.01	
	O'Neill et al. Szlam et al.	6,418,214 B1 7/2002 Smythe et al.	
	Henits et al.	6,510,220 B1 1/2003 Beckett, II et al.	
	Crick	6,538,684 B1 3/2003 Sasaki 6,542,602 B1 4/2003 Elazar	
	Chencinski et al.	6,560,323 B2 * 5/2003 Gainsboro	
	Palmer et al.	6,560,328 B1 5/2003 Bondarenko et al.	
	Lane et al. Casselman et al.	6,570,967 B2 5/2003 Katz	
	Henits et al.	6,668,044 B1 12/2003 Schwartz et al.	
	Harriman, Jr.	6,690,663 B1 2/2004 Culver 6,728,345 B2 4/2004 Glowny et al.	
	Barris	6,728,345 B2 4/2004 Glowny et al. 6,754,181 B1 6/2004 Elliott et al.	
	Tung et al.	6,757,361 B2 6/2004 Blair et al.	
	Schoof, II Henits et al.	6,775,372 B1 8/2004 Henits	
	Henits et al.	6,785,369 B2 8/2004 Diamond et al.	
, ,	Palmer et al.	6,785,370 B2 8/2004 Glowny et al.	
5,488,570 A 1/1996	Agarwal	6,865,604 B2 3/2005 Nisani et al. 6,871,229 B2 3/2005 Nisani et al.	
	Bielby et al.	6,880,004 B2 4/2005 Nisani et al.	
	Tung et al. Powers et al.	6,959,079 B2 10/2005 Elazar	
	Arshi et al.	7,203,285 B2 * 4/2007 Blair	
	Agarwal	7,330,536 B2 * 2/2008 Claudatos et al 379/68 2001/0043697 A1 11/2001 Cox et al.	
	Agarwal	2001/0043097 A1 11/2001 Cox et al. 2004/0028193 A1 2/2004 Kim	
	Agarwal	2004/0064316 A1 4/2004 Gallino	
	Russell et al. Regyey et al	EODEICKI DATEKIT DOCI IMEKITO	
	Peavey et al. Maloney et al.	FOREIGN PATENT DOCUMENTS	
	Brown et al.	EP 0841832 A2 5/1998	
	Palmer et al.	EP 0833489 A3 5/2002 ED 1210200 B1 12/2005	
	Stanford et al.	EP 1319299 B1 12/2005 GB 2 257 872 1/1993	
	Bassenyemukasa et al. Palmer et al.	WO WO9741674 A 11/1997	
	Ron	WO WO0028425 A 5/2000	
	Gerber et al.	WO WO0052916 A 9/2000	
	Maloney et al.	WO WO03107622 12/2003	
	B Dezonno B Moron et el	OTHER PUBLICATIONS	
, , ,	Moran et al. Nelson et al.		
	Dezonno	So-Lin Yen et al. "Intelligent MTS Monitoring System", Oct. 1994,	
5,764,901 A 6/1998	Skarbo et al.	pp. 185-187, Scientific and Research Center for Criminal Investiga-	
	McCreery et al.	tion, Taiwan, Republic of China.	
	Beckett, II et al. Walker	Network Resource Group of Lawrence Berkeley National Labora-	
	Maloney et al.	tory, vat-LBNL Audio Conferencing Tool, web.archive.org/web/	
	Van Berkum et al.	19980126183021/www-nrg.ee.lbl.gov/vat (Jan. 26, 1998), 5 pp.  Mach Research Team, via video conference, at web archive arg/web/	
	Daly et al.	Mash Research Team, <i>vic-video conference</i> , at web.archive.org/web/ 19980209092254/mash.cs.berkeley.edu/mash (Feb. 9, 1998), 11 pp.	
	Garberg et al.	Mash Research Team, <i>Player</i> , at web.archive.org/web/	
, ,	Golan Power et al.	19980209092521/mash.cs.berkeley.edu/mash (Feb. 9, 1998), 3 pp.	
, , ,	Barak	Raman et al., "On-demand Remote Playback", Paper, Department of	
, , , , , , , , , , , , , , , , , , , ,	Bernard et al.	EECS, University of California at Berkeley (1997), 10 pp.	
, ,	Yosef	Intel Corporation, Intel Internet Video Phone Trial Applet 2.1: The	
, , ,	Pattison et al.	Problems and Pitfalls of Getting H.323 Safely Through Firewalls, at	
, ,	Kuroiwa et al. Miyazawa et al.	web.archive.org/web/19980425132417//http://support.intel.com/	
, ,	Krishnaswamy et al.	support/videophone/trial21/h323_wpr.htm#a18 (Apr. 24, 1998), 32	
	Fenton et al.	pp. Posting of Brett Eldridge to muc lists firewalls: MS NetMeeting 2.0	
, ,	Barak	Posting of Brett Eldridge to muc.lists.firewalls: MS NetMeeting 2.0 and Raptor Eagle vers. 4.0, at groups-beta.google.com/groups/muc.	
, , , , , , , , , , , , , , , , , , , ,	Fedorov et al.	lists.firewalls/browse_thread/thread/ec0255b64bf36ad4?tvc=2	
, ,	Pattison et al. Gainsboro	(May 2, 1997), 3 pp.	
, , ,	Fletcher et al.	Press Release, RADCOM, Breakthrough Internetworking Applica-	
	Bar et al.	tion for Latency & Loss Measurements from RADCOM, at web.	
	Ayala et al.	archive.org/web/19980527022443/www.radcom-inc.com/press21.	
6,233,234 B1 5/2001	Curry et al.	htm (May 27, 1998), 2 pp.	

RADCOM, Supported Protocols, at web.archive.org/web/19980527014033/www.radcom-inc.com/protocol.htm (May 27, 1998), 10 pp.

Press Release, RADCOM, RADCOM Adds UNI 4.0 Signalling and MPEG-II Support to ATM Analysis Solutions, at web.archive.org/web/19980527022611/www.radcom-inc.com/press13.htm (May 27, 1998), 1 p.

RADCOM, *Prism200 Multiport WAN/LAN/ATM Analyzer*, at web. archive.org/web/19980527020144/www.radcom-inc.com/pro-p1. htm (May 27, 1998), 3 pp.

The AG Group, Inc., User Manual: Etherpeek Ethernet Network Software Analysis (1997), 168 pp.

Beckman, Mel *See and hear your network*, at web.archive.org/web/19990224183147/macworld.zdnet.com/pages/june.96/Reviews. 2144.htm 1 (Feb. 24, 1999), 3 pp.

AG Group, Inc., *About Satellite*, at //web.archive.org/web/19980206033053/www.aggroup.com/skyline (Feb. 6, 1998), 1 p. Check Point, *Supported Applications*, at web.archive.org/web/19980212233542/www.checkpoint.com/products/technology/index.html (Feb. 12, 1998), 6 pp.

Check Point, *Stateful Inspection in Action*, at web.archive.org/web/19980212235911/www.checkpoint.com/products/technology/page2.html (Feb. 12, 1998), 4 pp.

Check Point, Check Point Fire Wall-1: Extensible Stateful Inspection, at web.archive.org/web/19980212235917/www.checkpoint.com/products/technology/page3.html (Feb. 12, 1998), 3 pp.

RADCOM, *PrismLite: Portable WAN/LAN/ATM Protocol Analyzer*, at //web.archive.org/web/19980527020156/www.radcom-inc.com/pro-p2.htm (May 27, 1998), 3 pp.

Simpson, David, *Viewing RTPDump Files*, at //bmrc.berkeley.edu/~davesimp/viewingNotes.html (Oct. 12, 1996), 1 p.

Waldbusser, S., RFC 1757—Remote Network Monitoring Management Information Base, at www.faqs.org/rfcs/rfc1747.html (Feb. 1995), 65 pp.

Microsoft Corporation, *GFF Format Summary: Microsoft RIFF*, at netghost.narod.ru/gff/graphics/summary/micriff.htm (1996), 5 pp. Cohen, D. "A Voice Message System", Proceedings of the IFIP TC-6 International Symposium on Computer Message Systems, Computer Message Systems, edited by Ronald P. Uhlig, Bell Northern Research Limited, Ottawa, Canada, Apr. 6-8, 1981, pp. 17-28.

Cohen, D. "On Packet Speech Communication", Proceedings of the Fifth International Conference, Computer Communications: Increasing Benefits to Society, the International Council for Computer Communication, Hosted by American Telephone and Telegraph Company., Atlanta, Georgia, Oct. 27-30, 1980. pp. 269-274.

Cohen, Danny, "Packet communication of online speech", USCI, Information Sciences Institute, Marina del Rey, CA, National Computer Conference, 1981, pp. 169-176.

Cohen, Danny, NWG/RFC 741, "Specification for the Network Voice Protocol (NVP)", ISI, DC, Nov. 22, 1977, 40 pages.

Holfelder, Wieland, Tenet Group, International Computer Science Institute and University of California, "VCR(1), MBone VCR—Mbone Video Conference Recorder", Berkley, CA, Nov. 5, 1995, pp. 1-8.

Information Sciences Institute, University of Southern California, Marina del Rey, "RFC:791 Internet Protocal DARPA Internet Program Protocol Specification", Prepared for Defense Advanced Research Projects Agency Information Processing Techniques Office, Arlington, VA, Sep. 1981, pp. 1-45.

Schulzrinne, Henning, "Voice Communication Across the Internet: A Network Voice Terminal", Dept. of Electrical and Computer Engineering, Dept. of Computer Science, Univ. of Massachusetts, Amherst, MA Jul. 29, 1992, pp. 1-34.

Terry, Douglas B. and Daniel C. Swinehart, "Managing Stored Voice in the Etherphone System", Computer Science Laboratory, Xerox Palo Alto Research Center, 1987, pp. 103-104.

Zellweger, Polle T., Douglas B. Terry, and Daniel C. Swinehart, "An Overview of the Etherphone System and Its Applications", Xerox Palo Alto Research Center, Palo Alto, CA, 1988, pp. 160-168.

Telecommunication Standardization Sector of International Telecommunication Union, Recommendation H.245 Control Protocol for Multimedia Communication, Feb. 1998.

Telecommunication Standardization Sector of International Telecommunication Union, Recommendation H.225 Call Signaling Protocols and Media Stream Packetization for Packet-Based Multimedia Communication Systems, Feb. 1998 (WSISTS000177-331).

Telecommunication Standardization Sector of International Telecommunication Union, Recommendation H.323 Packet-Based Multimedia Communications Systems, Feb. 1998 (WSISTS000049-176).

Ruiz, Antonio, Voice and Telephony Applications for the Office Workstation, 1st International Conference on Computer Workstations, IEEE Computer Society Press (Nov. 11-14, 1985).

Swinehart, Daniel C., Telephone Management in the Etherphone System, IEEE/IEICE Global Telecommunications Conference, Tokyo Conference Proceedings, vol. 2 of 3 (1987).

Swinehart, D.C. et al., Adding Voice to an Office Computer Network, IEEE Global Telecommunications Conference, San Diego, California, Conference Record vol. 1 of 3 (Nov. 28-Dec. 1, 1983.

Terry, Douglas B., Distributed System Support for Voice in Cedar, Proc. of Second European SIGOPS Workshop on Distributed Systems (Aug. 1986).

Clark, David D. et al., Supporting Real-Time Applications in an Integrated Services Packet Network: Architecture and Mechanism, Conference Proceedings on Communications Architectures & Protocols (Aug. 17-20, 1992).

Vin, Harrick M. et al., Multimedia Conferencing in the Etherphone Environment, IEEE Computer Society Press, vol. 24, Issue 10 (Oct. 1991).

Terry, Douglas B. et al., Managing Stored Voice in the Etherphone System, ACM Transactions on Computer Systems, vol. 6, No. 1, ACM 0734-2071/88/0200-0003 (Feb. 1988).

Boggs, David R. et al., Pup: An Internetwork Architecture, Report CSL-79-10, Xerox Palo Alto Research Center (Jul. 1979).

Postel, Jonathan B. et al., The ARPA Internet Protocol, Computer Networks: The International Journal of Distributed Informatique, vol. 5, No. 4 (Jul. 1981).

Mash Research Team, Recorder, at http://web.archive.org/web/19980209092445/mash.cs.berkeley.edu/mash/software/recorder-usage.html (archived Feb. 9, 1998).

Mash Research Team, Archive Tools Overview (last modified Aug. 30, 1997) at http://web.archive.org/web/19980209092409/mash.cs. berkeley.edu/mash/software/archive-usage.html (archived Feb. 9, 1998).

Howell, Peter et al., "Development of a Two-Stage Procedure for the Automatic Recognition of Dysfluencies in the Speech of Children Who Stutter: I. Psychometric Procedures Appropriate for Selection of Training Material for Lexical Dysfluency Classifiers," University College London, Department of Psychology, J Speech Lang Hear Res., vol. 40, Issue 5, pp. 1073-1084 (Oct. 1997).

Schuett, A. et al., A Soft State Protocol for Accessing Multimedia Archives, Proc. 8th International Workshop on Network and Operating Systems Support for Digital Audio and Video (NOSSDSV), Jul. 1998, 11 pgs.

Witness Systems, Inc., Local Patent Rule (LPR) 4.3 Disclosures (including claim chart), submitted to the Court in *STS Software Systems Ltd.* v. *Witness Systems, Inc. et al.*, U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Apr. 25, 2005, 36 pgs.

Witness Systems, Inc., Supplemental Local Patent Rule (LPR) 4.3 Disclosures (including claim chart), submitted to the Court in *STS Software Systems Ltd.* v. *Witness Systems, Inc. et al.*, U.S. District Court Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Sep. 9, 2005, 19 pgs.

Witness Systems, Inc., Second Supplemental Local Patent Rule (LPR) 4.3 Disclosures (including claim chart), submitted to the Court in STS Software Systems Ltd. v. Witness Systems, Inc. et al., U.S. District Court Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Jan. 29, 2007, 48 pgs.

Witness Systems, Inc., Third Supplemental Local Patent Rule (LPR) 4.3 Disclosures (including claim chart), submitted to the Court in *STS Software Systems Ltd.* v. *Witness Systems, Inc. et al.*, U.S. District Court Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Feb. 20, 2007, 20 pgs.

Witness Systems, Inc., Fourth Supplemental Local Patent Rule (LPR) 4.3 Disclosures (including claim chart), submitted to the Court in STS Software Systems Ltd. v. Witness Systems, Inc. et al., U.S. District Court Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Mar. 22, 2007, 69 pages.

Parnes, Peter et al., mMOD: The Multicast Media-on-Demand System, Lulea University of Technology, Sweden, Mar. 6, 1997.

Hirschberg, Julia et al., "Experiments in Emotional Speech," Columbia University (Feb. 18, 2003), 4 pgs.

Posting of Michael Pelletier to comp. security.firewalls: Netmeeting through a packet filter, at http://groups-beta.google.com/group/comp.security.firewalls/browse\_thread/thread/c14c3ac7d190a58/a4010ede22ff83a0, Jan. 23, 1998, 4 pgs.

Communications Solutions CTI News, at http://www.tmcnet.com/articles/ctimag/0699/0699news.htm, Jun. 1999.

Press Release, RADCOM, New VoIP Testing Applications from RADCOM, at www.radcom.com/radcom/about/pr020999.htm, Feb. 9, 1999, 2 pgs.

Willis, David, "Voice Over IP, The Way It Should Be," Network Computing, at http://www.nwc.com/1001/1001ws12.html, Jan. 11, 1999.

Willis, David, "Hear it for yourself: Audio Samples from our H.323 test, Network Computing," at http://www.nwc.com/1001/1001ws2. html, Jan. 11, 1999.

Posting of Dameon D. Welch-Abernathy, Re: [fw1-wizards] tcpdump for solaris 2.6, at http://oldfaq.phoneboy.com/gurus/200007/msg00081.html, Jul. 18, 2000.

Wessler, Dr. Barry, Rebuttal Expert Report, submitted to the Court in STS Software Systems Ltd. v. Witness systems, Inc. et al., U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Nov. 6, 2007, 38 pages.

Witness Systems, Inc., Expert Report of Danny Cohen on Invalidity (28 pgs) with claim cart Exhibit C (44 pgs), submitted to the Court in *STS Software Systems Ltd.* v. *Witness Systems, Inc. et al.*, U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Sep. 19, 2007.

Witness Systems, Inc., Rebuttal Expert Report of Dr. Danny Cohen (53 pages) with claim chart Exhibit C (44 pgs), submitted to the Court in STS Software Systems Ltd. v. Witness Systems, Inc. et al., U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Nov. 20, 2007.

Witness Systems, Inc., Expert Report of Stephen L. Casner on Invalidity (39 pgs), with claim chart exhibits (Exhibit E—20 pgs; Exhibit F—24 pgs; Exhibit G—20 pgs; Exhibit H—41 pgs; Exhibit I—19 pgs; Exhibit J—20 pgs; Exhibit K—29 pgs; and Exhibit L—30 pgs), submitted to the Court in *Sts Software Systems Ltd.* v. *Witness Systems, Inc. et al.*, U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Sep. 21, 2007.

Witness Systems, Inc. Rebuttal Expert Report of Stephen Casner (75 pgs) with claim chart exhibits (Exhibit E—17 pgs; Exhibit F—21 pgs; Exhibit H—38 pgs; and Exhibit L—26 pgs), submitted to the Court in STS Software Systems Ltd. v. Witness Systems, Inc. et al., U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Nov. 20, 2007.

Witness Systems, Inc., Rebuttal Expert Report of Dr. David Clark (111 pgs), with claim chart exhibits ((Exhibit E—35 pgs; Exhibit J—36 pgs; Exhibit O—58 pgs; Exhibit P—12 pgs; Exhibit Q—12 pgs; Exhibit R—19 pgs; Exhibit S—47 pgs; Exhibit U—63 pgs; Exhibit V—37 pgs; and Exhibit W—32 pgs), submitted to the Court in STS Software Systems Ltd. v. Witness Systems, Inc. et al., U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Nov. 20, 2007.

Witness Systems, Inc., Expert Report of Dr. Jeffrey S. Vitter on Validity (including claim chart), submitted to the Court in *Nice Systems, Inc. and Nice Systems Ltd.* v. *Witness Systems, Inc. et al.*, U.S. District Court, for the District of Delaware, Case No. 06-311-JJF on Dec. 21, 2007 (85 pgs).

Witness Systems, Inc., Expert Report of John Henits on Validity Issues, submitted to the Court in *Nice Systems, Inc. and Nice Systems Ltd.* v. *Witness Systems, Inc. et al.*, U.S. District Court, for the District of Delaware, Case No. 06-311-JJF on Dec. 31, 2007 (99 pgs).

Nice Systems, Inc. and Nice Systems, Ltd.'s Local Patent Rule (LPR) 4.3 Disclosures (including claim chart) submitted to the Court in

Witness Systems, Inc. v. Nice Systems, Inc. and Nice Systems, Ltd., District Court Northern District of Georgia, Atlanta Division, Case No. 1:06-CV-00126-RLV on May 1, 2006, 236 pgs.

Nice Systems, Inc. and Nice Systems, Ltd.'s Supplemental Local Patent Rule 4.3 Disclosures (including claim chart) submitted to the Court in *Witness Systems, Inc.* v. *Nice Systems, Inc. and Nice Systems, Ltd.*, District Court Northern District of Georgia, Atlanta Division, Case No. 1:06-CV-00126-TCB on Sep. 28, 2007, 131 pgs.

Nice Systems, Inc. and Nice Systems, Ltd.'s Second Supplemental Local Patent Rule 4.3 Disclosures submitted to the Court in *Witness Systems, Inc.* v. *Nice Systems, Inc. and Nice Systems, Ltd.*, District Court Northern District of Georgia, Atlanta Division, Case No. 1:06-CV-00126-TCB on Oct. 23, 2007, 6 pgs.

Hirschberg, Julia et al., "Prosodic and Other Cues to Speech Recognition Failures," Department of Elsevier B.V., Speech Communication, vol. 43 (2004) pp. 155-175.

Hirschberg, Julia et al., "The influence of pitch range, duration, amplitude and spectral features on the interpretation of the rise-fall-rise intonation contour in English," Journal of Phonetics, vol. 20, (1992) pp. 241-251.

Hargadon, Andrew et al., "Building an Innovation Factory," Harvard Business Review (HBR OnPoint), Product No. 6102 (May-Jun. 2000), pp. 1, 3-17.

Von Hippel, Eric et al., "Creating Breakthroughs at 3M," Harvard Business Review (HBR OnPoint), Product No. 6110 (Sep.-Oct. 1999), pp. 1, 19-29, 47.

Thomke, Stefan, "Enlightened Experimentation: The New Imperative for Innovation," Harvard Business Review (HBR OnPoint), Product No. 6099 (Feb. 2001), pp. 1, 31-47.

Hamel, Gary et al., "Strategic Intent," Harvard Business Review (HBR), (May-Jun. 1989), 14 pgs.

Howell, Peter et al., "Development of a Two-Stage Procedure for the Automatic Recognition of Dysfluencies in the Speech of Children Who Stutter: II. ANN Recognition of Repetitions and Prolongations With Supplied Word Segment Markers," University College London England, UKPMC Funders Group, J Speech Lang Hear Res., vol. 40, Issue 5 (Oct. 1997), pp. 1085-1096.

Touchstone Technologies, Inc., "Voice and Video over IP Test Solutions," Hatboro, Pennsylvania, (Sep. 19, 2006), 3 pgs.

Ades, Stephen, "An Architecture for Integrated Services on the Local Area Network," University of Cambridge, Computer Laboratory, Technical Report, No. 114, Sep. 1987, 177 pgs.

Emmerson, Bob et al., "The Surging CTI Tide," Byte, Nov. 1996, 3 pgs.

Speech Processing Peripheral (SPP) User's Manual, Adams-Russell Company, Inc., Digital Processing Division, Waltham, Massachusetts, Oct. 2, 1984, 64 pgs.

Press Release, PhoNet Communications Ltd., "PhoNet Introduces EtherPhone: The First Data PBX Solution to Offer Toll Quality, Scalability, and Fault Tolerance Regardless of Network Topology," Oct. 10, 1997, 2 pgs.

Press Release, PhoNet Communications Ltd., "PhoNet Communications Introduces PhoNetWork For Voice Calls over Intranets or the Internet," Oct. 10, 1997, 1 pg.

Nance, Barry, "Your PC's Ringing—Answer It!," CMP Media LLC, Byte Digest, Byte.com, (archived Feb. 1997), 5 pgs.

CTI News, Year End Issue, New Products From Amtelco XDS, Technology Marketing Corporation, 2007, 18 pgs.

Cohen, Danny et al., "A Network Voice Protocol NVP-II," USC/ISI, ISI/RR-81-90, Apr. 1, 1981, 75 pgs.

Cohen, Danny "Using Local Area Networks for Carrying Online Voice," Proceedings of the IFIP TC 6 International In-Depth Symposium on Local Computer Networks, edited by Piercarlo Ravasio, Ing. Olivetti & C.S.p.A., Ivrea, Italy, Greg Hopkins, The Mitre Corporation, Medford, Massachusetts, and Najah Naffah, Inria, Le Chesnay, France, North Holland Publishing Company, Florence, Italy, Apr. 19-21, 1982, pp. 13-21.

Schooler, Eve M. et al., "A Packet-switched Multimedia Conferencing System," University of Southern California, Information Sciences Institute, Marina del Rey, California, Reprinted from the ACM Sigois Bulletin, vol. 1, No. 1 (Jan. 1989), pp. 12-22.

Ober, Katie, "Assessing Validity of Computerized Voice Stress Analysis," study conducted at Edinboro University of Pennsylvania, presented at the 31st Annual Western Pennsylvania Undergraduate Psychology Conference—Mercyhurst College, Erie, Pennsylvania, Apr. 2003, 2 pgs.

Witness Systems, Inc., Expert Report of Dr. David D. Clark on Invalidity (60 pgs.), with claim chart exhibits (Exhibit E—38 pgs.; Exhibit F—23 pgs.; Exhibit G—37 pgs.; Exhibit H—32 pgs.; Exhibit I—62 pgs.; Exhibit J—39 pgs.; and Exhibit K—41 pgs.), submitted to the Court in STS Software Systems Ltd. v. Witness Systems, Inc. et al., U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Nov. 20, 2007.

Witness Systems, Inc., claim chart exhibits from Expert Report of Dr. David D. Clark on Invalidity (Exhibit L—43 pgs.; Exhibit M—19 pgs. Exhibit N—94 pgs.; and Exhibit O—61 pgs.), submitted to the Court in STS Software Systems Ltd. v. Witness Systems, Inc. et al., U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Nov. 20, 2007.

Witness Systems, Inc., claim chart exhibits from Expert Report of Dr. David D. Clark on Invalidity (Exhibit P—13 pgs.; Exhibit Q—13 pgs. Exhibit R—22 pgs.; Exhibit S—50 pgs.; Exhibit T—24 pgs.; Exhibit U—66 pgs.; Exhibit V—41 pgs.; and Exhibit W—36 pgs.), submitted to the Court in STS Software Systems Ltd. v. Witness Systems, Inc. et al., U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Nov. 20, 2007.

Witness Systems, Inc., Rebuttal Expert Report of Dr. David D. Clark (115 pgs.), with claim chart exhibits (Exhibit E—35 pgs.; Exhibit J—36 pgs.; and Exhibit O—58 pgs.), submitted to the Court in *STS Software Systems Ltd.* v. *Witness Systems, Inc. et al.*, U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Nov. 20, 2007.

Witness Systems, Inc., claim chart exhibits from Rebuttal Expert Report of Dr. David D. Clark (Exhibit P—12 pgs.; Exhibit Q—12 pgs.; Exhibit R—19 pgs.; Exhibit S—47 pgs.; Exhibit U—63 pgs.; Exhibit V—37 pgs.; and Exhibit W—32 pgs.), submitted to the Court in STS Software Systems Ltd. v. Witness Systems, Inc. et al., U.S. District Court, Northern District of Georgia, Atlanta Division, Case No. 1:04-CV-2111-RWS on Nov. 20, 2007.

Magar, Surendar S. et al., "A Microcomputer with Digital Signal Processing Capability," Session II: Digital Signal Processors, ISSCC 82, IEEE, 1982, 4 pages.

Abadjieva, Elissaveta et al., "Applying Analysis of Human Emotional Speech to Enhance Synthetic Speech," The MicroCentre, Department of Mathematics and Computer Science, The University, Scotland, U.K., 1993, pp. 909-912.

Wilpon, Jay G. et al., "Automatic Recognition of Keywords in Unconstrained Speech Using Hidden Markov Models," IEEE Transactions on Acoustics, Speech, and Signal Processing, vol. 38, No. 11, Nov. 1990, pp. 1870-1878.

Frick, Robert W., "Communicating Emotion: The Role of Prosodic Features," Psychological Bulletin, vol. 97, No. 3, 1985, pp. 412-429. Byun, Jae W. et al., "The Design and Analysis of an ATM Multicast Switch with Adaptive Traffic Controller," IEEE/ACM Transactions on Networking, vol. 2, No. 3, Jun. 1994, pp. 288-298.

Oppenheim, Alan V. et al., "Digital Signal Processing," Prentice-Hall, Inc., Englewood Cliffs, New Jersey, 1974, 4 pages.

Rose, Richard C., "Discriminant Wordspotting Techniques for Rejecting Non-Vocabulary Utterances in Unconstrained Speech," IEEE, 1992, pp. 105-108.

Engineering and Operations in the Bell System (Second edition), Members of the Technical Staff and the Technical Publication Department, AT&T Bell Laboratories, Murray Hill, New Jersey, 1984, 6 pages.

Callegati, Franco et al., "On the Dimensioning of the Leaky Bucket Policing Mechanism for Multiplexer Congestion Avoidance," IEEE, 1993, pp. 617-621.

Erimli, Bahadir et al., "On Worst Case Traffic in ATM Networks," The Institution of Electrical Engineers, IEE, Savoy Place, London, U.K., 1995, 12 pages.

Bullock, Darcy et al., "Roadway Traffic Control Software," IEEE Transactions on Control Systems Technology, vol. 2, No. 3, Sep. 1994, pp. 255-264.

Cahn, Janet E., "The Generation of Affect in Synthesized Speech," Journal of the American Voice I/O Society, vol. 8 (Jul. 1990), pp. 1-19.

Rabiner, Lawrence R., "A Tutorial on Hidden Markov Models and Selected Applications in Speech Recognition," Proceedings of the IEEE, vol. 77, No. 2 (Feb. 1989), pp. 257-286.

Southcott, C.B. et al., "Voice Control of the Pan-European Digital Mobile Radio System," IEEE, 1989, pp. 1070-1074.

Nice Systems Ltd.'s content analysis package, "Emotion Detection," Ra'Anana, Israel, 2005, 33 pages.

Liscombe, Jackson et al., "Classifying Subject Ratings of Emotional Speech Using Acoustic Features," Department of Computer Science, Columbia University, New York City, 4 pgs.

Dellaert, Frank et al., "Recognizing Emotion in Speech," School of Computer Science, Carnegie Mellon University, Pittsburg, Pennsylvania, 4 pgs.

Rosenberg, Andrew et al., Acoustic/Prosodic and Lexical Correlates of Charismatic Speech, Department of Computer Science, Columbia University, New York, USA., 4 pgs.

Rosenberg, Andrew et al., "On the Correlation between Energy and Pitch Accent in Read English Speech," Department of Computer Science, Columbia University, New York, USA., 4 pgs.

Leath, Ted, "Audient: An Acoustic Search Engine," Supervisor: Prof. Paul McKevitt, Research plan. Faculty of Engineering, University of Ulster, Magee, Londonderry, 14 pgs.

Holfelder, W., "Interactive Remote Recording and Playback of Multicase Videoconferences," in Interactive Distributed Multimedia Systems and Telecommunications Services, 4th International Workshop, IDMS '97, Darmstadt, Germany, 450-463 (Sep. 10-12, 1997 Proceedings, Steinmetz, R. and Wolf, L. Eds).

Glover, Mark V., "Internetworking: Distance Learning 'To Sea' via Disktop Videoconferencing Tools and IP Multicast Protocols" (Mar. 1998) (unpublished M. Sc. Thesis, Naval Postgraduate School, Monterey, California).

Maxemchuk, N.F., "An Experimental Speech Storage and Editing Facility," American Telephone and Telegraph Company, The Bell System Technical Journal, vol. 59, No. 8 (Oct. 1980), pp. 1383-1395. Nicholson, Robert T., "Integrating Voice in the Office World," Byte Publications Inc., McGraw-Hill, vol. 8, No. 12 (Dec. 1983), pp. 177-184.

Schmandt, Chris et al., "An Audio and Telephone Server for Multi-Media Workstations," Media Laboratory, Massachusetts Institute of Technology, IEEE, 1988, pp. 150-159.

Thomas, Robert H. et al., "Diamond: A Multimedia Message System Built on a Distributed Architecture," IEEE, (Dec. 1985), pp. 65-78. Academia Weighs in on Speech Analysis (WSNB019379).

Cohen, Danny, USC/ISI, Summary of the ARPA/Ethemet Community Meeting, Xerox-PARC, Nov. 1979, 16 pgs.

Clark, main loop for Internet protocol (WSISTS066835-WSISTS066838), Dec. 3, 1979.

O'Mahony, Dr. Donal, Network & Telecommunications Research Group, Trinity College Dublin, 1998, 80 pgs.

Saltzer, Jerome H. et al., "The Desktop Computer as a Network Participant," IEEE Journal on Selected Areas in Communications, vol. SAC-3, No. 3 (May 1985), pp. 468-478.

Nance, Barry, "Your PC's Ringing—Answer It!," CMP Media LLC, Byte Digest, Byte.com, (archived Feb. 1997), 5 pgs.

Jamison, Nancy, "Speech Analytics in the Contact Center: Optimizing Workforce Optimization," Jamison Consulting, 5 pgs.

Jamison, Nancy, (first revised Abstract) "Speech Analytics in the Contact Center: Optimizing Workforce Optimization," Jamison Consulting, 6 pgs.

Jamison, Nancy, (second revised Abstract) "Speech Analytics in the Contact Center: Optimizing Workforce Optimization," Jamison Consulting, 7 pgs.

Jamison, Nancy, (third revised Abstract) "Speech Analytics in the Contact Center: Optimizing Workforce Optimization," Jamison Consulting, 6 pgs.

Jamison, Nancy, (fourth revised Abstract) "Speech Analytics in the Contact Center: Optimizing Workforce Optimization," Jamison Consulting, 4 pgs.

Word Spotting vs. Topic Identification (WSNB004077).

Russ, Donna, "Speech Recognition: Ripe for the Picking," Customer Interface (Jun. 2002), 3 pgs.

Neustein, Amy, "Using Sequence Package Analysis to Improve Natural Language Understanding," Linguistic Technology Systems, New York, New York, Kluwer Academic Publishers, International Journal of Speech Technology vol. 4 (2001), pp. 31-44.

Neustein, Amy, "Sequence Package Analysis: A Data Mining Tool to Speed Up Wiretap Analysis," Linguistic Technology Systems, Edgewater, New Jersey, presented at AVIOS May 10, 2002, 4 pgs. "Speech Analytics—The Art of Automated Voice Analysis in the Contact Center," Robert Frances Group IT Agenda, Feb. 26, 2002, 4 pgs.

Coffee, Peter, "Speech Server Launch Re-asks Old Questions," 1 pg. Herrell, Elizabeth, "Telephony @Work Globalizes Contact Center Platform with Multi-Lingual Support," IdeaByte, copyright 2002 Giga Information Group, Mar. 11, 2002, 1 pg.

Neustein, Ph.D., Amy, "Sequence Package Analysis: a New Natural Language Understanding Method for Performing Data Mining of Help-Line Calls and Doctor-Patient Interviews," Linguistic Technology Systems, Edgewater, New Jersey, published proceedings of the

Natural Language Understanding and Cognitive Science Workshop at the 6th ICEIS (University of Portugal, Apr. 13, 2004), 11 pgs. Neustein, Ph.D. Amy, "A New Natural Language Method for Performing Efficient Mining of Government Tape-Recordings of the Conversations of Terror Suspects," Linguistic Technology Systems,


Edgewater, New Jersey, 5 pgs. Lazarus, David, "Now call centers can make Nice on Phone," SFGate.com, Jan. 30, 2005, 4 pgs.


Herrell, Elizabeth, "Genesys and VoiceGenie: Speech Leaders Merge," QuickTake, Forrester Research, Apr. 11, 2006, 2 pgs. Autonomy Group, "Understanding how your company thinks," 1 pg. (WSNB011874).

McCanne, et al., "The BSD Packet Filter: A New Architecture for User-level Packet Capture," Lawrence Berkeley Laboratory, Berkeley, California, (preprint of paper to be presented at the 1993 Winter USENIX conference, Jan. 25-29, 1993, San Diego, California), (Dec. 19, 1992), 11 pgs.

So-Lin Yen et al., "Intelligent MTS Monitoring System", Oct. 1994, pp. 185-187, Scientific and Research Center for Criminal Investigation, Taiwan, Republic of China.

\* cited by examiner








FIG. 3

# **PARAMETERS**

- NON-VOICE ELEMENTS
- INTERACTIVE VOICE RESPONSE PROMPTS
- COMPUTER SYNTHESIZED SPEECH
- BACKGROUND NOISE
- THE RELATIONSHIP BETWEEN TRANSMISSIONS IN EACH DIRECTION
- THE AMPLITUDE ENVELOPE OF THE SIGNALS
- THE FREQUENCY SPECTRUM OF THE SIGNAL
- THE ACTUAL SPEAKER
- MEASURES OF THE SPEED OF INTERACTION
- THE SEX OF THE SPEAKER(S)
- THE PRESENCE OR ABSENCE OF PARTICULAR WORDS
- THE FREQUENCY AND CONTENT OF PROSODY
- DATE, TIME, DURATION AND DIRECTION OF CALL
- EXTERNALLY GENERATED "TAGGING" INFORMATION
- DEGREE OF INTERRUPTION (I.E. OVERLAP BETWEEN AGENT TALKING AND CUSTOMER TALKING);
- COMMENTS MADE DURING MUSIC OR ON-HOLD PERIODS;
- DELAYS EXPERIENCED BY CUSTOMERS
- CALLER/AGENT TALK RATIOS
- "RELAXED/STRESSED" PROFILE (I.E. DETERMINING CHANGES IN VOLUME, SPEED AND TONE OF SPEECH)
- FREQUENCY OF KEYWORDS HEARD
- FREQUENCY OF REPEAT CALLS
- LANGUAGES USED BY CALLERS
- NORMAL SPEECH PATTERNS OF AGENTS

FIG. 4

<u>NEW</u>

## SIGNAL MONITORING APPARATUS ANALYZING VOICE COMMUNICATION CONTENT

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

This application is a reissue of U.S. patent application Ser. No. 10/073,966, filed Feb. 14, 2002, now U.S. Pat. No. 6,757, 361. U.S. patent application Ser. No. 10/073,966 is a division of U.S. patent application Ser. No. 09/500,800, filed Feb. 10, 2000, now U.S. Pat. No. 6,404,857. U.S. patent application Ser. No. 09/500,800 is a division of U.S. patent application Ser. No. 08/936,428, filed Sep. 24, 1997, now abandoned claims foreign priority to United Kingdom Patent Application 9620082, filed Sep. 26, 1996.

# CROSS-REFERENCE TO RELATED APPLICATIONS

Notice: More than one reissue application has been filed for the reissue of U.S. Pat. No. 6,757,361. The reissue applications are: "Voice Interaction Analysis Module," Ser. No. 11/509,553, filed on Aug. 24, 2006; "Machine Learning Based Upon Feedback From Contact Center Analysis," Ser. 30 No. 11/509,550, filed on Aug. 24, 2006; "Distributed Analysis" of Voice Interaction Data," Ser. No. 11/509,554, filed on Aug. 24, 2006; "Distributed Recording of Voice Interaction Data," Ser. No. 11/509,552, filed on Aug. 24, 2006; "VoIP Voice Interaction Monitor," Ser. No. 11/509,549, filed on Aug. 24, 35 2006; "VoIP Voice Interaction Recorder," Ser. No. 11/509, 551, filed on Aug. 24, 2006; and, "Communication Management System for Network-Based Telephones," Ser. No. 11/583,381, filed on Oct. 19, 2006, all of which are divisional reissues of "Signal Monitoring Apparatus Analyzing Voice Communication Content," Ser. No. 11/477,124, filed on Jun. 28, 2006 (the present application), which is a reissue of U.S. Pat. No. 6,757,361, issued on Jun. 29, 2004.

## BACKGROUND OF THE INVENTION

The present invention relates to signal monitoring apparatus and in particular, but riot exclusively to telecommunications monitoring apparatus which may be arranged for monitoring a plurality of telephone conversations.

## DESCRIPTION OF THE RELATED ART

Telecommunications networks are increasingly being used for the access of information and for carrying out commercial and/or financial transactions. In order to safeguard such use of the networks, it has become appropriate to record the two-way telecommunications traffic, whether voice traffic or data traffic, that arises as such transactions are carried out. The 60 recording of such traffic is intended particularly to safeguard against abusive and fraudulent use of the telecommunications network for such purposes.

More recently, so-called "call-centers" have been established at which operative personnel are established to deal 65 with enquiries and transactions required of the commercial entity having established the call-center. An example of the

2

increasing use of such call-centers is the increasing use of "telephone banking" services and the telephone ordering of retail goods.

Although the telecommunications traffic handled by such call-centers is monitored in an attempt to preserve the integrity of the call-centre, the manner in which such communications networks, and their related call-centers, are monitored are disadvantageously limited having regard to the data/information that can be provided concerning the traffic arising in association with the call-center.

For example, in large call-centers, it is difficult for supervisors to establish with any confidence that they have accurately, and effectively, monitored the quality of all their staff's work so as to establish, for example, how well their staff are handling customers' enquiries and/or transaction requirements, or how well their staff are seeking to market/publicise a particular product etc.

#### SUMMARY OF THE INVENTION

The present invention seeks to provide for telecommunications monitoring apparatus having advantages over known such apparatus.

According to one aspect of the present invention there is provided signal monitoring apparatus comprising:

means for monitoring signals representing communications traffic;

means for identifying at least one predetermined parameter by analysing the content of at least one monitored signal; means for recording the occurrence of the identified parameter;

means for identifying the traffic stream associated with the identified parameter;

means for analysing the recorded data relating to the said occurrence; and

means, responsive to the analysis of the said recorded data, for controlling the handling of communications traffic within the apparatus.

Preferably, the means for controlling the handling of the communications traffic serves to identify at least one section of traffic relative to another.

Also, the means for controlling may serve to influence further monitoring actions within the apparatus.

Advantageously, the analysed contents of the at least one signal comprise the interaction between at least two signals of traffic representing an at least two-way conversation. In particular, the at least two interacting signals relate to portions of interruption or stiltedness within the traffic.

Preferably, the means for monitoring signals can include means for recording signals.

Preferably, the means for recording the occurrence of the parameter comprises means for providing, in real time, a possibly instantaneous indication of said occurrence, and/or comprises means for storing, permanently or otherwise, information relating to said occurrence.

Dependent upon the particular parameter, or parameters, relevant to a call-center provider, the present invention advantageously allows for the improved monitoring of traffic so as to identify which one(s) of a possible plurality of data or voice interactions might warrant further investigation whilst also allowing for statistical trends to be recorded and analysed.

The apparatus is advantageously arranged for monitoring speech signals and indeed any form of telecommunication traffic.

For example, by analysing a range of parameters of the signals representing traffic such as speech, data or video, patterns, trends and anomalies within a plurality of interac-

tions can be readily identified and these can then be used for example, to influence future automated analysis, and rank or grade the conversations and/or highlight conversations likely to be worthy of detailed investigation or playback by the call-center provider. The means for monitoring the telecommunications signals may be advantageously arranged to monitor a plurality of separate two-way voice, data or video conversations, and this makes the apparatus particularly advantageous for use within a call-centre.

The means for monitoring the telecommunications signals advantageously arranged to monitor the signals digitally by any one variety of appropriate means which typically involve the use of high impedance taps into the network and which have little, or no, effect on the actual network.

It should of course be appreciated that the invention can be arranged for monitoring telecommunications signals transmitted over any appropriate medium, for example a hardwired network comprising twisted pair or co-axial lines or indeed a telecommunications medium employing radio 20 waves.

In cases where the monitored signal is not already in digital form, the apparatus can advantageously include analogue/digital conversion means for operating on the signal produced by the aforesaid means for monitoring the telecommunications signals.

It should also be appreciated that the present invention can comprise means for achieving passive monitoring of a telecommunications network or call-centre etc.

The means for identifying the at least one predetermined parameter advantageously includes a Digital Signal Processor which can be arranged to operate in accordance with any appropriate algorithm. Preferably, the signal processing required by the means for identifying the at least one parameter can advantageously be arranged to be provided by spare capacity arising in the Digital Signal Processors found within the apparatus and primarily arranged for controlling the monitoring, compression and/or recording of signals.

As mentioned above, the particular parameters arranged to 40 be identified by the apparatus can be selected from those that are considered appropriate to the requirements of, for example, the call-centre provider.

However, for further illustration, the following is a non-exhaustive list of parameters that could be identified in accor- 45 dance with the present invention and assuming that the telecommunications traffic concerned comprises a plurality of two-way telephone interactions such as conversations:

non-voice elements within predominantly voice-related interactions for example dialling, Interactive Voice 50 Response Systems, and recorded speech such as interactive voice response prompts, computer synthesized speech or background noise such as line noise;

the relationship between transmissions in each direction, for example the delay occurring, or the overlap between, 55 transmissions in opposite directions;

the amplitude envelope of the signals, so as to determine caller anger or episodes of shouting;

the frequency spectrum of the signal in various frequency bands;

advanced parameters characterizing the actual speaker which may advantageously be used in speech authentication;

measures of the speed of interaction, for example for determining the ratio of word to inter-word pauses;

the language used by the speaker(s);

the sex of the speaker(s);

4

the presence or absence of particular words, for example word spotting using advanced speech recognition techniques;

the frequency and content of prosody including pauses, repetitions, stutters and nonsensical utterances in the conversation;

vibration or tremor within a voice; and

the confidence/accuracy with which words are recognized by the receiving party to the conversation so as to advantageously identify changes in speech patterns arising from a caller.

Parameters such as the following, and having no direct relationship to each call's content, can also be monitored:

date, time, duration and direction of call:

externally generated "tagging" information for transferred calls or calls to particular customers;

As will be appreciated, the importance of each of the above parameters and the way in which they can be combined to highlight particular good, or bad, caller interactions can be readily defined by the call-center provider.

Advantageously, the apparatus can be arranged so as to afford each of the parameters concerned a particular weighting, or relative value.

The apparatus may of course also be arranged to identify the nature of the data monitored, for example whether speech, facsimile, modem or video etc. and the rate at which the signals are monitored can also be recorded and adjusted within the apparatus.

According to a further feature of the invention, the means for identifying the at least one parameter can be arranged to operate in real time or, alternatively, the telecommunications signals can be recorded so as to be monitored by the means for identifying at least one parameter at some later stage.

Advantageously, the means for recording the actual occurrence of the identified parameter(s) can be arranged to identify an absolute value for such occurrences within the communications network and/or call-centre as a whole or, alternatively, the aforementioned recording can be carried out on a per-conversation or a per-caller/operative basis.

The means for recording the occurrence of the identified parameter(s) can advantageously be associated means for analysing the results of the information recorded so as to identify patterns, trends and anomalies within the telecommunications network and/or call-center.

Advantageously, the means for recording the occurrence of the identified parameter(s) can, in association with the means for identifying the predetermined parameter and the means for monitoring the telecommunications signals, be arranged to record the aforementioned occurrence in each of the two directions of traffic separately.

Preferably, the means for identifying the source of the two-way traffic includes means for receiving an identifier tagged on to the traffic so as to identify its source, i.e. the particular operative within the call-centre or the actual caller. Alternatively, means can be provided within the telecommunications monitoring apparatus for determining the terminal number, i.e. the telephone number, of the operative and/or the caller.

The aforementioned identification can also be achieved by way of data and/or speech recognition.

It should also be appreciated that the present invention can include means for providing an output indicative of the required identification of the at least one predetermined parameter. Such output can be arranged to drive audio and/or visual output means so that the call-centre provider can readily identify that a particular parameter has been identified and in which particular conversation the parameter has

occurred. Alternatively, or in addition, the occurrence of the parameter can be recorded, on any appropriate medium for later analysis.

Of course, the mere single occurrence of a parameter need not establish an output from such output means and the apparatus can be arranged such that an output is only provided once a decision rule associated with such parameter(s) has been satisfied. Such a decision rule can be arranged such that it depends on present and/or past values of the parameter under consideration and/or other parameters.

Further, once a particular conversation has been identified as exhibiting a particular predetermined parameter, or satisfying a decision rule associated with such parameters, the apparatus can be arranged to allow ready access to the telecommunications "line" upon which the conversation is occurring so that the conversation can be interrupted or suspended as required.

As mentioned previously, the apparatus can be arranged to function in real time or, alternatively, the apparatus can include recording means arranged particularly to record the telecommunications traffic for later monitoring and analysis.

Preferably, the apparatus includes means for reconstructing the signals of the telecommunications traffic to their original form so as, for example, to replay the actual speech as it was delivered to the telecommunications network and/or call-center.

The apparatus can therefore advantageously recall the level of amplification, or attenuation, applied to the signal so as to allow for the subsequent analysis of the originating signal with its original amplitude envelope.

Further, the apparatus may include feedback means arranged to control the means for monitoring the telecommunications signals responsive to an output from means being provided to identify the source of the conversation in which the parameter has been identified, or the decision rule associated with the parameter has been exceeded.

A further embodiment of the present invention comprises 40 an implementation in which means for recording and analysing the monitored signals are built into the actual system providing the transmission of the original signals so that the invention can advantageously take the form of an add-in card to an Automatic Call Distribution System or any other telecommunications system.

Also, it will be appreciated that the present invention can be advantageously arranged so as to be incorporated into a call-centre and indeed the present invention can provide for such a call-centre including apparatus as defined above.

In accordance with another aspect of. the present invention, there is provided a method of monitoring signals representing communications traffic, and comprising the steps of:

identifying at least one predetermined parameter associated with a monitored signal:

recording the occurrence of the identified parameter: and identifying the traffic stream in which the parameter was identified.

The invention is therefore particularly advantageous in allowing the monitoring of respective parts of an at least two-way conversation and which may include the of analysis of the interaction of those parts.

Of course, the method of the present invention can advan- 65 tageously be arranged to operate in accordance with the further apparatus features defined above.

6

#### BRIEF DESCRIPTION OF THE DRAWINGS

The invention is described further hereinafter, by way of example only, with reference to the accompanying drawings in which:

FIG. 1 is a block diagram of a typical recording and analysis system embodying the present invention; [and]

FIG. 2 is a diagram illustrating a typical data packetisation format employed within the present invention[.];

FIG. 3 is a flowchart of an example process for monitoring communications traffic; and

FIG. 4 is a list of exemplary parameters.

#### DESCRIPTION OF THE EMBODIMENT

As mentioned above, the apparatus can advantageously form part of a call-centre in which a plurality of telephone conversations can be monitored so as to provide the call-centre operator with information relating to the "quality" of the service provided by the call-centre operatives. Of course, the definition of "quality" will vary according to the requirements of the particular call-centre and, more importantly, the requirements of the customers to that call-centre but typical examples are how well the call-centre operatives handle customers telephone calls, or how well an Interactive Voice Response System serves customers calling for, for example, product details.

The system generally comprises apparatus for the passive monitoring of voice or data signals, algorithms for the analysis of the monitored signals and, apparatus for the storage and reporting of the results of the analysis.

Optional features can include apparatus for recording the actual monitored signals particularly if real time operation is not required, and means for reconstructing the monitored signals into their original form so as to allow for, for example, replay of the speech signal.

FIG. 1 is a block diagram of a recording and analysis system for use in association with a call-centre 10 which includes an exchange switch 14 from which four telephone terminals 12 extend: each of which is used by one of four call-centre operatives handling customer enquiries/transactions via the exchange switch 14.

The monitoring apparatus 16 embodying the present invention, comprises a digital voice recorder 18 which is arranged to monitor the two-way conversation traffic associated with the exchange switch 14 by way of high impedance taps 20, 22 which are connected respectively to signal lines 24, 26 associated with the exchange switch 14 (*Step 302; FIG. 3*). As will be appreciated by the arrows employed for the signal lines 24, 26, the high impedance tap 20 is arranged to monitor outgoing voice signals from the call-centre 10 whereas the high impedance tap 22 is arranged to monitor incoming signals to the call-centre 10. The voice traffic on the lines 24, 26 therefore form a two-way conversation between a call-centre operative using one of the terminals 12 and a customer (not illustrated).

The monitoring apparatus 16 embodying the present invention further includes a computer telephone link 28 whereby data traffic appearing at the exchange switch 14 can be monitored as required.

The digital voice recorder 18 is connected to a network connection 30 which can be in the form of a wide area network (WAN), a local area network (LAN) or an internal bus of a central processing unit of a computer.

Also connected to the network connection 30 is a replay station 32, a configuration management application station 34, a station 36 providing speech and/or data analysis engine(s) and also storage means comprising a first storage

means 38 for the relevant analysis rules and the results obtained and a second storage means 40 for storage of the data and/or speech monitor.

FIG. 2 illustrates the typical format of a data packet 42 used in accordance with the present invention and which comprises a packet header 44 of typically 48 bytes and a packet header 46 of typically of 2000 bytes.

The packet header is formatted so as to include the packet identification 48, the data format 50, a date and time stamp 52, the relevant channel number within which the data arises 54, 10 the gain applied to the signal 56 and the data length 58.

The speech, or other data captured in accordance with the apparatus of the present invention, is found within the packet body 46 and within the format specified within the packet header 44.

The high impedance taps 20, 22 offer little or no effect on the transmission lines 24, 26 and, if not in digital form, the monitored signal is converted into digital form. For example, when the monitored signal comprises a speech signal, the signal is typically converted to a pulse code modulated 20 (PCM) signal or is compressed as an Adaptive Differential PCM (ADPCM) signal.

Further, where signals are transmitted at a constant rate, the time of the start of the recordings is identified, for example by voltage or activity detection, i.e. so-called "vox" level detection, and the time is recorded. With asynchronous data signals, the start time of a data burst, and optionally the intervals between characters, may be recorded in addition to the data characters themselves.

The purpose of this is to allow a computer system to model 30 the original signal to appropriate values of time, frequency and amplitude so as to allow the subsequent identification of one or more of the various parameters arising in association with the signal (*see*, *FIG*. 4). The digital information describing the original signals is then analysed at station 36 (*Step* 35 304; *FIG*. 3), in real time or later, to determine the required set of metrics, i.e. parameters, appropriate to the particular application (*Step* 306; *FIG*. 3).

FIG. 3 is a flowchart of an example process 300 for monitoring communications traffic. At stage 302, signals repre-40 senting communications traffic are monitored. For example, the digital voice recorder 18 can monitor two-way conversation traffic associated with the exchange switch 14. At stage 304, a predetermined parameter is identified by analyzing the content. For example, a digital signal processor programmed 45 with an appropriate algorithm can identify the predetermined parameter. At stage 306, the occurrence of the identified parameter is recorded. For example, the first storage 38 (analysis rules and results) can store the occurrence of the identified parameter. At stage 308, the traffic stream associ- 50 ated with the parameter is identified. For example, the speech/ data analysis engine 36 can identify the traffic stream. At stage 310, the recorded data relating to the occurrence is analyzed. For example, the speech/data analysis engine 36 can analyze the recorded data stored in the first storage 38.

A particular feature of the system is in recording the two directions of data transmission separately so allowing further analysis of information sent in each direction independently. In analogue telephone systems, this may be achieved by use of a four-wire (as opposed to two-wire) circuit whilst in 60 digital systems, it is the norm to have the two directions of transmission separated onto separate wire pairs. In the data world, the source of each data packet is typically stored alongside the contents of the data packet.

A further feature of the system is in recording the level of amplification or attenuation applied to the original signal. This may vary during the monitoring of even a single inter-

8

action (e.g. through the use of Automatic Gain Control Circuitry). This allows the subsequent reconstruction and analysis of the original signal amplitude.

Another feature of the system is that monitored data may be "tagged" with additional information such as customer account numbers by an external system (e.g. the delivery of additional call information via a call logging port or computer telephony integration (CTI) port).

The importance of each of the parameters and the way in which they can be combined to highlight particularly good or bad interactions is defined by the user of the system (*Step 308; FIG. 3*). One or more such analysis profiles can be held in the system. These profiles determine the weighting given to each of the above parameters.

The profiles are normally used to rank a large number of monitored conversations and to identify trends, extremes, anomalies and norms. "Drill-down" techniques are used to permit the user to examine the individual call parameters that result in an aggregate or average same and, further, allow the user to select individual conversations to be replayed to confirm or reject the hypothesis presented by the automated analysis.

A particular variant that can be employed in any embodiment of the present invention uses feedback from the user's own scoring of the replayed calls to modify its own analysis algorithms (*Step 310; FIG. 3*). This may be achieved using neural network techniques or similar giving a system that learns from the user's own view of the quality of recordings.

A variant of the system uses its own and/or the scoring/ ranking information to determine its further patterns of operation i.e.

determining which recorded calls to retain for future analysis,

determining which agents/lines to monitor and how often, and

determining which of the monitored signals to analyse and to what depth.

In many systems it is impractical to analyse all attributes of all calls hence a sampling algorithm may be defined to determine which calls will be analysed. Further, one or more of the parties can be identified (e.g. by calling-line identifier for the external party or by agent log-on identifiers for the internal party). This allows analysis of the call parameters over a number of calls handled by the same agent or coming from the same customer.

The system can use spare capacity on the digital signal processors (DSPs) that control the monitoring, compression or recording of the monitored signals to provide some or all of the analysis required. This allows analysis to proceed more rapidly during those periods when fewer calls are being monitored.

Spare CPU capacity on a PC at an agent's desk could be used to analyse the speech. This would comprise a secondary tap into the speech path being recorded as well as using "free" CPU cycles. Such an arrangement advantageously allows for the separation of the two parties, e.g. by tapping the headset/handset connection at the desk. This allows parameters relating to each party to be stored even if the main recording point can only see a mixed signal.

A further variant of the system is an implementation in which the systems recording and analysing the monitored signals are built into the system providing the transmission of the original signals (e.g. as an add-in card to an Automatic Call Distribution (ACD) system).

The apparatus illustrated is particularly useful for identifying the following parameters:

degree of interruption (i.e. overlap between agent talking and customer talking);

comments made during music or on-hold periods;

delays experienced by customers (i.e. the period from the end of their speech to an agent's response);

caller/agent talk ratios, i.e. which agents might be talking too much.

However, it should be appreciated that the invention could 10 be adapted to identify parameters such as:

"relaxed/stressed" profile of a caller or agent (i.e. by determining changes in volume, speed and tone of speech)

frequency of keywords heard (separately from agents and from callers) e.g. are agents remembering to ask follow- 15 up questions about a certain product/service etc; or how often do customers swear at each agent? Or how often do agents swear at customers?

frequency of repeat calls. A combination of line, ID and caller ID can be provided to eliminate different people 20 calling from single switchboard/business number

languages used by callers?

abnormal speech patterns of agents. For example if the speech recognition applied to an agent is consistently and unusually inaccurate for, say, half an hour, the agent 25 should be checked for: drug abuse, excessive tiredness, drunkenness, stress, rush to get away etc.

It will be appreciated that the illustrated and indeed any embodiments of the present invention can be set up as follows.

The Digital Trunk Lines (e.g. T1/E1) can be monitored trunk side and the recorded speech tagged with the direction of speech. A MediaStar Voice Recorder chassis can be provided typically with one or two E1/T1 cards plus a number of DSP cards for the more intense speech processing require- 35 ments.

Much of its work can be done overnight and in time, some could be done by the DSPs in the mediastar's own cards: It is also necessary to remove or at least recognise, periods of music, on-hold periods, IVR rather than real agents speaking 40 etc. thus, bundling with Computer Integrated Telephony Services such as Telephony Services API (TSAPI) in many cases is appropriate.

Analysis and parameter identification as described above can then be conducted. However, as noted, if it is not possible 45 to analyse all speech initially, analysis of a recorded signal can be conducted.

In any case the monitoring apparatus may be arranged to only search initially for a few keywords although re-play can be conducted so as to look for other keywords.

It should be appreciated that the invention is not restricted to the details of the foregoing embodiment. For example, any appropriate form of telecommunications network, or signal transmission media, can be monitored by apparatus according to this invention and the particular parameters identified 55 provide a real-time indication of the occurrence. can be selected, and varied, as required.

What is claimed is:

- 1. A signal monitoring system for monitoring and analyzing voice communications [passing through a monitoring point, the system comprising:
  - a digital voice recorder [(18) for ] operable to monitor [ing] two-way conversation traffic streams passing through [the] a monitoring point, said digital voice recorder having connections [(20)] for being operatively [attached] coupled to the monitoring point;
  - [a digital processor (30) connected] a speech analysis engine operable to analyze voice communications

**10** 

received by the system, the speech analysis engine being coupled to said digital voice recorder [for] and operable to identify [ing] at least one non-speech recognition predetermined parameter by analyzing [the] voice communication content of at least one monitored signal taken from the traffic streams; and

- a recorder [(38)] attached to said [digital processor] speech analysis engine for recording occurrences of the nonspeech recognition predetermined parameter[;],
- [a traffic stream identifier (36) for identifying the traffic stream associated with the predetermined parameter;
- a data analyzer (36) connected to said digital processor for analyzing the recorded data relating to the occurrences; and
- a communication traffic controller (34) operatively connected to said data analyzer and, operating responsive to the analysis of the recorded data, for controlling the handling of communications traffic within said monitoring system
- wherein the speech analysis engine automatically identifies an occurrence of said at least one non-speech recognition predetermined parameter in a voice interaction.
- 2. The monitoring system of claim 1, wherein said at least one non-speech recognition predetermined parameter includes a frequency of keywords identified in the voice communication content of the at least one monitored signal.
- 3. The monitoring system of claim 1, wherein said [digital] processor speech analysis engine further identifies episodes of anger or shouting by analyzing amplitude envelope.
  - 4. The monitoring system of claim 1, wherein said at least one non-speech recognition predetermined parameter is a prosody of the voice communication content of the at least one monitored signal.
  - [5. The monitoring system of claim 1, wherein said connections for being operatively attached to the telephony exchange switch are attached via high impedance taps (20) to telephone signal lines (24, 26) attached to said telephony exchange switch.
  - 6. The monitoring system of claim 1, wherein said [communication traffic controller serves speech analysis engine is operable to identify at least one section of traffic relative to another so as to identify a source of the non-speech recognition predetermined parameter.
  - 7. The monitoring system of claim 1, [wherein said] further comprising a communication traffic controller [serves] operable to influence [further] monitoring actions within the [apparatus] system.
- 8. The monitoring system of claim 1, wherein the analyzed 50 contents of the at least one monitored signal comprise the interaction between at least two signals representing an at least two-way conversation.
  - **9**. The monitoring system of claim **1**, wherein the [recorder] speech analysis engine operates in real time to
  - 10. The monitoring system of claim 1, wherein said digital voice recorder comprises an analog/digital [convertor (18)] converter for converting analog voice into a digital signal.
- 11. The monitoring system of claim 1, wherein said [digital oprocessor speech analysis engine is a [Digital Signal Processor (30)] digital signal processor arranged to operate in accordance with an analyzing algorithm.
  - 12. The monitoring system of claim 1, wherein the digital signal processor is arranged to operate in real time.
  - 13. The monitoring system of claim 1, further comprising a replay station [(32)] connected to said [digital processor] speech analysis engine and arranged such that the voice com-

munication content of the at least one monitored signal can be recorded and monitored by said [digital processor] speech analysis engine for identifying the at least one non-speech recognition parameter at some later time.

- 14. The monitoring system of claim 1, wherein the at least 5 one non-speech recognition predetermined parameter comprises plural predetermined parameters and wherein said digital voice recorder records the occurrence of the plural predetermined parameters in each of the two directions of traffic separately.
- 15. The monitoring system of claim 1, wherein said [traffic 10] stream identifier speech analysis engine comprises a means for receiving an identifier tagged onto the traffic so as to identify its source.
- 16. The monitoring system of claim 1, wherein said digital voice recorder for monitoring the traffic streams is operative 15 responsive to an output from said [traffic stream identifier] speech analysis engine identifying the source of the conversation in which the *non-speech recognition* predetermined parameter has been identified, or a threshold occurrence of the non-speech recognition predetermined parameter has 20 been exceeded.
- 17. The monitoring system of claim 1, wherein said digital voice recorder, said [digital processor, said recorder, said traffic stream identifier, and said data analyzer] speech analysis engine, reside on an add-in card to a telecommunications 25 interactions substantially in real-time. system.
- 18. The monitoring system of claim 1, wherein the telecommunications system comprises an automatic call distributor.
- 19. The monitoring system of claim 1, wherein the speech analysis engine is operable to examine incoming and outgoing traffic streams to determine whether a talk-over condition exists with respect to the voice interaction.
- 20. The monitoring system of claim 1, wherein the speech analysis engine is operable to examining incoming or outgoing traffic streams to determine whether one or more of a predetermined group of words exists with respect to the voice 35 interaction.
- 21. The monitoring system of claim 1, wherein the speech analysis engine is operable to examine incoming or outgoing traffic streams to identify stress on either or both sides of the voice interaction.

- 22. The monitoring system of claim 21, wherein stress is identified by determining changes in volume, speed and tone of speech.
- 23. The monitoring system of claim 1, wherein the speech analysis engine is operable to examine incoming or outgoing traffic streams to identify anger on either or both sides of the voice interaction.
- 24. The monitoring system of claim 23, wherein anger is identified by analyzing a voice envelope associated with the incoming or outgoing traffic streams.
- 25. The monitoring system of claim 1, wherein the speech analysis engine is operable to examine incoming and outgoing traffic streams to identify delay between transmissions in opposite directions.
- 26. The monitoring system of claim 1, wherein the speech analysis engine receives voice interactions via the digital voice recorder.
- 27. The monitoring system of claim 26, wherein voice interactions are analyzed after the voice interactions are complete.
- 28. The monitoring system of claim 1, wherein the speech analysis engine receives voice interactions via a tap, the speech analysis engine being operable to analyze the voice
- 29. The monitoring system of claim 28, wherein the speech analysis engine is operable to direct the digital voice recorder to record an interaction based upon the occurrence of one or more of said at least non-speech recognition one predeter-30 mined parameter.
  - 30. The monitoring system of claim 1, wherein the two-way conversation traffic streams comprise packetized voice data.
  - 31. The monitoring system of claim 1, wherein the speech analysis engine is operable to instruct the digital voice recorder to highlight a record associated with a voice interaction based upon the occurrence of one or more of said at least one non-speech recognition predetermined parameter.