



US00RE43348E

(19) **United States**
(12) **Reissued Patent**
Qualman et al.

(10) **Patent Number:** **US RE43,348 E**
(45) **Date of Reissued Patent:** **May 8, 2012**

(54) **TOOL FOR REMOVING VALVE SPRINGS AND VALVE GUIDE SEALS FROM AN ENGINE**

6,266,859 B1 * 7/2001 Hernandez 29/256
6,321,432 B1 11/2001 Przybyla
6,415,491 B1 * 7/2002 Klann 29/259
7,181,818 B1 * 2/2007 Qualman et al. 29/213.1
7,653,975 B2 * 2/2010 Hu 29/259

(76) Inventors: **Richard K. Qualman**, Butler, WI (US);
Karen A. Qualman, Butler, WI (US)

OTHER PUBLICATIONS

(21) Appl. No.: **11/891,617**

USPTO Office Action dated Aug. 17, 2006 regarding U.S. Appl. No. 10/929,265, 4 pages.

(22) Filed: **Aug. 10, 2007**

USPTO Office Action dated Apr. 11, 2006 regarding U.S. Appl. No. 10/929,265, 4 pages.

Related U.S. Patent Documents

* cited by examiner

Reissue of:

(64) Patent No.: **7,181,818**
Issued: **Feb. 27, 2007**
Appl. No.: **10/929,265**
Filed: **Aug. 30, 2004**

Primary Examiner — Lee D Wilson

(74) *Attorney, Agent, or Firm* — Ryan Kromholz & Manion, S.C.

(51) **Int. Cl.**
B23P 19/04 (2006.01)

ABSTRACT

(52) **U.S. Cl.** **29/213.1; 29/244; 29/278; 29/270**

A tool for removing valve springs and seals from an engine's intake and exhaust valves includes a bracket having apertures spaced therealong and for receiving fastening members there-through. The tool further includes a plurality of support pedestals provided with channels extending therethrough and for receiving the fastening members respectively so that the bracket is maintained at a substantially stable position. The tool also includes a mechanism for [simultaneously] compressing a *valve spring by exerting pressure upon a valve [head keeper and] retainer, thereby* releasing associated [locks] *keepers* so that a user can remove the valve springs and valve seals from the valve [head]. The compressing mechanism cooperates with the pedestals and the bracket and is rotatable about a fulcrum axis traversing the pedestals wherein the fulcrum axis extends along a horizontal plane subjacent the bracket.

(58) **Field of Classification Search** 29/213.1,
29/255–268, 270–278; 354/10.5


See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,566,460	A	9/1951	Mihalic
3,352,002	A	11/1967	Kryk
3,984,909	A	10/1976	Velazquez
4,223,431	A	9/1980	Skeels
4,912,825	A	4/1990	Policella
5,042,128	A	8/1991	Barbour
5,241,734	A	9/1993	Brackett
5,339,515	A	8/1994	Brackett et al.
D377,494	S	1/1997	Ewers
5,689,870	A	11/1997	Robey

27 Claims, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4

1

**TOOL FOR REMOVING VALVE SPRINGS
AND VALVE GUIDE SEALS FROM AN
ENGINE**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

CROSS REFERENCE TO RELATED
APPLICATIONS

Not Applicable.

STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT

Not Applicable.

REFERENCE TO A MICROFICHE APPENDIX

Not Applicable.

BACKGROUND OF THE INVENTION

1. Technical Field

This invention relates to a component removal tool and, more particularly, to a tool for removing valve springs and valve guide seals from an engine.

2. Prior Art

An automotive engine "valve job" involves removal of the valve cover and cylinder head, followed by disassembly and removal of each valve from the cylinder head for replacement or repair.

The valves are held in place in the cylinder head, each by a compression spring acting on the valve stem to keep it tightly closed. A dish-shaped retainer centered on top of the valve spring has a frusto-conical inner ramp surface which engages a pair of frusto-conical "keepers", forcing them into positive locking engagement with the valve stem. The two keepers are halves of a split ring, together forming a frusto-conical ring to surround and engage the inner ramp of the retainer. The inner surfaces of the keepers together form one or more circumferential keys to engage corresponding circumferential keyways near the top of the valve stem. The conical inner surface of the retainer engages the conical outer surface of the keepers to force them into locking engagement with the valve stem.

To disassemble and remove a valve, it is first necessary to further compress the valve spring, move the retainer out of engagement with the keepers, remove the keepers which are now loose, remove the retainer and spring (which are now free), then slide the valve stem (which is now free) out through the underside of the cylinder head.

The procedure described above is usually performed by using a C-clamp or the like to compress the valve spring, then using one's fingers or needle nose pliers to remove the keepers. Another expedient is the use of a lever having a notch at its end to straddle the valve stem, the fulcrum of the lever being anchored to a rocker arm stud. The lever is pivoted about the rocker arm stud to thereby compress the valve spring and permit manual removal of the keepers. All of these methods, though, still require the complete removal of the engine block from the automobile and then the cylinder head from the engine block, and other time consuming preparatory procedures.

2

Accordingly, a need remains for a tool for removing valve springs and valve guide seals from an engine to overcome the above noted shortcomings. The present invention satisfies such a need by providing a convenient, easy to use, effective and time saving tool for valve spring removal. Such a tool takes advantage of existing bolt holes in the engine block and thus requires no removal or modification of an engine block in order to use.

BRIEF SUMMARY OF THE INVENTION

In view of the foregoing background, it is therefore an object of the present invention to provide a tool for removing valve springs and valve guide seals from an engine. These and other objects, features, and advantages of the invention are provided by a tool for allowing an operator to remove valve springs and valve seals from an engine's intake and exhaust valves without requiring the removal of the engine from a support frame.

The tool includes an arcuate bracket, preferably having a generally U-shape [for extending about the engine valve head] and formed from rigid material for distributing external forces away from an engine [valve] cylinder head. Such a bracket has a plurality of apertures spaced along a perimeter thereof, including a plurality of fastening members threadably positionable therethrough for advantageously securing the bracket adjacent the [valve] cylinder head.

The present invention further includes a plurality of elongated support pedestals having predetermined uniform axial lengths respectively. Such pedestals further have vertically disposed longitudinal axes and are provided with channels extending axially therethrough respectively. The pedestals are aligned and abutted with the bracket apertures for receiving the fastening members therethrough so that the bracket can conveniently be maintained at a substantially stable and elevated position during operating conditions.

The tool also includes a mechanism for [simultaneously] compressing a valve spring by exerting pressure upon a valve [head keeper and] retainer, thereby releasing associated [locks] keepers so that a user can readily remove the valve springs and valve seals from the valve [head]. Such a compressing mechanism cooperates with the pedestals and the bracket and is manually rotatable along a selected radial direction and about a fulcrum axis traversing the pedestals wherein the fulcrum axis extends along a horizontal plane subjacent the bracket.

The compressing mechanism includes an elongated anchor bolt that defines the fulcrum axis and is disposed along a substantially horizontal plane. Such a bolt has a threaded end portion and an oppositely disposed head portion extending outwardly from the bracket respectively. The bolt head portion preferably has a substantially hexagonal shape so that a user can readily rotate same by employing a conventional ratchet and socket.

The compressing mechanism further includes a plurality of fingers secured to the bolt and extending outwardly therefrom along a generally perpendicular path to the bolt. The fingers may be medially spaced along the bolt and within an inner perimeter of the bracket and terminate above a top surface of the bracket. Each such finger has an inner surface area provided with a longitudinal axis offset from a vertical plane so that the valve [spring] retainer can be effectively engaged during operating conditions.

The mechanism also includes a plurality of stop members adjustably engaged with the bolt for defining a linear path along which the bolt can be positioned. One such stop member protrudes outwardly and orthogonally from the bolt and

3

adjacent the head portion thereof. The bolt further includes an integrally disposed collar portion extending radially therefrom adjacent to the head portion. Such a collar portion is engageable with another of the stop members as the bolt is selectively positioned along the linear path.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The novel features believed to be characteristic of this invention are set forth with particularity in the appended claims. The invention itself, however, both as to its organization and method of operation, together with further objects and advantages thereof, may best be understood by reference to the following description taken in connection with the accompanying drawings in which:

FIG. 1 is a perspective view showing a tool for removing valve springs and valve guide seals from an engine, in accordance with the present invention;

FIG. 2 is a perspective view showing the individual components of the tool in FIG. 1;

FIG. 3 is a cross-sectional view of the bolt shown in FIG. 2, taken along line 3—3; and

FIG. 4 is an exploded view of the tool shown in FIG. 1.

DETAILED DESCRIPTION OF THE INVENTION

The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which a preferred embodiment of the invention is shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiment set forth herein. Rather, this embodiment is provided so that this application will be thorough and complete, and will fully convey the true scope of the invention to those skilled in the art. Like numbers refer to like elements throughout the figures.

The tool of this invention is referred to generally in FIGS. 1–4 by the reference numeral 10 and is intended to provide a tool for removing valve springs and valve guide seals from an engine. It should be understood that the tool 10 may be used to remove valve spring and guide members on many different types of engines and should not be limited to only motorcycle engines.

Referring initially to FIG. 1, the tool 10 includes an arcuate bracket 20, having a generally U-shape [for extending about the engine valve head 31] and formed from rigid material for distributing external forces away from an engine [valve] cylinder head 31. Such a bracket 20 has a plurality of apertures 21 spaced along a perimeter thereof, including a plurality of fastening members 22 threadably positionable therethrough for advantageously securing the bracket 20 adjacent the [valve] cylinder head 31.

As is shown in FIGS. 2 and 4, the present invention further includes a plurality of elongated support pedestals 40 having predetermined uniform axial lengths respectively. Such pedestals 40 further have vertically disposed longitudinal axes and are provided with channels 41 extending axially therethrough respectively. The pedestals 40 are aligned and abutted with the bracket apertures 21 for receiving the fastening members 22 therethrough so that the bracket 20 can conveniently be maintained at a substantially stable and elevated position during operating conditions. Such a plurality of support pedestals 40 advantageously allows easy access to the functional parts of the tool 10 during operating conditions.

The tool 10 also includes a mechanism 50 for [simultaneously] compressing a valve spring 32 by exerting pressure

4

upon a valve [head keeper] retainer 90, [and] thereby releasing associated [locks] keepers 91 so that a user can readily remove the valve springs 32 and valve seals 33 from the valve [head 31]. Such a compressing mechanism 50 cooperates with the pedestals 40 and the bracket 20 and is manually rotatable along a selected radial direction and about a fulcrum axis traversing the pedestals 40 wherein the fulcrum axis extends along a horizontal plane subjacent the bracket 20. The compressing mechanism 50 conveniently decreases the amount of force needed [to compress the valve head keeper] for compression, allowing for easier and more rapid replacement of the valve spring 32 and seal 33.

As can be seen in FIGS. 2, 3 and 4, the compressing mechanism 50 includes an elongated anchor bolt 51 that defines the fulcrum axis and is disposed along a substantially horizontal plane. Such a bolt 51 has a threaded end portion 52 and an oppositely disposed head portion 53 extending outwardly from the bracket 20 respectively. The bolt head portion 53 has a substantially hexagonal shape so that a user can readily rotate same by employing a conventional ratchet and socket.

The compressing mechanism 50 further includes a plurality of fingers 54 secured to the bolt 51 and extending outwardly therefrom along a generally perpendicular path to the bolt 51. The fingers 54 are medially spaced along the bolt 51 and within an inner perimeter of the bracket 20 and terminate above a top surface 23 of the bracket 20. Each such finger 54 has an inner surface area 55 and a longitudinal axis offset from a vertical plane so that the valve [spring 32] retainer 90 can be effectively engaged during operating conditions.

The mechanism 50 also includes a plurality of stop members 56 adjustably engaged with the bolt 51 for defining a linear path along which the bolt 51 can be positioned. The stop members 56 advantageously prevent the bolt 51 from becoming disengaged from the bracket 20, effectively avoiding damage to the engine [valve] cylinder head 31. One such stop member 56 protrudes outwardly and orthogonally from the bolt 51 and adjacent the head portion 53 thereof. The bolt 51 further includes an integrally disposed collar portion 57 extending radially therefrom adjacent to the head portion 53. Such a collar portion 57 is engageable with another of the stop members 56 as the bolt 51 is selectively positioned along the linear path.

While the invention has been described with respect to a certain specific embodiment, it will be appreciated that many modifications and changes may be made by those skilled in the art without departing from the spirit of the invention. It is intended, therefore, by the appended claims to cover all such modifications and changes as fall within the true spirit and scope of the invention.

In particular, with respect to the above description, it is to be realized that the optimum dimensional relationships for the parts of the present invention may include variations in size, materials, shape, form, function and manner of operation. The assembly and use of the present invention are deemed readily apparent and obvious to one skilled in the art.

What is claimed as new and what is desired to secure by Letters Patent of the United States is:

[1. A tool for allowing an operator to remove valve springs and valve seals from an engine's intake and exhaust valves without requiring the removal of the engine from a support frame, said tool comprising:

a bracket formed from rigid material and for distributing external forces away from an engine valve head, said bracket having a plurality of apertures spaced along a perimeter thereof and comprising a plurality of fastening

5

members threadably positionable therethrough for securing said bracket adjacent the valve head;
 a plurality of support pedestals having vertically disposed longitudinal axes and being provided with a channel extending axially therethrough, said pedestals for receiving said fastening members therethrough so that said bracket can be maintained at a substantially stable and elevated position during operating conditions; and means for compressing a valve head keeper and associated locks so that a user can readily remove the valve springs and valve seals from the valve head, said compressing means cooperating with said pedestals and said bracket and being manually rotatable along a selected radial direction and about a fulcrum axis traversing said pedestals.]

[2. The tool of claim 1, wherein said compressing means comprises:

an elongated anchor bolt defining the fulcrum axis and being disposed along a substantially horizontal plane, said bolt having a threaded end portion and an oppositely disposed head portion extending outwardly from said bracket respectively;

a plurality of fingers secured to said bolt and extending outwardly therefrom along a generally perpendicular path to said bolt, each said finger having an inner surface area provided with a longitudinal axis offset from a vertical plane so that the valve spring can be effectively engaged during operating conditions; and

a plurality of stop members adjustably engaged with said bolt and for defining a linear path along which said bolt can be positioned, one said stop members protruding outwardly and orthogonally from said bolt and adjacent said head portion thereof;

wherein said fingers are rotated downwardly onto the valve spring and the valve head keeper which causes release of the associated locks, said fingers being rotatable upwardly such that the valve springs and the valve seals can be removed.]

[3. The tool of claim 2, wherein said bolt head portion has a substantially hexagonal shape so that a user can readily rotate same by employing a conventional ratchet and socket.]

[4. The tool of claim 1, wherein said bracket has a generally U-shape for extending about the engine valve head.]

[5. The tool of claim 2, wherein said fingers are medially spaced along said bolt and within an inner perimeter of said bracket, said fingers terminating above a top surface of said bracket.]

[6. The tool of claim 2, wherein said bolt further includes an integrally disposed collar portion extending radially therefrom adjacent said head portion, said collar portion being engageable with another said stop members as said bolt is selectively positioned along the linear path.]

7. A tool for allowing an operator to remove valve springs and valve seals from an engine's intake and exhaust valves without requiring the removal of the engine from a support frame, said tool comprising:

an arcuate bracket formed from rigid material and for distributing external forces away from an engine [valve] cylinder head, said bracket having a plurality of apertures spaced along a perimeter thereof and comprising a plurality of fastening members [threadably] positionable therethrough for securing said bracket adjacent the [valve] cylinder head;

a plurality of elongated support pedestals having vertically disposed longitudinal axes and being provided with [threaded] channels extending axially therethrough respectively, said pedestals being aligned and abutted

6

with the bracket apertures for receiving said fastening members therethrough so that said bracket can be maintained at a substantially stable and elevated position during operating conditions; and

means for compressing *a valve spring by exerting pressure upon a valve [head keeper and] retainer, thereby releasing associated [locks] keepers* so that a user can readily remove the valve springs and valve seals from the valve [head], said compressing means cooperating with said pedestals and said bracket and being manually rotatable along a selected radial direction and about a fulcrum axis traversing said pedestals.

8. The tool of claim 7, wherein said compressing means comprises:

an elongated anchor bolt defining the fulcrum axis and being disposed along a substantially horizontal plane, said bolt having a threaded end portion and an oppositely disposed head portion extending outwardly from said bracket respectively;

a plurality of fingers secured to said bolt and extending outwardly therefrom along a generally perpendicular path to said bolt, each said finger having an inner surface area provided with a longitudinal axis offset from a vertical plane so that the valve spring can be effectively engaged during operating conditions; and

a plurality of stop members adjustably engaged with said bolt and for defining a linear path along which said bolt can be positioned, one said stop members protruding outwardly and orthogonally from said bolt and adjacent said head portion thereof.

9. The tool of claim 8, wherein said bolt head portion has a substantially hexagonal shape so that a user can readily rotate same by employing a conventional ratchet and socket.

10. The tool of claim 7, wherein said bracket has a generally U-shape for extending about the [engine] valve [head] retainer.

11. The tool of claim 8, wherein said fingers are medially spaced along said bolt and within an inner perimeter of said bracket, said fingers terminating above a top surface of said bracket.

12. The tool of claim 8, wherein said bolt further includes an integrally disposed collar portion extending radially therefrom adjacent said head portion, said collar portion being engageable with another said stop members as said bolt is selectively positioned along the linear path.

13. A tool for allowing an operator to remove valve springs and valve seals from an engine's intake and exhaust valves without requiring the removal of the engine from a support frame, said tool comprising:

an arcuate bracket formed from rigid material and for distributing external forces away from an engine [valve] cylinder head, said bracket having a plurality of apertures spaced along a perimeter thereof and comprising a plurality of fastening members [threadably] positionable therethrough for securing said bracket adjacent the [valve] cylinder head;

a plurality of elongated support pedestals having predetermined uniform axial lengths respectively, said pedestals further having vertically disposed longitudinal axes and being provided with channels extending axially therethrough respectively, said pedestals being aligned and abutted with the bracket apertures for receiving said fastening members therethrough so that said bracket can be maintained at a substantially stable and elevated position during operating conditions; and

means for simultaneously compressing *a valve spring by exerting pressure upon a valve [head keeper] and releas-*

7

ing associated [locks] keepers so that a user can readily remove the valve springs and valve seals from the valve [head], said compressing means cooperating with said pedestals and said bracket and being manually rotatable along a selected radial direction and about a fulcrum axis traversing said pedestals wherein the fulcrum axis extends along a horizontal plane subjacent said bracket.

14. The tool of claim 13, wherein said compressing means comprises:

an elongated anchor bolt defining the fulcrum axis and being disposed along a substantially horizontal plane, said bolt having a threaded end portion and an oppositely disposed head portion extending outwardly from said bracket respectively;

a plurality of fingers secured to said bolt and extending outwardly therefrom along a generally perpendicular path to said bolt, each said finger having an inner surface area provided with a longitudinal axis offset from a vertical plane so that the valve spring can be effectively engaged during operating conditions; and

a plurality of stop members adjustably engaged with said bolt and for defining a linear path along which said bolt can be positioned, one said stop members protruding outwardly and orthogonally from said bolt and adjacent said head portion thereof.

15. The tool of claim 14, wherein said bolt head portion has a substantially hexagonal shape so that a user can readily rotate same by employing a conventional ratchet and socket.

16. The tool of claim 13, wherein said bracket has a generally U-shape for extending about the [engine] valve [head] retainer.

17. The tool of claim 14, wherein said fingers are medially spaced along said bolt and within an inner perimeter of said bracket, said fingers terminating above a top surface of said bracket.

18. The tool of claim 14, wherein said bolt further includes an integrally disposed collar portion extending radially therefrom adjacent said head portion, said collar portion being engageable with another said stop members as said bolt is selectively positioned along the linear path.

19. A tool for allowing an operator to remove valve springs and valve seals from an engine's intake and exhaust valves without requiring the removal of the engine from a support frame, said tool comprising:

a support structure adapted to be mounted fixedly relative to an engine cylinder head;

and means for compressing a valve spring by exerting pressure upon a valve retainer in a compression direction, thereby releasing associated keepers so that a user can readily remove the valve springs and valve seals from said cylinder head, said means for compressing cooperating with said support structure and being manually rotatable about a fulcrum axis positioned substantially orthogonally skew relative to said compression direction wherein said means for compressing a shaft rotatably mounted co-axial with said fulcrum axis and wherein said pressure is generated by rotation of said shaft.

20. A tool according to claim 19, said fulcrum axis defined by said shaft.

21. A tool according to claim 20, said shaft being rotatably supported by the support structure.

22. A tool according to claim 19, said support structure comprising:

a bracket formed from rigid material and for distributing external forces away from said engine cylinder head, said bracket having a plurality of apertures spaced

8

along a perimeter thereof and comprising a plurality of fastening members threadably positionable there-through for securing said bracket adjacent said cylinder head; and

a plurality of support pedestals having vertically disposed longitudinal axes and being provided with a channel extending axially therethrough, said pedestals for receiving said fastening members therethrough so that said bracket can be maintained at a substantially stable and elevated position during operating conditions.

23. A tool according to claim 22, wherein said means for compressing comprises:

an elongated anchor bolt defining said fulcrum axis and being disposed along a substantially horizontal plane, said bolt having a threaded end portion and an oppositely disposed head portion extending outwardly from said bracket respectively;

a plurality of fingers secured to said bolt and extending outwardly therefrom along a generally perpendicular path to said bolt, each said finger having an inner surface area provided with a longitudinal axis offset from a vertical plane so that the valve retainer can be effectively engaged during operating conditions; and

a plurality of stop members adjustably engaged with said bolt and for defining a linear path along which said bolt can be positioned, one of said stop members protruding outwardly and orthogonally from said bolt and adjacent said head portion thereof;

wherein said fingers are rotated downwardly onto the valve retainer which causes release of the associated keepers, said fingers being rotatable upwardly such that the valve springs and the valve seals can be removed.

24. A tool according to claim 23, wherein said bolt head portion has a substantially hexagonal shape so that a user can readily rotate same by employing a conventional ratchet and socket.

25. A tool according to claim 22, wherein said bracket has a generally U-shape.

26. A tool according to claim 23, wherein said fingers are medially spaced along said bolt and within an inner perimeter of said bracket, said fingers terminating above a top surface of said bracket.

27. A tool according to claim 23, wherein said bolt further includes an integrally disposed collar portion extending radially therefrom adjacent said head portion, said collar portion being engageable with another said stop members as said bolt is selectively positioned along the linear path.

28. A method of using a tool in conjunction with an engine including valves, the method comprising the steps of:

providing a tool comprising an arcuate bracket formed of rigid material, said bracket having a plurality of apertures spaced along a perimeter thereof, a plurality of fastening members positionable through said apertures, a plurality of elongated support pedestals having longitudinal channels extending axially therethrough, and means for compressing a valve spring rotatable about a fulcrum axis;

securing said bracket at a substantially stable and elevated position above a cylinder head by positioning each fastening member through one of said bracket apertures, aligning each support pedestal channel with one of said bracket apertures, positioning each fastening member through one of said channels of said support pedestal, and threadably engaging each fastening member with a threaded aperture provided on said cylinder head; and

9

using said means for compressing to compress a valve spring by exerting pressure upon a valve retainer to release associated valve keepers.

29. The method of claim 28 further comprising the step of removing valve springs and valve seals from the valve while said valve keepers are released.

30. The method of claim 28 wherein after said securing step, said fulcrum axis is in a position substantially parallel to said bracket.

31. The method of claim 28 wherein said means for compressing is used in cooperation with said support pedestals

10

and said bracket, and manually rotatable along a selected radial direction and about said fulcrum axis.

32. The tool of claim 7 wherein said fastening members are threadably positionable through said apertures in said bracket.

33. The tool of claim 13 wherein said fastening members are threadably positionable through said apertures in said bracket.

* * * * *