

US00RE43352E

(19) **United States**
(12) **Reissued Patent**
Cipriani

(10) **Patent Number:** **US RE43,352 E**
(45) **Date of Reissued Patent:** ***May 8, 2012**

(54) **MECHANISM FOR BRAKING THE UNWINDING OF A BUNDLE OF METALLIC WIRE HOUSED IN A DRUM**

(58) **Field of Classification Search** 242/156, 242/156.1, 156.2, 423.1, 566, 593, 125.3, 242/172, 419, 157 R
See application file for complete search history.

(75) **Inventor:** **Giancarlo Cipriani**, Bibbiena-Arezzo (IT)

(56) **References Cited**

(73) **Assignee:** **Lincoln Global, Inc.**, Cleveland, OH (US)

U.S. PATENT DOCUMENTS

(*) **Notice:** This patent is subject to a terminal disclaimer.

318,062 A 5/1885 Warren
532,565 A 1/1895 Kilmer
617,353 A 1/1899 Redmond
627,722 A 6/1899 Edwards
(Continued)

(21) **Appl. No.:** **11/776,331**

FOREIGN PATENT DOCUMENTS

(22) **Filed:** **Jul. 11, 2007**

CN 1626423 A 6/2005
(Continued)

(65) **Prior Publication Data**
US 2007/0295853 A1 Dec. 27, 2007

OTHER PUBLICATIONS

CA 2,205,755 Office Action dated Jan. 17, 2005.
(Continued)

Related U.S. Patent Documents

Reissue of:

(64) **Patent No.:** **5,845,862**
Issued: **Dec. 8, 1998**
Appl. No.: **08/854,691**
Filed: **May 12, 1997**

Primary Examiner — William A Rivera
(74) *Attorney, Agent, or Firm* — Hahn Loeser & Parks LLP;
Jason R. Strobel

U.S. Applications:

(63) Continuation of application No. 09/712,836, filed on Nov. 14, 2000, now Pat. No. Re. 40,351.

(57) **ABSTRACT**

A circular crown shaped pressure disk (1), furnished with, on its external rim, jutting stirrup shaped, flexible elements (2) whose size makes them press on the internal surface of the drum (7) within which the disk is housed. The internal rim of the disk is equipped with winglets (3) and with flexible tabs (5) directed nearly tangentially in respect to the tubular trunk (8), placed at the center of the drum (7). The flexible tabs are for stopping the rise of the bundle of coils so as to impede their knotting and to help guiding the wire, as it is pulled to the outside of the drum and unwound from the bundle.


(30) **Foreign Application Priority Data**

Jul. 24, 1996 (IT) AR96A0022

(51) **Int. Cl.**
B65H 59/02 (2006.01)

(52) **U.S. Cl.** 242/423.1; 242/128; 242/156.1

5 Claims, 1 Drawing Sheet



US RE43,352 E

Page 2

U.S. PATENT DOCUMENTS

932,808	A	8/1909	Pelton	
1,640,368	A	8/1927	Obetz	
1,907,051	A	5/1933	Emery	
2,059,462	A	11/1936	Jungmann	
2,407,746	A	9/1946	Johnson	
2,713,938	A	7/1955	Snyder	
2,724,538	A	11/1955	Schweich	
2,838,922	A	6/1958	Gift	
2,849,195	A	8/1958	Richardson	
2,864,565	A	12/1958	Whearley	
2,869,719	A	1/1959	Hubbard	
2,880,305	A	3/1959	Baird	
2,929,576	A	3/1960	Henning	
2,966,258	A	12/1960	Krafft	
2,974,850	A	3/1961	Mayer	
3,185,185	A	5/1965	Pfund	
3,244,347	A	4/1966	Jenk	
3,463,416	A	8/1969	Quenot	
3,478,435	A	11/1969	Cook	
3,491,876	A	1/1970	Zecchin	
3,512,635	A	5/1970	Lang	
3,565,129	A	2/1971	Field	
3,567,900	A	3/1971	Nelson	
3,576,966	A	5/1971	Sullivan	
3,595,277	A	7/1971	Lefever	
3,648,920	A	3/1972	Stump	
3,724,249	A	4/1973	Asbeck et al.	
3,729,092	A	4/1973	Marcell	
3,799,215	A	3/1974	Willems	
3,815,842	A	6/1974	Scrogin	
4,044,583	A	8/1977	Kinney, Jr.	
4,074,105	A	2/1978	Minehisa et al.	
4,102,483	A	7/1978	Ueyama et al.	
4,172,375	A	10/1979	Rushforth et al.	
4,188,526	A	2/1980	Asano	
4,222,535	A	9/1980	Hosbein	
4,254,322	A	3/1981	Asano	
4,293,103	A	10/1981	Tsukamoto	
4,464,919	A	8/1984	Labbe	
4,546,631	A	10/1985	Eisinger	
4,582,198	A	4/1986	Ditton	
4,585,487	A	4/1986	Destree et al.	
4,623,063	A	11/1986	Balkin	
4,869,367	A	9/1989	Kawasaki et al.	
4,891,493	A	1/1990	Sato et al.	
4,949,567	A	8/1990	Corbin	
5,078,269	A	1/1992	Dekko et al.	
5,109,983	A	5/1992	Malone et al.	
5,205,412	A	4/1993	Krieg	
5,227,314	A	7/1993	Brown et al.	
5,261,625	A	11/1993	Lanoue	
5,277,314	A	1/1994	Cooper et al.	
5,314,111	A	5/1994	Takaku et al.	
5,372,269	A	12/1994	Sutton et al.	
5,452,841	A	9/1995	Sibata et al.	
5,494,160	A	2/1996	Gelmetti	
5,553,810	A	9/1996	Bobeczko	
5,590,848	A	1/1997	Shore et al.	
5,692,700	A	12/1997	Bobeczko	
5,739,704	A	4/1998	Clark	
5,746,380	A	5/1998	Chung	
5,816,466	A	10/1998	Seufer	
5,819,934	A	10/1998	Cooper	
5,845,862	A *	12/1998	Cipriani 242/423.1	
5,865,051	A	2/1999	Otzen et al.	
5,971,308	A	10/1999	Boulton	
6,019,303	A	2/2000	Cooper	
6,301,944	B1	10/2001	Offer	
6,322,016	B1	11/2001	Jacobsson et al.	
6,340,522	B1	1/2002	Burke et al.	
6,464,077	B1	10/2002	Liu	
6,648,141	B2	11/2003	Land	
6,708,864	B2	3/2004	Ferguson, III et al.	
6,745,899	B1	6/2004	Barton	
6,821,454	B2	11/2004	Visca et al.	
7,152,735	B2	12/2006	Dragoo et al.	
7,178,755	B2 *	2/2007	Hsu et al. 242/423.1	
7,220,942	B2	5/2007	Barton et al.	

2002/0003014	A1	1/2002	Homma
2002/0014477	A1	2/2002	Lee et al.
2004/0020041	A1	2/2004	Ferguson, III et al.
2004/0155090	A1	8/2004	B.-Jensen

FOREIGN PATENT DOCUMENTS

DE	1011840	B	7/1957
DE	1082215		11/1957
DE	2122958		11/1972
DE	2202177		7/1973
EP	0519424	A1	12/1992
EP	0686439	A1	12/1995
EP	1057751	A1	12/2000
FR	1215111		4/1960
FR	2055181		5/1971
FR	2595674		3/1988
GB	880502		10/1961
GB	1168928		10/1969
GB	1229913		4/1971
GB	2059462		4/1981
JP	49-13065		2/1974
JP	54-043856		4/1979
JP	55-156694		12/1980
JP	56-023376		3/1981
JP	57-102471		6/1982
JP	58-035068		3/1983
JP	58-70384		5/1983
JP	59-197386		11/1984
JP	59-229287		12/1984
JP	59-232669		12/1984
JP	60-021181		2/1985
JP	60-032281		2/1985
JP	60-184422		9/1985
JP	60-223664		11/1985
JP	61-293674		12/1986
JP	62-009774		1/1987
JP	62-111872		5/1987
JP	62-287055		12/1987
JP	63-147781		6/1988
JP	1-240222		9/1989
JP	03264169	A	11/1991
JP	04-133973		5/1992
JP	4-274875		9/1992
JP	08-150492		6/1996
JP	08-267274		10/1996
JP	2000-225468		8/2000
JP	2000-263239		9/2000
JP	2001-150187		6/2001
JP	2004-025242		1/2004
JP	2004-025243		1/2004
SU	793678		1/1981
SU	1412830		7/1988
WO	8810230		12/1988
WO	94-00493		1/1994
WO	94-19258		9/1994
WO	00-50197		8/2000
WO	03-106096	A1	12/2003

OTHER PUBLICATIONS

ESAB Marathon Pac Endless Feedability, ESAB Market Communications/BA/November/2004, 27 pages.

Now there's no end to robot productivity. Uninterrupted Mag-Welding With Endless Marthon Pac Wire Delivery, Mar. 11, 2004, pp. 1-8.

Lincoln Electric Completes Italian Acquisition, News/Lincoln Electric, web page, Aug. 23, 2009.

U.S. Appl. No. 60/298,555, filed Jun. 15, 2001, for "S" Shaped Cast in Wire Applicant David J. Barton.

Premium Quality Twist-Free Robotic Welding Wire, Prostar, Nov. 1997.

Premium Quality Twist-Free Robotic Welding Wire, Prostar, Jul. 1999.

Premium Quality Twist-Free Robotic Welding Wire, Prostar, Apr. 2000.

Weld Point Robotic Welding Wire, Technology of the Future, LEITC000532-LEITC000539, Jan. 23, 2001.

* cited by examiner




FIG. 1




FIG. 2



FIG. 3




FIG. 4

**MECHANISM FOR BRAKING THE
UNWINDING OF A BUNDLE OF METALLIC
WIRE HOUSED IN A DRUM**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

This application is a Continuation Reissue Application of Reissue application Ser. No. 09/712,836 filed on Nov. 14, 2000, now Reissue Pat. No. Re. 40,351, reissued Jun. 3, 2008 of U.S. Pat. No. 5,845,862 issued on Dec. 8, 1998.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention concerns a mechanism for the braking of the unwinding of a bundle of metallic wire housed in a container drum and aimed particularly at feeding soldering machines, in particular those operating continuously, with automatic advancing of the wire that constitutes the weld metal.

2. Description of the Prior Art

Coils of metal wire are used, particularly in the field of continuous soldering machines, where said wire is unrolled and carried to the soldering point where it is melted to join the two parts to be soldered.

When the quantity of wire being used is large, instead of being wound in rolls of a few [kilogrammes] *kilograms* in weight, the metallic wire, is contained as a bundle of various quintals inside a drum with a positioning cylindrical core, so that it is capable of feeding the soldering machine for a long period of time, eliminating in this way its frequent stoppage due to lack of the same soldering wire.

This type of feeder drum is positioned, when operative, with its axis in vertical position and the wire of the bundle is pulled up by a dragging unit. Due to the extreme elasticity of the wire and of its tendency to straighten out, when it is pulled towards the outside, various turns tend to rise together and they can become tangled among each other so as to provoke the stoppage of its advancement. This inconvenience is being presently avoided by the use of a crown shaped weight, placed inside the drum and on the bundle of wire with the aim of avoiding the rising of various turns at the same time and therefore their tangling up.

However, there is a clearance between said crown and the inner surface of the drum's contour and between the crown and the surface of the inner tubular trunk which keeps the bundle in position, without said clearance, due to the fact that the drums are not strictly identical to one another, the crown shaped weight could adhere to said surfaces and not slide enough to maintain itself adherent to the bundle, as the wire is used, or could impede the unwinding of the wire because of the pressure placed on the contours of the drum where it adheres, and would end up by carrying out a blockage on the wire that should instead move forward.

If instead the crown shaped weight should have a relatively ample clearance compared to the internal surface of the drum and of the internal tubular trunk, the movement of the coils at the top of the bundle, determined by the unrolling movement, could bring said turns or parts of them above the pressure disk and interact with it to form a knot, therefore blocking the unwinding of the bundle and consequently of the soldering machine.

SUMMARY OF THE INVENTION

Taking the disadvantages and problems of the above technique into consideration, consequently one of the main aims of this invention is to find a device which can stop the turns of the bundle inside the feeding drum from lifting from the bundle itself. This to avoid the tangling up of the wire that would stop the wire feeding unit therefore also the soldering machine.

Another aim of this invention is to find a device that can act on drums that are not strictly identical and that can avoid that one or more coils should pass over the device itself and therefore get tangled on it causing the advancement of the wire from the bundle which is being unrolled, to stop.

A further aim is to [realise] *realize* a low cost relatively light device, capable of carrying out a non-excessive but regular braking action in time, while the bundle unwinds. This *is* to avoid stress on the unit that pulls the wire from the bundle to allow an even pull towards the welding point to allow a uniform soldering in time.

An invention that can reach said results is particularly advantageous because it allows the use of drums containing metal wire bundles of various sizes. It allows the correct unwinding of the bundles, without the tangling up of the wire, and a correct feed of the non stop welding machines so that these latter ones can carry out uniform and sized welds as foreseen while making the project. This means without waste due to anomalous feed of the welding wire.

The invention which allows us to obtain said results consists in a circular crown shaped device, equipped with jutting flexible stirrup shaped elements on the external rim. The size of these elements is such that they can adhere, eventually by inflecting, on to the inner surface of the drum within which it will be placed. On its inner rim the crown is also equipped with guiding winglets and flexible tabs oriented in an almost tangential direction in respect to the tubular trunk placed at the center of the drum, such as to reach it to block the lifting from the bundle of turns and therefore to avoid their tangling and consequently to help guide the wire as it is pulled and unwound from the bundle to the outside of the drum.

The stirrup shaped elements, placed on the outside of the circular crown shaped structure, are such as to avoid the wire from the bundle to pass over from the external edge of the invention and to position itself over it, thus avoiding their tangling up. The flexible structure of these stirrups is such as to allow the use of the invention also when the drum in which it is placed has a reduced diameter compared with the one foreseen.

The internal winglets and flexible tabs are instead adequate to help direct the wire toward the tubular trunk in the middle of the drum. Said wire is pulled from the outside and at the same time the winglets and flexible tabs avoid the coils at the top of the bundle—on which the invention is placed—to move excessively and to emerge from the same winglets and tabs.

In this way the bundle is forced to unwind in a correct way, and thanks to the light weight of the invention, which is normally made through a [moulding] *molding* process of plastic materials, without having to exercise a considerable pressure that would determine an excessive braking action on the wire pulled by the dragging group.

BRIEF DESCRIPTION OF THE DRAWINGS

More features of the invention and the advantages which it determines will clearly appear in the following description, which is referred to a preferred shape in its execution, how-

3

ever it is illustrated as a pure example which by no means is limiting, in the figures of the enclosed drawing, in which:

FIG. 1 is the layout view of the lower part of the invention;

FIG. 2 is the view along the AA section line of FIG. 1;

FIG. 3 is the partial view along the BB section line of FIG. 1;

FIG. 4 is the view on a different scale of a section of the drum with the invention inserted on it, sectioned with an axial plane.

However, it must be clear that the drawings and the corresponding described parts are given exclusively as the illustration of the object of the invention, without in any way constituting a limitation of it.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the drawings we have indicated with 1 the circular shaped crown structure, with 2 the stirrup shaped flexible elements, with 3 the shaped winglets, with 4 their external profile, with 5 the flexible tabs, with 6 the thin skeletons that connect the winglets 3 with the tabs 5, with 7 the drum, with 8 its central tubular trunk. In substance, the invention consists in a device capable of carrying out a braking and containing action in the unwinding of the metal wire wound into a bundle and placed inside a containing drum 7, having a tubular center 8. The wire being used to feed welding machines and in particular those operating non stop (welding robots).

Said device operates a braking action on the movement of the coils at the top of the bundle that is being unwound. It consists in an element which can carry out a slight pushing action on the coils and is formed by [a] circular crown 1 having [on its outer edge distributed stirrup] a thickness extending between a top surface and a bottom surface of the crown. The crown extends between an inner edge and an outer edge and, based on the thickness of the crown, the crown is non-flexible. Stirrup shaped flexible elements 2, with a dimension that allows] can be equally distributed about the outer edge of the crown and are thinner than the crown thickness to allow their adherence—bending inwards if necessary—to the internal surface of the drum 7 in which the invention is positioned. [In this way it can stop the] Further, the stirrups can be U-Shaped. By utilizing flexible stirrups 2, external parts of the coils can be prevented from rising along the internal surface of the drum 7 and [to go over] rising above the level of the pressure disk itself [and as a consequence of]. If the wire is allowed to spring up between the device and the wall of the container, the pulling action[,] of the wire could move the springing wire close to the tubular trunk 8 and create a knot on the disk 1 with the effect of stopping its normal flow.

On its inner edge [the] disk 1 is equipped with distributed guiding winglets 3 and flexible tabs 5. [The former having the] Flexible tabs 5 can be generally rectangular and extend at a non-perpendicular angle from the inner edge. The flexible tabs also have a front edge facing the wire during the unwinding and an opposite rear edge. The front edge is at an angle less than 90 degrees from the inner edge of disk 1 wherein the wire travels along the front edge during the unwinding of the wire from the coil. Winglets 3 have a side profile 4 [of the side] oriented towards the axis of [the] drum 7, connected to the thin skeleton 6 curved into a spiral towards the center of the same drum, so that the wire of the bundle, when pulled, is evenly sustained and guided towards the center of the drum 7 to emerge from it staying adherent to the tubular trunk 8 against which it is pushed by the sequence of flexible tabs 5 that follow it as it unwinds.

4

The invention therefore carries out two actions, the first one consisting in a braking action that also regulates the movement of the coils at the top of the bundle, in fact said movement would be turbulent and disorganized without it. The second action is that of conveying the wire that unwinds making it emerge from the drum 7 in an almost axial direction as well as a rotatory one to follow the coils that unwind from the bundle.

I claim:

[1. A device for braking the unwinding of bundled metal wire placed in a drum, for the feeding of welding machines having an automatic advancing movement of the wire, the device having a circular crown with jutting flexible elements on its outer edge for pressing on an inner surface of the drum, and further comprising guiding winglets and flexible tabs on an inner edge of the crown.]

[2. The device as claimed in claim 1, wherein said jutting flexible elements are stirrup-shaped.]

[3. The device as claimed in claim 1, wherein the winglets have a circular inner periphery, the inner periphery including a skeleton curved into a spiral towards a center of the crown.]

[4. The device as claimed in claim 1, wherein the flexible tabs are oriented in an almost tangential direction toward a circle interior to the inner edge of the crown and are for suppressing inadvertent release of the wire in the drum.]

5. A device for braking the unwinding of bundled metal wire placed in a container of welding wire, for the feeding of welding machines having an automatic advancing movement of the wire, the container having an internal surface, said device comprising a circular crown having an outer peripheral edge which is spaced from the internal surface of the container which allows said device to descend with the unwinding of the wire, said device further including inwardly extending flexible tabs on an inner edge of said crown having a front edge facing the wire exiting the bundle of wire during the unwinding of the wire, said flexible tabs on said inner edge being generally rectangular and extending at a non-perpendicular angle from said inner edge such that the wire traveling along said front edge during the unwinding is urged radially inwardly, said device further including guide winglets between each of said flexible tabs, said guide winglets each having an inner profile that is arcuate.

6. The device as described in claim 5, wherein said guide winglets further include a skeleton on said inner profile and extending inwardly and toward an adjacent one of said flexible tabs.

7. A device for braking the unwinding of bundled metal wire placed in a container, for the feeding of welding machines having an automatic advancing movement of the wire, the container having an internal surface, said device comprising a crown portion having an outer peripheral edge which is spaced from the internal surface of the container which allows said device to descend with the unwinding of the wire and an inner peripheral edge opposite of said outer edge, said crown having a thickness between said inner and outer edges, said device further includes inwardly extending flexible tabs on said inner edge of said crown having a front edge facing the wire during the unwinding, said flexible tabs having a thickness less than said crown thickness and extending from said inner edge at a non-perpendicular angle, said flexible tabs further including a front edge facing the wire being unwound from the bundled wire such that the wire travels along said front edge during the unwinding, said front edge being at an angle less than 90 degrees from said inner edge such that the wire is urged inwardly during the unwinding, said device further including U-shaped flexible elements on the outer edge of said crown, said U-shaped flexible ele-

5

ments engaging the internal surface of the container and being transverse to said outer edge.

8. A device for braking the unwinding of bundled metal wire placed in a container, for the feeding of welding machines having an automatic advancing movement of the wire, the container having an internal surface, said device comprising a circular crown having an outer peripheral edge which is spaced from the internal surface of the container which allows said device to descend with the unwinding of the wire and an inner peripheral edge opposite of said outer edge, said crown having a crown thickness between said inner and out edges, said device further including inwardly extending flexible tabs on said inner crown edge and said tabs each

6

having a front edge facing the wire exiting the bundle of wire during the unwinding of the wire, said each tab being generally rectangular and extending at a non-perpendicular angle from said inner edge and having a tab thickness less than said crown thickness, said device still further including guide winglets between each of said flexible tabs, said guide winglets each having an inner profile that is arcuate.

9. The device as described in claim 8, wherein said guide winglets further include a skeleton on said inner profile and extending inwardly and toward an adjacent one of said flexible tabs.

* * * * *