

US00RE43585E

(19) **United States**
(12) **Reissued Patent**
Garrett et al.

(10) **Patent Number:** **US RE43,585 E**
(45) **Date of Reissued Patent:** ***Aug. 14, 2012**

(54) **DATA TRANSFER RATE DISPLAY SELECTION**

(56) **References Cited**

(75) Inventors: **Tara A. Garrett**, San Marcos, CA (US);
Erin Harnden, San Diego, CA (US)

(73) Assignee: **Calton Research L.L.C.**, Wilmington, DE (US)

(*) Notice: This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/188,052**

(22) Filed: **Jul. 21, 2011**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,565,176**
Issued: **Jul. 21, 2009**
Appl. No.: **11/652,175**
Filed: **Jan. 10, 2007**

U.S. Applications:

(62) Division of application No. 10/036,304, filed on Dec. 28, 2001, now Pat. No. 7,184,797.

(51) **Int. Cl.**
H04B 1/38 (2006.01)
H04M 1/00 (2006.01)

(52) **U.S. Cl.** **455/566**; 455/569.1; 455/557;
455/556.1; 455/414.4; 455/414.1; 455/419;
345/537; 348/391.1; 348/396.1; 342/357.1;
342/357.06; 342/357.31

(58) **Field of Classification Search** 455/566,
455/569.1, 557, 556.1, 414.1, 414.4, 419
See application file for complete search history.

U.S. PATENT DOCUMENTS

4,500,751 A	2/1985	Darland et al.
5,027,212 A	6/1991	Marlton et al.
5,553,220 A	9/1996	Keene
5,594,467 A	1/1997	Marlton et al.
5,732,212 A	3/1998	Perholtz et al.
5,859,879 A	1/1999	Bolgiano et al.
5,903,261 A	5/1999	Walsh et al.
5,930,341 A	7/1999	Cardillo et al.
6,055,563 A	4/2000	Endo et al.
6,144,848 A	11/2000	Walsh et al.
6,161,932 A	12/2000	Goto et al.
6,175,569 B1	1/2001	Ellington et al.
6,201,552 B1	3/2001	Itou et al.
6,243,581 B1	6/2001	Jawanda
6,249,689 B1	6/2001	Aizawa
6,366,951 B1	4/2002	Schmidt
6,389,039 B1	5/2002	Katinakis et al.
6,405,049 B2	6/2002	Herrod et al.
6,445,932 B1	9/2002	Soini et al.
6,590,529 B2	7/2003	Schwoegler

(Continued)

OTHER PUBLICATIONS

Stolowitz Ford Cowger LLP; Related Case Listing; Feb. 2, 2012; 1 Page.


Primary Examiner — Marceau Milord

(74) *Attorney, Agent, or Firm* — Stolowitz Ford Cowger LLP

(57) **ABSTRACT**

A device for displaying data transfer rates on a display. The device includes a system for displaying the transfer rates in an alphanumeric mode or an alternative graphics mode; and a system for switching between displaying the transfer rates in the alphanumeric mode and the graphics mode.

26 Claims, 6 Drawing Sheets




US RE43,585 E

Page 2

U.S. PATENT DOCUMENTS			
6,633,905	B1	10/2003	Anderson et al.
6,643,371	B2	11/2003	Mager
6,714,794	B1 *	3/2004	O'Carroll 455/466
6,714,797	B1	3/2004	Rautila
6,745,025	B1	6/2004	Chow et al.
6,874,029	B2	3/2005	Hutcheson et al.
6,976,075	B2 *	12/2005	Ma 709/228
6,999,791	B1	2/2006	Ishikura et al.
7,003,302	B2 *	2/2006	Yoshida et al. 455/450
7,184,797	B2 *	2/2007	Burnhouse et al. 455/566
7,349,956	B2	3/2008	Anderson et al.
7,383,038	B2	6/2008	Koenck et al.
7,565,176	B2 *	7/2009	Garrett et al. 455/566

* cited by examiner

FIG. 1






FIG. 3A





FIG. 3B






FIG. 5




FIG. 6A




FIG. 6B





FIG. 6C



DATA TRANSFER RATE DISPLAY SELECTION

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

CROSS REFERENCE TO RELATED APPLICATION

This is a *reissue of U.S. patent application Ser. No. 11/652,175, filed on Jan. 10, 2007, now issued as U.S. Pat. No. 7,565,176, which is a divisional patent application of U.S. patent application Ser. No. 10/036,304 filed Dec. 28, 2001, now U.S. Pat. No. 7,184,797.*

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to communication devices capable of data and/or fax communication and, more particularly, to a system for displaying data transfer rates on a display.

2. Brief Description of Prior Developments

Traditional modems tend to indicate data transmission rates with blinking lights. Mobile communication devices, such as mobile phones, are now capable of acting as modems. Because these mobile communication devices include a more intrinsic display than those available on a traditional modem, there is an ability to portray more useful connection rate information to the user. In the past, Nokia Corp. has manufactured and sold mobile phones which indicate data transmission rates using graphical indicators.

There may be a desire by a first type of user to provide this communication rate information in an alphanumeric form. However, a second type of user might be overwhelmed by the technical nature of the information if communicated in an alphanumeric form. For such second type of user, a graphical display format, such as in the Nokia Corp. mobile phones, might be preferred. For a third type of user, there might be a desire to not display the data transfer rate at all. There is a desire to provide a system which can accommodate at least two and perhaps all three types of these users.

SUMMARY OF THE INVENTION

In accordance with one aspect of the present invention, a device for displaying data transfer rates on a display is provided. The device includes a system for displaying the transfer rates in an alphanumeric mode or an alternative graphics mode; and a system for switching between displaying the transfer rates in the alphanumeric mode and the graphics mode.

In accordance with another aspect of the present invention, a mobile radio communication device is provided having a display and a transceiver for transmitting and receiving data. The improvement comprises means for displaying a data transfer rate of data with the transceiver on the display in an alphanumeric format.

In accordance with another aspect of the present invention, a mobile radio communication device is provided comprising a transceiver, a controller coupled to the transceiver, and a display. The display is coupled to the controller. The controller is adapted to display on the display an indication of a data transfer rate of data by the transceiver. The communication

device further comprises a system for inactivating display of the data transfer rate on the display while the transceiver is transmitting or receiving the data.

In accordance with one method of the present invention, a method of displaying a data transfer rate on a display is provided comprising steps of selecting, by a user, a data transfer rate display mode from a plurality of data transfer rate display modes; and displaying the data transfer rate on the display based upon the selected data transfer rate display mode.

In accordance with another method of the present invention, a method of changing displaying of a data transfer rate on a display of a portable communication device is provided comprising steps of selecting, by a user, to turn a displaying feature of the data transfer rate ON or OFF; and during data transfer by the portable communication device, a controller of the portable communication device, connected to the display, preventing the display from displaying the data transfer rate when the user has selected to turn the displaying feature OFF.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing aspects and other features of the present invention are explained in the following description, taken in connection with the accompanying drawings, wherein:

FIG. 1 is a diagram of a wireless communications system having a portable communication device incorporating features of the present invention shown operably coupled to a base station;

FIG. 2 is a block diagram of the wireless communications system shown in FIG. 1;

FIG. 3A is a diagram of a first type of information which can be displayed on the display of the portable communication device shown in FIG. 1;

FIG. 3B is a diagram of a second type of information which can be displayed on the display;

FIG. 4 is a diagram of menus which can be displayed on the display of the portable communication device shown in FIG. 1 for selecting a data transfer rate display mode;

FIG. 5 is a diagram of menus which can be displayed on the display of the portable communication device shown in FIG. 1 during data transfer; and

FIGS. 6A-6C are diagrams of alternate forms of display screens which can be displayed on the display of the portable communication device shown in FIG. 1.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIG. 1, there is shown a diagram of a portion of a wireless telecommunications system 5 having a mobile station or portable communication device 10 incorporating features of the present invention shown operably coupled by a wireless link to a base transceiver station (BTS) 9 of an exemplary network operator. Although the present invention will be described with reference to the embodiments shown in the drawings, it should be understood that the present invention can be embodied in many alternate forms of embodiments. In addition, any suitable size, shape or type of elements or materials could be used.

Referring also to FIG. 2, the network operator 6 generally comprises a mobile switching center (MSC) 7 for connecting to a telecommunications network, such as a public switched telephone network or PSTN, at least one base station controller (BSC) 8, and a plurality of base transceiver stations (BTS) 9 that transmit in a forward or downlink direction both physical and logical channels to the mobile station 10 in accor-

dance with a predetermined air interface standard. A reverse or uplink communication path exists from the mobile station **10** to the network operator **6**, and conveys mobile station originated access requests and traffic, such as voice and possible packet data traffic.

The air interface standard may conform to, for example, a Time Division Multiple Access (TDMA) air interface, or a Code Division Multiple Access (CDMA) air interface, or a Frequency Division Multiple Access (FDMA) air interface. In alternate embodiments, features of the present invention could be used with any suitable type of air interface standard. In an alternate embodiment, features of the present invention could be used with a wired communications system, such as a land line telephone system.

The network operator **6** can include a Message Service Center (MSCT) **6A** that receives and forwards messages from the mobile station **10**, such as Short Message Service (SMS) messages, or any wireless messaging technique including Email and supplementary data services. In an alternate embodiment, features of the present invention could be used with any suitable type of network operator system.

The mobile station **10** typically includes a micro control unit (MCU) **12** having an output coupled to an input of a display **14** and an input coupled to an output of a keyboard or keypad **16**. The mobile station **10** may be considered to be a hand-held radio telephone, such as a cellular telephone or a personal communicator, and may have a microphone and a speaker for conducting voice communications. The mobile station **10** could also be contained within a card or module that is connected during use to another device. For example, the mobile station **10** could be contained within a PCMCIA or similar type of card or module that is installed during use with a portable data processor, such as a laptop or notebook computer, or even a computer that is wearable by the user.

The MCU **12** is assumed to include or be coupled to some type of memory **13**, including a read only memory (ROM) for storing an operating program, as well as a random access memory (RAM) for temporarily storing received data, scratchpad data memory, received data packets and data packets prepared for transmission, etc. A separate removable SIM (not shown) can be provided as well. The SIM could store, for example, a preferred public land mobile network (PLMN) list and other subscriber related information.

The mobile station **10** also contains a wireless section that includes a digital signal processor (DSP) **18**, or equivalent high-speed processor, as well as a wireless radio frequency (RF) transceiver comprising a transmitter **20** and a receiver **22**. The transceiver is coupled to an antenna **24** for communication with the network operator **6**. In an alternate embodiment, features of the present invention could be used with any suitable type of wireless communications device or mobile phone. As seen in FIG. 1, the keypad **16** includes an alphanumeric key section **16a** and a control key section **16b**. The control key section **16b** includes two soft keys **24**, **25** and an up/down scroll key **26**. However, in alternate embodiments, the control key section could be comprised of any suitable number or type of keys or cursor control device. The two soft keys **24**, **25** are located beneath two control indicator sections **27**, **28** of the display **14**. When one of the soft keys **24**, **25** are depressed, the controller **12** can perform the function listed in the control indicator section **27**, **28** located above the depressed soft key.

Referring now also to FIG. 3A, a diagram of a display screen using a first mode of displaying information on the display **14** of the portable communication device **10** is shown. The display screen includes a graphical signal strength indicator **30**, a graphical battery strength indicator **32**, the two

control indicator sections **27**, **28** having control/menu features listed therein, and a data transfer rate indication **34**. The data transfer rate indication **34** is displayed on the display **14** during data transfer between the phone **10** and the base station **9**. The data transfer rate indication **34** is displayed on the display **14** to indicate to the user transmitting and/or receiving rates between the phone **10** and the base station **9**.

In the embodiment shown, the data transfer rate indication **34** comprises two sections; a transmitting data transfer rate section **36** and a receiving data transfer rate section **38**. However, in alternate embodiment, the data transfer rate indication **34** could comprise only a transmitting data transfer rate indication or only a receiving data transfer rate indication. In such an alternate embodiment, the data transfer rate indication **34** displayed on the display **14** could automatically switch between the transmitting and the receiving indications based upon the status of the phone **10** receiving or transmitting data.

In the embodiment shown in FIG. 3A, the transmitting data transfer rate section **36** generally comprises a text descriptor **40** associated with a graphical indicator **42**. The text descriptor **40**, in the embodiment shown, merely comprises the term "Transmitting:". However, in alternate embodiments, the text descriptor **40** could comprise any suitable type of descriptive text, or could comprise a graphical descriptor, or could comprise a combination of text and graphics. For example, in an alternate embodiment the text descriptor **40** could comprise the term "Sending:".

The graphical indicator **42**, in the embodiment shown, comprises a plurality of sideward facing arrows or triangles **44**. The arrows **44** comprise a darkened center or a non-darkened center. The totality of the arrows **44** (six in the embodiment shown) graphically indicate a maximum transmission rate between the phone **10** and the base station **9**. The number of arrows having a darkened center indicate a percentage of the maximum transmission rate actually being used to transmit data from the phone **10** to the base station **9**. In the illustration shown in FIG. 3A, three of the six arrows **44** have a darkened center. Thus, in the example illustrated, the phone **10** is transmitting at a data transfer rate of about fifty percent of its maximum transmission rate. The number of arrows having a darkened center and a non-darkened center will increase and decrease as the actual data transfer rate of transmitting data from the phone **10** to the base station **9** increases and decreases.

The receiving data transfer rate section **38** generally comprises a text descriptor **46** associated with a graphical indicator **48**. The text descriptor **46**, in the embodiment shown, merely comprises the term "Receiving:". However, in alternate embodiments, the text descriptor **46** could comprise any suitable type of descriptive text, or could comprise a graphical descriptor, or could comprise a combination of text and graphics.

The graphical indicator **48**, in the embodiment shown, comprises a plurality of sideward facing arrows or triangles **50**. The arrows **50** point in an opposite direction relative to the arrows **44**. The arrows **50** comprise a darkened center or a non-darkened center. The totality of the arrows **50** (six in the embodiment shown) graphically indicate a maximum receiving rate between the phone **10** and the base station **9**. The number of arrows having a darkened center indicate a percentage of the maximum receiving rate actually being used to transmit data to the phone **10** from the base station **9**. In the illustration shown in FIG. 3A, three of the six arrows **50** have a darkened center. Thus, in the example illustrated, the phone **10** is receiving at a data transfer rate of about fifty percent of its maximum receiving rate. The number of arrows **50** having a darkened center and a non-darkened center will increase and

5

decrease as the actual data transfer rate of receiving data by the phone 10 from the base station 9 increases and decreases.

The embodiment shown in FIG. 3A is intended to illustrate a graphics mode of displaying data transfer rates on the display 14. In alternate embodiments, any suitable type of graphics could be used in the graphical indicators 42, 48. In addition, any suitable graphics could be used to illustrate a change between data transfer maximum rate and actual rate. In addition to the graphics mode of display data transfer rates on the display 14, the phone 10 is also adapted to use an alphanumeric mode of displaying data transfer rates on the display 14.

Referring also to FIG. 3B, a diagram of a display screen comprising a second mode of displaying information on the display 14 of the portable communication device 10 is shown. The display screen includes the graphical signal strength indicator 30, the graphical battery strength indicator 32, the two control indicator sections 27, 28 having control/menu features listed therein, and the data transfer rate indication 52. The data transfer rate indication 52 is displayed on the display 14 during data transfer between the phone 10 and the base station 9. The data transfer rate indication 52 is displayed on the display 14 to indicate to the user transmitting and/or receiving rates between the phone 10 and the base station 9.

In the embodiment shown, the data transfer rate indication 52 comprises two sections; a transmitting data transfer rate section 54 and a receiving data transfer rate section 56. However, in alternate embodiment, the data transfer rate indication 52 could comprise only a transmitting data transfer rate indication or only a receiving data transfer rate indication. In such an alternate embodiment, the data transfer rate indication 52 displayed on the display 14 could automatically switch between the transmitting and the receiving indications based upon the status of the phone 10 receiving or transmitting data.

In the embodiment shown in FIG. 3B, the transmitting data transfer rate section 54 generally comprises a text descriptor 58 associated with an alphanumeric indicator 60. The text descriptor 58, in the embodiment shown, merely comprises the term "Transmitting:". However, in alternate embodiments, the text descriptor 58 could comprise any suitable type of descriptive text, or could comprise a graphical descriptor, or could comprise a combination of text and graphics.

The alphanumeric indicator 60 generally comprises a number followed by a rate descriptor. In the embodiment shown, the rate descriptor comprises the term "kbps" to indicate kilobits per second. Thus, in the illustration shown, the phone 10 is transmitting at 145 kilobits per second. The number in the alphanumeric indicator 60 will change to indicate the actual or approximate data transfer rate of data being transmitted from the phone 10 to the base station 9.

In the embodiment shown in FIG. 3B, the receiving data transfer rate section 56 generally comprises a text descriptor 62 associated with alphanumeric indicator 64. The text descriptor 62, in the embodiment shown, merely comprises the term "Receiving:". However, in alternate embodiments, the text descriptor 62 could comprise any suitable type of descriptive text, or could comprise a graphical descriptor, or could comprise a combination of text and graphics.

The alphanumeric indicator 64 generally comprises a number followed by a rate descriptor. In the embodiment shown, the rate descriptor comprises the term "kbps" to indicate kilobits per second. Thus, in the illustration shown, the phone 10 is receiving at 28 kilobits per second. The number in the alphanumeric indicator 64 will change to indicate the actual or approximate data transfer rate of data being received by the phone 10 from the base station 9.

The phone 10 could be adapted to display the data transfer rates in either only the alphanumeric mode (FIG. 3B) or only

6

the graphics mode (FIG. 3A). However, in a preferred embodiment, the phone 10 is adapted to display the data transfer rates both in the alphanumeric mode or alternatively in the graphics mode. In a preferred embodiment, the phone 10 is adapted to allow the user to select the mode of display. However, in an alternate embodiment, the mode of display could be selected by a manufacturer and intended not to be changed by a user. This could allow a manufacturer to configure a same phone for different regions having different user preferences in those regions.

Referring now also to FIG. 4, a series of menus or screens displayed on the display 14 for changing the data transfer rate display mode is shown. As shown in FIG. 1, the soft key 25 would initially be depressed to activate the menu function listed in the control indicator section 28 of the display 14. When entered into the menu function the user could depress the up/down scroll key 26 to scroll to the setting screen 70 shown in FIG. 4. The user could then depress the soft key 25 to select the settings menu. The user could then depress the up/down scroll key 26 to scroll to the call settings screen 72. The user could then depress the soft key 25 to select the call settings menu. The user could then depress the up/down scroll key 26 to scroll to the data/fax calls screen 74. The user could then depress the soft key 25 to select the data/fax calls menu. The user could then to depress the up/down scroll key 26 to scroll to the data rate indicators screen 76. The data rate indicators screen 76 preferably as an indicator section 78 which indicates the present data rate illustration mode. The user could then depress the soft key 25 to show the data rate indicators screen 80. The user could then use the up/down scroll key 26 to move the highlighter 82 to a desired one of the data rate illustration modes on the menu. By pressing the soft key 25 the user would select the mode highlighted by the highlighter 82.

The method and screens illustrated in FIG. 4 is only one type of method that could be employed to change the data transfer rate illustration mode. In an alternate embodiment, any suitable type of menus or screens for the user to select or changed the data transfer rate illustration mode could be provided.

In the embodiment shown in FIG. 4, the data rate indicators screen 80 includes a third data transfer rate illustration mode; an OFF or NONE mode. This type of mode prevents the data transfer rate from being displayed. The user can select the OFF mode. If the OFF mode is selected, then the data transfer rate indications 34 and/or 52 will not be displayed on the display 14 during data transfer. Thus, the user can select to turn the displaying feature of the data transfer rate ON or OFF.

The method and screens illustrated in FIG. 4 are generally intended to be used while the phone 10 is not in active communication with the base station 9. Referring now also to FIG. 5, a series of menus displayed on the display 14 for changing the data transfer rate display mode while the phone 10 is in active communication with the base station 9 is shown. When the phone 10 is in active communication with the base station 9, the control indicator section 28 of the display 14 does not list the menu function, but instead lists an "options" function. If the user depresses the soft the 25 the Options screen 84 will appear on the display 14. With the Options screen 84 displayed on the display 14, the user can depress the up/down scroll key 26 to move the highlighter 82 onto the data rate indicators selection. The user can then depress the soft key 25 to show the data rate indicators screen 80. The user can then depress the up/down scroll key 26 to move the highlighter 82 to the desired display mode. The user can then depress the soft key 25 to select the highlighted display mode and thereby return to the main screen with the selected data transfer rate

display mode now being used to display the data transfer rate information on the display 14.

The method and screens illustrated in FIG. 5 is only one type of method that could be employed to change the data transfer rate illustration mode while the phone 10 is in active communication with the base station 9. In an alternate embodiment, any suitable type of menus or screens for the user to select or changed the data transfer rate illustration mode while the phone 10 is in active communication with the base station 9 could be provided. For example, in one type of alternate embodiment, during active communication with the base station the display 14 could comprise the "Menu" descriptor for the control indicator section 27 as shown in FIG. 1 and, the menus and screens illustrated in FIG. 4 could be used. Thus, in this alternate embodiment, the method illustrated in FIG. 5 might not be used and the method illustrated in FIG. 4 might be used for both situations; the first situation of when the phone is in active communication with the base station and, the second situation of when the phone is not in active communication with the base station. In alternate embodiments, the phone 10 could be adapted to allow the change in the data transfer rate illustration mode to be made only while the phone is in active communication with the base station, or only while the phone is not in active communication with the base station.

Referring now also to FIGS. 6A, 6B and 6C, an alternate embodiment of the graphical display mode is shown. In this alternate embodiment, the graphical indicator 90 comprises a plurality of slanted blocks 92. The blocks 92 comprise a darkened center or a non-darkened center. The totality of the blocks (six in the embodiment shown) graphically indicate a maximum transmission rate between the phone 10 and the base station 9. The number of blocks having a darkened center indicate a percentage of the maximum transmission rate actually being used to transmit data from the phone 10 to the base station 9. In the illustration shown in FIG. 6A, three of the six blocks 92 have a darkened center. Thus, in the example illustrated, the phone 10 is transmitting at a data transfer rate of about fifty percent of its maximum transmission rate. The number of blocks having a darkened center and a non-darkened center will increase and decrease as the actual data transfer rate of transmitting data from the phone 10 to the base station 9 increases and decreases.

The graphical indicator 94 comprises a plurality of slanted blocks 96. However, the slanted blocks 96 are slanted in an opposite direction relative to the slanted blocks 92. The blocks 96 comprise a darkened center or a non-darkened center. The darkened and non-darkened centers of the blocks 96 function the same way as the blocks 92 to indicate the actual reception rate versus maximum reception rate of data with the phone. Use of slanted blocks 92, 96 can allow for a greater plurality of indicators in each line. Although only six blocks are shown in each line, if the width of each line is diminished, more than six blocks can be provided.

FIG. 6A generally illustrates data being transmitted and received by the phone 10 at the same time. FIG. 6B generally illustrates transmitting of data by the phone 10 without data being received by the phone at the same time. FIGS. 6C generally illustrates receiving of data by the phone without data being transmitted by the phone at the same time. In the embodiment shown, the blocks 92 darken from left to right and the blocks 96 darken from right to left. However, they could darken in the same direction.

The present invention provides a mechanism whereby the user may select the type of data transmission rate display most appropriate for them. This mechanism also allows the user to shut OFF all data transmission rate displays, in view the

standard in-call user interface using active data (or fax) calls. In the alphanumeric display mode, numerical data rates can indicate to the users their current data rate in exact numbers. However, for some less technical users, this information may be overwhelming. Graphical data indicators, on the other hand, are less intimidating for the user, but do not give exact information about the current data rate. Instead, they only provide information about where the current rate falls in relation to the peak rate. The present invention allows the user to choose the display mode based upon their own level of technical information desired. This provides an advantage of greater flexibility and personalization of the telephone's operation for the specific user.

It should be understood that the foregoing description is only illustrative of the invention. Various alternatives and modifications can be devised by those skilled in the art without departing from the invention. Accordingly, the present invention is intended to embrace all such alternatives, modifications and variances which fall within the scope of the appended claims.

What is claimed is:

1. A portable electronic device adapted to communicate by a wireless connection, the device comprising:

a display; and

a user interface adapted to allow a user to select a data transfer rate display mode, between an alphanumeric mode or an alternative graphics mode, for displaying a data transfer rate on the display.

2. A portable electronic device as in claim 1 wherein the user interface comprises a soft key.

3. A portable electronic device as in claim 1 wherein the user interface comprises a scroll key.

4. A portable electronic device as in claim 1 wherein the user interface comprises a menu screen displayed on the display to allow a user to select between the alphanumeric mode and the alternative graphics mode.

5. A portable electronic device as in claim 1 wherein the user interface comprises a menu screen displayed on the display to allow a user to select an OFF setting for not displaying the data transfer rate on the display.

6. A portable electronic device as in claim 1 wherein the device comprises a hand-held mobile telephone.

7. A portable electronic device as in claim 1 wherein the device comprises a receiver and the data transfer rate is the rate of information received by the receiver.

8. A portable electronic device as in claim 1 wherein the device comprises a transmitter and the data transfer rate is the rate of information transmitted by the transmitter.

9. A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine for performing operations to display a data transfer rate on a display, the operations comprising:

determining a data transfer rate display mode comprising determining a data transfer rate display mode selected by a user from a plurality of data transfer rate display modes; and

displaying the data transfer rate on the display based upon the determined data transfer rate display mode.

10. A portable electronic device comprising:

a display;

a communications section comprising a receiver and/or a transmitter; and

a controller coupled to the display and the communications section, wherein the controller comprises a system for displaying a data transfer rate of the communications section on the display comprising:

9

a system for displaying the transfer rate in an alphanumeric mode or an alternative graphics mode; and
 a system for switching between displaying the transfer rate in the alphanumeric mode and the graphics mode.

11. A portable electronic device as in claim 10 wherein the device comprises a mobile telephone.

12. A portable electronic device as in claim 10 wherein the device comprises a hand-held, mobile electronic device.

13. A device comprising:

a display; and

a control unit configured to selectively display data transfer information in a first mode and a second mode, wherein in the first mode, the data transfer information is indicated by alphanumeric characters, and wherein in the second mode, the data transfer information is indicated by darkening at least one graphic image.

14. The device of claim 13 wherein an amount of the darkening indicates a percentage of the data transfer.

15. The device of claim 13 wherein the selection of the first mode and the second mode is preset.

16. The device of claim 13 wherein the data transfer information is a data transfer rate.

17. The device of claim 13 wherein the device is a cellular telephone.

10

18. The device of claim 13 wherein data being transferred includes a short message service (SMS).

19. The device of claim 18 wherein the transfer of the SMS is indicated by the second mode.

20. A method comprising:

selectively displaying, by a portable electronic device, data transfer information in a first mode and a second mode, wherein in the first mode, the data transfer information is indicated by alphanumeric characters, and wherein in the second mode, the data transfer information is indicated by darkening at least one graphic image.

21. The method of claim 20 wherein an amount of the darkening indicates a percentage of the data transfer.

22. The method of claim 20 wherein the selection of the first mode and the second mode is preset.

23. The method of claim 20 wherein the data transfer information is a data transfer rate.

24. The method of claim 20 wherein the device is a cellular telephone.

25. The method of claim 20 wherein data being transferred includes a short message service (SMS).

26. The method of claim 25 wherein the transfer of the SMS is indicated by the second mode.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : RE43,585 E
APPLICATION NO. : 13/188052
DATED : August 14, 2012
INVENTOR(S) : Garrett et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specifications:

In Column 2, Line 65, delete “(BTS)” and insert -- (BTSS) --, therefor.

In Column 3, Lines 52-62, delete “As seen.....soft key.” and insert the same in Line 53 as a new Paragraph.

Signed and Sealed this
First Day of January, 2013



David J. Kappos
Director of the United States Patent and Trademark Office