

US00RE43683E

(19) **United States**
(12) **Reissued Patent**
King et al.

(10) **Patent Number:** **US RE43,683 E**
(45) **Date of Reissued Patent:** **Sep. 25, 2012**

(54) **WIRELESS COMMUNICATION DEVICE AND METHOD FOR DISCS**

(75) Inventors: **Patrick F. King**, Simpsonville, SC (US);
Ian J. Forster, Essex (GB)

(73) Assignee: **Mineral Lassen LLC**, Las Vegas, NV (US)

(21) Appl. No.: **11/584,478**

(22) Filed: **Oct. 19, 2006**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,806,842**
Issued: **Oct. 19, 2004**
Appl. No.: **10/131,576**
Filed: **Apr. 24, 2002**

U.S. Applications:

(63) Continuation-in-part of application No. 09/678,271, filed on Oct. 3, 2000, now Pat. No. 6,501,435, which is a continuation-in-part of application No. 09/618,505, filed on Jul. 18, 2000, now Pat. No. 6,483,473.

(51) **Int. Cl.**
H01Q 9/28 (2006.01)
H01Q 1/38 (2006.01)
H01Q 13/12 (2006.01)
G08B 13/14 (2006.01)

(52) **U.S. Cl.** **343/795**; 343/700 MS; 343/769; 340/572.8

(58) **Field of Classification Search** 343/700 MS, 343/767, 769, 795, 793; 340/572.8, 568.1
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,507,528 A 5/1950 Kandoian
3,972,049 A 7/1976 Kaloi

4,054,886 A 10/1977 Bergander et al.
4,117,489 A 9/1978 Kaloi
4,278,186 A 7/1981 Williamson
4,410,890 A 10/1983 Davis
4,530,483 A 7/1985 Nordstrom
4,545,761 A 10/1985 Cartwright

(Continued)

FOREIGN PATENT DOCUMENTS

DE 3247 425 A1 12/1982

(Continued)

OTHER PUBLICATIONS

European Examination Report dated Jan. 3, 2008, issued in European Application No. 06011798.3, 4 pages.

(Continued)

Primary Examiner — Jacob Y Choi


Assistant Examiner — Hasan Islam

(74) *Attorney, Agent, or Firm* — Christensen O'Connor Johnson Kindness PLLC

(57) **ABSTRACT**

A compact disc coupled to a wireless communication device comprises the disc with a metalized outer portion, a wireless communication chip and a pair of tabs. The first tab may capacitively couple the wireless communication chip to the metalized portion of the disc. The second tab may be positioned in an inner portion of the disc with a gap delimited by the metalized portion and the second tab. A slot antenna is thus formed through which the wireless communication device may communicate. Wireless communication chip allows disc to be interrogated and identified for a variety of purposes, including, but not limited to security, advertising and promotion, and issuing of related coupons to customers for subsequent purchases.

66 Claims, 22 Drawing Sheets



US RE43,683 E

Page 2

U.S. PATENT DOCUMENTS

4,575,725	A	3/1986	Tresselt	
4,662,503	A	5/1987	Lycke	
4,670,757	A	6/1987	Munich	
4,673,923	A	6/1987	Boscoe	
4,678,425	A	7/1987	Gibbemeyer	
4,694,283	A	9/1987	Reeb	
4,850,020	A	7/1989	Kahn	
4,873,532	A	10/1989	Sakurai	
4,916,457	A	4/1990	Foy	
4,947,181	A	8/1990	Duncan	
4,967,184	A	10/1990	Regelsberger	
4,975,711	A	12/1990	Lee	
4,987,421	A	1/1991	Sunahara	
5,006,857	A	4/1991	DeHart	
5,073,971	A	12/1991	Schaeffer	
5,081,446	A	1/1992	Gill	
5,119,353	A	6/1992	Asakura	
5,123,541	A	6/1992	Giannini	
5,155,493	A	10/1992	Thursby	
5,187,489	A	2/1993	Whelan	
5,216,430	A	6/1993	Rahm	
5,216,435	A	6/1993	Hirata	
5,298,894	A	3/1994	Cerny	
5,315,303	A	5/1994	Tsou	
5,347,280	A	9/1994	Schuermann	
5,350,074	A	9/1994	Rosenband	
5,376,943	A	12/1994	Blunden	
5,381,137	A	1/1995	Ghaem	
5,382,952	A	1/1995	Miller	
5,406,263	A	4/1995	Tuttle	
5,430,441	A	7/1995	Bickley	
5,461,393	A	10/1995	Gordon	
5,508,706	A	4/1996	Tsou	
5,512,901	A	4/1996	Chen	
5,528,222	A	6/1996	Moskowitz	
5,539,414	A	7/1996	Keen	
5,541,399	A	7/1996	de Vall	
5,566,441	A	10/1996	Marsh	
5,574,470	A	11/1996	de Vall	
5,577,268	A	11/1996	Ho	
5,584,113	A	12/1996	Hovorka	
5,585,953	A	12/1996	Zavrel	
5,593,040	A	1/1997	Shelton	
5,598,169	A	1/1997	Drabeck	
5,600,333	A	2/1997	Justice	
5,603,430	A	2/1997	Loehrke	
5,635,917	A	6/1997	Todman	
5,652,838	A	7/1997	Lovett	
5,790,029	A	8/1998	Curnutte	
5,814,797	A	9/1998	Rifkin	
5,821,859	A	10/1998	Schrott	
5,826,175	A	10/1998	Schmidt	
5,842,555	A	12/1998	Gannon	
5,862,117	A *	1/1999	Fuentes et al.	369/100
5,892,486	A	4/1999	Cook	
5,892,487	A	4/1999	Fujimoto	
5,897,741	A	4/1999	Mills	
5,910,770	A	6/1999	Ohara	
5,922,550	A	7/1999	Everhart	
5,929,760	A	7/1999	Monahan	
5,929,820	A	7/1999	Caulfield	
5,936,528	A	8/1999	Kobayashi	
5,939,984	A	8/1999	Brady	
5,945,201	A	8/1999	Holat	
5,955,048	A	9/1999	Cedro, III	
5,972,152	A	10/1999	Lake	
5,973,600	A	10/1999	Mosher, Jr.	
5,973,648	A	10/1999	Lindenmeier	
6,008,727	A	12/1999	Want	
6,018,299	A	1/2000	Eberhardt	
6,018,324	A	1/2000	Kitchener	
6,023,244	A	2/2000	Snygg	
6,024,333	A	2/2000	Raasch	
6,027,622	A	2/2000	Graser	
6,031,503	A	2/2000	Preiss, II	
6,034,636	A	3/2000	Saitoh	
6,036,810	A	3/2000	Holat	
6,044,046	A *	3/2000	Diezmann et al.	369/14

6,054,961	A	4/2000	Gong
6,057,803	A	5/2000	Kane
6,068,214	A	5/2000	Kook
6,075,493	A	6/2000	Sugawara
6,082,030	A	7/2000	Kesselring
6,097,347	A	8/2000	Duan
6,100,804	A	8/2000	Brady
6,107,920	A	8/2000	Eberhardt
6,114,962	A	9/2000	Wiklof
6,118,426	A	9/2000	Albert
6,124,829	A	9/2000	Iwasaki
6,140,969	A	10/2000	Lindenmeier
6,155,098	A	12/2000	Shapiro
6,239,765	B1	5/2001	Johnson
6,243,013	B1	6/2001	Duan
6,249,260	B1	6/2001	Holloway
6,259,369	B1	7/2001	Monico
6,278,413	B1	8/2001	Hugh
6,325,199	B1	12/2001	Becherucci
6,329,915	B1	12/2001	Brady
6,359,842	B1	3/2002	Taguchi
6,411,213	B1	6/2002	Vega
6,483,473	B1	11/2002	King
6,501,435	B1	12/2002	King
6,501,965	B1	12/2002	Lucidarme
6,533,108	B1	3/2003	Ledingham
6,806,842	B2	10/2004	King
6,828,941	B2	12/2004	King
6,853,345	B2	2/2005	King
7,098,850	B2	8/2006	King
7,193,563	B2	3/2007	King
2001/0000430	A1	4/2001	Smith
2002/0000430	A1	1/2002	Nakai
2002/0167450	A1	11/2002	Korden

FOREIGN PATENT DOCUMENTS

DE	3247425	A1	1/1987
EP	0615285	A2	9/1994
EP	0673007	A2	9/1995
EP	0706232	A2	10/1996
EP	0861788	A1	9/1998
EP	0993069	A2	4/2000
EP	1018779	A2	7/2000
EP	1055943	A2	11/2000
EP	1058338	A2	12/2000
EP	1128466	A2	8/2001
FR	2697801	A1	5/1994
FR	2706422	A1	12/1994
GB	2 335 081	A1	9/1999
GB	2335081	A	9/1999
JP	03196704		8/1991
JP	03196704	A2	8/1991
JP	09 330388	A	6/1996
JP	09188248	A2	7/1997
JP	09330388	A2	12/1997
JP	11035038	A2	2/1999
WO	94/14208	A1	6/1994
WO	WO 94/14208		6/1994
WO	9724689	A1	7/1997
WO	WO 97/24689		7/1997
WO	98/27609	A1	6/1998
WO	9918000	A1	4/1999
WO	99/60657	A1	11/1999
WO	9965002	A1	12/1999
WO	00/23994	A1	4/2000
WO	WO 00/23994	*	4/2000
WO	0026856	A2	5/2000
WO	01/24109	A1	4/2001
WO	0124314	A1	4/2001
WO	01/37215	A1	5/2001
WO	01/73675	A2	10/2001
WO	02/07085	A1	1/2002
WO	0207084	A1	1/2002
WO	0207496	A2	1/2002

OTHER PUBLICATIONS

Supplementary European Search Report dated May 10, 2007, issued in European Application No. 06007370.7, 8 pages.

Supplementary European Search Report dated Nov. 30, 2007, issued in European Application No. 07019560.7, 8 pages.

“AT5510 Transportation Tag,” Product Profile and Specifications, Intermec Technologies Corporation, Sep. 1999, 2 pages.

“BiStatix Whitepaper,” Version 4.1, as early as Mar. 1999, <<http://www.motorola.com/LMPS/Indala/bistatix.htm>> [retrieved Jul. 13, 2000], pp. 1-10.

Cho, Y.K., et al., “Improved Analysis Method for Broadband Rectangular Microstrip Antenna Geometry Using E-Plane Gap Coupling,” Electronics Letters 29(22):1907-1909, Oct. 28, 1993.

“Multi-Purpose Tote and Insertion System for Generic Material Handling,” IBM Technical Disclosure Bulletin 31(6):314-315, Nov. 1, 1988, 2 pages.

Zhu, L., and K. Wu, “Accurate Circuit Model of Interdigital Capacitor and Its Application to Design of New Quasi-Lumped Miniaturized Filters With Suppression of Harmonic Resonance,” IEEE Transactions on Microwave Theory and Techniques 48(3):347-356, Mar. 2000.

“BiStatix Whitepaper,” www.motorola.com, pp. 1019, Jul. 13, 2000. AT5510 Transportation Tag, Intermec Technologies Corporation, pp. 1-2, Sep. 1999.

www.sculptedcd.com/home1.htm.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7




FIG. 8A





FIG. 8B

**FIG. 9**




FIG. 10




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 16




FIG. 17




FIG. 18




FIG. 19





FIG. 20

**FIG. 21**

WIRELESS COMMUNICATION DEVICE AND METHOD FOR DISCS

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

RELATED APPLICATIONS

This application is a continuation-in-part of patent application entitled "Wireless Communication Device and Method," Ser. No. 09/678,271, filed on Oct. 3, 2000, now U.S. Pat. No. 6,501,435, which is a continuation-in-part of application Ser. No. 09/618,505, filed on Jul. 18, 2000, now U.S. Pat. No. 6,483,473, the disclosures of which are hereby incorporated by reference in their entireties as if set forth fully herein.

FIELD OF THE INVENTION

The present invention relates to an apparatus, system and method of providing wireless communication devices in discs and communicating of information concerning the disc containing the wireless communication device.

BACKGROUND OF THE INVENTION

It is often desired to track and identify items, such as packages, containers, discs, etc., and to communicate information concerning such items wirelessly. One method of tracking and providing information concerning packages is to attach a wireless communication device, such as a radio frequency identification (RFID) transponder or other identification device, to packages. The information communicated concerning the packages may include identification information, expiration dates, "born on" dates, lot numbers, manufacturing information, and the like. A wireless communication device may be attached to an individual package or to a container containing multiple packages.

A problem exists when a wireless communication device is attached to packaging or containers constructed out of a conductive material such as foil, or comprised of a metalized or conductive portion. A pole antenna connected to the wireless communication device will not radiate properly if the wireless communication device is attached on the outside of the package. The pole antenna will be shielded if the wireless communication device is placed inside the package.

In addition to conductive materials, wireless communication devices are also used with many other substrates. Each substrate has its own dielectric characteristics that typically affect the impedance matching between the wireless communication device and its antenna. Impedance matching ensures the most efficient energy transfer between an antenna and the wireless communication device.

One particular item for which tracking may be desirable is a disc. Discs can be any type of circular substrate, but the present invention address discs that store digital information in particular such as compact discs or mini discs. Note that in this context, the term "mini disc" does not refer to the trademark used by SONY, but rather to a miniature compact disc that is optically read. Most compact discs and mini discs are made from a metalized outer portion and a plastic inner portion. Digital video discs or Digital versatile discs (collectively DVDs) are made from substantially the same structure. This tracking may be for identification, such as in a retail outlet,

computer system or jukebox (for compact-discs), theft prevention, authenticity purposes or the like as needed or desired.

It may be also advantageous for such a wireless communication device to communicate on different frequencies so that one device can be used for various applications. For instance, an operating frequency of 2.45 GHz is used frequently outside the United States, but an operating frequency of 915 MHz is frequently used in the United States. Many companies manufacture wireless communication devices that are capable of operating at both 915 MHz and 2.45 GHz frequencies so that either frequency can be chosen for operation. However, wireless communications device applications, such as attaching wireless communication devices to packages for informative and tracking purposes, configure the device to communicate on only one frequency—either a frequency for the United States or a frequency for use abroad. It would be advantageous to construct a wireless communication device with an antenna structure that is capable of communicating at more than one frequency. This would allow one wireless communication device to be applicable for uses in both the United States and abroad.

SUMMARY OF THE INVENTION

The present invention relates to a wireless communication device for use in conjunction with a disc, such as a compact disc, mini disc or digital video disc, or comparable item. In particular, an antenna is formed with a conductive tape or the like attached to a center portion of the disc. The metalization of the disc coupled with the tape, form a slot antenna for operation at a first frequency. Further, conductive tabs may be used to couple to the slot in such a fashion that the tabs form an antenna at a second frequency. These conductive tabs may also serve the purpose of delimiting the length of the slot regardless of their use as a second antenna.

It should be appreciated that the parent applications discussed wireless communication devices associated with a package, container or other material to communicate information concerning the package, container or other material. A wireless communication device is provided that contains a control system, communication electronics, memory, and an antenna. The wireless communication device may contain a sensor to sense environmental conditions surrounding the wireless communication device. The wireless communication device contains one or more tabs constructed out of conductive material. The tab(s) may serve as both a pole antenna and may attach the wireless communication device to a slot, thereby forming a slot antenna. While helpful in some embodiments such is not required in all the embodiments herein presented.

In one embodiment, the wireless communication device is a transponder that is interrogated by an interrogation reader for communication purposes. The wireless communication device is attached to a package that may be constructed out of a conductive material, such as foil packaging used for food or liquid.

In another embodiment, the tab(s) form a pole antenna to communicate in a first mode at one frequency, and the tab(s) are attached across a slot in a package to communicate in a second mode at a second frequency. One tab is used in one embodiment to form a monopole type antenna, and two tabs are used in another embodiment to form a dipole antenna. In another embodiment, the tab(s) can be varied in shape and size to adjust to surfaces that vary in form.

An asymmetrical antenna arrangement may be provided so that the impedance of the antenna is not substantially affected

by the substrate to which the wireless communication device is attached. In one embodiment, the asymmetrical antenna arrangement is an asymmetrical dipole antenna formed by asymmetrical tabs. For example, the wireless communication device may be placed in an indentation in the substrate so that the wireless communication device does not protrude from the substrate surface. Asymmetrical tabs are placed on the surface of the substrate. The asymmetrical tabs are connected to the wireless communication device with feed lines to provide an asymmetrical dipole antenna. In a second embodiment, the asymmetrical antenna arrangement is an asymmetrical slot antenna.

In another embodiment, a wireless communication device placed onto a disc, such as a compact disc or video disc, is used in conjunction with an interrogator to identify a disc for either promotional or security purposes. A customer may purchase a compact disc or video disc in a retail store. As the customer leaves the retail store, an interrogator determines the identification of the disc purchased by the customer and displays and/or plays a special message to the customer. If an interrogator detects an unpurchased disc leaving the retail store, the interrogator may indicate an alert and/or alarm condition.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram illustrating communication between a wireless communication device and an interrogation reader;

FIG. 2 is an illustration of the wireless communication device with slot antenna on a foil food package;

FIG. 3A is a schematic top view diagram of the wireless communication device with coupling tab devices containing a dielectric, adhesive material;

FIG. 3B is a schematic side view diagram of the wireless communication device in FIG. 3A;

FIG. 3C is a schematic diagram of the wireless communication device having its own slot;

FIG. 4 is a schematic diagram of the wireless communication device attached across a slot to form a slot antenna;

FIG. 5A is a schematic diagram of the wireless communication device having a slot antenna of a particular width to match the impedance between the wireless communication device and the slot;

FIG. 5B is a schematic diagram of the wireless communication device illustrated in FIG. 5A with a slot of different width;

FIG. 6 is a schematic diagram of a circularly polarized slot antenna;

FIG. 7 is a schematic diagram of another type of packaging containing a wireless communication device;

FIG. 8A is a schematic diagram of the wireless communication device having a slot antenna formed by a foil package closing;

FIG. 8B is a schematic diagram of the wireless communication device illustrated in FIG. 8A with the foil package having an additional seal below the wireless communication device;

FIG. 9 is a flowchart illustrating the operation of the wireless communication device when sensing to detect its presence outside of a package;

FIG. 10 is a schematic diagram of wireless communication devices mounted on a carrier or support for stamping into packages in an assembly line;

FIG. 11A is a top plan view of a wireless communication device with an asymmetrical antenna arrangement;

FIG. 11B is a side elevational view of the wireless communication device of FIG. 11A;

FIG. 12A is a schematic diagram of a particular asymmetrical antenna arrangement;

FIG. 12B is a schematic diagram of the matched gain of the particular asymmetrical antenna arrangement in FIG. 12A;

FIG. 12C is a schematic diagram of the matched gain of the particular asymmetrical antenna arrangement in FIG. 12A with lossless FR4;

FIG. 13 is a schematic diagram of an alternative asymmetrical antenna arrangement;

FIG. 14A is a schematic diagram of another alternative asymmetrical antenna arrangement;

FIG. 14B is a schematic diagram of a second embodiment of the alternative asymmetrical antenna arrangement of FIG. 14A;

FIG. 15A is a schematic diagram of a wireless communication device having an asymmetrical antenna arrangement on a side of an aluminum beverage can;

FIG. 15B is a schematic diagram of wireless communication device having an asymmetrical antenna arrangement on the bottom dome of an aluminum beverage can;

FIG. 16 is a schematic diagram of a wireless communication device mounting arrangement;

FIG. 17 is a schematic diagram of a wireless communication device using an asymmetrical slot antenna;

FIG. 18 illustrates a top plan view of a compact disc with an exemplary embodiment of a wireless communication device secured thereto; and

FIG. 19 illustrates a top plan view of selected elements of the wireless communication device of FIG. 18 removed from the compact disc;

FIG. 20 illustrates a flow chart process of an interrogation reader identifying a disc in a retail store to determine if the disc was purchased before its removal from the retail store; and

FIG. 21 illustrates a flowchart process of an interrogation reader performing a trigger event in response to identification of a disc purchased by a customer in a retail store.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention is directed to a particular wireless communication device positioned on a disc. However, this technology builds on a line of patent applications with related subject matter. This related subject matter is presented in full below, with the new material described with reference to FIGS. 18 and 19 following. For the purposes of the present invention, the term "mini disc" is a miniaturized optical disc. The term "DVD" includes digital video discs and digital versatile discs, the latter capable of storing computer data as well as video data. The prior inventions were directed to a device, system and method of attaching a wireless communication device, such as a radio frequency identification device (RFID), to a package or container to communicate information about the package or container. The package may be an individual package containing specific contents, or an individual, exterior package containing a group of additional, interior individual packages. The word "package" and "container" are used interchangeably herein to describe a material that houses contents, such as goods or other individual packages, and equivalent structures. The present invention should not be limited to any particular meaning or method when either "package" or "container" is used.

As illustrated in FIG. 1, the invention includes a wireless communication device 10 for electronic communication.

5

Some wireless communication devices **10** have both a transmitter and receiver. Other wireless communication devices **10**, known in the art as “transponders,” are interrogated by interrogation reader **50**, whereby the transponder communicates back by altering field **58** containing interrogation signal **56**. This description refers to the terms “transponder” and wireless communication device **10** interchangeably, and the use of the term transponder is not intended to limit the type of wireless communication device **10** applicable to the present invention. Wireless communication devices **10** are available that communicate at various frequencies, including UHF and VHF. One embodiment of the present invention uses a wireless communication device **10**, also called a “transponder,” that is a passive radio-frequency device with the ability to rectify incoming radio energy and provide power to power the device for communication and operation. The invention is also applicable to active devices that have their own power source for communications. It should be readily understood to one of ordinary skill in the art that there are many other different types of wireless communication devices **10** that allow electronic communication and thus the present invention is not limited to any one particular type.

Transponder **10** includes a control system **12** and communication electronics **14**. Transponder **10** may also contain memory **18** for storage of information to be communicated to an interrogation reader **50**. Alternatively, transponder **10** may store information such as an identification number or other information by using diodes, dip switches or some other like circuitry in lieu of erasable memory **18**. Antenna **16** is provided to receive the interrogation signal **56** from interrogation reader **50**. Antenna **16** may be either external to or internal to transponder **10**. The particular type and location of antenna **16** will depend on the operating frequency of transponder **10** and the particular design desired. Transponder **10** may also be connected to sensor **20** for sensing ambient or environmental information surrounding transponder **10**, package **200** containing transponder **10**, or the contents of package **200**. One example of sensor **20** may be a quartz crystal resonator like that described in U.S. Pat. No. 5,922,550, entitled “Biosensing devices which produce diffraction images,” incorporated herein by reference in its entirety. A quartz crystal resonator detects analytes that may be present in food. Analytes include, but are not limited to, microorganisms such as bacteria, yeasts, fungi and viruses.

Antenna **16** receives signal **56** through the radiated interrogation field **58**. Antenna **16** passes received signals **56** to communication electronics **14**. Communication electronics **14** contain circuitry necessary to interpret signal **56** from field **58** and to further communicate the interpreted signal to control system **12**. Control system **12** is an integrated circuit, printed circuit board, or other type of microprocessor or micro-controller electronics that controls the operations of the transponder **10**. Control system **12** is connected to communication electronics **14** to communicate and receive transmissions. Control system **12** is also connected to memory **18** for storing and retrieving information. Control system **12** may further include a clock (not shown). Control system **12** determines if any actions are needed in response to the communications received from communication electronics **14**.

FIG. **1** also depicts how communication is achieved with transponder **10** using an interrogation reader **50**. Interrogation reader **50** contains interrogation communication electronics **52** and an interrogation antenna **54**. Interrogation reader **50** communicates with the transponder **10** by emitting an electronic signal **56** modulated in a frequency by interrogation communication electronics **52** through interrogation antenna **54**. Interrogation antenna **54** may be any type of

6

antenna that can radiate signal **56** through a field **58** so that a compatible device, such as transponder **10**, can receive such signal **56** through its own antenna **16**. Field **58** could be electro-magnetic, magnetic, or electric. Signal **56** is a message containing information or a specific request for the transponder **10**.

When antenna **16** is in the presence of field **58** emitted by interrogation reader **50**, communication electronics **14** are energized by signal **56**, thereby energizing transponder **10**. Transponder **10** remains energized so long as antenna **16** is in the field **58** of interrogation reader **50**. Communication electronics **14** demodulates signal **56** and sends the message containing information or request to control system **12** for appropriate actions. For example, the request may be for transponder **10** to communicate its identification, or information about a material or package containing transponder **10**, such as date of manufacture, place of manufacture, and/or lot number. The message may also be a request for information regarding ambient or environmental measurements sensed by sensor **20**.

Another description of a transponder **10** that may be used with the present invention is located in U.S. Pat. No. 5,347,280, entitled “Frequency diversity transponder arrangement,” incorporated herein by reference in its entirety. Transponder **10** is one type of wireless communication device. Other types of wireless communication devices **10** may be used with the present invention. For instance, transponder **10** may have a transmitter that can send information to interrogation reader **50** without having to alter signal **56**. Transponder **10** may contain a battery to power the transmitter, or an energy storage unit that is charged by energy received from signal **56** when wireless communication device **10** is in the range of field **58**. It is readily understood to one of ordinary skill in the art that there are many other types of wireless communications devices and communication techniques than those described herein, and the present invention is not limited to a particular type of device, technique or method.

Transponder **10** may be attached on any type of device or package to identify and communicate information concerning the device or package. For instance, transponder **10** can be attached to a food package and may contain identification information and other information about the food contained inside the package, such as its date of manufacture, “born on” date, expiration date for sale or consumption and lot number. For example, transponder **10** can be attached to a wine bottle and contain information concerning the type of wine and its ingredients or make up, the date of manufacture, and expiration dates, if applicable. Transponder **10** can be attached to virtually any device or package conceivable.

FIG. **2** illustrates transponder **10** attached to a food package **200**. Antenna **16** can either be a slot antenna **16A**, as illustrated in FIG. **2**, or a pole antenna **16B**, as illustrated in FIGS. **3A** and **3B**. A slot **300** is provided in package **200** to provide a slot antenna **16A**. Package **200** includes a surface **202**. At least one tab, made out of conductive material, such as a metallic material, is attached to transponder **10**, and more particularly to communication electronics **14** inside transponder **10**. Two or more tabs **100** may also be attached to transponder **10** to provide antenna **16**. The use of “tab” is used in singular and plural herein, and reference in either form is not intended to limit the invention to only one tab **100**, or more than one tab **100**.

Tabs **100** are attached to slot **300** to form a slot antenna **16A**. For the purposes of this specification, the word “attached” is used generically to mean either attached directly or connected to slot **300**. The tabs **100** may either be attached on slot **300** or proximate to slot **300**. Tabs **100** may also serve

as pole antenna 16B. Tabs 100 may also be constructed by applying a conductive fluid (e.g. conductive ink) onto surface 202.

The present invention can also be used with transponder 10 containing one tab 100 to form either slot antenna 16A or pole antenna 16B. One tab 100 can be used to form pole antenna 16B in the form of an antenna having monopole-like radiation pattern. If one tab 100 is used to form slot antenna 16B, tab 100 is attached to slot 300, and transponder 10 is attached, in the form of grounding, to slot 300 to form a ground plane. Using one tab 100 as a slot antenna 16B will create a monopole-like radiation pattern.

If surface 202 is constructed out of a conductive material, it may be advantageous to use tabs 100 to create a slot antenna 16A rather than a pole antenna 16B. Examples of conductive surfaces 202 include food foil packaging, wine bottles cork foil, jewelry, watches, cigar label foil, and alcoholic bottle foil labels. If tabs 100 are attached on a conductive surface 202 without forming a slot antenna 16A, the radiation pattern of the resulting pole antenna 16B created by tabs 100 may not be properly tuned to the operating frequency of transponder 10. Factors such as the conductivity and surface area of surface 202 affect the radiation pattern of a pole antenna 16B formed by tabs 100 when tabs 100 are attached to surface 202. Packages 200 vary greatly in size, shape, and area. It is desirable for transponder 10 and tabs 100 to be manufactured such that transponder 10 operates at a desired frequency when using tabs 100 as a pole antenna 16B, regardless of the particular characteristics of package 200.

Packages 200 that are constructed out of conductive material, such as foil, containing transponder 10 inside the package 200 cannot use a pole antenna 16B. The radiation pattern of pole antenna 16B is shielded by the conductive material. Therefore, another reason for using tabs 100 to create a slot antenna 16A rather than a pole antenna 16B may be so that packages constructed out of conductive material and containing transponder 10 inside package 200 can effectively communicate desired information wirelessly.

If tabs 100 are attached on surface 202 that is not conductive, tabs 100 can function at the desired operating frequency as a pole antenna 16B, regardless of the characteristics of package 200. If two tabs 100 are used, the tabs 100 serve as a dipole antenna 16B. One tab 100, instead of two tabs 100, may also be used to serve as antenna 16, creating a monopole type radiation pattern as previously described above. A ground plane may be provided between transponder 10 and surface 202 such that communication electronics 12 is attached to surface 202 to from a ground. In summary, tabs 100 can serve to provide either a pole antenna 16B or slot antenna 16A depending on the package 200 and its characteristics.

FIGS. 3A, 3B and 3C illustrate transponder 10 shown in FIG. 2 in more detail. FIG. 3A illustrates transponder 10 from a top view perspective. Tabs 100 are made out of a conductive material. For example, tabs 100 may be constructed out of metals, such as aluminum or copper. FIG. 3B illustrates transponder 10 from a side view perspective. Tabs 100 can either be attached directly to surface 202 or coupled to surface 202 by placing tabs 100 on an optional dielectric adhesive material 102 that is attached to surface 202. Use of adhesive material 102 may be necessary to attach the transponder 10 to surface 202. If transponder 10 is attached on a package 200 constructed out of a conductive material without a slot 300, such that tabs 100 act as a dipole antenna 16B, a dielectric material 102 may be attached between the surface 202 and tabs 100 so that the radiation pattern of the dipole antenna 16B is not affected by the conductive package 200. If such a

dielectric material 102 is used, tabs 100 are reactively coupled, rather than directly connected, to surface 202. One tab 100, instead of two tabs 100, may also be used to serve as antenna 16, creating a monopole type radiation pattern. If transponder 10, with tabs 100, is attached across a slot 300 in a conductive surface 202, a slot antenna 16A is formed for antenna 16.

A transponder 10 may be attached to a slot antenna 16A as part of its construction, instead of using a slot 300 created in package 200 to form a slot antenna 16A. FIG. 3C illustrates slot 300 as a rectangular, conductive material 250 having a hollow portion cut out to form an inner, non-conductive portion 252. Tabs 100 are attached to non-conductive portion 252. Slot 300 may be constructed in any shape desired so long as slot 300 is constructed out of a conductive material 250 that contains an inner, non-conductive portion 252. This inner, non-conductive portion 252 can be air, formed by a cut out as illustrated in FIG. 3C, or can be formed by placing a non-conductive material, such as plastic, onto or inside conductive material 250. The conductive material 250 may also contain an adhesive 102, so that slot 300, with transponder 10 attached, can be easily attached to package 200. It may be desirable to provide slot 300 as part of transponder 10, instead of package 200, insofar as this eliminates the requirement to create a slot 300 in package 200 as part of the construction of package 200. For example, it may be impractical or impossible to provide a slot 300 in package 200, but still desirable to attach transponder 10 to package 200 using a slot antenna 16A. As an additional advantage of this embodiment illustrated in FIG. 3C, since slot 300 is provided as part of transponder 10, package 200 can be constructed out of non-conductive material.

FIG. 4 illustrates transponder 10 with tabs 100 acting as both a pole antenna 16B and slot antenna 16A. A slot 300 is provided by cutting out a portion of conductive surface 202. The length of the tabs 100 define the operating frequency of the antenna 16 if tabs 100 are configured to act as a pole antenna 16B. In one embodiment, the tabs 100 are each $\frac{1}{4}$ in length, or 30.6 millimeters each, to form a dipole antenna 16B with a total length of $\frac{1}{2}$ and an operating frequency of 2.45 GHz.

As previously discussed, tabs 100 may also serve to form a slot antenna 16A if attached across a slot 300 in a conductive surface 202. The slot 300 length defines the operating frequency of the slot antenna 16A. In one embodiment, the slot 300 length is $\frac{1}{2}$ or 164 millimeters so that the transponder 10 operates at a frequency of 915 MHz. More information on slot antennas 16A and their operation is described in U.S. Pat. No. 4,975,711, entitled "Slot antenna device for portable radio-telephone," incorporated herein by reference in its entirety.

In this manner, the transponder 10 has two antenna 16 configurations that are capable of communicating at two frequencies. If transponder 10 is capable of communicating at two different frequencies, as discussed above, the pole antenna 16B and slot antenna 16A can be configured to communicate at different frequencies as well, enabling the transponder 10 to effectively communicate at both frequencies. This arrangement provides an advantage in particular if 915 MHz is a desired frequency. 915 MHz is frequently used as an operating frequency for electronic communication in the United States, but 2.45 GHz is frequently used outside the United States. Therefore, providing transponder 10 with the capability of communicating at both 915 MHz and 2.45 GHz is advantageous so that transponder 10 can be used for applications in both the United States and abroad. However, if this

dual capability is not required, transponder 10 can be configured to operate solely using a pole antenna 16B or slot antenna 16A.

FIGS. 5A and 5B illustrate transponder 10 attached across slots 300 of varying widths. The width of slot 300 affects the impedance of slot 300. For example, a wider slot 300, illustrated in FIG. 5A, may have a higher impedance than the narrower slot 300, illustrated in FIG. 5B. Varying the slot 300 width varies the impedance of the slot antenna 16B to maximize antenna 16 strength. It is desirable to match the impedance of slot 300 to the impedance of transponder 10. In the one embodiment, the slot antenna 16A has a fairly low impedance. Therefore, it is desirable to transform the slot 300 impedance so as to match the impedance of transponder 10, thereby maximizing energy transfer between transponder 10 and slot 300 and maximizing the strength of the radiation pattern emitted by the slot antenna 16A. Matching the impedances also minimizes reflection in the radiation pattern of slot antenna 16A. Transponder 10 may comprise more than one layer, including conductive, dielectric and magnetic materials, such as ferrites, to introduce inductance, thereby aiding modification of the characteristics of surface 202 for impedance matching purposes.

In addition to the composition of transponder 10, the area of tabs 100 affect the impedance of transponder 10. As discussed above, it is desirable to match the impedance of transponder 10 and slot 300. Tabs 100 can also be varied to ensure optimal coupling to surface 202. The impedance of slot 300 may be varied for matching purposes by modifying relevant characteristics of surface 202. For example, a conductive package for food (e.g. foil) may have a surface 202 that is variable in width, dielectric or metallic characteristics. Capacitance of tabs 100 may be taken into consideration for impedance matching when attaching tabs 100 to a particular surface 202. The capacitance of tabs 100 affects the impedance of transponder 10. The total volume of tabs 100 (surface area times thickness) affects their capacitance. Tabs 100 are similar to parallel plate capacitors in series with wireless communication device 10. The larger the volume of tabs 100, the larger their capacitance. It is therefore desirable to design and construct tabs 100 with a capacitance that is commensurate with surface 202 to match impedance of transponder 10 and slot 300 for optimal performance.

An impedance matching network may also be used to match slot 300 impedance to transponder 10 impedance, as discussed in patent application Ser. No. 09/536,334, entitled "Remote Communication Using Slot Antenna," assigned to assignee of the present invention, and incorporated herein by reference in its entirety.

FIG. 6 illustrates two slots 300A, 300B in surface 202 that are substantially perpendicular to each other, with tabs 100 attached across the slots 300A and 300B. The tabs 100 are attached to slots 300A, 300B at vertical angles, but tabs 100 can also attach to slots 300A, 300B adjacent to each other. This structure creates a circularly polarized slot antenna 16A. Tabs 100 are attached to each of slots 300A and 300B. The length of the first slot 300A, a, is slightly shorter than $\frac{1}{2}$. The length of the second slot 300B, b, is slightly greater than $\frac{1}{2}$. The two slots 300A, 300B provide antennas 16 that can be considered resonant circuits, with their associated phase delay at the operating frequency of ± 45 degrees to each other. This causes transponder 10 to receive efficiently radiation in more than one dimension and, specifically, in the form of a circular pattern so that the orientation of transponder 10 on surface 202 is somewhat irrelevant for communication.

FIG. 7 illustrates another type of package 200 containing transponder 10. Package 200 is configured to contain gum

sticks (not shown). The package 200 is constructed out of a conductive material. Gum sticks are wrapped in their own individual foil wrappers and are placed inside paper non-conductive wrappings 900 contained inside package 200.

Parts of the non-conductive wrappings 900 touch or couple to the interior of package 200. Such attaching or coupling provides a slot antenna 300 as previously discussed, where the non-conductive wrappings provide slot 300 and the package 200 inside provides the surrounding conductive material. FIG. 7 illustrates transponder 10 placed inside package 200. Tabs 100 are attached to slot 300, as previously described, to provide communication. Again, tabs 100 are also capable of operating as a pole antenna 16A. The package 200 could also be a cigarette package 200. Again, the tabs 100 may be attached to a slot 300, formed by conductive material of the package 200 surrounding to an internal non-conductive portion internal to package 200, to form slot antenna 16A. In a variation on this embodiment, the slot 300 may be the dielectric that forms the tear away strip that allows such packages to be opened.

FIGS. 8A and 8B illustrate particular manners in which transponder 10 is placed inside package 200. FIG. 8A illustrates transponder 10 located inside the top of package 200 where package 200 opens and seals in a pouch-like fashion. The inside surface 202 of package 200 is a conductive material, such as a foil, including the sides of package 200 that come together when package 200 is closed and sealed. As discussed previously, it is desirable to configure transponder 10 to communicate using a slot antenna 16A when transponder 10 is inside a package 200 constructed out of conductive material. In this embodiment, slot antenna 16A is not formed by cutting out a portion of surface 202, but rather by inserting a non-conductive material 302, such as a dielectric, inside package 200 at the top to form a seal 306 where the sides come together. In this manner, a slot 300 is formed by the separation of the conductive material of inner surface 202 when the sides of package 200, are closed and sealed. Such a method of placing a transponder 10 inside a package 200 may be advantageous where it is desired to protect transponder 10 from theft, tampering or other unwanted elements.

Placing transponder 10 inside package 200 may also be useful to indicate if package 200 has been opened, and, therefore, possibly contaminated. Packages 200 that contain food for consumption or medical devices and equipment requiring sterility are also possible applications. Transponder 10 is placed inside package 200 as previously discussed and illustrated in FIGS. 8A and 8B.

One embodiment to detect the opening of package 200 is to provide tabs 100 constructed out of a material that reacts to ambient air. When package 200 is opened, tabs 100 become exposed to the outside air. If tabs 100 are constructed out of a material that loses its conductivity when exposed to air, transponder 10 cannot be interrogated and/or communicate as effectively since tabs 100 are attached to slot 300 to provide a slot antenna 16A for communication. Thus, lack of communication or degraded communication can be used as an indicator that package 200 has been previously opened.

FIG. 8B illustrates an embodiment where it is not only desirable to place transponder 10 inside package 200, but also to separate transponder 10 from the contents of package 200. In this embodiment, a second seal 304 is provided in package 200. The transponder 10 is located in first seal 306 as previously described above. The transponder 10 is still exposed to air when package 200 is opened, but transponder 10 is not contained in the same portion of package 200 where the contents of package 200 are contained. This embodiment may be desirable when the contents of package 200 are food or

11

liquid for consumption, or other materials where it is not safe or desirable for transponder 10 to come in contact with the contents of package 200.

Another embodiment uses sensor 20 to determine when package 200 is opened. Sensor 20 may be any type of sensor that senses elements of air in the area on the outside of package 200. Air contains oxygen, nitrogen and other gaseous elements. For instance, sensor 20 may be an oxygen sensor, including the sensor described in U.S. Pat. No. 6,027, 622, entitled "Sensor element," incorporated herein by reference in its entirety. Further, sensor 20 can be any type of sensor that senses an environmental factor, such as a gaseous element, that is not contained inside package 200 when sealed with transponder 10 therein.

FIG. 9 illustrates a flow chart of one embodiment of transponder 10 using sensor 20 to determine if package 200 has been opened. The process starts (block 400) and control system 12 receives signals from sensor 20 indicating a reading (block 402). The control system 12 determines if reading from sensor 20 indicates that package 200 is opened (decision 404). If package 200 is opened, control system 12 stores this event in memory 18 to communicate it the next time transponder 10 is interrogated by interrogation reader 50 (block 406). If transponder 10 has transmission capability, transponder 10 may transmit the event of package 200 being open immediately. The process then ends (block 408). Alternatively, if it is determined that the package 200 is not open (decision 404), transponder 10 takes another reading from sensor (block 402), repeating the process again.

FIG. 10 illustrates an embodiment of providing transponders 10 for stamping onto packages 200 in an assembly line or other manufacturing capacity. A carrier 700 is provided that contains individual slides 702. Carrier 700 may be a film or other similar type of material. Transponder 10 is manufactured and placed on carrier 700 during assembly whereby each portion 702 contains one transponder 10. The carrier 700 is constructed out of a conductive material. Carrier 700 may also contain, as part of its construction, one or more conductive tabs 100. Since carrier 700 is a conductive material, tabs 100 are conductive. Transponder 10 is placed onto carrier during assembly and connected to tabs 100 formed in carrier 700. Later during the manufacture or assembly process, transponder 10 is placed onto packages 200. Carrier 700 may have perforations 704 for movement by a machine in an assembly line when mounting transponders 10 to portions 702. Transponder 10, attached to one or more tabs 100 formed in carrier 700, is stamped onto packages 200 in an assembly line by placing carrier 700 proximate to packages 200. The carrier 700 is stamped in such a manner that transponder 10, with tabs 100 attached, is placed onto packages 200. When desired, a stamping process places carrier 700 and a particular portion 702 in contact with package 200 so that transponder 10 is more easily attached to package 200. The package 200 may contain slot 300, whereby transponder 10 is stamped across the slot 300. Transponder 10, tabs 100, or both, may also contain an adhesive 102, as previously discussed, so that transponder 10 attaches to package 200 securely.

FIG. 11A illustrates a top view of transponder 10 having an asymmetrical dipole antenna 16. An asymmetrical dipole antenna 16 is an antenna having a first pole different in shape, including, but not necessarily limited to, length, width, volume, and/or density, from the second pole. In FIG. 11A, transponder 10 is coupled to two conductive tabs [10A, 10B] 100A, 100B. The first conductive tab 100A is asymmetrical with respect to the second conductive tab [10B] 100B. The two [symmetrical] asymmetrical tabs [10A] 100A, 100B [comprises] comprise asymmetrical dipole antenna 16.

12

FIG. 11B illustrates a side view of one embodiment of the transponder 10 illustrated in FIG. 11A. Tabs 100A, 100B are placed on a dielectric 102. Dielectric 102 acts as an insulator between tabs 100A, 100B and substrate 202. Dielectric 102 is a material that is substantially non-conductive. Examples of materials that may be used to form a dielectric 102 include, but are not limited to: cardboard, plastic, Lexan plastic, fabric, and polypropylene.

If substrate 202 is constructed out of a conductive material, a separate dielectric 102 is provided between substrate 202 and transponder 10 as illustrated in FIG. 11B. If substrate 202 is constructed out of a non-conductive material, substrate 202 may additionally act as dielectric 102. In this case, a ground plane (not shown) may be placed on the opposite side of substrate 202, so that substrate 202, acting as a dielectric 102, is in between transponder 10 and the ground plane. Note that the ground plane may be placed on other places on substrate 202 and not necessarily on the opposite side from transponder 10.

The shape, type, and characteristics of antenna 16 affect the impedance of transponder 10. The substrate 202 also affects the impedance presented to transponder 10 by antenna 16. This is especially true when a thin dielectric 102 is used, because there is less insulation between the transponder 10/antenna 16 and substrate 202. A thin dielectric 102 is between approximately 0.1 mm and 2.0 mm. For transponder 10 to transfer radiation energy from antenna 16 at the highest radiation level possible without losses, the impedance of the transponder 10 should be matched to the impedance of antenna 16 as placed onto substrate 202. For example, in one embodiment, the transponder 10 may have an impedance of 15-j60 ohms. To get optimum transfer of energy between antenna 16 and transponder 10, antenna 16, as placed onto substrate 202, would need to have a conjugate impedance of transponder 10. In practice, impedance matching between transponder 10 and antenna 16 does not have to be exact to have energy transfer between transponder 10 and antenna 16 necessary for communication. Impedances between transponder 10 and antenna 16 that are substantially the same will still allow good energy transfer between antenna 16 and transponder 10.

The transponder 10 may be used with a variety of different substrates 202. To minimize the protrusion of transponder 10 from substrate 202, a thin dielectric 102 is used. Empirical and modeling data have shown that the operation of an asymmetrical antenna 16 is substantially insensitive to the size and/or dimensions of substrate 202 when using a dielectric 102 that is relatively thin. Materials with poorly defined structures and/or dielectric constants, such as cardboard, can be used as dielectric 102 materials, which also serve as substrate 202. This discovery allows antenna 16 and transponder 10 impedance to be matched more easily during manufacture without having to take characteristics of substrate 202 into consideration, such as substrate 202 size, thickness, and/or dielectric constant. Substrate 202 does have a certain dielectric constant depending on its material of manufacture and the amount of air present in substrate 202. The dielectric constant is the amount of permissivity of a particular material. In addition, antenna 16 elements, such as tabs 100, do not need precise dimensional control, allowing less precise and less expensive materials and methods to be used to define such elements. For example, tabs 100 may be constructed using label printing techniques and conductive ink, such as described in U.S. Pat. No. 5,566,441, entitled "Attaching an electronic circuit to a substrate," incorporated herein by reference in its entirety.

In the embodiment illustrated in FIGS. 11A and 11B, asymmetrical tabs 10A, 100B act as the asymmetrical

13

antenna 16. Although the impedance of tabs 100A, 100B are substantially insensitive to substrate 202, tabs 100A, 100B may be increased or decreased in size, length, and/or width depending on variations in the thickness and dielectric constant of substrate 202 to provide optimal impedance matching to transponder 10.

FIG. 12A illustrates one modeled example of asymmetrical tabs 100A, 100B used on a substrate 202. Substrate 202 is a common printed circuit board (PCB) material FR4 with an approximate dielectric constant of 4.65. Two additional tabs 101A, 101B are added to tabs 100A, 100B respectively to allow proper modeling and have no effect on results of the asymmetrical antenna 16. FIG. 12B illustrates the predicted gain of antenna 16, which is -0.85 dBi at 915 MHz. FIG. 12C illustrates the modeled gain of an asymmetrical antenna 16, using tabs 100A, 100B, on a substrate 202 having the same dielectric constant as FR4 without losses. The predicted gain for this model is 5.3 dBi at 915 MHz.

As previously stated, tabs 100A, 100B may vary in size in different manners to provide an asymmetrical antenna 16. FIGS. 13, 14A and 14B illustrate other embodiments of asymmetrical antennas 16. FIG. 13 illustrates an embodiment of an asymmetrical antenna 16, whereby tabs 10A, 100B are at right angles to each other. One tab 100A is substantially thinner than the other tab 100B. The performance of the asymmetrical antenna 16 illustrated in FIG. 13 was found to have similar performance characteristics of the asymmetrical antenna 16 illustrated in FIG. 12A.

FIGS. 14A and 14B illustrate two other embodiments of an asymmetrical antenna 16. In FIG. 14A, one tab 100B, hereto represented as being thicker than tab 100A, is in the shape of a ring, and the other tab 100A is nested inside the area bounded by tab 100B. This asymmetrical antenna 16 is almost one-half the total length of the asymmetrical antenna 16 illustrated in FIG. 12A, and may be used in applications where a shorter asymmetrical antenna 16 is desired. Similarly, FIG. 14B depicts another alternate embodiment of asymmetrical antenna 16. In contrast to the embodiment of FIG. 14A, a relatively thick tab 100B is nested within tab 100A, which is arranged in the shape of a ring or loop. Again, asymmetrical antenna 16 in FIG. 14B, is almost one-half the total length of the asymmetrical antenna 16 illustrated in FIG. 12A, and may be used in applications where a shorter asymmetrical antenna 16 is desired. For example, a shorter asymmetrical antenna 16 may be advantageous for design or manufacturing reasons.

FIG. 15A illustrates another embodiment of an asymmetrical antenna dipole antenna 16, whereby substrate 202 is an aluminum can 600. A separate dielectric 102 is provided between transponder 10 having tabs 100A, 100B and can 600, because can 600 is constructed out of a conductive material namely aluminum (as previously discussed). In this particular embodiment, an asymmetrical antenna 16 is created by using tab 100B that is longer in length than tab 100A. FIG. 15B illustrates another asymmetrical antenna embodiment, again using a can 600 as substrate 202. Transponder 10 is placed on the underneath dome 602 of can 600. Two asymmetrical tabs 100A, 100B are provided to form a dipole antenna 16. The resultant dipole antenna 16 is asymmetrical. Tab 100A is shorter in length than tab 100B, and tab 100B is wider than tab 100A.

FIG. 16 illustrates another embodiment of an asymmetrical dipole antenna 16. In this embodiment, transponder 10 is placed into an indentation 500 of substrate 202 so that transponder 10 will not protrude from substrate 202. Transponder 10 may be damaged or hit by an outside force if it protrudes from substrate 202. Tabs 100A, 100B are provided on the

14

surface of substrate 202 on each side of indentation 500. Conductive leads 502 are placed on the inside of indentation 500 and are electrically coupled to tabs 100A, 100B. Such coupling may be accomplished by direct connection, capacitive coupling or inductive coupling. Tabs 100A, 100B are asymmetrical to one another. Transponder 10 has feed lines 504 on each side that couple to conductive leads 502 to couple transponder 10 and tabs 100A, 100B together. In this manner, transponder 10 uses tabs 100A, 100B to form an asymmetrical dipole antenna 16. As illustrated, transponder 10 has not yet been positioned inside indentation 500 below the surface level of substrate 202. When properly positioned, transponder 10 does not protrude from the surface of substrate 202.

FIG. 17 illustrates another embodiment of an asymmetrical antenna 16. In this embodiment, the asymmetrical antenna 16 is provided using a slot 300 to form an asymmetrical slot antenna 16. In this particular embodiment, slot 300 length is $\lambda/4$ and slot 300 width is 3.625 mm, although other lengths and widths may be used. Transponder 10 is placed across the slot 300 using tabs 100 to form a slot antenna 16. The asymmetrical nature of the slot antenna 16 is controlled by the location of the placement of tabs 100 across slot 300, and not by differences in the size, width, and/or density of tabs 100. Tabs 100 are placed off-center of slot 300, thereby forming an asymmetrical slot 300. An asymmetrical slot 300 is a slot that is split into at least two separate portions whereby each portion is of different size, width, and/or depth. If substrate 202 is constructed out of a conductive material, a separate dielectric 102 is provided between transponder 10 and substrate 202. If substrate 202 is constructed out of a non-conductive material, substrate 202 is dielectric 102 with a ground plane provided (not shown). Again, this asymmetrical antenna 16 is substantially insensitive to substrate 202 when using a thin dielectric 102, as previously discussed above.

An alternative embodiment to FIG. 17 is to only couple one tab 100 to transponder 10 to provide a monopole asymmetric antenna 16. Again, tab 100 is placed off-center across slot 300. A ground plane is provided and coupled to transponder 10 so as to ground transponder 10.

The focus of the present invention is on providing wireless communication devices for use on discs, such as compact discs, mini discs, DVDs, and similar devices. Discs may be constructed out of metalized portions that allow storage of digital information. For the purposes of the present claims and the following discussion, some of the terms previously used may be used in a slightly different context.

Turning now to FIG. 18, a particular type of disc known as a compact disc 1000 is illustrated with wireless communication device 1010 disposed thereon. Compact disc 1000 may comprise an outer metalized portion 1002 upon which data is stored as is conventional, an inner portion 1006, typically made from a transparent plastic and delimiting a central hole 1008. Non-conductive gap 1004 exists between outer metalized portion 1002 and inner portion 1006.

Wireless communication device 1010, illustrated isolated from compact disc 1000 in FIG. 19, may comprise a first tab 1012, a second tab 1014, and a wireless communication chip 1016. Wireless communication device 1010 may be either active or passive as described with reference to U.S. Pat. Nos. 5,347,280 (previously incorporated) and 5,585,953, the latter of which is expressly incorporated by reference.

Tabs 1012, 1014 serve as either a pole antenna or to provide a slot antenna for wireless communication device 1010, as discussed below. Tabs 1012, 1014 are a material constructed out of a conductive material, such as metal, copper, or alumi-

15

num. Tabs **1012**, **1014** may also be in the form of a foil or tape depending on the geometry needs and/or constraints of disc **1000**.

Wireless communication chip **1016** may comprise a device from INTERMEC as used in their Intellitag® labels and those devices from SCS as used in their DL**100** label although other devices are certainly possible, especially in light of the present invention's suitability to both active and passive wireless communication devices **1010**. Wireless communication chip **1016** may comprise a control system **12**, memory **18**, a battery, a sensor **20**, and other conventional components.

First tab **1012** capacitively couples wireless communication chip **1016** to the outer metalized portion **1002** to form a first antenna element. The precise dimensions of the first tab **1012** are dictated in part by the compact disc **1000** and in part by impedance matching considerations, as previously discussed above. However, also note that first tab **1012** may be directly connected to outer metalized portion **1002** to directly connect wireless communication chip **1016** to outer metalized portion **1002**.

Second tab **1014** may be an annulus and is positioned on inner portion **1006** for form a second antenna element. Second tab **1014** substantially covers the annulus; however, second tab **1014** does not cover non-conductive gap **1004**.

Second tab **1014** may include a stub **1018** that extends across gap **1004** as illustrated in FIG. **18**. Wireless communication chip **1016** may likewise be positioned across gap **1004** as illustrated.

Gap **1004** may forms a slot antenna operating at a first frequency for wireless communication device **1010**. Likewise, tabs **1012** and **1014** may form an asymmetric dipole antenna for operation at a second frequency. Exemplary frequencies are 915 MHz and 2.45 GHz. However, the present invention is also applicable to wireless communication chip **1016** only being coupled to one tab forming a monopole antenna operating at a second frequency.

The relative positioning of wireless communication chip **1016** with respect to stub **1018** allows the slot antenna to be formed as an asymmetric slot antenna with first portion **1020** extending from stub **1018** to wireless communication chip **1016** and a second portion **1022** comprising the other arc between stub **1018** and wireless communication chip **1016**.

The size, shape, and placement of stub **1018** is dictated by impedance matching concerns and the desire for second tab **1014** to act as an antenna element at the second frequency. For example, while not shown, it is possible to position stub **1018** opposite wireless communication chip **1016** so that the slot antenna is not an asymmetrical slot antenna, but rather a normal symmetric dipole slot antenna.

In an exemplary embodiment stub **1018** is four (4) mm wide and extends the radius of compact disc **1000**. In this embodiment first tab **1012** may be ten (10) mm wide and extend the radius of compact disc **1000**. An arc of thirty-seven degrees separates stub **1018** from first tab **1012**. While copper foil is specifically contemplated as being a useful conductor for the construction of first tab **1012** and second tab **1014**, other conductive materials such as aluminum are also possible.

Attachment of wireless communication device **1010** to disc **1000** may have a variety of useful applications. For instance, wireless communication device **1010** may provide identification so that disc **1000** cannot be taken from a retail store without authorization and/or having been purchased. Interrogation reader **50** may be placed near exit locations in a retail store that sells discs **1000**, such as a retailer of compact-discs. The flowchart illustrated in FIG. **20** discusses the pro-

16

cess for detecting the unauthorized removal of disc **1000** having wireless communication device **1010** attached.

The process starts (block **1050**), and interrogation reader **50** sends out interrogation signal **56** (block **1052**) to determine if wireless communication device **1010** is in range of signal **56** (decision **1054**). If there is no detected wireless communication device **1010** in the range of interrogation reader **50**, interrogation reader **50** continues to send out interrogation signal **56** (block **1052**). If interrogation reader **50** detects wireless communication device **1010** (decision **1054**), interrogation reader **50** determines if disc **1000** was legally purchased (decision **1056**). If yes, the process start over by interrogation reader **50** sending out interrogation signal **56** for subsequent discs **1000** (block **1052**). If no, interrogation reader **50** causes an alert condition (block **1058**), and the process ends (block **1060**).

One way for interrogation reader to determine if disc **1000** was legally purchased or removed from a location with authorization is to interrogate discs **1000** at exit locations or other desired areas in a store. Interrogation readers **50** may also be located at points of purchase so that interrogation reader **50** can mark memory **18** in wireless communication device **1010** to indicate a legal purchase. Interrogation reader **50**, located around exits or other desired locations of store, may then interrogate memory **18** of wireless communication device **1010** to determine if disc **1000** was previously purchased or authorized for removal.

An alert condition may include an audio and/or visual message or signal. For instance, an audio signal may include a siren, alarm, or the like. Such audio signal may be public, or private whereby only certain personnel, such as security personnel, are alerted of the unauthorized removal of disc **1000** from the retail store. Alert conditions may also include a visual signal, both public and/or private as well.

Wireless communication device **1010** on disc **1000** may also cause an interrogation reader **50** to perform a trigger event in response to identification of disc **1000**. The identification of disc **1000** may be stored in memory **18** of wireless communication device **1010** in the form of a text or other message.

For instance, it may be desirable to display a visual message to a customer as the customer leaves a retail store with a newly purchased disc **1000**. If the customer purchases a disc **1000** that contains an audio recording of a particular artist or musical group, a video display, linked to an interrogation reader **50**, may display the artist or musical group thanking the customer for his purchase as customer leaves the store. Interrogation reader **50** determines the identification of disc **1000**, and causes a trigger event to occur in response thereto. The trigger event may be any type of communication signal, and may be an audio message or combination of video and audio.

The trigger event may also be a coupon issued to the customer for a future purchase. For instance if the customer purchases a disc **1000** containing jazz music style, interrogation reader **50**, through associated with a coupon dispensing station, may issue coupons for other jazz music discs **1000** of the same artist or musical group, or discs **1000** for other jazz artists or musical groups.

FIG. **21** illustrates an interrogation reader **50** that performs a trigger event in response to a disc **1000** identification. The process starts (block **1080**), and interrogation reader **50** sends out interrogation signal **56** (block **1082**). If interrogation reader **50** does not detect a disc **1000** in range of interrogation signal **56** (decision **1084**), interrogation reader **50** continues to send out interrogation signal (block **1082**). If interrogation reader **50** detects disc **1000** (decision **1084**), interrogation

17

reader determines the identification of disc **1000** (block **1086**) and performs the appropriate trigger event in response thereto (block **1088**) before the process ends (block **1090**). The trigger event may be an event that is external to interrogation reader **50**, whereby interrogation reader **50** is coupled to an external device to perform such event. For example, such external device may be a video player that plays when a signal is received from interrogation reader **50**.

It should be appreciated that while compact disc **1000** has been discussed in particular, other types of discs, including, but not limited to mini discs, DVDs, and the like are also equally suitable for use with the present invention. This is especially true in light of the uniformity of inner portion **1006** of a compact disc with comparable inner portions on mini discs and DVDs. Mini discs and DVDs are specifically defined elsewhere in the present application.

Note that the present invention is also well suited for use with a miniature compact disc that is shaped like a business card or in other shapes. Examples of shaped compact discs may be found at <http://www.sculptedcd.com/home1.htm> and in the document entitled "Sculpted CD, CD Business Card, Admission Ticket, CD-R 3" Minis," dated Jan. 4, 2001, incorporated herein by reference in its entirety.

In a non-illustrated embodiment, the wireless communication chip **1016** and the coupling structure of the tabs **1012**, **1014** may be mounted as part of the CD jewel case. The wireless communication chip **1016** may only be interrogated when the compact disc **1000** is inserted into the jewel case and the case is closed bringing the chip **1016** and the tabs **1012**, **1014** into close proximity to the elements that act as the antenna.

Certain modifications and improvements will occur to those skilled in the art upon a reading of the foregoing description. It should be understood that the present invention is not limited to any particular type of wireless communication device, tabs, disc, packaging, or slot arrangement. For the purposes of this application, couple, coupled, or coupling is defined as either directly connecting or reactive coupling. Reactive coupling is defined as either capacitive or inductive coupling. The present invention is intended to cover what is claimed and any equivalents. The specific embodiments used herein are to aid in the understanding of the present invention, and should not be used to limit the scope of the invention in a manner narrower than the claims and their equivalents.

What is claimed is:

1. A disc having a metal region for the storage of data thereon coupled to a wireless communication device, *wherein* the disc comprises an outer metalized portion and the outer metalized portion includes the metal region; **[and]** *wherein* the wireless communication device comprises:
 - a wireless communication chip;
 - a first tab positioned on the outer metalized portion;
 - a second tab spaced from the outer metalized portion by a gap with the wireless communication chip positioned between the first tab and the second tab; and
 - a stub extending from the second tab across the gap; *and* *wherein* the metal region of the disc is used as part of an antenna for the wireless communication device.
2. The disc of claim 1, wherein said disc is a compact disc.
3. The disc of claim 1, wherein said disc is a mini disc.
4. The disc of claim 1, wherein said disc is a DVD.
5. The disc of claim 1, wherein said second tab forms an annulus positioned over an inner portion of the disc.
6. The disc of claim 1, wherein said first tab capacitively couples to said outer metalized portion.

18

7. The disc of claim 1, wherein said first tab directly couples to said outer metalized portion.

8. The disc of claim 1, wherein said wireless communication device includes a memory.

9. The disc of claim 8, wherein said memory is operable to store **[the]** *an* identification of said disc.

10. The disc of claim 8, wherein said memory is operable to store whether or not said disc has been legally purchased.

11. The disc of claim 9, wherein said identification is an artist or musical group name.

12. A method of communicating information related to a disc having a metal region for the storage of data, comprising: positioning a wireless communication device on the disc, wherein the disc comprises an outer metalized portion and the outer metalized portion includes the metal region;

coupling a first tab of the wireless communication device to the outer metalized portion;

positioning a second tab of the wireless communication device on an inner portion of the disc and spaced by a gap from the *outer* metalized **[outer]** portion of the disc;

extending a stub from the second tab across the gap;

coupling the metal region as part of an antenna for the wireless communication device; and

interrogating the disc with an interrogation reader.

13. The method of claim 12, wherein *said* positioning a wireless communication device on the disc comprises coupling **[a]** *said* first tab of the wireless communication device to **[a]** *said* outer metalized **[outer]** portion of the disc.

14. The method of claim 13, wherein *said* positioning a wireless communication device on the disc comprises positioning **[a]** *said* second tab on **[an]** *said* inner portion of the disc and spaced by **[a]** *said* gap from the *outer* metalized **[outer]** portion of the disc.

15. The method of claim 12, wherein said interrogating further comprises reading a memory in said wireless communication device.

16. The method of claim 15, wherein said interrogating further comprises comparing said memory to determine if said disc has been legally purchased.

17. The method of claim 16, wherein said interrogating further comprises identifying said disc.

18. The method of claim 17, wherein said memory contains a name of **[the]** *an* artist or musical group.

19. The method of claim 15, further comprising generating a trigger event in response to said interrogating.

20. The method of claim 19, wherein said trigger event is an alarm.

21. The method of claim 19, wherein said trigger event is an audio alert.

22. The method of claim 19, wherein said trigger event is a visual alert.

23. The method of claim 22, wherein said visual alert comprises a visual message created by **[and]** *an* artist associated with said disc.

24. A method of communicating information related to a disc, comprising:

positioning a wireless communication device on the disc by:

coupling a first tab of the wireless communication device to **[a]** *an* outer metalized **[outer]** portion of the disc; **[and]**

positioning a second tab on an inner portion of the disc and spaced by a gap from the *outer* metalized **[outer]** portion of the disc; **[and]**

19

positioning a wireless communication chip between said first and second tabs such that the gap between said outer metalized portion and said second tab acts as a slot antenna; and

interrogating the disc with an interrogation reader.

25. The method of claim 24, wherein *said* interrogating the disc with an [interrogator] *interrogation reader* comprises interrogating the disc at a frequency such that the first and second tabs act as an antenna for a response.

26. The method of claim 24, wherein *said* positioning a wireless communication chip between said first and second tabs such that the gap between said outer metalized portion and said second tab acts as a slot antenna comprises positioning a stub across the gap to form an asymmetrical slot antenna.

27. A wireless communication device, comprising:

a wireless communication chip;

a first tab coupled to [a] *an outer* metalized [outer] portion of a disc and electrically connected to said wireless communication chip; and

a second tab [adapted to position] *configured to be positioned* on an inner portion of the disc and electrically connected to said wireless communication chip; [and] wherein said second tab [adapted] *is configured* to be spaced from the outer metalized portion so as to form a slot antenna therebetween.

28. The wireless communication device of claim 27, further comprising a stub extending from said second tab across a gap delimited by the outer metalized portion and the second tab.

29. The wireless communication device of claim 27, wherein said wireless communication device is sized to fit on a compact disc.

30. The wireless communication device of claim 27, wherein said wireless communication device [if] *is* sized to fit on a mini disc.

31. The wireless communication device of claim 27, wherein said wireless communication device is sized to fit on a DVD.

32. The wireless communication device of claim 28, wherein said stub is positioned so as to create an asymmetric slot antenna.

33. *A disc having data stored thereon coupled to a wireless communication device, wherein said disc comprises an outer metalized portion and said wireless communication device comprises:*

a wireless communication chip;

a first tab positioned on said outer metalized portion; and a second tab spaced from said outer metalized portion by a gap with said wireless communication chip positioned between said first tab and said second tab across the gap;

wherein said first tab and said second tab are constructed out of a conductive material; and

wherein said gap forms a slot antenna configured to operate at a first frequency and said first and second tabs form a dipole antenna configured to operate at a second frequency.

34. *The disc of claim 33, wherein said wireless communication device further comprises a stub extending from said second tab across said gap.*

35. *The disc of claim 33, wherein said first tab is electrically connected to said wireless communication chip.*

36. *The disc of claim 35, wherein said second tab is electrically connected to said wireless communication chip.*

20

37. *The disc of claim 36, wherein said wireless communication device further comprises a stub extending from said second tab across said gap.*

38. *The disc of claim 33, wherein said disc is selected from the group consisting of a compact disc, a mini disc, and a DVD.*

39. *The disc of claim 33, wherein said second tab forms an annulus positioned over an inner portion of said disc.*

40. *The disc of claim 33, wherein said first tab is capacitively coupled to said outer metalized portion.*

41. *The disc of claim 33, wherein said first tab is directly coupled to said outer metalized portion.*

42. *The disc of claim 33, wherein said wireless communication device further comprises a memory.*

43. *The disc of claim 42, wherein said memory is configured to store an identification of said disc.*

44. *The disc of claim 42, wherein said memory is operable to store whether or not said disc has been legally purchased.*

45. *The disc of claim 43, wherein said identification is an artist or musical group name.*

46. *The disc of claim 34, wherein said wireless communication chip is positioned with respect to the stub to allow said slot antenna to be formed as an asymmetric slot antenna.*

47. *A method of communicating information related to a disc, the method comprising:*

positioning a wireless communication device on said disc by coupling a first tab of said wireless communication device to an outer metalized portion of said disc;

positioning a second tab on an inner portion of said disc and spaced by a gap from the outer metalized portion of said disc, wherein said first and second tabs are constructed out of a conductive material and form a dipole antenna; and

positioning a wireless communication chip between said first and second tabs such that the gap between said outer metalized portion and said second tab acts as a slot antenna that operates at a first frequency, whereas said dipole antenna is configured to operate at a second frequency.

48. *The method of claim 47, wherein said positioning a wireless communication chip between said first and second tabs further comprises positioning a stub across said gap.*

49. *The method of claim 47, further comprising interrogating said disc with an interrogation reader.*

50. *The method of claim 49, wherein said interrogating said disc comprises interrogating said disc at a frequency such that the first and second tabs act as an antenna for a response.*

51. *The method of claim 49, wherein said interrogating said disc comprises reading a memory in said wireless communication device.*

52. *The method of claim 51, wherein said interrogating said disc further comprises determining from information in said memory whether said disc has been legally purchased.*

53. *The method of claim 51, wherein said interrogating said disc further comprises identifying said disc.*

54. *The method of claim 53, wherein said memory contains a name of an artist or musical group.*

55. *The method of claim 49, further comprising generating a trigger event in response to said interrogating said disc.*

56. *The method of claim 55, wherein said trigger event is selected from the group consisting of an alarm, an audio alert, and a visual alert.*

57. *The method of claim 53, further comprising issuing a coupon to a customer in response to identification of said disc.*

21

58. The method of claim 48, wherein said stub is positioned across said gap to form an asymmetric slot antenna.

59. A wireless communication device comprising:
a wireless communication chip;

a first tab electrically connected to said wireless communication chip, wherein said first tab is configured to be coupled to an outer metalized portion of a disc; and
a second tab electrically connected to said wireless communication chip, wherein said second tab is configured to be positioned on an inner portion of said disc;

wherein the second tab is further configured to be spaced by a gap from said outer metalized portion to form a slot antenna therebetween that operates at a first frequency; and

wherein said first and second tabs form a dipole antenna configured to operate at a second frequency.

60. The wireless communication device of claim 59, wherein said wireless communication chip is positioned across said gap.

61. The wireless communication device of claim 59, further comprising a stub extending from said second tab across said gap.

62. The wireless communication device of claim 59, wherein said wireless communication device is sized to fit on said disc, and wherein said disc is selected from the group consisting of a compact disc, a mini disc, and a DVD.

63. The wireless communication device of claim 61, wherein said stub is positioned to create an asymmetric slot antenna.

22

64. A method of communicating information related to a disc, the method comprising:

positioning a wireless communication device on said disc by coupling a first tab of said wireless communication device to an outer metalized portion of said disc;

positioning a second tab of said wireless communication device on an inner portion of said disc, wherein said second tab is spaced by a gap from said outer metalized portion of said disc; and

extending a stub from said second tab across said gap.

65. The method of claim 64, further comprising interrogating said disc with an interrogation reader.

66. A method of communicating information related to a disc, the method comprising:

positioning a wireless communication device on said disc by coupling a first tab of said wireless communication device to an outer metalized portion of said disc;

positioning a second tab on an inner portion of said disc, wherein said second tab is spaced by a gap from said outer metalized portion of said disc; and

positioning a wireless communication chip between said first and second tabs such that said gap between said outer metalized portion and said second tab acts as a slot antenna.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : RE43,683 E
APPLICATION NO. : 11/584478
DATED : September 25, 2012
INVENTOR(S) : King et al.

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page, item (56), under “FOREIGN PATENT DOCUMENTS”, in Column 2, Line 1,
delete “DE 3247425 A1 12/1982”.

On Page 2, item (56), under “FOREIGN PATENT DOCUMENTS”, in Column 2, Line 14,
delete “GB 2335081 A 9/1999”.

On Page 2, item (56), under “FOREIGN PATENT DOCUMENTS”, in Column 2, Line 15,
delete “JP 03196704 8/1991”.

On Page 2, item (56), under “FOREIGN PATENT DOCUMENTS”, in Column 2, Line 19,
delete “JP 09330388 A2 12/1997”.

On Page 2, item (56), under “FOREIGN PATENT DOCUMENTS”, in Column 2, Line 22,
delete “WO WO94/14208 6/1994”.

On Page 2, item (56), under “FOREIGN PATENT DOCUMENTS”, in Column 2, Line 24,
delete “WO WO97/24689 7/1997”.

On Page 2, item (56), under “FOREIGN PATENT DOCUMENTS”, in Column 2, Line 30,
delete “WO WO00/23994 4/2000”.

On Page 3, item (56), under “OTHER PUBLICATIONS”, in Column 1, Line 4, delete
“Techologies” and insert -- Technologies --, therefor.

On Page 3, item (56), under “OTHER PUBLICATIONS”, in Column 2, Line 7, delete
“ntermec” and insert -- Intermec --, therefor.

In Column 9, Line 63, delete “for” and insert -- form --, therefor.

Signed and Sealed this
Fifth Day of March, 2013



Teresa Stanek Rea
Acting Director of the United States Patent and Trademark Office

CERTIFICATE OF CORRECTION (continued)

Page 2 of 2

U.S. Pat. No. RE43,683 E

In Column 10, Line 34, delete “for” and insert -- form --, therefor.

In Column 12, Line 67, delete “10A,” and insert -- 100A, --, therefor.

In Column 13, Line 23, delete “10A,” and insert -- 100A, --, therefor.