



US00RE43772E

(19) **United States**
(12) **Reissued Patent**
Mariman et al.

(10) **Patent Number:** **US RE43,772 E**
(45) **Date of Reissued Patent:** **Oct. 30, 2012**

(54) **SEED TUBE FOR AN AGRICULTURAL SEEDING MACHINE**

(75) Inventors: **Nathan A. Mariman**, Geneseo, IL (US);
Mark S. Sommer, East Moline, IL (US);
Donna R. Sommer, legal representative,
Cedar Falls, IA (US); **James R. Peterson**,
Annawan, IL (US); **Donald K. Landphair**,
Bettendorf, IA (US); **William G. Bultinck**,
Mesa, AZ (US)

(73) Assignee: **Deere & Company**, East Moline, IL (US)

(21) Appl. No.: **12/984,470**

(22) Filed: **Jan. 4, 2011**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,472,660**
Issued: **Jan. 6, 2009**
Appl. No.: **11/250,655**
Filed: **Oct. 13, 2005**

(51) **Int. Cl.**
A01C 7/00 (2006.01)
A01C 9/00 (2006.01)

(52) **U.S. Cl.** **111/174**; 111/903

(58) **Field of Classification Search** 111/170,
111/174, 200, 903, 904

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,044,103 A 11/1912 Swan
3,804,036 A 4/1974 Seifert, Jr.
3,974,377 A 8/1976 Steffen

4,157,468 A 6/1979 Primiano
4,166,948 A 9/1979 Steffen
4,555,624 A 11/1985 Steffen
4,627,840 A 12/1986 Cuadra et al.
4,635,215 A 1/1987 Friend
4,915,258 A 4/1990 Olson
5,533,458 A 7/1996 Bergland et al.
5,650,609 A 7/1997 Mertins et al.
5,883,383 A 3/1999 Dragne
5,931,105 A 8/1999 Luxon
5,967,866 A 10/1999 Willows et al.
6,078,635 A 6/2000 DuBois
6,093,926 A 7/2000 Mertins et al.
6,158,363 A 12/2000 Memory et al.
6,296,425 B1 10/2001 Memory et al.
6,332,413 B1 12/2001 Stufflebeanm et al.
6,373,057 B1 4/2002 Penfold
6,872,933 B2 3/2005 Wirthlin
2001/0022342 A1 9/2001 Wirthlin

(Continued)

FOREIGN PATENT DOCUMENTS

GB 2223048 A 3/1990

OTHER PUBLICATIONS

Picture of a seed tube, subject of U.S. Patent No. 5,533,458, date unknown (see Transmittal Letter), 1 page.

(Continued)



Primary Examiner — Christopher J. Novosad

(74) *Attorney, Agent, or Firm* — Fitch, Even, Tabin & Flannery, LLP

(57) **ABSTRACT**

A seed tube for an agricultural seeding machine includes a side wall having at least a portion thereof formed from a transparent material. A sensor includes a transmitter which is positioned adjacent an outside of the side wall, and operates through the transparent material.

37 Claims, 3 Drawing Sheets



U.S. PATENT DOCUMENTS

2005/0139756 A1 6/2005 Brickey et al.

OTHER PUBLICATIONS

Complaint and Jury Demand against Great Plains Manufacturing Incorporated dated May 12, 2010 against Great Plains Manufacturing Incorporated and Exhibit A—*Deere & Company v. Great Plains Manufacturing Incorporated*, Civil No. 3:10-CV-00059.

Defendant's Answer to Amended Complaint, Counterclaim dated Oct. 12, 2010—*Deere & Company v. Great Plains Manufacturing Incorporated*, Civil No. 3:10-CV-00059.

Deere's Answer to 14 Counterclaim dated Nov. 5, 2010—*Deere & Company v. Great Plains Manufacturing Incorporated*, Civil No. 3:10-CV-00059.

Joint Motion to Dismiss dated Jul. 1, 2011—*Deere & Company v. Great Plains Manufacturing Incorporated*, Civil No. 3:10-CV-00059.

Order dismissing action due to settlement dated Jul. 5, 2011—*Deere & Company v. Great Plains Manufacturing Incorporated*, Civil No. 3:10-CV-00059.

Report on the filing or determination of an action regarding patent No. 7,472,660 B2 dated Jul. 5, 2011—*Deere & Company v. Great Plains Manufacturing Incorporated*, Civil No. 3:10-CV-00059.

Court's Docket—*Deere & Company v. Great Plains Manufacturing Incorporated*, Civil No. 3:10-CV-00059.




Fig. 3





Fig. 2




Fig. 4

1

SEED TUBE FOR AN AGRICULTURAL SEEDING MACHINE

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

FIELD OF THE INVENTION

The present invention relates to agricultural seeding machines, and, more particularly, to seed tubes for such seeding machines.

BACKGROUND OF THE INVENTION

An agricultural seeding machine such as a row crop planter or grain drill places seeds at a desired depth within a plurality of parallel seed trenches formed in soil. In the case of a row crop planter, a plurality of row crop units are typically ground driven using wheels, shafts, sprockets, transfer cases, chains and the like. Each row crop unit has a frame which is moveably coupled with a tool bar. The frame may carry a main seed hopper, herbicide hopper and insecticide hopper. If a granular herbicide and insecticide are used, the metering mechanisms associated with dispensing the granular product into the seed trench are relatively simple. On the other hand, the mechanisms necessary to properly meter the seeds, dispense the seeds at a predetermined rate and place the seeds at predetermined relative locations within the seed trench are relatively complicated.

The mechanisms associated with metering and placing the seeds generally can be divided into a seed metering system and a seed placement system which are in communication with each other. The seed metering system, also referred to herein as a seed meter, receives the seeds in a bulk manner from the seed hopper carried by the frame. Different types of seed meters may be used such as seed plates, finger plates, and seed discs. In the case of a seed disc metering system, a seed disc is formed with a plurality of seed cells spaced about the periphery thereof. Seeds are moved into the seed cells, with one or more seeds in each seed cell depending upon the size and configuration of the seed cell. A vacuum or positive pressure air may be used in conjunction with the seed disc to assist in movement of the seeds into the seed cells. The seeds are singulated and discharged at a predetermined rate to the seed placement system.

The seed placement system may be categorized as a gravity drop system or a power drop system. A seed placement system of the power drop variety generally can be classified as a seed conveyor belt drop, rotary valve drop, chain drop or air drop. Such power drop systems are known and thus not described further.

In the case of a gravity drop system, a seed tube has an inlet end which is positioned below the seed metering system. The singulated seeds from the seed metering system merely drop into the seed tube and fall via gravitational force from a discharge end thereof into the seed trench. The seed tube may be curved in a rearward manner to assist in directing seed into the seed trench. The rearward curvature also assists in reducing bouncing of the seeds back and forth within the tube as it falls therethrough into the seed trench. Further, the rearward curvature reduces bouncing of the seed as it strikes the bottom of the seed trench.

To ensure that the planting unit is operating correctly, the seed tube may be provided with a seed sensor. A light is

2

projected from a light source across the hollow interior of the seed tube to a light receiver located in an aperture of the front wall. When a seed passes between the light source and the light receiver, the seed interrupts the light beam and the seed is detected.

The light source and light receiver are designed to extend into the apertures and be substantially even with the interior surfaces of the front and rear walls. However, sometimes the sensor may extend past the interior surface of the front wall. In this situation, the seed may impact the top edge of the sensor, possibly damaging the seed and deflecting the seed trajectory into the seed trench.

What is needed in the art is a seed tube with a sensor which operates effectively, yet does not interfere with seed drop through the seed tube.

SUMMARY OF THE INVENTION

The present invention provides a seed tube having side walls which are at least in part transparent, and a sensor having a transmitter which is positioned on the outside of the seed tube and operates through the transparent side wall.

The invention comprises, in one form thereof, a seed tube for an agricultural seeding machine which includes a side wall having at least a portion thereof formed from a transparent material. A sensor includes a transmitter which is positioned adjacent an outside of the side wall, and operates through the transparent material.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of a portion of a seeding machine including an embodiment of a seed tube of the present invention;

FIG. 2 is a perspective view of the seed tube shown in FIG. 1;

FIG. 3 is a side view of the seed tube shown in FIGS. 1 and 2; and

FIG. 4 is a rear view of the seed tube shown in FIGS. 1-3.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings, and more particularly to FIG. 1, there is shown an embodiment of a seeding machine 10 of the present invention. In the embodiment shown, seeding machine 10 is in the form of a row crop planter but may also be in the form of a grain drill, etc. FIG. 1 illustrates a single row crop unit of a multi-row planter, with each row crop unit being substantially identical and connected to a common tool bar 12 using U-bolts 14. Only a single row crop unit is shown for simplicity sake.

Each row crop unit includes a multi-part frame 16 which is attached to tool bar 12 by parallel linkage 18. Tool bar 12 is coupled to a traction unit (not shown), such as an agricultural tractor. For example, tool bar 12 may be coupled to an agricultural tractor using a 3-point hitch assembly. Tool bar 12 may be coupled with transport wheel assemblies, marker arms, etc. which may be of conventional design and not shown for simplicity sake. The transport wheels, in known manner, may provide ground drive to the row crop unit through the use of shafts, chains, sprockets, transfer cases, etc.

Frame 16 carries a double disc furrow opener 20 for forming a seed trench in soil, and a pair of gauge wheels 22 positioned adjacent to the outside of each respective disc of double disc furrow opener 20. Each gauge wheel 26 may be vertically adjusted to adjust the depth of the trench which is

cut into the soil using double disc furrow opener 20. Frame 16 also carries a pair of closing wheels 24 positioned generally in line with double disc furrow opener 20.

Frame 16 also carries a seed hopper 26 and chemical hopper 28. A chemical meter 29 directs chemicals from chemical hopper 28 to a chemical applicator 30. The particular planting unit shown in FIG. 1 is in the form of a no-till planter having coultured no-till opening disks 32 for management of debris on the ground.

Seed meter 34 is positioned in communication with and receives seed from seed hopper 26. Seed meter 34 singulates the seeds and provides the seeds at a predetermined rate to seed tube 36. The seed falls through seed tube 36 and is deposited into the planting furrow formed by furrow opener 20.

Referring now to FIGS. 2-4, seed tube 36 will be described in greater detail. Seed tube 36 includes an open inlet end 38, an open outlet end 40, and four side walls 42, 44, 46 and 48 defining a hollow interior 50. Side wall 42 defines a front wall of seed tube 36 and side wall 44 defines a rear wall of seed tube 36 (with respect to the direction of travel of seeding machine 10). Front wall 42 and rear wall 44 are each curved in the rearward direction to deposit the seed in the seed trench while reducing the tendency of the seed to bounce out of the seed trench.

Approximately midway along the length of front wall 42 is a sensor pocket 52 which is sized and shaped to receive a sensor 54 forming half of a sensor pair which cooperate together to sense individual seeds passing through seed tube 36. In the embodiment shown, the sensor includes a transmitter 54 and receiver 56. Transmitter 54 is in the form of a light source and receiver 56 is in the form of a light receiver. More particularly, light source 54 is in the form of a light emitting diode (LED). LED 54 and light receiver 56 are connected to a seed population monitor in the tractor cab by suitable electrical leads 57. Sensors including LED's and light receivers for use in seed tubes are known and thus not described further.

Sensor pocket 52 is in the form of a circular upstanding wall extending from front wall 42. This circular shape matches with the external shape of LED 54, and allows a seal or adhesive (not specifically shown) to be used for hermetic sealing between LED 54 and front wall 42. Of course, the shape of sensor pocket 52 can vary depending upon the particular sensor utilized.

Surrounding sensor pocket 52 is a sensor mount 58 which provides mechanical structure for attachment with and mounting of LED 54. Again, the particular configuration of sensor mount 58 can vary depending upon the application.

Approximately midway along the length of rear wall 44 is a sensor pocket 60 which is sized and shaped to receive light receiver 56. In contrast with sensor pocket 52 described above carrying LED 54, sensor pocket 60 is merely in the form of a hole extending through rear wall 44 (although it could include an upstanding wall if desirable). Because the seed falls via gravity and rides along front wall 42, light receiver 56 can extend through rear wall 44, for reasons that will become more apparent hereinafter. Light receiver 56 and LED 54 are held in place using a tie strap (not shown) or any other suitable fastening technique.

According to an aspect of the present invention, LED 54 does not extend through front wall 42 to be exposed within hollow interior 50 of seed tube 36. Rather, the portion of front wall 42 within sensor pocket 52 is substantially transparent to light emitted from LED 54. In the embodiment shown, the transparent material within sensor pocket 52 is of the same type of material as the remainder of seed tube 36. For example, the material may be a plastic material with a tinting

agent that allows the particular frequency light from LED 54 to pass therethrough, while at the same time substantially preventing ambient light at a different frequency from passing therethrough. In this manner, the area within sensor pocket 52 acts as a "window" allowing light from LED 54 to pass therethrough, while the remainder of seed tube 36 blocks ambient light from passing therethrough. An example of such a material is polycarbonate, smoked using approximately 1 to 5% colorant. Ambient light can interfere with operation of sensor 54, 56 and therefore it is desirable to block ambient light to a reasonable extent. To further assist in blocking ambient light, the outside surface of seed tube 36 in the area outside of sensor pocket 52 can be formed with a textured surface, shown on a portion of seed tube 36 and represented by reference numbers 62 and 64 in FIGS. 2 and 66 in FIG. 4.

By forming seed tube 36 from the same selected material which is both transparent to sensor 54, 56 but opaque to ambient light, the inside surface of seed tube 36 adjacent LED 54 is a continuous, non-disjoint substantially smooth surface which does not present any surface or edge against which the seeds may impinge and be damaged or deflected. This ensures that undamaged seeds are properly placed within the seed trench.

In another embodiment of the present invention, the portion of seed tube 36 lying at the bottom of sensor pocket 52 can be formed from a material which is different than the material from which the remainder of seed tube 36 is formed. For example, the portion at the bottom of seed tube 36 can be formed from a clear plastic material or glass which does not interfere with the operation of sensor 54, 56. The separate material forming the window at the bottom of sensor pocket 52 is positioned such that the inside surface of hollow interior 50 is continuous and non-disjoint. With this embodiment, except in a cross-sectional view through sensor pocket 52 showing the different materials, seed tube 36 otherwise appears as shown in FIGS. 2-4.

In the embodiment shown and described above, seed tube 36 is formed from a tinted plastic material which is opaque to ambient light and transparent to sensor 54, 56. It may also be possible to form the remainder of seed tube 36 outside the area of sensor pocket 52 with a material which is opaque to both ambient light and sensor 54, 56 in the case of a separate transparent window. Further, it may also be possible to form the entire seed tube 36 from a material transparent to sensor 54, 56 (such as clear plastic) and then coat the area of seed tube 36 outside the area of sensor pocket 52.

Moreover, in the embodiment shown, only LED 54 of sensor 54, 56 is positioned adjacent a transparent window of seed tube 36, and light receiver 56 is positioned within a hole formed in rear wall 44. However, it is also possible to position each of LED 54 and light receiver 56 adjacent a transparent window.

Having described the preferred embodiment, it will become apparent that various modifications can be made without departing from the scope of the invention as defined in the accompanying claims.

The invention claimed is:

1. A seed tube, through which individual seeds pass, for an agricultural seeding machine, [said] the seed tube comprising:

[a side] a front wall and a rear wall opposite the front wall, the front wall and the rear wall defining a hollow interior therebetween, the front wall configured to face a direction of travel of the seed tube, the front wall having a continuous non-disjoint substantially smooth surface exposed to [said] the seeds and [including] at least a

5

portion [thereof comprised of] *of the front wall being formed from a substantially transparent material; [and] a sensor [including a transmitter, said transmitter positioned adjacent an outside of said side wall, and operating through said transparent material] including a first half sensor and a second half sensor, the sensor configured to operate through the transparent material to detect passage of individual seeds through said seed tube; and*
a mount having a structure which extends from an exterior surface of the front wall with the transparent material and configured to receive and hold the first half sensor on the exterior surface, and the rear wall including a second half mount configured to hold the second half sensor.

2. The seed tube of claim 1, wherein said transparent material is opaque to ambient light and transparent to [said transmitter] *the sensor.*

3. The seed tube of claim 1, wherein [said side wall includes a window comprised of said transparent material,] *the transparent material forms a window in the front wall and a remainder of [said side wall] the front wall being opaque to ambient light.*

4. The seed tube of claim 3, wherein said remainder of [said side] *the front wall comprises one of an opaque material, a transparent material with opaque tinting, and a transparent material with an opaque coating.*

[5. The seed tube of claim 1, wherein said side wall includes a sensor mount.]

6. The seed tube of claim [5] 1, wherein [said sensor mount] *the structure of the mount includes a sensor pocket.*

7. The seed tube of claim 6, further including one of a seal and an adhesive between [said] *the first half sensor and said sensor pocket.*

8. The seed tube of claim 1, wherein said transparent material comprises a substantially clear plastic material.

9. The seed tube of claim 1, wherein said transparent material comprises one of a plastic material and glass.

10. The seed tube of claim 1, wherein [said transmitter] *one of the first half sensor or second half sensor comprises a light source.*

11. The seed tube of claim 10, wherein said light source comprises an LED.

[12. The seed tube of claim 1, wherein said side wall comprises a front wall.]

13. The seed tube of claim 1, wherein [said side] *the front wall includes an outer surface which is textured in an area away from [said] the first half sensor.*

14. A seed tube, through which individual seeds pass, for an agricultural seeding machine, said seed tube comprising a front wall and a rear wall defining a hollow interior therebetween, at least one of said front wall and said rear wall having a continuous non-disjoint substantially smooth surface exposed to said seeds and including at least a portion thereof comprised of a substantially transparent material, and a sensor mount positioned in association with said transparent material on a side opposite said hollow interior to detect passage of individual seeds through said tube.

15. The seed tube of claim 14, wherein at least one of said front wall and said rear wall include a window comprised of said transparent material, a remainder of said front wall and said rear wall being configured opaque.

16. The seed tube of claim 15, wherein said remainder of said front wall and said rear wall comprises one of an opaque material, a transparent material with opaque tinting, and a transparent material with an opaque coating.

6

17. The seed tube of claim 14, wherein at least one of said front wall and said rear wall includes a sensor mount.

18. The seed tube of claim 14, wherein each of said front wall and said rear wall has an outer surface which is textured in an area away from each said sensor.

19. An agricultural seeding machine, comprising:

a seed meter; and

a seed tube positioned to receive individual seeds from [said] *the seed meter for passage through [said] the seed tube, [said] the seed tube including:*

a front side wall having an exterior and an interior surface, the front side wall interior surface having a continuous non-disjoint and substantially smooth surface exposed to [said] the seeds passing through the tube, a portion of the interior surface of the front side wall being concave, the exterior surface of the front side wall being configured to face a direction of travel of the seed tube, and [including] at least a portion [thereof] of the front side wall comprised of a substantially transparent material; and, the portion of the front side wall having substantially transparent material including a first half mount having a structure extending from the exterior surface; a rear wall opposite the front side wall, the rear wall having an exterior and interior surface and a second half mount, the front side wall and the rear wall defining a hollow interior through which the seeds pass, a portion of the interior surface of the rear wall being convex, the interior surfaces of the front side wall and the rear wall curved in a rearward direction; and

a sensor pair which includes a first half sensor and a second half sensor, the first half sensor mounted into the structure of the first half mount adjacent the transparent material which forms a part of the front side wall, the sensor pair configured to operate through the transparent material and to detect the passage of individual seeds through the interior of the seed tube.

[a sensor including a transmitter, said transmitter positioned adjacent an outside of said side wall, and operating through said transparent material to detect passage of individual seeds through said seed tube.]

20. The agricultural seeding machine of claim 19, wherein [said side wall includes] *the transparent material forms a window [comprised of said transparent material,] in the front side wall and a remainder of [said side] the front side wall being configured opaque.*

21. The agricultural seeding machine of claim 20, wherein said remainder of [said side] *the side front wall comprises one of an opaque material, a transparent material with opaque tinting, and a transparent material with an opaque coating.*

[22. The agricultural seeding machine of claim 19, wherein said side wall includes a sensor mount.]

23. The agricultural seeding machine of claim [22] 19, wherein [said sensor] *the structure of the first half mount includes a sensor pocket.*

24. The agricultural seeding machine of claim 23, further including one of a seal and an adhesive between [said] *the first half sensor and said sensor pocket.*

25. The agricultural seeding machine of claim 19, wherein [said side wall has an outer surface which] *the outer surface of the front side wall is textured in an area away from [said] the first half sensor.*

26. *The seed tube of claim 1, wherein the second half mount is a hole through the rear wall configured to receive and hold the second half sensor.*

27. The agricultural seeding machine of claim 19, wherein the second half mount on the rear wall is a hole through the rear wall configured to receive and hold the second half sensor.

28. A seed tube, through which individual seeds pass, for an agricultural seeding machine, the seed tube comprising:

a front wall and a rear wall opposite the front wall, the front wall and the rear wall defining a hollow interior through which the seeds pass, the front wall configured to face a direction of travel of the seed tube, the front wall and the rear wall curved in the rearward direction, the front wall having an interior surface a portion of which is concave and the front wall having an exterior surface a portion of which is convex, the rear wall having an exterior surface a portion of which is concave and an interior surface a portion of which is convex, the interior surface of the front wall exposed to the seeds passing through the hollow tube being continuous, non-disjoint and substantially smooth, the front wall including at least a portion thereof formed from a substantially transparent material, and a mount having a structure which extends from the outer surface of the front wall which includes the transparent material; and

a sensor pair having a first sensor half and a second sensor half, the sensor pair configured to detect passage of individual seeds through the interior of the seed tube, the structure of the mount configured to receive and hold the first sensor half adjacent to the substantially transparent material and the outside convex exterior surface of the front wall, and the rear wall including a hole through the rear wall, the hole configured to receive and hold the second sensor half.

29. The seed tube of claim 28, wherein the structure of the mount includes a sensor pocket.

30. The seed tube of claim 29, further including one of a seal and an adhesive between the first half sensor and said sensor pocket.

31. A seed tube, through which individual seeds pass, for an agricultural seeding machine, the seed tube comprising:

a front side wall and a rear side wall opposite the front side wall and two opposing side walls extending between the front and rear walls, the side walls defining a hollow interior through which the seeds pass, the front side wall configured to face a direction of travel of the seed tube, the front side wall and the rear side wall curved in the rearward direction, the front wall having an interior surface a portion of which is concave, and the front wall having an exterior surface a portion of which is convex, the rear wall having an exterior surface a portion of which is concave and an interior surface, the interior surface of the front wall exposed to the seeds passing through the hollow tube being continuous, non-disjoint

and substantially smooth, the opposing side walls including at least a portion thereof formed from a substantially transparent material, and a mount having a structure which extends from the outer surface of one side wall which includes the transparent material; and a sensor pair having a first sensor half and a second sensor half, the sensor pair configured to detect passage of individual seeds through the interior of the seed tube, the structure of the mount configured to associate with the first sensor half adjacent to the substantially transparent material and the outside exterior surface of one side wall, and one side wall including a hole, the hole configured to receive and hold the second sensor half.

32. A seed tube, through which individual seeds pass, for an agricultural seeding machine, the seed tube comprising:

a front wall and a rear wall opposite the front wall, the front wall and the rear wall defining a hollow interior therebetween, the front wall configured to face a direction of travel of the seed tube, the front wall having a continuous non-disjoint substantially smooth surface exposed to the seeds and at least a portion of the front wall being formed from a substantially transparent material;

a sensor including a first half sensor and a second half sensor, the sensor configured to operate through the transparent material to detect passage of individual seeds through said seed tube; and

a mount having a structure which extends from an exterior surface of the front wall with the transparent material and configured to engage the first half sensor on the exterior surface, and the rear wall including a second half mount configured to hold the second half sensor.

33. The seed tube of claim 32, wherein said transparent material is opaque to ambient light and transparent to the sensor.

34. The seed tube of claim 32, wherein the transparent material forms a window in the front wall and a remainder of the front wall being opaque to ambient light.

35. The seed tube of claim 32, wherein the structure of the mount includes a sensor pocket.

36. The seed tube of claim 35, further including one of a seal and an adhesive between the first half sensor and the sensor pocket.

37. The seed tube of claim 32, wherein said transparent material comprises a substantially clear plastic material.

38. The seed tube of claim 32, wherein said transparent material comprises one of a plastic material and glass.

39. The seed tube of claim 32, wherein one of the first half sensor or second half sensor comprises a light source.

40. The seed tube of claim 39, wherein said light source comprises an LED.

* * * * *