

US00RE43847E

(19) **United States**
(12) **Reissued Patent**
Le Gette et al.

(10) **Patent Number:** **US RE43,847 E**
(45) **Date of Reissued Patent:** **Dec. 11, 2012**

(54) **COLLAPSIBLE SUPPORT AND METHODS OF USING THE SAME**

(75) Inventors: **Brian Edward Le Gette**, Baltimore, MD (US); **David Reeb**, Columbia, MD (US); **Alan Tipp**, Bennington, NE (US); **Justin Saul Werner**, Millersville, MD (US); **Inna Alesina**, Owings Mills, MD (US)

(73) Assignee: **Kelsyus, LLC**, Virginia Beach, VA (US)

(21) Appl. No.: **12/417,425**

(22) Filed: **Apr. 2, 2009**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,198,324**
Issued: **Apr. 3, 2007**
Appl. No.: **11/199,136**
Filed: **Aug. 9, 2005**

U.S. Applications:

(63) Continuation of application No. 10/367,796, filed on Feb. 19, 2003, now Pat. No. 6,926,355, which is a continuation-in-part of application No. 10/233,784, filed on Sep. 4, 2002, now Pat. No. 6,820,927, which is a continuation-in-part of application No. PCT/US02/06695, filed on Mar. 5, 2002, which is a continuation-in-part of application No. 09/797,948, filed on Mar. 5, 2001, now Pat. No. 6,698,827.

(51) **Int. Cl.**
A47C 4/30 (2006.01)
A47C 7/66 (2006.01)

(52) **U.S. Cl.** **297/16.2; 297/17; 297/45; 297/129; 297/184.1; 297/184.11; 297/184.15**

(58) **Field of Classification Search** 297/184.1, 297/184.11, 184.15, 220, 397
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

180,610 A	8/1876	Lungren
244,216 A	7/1881	Fenby
291,062 A	1/1884	Latour
900,572 A	10/1908	Morton
1,035,823 A	8/1912	Hay
1,256,902 A	2/1918	Howe

(Continued)

FOREIGN PATENT DOCUMENTS

AU 15170/92 A 12/1993

(Continued)

OTHER PUBLICATIONS

Shakespeare Deluxe High Back Lounge Chair, Outdoor World of California [online], 1 page. Retrieved from the internet: Jun. 1, 2002, <URL: <http://www.outdoorworldca.com/products/specs/dlxhilou.htm>>.



(Continued)

Primary Examiner — Rodney B White
(74) *Attorney, Agent, or Firm* — Cooley LLP

(57) **ABSTRACT**

A support including a frame having a tension member coupled to the frame is disclosed. The frame has a collapsed configuration and an expanded configuration. The tension member is disposable in a first position to provide support for an arm of a user and a second position to be carried on a shoulder of the user.

46 Claims, 64 Drawing Sheets



US RE43,847 E

U.S. PATENT DOCUMENTS							
1,341,225	A	5/1920	Clough	4,836,601	A	6/1989	Cone
1,429,043	A	9/1922	Martin	4,836,938	A	6/1989	Kobasic
1,443,921	A	1/1923	Mackenzie	4,865,381	A	9/1989	Van Rogue
1,605,679	A	11/1926	McGrail	4,885,812	A	12/1989	Lindner
1,639,074	A	8/1927	Blackwood	4,889,383	A	12/1989	Jones
1,763,455	A	6/1930	De Bruijn	4,890,882	A	1/1990	Harrington
1,789,090	A	1/1931	Wawrunek	4,924,896	A	5/1990	Carter
1,979,278	A	11/1934	McMurtry	4,925,239	A	5/1990	Powers
2,001,252	A	5/1935	Johnson	D310,605	S	9/1990	Kwon
2,137,427	A	11/1938	Thomson	4,971,089	A	11/1990	Braman
2,166,832	A	7/1939	Wenker	5,000,210	A	3/1991	Worthington, Jr.
2,243,984	A	6/1941	Singewald	5,016,792	A	5/1991	Jay
2,429,763	A	10/1947	Lindabury	5,022,420	A	6/1991	Brim
2,473,090	A	6/1949	Becker	5,042,874	A	8/1991	Williams
2,490,367	A	12/1949	Maddocks	5,054,849	A	10/1991	Hoff
2,545,968	A	3/1951	Newstead	5,080,432	A	1/1992	Connell
2,561,886	A	7/1951	Rikelman	5,096,257	A	3/1992	Clark
2,658,562	A	11/1953	Androsiglio	5,139,308	A	8/1992	Ziman
2,690,792	A	10/1954	Moss	5,150,945	A	9/1992	Aupperlee et al.
2,691,410	A	10/1954	Boucher	5,154,473	A	10/1992	Joranco
2,729,276	A	1/1956	Volney	5,203,363	A	4/1993	Kidwell et al.
2,747,653	A	5/1956	Obradovich	5,205,308	A	4/1993	Kendall et al.
2,819,776	A	1/1958	Balsam	5,205,610	A	4/1993	Reninger
2,915,154	A	12/1959	Holder	5,209,381	A	5/1993	Jay
2,926,724	A	3/1960	Rittenberg	5,240,020	A	8/1993	Byers
2,973,888	A	3/1961	Beardsley	5,244,250	A	9/1993	Nordmeyer
3,034,523	A	5/1962	De Shano	5,289,958	A	3/1994	Jay
3,092,224	A	6/1963	O'Neil	5,299,337	A	4/1994	Venza
3,124,387	A	3/1964	MacLaren	5,320,405	A	6/1994	Foster et al.
3,179,465	A	4/1965	Roberts	5,332,283	A	7/1994	Gray
3,214,217	A	10/1965	Jente	5,362,130	A	11/1994	Hoffman
3,243,230	A	3/1966	Otto	5,385,390	A	1/1995	Freeman et al.
3,307,758	A	3/1967	Platt	5,409,291	A	4/1995	Lamb et al.
3,309,134	A	3/1967	Robert	5,429,413	A	7/1995	Levy et al.
3,404,915	A	10/1968	De Souza	5,441,067	A	8/1995	James et al. 297/184.15 X
3,580,633	A	5/1971	Du Priest	5,449,014	A	9/1995	Yan-ho
3,662,932	A	5/1972	Kerschner	5,499,760	A	3/1996	Pielocik
3,838,883	A	10/1974	Machen	5,499,857	A	3/1996	Lynch, Jr.
3,879,086	A	4/1975	Mocerri	5,527,088	A	6/1996	MacLean
3,909,061	A	9/1975	Johnson	5,536,064	A	7/1996	MacLean
3,918,109	A	11/1975	Barraclough	5,544,793	A	8/1996	Harrop
3,931,918	A	1/1976	Smith et al.	5,547,246	A	8/1996	Lambert
3,947,903	A	4/1976	Menke	5,551,110	A	9/1996	Armstrong et al.
4,014,591	A	3/1977	Gittings	5,579,797	A	12/1996	Rogers
4,030,748	A	* 6/1977	Brock 297/184.1	5,582,458	A	12/1996	Wildt
4,047,753	A	9/1977	Uchida	5,588,696	A	12/1996	Jay et al.
4,063,318	A	12/1977	Nicholson	5,593,205	A	1/1997	Vanderminden, Sr. et al.
4,082,102	A	* 4/1978	Heuer 297/184.1 X	5,628,437	A	5/1997	Kober
4,148,520	A	4/1979	Miller	D380,306	S	7/1997	Lin
4,201,416	A	* 5/1980	Vanderminden 297/184.15	D382,126	S	8/1997	Lee
4,230,363	A	* 10/1980	Borichevsky 297/184.15	D382,414	S	8/1997	Lee
4,245,849	A	1/1981	Thiboutot	5,695,100	A	12/1997	O'Brien
4,258,951	A	* 3/1981	Groom 297/16.2	5,718,473	A	2/1998	Lynch, Jr.
4,295,481	A	10/1981	Gee	5,797,650	A	8/1998	Gonzalez et al.
4,300,707	A	11/1981	Kjaer	5,819,999	A	10/1998	Tennant
4,359,244	A	11/1982	Koehm	5,829,832	A	* 11/1998	Molee et al. 297/397
4,487,345	A	12/1984	Pierce et al.	5,833,310	A	11/1998	Labelle
4,530,451	A	7/1985	Hamilton	5,873,625	A	2/1999	Uchtman
4,577,901	A	3/1986	Phillips	5,893,605	A	4/1999	Chang
4,595,232	A	6/1986	Glenn et al.	D411,387	S	6/1999	Zheng
4,605,261	A	8/1986	Lee	5,921,258	A	7/1999	Francois
4,635,667	A	1/1987	Harn	5,944,384	A	8/1999	Patterson
4,639,036	A	1/1987	Nichols	5,967,601	A	* 10/1999	Gillins 297/184.15
4,671,566	A	6/1987	Knapp et al.	5,984,406	A	11/1999	Lee
4,673,211	A	6/1987	Hoffman	5,984,409	A	11/1999	Eakin et al.
4,676,548	A	6/1987	Bradbury	6,015,189	A	1/2000	Broadhead et al.
4,687,248	A	8/1987	Ross et al.	6,030,034	A	2/2000	Plohetski
4,687,249	A	8/1987	Mills	6,045,177	A	4/2000	Grace
4,715,650	A	12/1987	Berman et al.	6,048,023	A	4/2000	Lampton
4,717,201	A	1/1988	Barras	6,056,172	A	5/2000	Welsh
4,736,825	A	4/1988	Belfi	6,082,813	A	7/2000	Chen
4,773,708	A	9/1988	Nastu	6,095,172	A	8/2000	Trapp et al.
4,795,068	A	1/1989	Blean	6,095,599	A	* 8/2000	Lambert 297/129
4,796,734	A	1/1989	Distasio	D430,976	S	9/2000	Tow
4,807,930	A	2/1989	Helfrich	D433,244	S	11/2000	Zheng
4,824,171	A	4/1989	Hollingsworth	D433,574	S	11/2000	Zheng
4,826,241	A	5/1989	Barras	6,145,716	A	11/2000	Caicedo
4,826,242	A	5/1989	Trethewey	6,152,156	A	11/2000	Tung
				6,164,726	A	12/2000	Reeves et al.

US RE43,847 E

Page 3

6,179,374 B1 1/2001 Tang
 6,206,463 B1 3/2001 Whigham
 6,217,113 B1 4/2001 Knatz
 6,231,119 B1 5/2001 Zheng
 6,237,993 B1 5/2001 Zheng
 6,241,311 B1 6/2001 Zheng
 6,247,748 B1 6/2001 Zheng
 6,247,749 B1 6/2001 Yu
 6,247,750 B1 6/2001 Tsai
 6,250,712 B1 6/2001 Livingston et al.
 6,264,271 B1 7/2001 Munn et al.
 6,296,002 B1 10/2001 Tashchyan
 6,296,304 B1 10/2001 Zheng
 6,302,479 B1 10/2001 Zheng
 6,322,138 B1 11/2001 Tang
 6,354,044 B1 3/2002 Lagace, Jr.
 6,371,553 B1 4/2002 Tang
 6,402,230 B1* 6/2002 Tang 297/16.2
 6,405,742 B1 6/2002 Driscoll
 6,425,590 B1 7/2002 Whiteside et al.
 6,520,574 B1 2/2003 Huang
 6,655,736 B1 12/2003 Arenas
 D487,297 S 3/2004 Tyler et al.
 6,698,827 B2 3/2004 Le Gette et al.
 6,764,132 B1 7/2004 Gaertner
 6,789,557 B1 9/2004 Wahl, Jr.
 6,820,927 B2 11/2004 Isom et al.
 6,823,883 B1 11/2004 Sears
 6,824,210 B2 11/2004 Zheng
 6,845,780 B2 1/2005 Bishirjian
 6,854,797 B1 2/2005 Thomas
 6,899,383 B2 5/2005 Hwang
 6,926,355 B2 8/2005 Le Gette et al.
 7,048,331 B2* 5/2006 Saakyan 297/16.2 X
 7,048,333 B2 5/2006 Martinez
 7,198,324 B2 4/2007 Le Gette et al.
 2002/0112752 A1 8/2002 Blakney

2004/0178665 A1 9/2004 May
 2004/0222678 A1 11/2004 Hansen
 2004/0232740 A1 11/2004 Enge
 2006/0061146 A1* 3/2006 Grace 297/16.2 X
 2007/0040422 A1 2/2007 Reeb et al.

FOREIGN PATENT DOCUMENTS

DE	26 55 028	A1	6/1978	
DE	31 31 166	A1	2/1983	
DE	42 01 743	A1	10/1992	
EP	172266	A1 *	1/1986 297/16.2
EP	172 266	A1	2/1986	
GB	2 042 960	A	1/1980	
GB	2 052 960	A	6/1980	
GB	2 074 853		11/1981	
GB	2074853	A *	11/1981 297/16.2
GB	2 091 648	A	8/1982	
JP	7-207962		8/1995	
WO	WO 82/01984	A1	6/1982	
WO	WO 91/14386	A1	10/1991	
WO	WO 96/39066	A1	12/1996	
WO	WO 02/38009		5/2002	
WO	WO 02/38009	A1	5/2002	

OTHER PUBLICATIONS

Sand Chair, The Crate and Barrel 1993 Spring and Summer Catalogue, 1993, 1 page.
 Portable Chair, MotorHome, Sep. 1994, pp. 106.
 Lafuma Sport/Travel Chair, Campmor, Late Spring 1994, 1 page.
 Pamphlet for Werland's Handcrafted Rocking Chairs, Austin, Texas, 2 pages.
 Product label for "Undercover the Sunshade" manufactured by Della USA, 1 page.

* cited by examiner

FIG. 1




FIG. 2





FIG. 3






FIG. 4

FIG. 5




FIG. 6




FIG. 7





FIG. 8






FIG. 9




FIG. 10




FIG. 13




FIG. 14




FIG. 15

FIG. II





FIG. 12






FIG. 16




FIG. 17




FIG. 18

FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24





FIG. 25






FIG. 26




FIG. 27

FIG. 28




FIG. 29




FIG. 30





FIG. 31






FIG. 32





FIG. 33

FIG. 34






FIG. 35




FIG. 36

FIG. 37





FIG. 38






FIG. 39

FIG. 40 A




FIG. 40 B




FIG. 40 C





FIG. 40 D







FIG. 42






FIG. 43




FIG. 44




FIG. 46




FIG. 48




FIG. 49





FIG. 50




FIG. 51




Fig. 52




FIG. 53A




FIG. 54A




FIG. 53B







FIG. 54B









FIG. 57B






Fig. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66






FIG. 67








FIG. 70




FIG. 71




FIG. 72




FIG. 73




FIG. 74




FIG. 75




FIG. 76




FIG. 77




FIG. 78




FIG. 79








FIG. 80





COLLAPSIBLE SUPPORT AND METHODS OF USING THE SAME

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

RELATED APPLICATIONS

This application is a continuation application of application Ser. No. 10/367,796, filed Feb. 19, 2003, titled "Collapsible Support and Methods of Using the Same," now U.S. Pat. No. 6,926,355, the entire content of which is hereby incorporated by reference, which is a continuation-in-part of U.S. patent application Ser. No. 10/233,784, entitled "Collapsible Support and Methods of Using the Same," filed Sep. 4, 2002, now U.S. Pat. No. 6,820,927, which is a continuation-in-part of International Application Serial No. PCT/US02/06695, entitled "Collapsible Support and Methods of Using the Same," filed Mar. 5, 2002, which is a continuation-in-part of U.S. patent application Ser. No. 09/797,948, entitled "Collapsible Support and Methods of Using the Same," filed Mar. 5, 2001, which is now U.S. Pat. No. 6,698,827, all of which are hereby incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION

This invention relates generally to a support having multiple configurations, and in particular, to a support that can be positioned in an expanded configuration and a collapsed configuration.

Some conventional supports can be used as chairs to support a user. Such chairs are often transported and used in various outdoor settings. Difficulty exists in transporting a chair. For example, conventional chairs cannot be easily collapsed and transported due to the shape and weight of the chairs.

The need exists for a collapsible support that can be easily transported to various locations.

SUMMARY OF THE INVENTION

A support includes a frame and a tension member. The support can be positioned in a collapsed configuration and an expanded configuration. In one embodiment, the support can be used with a cover that can be positioned around a portion of the frame.

In one embodiment, the support includes a seat portion coupled to the frame. In the open or expanded configuration, a user can sit on the support and the frame is self-supporting.

When the frame is in its expanded configuration, the tension member is coupled to the frame to provide support for an arm of the user. When the frame is in its collapsed configuration, a cover can be placed over a portion of the frame or support. In this configuration, the tension member is not contained by and extends from the cover, thereby enabling a user to place the tension member over the user's shoulder for transporting the support.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a side view of a support according to an embodiment of the invention.

FIG. 2 illustrates a front view of the support of FIG. 1.

FIG. 3 illustrates a rear perspective view of the support of FIGS. 1 and 2.

FIG. 4 illustrates a portion of a tension member of the support of FIG. 1.

FIG. 5 illustrates a portion of a tension member of the support of FIG. 1.

FIG. 6 illustrates a bottom coupler of the rear frame portion of the support of FIG. 1.

FIG. 7 illustrates a front view of a portion of the rear frame portion of the support of FIG. 1.

FIG. 8 illustrates a cover according to an embodiment of the invention.

FIGS. 9-15 illustrate a process, according to an embodiment of the present invention, by which the support can be transformed from an expanded configuration to a collapsed configuration.

FIGS. 16-18 illustrate the movement of the tension members relative to the rear frame portion.

FIG. 19 illustrates a storage bag of the support of FIG. 1.

FIGS. 20-21 illustrate a support and a pillow according to an embodiment of the invention.

FIG. 22 illustrates an alternative embodiment of a pillow according to the present invention.

FIG. 23 illustrates a combination of a support and a shade according to the present invention.

FIGS. 24-28 illustrate alternative embodiments of a shade according to the present invention.

FIG. 29 illustrates an alternative embodiment of a support according to the present invention.

FIGS. 30-32 illustrate a combination of a support and a storage device according to the present invention.

FIG. 33 illustrates an alternative embodiment of a storage device according to the present invention.

FIG. 34 illustrates an alternative embodiment of a support according to the present invention.

FIGS. 35-36 illustrate alternative embodiments of a support according to the present invention.

FIG. 37 illustrates a side view of a support according to an alternative embodiment of the invention.

FIG. 38 illustrates a perspective view of a rear portion of the support of FIG. 37.

FIG. 39 illustrates a top view of a rear portion of the support of FIG. 37.

FIGS. 40a-40d illustrate cross-sectional views of a rear portion of the support of FIG. 37.

FIG. 41 illustrates a rear perspective view of a support according to an alternative embodiment of the invention.

FIG. 42 illustrates a side view of the support of FIG. 41 in a collapsed configuration.

FIG. 43 shows a perspective view of a rear portion of a support in an upright position, according to an embodiment of the invention.

FIG. 44 shows a perspective view of the rear portion of the support shown in FIG. 43 in a reclined position.

FIGS. 45a and 45b show a side view of the rear portion of the support shown in FIG. 43 while in an upright position and collapsible position.

FIG. 46 shows a perspective view of a rear portion of a support in an upright position, according to another embodiment of the invention.

FIG. 47 shows a perspective view of the rear portion of the support shown in FIG. 46 in a reclined position.

FIG. 48 illustrates a front perspective view of a combination of a support and a shade according to an alternative embodiment of the invention.

FIG. 49 illustrates a rear perspective view of the combination of FIG. 48.

FIG. 50 illustrates a front view of the support member in a collapsed configuration, according to the embodiment shown in FIG. 49.

FIG. 51 illustrates a front perspective view of the shade of FIG. 48.

FIG. 52 illustrates a front perspective view of the combination of FIG. 48.

FIG. 53A illustrates a perspective view of a rear portion of a support in an upright position, according to an embodiment of the invention.

FIG. 53B illustrates a perspective view of a rear portion of a support in an upright position, according to an alternative embodiment of the invention.

FIG. 54A illustrates a top view of a rear portion of the support of FIG. 53A.

FIG. 54B illustrates a top view of a rear portion of the support of FIG. 53B.

FIG. 55 illustrates a side view of a rear portion of the support of FIG. 53 in an upright position.

FIG. 56 illustrates a side view of a rear portion of the support of FIG. 53 in a reclined position.

FIG. 57A illustrates a rear perspective view of a support in a reclined position according to an alternative embodiment of the invention.

FIG. 57B illustrates a rear perspective view of a support in a reclined position according to an alternative embodiment of the invention.

FIG. 58 illustrates a rear perspective view of the support of FIG. 57A in an upright position.

FIG. 59 illustrates a perspective view of a rear portion of the support of FIG. 57A in a reclined position.

FIG. 60 illustrates a perspective view of a rear portion of the support of FIG. 57A in an upright position.

FIG. 61 illustrates a rear perspective view of a support in an upright position according to an alternative embodiment of the invention.

FIG. 62 illustrates a rear perspective view of the support of FIG. 61 in a reclined position.

FIG. 63 illustrates a perspective view of an adjustment mechanism of the support of FIG. 61.

FIG. 64 illustrates a perspective view of a rear portion of a support in an upright position according to an alternative embodiment of the invention.

FIG. 65 illustrates a perspective view of a rear portion of the support of FIG. 64 in a reclined position.

FIG. 66 illustrates a perspective view of a rear portion of a support in a reclined position according to an alternative embodiment of the invention.

FIG. 67 illustrates a perspective view of a rear portion of the support of FIG. 66 in an upright position.

FIG. 68 illustrates a rear perspective view of a support according to an alternative embodiment of the invention.

FIG. 69 illustrates a side perspective view of the support of FIG. 68.

FIG. 70 illustrates some components of the support of FIG. 69.

FIG. 71 illustrates a front view of a seat according to an alternative embodiment of the invention.

FIG. 72 illustrates a front view of a seat according to an alternative embodiment of the invention.

FIG. 73 illustrates a process, according to an alternative embodiment of the invention, by which the frame can be retained in its collapsed configuration.

FIG. 74 illustrates a front view of the support of FIG. 68 in a collapsed configuration, according to an embodiment of the invention.

FIG. 75 illustrates a rear perspective view of a base according to an alternative embodiment of the invention.

FIG. 76 illustrates a side view of the base of FIG. 75.

FIG. 77 illustrates a rear view of the base of FIG. 75.

FIG. 78 illustrates a top view of the base of FIG. 75.

FIG. 79 illustrates a rear perspective view of some components of the support of FIG. 68 in an upright configuration.

FIG. 80 illustrates a rear perspective view of the components of FIG. 79 in a reclined configuration.

FIG. 81 illustrates a rear perspective view of some components of a support in an upright configuration.

FIG. 82 illustrates a rear perspective view of the components of the support of FIG. 81 in a reclined configuration.

FIG. 83 illustrates a rear perspective view of some components of a support in an upright configuration.

FIG. 84 illustrates a rear perspective view of the components of the support of FIG. 83 in a reclined configuration.

DETAILED DESCRIPTION OF THE INVENTION

A support includes a seat portion, a frame, and a tension member. The frame can be positioned in a collapsed configuration and an expanded configuration in which the frame is self-supporting. The tension member is disposable in a first position to provide support for an arm of a user and a second position to be carried on a shoulder of a user. When the frame is in its collapsed configuration, the tension member can be placed over a user's shoulder to transport the support. When the frame is in its expanded configuration, the tension member can be disposed in its first position to support an arm of a user.

A support according to an embodiment of the invention is illustrated in FIGS. 1-5. FIG. 1 illustrates a side view of the support or support assembly 10 in a deployed or expanded configuration. In one embodiment, support 10 can be used as a chair in its expanded configuration.

In the illustrated embodiment, the support 10 includes a seat portion 20, tension members 40, 70, and a frame 100. The seat portion 20 and the tension members 40, 70 are coupled to the frame 100.

In the illustrated embodiment, the frame 100 includes a rear frame portion 110 and a front frame portion 140, which are coupled together by upper side support bars 130, 132 and lower side support bars 134, 136.

Each of the support members 130, 132, 134, 136 are pivotally coupled to the front and rear frame portions 110, 140. Upper side support member 130 is pivotally coupled to lower side support member 134 proximate their midpoints. Similarly, upper side support member 132 is pivotally coupled to lower side support member 136.

In one embodiment, the upper ends of lower side support members 134, 136 are bent with respect to the remainder of the support members 134, 136. The bent portions of the lower side support members 134, 136 are located proximate to the seat portion 20. When the frame 100 is in its expanded configuration, the upper ends of the lower side support members 134, 136 do not extend into the seat portion 20 and engage the user on the support 10.

In the illustrated embodiment, the rear frame portion 110 includes support members 112, 114, and a coupler 120. The support members 112, 114 are coupled together at their upper and lower ends by an upper coupler 116 and a lower coupler 118, respectively. Additionally, the lower coupler 118 is pivotally coupled to the ends of lower side support members 134, 136. The rear frame portion 110 has a bottom surface 128 proximate the lower coupler 118. The bottom surface 128 is adapted to rest on a supporting surface.

In the illustrated embodiment, the support members are hollow, metal tubes, such as steel tubes. Support members can be formed of any material and configured in any cross-sectional shape that provides sufficient structural strength to support a user. For example, the support members can be

In one embodiment, the coupler **120** is a plate that includes holes **122**, **124** and is slidably mounted to support members **112**, **114**. As shown in FIG. 3, support members **112**, **114** extend through holes **122**, **124**, respectively. The holes **122**, **124** are sized to slide along the length of support members **112**, **114**. Slide plate **120** is pivotally coupled to the upper ends of the upper side support members **130**, **132**.

As shown in FIGS. 2 and 3, the support **10** includes an extension member **126** coupled to the slide plate **120**. In one embodiment, the extension member **126** is a cord. The cord **126** is used to collapse the support **10** from its expanded configuration. The cord **126** is threaded through apertures (not shown) in the upper coupler **116** and connected to the plate **120**. The function of the extension member is discussed in further detail below.

While the slide plate is formed of plastic in the disclosed embodiment, any suitable material may be used. Similarly the shape of the slide plate may be varied so long as the slide plate can move along the rear frame portion.

In the illustrated embodiment, the front frame portion **140** includes elongated support members or support members **146**, **148** that are pivotally coupled to each other. Support members **146**, **148** include upper ends **158**, **160** and lower ends **162**, **164** and form an "X" structure.

In one embodiment, support members **146**, **148** include portions **154**, **156** as illustrated in FIG. 2. Portions **154**, **156** are substantially linear. When the frame **100** is in its expanded configuration, portions **154**, **156** are oriented substantially horizontal and are positioned beneath the membrane **22** to provide support.

In one embodiment, support members **146**, **148** include portions **150**, **152** as illustrated in FIG. 2. Portions **150**, **152** are substantially linear. In this embodiment, the support members **146**, **148** are pivotally coupled together at portions **150**, **152**.

The lower ends **162**, **164** of the support members **146**, **148** are pivotally coupled to front feet **166**, **168**, respectively. Each of the front feet **166**, **168** has a bottom surface **170**, **172** that can engage the surface on which the support **10** is placed. Front feet **166**, **168** are pivotally coupled to upper side support members **130**, **132**.

Support members **146**, **148** are coupled to the seat portion **20** and to the lower side support members **134**, **136**. The seat portion **20** includes apertures or holes **30**, **32** through which the support members **146**, **148** can be inserted. The upper end of lower side support member **134** is pivotally coupled to the second planar portion **154** of support member **146**. Similarly, lower side support member **136** is pivotally coupled to the second planar portion **156** of support member **148**.

The front frame portion **140** has an upper portion **142** and a lower portion **144**. The upper front frame portion **142** includes the front frame portion **140** located above the seat portion **20**. The lower front frame portion **140** includes the front frame portion **140** located below the seat portion **20** in FIG. 2.

In the illustrated embodiment, the frame **100** is a self-supporting structure. When the frame **100** is in its expanded configuration, the weight of the components of the frame **100** hold the frame **100** in its expanded configuration. The frame **100** does not need the seat portion **20** or one of the tension members **40**, **70** to remain in its expanded configuration.

In the illustrated embodiment, the seat or seat portion **20** includes a membrane **22** that is supported on the frame **100**. The seat portion **20** includes a strip **24** along the perimeter of the membrane **22**. The membrane **22** has ends **26**, **28** and holes **30**, **32** that are located proximate to end **28**. End **26** of the membrane **22** is coupled to the rear frame portion **110**. End **28** is releasably coupled to the front frame portion **140**.

As shown in FIG. 2, the upper end **158** of the support member **146** is inserted through hole **30**. Similarly, the upper end **160** of support member **148** is inserted through hole **32**. Membrane **22** is supported on the second planar portions **154**, **156** of each support member **146**, **148**.

In the illustrated embodiment, the membrane **22** is darted at regions **33** on either side of the seat portion **20**. A triangular notch is cut in membrane **22** in each region **33**. The membrane **22** is collected together to close the notch, thereby causing the membrane **22** to form a cup-like shape as illustrated in FIG. 1. The straps **34**, **36** are secured to the membrane **22** in regions **33** to cover up the notch and to reinforce regions **33**. The straps **34**, **36** are also coupled to the membrane **22** to provide support to the seat portion **20**. In the illustrated embodiment, strip **24** and straps **34**, **36** are sewn to the membrane **22**. However, the components of seat portion **20** can be coupled together using any known method of coupling items.

The term "membrane" is used herein to include, but is not limited to, a layer of material. For example, the membrane can be a piece of fabric such as nylon or neoprene.

In the illustrated embodiment, the support **10** includes tension members **40**, **70** that are coupled to the frame **100**. While the tension members **40**, **70** are illustrated as substantially similar, the tension members do not have to be similar. Similarly, it is not necessary that the support has two tension members. Only one tension member will be discussed in detail below to simplify the description of the invention.

In the illustrated embodiment, the tension member is an elongated fabric strap. Alternatively, the strap can be a rope, cord, webbing, or any other structure that can provide a tensile force.

In the illustrated embodiment, the tension member includes a padded portion **42**, and a strap portion **60**. Tension member **40** is coupled to the rear frame portion **110** and the front frame portion **140**.

Tension member can be coupled to the frame at any number of locations. Tension member **40** can be coupled to the rear frame portion **110** at one or more locations. Similarly, tension member **40** can be coupled to the front frame portion **140** at one or more locations. For example, tension member can be coupled to the rear frame portion at two locations and to the front frame portion at one location. In one embodiment, tension member can be coupled to the rear frame portion at one location and to the front frame portion at two locations. In another embodiment, tension member can be coupled to the rear frame portion at one location and to the front frame portion at one location. In another embodiment, tension member can be coupled to the rear frame portion at two locations and to the front frame portion at two locations. When the tension member is connected to the rear frame portion or to the front frame portion at multiple locations, each location can be at the same or different height relative to the other locations on the same frame portion.

Tension member **40** can be either removably or fixedly coupled to the rear frame portion **110** and/or the front frame portion **140** at each location. For example, tension member **40** can be removably coupled to the front frame portion at one location and fixedly coupled to the rear frame portion at two

locations. Any combination of fixed and removable connections to the frame can be used to couple the frame and each tension member.

In alternative embodiments, tension member 40 can be coupled to the frame at locations other than on the rear frame portion and on the front frame portion.

The preceding discussion of the coupling of tension member to the rear frame portion and to the front frame portion can be applied to the various embodiments of tension members and supports described herein.

One end of tension member 40 includes a hole 48 through which support member 112 is inserted. Accordingly, the tension member 40 is slidably coupled to the support member 112 of the rear frame portion 110. The opposite end of the tension member 40 is connected to the front frame portion 140 at front foot 162.

In the illustrated embodiment, the tension member 40 is releasably coupleable to the front frame portion 140. As illustrated in FIG. 4, the padded portion 42 of the tension member 40 includes ends 44, 46 and a coupler 50 having an opening or hole 52 therein. Coupler 50 and hole 52 are located proximate end 46. The hole 52 is configured to receive a portion of the upper end 158 of the support member 146. Upper end 158 is inserted into and is seated in coupler 50.

As illustrated in FIG. 5, the strap portion 60 of tension member 40 includes ends 62, 64, a fixed portion 66, and an adjustable portion 68. One end 62 of the strap portion 60 is coupled to end 46 of the padded portion 42. The strap portion 60 also includes a tensioner 70 that couples the fixed portion 66 to the adjustable portion 68. Tensioner 70 can be adjusted to change the length of the strap portion 60.

In the illustrated embodiment, tensioner 70 is a buckle that is coupled to a free end of the fixed portion 66. Tensioner 70 can be any mechanism that can be used to retain two points on the strap portion together to vary the distance between the ends of the strap portion. For example, tensioner 70 can include a pair of buckles, a pair of clips, hook and loop fasteners, etc.

In an alternative embodiment, adjustment of the tension member can adjust the disposition of the frame. For example, the coupler can be sized to permit movement of the tension member relative to the upper end of the support member. Since the tension member is coupled to the rear frame portion, the tension member and the rear frame portion are pulled forwardly as the strap portion is shortened. When the rear frame portion is pulled forwardly, the angle that the rear frame portion is reclined relative to the supporting surface varies. Accordingly, the user can adjust the recline position of the support by adjusting the strap portion of the tension member.

An embodiment of a lower coupler is illustrated in FIG. 6. Lower coupler 118 includes mounting portions 180, 190 and a bottom portion 186. In the illustrated embodiment, the mounting portions 180, 190 and the bottom portion 186 are integrally formed.

Mounting portions 180, 190 include side walls 183, 184 and 193, 194, respectively. Mounting portion 180 includes coupling portions 181, 182. Coupling portion 181 can be referred to as straight section or portion 181. Coupling portion 182 can be referred to as angled section or portion 182. As illustrated in FIG. 6, coupling portion 181 is oriented at an angle relative to coupling portion 182. Similarly, mounting portion 190 includes coupling portions or straight section 191 and angled section 192.

As illustrated in FIG. 6, rear support members 112, 114 are coupled to mounting portions 180, 190 by fasteners 185, 195,

respectively. Fasteners 185, 195 can be any type of fastener that allows relative movement between the rear support members and the lower coupler.

Side support members 134, 136 are coupled to mounting portions 180, 190 by fasteners 185, 195. In the illustrated embodiment, the side support members 134, 136 are coupled to the angled sections 182, 192 of the mounting portions 180, 190. Rear support members 112, 114 are coupled to the straight sections 181, 191 of the mounting portions 180, 190.

When the frame is moved from its expanded configuration to its collapsed configuration, side support members 134, 136 pivot about fasteners 185, 195 in different planes. Since the angled sections 182, 192 are oriented at angles with respect to the coupler 118 as shown in FIG. 6, the planes in which the side support members 134, 136 move intersect each other.

Since the connections of the side support members 134, 136 to the lower coupler 118 are in front of and at angles to the connections of the rear support members 112, 114 to the lower coupler 118, the torque on the connections at the lower coupler 118 generated by the collapsing of the frame 100 is lower than the torque generated in conventional supports. Similarly, since the fasteners connecting a side support member and a rear support member to a particular mounting portion are not parallel, the torque generated in the fasteners during the collapsing or expanding of the frame is reduced.

The bottom portion 186 of the lower coupler 118 includes openings 196, 198. When the support 10 is placed on a surface with loose material, such as sand or dirt, the loose material can pass through openings 196, 198.

FIG. 7 illustrates a front view of an embodiment of the upper portion of the rear frame portion. The extension member 126 is coupled to the slide plate 120 and extends through openings in the upper coupler 116. The extension member 126 also passes through openings in the tension members 40, 70 behind the holes through which the rear support members 112, 114 extend.

In one embodiment, the extension member 126 includes two knots 125, 127. Each knot 125, 127 is positioned below and provides support for the end of one of the tension members 40, 70. Above the tension members 40, 70, the extension member 126 warps around each of the rear support members 112, 114 and passes through openings in the upper coupler 116 on the outside of the support members 112, 114. The operation of the extension member is discussed in greater detail below in FIGS. 16-18.

An embodiment of a cover is illustrated in FIG. 8. Cover 200 includes a membrane 202 having an edge 204 that defines an opening 206. An elastic band 208 is sewn along edge 204. In the illustrated embodiment, the membrane is a nylon material.

FIGS. 9-15 illustrate a process, in ascending order, according to an embodiment of the present invention, by which a collapsible support can be changed or transformed from an expanded configuration to a collapsed configuration. It should be understood that the process can be reversed to transform the support from its collapsed configuration to its expanded configuration by following FIGS. 9-15 in reverse order.

As shown in FIG. 9, the user releases the tension in the tension member 40 by increasing the length of the strap portion 60. The user then removes or decouples the upper end 158 of the support member 146 from the tension member 40 as illustrated in FIG. 10. These steps, releasing the tension and removing the tension member 40, are repeated for the second tension member 70.

As shown in FIGS. 11-12, the user grasps and pulls upwardly on the cord 126 while holding onto the upper cou-

pler 116. When the user pulls the cord 126, the slide plate 120 slides upwardly along support members 112, 114. As the slide plate 120 moves upwardly, the ends of the support members 130, 132 connected to the slide plate 120 move upwardly. As a result, the lower ends of the upper side support members 130, 132 are drawn toward the rear frame portion 110 and the lower side support members 134, 136 pivot about their lower ends. The scissor-like movement of the side support members 130, 132, 134, 136 draws the front frame portion 140 towards the rear frame portion 110. The movement also causes the front feet 162, 164 to move together and the upper ends 158, 160 to move together.

Once the frame 100 is collapsed, the user then secures the support 10 in its collapsed configuration by fastening the clip 128 that is coupled to the front frame portion 140 to cord 126 as illustrated in FIG. 13.

Cover 200 can be placed over the collapsed support 10 as illustrated in FIGS. 13-14. The cover 200 is configured to receive a portion of the collapsed support 10. In particular, the cover 200 encloses a portion of the frame 100. The tension members 40, 70, however, are not enclosed by and extend from the cover 200. As illustrated in FIG. 15, the tension members 40, 70 can be supported on the shoulders of the user. FIGS. 16-18 illustrate the rotation of the tension members during the collapsing of the frame. Line 111 represents a plane defined by the rear support members 112, 114. The direction in which the support 10 is facing is illustrated by the arrow F.

In FIG. 16, the support 10 is illustrated in its expanded configuration. As the user grasps the extension member 126 and pulls it upwardly, the tension members 40, 70 and the location of the knots 125, 127 rotate around the rear frame member 110. As illustrated in FIGS. 17 and 18, tension member 40 rotates around rear support member 112. Tension member 70 rotates in an opposite direction about rear support member 114. The rotation of the tension members 40, 70 is caused by the wrapping of the extension member 126 around each rear support member 112, 114.

Referring to FIG. 7, as the extension member 126 is pulled higher and advances upwardly along the rear frame portion 110, the relative positions of the knots 125, 127 move around the rear support members 112, 114. The wrapping movement of the extension member 126 around members 112, 114 causes the tension members 40, 70 to move between a position in which they provide support to a user's arm and a position on the rear of the frame 100 in which they can be carried on the shoulders of a user. The positions of the tension members 40, 70 relative to the frame 110 during the collapsing process are illustrated in FIGS. 11 and 12.

In one embodiment, the support 10 can include a pouch 220 as illustrated in FIG. 19. The pouch 220 is coupled proximate to the end 28 of the seat portion 20. The pouch 220 includes an attachment strap 222, a fabric portion 224, and a draw string 226. The attachment strap 222 is coupled to the seat portion 20 and supports the fabric portion 224 of the pouch 220. A draw string 226 is provided at the upper surface of the fabric portion 224 to close the opening 228.

While the illustrated fabric portion is made from a mesh material, the fabric portion can be any material that can be used to support and retain an article. Similarly, the fabric portion can be any size or shape that enables the pouch to hold articles.

In one embodiment, the support 10 includes a pillow 80. As illustrated in FIGS. 20-21, the pillow 80 includes a body with a front surface 82 and a rear surface 84. The front surface 82 of the pillow 80 can be used to support a portion of a user's

body, such as a head, neck, or back. The pillow 80 includes a fabric loop 86 mounted on its rear surface 84.

The pillow 80 is slidably coupled to an elongated strap 90 that extends along the back portion of the seat portion 20. Strap 90 is inserted into loop 86, thereby allowing the pillow 80 to slide along strap 90. The pillow 80 can slide between upper and lower position as illustrated in FIG. 20. In the upper position, the pillow 80 is a head cushion for the support 10.

The strap 90 includes ends 92, 94. End 92 is coupled to end 26 of the membrane 22. The other end 94 of the strap 90 includes a fastener 96 and can be selectively attached to the membrane 22. In the illustrated embodiment, fastener 96 is a hook fastener that can be coupled to the membrane 22 of the seat portion. Thus, the pillow 80 can be disposed in a plurality of positions on the membrane 22 as determined by the strap 90.

In one embodiment, the strap 90 can be flipped over the upper coupler 116 and rest against or be secured to the back of the support 10. When the support 10 is collapsed, the pillow 80 can be positioned along strap 90 so that it is positioned between the frame 100 and the user when the support 10 is carried on the user's back.

In the illustrated embodiment, the pillow is filled with a stuffing material. In an alternative embodiment, the pillow can be a pouch with a sealable opening into which material can be inserted. As illustrated in FIG. 22, pillow 240 may include a flexible membrane 242 that defines an opening 244. The pillow 240 can include a closing mechanism 246, such as a zipper or a hook and loop fastener, to close the opening 244. When the support 10 is in its expanded configuration, the cover 200 can be stuffed into the pillow 240 to enable the pillow 240 to be used as a support.

FIGS. 23-28 illustrate several alternative embodiments of shades that can be used with a support according to the present invention. Shades can be utilized with any type of support, including the support illustrated in FIGS. 1-3.

In the illustrated embodiments, each of the shades is releasably coupled to a support with tethering lines 314 and coupling elements 316. Coupling mechanisms other than tethering lines and coupling elements can be used to secure the shades to the supports. For example, straps with buckles, clips, or slide on pockets can be used. Alternatively, a shade can utilize sand anchors to position the shade relative to a chair, instead of coupling the shade to the chair.

Also, while the tethering lines are illustrated as secured to the shades via holes, the coupling mechanisms can be clipped, adhered, sewn, or connected to the shades using any other method of coupling items. The arrangement of the coupling mechanisms, including the holes on the shades, can vary depending on the desired arrangement.

In one embodiment, a support can include a shade 300 coupled thereto. In FIG. 23, shade 300 is coupled to the support 10 at three locations. Shade includes a membrane 340, a frame 320, and ends 302, 304. An opening 310 is formed in membrane 340 proximate to end 302. A fabric material 312, such as mesh, covers opening 310, which provides ventilation.

The membrane 340 is coupled to the frame 320 that provides support for the shade. In the illustrated embodiment, the frame 320 is a flexible band, such as a thin metal band. An example of a shade is disclosed in U.S. patent application Ser. No. 09/764,059, entitled "Collapsible Sunshade and Methods of Using the Same", filed Jan. 19, 2001, the disclosure of which is incorporated by reference herein.

The coupling mechanisms 316 are releasably secured to mounting elements that are connected to the support as illus-

11

trated. In one embodiment, the support 10 can include mounting elements 326, 328 located on the front frame portion 140.

As shown in FIGS. 23-28, the shape and features of the shade embodiments can vary. In FIG. 24, shade 400 includes a membrane 410, a frame member 420, and flaps 430, 432. The frame member 420 is a flexible metal band that provides support to the membrane 410. In this embodiment, the frame member 420 does not extend around the perimeter of the shade 400. The flaps 430, 432 are provided on the side of the center portion of the membrane 410.

Additional embodiments of a shade are illustrated in FIGS. 25-28. In FIG. 25, shade 500 includes flaps 530, 532. Shade 500 is substantially similar to shade 400, which is shown in FIG. 19, with the exception of the shapes of the flaps. In FIG. 26, shade 600 includes ends 602, 604, one of which has an inwardly curved shape. In FIG. 27, shade 700 includes ends 702, 704, one of which has an outwardly curved shape.

In FIG. 28, shade 800 has a hexagonal shape with several flaps 802, 804, 806 located on its perimeter.

The shapes of the shades, including the flaps, can be varied depending on the desired amount of protection from the sun, rain, etc. The frame member of a shade provides support and can be located in different portions of the shade, depending on the desired flexibility of the shade.

The support 10 can also include a storage bag 900 as illustrated in FIG. 29. The bag 900 includes a wall 910 that defines an opening 906 into which articles can be inserted. The opening 906 can be adjusted using a drawstring 914. The bag 900 includes a rod 912 along a portion of the wall 910. When the support 10 is in its expanded configuration the weight of the rod 912 causes the bag 900 to lean to one side of the support 10 to bias the bag 900 into an open position.

The support 10 is releasably coupled to the frame 100. In the illustrated embodiment, the support includes mounting element 904 that can be coupled to coupler 902 on the frame 100.

Alternatively, the support 10 can include a storage device 1000 as illustrated in FIGS. 30-33. The storage device 1000 includes mounting elements 1010, 1012, 1014, 1016, a mesh compartment 1030, a cooler compartment 1034, and pockets 1040, 1042, 1044. The support 10 includes couplers 1020, 1022, 1024, 1026 that can interact with the mounting elements 1010, 1012, 1014, 1016 to releasably couple the storage device 1000 to the support 10. For example, the storage device 1000 can be supported on the frame 100 when it is connected to primary mounting elements 1010, 1012, and one or both of the secondary mounting elements 1014, 1016.

As illustrated in FIG. 30, when the support 10 is in its expanded configuration, the storage device 1000 can be positioned on one side of the support 10 to allow for easy access to the cooler compartment 1034 and the pockets 1040, 1042, 1044.

As illustrated in FIGS. 31-32, when the support 10 is in its collapsed configuration, the storage device 1000 can be coupled to the support 10 opposite the tension members 40, 70. The connection of the storage device 1000 and the support 10 allows for easy transportation of the storage device 1000 with the support 10.

In one embodiment of the storage device 1000, as illustrated in FIGS. 30 and 32, the storage device 1000 includes a stake 1060 and a sleeve 1062. The stake 1060 is stored in the sleeve 1062 when the support 10 is in its collapsed configuration.

The stake 1060 can extend through the sleeve 1062 when the support 10 is in its expanded configuration. When the

12

stake 1060 extends from the sleeve 1062, the stake 1060 engages a support surface to provide support for the storage compartment 1000.

As illustrated in FIG. 31, storage device 1100 includes frame members 1050, 1052 and an anchor 1120. The frame members 1050, 1052 are mounted in sleeves 1054, 1056 and provide rigidity to the storage device 1110. The anchor 1120 can be used to support the storage device 1100 when the support 10 is in its expanded configuration.

The anchor 1120 can be releasably coupled to the frame members as illustrated in FIG. 31, or can be coupled at any point along the bottom or side of the storage device 1100.

In one embodiment, two anchors 1116, 1118 can be coupled to a single strap 1117 that is slidably threaded through loop 1110. In one embodiment, the storage device can include two or more loops through which the strap is threaded. Depending on the orientation of the storage device 1100, anchor 1116 or anchor 1118 can be pulled out to one side to be engaged with a supporting surface and to secure the storage device 1100. Strap 1117 can be any flexible, elongated member that can be positioned along the storage device 1110.

Many possible variations on the particular embodiments described above would be consistent with the principles of the invention. Several additional variations are described below.

In one embodiment, the support 1200 can include floatation devices. As illustrated in FIG. 34, support 1200 includes floatation devices 1210, 1212 coupled to the tension members 40, 70. Additional floatation devices can be coupled to the support 1200 at different locations to increase the buoyancy of the support 1200. For example, a floatation device can be positioned beneath part of the seat portion.

In the illustrated embodiment, floatation devices are inflatable members that are coupled to the tension members. The floatation devices can be any device that can float (i.e., has a density less than that of water).

In one embodiment, the support 10 can also include wheels coupled to support members that are pivotally coupled to the frame. As illustrated in FIG. 35, a wheel 1300 is rotatably mounted to a wheel support member 1310 that is coupled to the frame. The wheel support member 1310 can be moved between an upper position and a lower position as represented by the arrow in FIG. 35. Thus, when the support 10 is in its expanded configuration the wheel 1300 can be pivoted into and out of contact with the support surface. A user can lift up the front frame portion of the support so that only the wheels contact the support surface. Accordingly, the user can easily pull the support to a different location.

In another embodiment, the support 10 can include wheels 1400, 1402 as illustrated in FIG. 36. In this embodiment, the wheels 1400, 1402 are rotatably mounted to an axle positioned proximate to the lower coupler 118. A locking mechanism (not shown) can be provided to lock the wheels 1400, 1402.

Another embodiment of the invention is illustrated in FIGS. 37-40. In this embodiment, a support 1500 has a frame 1550, a seat 1540, and tension members 1560 (although two are present only one is shown in FIG. 37). Similar to the above-described embodiments, the frame 1550 can be placed in an expanded configuration and in a collapsed configuration. The frame 1550, while in an expanded configuration, can be placed in an upright position and in a reclined position. The frame 1550 has a rear frame portion 1510 that includes a pair of support members 1512 and 1514, a pair of extension members 1520 and 1522, a coupler 1532 and guide plate 1502.

In the illustrated embodiment, the support members are hollow metal tubes, but as described above for support members **112** and **114**, the support members **1512** and **1514** can be made of different materials and have different cross-sectional shapes.

The extension members **1520** and **1522** are similar in structure and function, thus only extension member **1522** will be discussed in detail. The extension member **1522** is elongated in shape. Extension member **1522** has a first end **1528** and a second end **1530**. The first end **1528** of the extension member **1522** is pivotally coupled to the lower end **1518** of the support member **1514**. The second end **1530** of the extension member **1522** is pivotally coupled to the coupler **1532**.

In the illustrated embodiment, the extension member **1522** is pivotally coupled to support member **1514** and to the coupler **1532** via rods **1580** and **1582**, respectively, that extend through the coupled components. For example, rod **1580** extends from one side of the extension member **1522**, through the support member **1514** (via through holes **1584**), and through another side of the extension member. In an alternative embodiment, the extension member is pivotally coupled to the support member and to the coupler via rivets, brads, or another connection device known in the art that would provide a pivotal connection between the coupled components.

As best illustrated in FIGS. **40a-40d**, the rear frame portion **1510** can be pivoted with respect to the coupler **1532** to convert the frame **1550** from an upright position to a reclined position. Support member **1512** and elongate member **1520** function in a similar manner as support member **1514** and elongate member **1522**, thus only the movements of support member **1514** and elongate member **1522** are illustrated and discussed in detail. To recline the frame **1550**, the support member **1514** can be lifted from its initial upright position on the coupler **1532**. Then the extension member **1522** can be pivoted with respect to the coupler **1532**, and the support member **1514** can be pivoted with respect to the extension member **1520**. These steps can then be repeated for support member **1512** and extension member **1520** to place the frame **1550** in a reclined position. The steps of this process can be reversed to convert the frame **1550** from a reclined position to an upright position.

Note that as support **1500** is moved between the upright position and the reclined position, the support members **1512** and **1514** slide through holes **1504** and **1505** of guide plate **1502**. The diameters of the holes **1504** and **1505** are greater than the diameters of support members **1512** and **1514**, respectively. Consequently, as the support **1500** is moved between the upright position and the reclined position, the incline of support members **1512** and **1514** can change while still allowing the support members **1512** and **1514** to be capable of slidably moving within guide plate **1502**. For example, support members **1512** and **1514** can slide within guide plate **1502** when moving support **1500** into a collapsed configuration.

Another embodiment of the invention is illustrated in FIGS. **41-42**. In this embodiment, a support **1600** has a frame **1601**, a coupler **1670**, a seat **1680**, tension members **1610** and **1612**, elongate members **1630** and **1632**, guide plate **1605** and guide-plate member **1606**. Frame **1601** also includes members **1690** and **1692**. Similar to the above-described embodiments, the frame **1601** can be placed in an expanded configuration and in a collapsed configuration. Also similar to the above-described embodiments, each of the tension members **1610** and **1612** can be placed in two positions. The tension members **1610** and **1612** can be placed in a first position when the frame **1601** is in its expanded configuration to provide supports for the arms of a user. In addition, the tension mem-

bers **1610** and **1612** can be placed in a second position when the frame is in its collapsed configuration to serve as shoulder straps while support **1600** is being transported on the user's back.

Tension members **1610** and **1612** are functionally and structurally similar. Thus, although only tension member **1610** is discussed in detail, the same features are present for tension member **1612**. Tension member **1610** has a first end **1614** that is coupled to a rear frame portion **1602** of the frame **1601** and a second end **1616**. The vertical position of first end **1614** of tension member **1610** can be maintained by support **1607**. In other words, the extent to which the first end **1614** of tension member **1610** slides down its respective the support member is defined by the support **1607**. Tension member **1610** also has a sleeve **1622** that is located near the second end **1616** of the tension member. The sleeve **1622** is configured to selectively couple the second end **1616** of the tension member **1610** to a front frame portion **1604** of the frame **1601** when the frame is its expanded configuration. In this position, tension member **1612** provides support for an arm of a user. In an alternative embodiment, the tension member does not include a sleeve, but rather includes another coupling device, such as a strap or a clip, that can be used to selectively couple the second end of the tension member to the front frame portion.

Elongate members **1630** and **1632** can be structurally similar. Thus, although only elongate member **1630** is discussed in detail, the same features are present for elongate member **1632**. Elongate member **1630** has a first end **1634** and a second end **1636**. The first end **1634** of the elongate member **1630** is coupled to the front frame portion **1604**. The second end **1636** of the elongate member **1630** is configured to be selectively coupled to the second end **1616** of the tension member **1610**. Thus, when the frame **1601** is in its collapsed configuration, the second end **1636** of the elongate member **1630** can be coupled to the second end **1616** of the tension member **1610** to form a strap that can be placed over a shoulder of a user to retain the support **1600** on the user.

Because the first end **1634** of elongate member **1630** is coupled the front frame portion **1604**, the second end **1636** of elongate member **1630** is drawn inwardly when the support **1600** is moved from the collapsed configuration to the expanded configuration. This allows the connector **1654** also to be drawn inwardly so that it is disposed close to the support **1600** and out of the way of the user when in the expanded configuration. When the support **1600** is moved from an expanded configuration to a collapsed configuration, the elongate member **1630** can be drawn outwardly to provide a greater overall length to the strap formed by tension member **1610** coupled to elongate member **1630**.

Note that although the elongate members **1630** and **1632** are shown as straps, elongate members can be cables, cords or any appropriate type of material that can be slidably coupled to coupler **1670** and can be used to form a shoulder strap. In an alternative embodiment, the elongate members are not coupled to the front frame portion, but rather are fixedly coupled to the rear frame portion; the particular length of the elongate members can be selected so that distance from the rear frame portion is minimized while optimizing the shoulder strap length when the support is in a collapsed configuration.

In the illustrated embodiment, a coupling mechanism **1650** is used to selectively couple the second end **1636** of the elongate member **1630** to the second end **1616** of the tension member **1610**. The coupling mechanism has a female portion **1658** coupled to the second end **1616** of the tension member **1610** and a male portion **1654** coupled to the second end **1636** of the elongate member **1630**. The female portion **1658** and

15

the male portion **1654** can be coupled to the respective ends of the members via any known method, such as by sewing or gluing the portion to the member.

In an alternative embodiment, the coupling mechanism **1650** is a hook and loop device, a lock and key mechanism, a fastener, a clip, a button or another item by which the tension member **1610** can be removably coupled to the elongate member **1630**.

A coupling mechanism **1652**, which is similar to coupling mechanism **1650**, is used to couple tension member **1612** to elongate member **1632**.

In the illustrated embodiment, the elongate members **1630** and **1632** are slidably coupled to the coupler **1670**, however the elongate members need not be slidably coupled to the coupler or to any other portion of the support **1600**. In an alternative embodiment, the elongate members are slidably coupled to the frame of the support.

FIG. **42** shows the support in a collapsed configuration. As shown in FIG. **42**, the guide-plate member **1606** can be pulled over the end of the frame member **1690** and **1692** to maintain the support in the collapsed configuration and prevent it from unfolding.

An alternative embodiment of the support is shown FIGS. **43-45**. In the shown embodiment, the support member **1814** is pivotably coupled to collar **1828** by rod **1880**. Collar **1828** is slidably attached to coupler **1832**. The support is in an upright position when the collar **1828** is positioned as shown in FIGS. **43** and **45a**. The support is in a reclined position when the collar **1828** is positioned as shown in FIGS. **44** and **45b**. As the support moves between the upright position and the reclined position, member **1814** has a range of motion pivoting around rod **1880**.

Yet other alternative embodiment of the support is shown FIGS. **46-47**. In the shown embodiment, the support member **1914** includes rod **1980**. Coupler **1932** includes grooves **1934** and **1935**. Rod **1980** is slidably coupled to coupler **1932** and has a range of motion within grooves **1934** and **1935**. The support is in an upright position when the rod **1980** is in the rear position within grooves **1934** and **1935**, as shown in FIG. **47**. The support is in a reclined position when the rod **1980** is in the front position within grooves **1934** and **1935**. FIG. **46** shows the rod **1980** in an intermediate position near the front position.

Another embodiment of the invention is illustrated in FIGS. **48-52**. In this embodiment, a support **1700** has a frame **1702**, a seat **1704**, tension members **1706** and **1708**, and a shade **1710**. The shade **1710** includes a first end **1711**, a second end **1713**, a membrane portion **1712**, a frame portion **1714**, and a resilient or shape-retention portion **1716**. The frame portion **1714** is a flexible band that provides support to the membrane portion **1712** to keep the membrane portion relatively taut within the interior area defined by the frame portion. In the illustrated embodiment, the frame portion **1714** extends around the entire perimeter of the membrane portion **1712**. In an alternative embodiment, the frame portion extends around only a portion of the perimeter of the membrane portion.

The shade can be placed in an expanded configuration and in a collapsed configuration. Similar to the shade disclosed in U.S. patent application Ser. No. 09/764,059, entitled "Collapsible Sunshade and Methods of Using the Same," filed on Jan. 19, 2001, when the shade **1710** is in its collapsed configuration, the frame portion **1714** forms a plurality of concentric, substantially circular rings. As shown in FIGS. **48**, **49**, and **50**, the shade **1710** can be releasably coupled to the support **1700** when the shade is in its expanded configuration.

16

The shade **1710** includes a coupling sleeve **1720** (shown in FIG. **51**) and a pair of tethering lines **1740** and **1742** to releasably couple the shade to the support **1700**. The coupling sleeve **1720** is coupled to the first end **1711** of the shade **1710**. Any known method can be used to couple the coupling sleeve **1720** to the shade **1710**. In one embodiment, the coupling sleeve **1720** is sewn to the shade **1710**.

The coupling pocket **1720** is configured to receive and couple to a portion of the frame **1702**. The coupling pocket **1720** has an upper cap **1724** and a pair of retention flaps **1726** and **1728** that define a cavity **1722** into which a portion of the rear frame portion **1703** can be inserted. In the illustrated embodiment, support members **1750** and **1752** are inserted into the cavity **1722**. The retention flaps **1726** and **1728** include a coupler **1730** that is configured to releasably couple one of the retention flaps to the other, thereby securing the coupling sleeve **1720** to the rear frame portion **1703**. In the illustrated embodiment, the coupler **1730** is a hook and loop type coupler, where hook type material is coupled to one of the retention flaps and loop type material is coupled to the remaining retention flap.

In an alternative embodiment, the retention flaps are coupled together via another releasable coupling device, such as a snap, a button, or a hook. In another alternative embodiment, the retention flaps are coupled together via a more permanent method, such as adhesive, or stitching. In yet another alternative embodiment, the retention flaps are integrally formed by a single piece of material. In yet another embodiment, the upper cap can be a strap configured to define a top portion of the cavity in which the frame is retained. Alternatively, each retention flap can be one or more straps or cords that individually wrap around a respective support member of the frame to maintain the position of the shade relative to the frame.

The tethering lines **1740** and **1742** are configured to couple the shade **1710** to the front frame portion **1705** of the support **1700**. First ends **1739** and **1741** of each of the tethering lines **1740** and **1742**, respectively, are coupled to the second end **1713** of the shade **1710**. Any known method can be used to couple the first ends **1739** and **1741** of the tethering lines **1740** and **1742** to the shade **1710**. In one embodiment, the tethering lines **1740** and **1742** are sewn to the shade **1710**. In another embodiment, the tethering lines **1740** and **1742** are removably coupled to the shade **1710**.

In the illustrated embodiment, second ends **1737** and **1743** of the tethering lines **1740** and **1742**, respectively, are releasably coupled to the support **1700**. Any known method can be used to couple the tethering lines **1740** and **1742** to the support **1700**. In one embodiment, the tethering lines **1740** and **1742** are tied to the support **1700**. In another embodiment, the tethering lines **1740** and **1742** include couplers, such as clips or hooks, that releasably fasten the tethering lines to the support **1700**. In an alternative embodiment, the tethering lines **1740** and **1742** extend to a support surface on which the support **1700** rests, and the second ends **1743** and **1737** include devices, such as anchors, that releasably couple the tethering lines to the support surface.

As illustrated in FIG. **49**, the shade **1710** has a longitudinal line **1780** that extends between ends **1711** and **1713**. The shade **1710** also has a lateral line **1782** that extends substantially perpendicularly to the longitudinal line **1780**. When the shade **1710** is in an expanded configuration, the shade has a surface that is defined by the longitudinal and lateral lines **1780** and **1782**. The shade **1710** can have a shape defined so that the shade **1710** is maintained off the user's head while the user is sitting in the support.

In the illustrated embodiment, the resilient portion **1716** provides support to the shade **1710** and stiffens the shade **1710** so as to increase the resistance of the shade **1710** to bending or sagging out of its expanded configuration surface. In particular, the resilient portion **1716** increases the stiffness of the shade **1710** along the longitudinal line **1780**. The resilient portion **1716** can increase the stiffness along all or only a portion of the shade **1710** along the longitudinal line **1780**. Similarly, the resilient portion **1716** increases the stiffness of the shade **1710** along the lateral line **1782**. The resilient portion **1716** can increase the stiffness along all or only a portion of the shade **1710** along the horizontal line **1782**.

In the illustrated embodiment, the resilient portion **1716** is made from a different material than the membrane portion of the shade **1710**. In one embodiment, the resilient portion **1716** is made of a flexible material, such as rubber. In other embodiments, the resilient portion is made of a semi-rigid or rigid material, such as plastic or metal. In other embodiments, the resilient portion can be a metal frame, flexible hoop or multiple separate components (e.g., batten-like rods). While the resilient portion is illustrated as being substantially circular, the resilient portion can have any geometric shape, such as oval, rectangular, or square.

In an alternative embodiment, the resilient portion may be a separate member that can be releasably or fixedly coupled to the shade. In another alternative embodiment, the frame portion is configured to provide sufficient stiffness to the shade along the longitudinal and horizontal lines such that a resilient portion is not necessary.

Support member **1790** also supports to the shade **1710** and stiffens the shade **1710** so as to increase the resistance of the shade **1710** to bending or sagging out of its expanded configuration surface. In particular, the support member **1790** increases the stiffness of the shade **1710** along the lateral line **1782**. The resilient portion **1716** can increase the stiffness along all or only a portion of the shade **1710** along the horizontal line **1782**. Support member **1790** can be, for example, a rod made of appropriate material such as plastic or metal. FIG. **50** shows an example where the support member **1790** is a collapsible rod having an elastic member inside the hollow tubing. Note that support member **1790** can be used with or without resilient member **1716**. Similarly, the resilient member **1716** can be used alone without support member **1790**.

Another embodiment of the invention is illustrated in FIGS. **53-56**. In this embodiment, a support **2000** has a frame **2002** that can be placed in an expanded configuration and in a collapsed configuration. The frame **2002**, while in an expanded configuration, can be placed in an upright position and in a reclined position. The frame **2002** has a rear frame portion **2004** that includes a pair of support members **2010** and **2012** and a coupler **2030**. The frame **2002** also has two side support members **2020** and **2022** that are pivotally coupled to the coupler **2030** as described below.

In the illustrated embodiment, the support members **2010** and **2012** are hollow metal tubes with a circular cross-section, but as described above for support members **1512** and **1514**, the support members **2010** and **2012** can be made of different materials and have different cross-sectional shapes.

In the illustrated embodiment, support members **2010** and **2012** are connected together by a link **2014**. Link **2014** includes a lower portion **2016** that engages the coupler **2030** as described below. In one embodiment, the link **2014** and the support members **2010** and **2012** can be integrally formed. In one embodiment, the link can be a linear member.

As illustrated in FIGS. **53A** and **54A**, the coupler **2030** includes mounting portions **2040** and **2050** and an adjustment portion **2060**. In the illustrated embodiment, the mounting

portions **2040** and **2050** are mounted on opposite sides of and at an angle with respect to the adjustment portion **2060**.

Mounting portion **2040** includes a pair of walls **2042** and **2044** that define a cavity **2046** therebetween. Each of the walls **2042** and **2044** includes an opening **2048** through which a connector, such as a rivet (not shown), can be inserted to couple the lower end of the support member **2020** to the mounting portion **2040**.

Similarly, mounting portion **2050** includes a pair of walls **2052** and **2054** that define a cavity **2056** therebetween. Each of the walls **2052** and **2054** includes an opening **2058** through which a connector, such as a rivet (not shown), can be inserted to couple the lower end of the support member **2022** to the mounting portion **2050**.

An alternative embodiment of a coupler is illustrated in FIGS. **53B** and **54B**. The coupler **2030'** includes the same components as coupler **2030** with the exception of the mounting portions. As illustrated, mounting portions **2040'** and **2050'** have a different orientation as compared to mounting portions **2040** and **2050**. In this embodiment, mounting portion **2040'** includes an upper wall **2041** and a lower wall (not shown) through which a fastener **2043**, such as a screw or rivet, can be inserted to couple the support member **2020** to the coupler **2030'**. Similarly, mounting portion **2050'** includes an upper wall **2051** and a lower wall **2055** through which a fastener **2053**, such as a screw or rivet, can be inserted to couple the support member **2022** to the coupler **2030'**. In alternative embodiments, the mounting portions of the coupler may be oriented at angle with respect to the support surface on which the coupler is placed.

As illustrated in FIGS. **55** and **56**, the adjustment portion **2060** includes a central opening or slot **2062** through which the lower portion **2016** of the link **2014** passes. The opening **2062** is configured to allow the lower portion **2016** to move along the length of the adjustment portion **2060** of the coupler **2030**. Side support members **2020** and **2022** are not illustrated in FIGS. **55** and **56** for reasons of simplicity only.

In the illustrated embodiment, the adjustment portion **2060** includes a lower inner surface **2063** that has several ridges or teeth **2064** that defines notches **2066** therebetween. The ridges **2064** are configured to retain the lower portion **2016** in one of the notches **2066**. Each notch **2066** corresponds to a different angle of inclination of the support members **2010** and **2012** and the frame **2002**. Each notch **2066** defines a retaining position in which the lower portion **2016** of the link **2014** can be retained. While the illustrated embodiment of the adjustment portion **2060** includes five ridges **2064** that define six notches **2066**, any number of ridges **2064** and notches **2066** can be provided on the adjustment portion **2060**. Similarly, the adjustment portion **2060** can be any length.

As best illustrated in FIGS. **55** and **56**, the rear frame portion **2004** can be pivoted with respect to the coupler **2030** to convert the frame **2002** from an upright position to a reclined position. Support member **2010** functions in a similar manner as support member **2012**, and thus only the movements of support member **2012** are illustrated and discussed in detail. To recline the frame **2002**, the support member **2012** is lifted from its initial upright position (see FIG. **55**) on the coupler **2030**. The lower portion **2016** of the support member **2012** can be moved along the slot **2062** of the coupler **2030** to the desired position. The support member **2012** and link **2014** can be lowered so that lower portion **2016** of link **2014** engages a notch **2066** on the coupler **2030**. The steps of this process can be reversed to convert the frame **2002** from a reclined position to an upright position.

Another embodiment of the invention is illustrated in FIGS. **57A-60**. In this embodiment, a support **2100** has a

frame 2101, a coupler 2150, tension members 2110 and 2112, elongate members 2130 and 2140, slide plate 2105 and slide-plate member 2106. Similar to the above-described embodiments, the frame 2101 can be placed in an expanded configuration and in a collapsed configuration. Also similar to the above-described embodiments, each of the tension members 2110 and 2112 can be placed in two positions. The tension members 2110 and 2112 can be placed in a first position when the frame 2101 is in its expanded configuration to provide supports for the arms of a user. In addition, the tension members 2110 and 2112 can be placed in a second position when the frame 2101 is in its collapsed configuration to serve as shoulder straps when support 2100 is being transported on the user's back.

Elongate members 2130 and 2140 are structurally similar to each other and to elongate members 1630 and 1632 described above. Note that although the elongate members 2130 and 2140 are shown as straps, elongate members can be cables, cords or any appropriate type of material that can be coupled to coupler 2150 and can be used to form a shoulder strap or just be used for adjustment.

Elongate member 2130 has a first end 2132 and a second end 2134. The first end 2132 of the elongate member 2130 can be formed into a loop that can be grasped by the user. The second end 2134 of the elongate member 2130 is coupled to the coupler 2150. Similarly, elongate member 2140 has a first end 2142 and a second end 2144. The first end 2142 of the elongate member 2140 can be formed into a loop that can be grasped by the user. The second end 2144 of the elongate member 2140 is coupled to the coupler 2150.

In the illustrated embodiment, the second end 2134 of elongate member 2130 includes the male portion 2136 of a buckle. The male portion 2136 can be coupled to a corresponding female portion of the buckle (not shown) on tension member 2112 when tension member 2112 is disconnected from the front frame portion. Similarly, the second end 2144 of elongate member 2140 includes the male portion 2146 of a buckle. The male portion 2146 can be coupled to a corresponding female portion of the buckle (not shown) on tension member 2110 when tension member 2110 is disconnected from the front frame portion.

As illustrated in FIGS. 57A, and 58-60, the coupler 2150 includes a front surface 2151, a rear surface 2152, an upper end 2153, and a lower end 2154. The lower end 2154 engages the support surface on which support 2100 is placed. The coupler 2150 includes mounting portions 2160 and 2162 proximate to upper end 2153 to which support members 2102 and 2104 are coupled, respectively. In one embodiment, connectors, such as bolts or rivets, can be used to couple the lower ends of support members 2102 and 2104 to the mounting portions 2160 and 2162 of the coupler 2150. In alternative embodiments, any device that can movably couple the support members 2102 and 2104 to coupler 2150 can be used.

As best illustrated in FIGS. 59 and 60, coupler 2150 includes openings 2164 and 2166, a pair of slots 2168 and 2170 and a pair of slots 2172 and 2174. Openings 2164 and 2166 and slots 2168, 2170, 2172 and 2174 are configured to receive elongate members 2130 and 2140, respectively. As illustrated in FIG. 57A, elongate member 2140 passes through slot 2174, through opening 2166, and through slot 2170. Elongate member passes through slot 2168. By connecting elongate members 2130 and 2140 to different parts of the coupler 2150, movement of either of the elongate members 2130 and 2140 can cause movement of the coupler 2150. While the illustrated embodiment includes a sliding connection between the elongate members 2130 and 2140 and the

coupler 2150, any type of connection between the elongate members 2130 and 2140 and the coupler 2150 can be used.

An alternative embodiment of a coupler is illustrated in FIG. 57B. In this embodiment, the coupler 2150' only includes a pair of slots and a pair of openings. As illustrated, elongate member 2140 passes around the lower end 2154 of the coupler 2150', through opening 2166 and through slot 2170. Elongate member 2130 passes through slot 2168. By connecting elongate members 2130 and 2140 to different parts of the coupler 2150', movement of either of the elongate members 2130 and 2140 can cause movement of the coupler 2150'. While the illustrated embodiment includes a sliding connection between the elongate members 2130 and 2140 and the coupler 2150', any type of connection between the elongate members 2130 and 2140 and the coupler 2150' can be used.

In alternative embodiments, elongate members 2130 and 2140 can be coupled to the coupler 2150' in a variety of ways. For example, elongate member 2130 could pass through the slot 2172 near the lower end 2154 of the coupler 2150, through opening 2150, through opening 2164 and through slot 2168. Elongate member 2140 can then pass through slot 2170 only.

Returning to the illustrated embodiment, side or forwardly extending support members 2120 and 2122 are pivotally coupled to the coupler 2150. As illustrated in FIG. 59, side support member 2120 is coupled to the coupler 2150 by connector 2180. Similarly, side support member 2122 is coupled to the coupler 2150 by connector 2182. It can be appreciated that any connectors or fasteners of the supports described herein can be any type of connector, such as a rivet, screw, bolt, etc.

In alternative embodiments, the support members 2102 and 2104 and the side support members 2120 and 2122 can be coupled to various locations on the coupler 2150. For example, the support members 2102 and 2104 can be coupled proximate to the middle of the coupler 2150 and the side support members 2120 and 2122 can be coupled proximate to the upper end of the coupler 2150. Alternatively, the support members 2102 and 2104 can be coupled along the lower end 2154 of the coupler 2150 and the side support members 2120 and 2122 can be coupled to the upper end 2153 or the along the middle of the coupler 2150. In one embodiment, the support members 2102 and 2104 can be coupled to the coupler 2150 on its rear surface.

In one embodiment, elongate members 2130 and 2140 can be coupled together or formed integrally in a continuous loop that is coupled to the coupler 2150. The continuous elongate member loop can be coupled to the coupler 2150 in any manner that facilitates movement of the coupler 2150 in response to movement of any the loop. For example, when the user pulls on a first portion of the loop, the coupler 2150 is moved in a first direction. When the user pulls on a second portion of the loop, the coupler 2150 is moved in a second direction.

As illustrated in FIG. 57A, the support 2100 can be adjusted to a recline position by pulling forward on the elongate member 2130. When the user pulls elongate member 2130 along the direction of arrow "A," the upper end 2153 of the coupler 2150 moves forwardly and the lower end 2154 of the coupler 2150 moves rearwardly about pivots 2180 and 2182 of the coupler 2150. As the coupler 2150 rotates to its reclined position in FIG. 57A, the support members 2102 and 2104 pivot relative to the coupler 2150 to their reclined positions. As the coupler 2150 is moved, elongate member 2140 moves along the direction of arrow "B." In other words, because elongate member 2140 is threaded through slot 2174,

21

through opening 2166 and through slot 2170, elongate member 2140 moves coupler 2150 in the direction of arrow "B" when elongate member 2140 is pulled in the direction of arrow "A."

As illustrated in FIG. 58, the support 2100 can be adjusted to an upright position by pulling forwardly on the elongate member 2140. When the user pulls the elongate member 2140 along the direction of arrow "D," the lower end 2154 of the coupler 2150 moves forwardly and the upper end 2153 of the coupler 2150 moves rearwardly about pivots 2180 and 2182. As the coupler 2150 rotates to its upright position in FIG. 58, the support members 2102 and 2104 pivot relative to the coupler 2150 to their upright positions. As the coupler 2150 is moved, elongate member 2130 also moves along the direction of arrow "C." While the user can pull his weight upwardly to make the movement of the coupler 2150 easier, it is not necessary for the user to shift any weight to move the coupler 2150.

The coupler 2150 functions as a single joint to which the support members 2102 and 2104 and the side support members 2120 and 2122 are mounted. Movement of the coupler 2150 causes relative movement of the support members 2102 and 2104 and side support members 2120 and 2122 simultaneously.

In the illustrated embodiment, end 2132 of elongate member 2130 and end 2142 of elongate member 2140 are resting on part of the front frame portion. In alternative embodiments, ends 2132 and 2142 can be located anywhere along the frame 2101 as long as a user can grasp the ends 2132 and 2142 to adjust the frame 2101 and the support 2100.

In an alternative embodiment, the support can include four elongate members. For example, two elongate members can be coupled to the coupler and can be used and pull straps to change the angle of inclination of the support. Two elongate members can be coupled proximate to the upper portion and to the lower portion of the rear frame portion and can be used as carrying straps.

Another embodiment of the invention is illustrated in FIGS. 61-63. In this embodiment, a support 2200 has a frame 2201, a coupler 2250, tension members 2210 and 2212, and elongate members 2230 and 2240. Most of the components of support 2200 are similar to the corresponding components of support 2100. Similar to the above-described embodiments, the frame 2201 can be placed in an expanded configuration and in a collapsed configuration. Also similar to the above-described embodiments, each of the tension members 2210 and 2212 can be placed in two positions. The tension members 2210 and 2212 can be placed in a first position when the frame 2201 is in its expanded configuration to provide supports for the arms of a user. In addition, the tension members 2210 and 2212 can be placed in a second position when the frame 2201 is in its collapsed configuration to serve as shoulder straps when support 2200 is being transported on the user's back.

In the illustrated embodiment, support 2200 includes an adjustment mechanism 2260. Adjustment mechanism 2260 can be used to adjust the angle of inclination of the frame 2201. As illustrated in FIG. 61, elongate member 2230 has a first end 2232 and a second end 2234. Similarly, elongate member 2240 has a first end 2242 and a second end 2244.

The first end 2232 of the elongate member 2230 is coupled to the adjustment mechanism 2260 and the second end 2234 is coupled to the coupler 2250. The first end 2242 of the elongate member 2240 is coupled to the adjustment mechanism 2260 and the second end 2244 is coupled to the coupler 2250. First ends 2232 and 2242 of elongate members 2230 and 2240 are coupled to the adjustment mechanism via con-

22

nectors, such as rivets or bolts. In alternative embodiments, any type of fasteners or method of coupling different parts, such as gluing, welding, etc., can be used to couple the elongate members to the adjustment mechanism.

Adjustment mechanism 2260 is mounted for movement relative to the frame 2201. In one embodiment, adjustment mechanism 2260 is pivotally mounted to the frame 2201. While the adjustment mechanism 2260 is illustrated as coupled to the front of the frame 2201, the adjustment mechanism 2260 can be mounted at any location on the frame 2201 as long as the user of the support 2200 can manipulate the adjustment mechanism 2260. For example, the adjustment mechanism 2260 can be mounted to a rear portion of the frame 2201.

An embodiment of an adjustment mechanism is illustrated in FIG. 63. In this embodiment, the adjustment mechanism 2260 includes a mount 2262 that is coupled to the frame 2201. In one embodiment, the mount 2262 is a separate piece that can be coupled to any part of the frame 2201. For example, the mount 2262 can be coupled to the front frame portion 2206 of the frame 2201. Mount 2262 can be coupled to the front frame portion 2206 using any conventional fastener or coupling techniques. In alternative embodiments, the mount can be integrally formed on the frame or the adjustment mechanism can be directly coupled to the frame.

The adjustment mechanism 2260 includes a link 2264 that is pivotally coupled to the mount 2262 for rotation about the pivot point 2272. Link 2264 can include a handle 2266 that can be grasped by the user. In the illustrated embodiment, link 2264 includes openings 2268 and 2270 that are configured to receive fasteners (not shown) that couple the elongate members 2230 and 2240 to the link 2264.

In the illustrated embodiment, when the adjustment mechanism 2260 is pivoted about pivot point 2272 along the direction of arrow "E," the lower end 2276 of the link 2264 moves forwardly and the upper end 2274 moves rearwardly (see FIG. 61). As the lower end 2276 moves forwardly, elongate member 2240 is pulled in the same direction and the coupler 2250 can be moved to its upright position, thereby changing the inclination of the frame 2201. While the user can pull his weight upwardly to make the movement of the coupler 2250 easier, it is not necessary for the user to shift any weight to move the coupler 2250.

When the adjustment mechanism 2260 is pivoted about pivot point 2272 along the direction of arrow "F," the upper end 2274 of the link 2264 moves forwardly and the lower end 2276 moves rearwardly (see FIG. 62). As the upper end 2274 moves forwardly, elongate member 2230 is pulled in the same direction. If the user lifts his weight up from the support 2200, the coupler 2250 can be moved to its reclined position, thereby changing the inclination of the frame 2201.

As discussed above, the movements of elongate members 2230 and 2240 relative to each other cause movement of the coupler 2250. Thus, while the adjustment mechanism 2260 is illustrated as having an elongate link, any type of structure that facilitates the movement of elongate members 2230 and 2240 relative to each other can be used. For example, any structure that can be manipulated to selectively move one elongate member with respect to the other elongate member can be used.

In an alternative embodiment, the adjustment mechanism can include one or more members. For example, the adjustment mechanism can include two independently mounted pieces. Each elongate member can be coupled to a separate piece of the adjustment mechanism and can be moved independent of the other elongate member.

23

In one embodiment, the coupler **2250** of support **2200** can include additional slots corresponding to slots **2172** and **2174** of coupler **2150** described above. In other embodiments, couplers **2150** and **2250** can include any number of slots and/or openings.

An alternative embodiment of a support is illustrated in FIGS. **64** and **65**. In this embodiment, the support **2300** includes support members **2302** and **2304**, side support members **2306** and **2308**, and a coupler **2310**. Coupler **2310** is pivotally coupled to support members **2302** and **2304** and side support members **2306** and **2308**. Coupler **2310** can be positioned in an upright position as illustrated in FIG. **64** and in a reclined position as illustrated in FIG. **65**.

In this embodiment, the coupler **2310** can be used with or without elongate members. For example, the coupler **2310** can be used with one or more elongate members in a similar manner as described above with respect to coupler **2250**. Also, coupler **2310** can be moved without any elongate members, as described in detail below. While this embodiment is illustrated without elongate members coupled to the coupler **2310**, it can be appreciated that coupler **2310** can be used with any type of elongate members as described above.

In this embodiment, coupler **2310** includes an upper end **2312** to which support members **2302** and **2304** are coupled. Coupler **2310** has a lower end **2314** with a rounded bottom surface **2316** that engages the support surface on which support **2300** is placed. As illustrated, the lower end **2314** is larger than the upper end **2312**. In the illustrated embodiment, the radius of curvature of the lower end **2314** is greater than the radius of curvature of the upper end **2312**. The rounded bottom surface **2316** facilitates the movement of the coupler **2310** between the upright and reclined positions. It is not necessary that the lower end **2314** be rounded and larger than the upper end **2312** for the coupler **2350** to operate.

The bottom surface **2316** includes several ridges **2318** that facilitate the movement of the lower end **2314** and bottom surface **2316** along the support surface. For example, if the support **2300** is deployed on a sandy support surface, the ridges **2318** provide increased friction with the support surface, thereby facilitating the movement of the coupler **2310** between its upright and reclined positions.

In order to move the coupler **2310** between these positions, elongate members can be pulled to move the coupler **2310** in a particular direction. In an alternative embodiment, the coupler can be moved when the occupant shifts his weight on the support. For example, when the occupant shifts his weight from the back to the front of the support **2300**, the coupler **2310** is moved from its upright position (see FIG. **64**) to its reclined position (see FIG. **65**). The process can be reversed to move the coupler **2310** from its reclined position to its upright position.

In an alternative embodiment, the coupler can be formed without any openings or slots. In such an embodiment, the coupler is moved in response to the shifting of the occupant's weight.

An alternative embodiment of a support is illustrated in FIGS. **66** and **67**. In this embodiment, the support **2400** includes support members **2402** and **2404**, side support members **2406** and **2408**, and a coupler **2410**.

Coupler **2410** includes a lower portion **2420** and an upper portion **2440**. Upper portion **2440** is pivotally coupled to the lower portion **2420**. Lower portion **2420** has a base **2421** that remains in contact with the support surface on which the support **2400** is placed. Base **2421**, for example, can be in stationary, non-pivoting contact with the support surface on which the support **2400** is placed. Upper portion **2440** is

24

movable relative to the lower portion **2420** between a reclined position (see FIG. **66**) and an upright position (see FIG. **67**).

Lower portion **2420** includes mounting portions **2422** and **2424** to which side support members **2406** and **2408** are coupled. Mounting portions **2422** and **2424** include cavities **2426** and **2428**, respectively, into which the lower ends of side support members **2406** and **2408** are inserted. Mounting portion **2422** includes an inner wall surface **2430**. Similarly, mounting portion **2424** includes an inner wall surface **2432**.

Upper portion **2440** includes mounting portions **2442** and **2444**. Mounting portion **2442** has an opening **2446** into which support member **2402** is inserted. Support member **2402** is pivotally coupled to mounting portion **2442**, for example, via any conventional fastener, such as a rivet. Similarly, mounting portion **2444** has an opening **2448** into which support member **2404** is inserted. Support member **2404** is pivotally coupled to mounting portion **2444**, for example, via any conventional fastener, such as a rivet.

Upper portion **2440** includes a connecting portion **2450** that is coupled to the lower portion **2420** of the coupler **2410**. The connecting portion **2450** has extensions **2452** and **2454** that are coupled to the lower portion **2420**. In the illustrated embodiment, the extensions **2452** and **2454** are coupled to the inner wall surfaces **2430** and **2432**, respectively, of the lower portion **2420**. Connectors **2460** and **2462**, such as rivets, can be used to pivotally couple the upper portion extensions **2452** and **2454** to the lower portion **2420**.

In the illustrated embodiment, the lower portion **2420** has several openings **2470** that pass through the lower portion **2420**. Openings **2470** reduce the material in the lower portion **2420**. Also, when the support **2400** is used on a sandy support surface, sand can pass through the openings **2470**, thereby allowing the lower portion **2420** of the coupler **2410** to settle on the support surface. In alternative embodiments, the lower portion **2420** may not include any openings or the lower portion **2420** can include any number of openings **2470**.

In an alternative embodiment, the upper portion of the coupler can be moved relative to the lower portion of the coupler using one or more elongate members. The elongate members can be coupled to the upper portion of the coupler to move the coupler and position the upper portion of the coupler into its reclined position (see FIG. **66**) and into its upright position (see FIG. **67**). For example, an elongate member can be couple to the upper portion and another elongate member can pass around a support member and then be coupled to the upper portion. Movement of either elongate member can cause movement of the upper portion.

In alternative embodiments, the couplers of the supports can be any size, shape or configuration.

In alternative embodiment, the elongate members for a support can be rigid.

A support according to an alternative embodiment of the invention is illustrated in FIGS. **68-84**. In this embodiment, support **2500** includes several components that are structurally and functionally similar to components of the various embodiments of the supports previously discussed. Accordingly, the above descriptions of such components are incorporated in this section.

As illustrated in FIG. **68**, support **2500** includes a frame **2510** and a seat or support membrane **2570**. The frame **2510** can be disposed in a deployed configuration **2502** (see FIGS. **68-69**) and in a collapsed configuration **2504** (see FIGS. **73-74**).

The frame **2510** includes a front frame portion **2512** and a rear frame portion **2522**. The front frame portion **2512** includes front legs **2514** and **2516** that have upper ends **2518** and **2520**, respectively. The rear frame portion **2522** includes

25

rear legs **2524** and **2526** that have upper ends **2528** and **2532** and lower ends **2530** and **2534**, respectively.

In the illustrated embodiment, the rear frame portion **2522** includes an elongate member or connector portion **2536** that is coupled to the lower ends **2530** and **2534** of the rear legs **2524** and **2526**, respectively. The connector portion **2536** can be coupled to the rear legs **2524** and **2526** by one or more connectors **2538**, which can be, for example, any conventional connector mechanism, such as a bolt, rivet, screw, etc. In an alternative embodiment, the rear legs and the connector portion of the rear frame portion can be integrally formed.

The frame **2510** includes side legs **2540**, **2542**, **2544** and **2546** that extend between the front frame portion **2512** and the rear frame portion **2522**. Each of the side legs **2540**, **2542**, **2544** and **2546** extends between the front frame portion **2512** and the rear frame portion **2522**, thereby facilitating the collapsing of the frame **2510**. When the frame **2510** is in a collapsed configuration, the legs of the frame **2510** are substantially parallel (see FIGS. **73** and **74**).

Side leg **2542** has an upper end **2542b** that is pivotally coupled to the guide plate **2566** and a lower end **2542a** that is coupled to a foot **2511a**. Similarly, side leg **2546** has an upper end that is pivotally coupled to the guide plate **2566** and a lower end that is coupled to a foot **2511b**. Side leg **2540** has an upper end **2540a** that is coupled to the front frame portion **2512**. Similarly, side leg **2544** has an upper end that is coupled to the front frame portion **2512**.

Referring to FIG. **68**, the support **2500** includes a base or foot **2700**. The base **2700** includes slots **2722** and **2742** formed therein. The side legs **2540** and **2544** are coupled to the base **2700**. For example, the lower end **2540b** of side leg **2540** is coupled to the base **2700**. Similarly, the lower end (not shown) of side leg **2544** is coupled to the base **2700**.

The rear frame portion **2522** is movably coupled to the base **2700**. In this embodiment, the connector portion **2536** is inserted into the slots **2722** and **2742** and moves along the slots **2722** and **2742**. The inclination of the rear frame portion **2522**, and thus the support **2500**, can be adjusted by moving the connector portion **2536** along the slots **2722** and **2742** between an upright configuration **2508** (see FIGS. **68**, **69** and **79**) and a reclined configuration **2506** (see FIG. **80**). The base **2700** and its function are described in detail later with respect to FIGS. **75-84**.

The support **2500** also includes tension members **2550** and **2560** coupled to the frame **2510**. Tension member **2550** has a first end **2552** to which the front leg **2514** can be coupled and a second end **2554** that is slidably coupled to the rear leg **2524**. The first end **2552** is removably coupled to the front leg **2514**. Similarly, tension member **2560** has a first end **2562** to which the front leg **2516** can be coupled and a second end **2564** that is slidably coupled to the rear leg **2526**. The first end **2562** is removably coupled to the front leg **2516**.

The tension members **2550** and **2560** are movable between coupled positions **2556** (see FIGS. **68**) and decoupled positions **2558** (see FIG. **69**). In their decoupled positions **2558**, each of the tension members **2550** and **2560** can be coupled to a connector **2568** (see FIG. **69**), such as a buckle on a strap, that is coupled to the frame **2510**. In one embodiment, the connector **2568** is coupled to the base **2700**. The connector **2568** can be configured as discussed above with respect to previous embodiments. When a tension member is connected to a connector, the tension member can be used as a carrying strap to transport the support **2500**.

As shown in FIG. **68**, the support **2500** includes a guide plate **2566** that is configured to move along the rear legs **2524** and **2526**. Attached to the guide plate **2566** is a pull cord **2567** that can be grasped by a user to move the guide plate **2566**

26

upwardly to collapse the frame **2510**. In the illustrated embodiment, the guide plate **2566** extends upwardly a distance that is sufficient to support the rear ends of the tension members **2550** and **2560** at locations that enable the tension members to be used as arm rests. The cords that were previously described with respect to other embodiments as retaining the rear ends of tension members at particular locations are no longer needed for this embodiment.

The seat **2570** of the support **2500** is supported on the frame **2510**. As illustrated in FIG. **68**, the seat **2570** can be supported on the front frame portion **2512** and the rear frame portion **2522**.

As illustrated in FIG. **69**, the seat **2570** includes a body portion **2572**. The body portion **2572** includes a front portion **2574** and a rear portion **2578**. The front portion **2574** includes a pair of openings **2576** through which the upper ends **2518** and **2520** of front legs **2514** and **2516**, respectively, are inserted. The rear portion **2578** is coupled to the rear frame portion **2522** proximate to an upper end of the rear frame portion **2522**.

The seat **2570** has a perimeter **2580** that defines the outer edge **2586** (see FIG. **70**) of the seat **2570**. In one embodiment, the seat **2570** includes a binding **2588** that is attached to the seat **2570** along the perimeter **2580**. The seat **2570** can be made from any flexible material that provides sufficient strength to support a user.

In the illustrated embodiment, the support **2500** includes side portions **2600** and **2620**. The side portions **2600** and **2620** are coupled to the body portion **2572** of the seat **2570**. In one embodiment, the side portions **2600** and **2620** are pieces of material that can be referred to as a retainer, flaps, closure mechanisms, etc. The side portions **2600** and **2620** can be made, for example, of the same material as body portion **2572**.

In an alternative embodiment, side portions **2600** and **2620** and body portion **2572** can be made of different materials. The side portions **2600** and **2620** can vary in size and configuration. The side portions **2600** and **2620** do not have to enclose any particular portion of the frame. In alternative embodiments, each side portion can be an elongate member, such as a cord, a rope, a string, a strap, an elastic member, etc. Each of these side portion variations can be formed integrally with the frame and/or seat. Alternatively, each of these side portion variations can be coupled to the frame and/or to the seat.

Side portion **2600** can be located proximate to a first portion **2582** of the perimeter **2580** of the seat **2570**. Side portion **2620** can be located proximate to a second portion **2584** of the perimeter **2580** of the seat **2570**. While first portion **2582** and second portion **2584** are located along the upper edge of the seat **2570**, the portions **2582** and **2584** can be located at any location along the perimeter that enables the side portions **2600** and **2620** to be used as closures or retainers as described herein. In an alternative embodiment, the first portion **2582** and the second portion **2584** can be coupled along the upper part of the seat **2570** at locations spaced apart from the edge.

In the illustrated embodiment, side portion **2600** is coupled to the body portion **2572** of the seat **2570** in the binding **2588**. Similarly, side portion **2620** is also coupled to the body portion **2572** of the seat **2570** in the binding **2588**. By coupling the side portions using the bindings, the side portions naturally fall or rest rearwardly behind the body portion **2572** in their open positions **2648** and **2650**, which correspond to an open configuration **2644** (see FIGS. **68** and **69**).

One embodiment of the coupling of a side portion to the seat is illustrated in detail in FIG. **70**. Side portion **2600** includes an inner edge **2604** and outer edges **2606**, **2608** and

2610 that collectively form a perimeter 2602 of the side portion 2600. Side portion 2600 includes a coupling mechanism 2640 that is coupled to an inner surface 2601 of the side portion 2600. In an alternative embodiment, the coupling mechanism 2640 is coupled to an outer surface of side portion 2600.

Side portion 2620 is structurally similar to side portion 2600 and has a coupling mechanism 2642 attached to its outer surface. In an alternative embodiment, the coupling mechanism 2642 is coupled to an inner surface of side portion 2620. The coupling mechanisms 2640 and 2642 (not shown in FIG. 70) can engage each other when the side portions are positioned proximate to each other as discussed in detail later.

In various embodiments, any type of coupling mechanisms can be used. Some examples of coupling mechanisms include a hook, a plastic clip or buckle, etc. In an alternative embodiment, a single side portion can be provided that is configured to couple to a connector or coupling mechanism.

In the illustrated embodiment, side portions 2600 and 2620 are coupled to the body portion 2572 of the seat 2570 in a similar manner. Therefore, only the coupling of the side portion 2600 and the body portion 2572 is discussed in detail here. As noted above, side portions 2600 and 2620 can be coupled to the frame 2500.

As illustrated in FIG. 70, the body portion 2572 includes an edge 2586 that forms part of the perimeter of the body portion 2572. During the assembly of the components, side portion 2600 is placed proximate to the body portion 2572 so that the inner edge 2604 is proximate to edge 2586. In an alternative embodiment, side portion 2600 is coupled to the body portion 2572 at a location spaced apart from the edge 2586.

In one embodiment, a conventional binding 2588 is attached, such as by sewing or an adhesive, to the side portion 2600 and the body portion 2572 to couple them together. The flexibility of the side portion 2600 and the use of a binding to couple the side portion 2600 and the seat 2570 cause the side portion 2600 to hang downwardly and toward the rear of the support 2500, and thereby out of the way of the user or the occupant of the support 2500 (see FIG. 68).

In an alternative embodiment, no binding is used. In this example, the side portion 2600 and the body portion 2572 can be sewn together without any binding. The side portion 2600 still hangs or extends rearwardly relative to the support 2500.

In one embodiment, side portion 2600 includes a binding 2612 that is attached around the outer edges 2606, 2608 and 2610. Binding 2612 reduces the likelihood of fraying of the outer edges 2606, 2608 and 2610. Side portion 2620 can have a similar binding.

A seat according to an alternative embodiment of the invention is illustrated in FIG. 71. In this embodiment, seat 2900 is a single membrane that includes a body portion 2910 and side portions 2920 and 2930. Body portion 2910 includes openings (not shown) to receive the front legs of a frame.

The body portion 2910 and side portions 2920 and 2930 are integrally formed as a single piece of material. In alternative embodiments, the size and configuration of the side portions can vary. It is not necessary that the side portions have the same size and/or configuration.

In an alternative embodiment, each side portion can be folded back and a seam can be sewn along the lines 2940 and 2950 illustrated in FIG. 71. By sewing along these lines 2940 and 2950, the side portions 2920 and 2930 extend rearwardly with respect to the body portion 2910. In an alternative embodiment, a binding (not shown) can be located along a portion of each line 2940 and 2950 and connected thereto (i.e., sewing, adhesive, etc.).

A seat according to an alternative embodiment of the invention is illustrated in FIG. 72. In this embodiment, seat 3000 includes a body portion 3010 that has a front surface 3012. A separate piece of material 3020 is coupled to the body portion 3010. Body portion 3010 includes openings (not shown) to receive the front legs of the frame.

In this embodiment, the material 3020 is coupled to the rear surface of the body portion 3010 using any conventional technique or procedure, such as sewing, an adhesive, etc. In an alternative embodiment, the material 3020 can be coupled to the front surface 3012 of the body portion 3010. The material 3020 includes a first side portion 3022 proximate to one end and a second side portion 3024 proximate to another end.

In an alternative embodiment, the sides of the separate piece of material 3020 can be folded back and a seam can be sewn along the lines 3030 and 3040 illustrated in FIG. 72. By sewing along these lines 3030 and 3040, the sides extend rearwardly with respect to the body portion 3010. In an alternative embodiment, a binding (not shown) can be located along a portion of each line 3030 and 3040 and connected thereto (i.e., sewing, adhesive, etc.).

Referring to FIGS. 73-74, a process of retaining the frame 2510 in its collapsed configuration is illustrated. Initially, the guide plate 2566 is moved upwardly to pull the frame legs together and collapse the frame 2510. The frame 2510 of support 2500 is illustrated in its collapsed configuration in FIGS. 73 and 74. The side portions 2600 and 2620 are positioned so that they extend outwardly from the collapsed frame 2510.

As illustrated in FIG. 73, side portion 2600 includes a coupling mechanism 2640, such as one of a hook type or loop type fastener. Similarly, side portion 2620 includes a coupling mechanism 2642, such as the other of a hook type or loop type fastener. The coupling mechanisms 2640 and 2642 are configured to engage each other and can be coupled to the side portions 2600 and 2620, respectively, using any conventional technique, such as, for example, sewing, an adhesive, etc.

In alternative embodiments, the coupling mechanisms can be any structure that can be used to couple the side portions 2600 and 2620 together. Other coupling mechanisms such as, for example, snaps, fasteners, connectors, etc. can be used. In one embodiment, only one of the side portions can include a coupling mechanism, such as a clip, that can be used to grip and hold a part of the other side portion.

Referring to FIG. 73, initially, either side portion 2600 or side portion 2620 is moved so that it wraps around a portion of the collapsed frame 2510. As illustrated, side portion 2620 is first wrapped around a portion of the frame 2510. Side portion 2620 is held in position while the side portion 2600 is wrapped around another portion of the collapsed frame 2510. The side portions 2600 and 2620 can be moved sequentially or simultaneously.

The side portions 2600 and 2620 are placed proximate to each other so that coupling mechanisms 2640 and 2642 engage each other. When the coupling mechanisms 2640 and 2642 are coupled together, as illustrated in FIG. 74, the side portions 2600 and 2620 are retained together and form a retainer or closure mechanism that retains the frame 2510 in its collapsed configuration 2504. Accordingly, side portions 2600 and 2620 can be collectively referred to as a retainer or a closure or enclosure mechanism.

The side portions 2600 and 2620 are illustrated in FIG. 74 in their closed positions 2652 and 2654 which correspond to a closed configuration 2646. As noted above, the sizes and configurations of the side portions 2600 and 2602 can vary as

long as the side portions can engage each other and retain the frame **2510** in its collapsed configuration **2504**.

In an alternative embodiment, the closure mechanism can include a single side portion instead of two side portions that engage each other. In such an embodiment, a single flap or side portion is coupled to the seat and has a sufficient size that enables the side portion to extend around the collapsed frame **2510**. The single side portion can be coupled to any part of the support that enables the side portion to maintain its position in which it retains the frame **2510** in its collapsed configuration.

A base of a support according to an embodiment of the invention is illustrated in FIGS. **75-78**. In this embodiment, base **2700** includes a housing **2702** that includes side walls **2710** and **2730** and a rear wall **2750**. The housing **2702** has extensions **2760** and **2780** coupled to either side of the housing **2702**.

In one embodiment, the side walls **2710** and **2730**, the rear wall **2750** and the extensions **2760** and **2780** are integrally formed. In an alternative embodiment, the side walls **2710** and **2730**, the rear wall **2750** and the extensions **2760** and **2780** can be formed separately and coupled together.

In one embodiment, side walls **2710** and **2730** have substantially similar structure. Each side wall includes an inner surface, an outer surface, an upper end, a lower end and a hole and a slot formed therein.

As illustrated in FIGS. **75-78**, side wall **2710** includes an outer surface **2712**, an inner surface **2714**, an upper end **2716**, a lower end, a hole **2720** extending through the side wall **2710**, and a slot **2722** extending along the upper end **2716** of the side wall **2710**. In this embodiment, slot **2722** has a front end **2724** and a rear end **2726**.

Similarly, side wall **2730** includes an inner surface **2732**, an outer surface **2734**, an upper end **2736**, a lower end **2738**, a hole **2740** extending through the side wall **2730**, and a slot **2742** extending along the upper end **2736** of the side wall **2730**. In this embodiment, slot **2742** has a front end **2744** and a rear end **2746**.

While the slots **2722** and **2742** are located proximate to the upper ends of the side walls **2710** and **2730**, respectively, the slots **2722** and **2742** can be located at any locations on the side walls **2710** and **2730** that allow a portion of the frame to travel along the slots **2722** and **2742**. In alternative embodiments, the slots **2722** and **2742** can have any shape, configuration or length (i.e., slots or ridges for adjustment).

In the illustrated embodiment, extension **2760** has a wall **2762** that forms an internal cavity **2775**. A front end **2764** of the wall **2762** defines a front opening **2776** and a rear end **2766** of the wall **2762** defines a rear opening **2778**. The wall **2762** has an upper portion **2770** that includes a hole **2771** therethrough. Similarly, the wall **2762** has a lower portion **2772** that includes a hole **2773** therethrough. Holes **2771** and **2773** are configured to receive a conventional fastener that passes through part of side leg **2540** to couple side leg **2540** to the base **2700**.

Similarly, extension **2780** has a wall **2782** that forms an internal cavity **2795**. A front end **2784** of the wall **2782** defines a front opening **2796** and a rear end **2786** of the wall **2782** defines a rear opening **2798**. The wall **2782** has an upper portion **2790** that includes a hole **2791** therethrough. Similarly, the wall **2782** has a lower portion **2792** that includes a hole **2793** therethrough. Holes **2791** and **2793** are configured to receive a conventional fastener that passes through part of side leg **2544** to couple side leg **2544** to the base **2700**.

Extensions **2760** and **2780** are disposed at an angle with respect to a horizontal plane. As illustrated in FIG. **76**, extension **2780** includes a longitudinal axis **2788** that is oriented at an angle with respect to a support surface on which the sup-

port **2500** is placed. The angle determines the angles at which side legs **2540** and **2544** extend from the rear frame portion **2522** to the front frame portion **2512**.

Each of the extensions **2760** and **2780** includes a tapered portion that engages a support surface on which the support **2500** is placed. As illustrated in FIG. **76**, extension **2780** includes a tapered portion **2794**. Extension **2760** includes a similar tapered portion (not shown).

As illustrated in FIGS. **75** and **76**, side wall **2730** includes an opening **2748**, the function of which is described later. Side wall **2710** includes a similar opening (not shown). The size and configuration of the openings in the side walls can vary.

The rear wall **2750** has an inner surface **2752**, an outer surface **2754** and openings **2756** and **2758** therethrough. Each of the openings **2756** and **2758** is configured to receive a strap that has a connector **2568** coupled thereto.

The process of reclining the support is illustrated in FIGS. **79** and **80**. As described above, the rear frame portion **2522** includes rear legs **2524** and **2526** and connector portion **2536**. Connector portion **2536** is slidably mounted for movement along slots **2722** and **2742** in side walls **2710** and **2730** of the base **2700**.

When the connector portion **2536** is located proximate to the rear ends of the slots **2722** and **2742**, the rear legs **2524** and **2526** are in their upright positions and the frame **2510** has an upright configuration **2549**. When the connector portion **2536** is located proximate to the front ends of the slots **2722** and **2742**, the rear legs **2524** and **2526** are in their reclined positions and the frame **2510** has a reclined configuration **2548**. It is to be understood that the terms "upright" and "reclined" are relative terms that are used to designate two different configurations. It is not necessary that the rear legs be exactly upright or perpendicular with a horizontal support surface when the legs are in their upright positions or the frame is in its upright configuration. The upright and reclined configurations of the frame are two configurations in which the rear frame portion is disposed at different angles with respect to the support surface on which the support is placed.

The support **2500** includes a recline mechanism **2800** as illustrated in FIGS. **79** and **80**. In this embodiment, the recline mechanism **2800** includes a biasing mechanism **2810** that is coupled to the base **2700**.

In one embodiment, the biasing mechanism **2810** has a first portion **2812** that is coupled to the base **2700** by being inserted into the slot **2748** on the base **2700**. The biasing mechanism **2810** includes a second portion **2814** that is wrapped around a portion of the rear frame portion **2522**, which in this embodiment, is the connector portion **2536**. The biasing mechanism **2810** includes a third portion **2816** that passes through openings **2740** and **2720** in side walls **2730** and **2710**, respectively. The biasing mechanism **2810** also includes a fourth portion **2818** that is wrapped around the connector portion **2536** and a fifth portion (not shown) that is inserted into an opening proximate to the bottom of side wall **2710** of the base **2700**.

In one embodiment, the biasing mechanism **2810** has two ends. In another embodiment, the biasing mechanism **2810** forms a continuous loop.

The biasing mechanism **2810** biases the connector portion **2536** downwardly and rearwardly in the slots **2722** and **2742** along the direction of arrow "G." In alternative embodiments, the biasing mechanism can be coupled to the base and the rear frame portion in any configuration that enables the biasing mechanism to bias the connector portion in a rearward and/or downward directions along the slots in the base.

In the illustrated embodiment, the biasing mechanism is an elastic member, such as a bungy cord. In alternative embodi-

ments, the biasing mechanism can be any mechanism that can generate a sufficient pressure or force to bias the rear frame portion rearwardly. The pressure or force can be applied in either a compression mode or a tension mode.

In one embodiment, the biasing mechanism can be a spring. The spring can be coupled to the base at any location. The spring is disposed so that the spring either pushes rearwardly on the rear frame portion or pulls rearwardly on the rear frame portion. In another embodiment, the biasing mechanism can be a flexible member, such as a plastic lever. The plastic lever can be formed integrally with the base. Alternatively, the plastic lever can be coupled to the base via fastener, such as a rivet. In another embodiment, the biasing mechanism can be a spring steel member.

In another embodiment, several biasing mechanisms can be used. For example, one or more plastic plates can be aligned in series with respect to each other and the base.

To recline the support **2500** from its upright configuration **2508** to its reclined configuration **2506**, the rear frame portion **2522** is moved from its upright position **2549** (see FIG. **79**) to its reclined position **2548** (see FIG. **80**). When the user or occupant of the seat **2570** shifts the user's weight toward the rear of the support **2500**, the rear frame portion **2522** pivots about a pivot point **2509** (see FIG. **68**), and the elongate member **2536** moves to the front ends of the slots **2722** and **2742**. When the user moves the upper part of the rear frame portion **2522** rearwardly, for example, by pressing rearwardly on the rear frame portion **2522** with the user's shoulders, the lower part of the rear frame portion **2522** moves forwardly along the direction of arrow "H."

In this configuration, the weight of the user or the occupant of the seat **2570** causes the support **2500** to remain in its reclined configuration **2506**.

To move the support **2500** from its reclined configuration **2506** to its upright configuration **2508**, the rear frame portion **2522** is moved from its reclined position **2548** to its upright position **2549**. When the user leans forward or moves upwardly, lifting a significant portion of the user's weight slightly off the seat **2570**, the rear frame portion **2522** pivots about the pivot point **2509** to its upright position **2549**. The support **2500** is retained in this configuration by the elastic member **2810**.

An alternative embodiment of a recline mechanism is illustrated in FIGS. **81** and **82**. In this embodiment, the recline mechanism **3100** includes a biasing mechanism **3120** that is coupled to the base **3110**. In one embodiment, the biasing mechanism **3120** is a continuous loop that extends through sets of holes in the base **3110**. In alternative embodiment, the biasing mechanism **3120** is a not a continuous loop. The biasing mechanism **3120** applies a biasing force on the rear frame portion along the direction of arrow "I." The biasing force biases the rear frame portion into an upright configuration **3130**. The rear frame portion can be disposed in a reclined configuration **3132** in which the rearwardly biasing force is applied to the rear frame portion as well.

An alternative embodiment of a recline mechanism is illustrated in FIGS. **83** and **84**. In this embodiment, the recline mechanism **3200** includes a biasing mechanism **3220** that is coupled to the base **3210**. The biasing mechanism **3220** is a flexible plate like member. The biasing mechanism **3220** can be coupled to or integrally formed with the base **3210**. The biasing mechanism **3220** applies a biasing force on the rear frame portion along the direction of arrow "J." The biasing force biases the rear frame portion into an upright configuration **3230**. The rear frame portion can be disposed in a reclined configuration **3232** in which the rearwardly biasing force is applied to the rear frame portion as well.

While the invention has been described in detail and with reference to specific embodiments thereof, it will be apparent to one skilled in the art that various changes and modifications can be made therein without departing from the spirit and scope thereof. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A support, comprising:

a frame, the frame including a front frame portion and a rear frame portion, the frame having a collapsed configuration and an expanded configuration;

a seat membrane, the seat membrane having a first end portion being coupled to the rear frame portion and a second end portion coupled to the front frame portion, the second end portion of the seat membrane being larger in length than the first end portion of the seat membrane; and

a tension member having a first end portion coupled to the rear frame portion and a second end portion, the second end portion of the tension member being configured to be removably coupled to the front frame portion when the frame is in its expanded configuration, the second end portion of the tension member being [configured to be] removably coupled to the rear frame portion when the frame is in its collapsed configuration.

2. The support of claim 1, wherein the first end portion of the tension member is pivotally coupled to the rear frame portion.

3. The support of claim 1, wherein the second end portion of the seat membrane is coupled to the front frame portion at a first location and at a second location.

4. The support of claim 1, wherein the second end portion of the seat membrane is slideably coupled to the front frame portion at a first location and is slideably coupled to the front frame portion at a second location.

5. The support of claim 1, wherein the second end portion of the seat membrane includes a first opening and a second opening, a first portion of the front frame portion extending through first opening of the second end portion of the seat membrane, a second portion of the front frame portion extending through the second opening of the second end portion of the seat membrane.

6. The support of claim 1, wherein the second end portion of the tension member includes an opening configured to removably receive a portion of the front frame portion.

7. The support of claim 1, wherein the second end portion of the tension member includes a first coupler, the rear frame portion includes a second coupler, the first and second couplers being configured to engage to removably couple the second end portion of the tension member to the rear frame portion.

8. The support of claim 1, further comprising:
a shade member coupled to the support.

9. The support of claim 8, further comprising:
a cushion coupled to the seat member and configured to help support a head of a user.

10. The support of claim 1, wherein the front frame portion includes a first support member pivotally coupled to a second support member.

11. The support of claim 1, wherein the frame includes a first front foot, a second front foot, and a rear foot, a first support of the front frame portion is pivotally coupled to the first foot, a second support of the front frame portion is

pivotally coupled to the second front foot, a first rear support member and a second rear support member being pivotally coupled to the rear foot.

12. The support of claim 1, wherein the second end portion of the tension member is configured to be removably coupled to a rear foot, a first support member of the rear frame portion and a second support member of the rear frame portion being pivotally coupled to the rear foot.

13. A support, comprising:

a frame, the frame including a front frame portion and a rear frame portion, the frame having a collapsed configuration and an expanded configuration, the frame including a first front foot, a second front foot, and a rear foot, a first support of the front frame portion being pivotally coupled to the first foot, a second support of the front frame portion being pivotally coupled to the second front foot, a first rear support member and a second rear support member of the frame being pivotally coupled to the rear foot;

a seat membrane, the seat membrane having a first end portion being coupled to the rear frame portion and a second end portion coupled to the front frame portion; and

a tension member having a first end portion coupled to the rear frame portion and a second end portion, the second end portion of the tension member being configured to be removably coupled to the front frame portion when the frame is in its expanded configuration, the second end portion of the tension member being [configured to be] removably coupled to the rear frame portion when the frame is in its collapsed configuration.

14. The support of claim 13, wherein the second end portion of the tension member is configured to be removably coupled to the rear foot, a first support member of the rear frame portion and a second support member of the rear frame portion being pivotally coupled to the rear foot.

15. The support of claim 13, wherein the second end portion of the tension member includes an opening configured to removably receive a portion of the front frame portion.

16. The support of claim 13, wherein the second end portion of the tension member includes a first coupler, the rear frame portion includes a second coupler, the first and second couplers being configured to engage to removably couple the second end portion of the tension member to the rear frame portion.

17. The support of claim 13, further comprising: a shade member coupled to the support.

18. The support of claim 17, further comprising: a cushion coupled to the seat member and configured to help support a head of a user.

19. The support of claim 13, wherein the front frame portion includes a first support member pivotally coupled to a second support member.

20. A support, comprising:

a frame, the frame including a front frame portion and a rear frame portion, the frame having a collapsed configuration and an expanded configuration;

a seat membrane, the seat membrane having a first end portion being coupled to the rear frame portion and a second end portion coupled to the front frame portion, the second end portion of the seat membrane including a first opening and a second opening, a first portion of the front frame portion extending through the first opening of the second end portion of the seat membrane, a second portion of the front frame portion extending through the second opening of the second end portion of the seat membrane; and

a tension member having a first end portion coupled to the rear frame portion and a second end portion, the second end portion of the tension member being configured to be removably coupled to the front frame portion when the frame is in its expanded configuration, the second end portion of the tension member being [configured to be] removably coupled to the rear frame portion when the frame is in its collapsed configuration.

21. The support of claim 20, wherein the second end portion of the tension member includes a first coupler, the rear frame portion includes a second coupler, the first and second couplers being configured to engage to removably couple the second end portion of the tension member to the rear frame portion.

22. The support of claim 13, wherein the retainer includes a first retainer portion and a second retainer portion, the first retainer portion configured to releasably couple to the second retainer portion to retain the frame in its collapsed configuration.

23. The support of claim 13, wherein the retainer includes one of a hook, a clip or a buckle.

24. The support of claim 13, wherein the retainer is coupled to at least one of the frame and the seat membrane.

25. The support of claim 13, wherein the retainer includes at least one of a flap, an elongate member, a cord, a rope, a string, a strap and an elastic member.

26. The support of claim 13, wherein the retainer has a body portion, a first side portion and a second side portion, the retainer includes a coupling mechanism configured to releasably couple the first side portion of the retainer to the second side portion of the retainer.

27. The support of claim 13, wherein the tension member is a first tension member, the first tension member being configured to support a first arm of a user when the frame is in its expanded configuration, the support further comprising:

a second tension member coupled to the front frame portion and the rear frame portion, the second tension member configured to support a second arm of the user when the frame is in its expanded configuration.

28. The support of claim 13, wherein the first support member of the front frame portion is pivotally coupled to the second support member of the front frame portion,

the frame including a side frame portion, the side frame portion including a first support member and a second support member, the first support member of the side frame portion being pivotally coupled to the second support member of the side frame portion.

29. The support of claim 13, wherein the first support member of the front frame portion is pivotally coupled to the second support member of the front frame portion,

the frame including a first side frame portion and a second side frame portion, the first side frame portion including a first support member and a second support member, the first support member of the first side frame portion being pivotally coupled to the second support member of the first side frame portion, the second side frame portion including a first support member and a second support member, the first support member of the second side frame portion being pivotally coupled to the second support member of the second side frame portion.

30. The support of claim 13, wherein the first support member of the front frame portion is pivotally coupled to the second support member of the front frame portion, the first support member of the front frame portion and the second support member of the front frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration,

35

the frame including a first side frame portion and a second side frame portion, the first side frame portion including a first support member and a second support member, the first support member of the first side frame portion being pivotally coupled to the second support member of the first side frame portion, the first support member of the first side frame portion and the second support member of the second side frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration, the second side frame portion including a first support member and a second support member, the first support member of the second side frame portion being pivotally coupled to the second support member of the second side frame portion, the first support member of the second side frame portion and the second support member of the second side frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration.

31. The support of claim 13, wherein:

the retainer includes a first retainer portion and a second retainer portion, the first retainer portion configured to releasably couple to the second retainer portion to retain the frame in its collapsed configuration;

the first support member of the front frame portion being pivotally coupled to the second support member of the front frame portion, the first support member of the front frame portion and the second support member of the front frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration,

the frame including a first side frame portion and a second side frame portion, the first side frame portion including a first support member and a second support member, the first support member of the first side frame portion being pivotally coupled to the second support member of the first side frame portion, the first support member of the first side frame portion and the second support member of the second side frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration, the second side frame portion including a first support member and a second support member, the first support member of the second side frame portion being pivotally coupled to the second support member of the second side frame portion, the first support member of the second side frame portion and the second support member of the second side frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration; and

the tension member is a first tension member, the first tension member being configured to support a first arm of a user when the frame is in its expanded configuration, the support further comprising:

a second tension member coupled to the front frame portion and the rear frame portion, the second tension member configured to support a second arm of the user when the frame is in its expanded configuration.

32. The support of claim 13, wherein the rear frame portion has a height when the frame is in its expanded configuration, the front frame portion having a height when the frame is in its expanded configuration, the height of the rear frame portion when the frame is in its expanded configuration being larger than the height of the front frame portion when the frame is in its expanded configuration.

33. The support of claim 20, wherein the retainer includes a first retainer portion and a second retainer portion, the first retainer portion being configured to engage the second retainer portion such that the retainer retains the frame in its collapsed configuration.

36

34. The support of claim 20, wherein the retainer includes one of a hook, a clip or a buckle.

35. The support of claim 20, wherein the retainer is coupled to at least one of the frame and the seat membrane.

36. The support of claim 20, wherein the retainer includes at least one of a flap, an elongate member, a cord, a rope, a string, a strap and an elastic member.

37. The support of claim 20, wherein the retainer has a body portion, a first side portion and a second side portion, the retainer includes a coupling mechanism configured to releasably couple the first side portion of the retainer to the second side portion of the retainer.

38. The support of claim 20, wherein the tension member is a first tension member, the support further comprising:

a second tension member coupled to the front frame portion and the rear frame portion, the second tension member configured to support a second arm of the user when the frame is in its expanded configuration.

39. The support of claim 20, wherein the front frame portion includes a first support member and a second support member, the first support member of the front frame portion being pivotally coupled to the second support member of the front frame portion,

the frame including a side frame portion, the side frame portion including a first support member and a second support member, the first support member of the side frame portion being pivotally coupled to the second support member of the side frame portion.

40. The support of claim 20, wherein the front frame portion includes a first support member and a second support member, the first support member of the front frame portion being pivotally coupled to the second support member of the front frame portion,

the frame including a first side frame portion and a second side frame portion, the first side frame portion including a first support member and a second support member, the first support member of the first side frame portion being pivotally coupled to the second support member of the first side frame portion, the second side frame portion including a first support member and a second support member, the first support member of the second side frame portion being pivotally coupled to the second support member of the second side frame portion.

41. The support of claim 20, wherein the front frame portion includes a first support member and a second support member, the first support member of the front frame portion being pivotally coupled to the second support member of the front frame portion,

the frame including a first side frame portion and a second side frame portion, the first side frame portion including a first support member and a second support member, the first support member of the first side frame portion being pivotally coupled to the second support member of the first side frame portion, the second side frame portion including a first support member and a second support member, the first support member of the second side frame portion being pivotally coupled to the second support member of the second side frame portion,

the rear frame portion including a first support member and a second support member, the first support member of the rear frame portion being substantially parallel to the second support member of the rear frame portion.

42. The support of claim 20, wherein the front frame portion includes a first support member and a second support member, the first support member of the front frame portion being pivotally coupled to the second support member of the front frame portion, the first support member of the front

37

frame portion and the second support member of the front frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration,

the frame including a first side frame portion and a second side frame portion, the first side frame portion including a first support member and a second support member, the first support member of the first side frame portion being pivotally coupled to the second support member of the first side frame portion, the first support member of the first side frame portion and the second support member of the second side frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration, the second side frame portion including a first support member and a second support member, the first support member of the second side frame portion being pivotally coupled to the second support member of the second side frame portion, the first support member of the second side frame portion and the second support member of the second side frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration,

the rear frame portion including a first support member and a second support member, the first support member of the rear frame portion being substantially parallel to the second support member of the rear frame portion.

43. The support of claim 20, wherein the first end portion of the seat membrane defines a first opening and a second opening, a first portion of the rear frame portion extending through the first opening of the first end portion of the seat membrane, a second portion of the rear frame portion extending through the second opening of the first end portion of the seat membrane.

44. The support of claim 20, wherein:

the retainer includes a first retainer portion and a second retainer portion, the first retainer portion configured to releasably couple to the second retainer portion to retain the frame in its collapsed configuration,

the first end portion of the seat membrane defines a first opening and a second opening, a first portion of the rear frame portion extending through the first opening of the first end portion of the seat membrane, a second portion of the rear frame portion extending through the second opening of the first end portion of the seat membrane,

the front frame portion includes a first support member and a second support member, the first support member of the front frame portion being pivotally coupled to the second support member of the front frame portion, the first support member of the front frame portion and the

38

second support member of the front frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration, the rear frame portion including a first support member and a second support member, the first support member of the rear frame portion being substantially parallel to the second support member of the rear frame portion,

the frame including a first side frame portion and a second side frame portion, the first side frame portion including a first support member and a second support member, the first support member of the first side frame portion being pivotally coupled to the second support member of the first side frame portion, the first support member of the first side frame portion and the second support member of the second side frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration, the second side frame portion including a first support member and a second support member, the first support member of the second side frame portion being pivotally coupled to the second support member of the second side frame portion, the first support member of the second side frame portion and the second support member of the second side frame portion collectively forming a substantially X-shape when the frame is in its expanded configuration; and the tension member is a first tension member, the support further comprising:

a second tension member coupled to the front frame portion and the rear frame portion, the second tension member configured to support a second arm of the user when the frame is in its expanded configuration.

45. The support of claim 20, wherein the rear frame portion has a height when the frame is in its expanded configuration, the front frame portion has a height when the frame is in its expanded configuration, the height of the rear frame portion when the frame is in its expanded configuration is larger than the height of the front frame portion when the frame is in its expanded configuration.

46. The support of claim 1, wherein at least one of (1) the first end portion of the tension member is coupled to the rear frame portion, (2) the second end portion of the tension member is removably coupled to the front frame portion in the expanded configuration, or (3) the second end portion of the tension member is removably coupled to the rear frame portion in the collapsed configuration, independently of the seat membrane.

* * * * *