

US00RE44208E

(19) **United States**  
(12) **Reissued Patent**  
**Ogasawara**

(10) **Patent Number:** **US RE44,208 E**  
(45) **Date of Reissued Patent:** **May 7, 2013**

(54) **SYSTEM AND METHOD FOR PROVIDING INFORMATION, AND RECORDING MEDIUM**

(75) Inventor: **Satoshi Ogasawara**, Saitama (JP)

(73) Assignee: **Intellectual Ventures Holding 56 LLC**,  
Carson City, NV (US)

(21) Appl. No.: **12/428,941**

(22) Filed: **Apr. 23, 2009**

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **7,209,944**  
Issued: **Apr. 24, 2007**  
Appl. No.: **09/957,284**  
Filed: **Sep. 20, 2001**

**Foreign Application Priority Data**

(30) Sep. 27, 2000 (JP) ..... 2000-293387

(51) **Int. Cl.**  
**G06F 15/16** (2006.01)

(52) **U.S. Cl.**  
USPC ..... 709/217; 709/203; 709/206; 709/228

(58) **Field of Classification Search** ..... 709/203,  
709/201-202, 204-207, 217, 228  
See application file for complete search history.

**References Cited**

**U.S. PATENT DOCUMENTS**

5,697,793 A 12/1997 Huffman et al.  
6,085,226 A 7/2000 Horvitz

6,385,614	B1	5/2002	Vellandi	
6,460,038	B1	10/2002	Khan et al.	
6,463,466	B1 *	10/2002	Weyer	709/217
6,499,052	B1	12/2002	Hoang et al.	
6,516,337	B1	2/2003	Tripp et al.	
6,546,393	B1	4/2003	Khan	
6,571,054	B1	5/2003	Tomomura et al.	
6,832,222	B1	12/2004	Zimowski	
7,865,567	B1 *	1/2011	Hendricks et al.	709/214
2003/0061275	A1	3/2003	Brown et al.	

**FOREIGN PATENT DOCUMENTS**

JP	61-188554	8/1986
JP	63-092961	4/1988
JP	63-370549	12/1988
JP	2000-155766	6/2000


\* cited by examiner

*Primary Examiner* — David Lazaro

(57) **ABSTRACT**

To provide a system and a method for providing information and a recording medium, by which communications cost and network traffic are reduced in a system which provides a plurality of pages including successive contents via a communication network. A story provider site **100** generates user ID for identifying a reader terminal **300** and reader information which includes information representing a last page, and transmits web page data segments based on the reader information together with the user ID to the reader terminal **300** concerned. The reader terminal **300** requests the pages with transmitting the user ID. The story provider site **100** transmits web page data segments based on the reader information corresponding to the returned user ID. The story provider site **100** updates the reader information based on the transmitted web page.

**40 Claims, 12 Drawing Sheets**



# FIG. 1





FIG. 2



**FIG.3A**

READER INFORMATION FILE

USER ID	LAST PAGE	CONTINUATION PAGE	BOOKMARK FLAG	REPEAT FLAG	SESSION TERMINATION
.	.	.	.	.	.
.	.	.	.	.	.
.	.	.	.	.	.

**FIG.3B**

STORY FILE TABLE

FILE NAME OF STORY PAGE
.
.
.

FIG.4






FIG.5



# FIG.6



# FIG.7






FIG.8




FIG.9







FIG.10




**FIG.11**



**FIG.12A**



**FIG.12B**



## SYSTEM AND METHOD FOR PROVIDING INFORMATION, AND RECORDING MEDIUM

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.**

### CROSS-REFERENCE TO RELATED APPLICATIONS

*This is a Reissue application of U.S. Ser. No. 09/957,284, filed Sep. 20, 2001, now U.S. Pat. No. 7,209,944 granted Apr. 24, 2007. U.S. Ser. No. 09/957,284 claims the benefit of Japanese Application No. 2000-293387, filed Sep. 27, 2000.*

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to a system and a method for providing information and a recording medium, suitable for providing contents of readings via communications networks.

#### 2. Description of the Related Art

There are services for providing the contents of readings such as novels and serial columns to terminals (such as personal computers) via communications networks such as the Internet. Users of the terminals (that is, readers) operate web browser to establish sessions with the service provider's server for obtaining desired HTML based web pages representing the contents of the readings.

The readers must establish plural sessions when obtaining a full-length novel, because it requires much data. In case of providing serial column or novel, the story may be divided into plural sections, and those are uploaded one after another constantly. The readers also require plural sessions to obtain the contents of such the readings because it is impossible to download all sections at once.

Such the services generally provide the readers with index pages at beginning of each session. The index page may list indexes of available contents. In case of full-length novel, for example, the index page may list indexes of chapters, and a reader selects a chapter which follows to a chapter he/she read last time. The readers intend to forget which was the last chapter when he/she continues reading for the first time in a long while. Under such the situation, the service providers generally provide all pages at each session. It is helpful for avoiding the above problem, but increases connection time for downloading the pages. Thus, it increases network traffic and the readers' telecommunication costs.

### SUMMARY OF THE INVENTION

A first aspect of the present invention features a system for providing information being connected to a communications network, which selectively provides web page data segments representing a plurality of pages which include successive description via the communications network, in accordance with web page data segments provided last time.

The System Comprises:

a web page storage unit which stores the web page data segments;

an ID information managing unit which receives a request for the web pages, generates ID information for identifying the source of the request and additional information representing a last page represented by the web page data segment

which has been transmitted to the request source, and stores the generated ID information and additional information so that the ID information and additional information are associated with each other;

a web page providing unit which retrieves the web page data segments corresponding to the additional information from the web page storage unit, and transmits the retrieved web page data segments to the request source together with the corresponding ID information;

a provision progress managing unit which updates the additional information if the web page providing unit transmits the web page data segments; and

an ID information receiver which receives the ID information returned from the request source.

In this case, the web page providing unit further transmits the web page data segments based on the additional information corresponding to the ID information received by the ID information receiver, that is, the web page providing unit provides the web pages corresponding to the reader's reading progress.

A second aspect of the present invention features a method for providing information by which an information providing apparatus selectively provides a plurality of terminals with web page data segments representing a plurality of pages including successive description, in accordance with web page data segments provided last time.

The Method Comprises the Steps of:

generating ID information for identifying the terminal in response to request for providing web pages from the terminal, and of generating additional information representing a last page represented by the web page data segments which has been provided to the terminal;

transmitting web page data segments corresponding to the additional information together with the corresponding ID information to the terminal which requested the web pages; and

receiving the ID information from the terminal together with the page request;

transmitting web page data segments to the terminal based on the additional information corresponding to the received ID information.

The method further updates the additional information in a case where the web page data segments representing a page corresponding to the additional information are transmitted to the terminal, and/or in a case where the web page data segments representing pages following to the page corresponding to the additional information are transmitted to the terminal. Thus, the web pages are provided to the terminal in accordance with the reader's reading progress.

A third aspect of the present invention features a system for providing information which comprises an information providing apparatus being connected to a communications network, and a plurality of terminals each of which receives web page data segments representing a plurality of pages including successive description from the apparatus via the communications network, wherein

the terminal may comprise:

a web page browser which receives web page data segments and ID information for identifying the terminal from the information providing apparatus, and outputs the received web page data segments; and

an additional information generator which generates additional information which designates a last page of the pages output by the web page browser, and transmits the generated additional information to the information providing apparatus together with the ID information when requesting the web pages, and

the information providing apparatus may comprise:  
 a storage unit which stores the ID information and additional information provided by the terminal so that the ID information and additional information are associated with each other; and  
 a transmitter which transmits the web page data segments to the terminal designated by the ID information corresponding to the additional information.

#### BRIEF DESCRIPTION OF THE DRAWINGS

These objects and other objects and advantages of the present invention will become more apparent upon reading of the following detailed description and the accompanying drawings in which:

FIG. 1 is a diagram schematically showing a story providing system according to an embodiment of the present invention;

FIG. 2 is a block diagram schematically showing the structure of a story provider site shown in FIG. 1;

FIG. 3A is a diagram exemplifying the contents of a reader information file in a reader information database shown in FIG. 2;

FIG. 3B is a diagram exemplifying the contents of a story file table in a story document database shown in FIG. 2;

FIG. 4 is a flowchart for explaining the process carried out by the story providing system shown in FIG. 1;

FIG. 5 is a flowchart for explaining the process for "continue or repeat all" carried out in the process flow shown in FIG. 4;

FIG. 6 is a flowchart for explaining the process for "initial registration" carried out in the process flow shown in FIG. 4;

FIG. 7 is a flowchart for explaining the process for "designated page request" carried out in the process flow shown in FIG. 4;

FIG. 8 is a flowchart for explaining the process for "page designation" carried out in the process flow shown in FIG. 4;

FIG. 9 is a flowchart for explaining the process for "session termination" carried out in the process flow shown in FIG. 4;

FIG. 10 is a flowchart for explaining the process for "deadline management" according to the embodiment of the present invention;

FIG. 11 is a diagram exemplifying a page to be displayed on the reader terminal shown in FIG. 1;

FIG. 12A is a diagram exemplifying a page transmitted during the process for "page designation"; and

FIG. 12B is a diagram exemplifying a page transmitted during the process for "session termination".

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

An embodiment according to the present invention will now be described with reference to accompanying drawings. The following embodiment is intended to illustrate the present invention, not to limit the scope of the present invention.

FIG. 1 is a diagram schematically showing a story providing system according to the embodiment of the present invention.

A story providing system 1 according to the embodiment of the present invention comprises a story provider site 100, a communications network 200, and a plurality of reader terminals 300-1 to 300-n.

A business for story providing service according to the embodiment runs the story provider site 100 to provide text

data (novels, columns, and the like) and image data (illustrations, and the like) via the communications network 200.

The communications network 200 may be the Internet which transfers the text data and the image data provided by the story provider site 100. In the present embodiment, the Internet is employed as the communications network 200, therefore, hereinafter it is referred to as Internet 200.

Each of the reader terminals 300-1 to 300-n may be a personal computer, PDA (Personal Data Assistant), a mobile phone, and/or the like which is suitable for data communications. Such the reader terminal 300 receives the text data and the image data provided by the story provider site 100 via the Internet 200, and displays information represented by the received data.

The detailed structure of the story provider site 100 will now be described with reference to FIG. 2. FIG. 2 is a block diagram schematically showing the structure of the story provider site 100.

As shown in FIG. 2, the story provider site 100 comprises a web server 10, a user ID storage unit 20, a story provision managing unit 30, databases 40, and a web page storage unit 50, which are interconnected to each other via a local network.

The web server 10 may be a data processor such as a workstation comprising at least a control unit, a memory, and a CCU (Communications Control Unit), and is a main server in the story provider site 100. The web server 1 includes a user identifier 11, a user ID issuer 12, and a web page finder 13. The control unit of the web server 10 may be a CPU (Central Processing Unit), and the memory stores programs being compatible with the interaction interface such as CGI (Common Gateway Interface). The control unit executes such the programs to activate the story provision managing unit 30 in accordance with commands given by the reader terminals 300 through the Internet 200, thus, necessary information sets are collected and processed. The control unit then creates web pages including thus collected information, and provides the web pages to the reader terminals 300 through the Internet 200.

The user identifier 11 refers to information stored in the user ID storage unit 20 to determine whether a visitor is a new comer or a registered user.

The user ID issuer 12 issues ID information (Cookie, Subscribe-ID, or the like) to the reader terminal 300 whose user is a new comer.

The web page finder 13 retrieves web pages to be transmitted to the reader terminal 300 from the web page storage unit 50. The web pages stored in the web page storage unit 50 represent the contents of the stories to be provided.

The user ID storage unit 20 may be a rewritable storage unit such as a hard disk drive, which stores information representing user ID issued by the user ID issuer 12.

The story provision managing unit 30 may be a data processor such as a workstation which includes at least a control unit and a storage unit. The story provision managing unit 30 comprises a reader managing unit 31, a provision progress managing unit 32, and a deadline managing unit 33. The story provision managing unit 30 retrieves the contents (document files) to be provided in accordance with the destination reader. The control unit of the story provision managing unit 30 executes predetermined programs being stored in the storage unit, to control the story provision managing unit 30, thus, carrying out the later described processes.

The reader managing unit 31 controls the provision progress managing unit 32 and the deadline managing unit 33 to coordinate the data in the reader information file stored in the reader information database 41.

The provision progress managing unit **32** manages data corresponding to “Last Page”, “Continuation Page”, “Bookmark Flag” and “Repeat Flag” in the reader information file, to coordinate story provision progress for each reader.

The deadline managing unit **33** manages information representing date and time in “Session Termination” in the reader information file, to coordinate accessible period given to each reader.

The databases **40** may be a rewritable storage units such as hard disk drives, which include the reader information database **41** and the story document database **42**.

The reader information database **41** stores the reader information file. FIG. **3A** shows an example of the reader information file. As shown in FIG. **3A**, the reader information file includes the records corresponding to user ID issued by the user ID issuer **12**. Each record includes items “Last Page”, “Continuation Page”, “Bookmark Flag”, “Repeat Flag”, and “Session Termination”. “Last Page” represents file name of the web page transmitted to the corresponding reader last time (at the last session). “Continuation Page” represents file name of a web page which should be transmitted to the corresponding reader next time (at the next session). “Bookmark Flag” is a flag representing whether the corresponding reader sent “Bookmark” command (described later) at the end of the last session. “Repeat” flag is a flag representing whether the corresponding reader sent “Repeat All” command at the end of the last session. “Session Termination” represents date and time when the last session was terminated.

The story document database **42** stores story file tables prepared for each story. FIG. **3B** exemplifies one of the story file tables. As shown in FIG. **3B**, the story file table stores file names of files which consist web pages for one story (for example, a novel).

The web page storage unit **50** may be a rewritable storage unit such as a hard disk drive, and stores web page files representing stories (novels, columns, etc.) to be provided by the story provider site **100**.

Process carried out in the story providing system **1** according to the present embodiment will now be described with reference to a flowchart shown in FIG. **4**.

When the story provider site **100** receives request information requesting provision of story documents from the reader terminal **300** via the Internet **200** (step **S101**), the user identifier **11** determines whether the request information includes user ID issued by the user ID issuer **12** (step **S102**). More precisely, once the user ID issuer **12** issues user ID information (such as, cookie) to the reader terminal **300**, the user ID information stays in the reader terminal **300**. And the reader terminal **300** transmits the request information with the given user ID information when the reader terminal **300** accesses the story provider site **100**.

If it is determined that the request information includes the user ID information, the user identifier **11** refers to the user ID information in the user ID storage unit **20** to determine whether the user ID is valid or not (step **S103**). In this embodiment, since the user ID information of a user whose deadline has passed will be deleted from the user ID storage unit **20** in “Deadline Management” process (described later), the user identifier **11** regards the visitor as a new comer when the received user ID information does not exist in the user ID storage unit **20**.

If it is determined at step **S103** that the user ID is valid (step **S103: Yes**), the user identifier **11** recognizes that the visitor is the registered reader. In this case, the story provider site **100**

carries out “Continue or Repeat All” process. The process will now be described with reference to a flowchart shown in FIG. **5**.

The reader managing unit **31** accesses the reader information database **41** to read out reader information corresponding to the received user ID information (step **S201**).

The provision progress managing unit **32** determines whether the bookmark flag in the read-out user information is set to “1” or not (step **S202**). The set bookmark flag represents that the reader terminal **300** of the reader concerned sent “Bookmark” command to the story provider site **100** at the end of the last session. The “Bookmark” command represents that the reader intends to read continuous pages at the next session. In a case where the bookmark flag is “1”, the provision progress managing unit **32** transfers the file name in “Last Page” to “Continuation Page” (step **S203**) and reset the bookmark flag to “0”.

On the contrary, if it is determined at step **S202** that the bookmark flag is “0”, the provision progress managing unit **31** further determines whether the repeat flag is set to “1” or not (step **S205**). The set repeat flag represents that the reader terminal **300** of the reader concerned sent “Repeat All” command to the story provider site **100** at the end of the last session. The “Repeat All” command represents that the reader intends to read the story again from its head page at the next session. In a case where the repeat flag is “1”, the provision progress managing unit **32** accesses the story document database **42** to obtain file name of the head page of the story, and stores the obtained file name in “Last Page” (step **S206**). And the provision progress managing unit **32** resets the repeat flag to “0” (step **S207**).

Then the web page finder **13** searches the web page storage unit **50** for an HTML file corresponding to the file name recorded at step **S203** or **S206**, and obtains it. The web page finder **13** transmits the obtained HTML file to the reader terminal **300** of the reader concerned (step **S208**).

The reader managing unit **31** stores the file name of the web page transmitted at step **S208** in “Last Page” of the reader information file in the reader information database **41** (step **S209**), and terminates the process.

If it is determined at step **S102** that the visitor is a new comer (step **S102: No**), or if it is determined at step **S103** that the user ID is invalid (step **S103: No**), the user ID issuer **12** generates user ID information and registers it in the user ID storage unit **20** (step **S104**). Then, the process for “Initial Registration” is carried out (step **S300**).

The initial registration process will now be described with reference to a flowchart shown in FIG. **6**.

The reader managing unit **31** creates a new record in the reader information file being stored in the reader information database **41** (step **S301**). The new record is prepared for the user ID issued at step **S104**.

Then, the web page finder **13** accesses the web page storage unit **50** to retrieve an index page as shown in the upper section of FIG. **11**. The index page represents a contents table of a story desired by the reader concerned. And the web page finder **13** transmits the retrieved web page together with the user ID to the reader terminal **300** (step **S302**). As shown in FIG. **11** (upper section), the index page includes hyperlinks representing chapters of the story. Each of the hyperlinks includes URL (Uniform Resource Locator) information invisibly. When the reader clicks on the hyperlink, the corresponding URL information is transmitted to the story provider site **100**.

When the story provider site **100** receives the URL information which designates the web page desired by the reader (step **S303: Yes**), the web page finder **13** retrieves the web



page concerned from the web page storage unit **50**, and transmits it to the reader terminal **300** (step **S304**).

The provision progress managing unit **32** obtains information representing file name of the web page transmitted at step **S304**. The provision progress managing unit **32** accesses the reader information database **41** to register the file name information in "Last Page" of the reader information file (step **S305**), and terminates the initial registration process.

The process flow returns to the process flow shown in FIG. **4**.

If the story provider site **100** receives URL information which designates a chapter desired by the reader (step **S105**: Yes), the story provider site **100** carries out the process for "Designated Page Request" (step **S400**).

The designated page request process will now be described with reference to a flowchart shown in FIG. **7**.

The web page finder **13** retrieves a web page corresponding to the URL received at step **S105**, and transmits it to the reader terminal **300** (step **S401**).

The provision progress managing unit **32** obtains information representing file name of the web page transmitted at step **S401**. The provision progress managing unit **32** accesses the reader information database **41** to register the file name in "Last Page" of the reader information file (step **S402**), and terminates the designated page request process.

A case where the reader terminal **300** transmits a predetermined command, instead of URL for the next page (step **S105**: No), will now be described.

When the story providing site **100** receives a command (step **S106**: Yes), the provision progress managing unit **32** determines the type of the command, "Page Designation" command or a "Session Termination" command (step **S107**).

If the received command is the "Page Designation" command (step **S107**: Yes), the process for "Page Designation" is carried out (step **S500**). The page designation process will now be described with reference to a flowchart shown in FIG. **8**.

The provision progress managing unit **32** determines whether the command requests the previous page or the next page (step **S501**). See a lower section of FIG. **11** exemplifying a web page displayed on the reader terminal **300**. As illustrated, the web page has a "NEXT" button. If the user clicks on this button, the command requesting the next page is transmitted to the story provider site **100**. The web page also has a "PREV." (=previous) button. Upon clicking on this button, the command requesting the previous page is transmitted to the story provider site **100**. Hereinafter, the command requesting the next page will be referred to as "command N", and the command requesting the previous page will be referred to as "command P".

If the received command is the command N (step **S501**: Yes), the provision progress managing unit **32** accesses the story document database **42** to refer to the story file table of the story concerned, to determine whether the page provided last time ("Last Page") is the final page of the story or not (step **S502**).

If it is determined at step **S502** that the page provided last time is the final page of the story (step **S502**: Yes), the provision progress managing unit **32** terminates the process because there is no page to be provided.

In a case where the page provided last time is not the final page of the story, the provision progress managing unit **32** obtains information representing file name of a page following to the page represented by the file name in "Last Page" (step **S503**).

The web page finder **13** retrieves a web page corresponding to the file name obtained at step **S503**, and transmit the retrieved web page to the reader terminal **300** (step **S504**).

The provision progress managing unit **32** registers the file name of the web page transmitted at step **S504** in "Last Page" of the reader information file (step **S505**), and terminates the process.

In a case where the received command is the command P (step **S506**: Yes), the provision progress managing unit **32** refers to the story file table of the story concerned, to determine whether the page represented by the file name in "Last Page" is a head page of the story or not (step **S507**).

If it is determined that the page provided last time is the head page of the story (step **S507**: Yes), the provision progress managing unit **32** terminates the process, because there is no page to be provided.

In a case where the page provided last time is not the head page of the story (step **S507**: No), the provision progress managing unit **32** refers to the story file table to obtain information representing file name of a page previous to the page represented by the file name in "Last Page" (step **S508**). The web page finder **13** retrieves a web page corresponding to the obtained file name from the web page storage unit **50**, and transmits the obtained web page to the reader terminal **300** (step **S509**). In this case, the provision progress managing unit **32** does not overwrite any information in the reader information file, and terminates the process.

In a case where the received command is a command for requesting session termination (step **S107**: No), the process for "Session Termination" is carried out (step **S600**). The session termination process will now be described with reference to a flowchart shown in FIG. **9**.

The command for requesting session termination (hereinafter, referred to as "command ST") is classified into "Bookmark" and "Repeat All". The provision progress managing unit **32** determines whether the received command ST is "Bookmark" or "Repeat All" (step **S601**).

See FIG. **12A** or **12B** exemplifying web pages displayed on the reader terminal **300**. As illustrated, the web pages include "Bookmark" button. When the "Bookmark" button is clicked on by the user, the command "Bookmark" is transmitted to the story provider site **100**. The web pages also include "Repeat All" button. In the same manner, upon clicking on the "Repeat All" button, the command "Repeat All" is transmitted. The command "Bookmark" represents that the reader intends to terminate the present session, and continue the reading next time (at the next session). On the other hand, the command "Repeat All" represents that the reader intends to terminate the present session, but read the story again from the beginning (chapter 1 or head page) next time (at the into session).

In a case where the received command ST is "Bookmark" (step **S601**: Yes), the provision progress managing unit **32** transfers the file name in "Last Page" of the reader information file to "Continuation Page", and sets the bookmark flag to "1" (step **S602**). Note that the provision progress managing unit **32** may set file name representing a web page following to the web page transmitted at the end of the last session to "Continuation Page", instead of the file name in "Last Page".

In a case where the received command ST is "Repeat All" (step **S601**: No), the provision progress managing unit **32** sets the repeat flag to "1" in the reader information file (step **S604**).

After the reader information file is thus updated (step **S602** or **S604**), the web server **10** terminates the session with the reader terminal **300** concerned (step **S605**).

Upon terminating the session at step S605, the deadline managing unit 33 records the present date/time in "Session Termination" of the reader information file (step S606), and terminates the process.

The process for "Deadline Management" carried out in the story providing system 1 according to the embodiment of the present invention will now be described with reference to a flowchart shown in FIG. 10.

In this embodiment, the deadline management process is carried out constantly at predetermined intervals (timings) (step S701).

The deadline managing unit 33 obtains information (date/time) in "Session Termination" from the first record (record No. 1) of the reader information file (steps S702 and S703).

The deadline managing unit 33 determines whether a first predetermined time period T1 (hereinafter, referred to as "time period T1") has lapsed since the date/time obtained at step S703 (step S704). The time period T1 may represent, for example, 1 month.

If it is determined at step S704 that the time period T1 has lapsed (step S704: Yes), the deadline managing unit 33 further determines whether a second predetermined time period T2 (hereinafter, referred to as "time period T2") has lapsed since the date/time obtained at step S703 (step S705). The time period T2 may represent, for example, 3 months.

If it is determined at step S705 that the time period T2 has not lapsed (step S705: No), the deadline managing unit 33 recognizes that the reader corresponding to the user ID for the record concerned has not accessed the story provider site 100 for over 1 month but within 3 months. Since the reader may forget which page was the last page, the deadline managing unit 33 sets the repeat flag to "1" in the record concerned (step S706) in order to provide the head page to the reader at the next session.

On the contrary, if it is determined at step S705 that the time period has lapsed (step S705: Yes), the deadline managing unit 33 recognizes that the reader concerned has not accessed the story provider site 100 for over 3 months. Since an assumption that the reader who has not accesses the story provider site 100 for such the long time will not accesses the story provider site 100 may be reasonable, the deadline managing unit 33 deletes the user ID stored in the record concerned and the user ID storage unit 20 (step S707).

The above "repeat flag setting" or "user ID deletion" is carried out for each record in the reader information file (step S708, S709: No). When the task for the final record is done (step S709: Yes), the deadline managing unit 33 terminates the process.

Though the story provider site 100 updates file names in "Last Page" and "Continuation Page" for identifying the page which was transmitted last time in the above described embodiment, such the update may be done by the reader terminal 300. In this case, the reader terminal 300 obtains file name of the final page at the end of the session, and transmits it to the story provider site 100 together with the command ST. The story provider site 100 will transmit the following page at the next session based on the file name provided by the reader terminal 300.

In the above described embodiment, the reader selects "Bookmark" or "Repeat All." at the end of the session, however, the story providing system 1 may allows the readers to select "Bookmark" or "Repeat All" at the beginning of the session. In this case, the story provider site 100 may transfer the lastly provided page at the beginning of a new session together with the "Repeat All" button. If the reader intends to continue the reading, he/she may just designate "Next" but-

ton, while designating "Repeat All" button if he/she intends to read the story again from the head page.

The above described embodiment has exemplified the document files written in HTML. However, any languages which are compatible with the data communications through the Internet are applicable to the present invention. For example, since languages such as WML (Wireless Markup Language) and compact HTML may be suitable for a case where the reader terminal 300 is an internet connectable mobile phone or the like, the story provider site 100 may create the document files written in such the languages. Moreover, the story may be distributed by e-mails, instead of the web page.

As for the deletion of user ID for the reader who has not accessed the story provider site 100 for a long time, the deadline managing unit 33 may remains the user ID stored in the user ID storage unit 20.

A general computer system is applicable to the story provider site 100 and the reader terminals 300, instead of the purpose specific system. Such the general computers may act as the story provider site 100 and the reader terminals 300 by, for example, installing programs for the above described processes from a recording medium (a flexible disk, a CD-ROM, or the like), or the like. In a case where the OS (Operating System) has necessary part for realizing the processes or collaborates with the application program(s) for realizing the processes, the recording medium may store only the program sets other than the OS.

The programs for realizing the process may be distributed via the telecommunications network. In this case, the program may be superimposed on a carrier wave signal. Such the program may be uploaded to the BBS (Bulletin Board System) or the like for the distribution.

Thus distributed programs may be invoked as well as the other application programs under control of the OS to realize the above processes.

According to the information providing system of the present invention, an information providing system prepares ID information (such as cookie) and additional information representing the last page and transmits them to a terminal used by a new comer user together with web page data. The terminal stores the given ID information, and transmits it when requesting pages. The information providing system updates the additional information so as to represent the last page provided in response to the request from the terminal. A page following to the page designated by the updated additional information or pages following to the page designated by the updated additional information will be provided to the terminal at the next session. Thus, the information providing system provides the user who continues the reading with the continuous pages. In other words, the information providing system memorizes which page the reader read the last time, and provides the continuous pages at the next session. According to this feature, the users are released from downloading unnecessary pages. It is helpful for reducing connection time and network traffic.

Moreover, the information providing system provides a user who has not accessed the information provider site over a predetermined time period (for example, 1 month) with a head page of the story again. According to this structure, it is able to provide the story providing service in consideration of the situation where such the users intend to forget which page was provided last time.

Furthermore, the information providing system deletes (cancels) user information and user ID for a user who has not accessed the information provider site for a longer time period (for example, 3 months), because it is reasonable that

11

such the user will access the site no more. This structure is helpful for efficient use of storage for storing; user ID information. It is further suitable for a case where, for example, the documents are updated (changed) regularly or irregularly, because setting the deadline for using the service may promote the reading.

What is claimed is:

1. An information providing system which is connected to a communications network, and which individually provides web page data segments representing a plurality of pages which include successive description to respective individual user terminals at respective individual timings via the communications network, said system comprising:

a web page storage unit which stores the web page data segments;

an ID information managing unit which stores ID information corresponding to each of the user terminals and additional information corresponding to each of the user terminals, said additional information comprising information indicating a web page data segment most recently transmitted to the corresponding user terminal;

a web page providing unit which, in response to designation of continuous provision by one of the user terminals, retrieves at least one web page data segment subsequent to the most recently transmitted web page data segment from the web page storage unit, based on the additional information stored in the ID information managing unit corresponding to the user terminal, and individually transmits the retrieved at least one web page data segment to the user terminal at an individual timing based on the ID information corresponding to the user terminal; and

an additional information managing unit which, when the web page providing unit transmits the at least one web page data segment following the most recently transmitted web page data segment, updates the additional information corresponding to the user terminal to indicate a last transmitted web page data segment as the most recently transmitted web page data segment;

wherein the additional information further comprises date/time information representing a date and time when the additional information was last updated; and

wherein, if the designation of continuous provision by the user terminal is made after a predetermined time has elapsed after the date and time indicated by the date/time information, the at least one web page data segment transmitted to the user terminal comprises a plurality of sequential said web page data segments beginning at a head page of the web page data segments and extending to a web page data segment that is a predetermined number of web page data segments subsequent to the most recently transmitted web page data segment indicated by the additional information corresponding to the user terminal.

2. The system according to claim 1, wherein the web page storage unit stores file name data corresponding to the web page data segments, and the additional information includes file name data of the web page data segment; and

wherein the web page providing unit, in response to a designation of repeat transmission from the user terminal, transmits at least a head page of the web page data segments based on the file name data in the additional information to the user terminal.

3. The system according to claim 1, wherein the web page providing unit deletes at least one of the ID information and the additional information corresponding to a user terminal, if the user terminal does not issue a request for the web page

12

data segments for a predetermined time after the date and time indicated by the date/time information.

4. The system according to claim 1, wherein:

the web page storage unit stores file name data corresponding to the web page data segments, and the additional information includes file name data of the web page data segment; and

the web page providing unit, in response to a request from one of the user terminals for one of a next page and a previous page, retrieves a corresponding web page data segment from the web page storage unit based on the file name of the web page data segment, and transmits the retrieved web page data segment to the user terminal based on the corresponding ID information; and

the additional information managing unit updates, in response to a designation of an end of reading by the user terminal, the additional information to indicate the most recently transmitted web page data segment, and stores the updated additional information.

5. An information providing method for individually providing web page data segments representing a plurality of pages including successive description from an information providing apparatus to a plurality of respective individual user terminals at respective individual timings, said method comprising:

storing the web page data segments;

storing ID information corresponding to each of the user terminals and additional information corresponding to each of the user terminals, said additional information comprising information indicating a web page data segment most recently transmitted to the corresponding user terminal;

retrieving, in response to designation of continuous provision by one of the user terminals, at least one stored web page data segment subsequent to the most recently transmitted web page data segment, based on the stored additional information corresponding to the user terminal, and individually transmitting the retrieved at least one web page data segment to the user terminal at an individual timing based on the ID information corresponding to the user terminal; and

updating, when the at least one web page data segment following the most recently transmitted web page data segment is transmitted, the additional information corresponding to the user terminal to indicate a last transmitted web page data segment as the most recently transmitted web page data segment;

wherein the additional information further comprises date/time information representing a date and time when the additional information was last updated; and

wherein, if the designation of continuous provision by the user terminal is made after a predetermined time has elapsed after the date and time indicated by the date/time information, the at least one web page data segment transmitted to the user terminal comprises a plurality of sequential said web page data segments beginning at a head page of the web page data segments and extending to a web page data segment that is a predetermined number of web page data segments subsequent to the most recently transmitted web page data segment indicated by the additional information corresponding to the user terminal.

6. The method according to claim 5, further comprising storing file name data of web page data corresponding to the web page data segments, said additional information including file name data of the web page data segment;

## 13

wherein, in response to a designation of repeat transmission by the user terminal, at least a head page of the web page data segments is transmitted to the user terminal based on the file name data in the additional information.

7. The method according to claim 5, wherein at least one of stored the ID information and the stored additional information corresponding to a user terminal is deleted, if the user terminal does not issue a request for the web page data segments for a predetermined time after the date and time indicated by the date/time information.

8. An information providing system comprising:  
an information providing apparatus connected to a communications network; and  
a plurality of terminals each of which individually receives, at respective individual timings, web page data segments representing a plurality of pages including successive description from the apparatus via the communications network;

wherein each said terminal comprises:

a web page browser which receives the web page data segments and ID information for identifying the terminal from the information providing apparatus, and which outputs the received web page data segments; and

an additional information generator which generates additional information that designates a most recently outputted web page data segment outputted by the web page browser, and which transmits the generated additional information to the information providing apparatus together with the ID information when requesting at least one said web page data segment; and

wherein the information providing apparatus comprises:

a storage unit which stores the ID information and the additional information transmitted by the terminal in association with each other; and

a transmitter which, in response to a request for the at least one said web page data segment from one said user terminal, individually transmits at least one web page data segment subsequent to the most recently outputted web page data segment to the terminal designated by the ID information at an individual timing, based on the stored additional information corresponding to the user terminal;

wherein the additional information further comprises date/time information representing a date and time when the additional information was last updated; and

wherein, if a designation of continuous provision of the web page data segments is made by the user terminal after a predetermined time has elapsed after the date and time indicated by the date/time information, the at least one web page data segment transmitted to the user terminal comprises a plurality of sequential said web page data segments beginning at a head page of the web page data segments and extending to a web page data segment that is a predetermined number of web page data segments subsequent to the most recently transmitted web page data segment indicated by the additional information corresponding to the user terminal.

9. An information providing system for individually providing ordered web page data segments representing successive sections of a document to a respective individual user terminal at a respective individual timing via a communication network, the system comprising:

a web page storage section which stores the ordered web page data segments;

## 14

an ID information managing section which, when a request is received from the user terminal, (i) generates ID information to identify the user terminal if the user terminal is a new user terminal, (ii) generates additional information for tracking a web page data segment most recently transmitted to the user terminal, and (iii) stores the ID information in association with the additional information;

a web page providing section which retrieves at least one web page data segment designated by the new user terminal from the web page storage section, and which individually transmits the retrieved web page data segment to the user terminal at an individual timing together with the generated ID information;

a provision progress managing section which updates the additional information to identify a final web page data segment of the transmitted at least one web page data segment as the most recently transmitted web page data segment; and

an ID information receiving section which, when the user terminal is a returning user terminal, receives the ID information from the user terminal which was generated by the ID information managing section;

wherein when the user terminal is a returning user terminal and the request from the returning user terminal includes an instruction to retrieve at least one web page data segment following the most recently transmitted web page data segment, the web page providing section: accesses the stored additional information corresponding to the ID information received from the user terminal, retrieves the at least one web page data segment following the most recently transmitted web page data segment identified in the accessed additional information, and transmits the retrieved at least one web page data segment;

wherein the additional information further comprises date/time information representing a date and time when the additional information was last updated; and

wherein, if a designation of continuous provision of the web page data segments is made by the returning user terminal after a predetermined time has elapsed after the date and time indicated by the date/time information, the at least one web page data segment transmitted to the user terminal comprises a plurality of sequential said web page data segments beginning at a head page of the web page data segments and extending to a web page data segment that is a predetermined number of web page data segments subsequent to the most recently transmitted web page data segment indicated by the additional information corresponding to the user terminal.

10. An information providing system which is connected to a communications network, and which provides page data segments representing a plurality of pages which include successive description via the communication network, said system comprising:

a page data storage unit which stores the page data segments;

an ID information managing unit which generates: (i) ID information representing a requester in response to a request for page data transmission, and (ii) additional information corresponding to the requester indicating a page data segment most recently transmitted to the requestor and a date and time when the most recently transmitted page data segment was transmitted, and which stores the generated ID information and additional information;

15

a page providing unit which retrieves, from the page data storage unit, at least one page data segment in accordance with the page data segment indicated by the additional information, and which transmits the retrieved at least one page data segment to the requester together with the ID information representing the requester, wherein if the request for page data transmission is received a predetermined amount of time after the date and time indicated by the additional information, the at least one page data segment transmitted to the requester comprises a plurality of sequential said page data segments beginning at a head page of the page data segments and extending to a page data segment that is a predetermined number of web page data segments subsequent to the most recently transmitted page data segment indicated by the additional information; and

a status managing unit which updates the additional information when a page data segment subsequent to the most recently transmitted page data segment is transmitted, and which cancels at least one of the additional information and the ID information corresponding to the requester if no request for page data transmission is received from the requester for a predetermined amount of time after the date and time indicated by the additional information.

11. An information providing system, the system comprising:

a first storage unit configured to store a web page data segment;

a second storage unit configured to store ID information corresponding to an individual user or individual user terminal;

a database configured to store reader information, wherein the reader information comprises an indication of a last transmitted web page data segment; and

date/time information representing a date and time when the reader information was last updated;

a providing unit configured to retrieve the web page data segment from the first storage unit in response to a command from the individual user terminal; and

transmit the retrieved web page data segment to the individual user terminal; and

a management unit configured to update the reader information to indicate a new last transmitted web page data segment;

wherein, upon a start of a new session, if a predetermined time period has lapsed since the date and time when the reader information was last updated, the providing unit transmits to the individual user terminal a plurality of sequential web page data segments beginning at a head page of the web page data segments and extending to a web page data segment that is a predetermined number of web page data segments subsequent to a most recently transmitted web page data segment indicated by the date/time information.

12. The system of claim 11, wherein the first storage unit is a web page storage unit, and wherein the second storage unit is a user ID storage unit.

13. The system of claim 11, wherein the web page data segment is a web page data segment immediately subsequent to the last transmitted web page data segment.

14. The system of claim 11, wherein the providing unit is configured to retrieve and transmit a web page data segment

16

subsequent to the last transmitted web page data segment in response to a corresponding command received from the individual user terminal.

15. The system of claim 11, wherein the providing unit is configured to transmit the retrieved web page data segment based at least in part on the ID information corresponding to the individual user terminal.

16. The system of claim 11, wherein the management unit is configured to update the reader information upon transmission of the retrieved web page data segment by the providing unit.

17. The system of claim 11, wherein the first storage unit is configured to store file name data corresponding to the web page data segment, and wherein the file name data includes the ID information corresponding to the individual user or the individual user terminal.

18. The system of claim 17, wherein the providing unit is configured to transmit the head page of the web page data segment based at least in part on the stored file name data of the web page data segment.

19. The system of claim 11, wherein the providing unit is configured to delete at least a portion of the stored ID information corresponding to the individual user or the individual user terminal if the individual user or the individual user terminal does not issue a request for the web page data segment for a second predetermined time period.

20. The system of claim 11, wherein the providing unit is configured to, in response to a request from the individual user terminal for a next page or a previous page, retrieve a corresponding web page data segment from the first storage unit and transmit the corresponding web page data segment to the individual user terminal.

21. The system of claim 11, wherein the management unit is configured to update the reader information to indicate the new last transmitted web page data segment in response to a designation of an end of reading by the individual user or the individual user terminal.

22. The system of claim 11, wherein the reader information further comprises a bookmark flag or a repeat flag, wherein the bookmark flag indicates a designation of continuous provision of webpage data segments subsequent to the last transmitted web page data segment upon the start of the new session, and wherein the repeat flag indicates a designation that the head page of the last transmitted web page data segment is to be transmitted upon the start of the new session.

23. The system of claim 11, wherein the providing unit is configured to compare user information submitted by the individual user to the ID information stored in the second storage unit to determine if the individual user is a registered user.

24. A method for providing information, said method comprising:

storing a web page data segment at a first storage unit;

storing ID information at a second storage unit, wherein the ID information corresponds to an individual user or an individual user terminal;

storing reader information at a database, wherein the reader information comprises an indication of a last transmitted web page data segment; and

date/time information representing a date and time when the reader information was last updated;

retrieving the web page data segment from the first storage unit in response to a command from the individual user terminal;

transmitting the retrieved web page data segment to the individual user terminal; and

17

updating the reader information to indicate a new last transmitted web page data segment;  
 wherein, if a predetermined time period has lapsed since the date and time when the reader information was last updated, the transmitting step comprises transmitting to the individual user terminal a plurality of sequential web page data segments beginning at a head page of the web page data segments extending to a web page data segment that is a predetermined number of web page data segments subsequent to a most recently transmitted web page data segment indicated by the date/time information.

25. The method of claim 24, wherein the first storage unit is a web page storage unit, and wherein the second storage unit is a user ID storage unit.

26. The method of claim 25, wherein the web page data segment is a web page data segment immediately subsequent to the last transmitted web page data segment.

27. The method of claim 25, wherein the retrieving step comprises retrieving a web page data segment subsequent to the last transmitted web page data segment in response to a corresponding command received from the individual user terminal, and wherein the transmitting step comprises transmitting the web page data segment subsequent to the last transmitted web page data segment in response to the corresponding command.

28. The method of claim 25, wherein the transmitting step comprises transmitting the retrieved web page data segment based at least in part on the ID information corresponding to the individual user terminal.

29. The method of claim 25, wherein the updating step comprises updating the reader information to indicate the new last transmitted web page data segment in response to the transmission of the retrieved web page data segment.

30. The method of claim 25, further comprising deleting at least a portion of the stored ID information corresponding to the individual user or the individual user terminal if the individual user or the individual user terminal does not issue a request for the web page data segment for a second predetermined time period.

31. The method of claim 25, further comprising, in response to a request from the individual user or individual user terminal for a next page or a previous page, retrieving a corresponding web page data segment from the first storage unit and transmitting the corresponding web page data segment to the individual user terminal.

32. The method of claim 25, further comprising updating the reader information to indicate the new last transmitted web page data segment in response to a designation of an end of reading by the individual user or the individual user terminal.

33. The method of claim 25, further comprising comparing user information submitted by the individual user to the ID information stored in the second storage unit to determine if the individual user is a registered user.

34. An information providing system, the system comprising:

an information providing apparatus comprising  
 a first storage unit configured to store a web page data segment;

an second storage unit configured to store ID information corresponding to an individual user or individual user terminal;

a database configured to store reader information, wherein the reader information comprises  
 an indication of a last transmitted web page data segment; and

18

date/time information representing a date and time when the reader information was last updated;

a providing unit configured to

retrieve the web page data segment from the first storage unit in response to a command from the individual user terminal; and

transmit the retrieved web page data segment to the individual user terminal; and

a management unit configured to update the reader information to indicate a new last transmitted web page data segment;

wherein, upon a start of a new session, if a predetermined time period has lapsed since the date and time when the reader information was last updated, the providing unit transmits to the individual user terminal a plurality of sequential web page data segments beginning at a head page of the web page data segments and extending to a web page data segment that is a predetermined number of web page data segments subsequent to a most recently transmitted web page data segment indicated by the date/time information; and

the individual user terminal configured to individually receive at a respective individual timing the transmitted web page data segment.

35. The system of claim 34, wherein the individual user terminal comprises:

a browser configured to receive and display the transmitted web page data segment; and

an information generator configured to generate a designation of the last transmitted web page data segment for transmission to the information providing apparatus.

36. The system of claim 34, wherein the providing unit is configured to, in response to a request from the individual user terminal for a next page or a previous page, retrieve a corresponding web page data segment from the first storage unit and transmit the corresponding web page data segment to the individual user terminal.

37. A non-transitory computer-readable storage medium having stored thereon, computer executable instructions that, if executed by a computing device, cause the computing device to perform a method comprising:

storing a web page data segment at a first storage unit;

storing ID information at a second storage unit, wherein the ID information corresponds to an individual user or an individual user terminal;

storing reader information at a database, wherein the reader information comprises

an indication of a last transmitted web page data segment; and

date/time information representing a date and time when the reader information was last updated;

retrieving the web page data segment from the first storage unit in response to a command from the individual user terminal;

transmitting the retrieved web page data segment to the individual user terminal; and

updating the reader information to indicate a new last transmitted web page data segment;

wherein, if a predetermined time period has lapsed since the date and time when the reader information was last updated, the transmitting step comprises transmitting to the individual user terminal a plurality of sequential web page data segments beginning at a head page of the web page data segments and extending to a web page data segment that is a predetermined number of web

*page data segments subsequent to a most recently transmitted web page data segment indicated by the date/time information.*

38. *The computer-readable storage medium of claim 37, wherein the web page data segment is a web page data segment immediately subsequent to the last transmitted web page data segment.* 5

39. *The computer-readable storage medium of claim 37, wherein the updating step comprises updating the reader information to indicate the new last transmitted web page data segment in response to the transmission of the retrieved web page data segment.* 10

40. *The computer-readable storage medium of claim 37, wherein the computer executable instructions cause the computing device to perform the method further comprising, in response to a request from the individual user or individual user terminal for a next page or a previous page, retrieving a corresponding web page data segment from the first storage unit and transmitting the corresponding web page data segment to the individual user terminal.* 15  
20

\* \* \* \* \*