

US00RE44452E

(19) **United States**
(12) **Reissued Patent**
Stewart et al.

(10) **Patent Number:** **US RE44,452 E**
(45) **Date of Reissued Patent:** **Aug. 27, 2013**

(54) **PEDAL POSITION AND/OR PEDAL CHANGE RATE FOR USE IN CONTROL OF AN ENGINE**

(75) Inventors: **Gregory Stewart**, North Vancouver (CA); **Syed M. Shahed**, Ranch Palos Verdes, CA (US); **Francesco Borrelli**, Kensington, CA (US); **Gregory J. Hampson**, Boulder, CO (US)

(73) Assignee: **Honeywell International Inc.**, Morristown, NJ (US)

(21) Appl. No.: **12/976,844**

(22) Filed: **Dec. 22, 2010**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,467,614**
Issued: **Dec. 23, 2008**
Appl. No.: **11/025,221**
Filed: **Dec. 29, 2004**

(51) **Int. Cl.**
F02D 13/06 (2006.01)
F02D 17/02 (2006.01)
F02M 51/00 (2006.01)
F02M 25/07 (2006.01)
F02B 33/44 (2006.01)

(52) **U.S. Cl.**
USPC **123/198 F**; 123/478; 123/568.21;
123/568.27; 701/101; 701/108; 60/605.2

(58) **Field of Classification Search**
USPC 60/600-603, 605.2; 701/99-100,
701/104, 108, 110; 123/399, 361, 682, 391,
123/198 F, 435, 568.18, 568.19, 568.21,
123/568.22, 568.27, 478; 477/102
IPC F02D 41/38
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,744,461 A 7/1973 Davis
4,005,578 A 2/1977 McInerney
4,055,158 A 10/1977 Marsee
4,206,606 A * 6/1980 Yamada 60/605.2
4,252,098 A 2/1981 Tomczak et al.
4,359,991 A 11/1982 Stumpp et al.
4,383,441 A 5/1983 Willis et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2441686 A1 * 3/2004
DE 19628796 10/1997

(Continued)

OTHER PUBLICATIONS

Bertsekas, "On the Goldstein-Levitin-Polyak Gradient Projection Method," IEEE Transactions on Automatic Control, vol. AC-21, No. 2, pp. 174-184, Apr. 1976.

(Continued)



Primary Examiner — Thai Ba Trieu

(74) *Attorney, Agent, or Firm* — Seager Tufte & Wickhem LLC.

(57) **ABSTRACT**

Systems and methods for using pedal position and/or pedal change rate in the fuel side and/or air side control of an engine. By knowing the pedal position and/or pedal rate, an engine controller may anticipate future fuel and/or air needs of the engine, and adjust the fuel profile and/or air profile to meet those anticipated needs. This may help improve the responsiveness, performance and emissions of the engine.

42 Claims, 14 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS							
4,426,982	A	1/1984	Lehner et al.	6,263,672	B1	7/2001	Roby et al.
4,438,497	A	3/1984	Willis et al.	6,273,060	B1	8/2001	Cullen
4,440,140	A	4/1984	Kawagoe et al.	6,279,551	B1	8/2001	Iwano et al.
4,456,883	A	6/1984	Bullis et al.	6,312,538	B1	11/2001	Latypov et al.
4,485,794	A	12/1984	Kimberley et al.	6,314,724	B1	11/2001	Kakuyama et al.
4,601,270	A	7/1986	Kimberley et al.	6,321,538	B2	11/2001	Hasler
4,616,308	A	10/1986	Morshedi et al.	6,327,361	B1	12/2001	Harshavardhana et al.
4,653,449	A	3/1987	Kamei et al.	6,338,245	B1	1/2002	Shimoda et al.
4,671,235	A	6/1987	Hosaka	6,341,487	B1	1/2002	Takahashi et al.
4,677,559	A	6/1987	Van Bruck	6,347,619	B1	2/2002	Whiting et al.
4,735,181	A *	4/1988	Kaneko et al. 123/399	6,360,159	B1	3/2002	Miller et al.
4,947,334	A	8/1990	Massey et al.	6,360,541	B2	3/2002	Waszkiewicz et al.
4,962,570	A *	10/1990	Hosaka et al. 123/399	6,360,732	B1	3/2002	Bailey et al.
5,044,337	A	9/1991	Williams	6,363,715	B1	4/2002	Bidner et al.
5,076,237	A	12/1991	Hartman et al.	6,363,907	B1	4/2002	Arai et al.
5,089,236	A	2/1992	Clerc	6,379,281	B1	4/2002	Collins et al.
5,095,874	A	3/1992	Schnaibel et al.	6,389,803	B1	5/2002	Surnilla et al.
5,108,716	A	4/1992	Nishizawa	6,425,371	B2	7/2002	Majima
5,123,397	A	6/1992	Richeson	6,427,436	B1	8/2002	Allansson et al.
5,150,289	A	9/1992	Badavas	6,431,160	B1	8/2002	Sugiyama et al.
5,186,081	A	2/1993	Richardson et al.	6,445,963	B1	9/2002	Blevins et al.
5,233,829	A	8/1993	Komatsu	6,446,430	B1	9/2002	Roth et al.
5,273,019	A	12/1993	Matthews et al.	6,453,308	B1	9/2002	Zhao et al.
5,282,449	A	2/1994	Takahashi et al.	6,463,733	B1	10/2002	Asik et al.
5,349,816	A	9/1994	Sanbayashi et al.	6,463,734	B1	10/2002	Tamura et al.
5,365,734	A	11/1994	Takeshima	6,466,893	B1	10/2002	Latwesen et al.
5,398,502	A	3/1995	Watanabe	6,470,682	B2	10/2002	Gray, Jr.
5,431,139	A	7/1995	Grutter et al.	6,470,866	B2	10/2002	Cook
5,452,576	A	9/1995	Hamburg et al.	6,470,886	B1	10/2002	Jestrabek-Hart
5,477,840	A	12/1995	Neumann	6,494,038	B2	12/2002	Kobayashi et al.
5,560,208	A	10/1996	Halimi et al.	6,502,391	B1	1/2003	Hirota et al.
5,570,574	A	11/1996	Yamashita et al.	6,510,351	B1	1/2003	Blevins et al.
5,598,825	A	2/1997	Neumann	6,512,974	B2	1/2003	Houston et al.
5,609,139	A	3/1997	Ueda et al.	6,513,495	B1	2/2003	Franke et al.
5,611,198	A	3/1997	Lane et al.	6,532,433	B2	3/2003	Bharadwaj et al.
5,690,086	A	11/1997	Kawano et al.	6,546,329	B2	4/2003	Bellinger
5,692,478	A	12/1997	Nogi et al.	6,553,754	B2	4/2003	Meyer et al.
5,697,339	A	12/1997	Esposito	6,560,528	B1	5/2003	Gitlin et al.
5,704,011	A	12/1997	Hansen et al.	6,560,960	B2	5/2003	Nishimura et al.
5,746,183	A	5/1998	Parke et al.	6,571,191	B1	5/2003	York et al.
5,765,533	A	6/1998	Nakajima	6,579,206	B2	6/2003	Liu et al.
5,771,867	A	6/1998	Amstutz et al.	6,591,605	B2	7/2003	Lewis
5,785,030	A	7/1998	Paas	6,594,990	B2	7/2003	Kuentler et al.
5,788,004	A	8/1998	Friedmann et al.	6,601,387	B2	8/2003	Zurawski et al.
5,842,340	A	12/1998	Bush et al.	6,612,293	B2	9/2003	Schweinzer et al.
5,846,157	A	12/1998	Reinke et al.	6,615,584	B2	9/2003	Ostertag
5,893,092	A	4/1999	Driscoll	6,625,978	B1	9/2003	Eriksson et al.
5,942,195	A	8/1999	Lecea et al.	6,629,408	B1	10/2003	Murakami et al.
5,964,199	A	10/1999	Atago et al.	6,637,382	B1	10/2003	Brehob et al.
5,970,075	A	10/1999	Wasada	6,644,017	B2	11/2003	Takahashi et al.
5,974,788	A	11/1999	Hepburn et al.	6,647,710	B2	11/2003	Nishiyama et al.
5,995,895	A	11/1999	Watt et al.	6,647,971	B2	11/2003	Vaughan et al.
6,029,626	A	2/2000	Bruestle	6,651,614	B2	11/2003	Flamig-Vetter et al.
6,035,640	A	3/2000	Kolmanovsky et al.	6,662,058	B1	12/2003	Sanchez
6,048,620	A	4/2000	Zhong	6,666,198	B2	12/2003	Mitsutani
6,048,628	A	4/2000	Zhong	6,671,603	B2	12/2003	Cari et al.
6,055,810	A	5/2000	Borland et al.	6,672,052	B2	1/2004	Taga et al.
6,058,700	A	5/2000	Yamashita et al.	6,672,060	B1	1/2004	Buckland et al.
6,067,800	A	5/2000	Kolmanovsky et al.	6,679,050	B1	1/2004	Takahashi et al.
6,076,353	A	6/2000	Fruedenberg et al.	6,687,597	B2	2/2004	Sulatsky et al.
6,105,365	A	8/2000	Deeba et al.	6,688,283	B2	2/2004	Jaye
6,122,555	A	9/2000	Lu	6,694,244	B2	2/2004	Meyer et al.
6,134,883	A	10/2000	Kato et al.	6,694,724	B2	2/2004	Tanaka et al.
6,153,159	A	11/2000	Engeler et al.	6,705,084	B2	3/2004	Allen et al.
6,161,528	A	12/2000	Akao et al.	6,718,254	B2 *	4/2004	Hashimoto et al. 701/110
6,170,259	B1	1/2001	Boegner et al.	6,718,753	B2	4/2004	Bromberg et al.
6,171,556	B1	1/2001	Burk et al.	6,722,350	B2 *	4/2004	Volz et al. 123/568.16
6,178,743	B1	1/2001	Hirota et al.	6,736,120	B2	5/2004	Surnilla
6,178,749	B1	1/2001	Kolmanovsky et al.	6,739,122	B2	5/2004	Kitajima et al.
6,208,914	B1	3/2001	Ward et al.	6,742,330	B2	6/2004	Genderen
6,216,083	B1	4/2001	Ulyanov et al.	6,743,352	B2	6/2004	Ando et al.
6,233,922	B1	5/2001	Maloney	6,748,936	B2	6/2004	Kinomura et al.
6,236,956	B1	5/2001	Mantooth et al.	6,752,131	B2	6/2004	Poola et al.
6,237,330	B1	5/2001	Takahashi et al.	6,752,135	B2	6/2004	McLaughlin et al.
6,242,873	B1	6/2001	Drozdz et al.	6,758,037	B2	7/2004	Terada et al.
				6,760,631	B1	7/2004	Berkowitz et al.
				6,760,657	B2	7/2004	Katoh
				6,770,009	B2 *	8/2004	Badillo et al. 477/102
				6,772,585	B2	8/2004	Ihoshi et al.

US RE44,452 E

6,779,344 B2	8/2004	Hartman et al.	7,493,236 B1	2/2009	Mock et al.
6,779,512 B2	8/2004	Mitsutani et al.	7,515,975 B2	4/2009	Stewart
6,788,072 B2	9/2004	Nagy et al.	7,542,842 B2	6/2009	Hill et al.
6,789,533 B1	9/2004	Hashimoto et al.	7,577,483 B2	8/2009	Fan et al.
6,792,927 B2	9/2004	Kobayashi	7,591,135 B2	9/2009	Stewart et al.
6,804,618 B2	10/2004	Junk	7,627,843 B2	12/2009	Dozorets et al.
6,805,095 B2	10/2004	Sun et al.	7,630,868 B2	12/2009	Turner et al.
6,814,062 B2	11/2004	Esteghlal et al.	7,668,704 B2	2/2010	Perchanok et al.
6,817,171 B2	11/2004	Zhu	7,743,606 B2	6/2010	Havlena et al.
6,823,667 B2	11/2004	Braun et al.	7,752,840 B2	7/2010	Stewart
6,823,675 B2	11/2004	Brunell et al.	7,765,792 B2	8/2010	Rhodes et al.
6,826,903 B2	12/2004	Yahata et al.	7,798,938 B2	9/2010	Matsubara et al.
6,827,060 B2	12/2004	Huh	7,826,909 B2	11/2010	Attarwala
6,827,061 B2	12/2004	Nytomt et al.	7,846,299 B2	12/2010	Backstrom et al.
6,827,070 B2	12/2004	Fehl et al.	7,850,104 B2	12/2010	Havlena et al.
6,834,497 B2	12/2004	Miyoshi et al.	7,856,966 B2	12/2010	Saitoh
6,839,637 B2	1/2005	Moteki et al.	7,877,239 B2	1/2011	Grichnik et al.
6,849,030 B2	2/2005	Yamamoto et al.	7,904,280 B2	3/2011	Wood
6,874,467 B2	4/2005	Hunt et al.	7,958,730 B2	6/2011	Stewart
6,879,906 B2	4/2005	Makki et al.	7,996,140 B2	8/2011	Stewart et al.
6,904,751 B2	6/2005	Makki et al.	8,019,911 B2	9/2011	Dressler et al.
6,911,414 B2	6/2005	Kimura et al.	8,265,854 B2	9/2012	Stewart et al.
6,915,779 B2	7/2005	Sriprakash	8,360,040 B2	1/2013	Stewart et al.
6,920,865 B2	7/2005	Lyon	2001/0002591 A1	6/2001	Majima
6,925,796 B2	8/2005	Nieuwstadt et al.	2002/0029564 A1	3/2002	Roth et al.
6,928,362 B2	8/2005	Meaney	2002/0056434 A1	5/2002	Flamig-Vetter et al.
6,928,817 B2	8/2005	Ahmad	2002/0073696 A1	6/2002	Kuenstler et al. 60/295
6,931,840 B2	8/2005	Strayer et al.	2002/0098975 A1	7/2002	Kimura et al.
6,941,744 B2	9/2005	Tanaka	2002/0116104 A1	8/2002	Kawashima et al.
6,945,033 B2	9/2005	Sealy et al.	2002/0170550 A1	11/2002	Mitsutani
6,948,310 B2	9/2005	Roberts, Jr. et al.	2002/0173919 A1	11/2002	Moteki et al.
6,953,024 B2	10/2005	Linna et al.	2002/0184879 A1	12/2002	Lewis
6,965,826 B2	11/2005	Andres et al.	2002/0194835 A1	12/2002	Bromberg et al.
6,968,677 B2	11/2005	Tamura	2003/0022752 A1	1/2003	Liu et al.
6,971,258 B2	12/2005	Rhodes et al.	2003/0041590 A1	3/2003	Kitajima et al.
6,973,382 B2	12/2005	Rodriguez et al.	2003/0089101 A1	5/2003	Tanaka et al.
6,978,744 B2	12/2005	Fisher et al.	2003/0089102 A1	5/2003	Colignon et al.
6,996,975 B2	2/2006	Radhamohan et al.	2003/0101713 A1	6/2003	Dalla Betta et al.
7,000,379 B2	2/2006	Makki et al.	2003/0120410 A1	6/2003	Cari et al.
7,013,637 B2	3/2006	Yoshida et al.	2003/0143957 A1	7/2003	Lyon
7,016,779 B2	3/2006	Bowyer	2003/0145837 A1	8/2003	Esteghlal et al.
7,047,938 B2	5/2006	Flynn et al.	2003/0150422 A1	8/2003	Huh
7,052,434 B2	5/2006	Makino et al.	2003/0150961 A1	8/2003	Boelitz et al.
7,055,311 B2	6/2006	Beutel et al.	2003/0172907 A1	9/2003	Nytomt et al.
7,063,080 B2	6/2006	Kitah et al.	2003/0200016 A1	10/2003	Spillane et al.
7,082,753 B2	8/2006	Dalla Betta et al.	2003/0213465 A1	11/2003	Fehl et al. 123/478
7,085,615 B2	8/2006	Persson et al.	2003/0221679 A1	12/2003	Surnilla
7,106,866 B2	9/2006	Astorino et al.	2003/0225507 A1	12/2003	Tamura
7,107,978 B2	9/2006	Itoyama	2004/0006973 A1	1/2004	Makki et al.
7,111,455 B2	9/2006	Okugawa et al.	2004/0007211 A1	1/2004	Kobayashi
7,149,590 B2	12/2006	Martin et al.	2004/0007217 A1	1/2004	Poola et al.
7,151,976 B2	12/2006	Lin	2004/0025837 A1	2/2004	Hunt et al.
7,155,334 B1	12/2006	Stewart et al.	2004/0034460 A1	2/2004	Folkerts et al.
7,165,393 B2	1/2007	Betta et al.	2004/0040283 A1	3/2004	Yasui et al.
7,165,399 B2	1/2007	Stewart	2004/0040287 A1	3/2004	Beutel et al.
7,182,075 B2	2/2007	Shahed et al.	2004/0050037 A1	3/2004	Betta et al.
7,184,992 B1	2/2007	Polyak et al.	2004/0055278 A1	3/2004	Miyoshi et al.
7,194,987 B2	3/2007	Mogi	2004/0060284 A1	4/2004	Roberts, Jr. et al.
7,200,988 B2	4/2007	Yamashita	2004/0074226 A1	4/2004	Tanaka
7,204,079 B2	4/2007	Audoin	2004/0086185 A1	5/2004	Sun
7,275,374 B2	10/2007	Stewart et al.	2004/0089279 A1	5/2004	McLaughlin et al.
7,275,415 B2	10/2007	Rhodes et al.	2004/0112335 A1	6/2004	Makino et al. 123/399
7,302,937 B2	12/2007	Ma et al.	2004/0117766 A1	6/2004	Mehta et al.
7,321,834 B2	1/2008	Chu et al.	2004/0118107 A1	6/2004	Ament
7,328,577 B2	2/2008	Stewart et al.	2004/0118117 A1	6/2004	Hartman et al.
7,337,022 B2	2/2008	Wojcisz et al.	2004/0128058 A1	7/2004	Andres et al.
7,349,776 B2	3/2008	Spillane et al.	2004/0129259 A1	7/2004	Mitsutani
7,357,125 B2	4/2008	Kolavennu	2004/0134464 A1	7/2004	Mogi
7,389,773 B2	6/2008	Stewart et al.	2004/0135584 A1	7/2004	Nagy et al.
7,392,129 B2	6/2008	Hill et al.	2004/0139735 A1	7/2004	Zhu
7,400,967 B2	7/2008	Ueno et al.	2004/0139951 A1	7/2004	Fisher et al.
7,413,583 B2	8/2008	Langer et al.	2004/0165781 A1	8/2004	Sun
7,415,389 B2	8/2008	Stewart et al.	2004/0221889 A1	11/2004	Dreyer et al.
7,418,372 B2	8/2008	Nishira et al.	2004/0226287 A1	11/2004	Edgar et al.
7,444,191 B2	10/2008	Caldwell et al.	2004/0249558 A1	12/2004	Meaney
7,444,193 B2	10/2008	Cutler	2005/0143952 A1	6/2005	Tomoyasu et al.
7,447,554 B2	11/2008	Cutler	2005/0171667 A1	8/2005	Morita
7,467,614 B2	12/2008	Stewart et al.	2005/0171670 A1*	8/2005	Yoshioka et al. 123/568.21
7,469,177 B2	12/2008	Samad et al.	2005/0178675 A1	8/2005	Hall

2005/0187643	A1	8/2005	Sayyar-Rodsari et al.
2005/0209714	A1	9/2005	Rawlings et al.
2005/0210868	A1	9/2005	Funabashi
2006/0168945	A1	8/2006	Samad et al.
2006/0265203	A1	11/2006	Jenny et al.
2006/0272315	A1	12/2006	Wang et al.
2006/0282178	A1	12/2006	Das et al.
2007/0142936	A1	6/2007	Denison et al.
2007/0144149	A1	6/2007	Kolavennu et al.
2007/0275471	A1	11/2007	Coward
2008/0071395	A1	3/2008	Pachner
2008/0097625	A1	4/2008	Vouzis et al.
2008/0125875	A1	5/2008	Stewart et al.
2008/0132178	A1	6/2008	Chatterjee et al.
2008/0183311	A1	7/2008	MacArthur et al.
2008/0208778	A1	8/2008	Sayyar-Rodsari et al.
2008/0244449	A1	10/2008	Morrison et al.
2008/0249697	A1	10/2008	Stewart et al.
2009/0005889	A1	1/2009	Sayyar-Rodsari
2009/0008351	A1	1/2009	Schneider et al.
2009/0043546	A1	2/2009	Srinivasan et al.
2009/0131216	A1	5/2009	Matsubara et al.
2009/0182518	A1	7/2009	Chu et al.
2009/0240480	A1	9/2009	Baramov
2009/0254202	A1	10/2009	Pekar et al.
2010/0017094	A1	1/2010	Stewart et al.
2010/0038158	A1	2/2010	Whitney et al.
2010/0050607	A1	3/2010	He et al.
2010/0122523	A1	5/2010	Vosz
2010/0300070	A1	12/2010	He et al.
2010/0327090	A1	12/2010	Havlena et al.
2011/0071653	A1	3/2011	Kihas
2011/0087420	A1	4/2011	Stewart et al.
2011/0167025	A1	7/2011	Danai et al.
2011/0270505	A1	11/2011	Chaturvedi et al.

FOREIGN PATENT DOCUMENTS

DE	10219382	11/2002
DE	10219832	11/2002
EP	0301527	2/1989
EP	0950803	4/1999
EP	1134368	3/2001
EP	1180583	2/2002
EP	1221544	7/2002
EP	1245811	10/2002
EP	1686251	8/2006
JP	59190443	10/1984
JP	2010282618	12/2010
WO	0232552	4/2002
WO	WO 02/101208	12/2002
WO	03048533	6/2003
WO	03065135	8/2003
WO	WO 03065135	A1 * 8/2003
WO	03078816	9/2003
WO	WO 2004/027230	4/2004
WO	2008033800	3/2008
WO	2008115911	9/2008

OTHER PUBLICATIONS

Bertsekas, "Projected Newton Methods for Optimization Problems with Simple Constraints*," Siam J. Control and Optimization, vol. 20, No. 2, pp. 221-246, Mar. 1982.

U.S. Appl. No. 12/792,468, filed Jun. 2, 2010.

"SCR, 400-csi Coated Catalyst," Leading NOx Control Technologies Status Summary, 1 page prior to the filing date of the present application.

Advanced Petroleum-Based Fuels-Diesel Emissions Control (APBF-DEC) Project, "Quarterly Update," No. 7, 6 pages, Fall 2002.

Allanson, et al., "Optimizing the Low Temperature Performance and Regeneration Efficiency of the Continuously Regenerating Diesel Particulate Filter System," SAE Paper No. 2002-01-0428, 8 pages, Mar. 2002.

Amstutz, et al., "EGO Sensor Based Robust Output Control of EGR in Diesel Engines," IEEE TCST, vol. 3, No. 1, 12 pages, Mar. 1995.

Bemporad, et al., "Explicit Model Predictive Control," 1 page, prior to filing date of present application.

Borrelli, "Constrained Optimal Control of Linear and Hybrid Systems," Lecture Notes in Control and Information Sciences, vol. 290, 2003.

Catalytica Energy Systems, "Innovative NOx Reduction Solutions for Diesel Engines," 13 pages, 3rd Quarter, 2003.

Chatterjee, et al., "Catalytic Emission Control for Heavy Duty Diesel Engines," JM, 46 pages, prior to filing date of present application.

U.S. Appl. No. 12/973,704, filed Dec. 20, 2010.

Delphi, Delphi Diesel NOx Trap (DNT), 3 pages, Feb. 2004.

GM "Advanced Diesel Technology and Emissions," powertrain technologies—engines, 2 pages, prior to filing date of present application.

Guzzella, et al., "Control of Diesel Engines," IEEE Control Systems Magazine, pp. 53-71, Oct. 1998.

Havelena, "Componentized Architecture for Advanced Process Management," Honeywell International, 42 pages, 2004.

Hiranuma, et al., "Development of DPF System for Commercial Vehicle—Basic Characteristic and Active Regeneration Performance," SAE Paper No. 2003-01-3182, Mar. 2003.

Honeywell, "Profit Optimizer A Distributed Quadratic Program (DQP) Concepts Reference," 48 pages, prior to filing date of present application.

http://www.not2fast.wryday.com/turbo/glossary/turbo_glossary.shtml,

"Not2Fast: Turbo Glossary," 22 pages, printed Oct. 1, 2004.

<http://www.tai-cwv.com/sbl106.0.html>, "Technical Overview—Advanced Control Solutions," 6 pages, printed Sep. 9, 2004.

Kelly, et al., "Reducing Soot Emissions from Diesel Engines Using One Atmosphere Uniform Glow Discharge Plasma," SAE Paper No. 2003-01-1183, Mar. 2003.

Kolmanovsky, et al., "Issues in Modeling and Control of Intake Flow in Variable Geometry Turbocharged Engines," 18th IFIP Conf. System Modeling and Optimization, pp. 436-445, Jul. 1997.

Kulhavy, et al., "Emerging Technologies for Enterprise Optimization in the Process Industries," Honeywell, 12 pages, Dec. 2000.

Locker, et al., "Diesel Particulate Filter Operational Characterization," Corning Incorporated, 10 pages, prior to filing date of present application.

Lu, "Challenging Control Problems and Engineering Technologies in Enterprise Optimization," Honeywell Hi-Spec Solutions, 30 pages, Jun. 4-6, 2001.

Moore, "Living with Cooled-EGR Engines," Prevention Illustrated, 3 pages, Oct. 3, 2004.

National Renewable Energy Laboratory (NREL), "Diesel Emissions Control—Sulfur Effects Project (DECSE) Summary of Reports," U.S. Department of Energy, 19 pages, Feb. 2002.

Salvat, et al., "Passenger Car Serial Application of a Particulate Filter System on a Common Rail Direct Injection Engine," SAE Paper No. 2000-01-0473, 14 pages, Feb. 2000.

Shamma, et al., "Approximate Set-Valued Observers for Nonlinear Systems," IEEE Transactions on Automatic Control, vol. 42, No. 5, May 1997.

Soltis, "Current Status of NOx Sensor Development," Workshop on Sensor Needs and Requirements for PEM Fuel Cell Systems and Direct-Injection Engines, 9 pages, Jan. 25-26, 2000.

Stefanopoulou, et al., "Control of Variable Geometry Turbocharged Diesel Engines for Reduced Emissions," IEEE Transactions on Control Systems Technology, vol. 8, No. 4, pp. 733-745, Jul. 2000.

Storset, et al., "Air Charge Estimation for Turbocharged Diesel Engines," vol. 1 Proceedings of the American Control Conference, 8 pages, Jun. 28-30, 2000.

The MathWorks, "Model-Based Calibration Toolbox 2.1 Calibrate complex powertrain systems," 4 pages, printed prior to filing date of present application.

The MathWorks, "Model-Based Calibration Toolbox 2.1.2," 2 pages, prior to filing date of present application.

Theiss, "Advanced Reciprocating Engine System (ARES) Activities at the Oak Ridge National Lab (ORNL), Oak Ridge National Laboratory," U.S. Department of Energy, 13 pages, Apr. 14, 2004.

Van Basshuysen et al., "Lexikon Motorentechnik," (Dictionary of Automotive Technology) published by Vieweg Verlag, Wiesbaden 039936, p. 518, 2004. (English Translation).

Zenlenka, et al., "An Active Regeneration as a Key Element for Safe Particulate Trap Use," SAE Paper No. 2001-0103199, 13 pages, Feb. 2001.

- “Model Predictive Control Toolbox Release Notes,” The Mathworks, 24 pages, Oct. 2008.
- “MPC Implementation Methods for the Optimization of the Response of Control Valves to Reduce Variability,” Advanced Application Note 002, Rev. A, 10 pages, 2007.
- Bemporad et al., “Model Predictive Control Toolbox 3, User’s Guide,” Matlab Mathworks, 282 pages, 2008.
- Bemporad et al., “The Explicit Linear Quadratic Regulator for Constrained Systems,” *Automatica*, 38, pp. 3-20, 2002.
- Bemporad, “Model Predictive Control Based on Linear Programming—the Explicit Solution,” *IEEE Transactions on Automatic Control*, vol. 47, No. 12, pp. 1974-1984, Dec. 2002.
- Bemporad, “Model Predictive Control Design: New Trends and Tools,” *Proceedings of the 45th IEEE Conference on Decision & Control*, pp. 6678-6683, Dec. 13-15, 2006.
- Boom et al., “MPC for Max-Plus-Linear Systems: Closed-Loop Behavior and Tuning”, Jun. 2001, *Proceedings of the 2001 American Control Conference*, Arlington, VA, pp. 325-300.
- Borrelli et al., “An MPC/Hybrid System Approach to Traction Control,” *IEEE Transactions on Control Systems Technology*, vol. 14, No. 3, pp. 541-553, May 2006.
- Borrelli, “Discrete Time Constrained Optimal Control,” A Dissertation Submitted to the Swiss Federal Institute of Technology (ETH) Zurich, Diss. ETH No. 14666, 232 pages, Oct. 9, 2002.
- Bunting, “Increased Urea Dosing Could Cut SCR Truck Running Costs”, <http://www.automotiveworld.com/article/85897-increased-urea-dosing-could-cut-scr-truck-running-costs>, *Automotive World*, 3 pages, Feb. 24, 2011, printed Mar. 2, 2011.
- International Application Status Report for WO 2008/033800.
- U.S. Appl. No. 13/236,217.
- U.S. Appl. No. 13/290,012.
- Johansen et al., “Hardware Architecture Design for Explicit Model Predictive Control,” *Proceedings of ACC*, 6 pages, 2006.
- Johansen et al., “Hardware Synthesis of Explicit Model Predictive Controllers,” *IEEE Transactions on Control Systems Technology*, vol. 15, No. 1, Jan. 2007.
- Keulen et al., “Predictive Cruise Control in Hybrid Electric Vehicles”, May 2009, *World Electric Journal*, vol. 3, ISSN 2032-6653.
- Maciejowski, “Predictive Control with Constraints,” Prentice Hall, Pearson Education Limited, 4 pages, 2002.
- Mariethoz et al., “Sensorless Explicit Model Predictive Control of the DC-DC Buck Converter with Inductor Current Limitation,” *IEEE Applied Power Electronics Conference and Exposition*, pp. 1710-1715, 2008.
- Marjanovic, “Towards a Simplified Infinite Horizon Model Predictive Controller,” 6 pages, *Proceedings of the 5th Asian Control Conference*, 6 pages, Jul. 20-23, 2004.
- Mayne et al., “Constrained Model Predictive Control: Stability and Optimality,” *Automatica*, vol. 36, pp. 789-814, 2000.
- Ortner et al., “MPC for a Diesel Engine Air Path Using an Explicit Approach for Constraint Systems,” *Proceedings of the 2006 IEEE Conference on Control Applications*, Munich Germany, pp. 2760-2765, Oct. 4-6, 2006.
- Ortner et al., “Predictive Control of a Diesel Engine Air Path,” *IEEE Transactions on Control Systems Technology*, vol. 15, No. 3, pp. 449-456, May 2007.
- Pannocchia et al., “Combined Design of Disturbance Model and Observer for Offset-Free Model Predictive Control,” *IEEE Transactions on Automatic Control*, vol. 52, No. 6, 6 pages, 2007.
- Qin et al., “A Survey of Industrial Model Predictive Control Technology,” *Control Engineering Practice*, 11, pp. 733-764, 2003.
- Rawlings, “Tutorial Overview of Model Predictive Control,” *IEEE Control Systems Magazine*, pp. 38-52, Jun. 2000.
- Schauffele et al., “Automotive Software Engineering Principles, Processes, Methods, and Tools,” SAE International, 10 pages, 2005.
- Schutter et al. “Model Predictive Control for Max-Min-Plus-Scaling Systems”, Jun. 2001, *Proceedings of the 2001 American Control Conference*, Arlington, VA, pp. 319-324.
- Stewart et al., “A Model Predictive Control Framework for Industrial Turbodiesel Engine Control,” *Proceedings of the 47th IEEE Conference on Decision and Control*, 8 pages, 2008.
- Stewart et al., “A Modular Model Predictive Controller for Turbodiesel Problems,” *First Workshop on Automotive Model Predictive Control*, Schloss Muhldorf, Feldkirchen, Johannes Kepler University, Linz, 3 pages, 2009.
- Tondel et al., “An Algorithm for Multi-Parametric Quadratic Programming and Explicit MPC Solutions,” *Automatica*, 39, pp. 489-497, 2003.
- “Model Predictive Control,” Wikipedia, pp. 1-5, Jan. 22, 2009. [http://en.wikipedia.org/w/index.php/title=Special:Book&bookcmd=download&collecton_id=641cd1b5da77cc22&writer=rl&return_to=Model predictive control](http://en.wikipedia.org/w/index.php/title=Special:Book&bookcmd=download&collecton_id=641cd1b5da77cc22&writer=rl&return_to=Model%20predictive%20control), retrieved Nov. 20, 2012.
- Axehill et al., “A Dual Gradient Projection Quadratic Programming Algorithm Tailored for Model Predictive Control,” *Proceedings of the 47th IEEE Conference on Decision and Control*, Cancun Mexico, pp. 3057-3064, Dec. 9-11, 2008.
- Axehill et al., “A Dual Gradient Projection Quadratic Programming Algorithm Tailored for Mixed Integer Predictive Control,” *Technical Report from Linkopings Universitet*, Report No. Li-Th-ISY-R-2833, 58 pages, Jan. 31, 2008.
- Baffi et al., “Non-Linear Model Based Predictive Control Through Dynamic Non-Linear Partial Least Squares,” *Trans IChemE*, vol. 80, Part A, pp. 75-86, Jan. 2002.
- Search Report for Corresponding, Application No. 11167549.2 dated Nov. 27, 2012.
- U.S. Appl. No. 13/290,025, filed Nov. 2011.
- De Oliveira, “Constraint Handling and Stability Properties of Model Predictive Control,” *Carnegie Institute of Technology, Department of Chemical Engineering*, Paper 197, 64 pages, Jan. 1, 1993.
- Dunbar, “Model Predictive Control: Extension to Coordinated Multi-Vehicle Formations and Real-Time Implementation,” *CDS Technical Report 01-016*, 64 pages, Dec. 7, 2001.
- Patrinos et al., “A Global Piecewise Smooth Newton Method for Fast Large-Scale Model Predictive Control,” *Tech Report TR2010-02*, National Technical University of Athens, 23 pages, 2010.
- Rajamani, “Data-based Techniques to Improve State Estimation in Model Predictive Control,” *Ph.D. Dissertation*, 257 pages, 2007.
- Takacs et al., “Newton-Raphson Based Efficient Model Predictive Control Applied on Active Vibrating Structures,” *Proceeding of the European Control Conference 2009*, Budapest, Hungary, pp. 2845-2850, Aug. 23-26, 2009.
- Wright, “Applying New Optimization Algorithms to Model Predictive Control,” *5th International Conference on Chemical Process Control*, 10 pages, 1997.
- The MathWorks, “Model-Based Calibration Toolbox 2.1 Calibrated complex powertrain systems,” 4 pages, printed prior to filing date of present application.
- The MathWorks, “Model-Based Calibration Toolbox 2.1.1,” 2 pages, prior to filing date of present application.

* cited by examiner




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5
(Prior Art)




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13




Figure 14

**PEDAL POSITION AND/OR PEDAL CHANGE
RATE FOR USE IN CONTROL OF AN
ENGINE**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

TECHNICAL FIELD

The present invention generally relates to engines, and more particularly, to methods for using pedal position and/or pedal rate in controlling engines.

BACKGROUND

Spark ignition engines typically have a gas pedal that is connected to an air throttle that meters air into engine. Stepping on the gas pedal typically opens the air throttle, which allows more air into the engine. In some cases, a fuel injector controller adjusts the fuel that is provided to the engine to maintain a desired air/fuel ratio (AFR). The AFR is typically held close to a stoichiometric ratio to produce stoichiometric combustion, which helps minimize engine emissions and allows three-way catalysts to simultaneously remove hydrocarbons, carbon monoxide, and oxides of nitrogen (NOX).

Compression ignition engines (e.g. diesel engines) typically do not operate at stoichiometric ratios, and thus greater emissions and different emission components often result. Because diesel engines are now making real headway into the car and light truck markets, federal regulations have been passed requiring more stringent emission levels for diesel engines.

Unlike spark ignition engines, the pedal of a diesel engine is typically not directly connected to an air throttle that meters air into engine. Instead, in diesel engines with electronic fuel injection (EFI), the pedal position is sensed by a pedal position sensor, and the sensed pedal position is used to control the fuel rate provided to the engine, which allows more or less fuel per fuel pump shot. In many modern diesel engines, the air to the engine is typically controlled by a turbocharger, often a Variable Nozzle Turbocharger (VNT) or waste-gate turbocharger.

In many diesel engines, there is a time delay, or “turbo-lag”, between when the operator moves the pedal—injecting more fuel—and when the turbocharger spins-up to provide the additional air required to produce the desired air-fuel ratio. This “turbo-lag” can reduce the responsiveness and performance of the engine, and can increase emissions from the engine.

There are typically no sensors in the exhaust stream of a diesel engine that are analogous to those emissions sensors found in spark ignition engines. One reason for this is that diesel engines typically operate at about twice as lean as spark so ignition engines. As such, the oxygen level in the exhaust of a diesel engine can be at a level where standard emission sensors do not provide useful information. At the same time, diesel engines typically burn too lean for conventional three-way catalysts. As such, control over combustion in a diesel engine is often performed in an “open-loop” manner, often relying on engine maps or the like to generate set points for the intake manifold parameters that are believed to be favorable for acceptable exhaust emissions.

In any event, after-treatment is often required to help clean up exhaust emissions in a diesel engine. In many cases, after-

treatment includes a “flow through oxidation” catalyst system, which typically does not have any controls. Hydrocarbons, carbon monoxide and most significantly those hydrocarbons that are adsorbed on particulates can sometimes be cleaned up when the conditions are right. Some after-treatment systems include particulate filters. These particulate filters, however, must typically be periodically cleaned often by burning off the soot particulate which has been collected on the filter to “Regenerate” the filter surface. Increasing the exhaust gas temperature is the primary way to initiate Regeneration, and injecting additional fuel in-cylinder or into an exhaust burner is one method. The control of this type of after-treatment may be based on a pressure sensor or on distance traveled, often in an open loop manner.

SUMMARY

The present invention relates to systems and methods for using pedal position and/or pedal change rate in the fuel side and/or air side control of an engine. By knowing the pedal position and/or pedal rate, an engine controller may anticipate future fuel and/or air needs of the engine, and adjust the fuel profile and/or air profile to meet those anticipated needs. This may help improve the responsiveness, performance and emissions of the engine.

In one illustrative embodiment, the present invention may be adapted for use with an internal combustion engine. The engine may have a fueling profile that defines the fuel that is delivered to the engine. The engine may also have an air charge profile that, in some cases is measured or monitored using intake manifold MAP, MAF and/or MAT sensors, that defines the air that is provided to the engine. Typically, the fueling profile is at least partially controlled by the pedal position. In one illustrative embodiment, a pedal change rate of the pedal position is identified, and an engine controller controls the air profile based, at least in part, on the pedal change rate. The fueling profile may also be controlled based, at least in part, on the pedal change rate. In some cases, a current pedal change rate and/or pedal position may be used, and in other cases, a current and/or one or more past pedal change rate and/or pedal position values may be used, as desired.

In some embodiments, the engine may have a turbocharger that boosts the manifold air pressure (MAP). The boosted MAP may be used to help control the air profile that is provided to the engine. In some cases, the MAP may be controlled based, at least in part, on the pedal change rate and/or pedal position. For example, if the pedal change rate is positive and relatively large, the MAP set point may be increased with little or no delay to meet the anticipated near term air needs of the engine. Thus may help reduce the effects of turbo lag, and may help reduce engine emissions.

In some cases, the engine may also include an exhaust recirculation valve for providing a selected amount of exhaust recirculation to the air that is provided to the engine. It is contemplated that the amount of exhaust recirculation may be based, at least in part, on the pedal change rate and/or pedal position. This may help reduce the emissions of the engine, particularly under transient operating conditions.

In some cases, an air side controller may receive a fueling rate signal from a fuel side controller. A fuel change rate of the fueling rate may be determined. The air side controller may then adjust the air profile that is provide to the engine based, at least in part, on the rate of change in the fuel rate. In some cases, the fuel rate may be controlled, at least in part, on the pedal change rate and/or pedal position.

The above summary is not intended to describe each disclosed embodiment or every implementation of the present invention. The Figures, Detailed Description and Examples which follow more particularly exemplify these embodiments.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects of the present invention and many of the attendant advantages of the present invention will be readily appreciated as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, in which like reference numerals designate like parts throughout the Figures thereof and wherein:

FIG. 1 is a schematic view of an illustrative diesel engine system in accordance with the present invention;

FIG. 2 is a schematic view of an illustrative air-side controller for use with the illustrative diesel engine system of FIG. 1;

FIG. 3 is a schematic view of an illustrative model predictive controller in accordance with the present invention;

FIG. 4 is a schematic view of another illustrative diesel engine system in accordance with the present invention;

FIG. 5 is a schematic view of a prior art speed controller;

FIG. 6 is a schematic view of an illustrative speed controller in accordance with the present invention;

FIG. 7 is a schematic view of another illustrative speed controller in accordance with the present invention;

FIG. 8 is a chart showing an engine speed set point response of a speed controller that has a dynamic map versus a static map;

FIG. 9 is a schematic view of an illustrative engine controller in accordance with the present invention;

FIG. 10 is a schematic view of another illustrative engine controller in accordance with the present invention;

FIG. 11 is a schematic view of another illustrative diesel engine system in accordance with the present invention;

FIG. 12 is a schematic view of another illustrative air-side controller in accordance with the present invention;

FIG. 13 is a schematic view of another illustrative air-side controller in accordance with the present invention; and

FIG. 14 is a schematic view of another illustrative air-side controller in accordance with the present invention.

DETAILED DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic view of an illustrative diesel engine system in accordance with the present invention. The illustrative diesel engine system is generally shown at 10, and includes a diesel engine 20 that has an intake manifold 22 and an exhaust manifold 24. In the illustrative embodiment, a fuel injector 28 provides fuel to the engine 20. The fuel injector 28 may be a single fuel injector, but more commonly may include a number of fuel injectors that are independently controllable. A fuel injector controller 26 is provided to control the fuel injector(s) 28 such that the fuel injector(s) 28 provide a desired fuel profile to the engine 20. The term fuel "profile", as used herein, may include any number of fuel parameters or characteristics including, for example, fuel delivery rate, change in fuel delivery rate, fuel timing, fuel pre-injection event(s), fuel post-injection event(s), fuel pulses, and/or any other fuel delivery characteristics, as desired. One or more fuel side actuators may be used to control these and other fuel parameters, as desired.

The fuel injector controller 26 may receive and use any number of input signals to produce the desired fuel profile.

For example, the illustrative fuel injector controller 26 receives a pedal position signal 66, an intake Manifold Air Flow (MAF) signal 50, an Engine Speed signal 68, and an Air-Fuel-Ratio (AFR) Low Limit signal 70. These signals are only illustrative. For example, and in some cases, the fuel injector controller 26 may receive one or more control signals from an air-side controller (see FIG. 2), but this is not required.

In the illustrative embodiment, exhaust from the engine 20 is provided to the exhaust manifold 24, which delivers the exhaust gas down an exhaust pipe 32. In the illustrative embodiment, a turbocharger 33 is provided downstream of the exhaust manifold 24. The illustrative turbocharger 33 includes a turbine 30, which is driven by the exhaust gas flow. In the illustrative embodiment, the rotating turbine 30 drives a compressor 34 through a mechanical coupling 36. The compressor receives ambient air through passageway 38, compresses the ambient air, and provides compressed air to the intake manifold 22, as shown.

The turbocharger 33 may be a variable nozzle turbine (VNT) turbocharger. However, it is contemplated that any suitable turbocharger may be used including, for example, a waste gated turbocharger, or a variable geometry inlet nozzle turbocharger (VGT) with an actuator to operate the waste gate or VGT vane set. The illustrative VNT turbocharger uses adjustable vanes inside an exhaust scroll to change the angle of attack of the incoming exhaust gasses as they strike the exhaust turbine 30. In the illustrative embodiment, the angle of attack of the vanes, and thus the amount of boost (MAP) pressure provided by the compressor 34, may be controlled by a VNT SET signal 42. In some cases, a VNT position signal 46 is provided to indicate the current vane position. A turbo speed signal 48 may also be provided to indicate the current turbine speed. In some cases, it may be desirable to limit the turbo speed to help prevent damage to the turbine 30.

To help reduce turbo lag, the turbine 30 may include an electrical motor assist (not explicitly shown). However, this is not required in all embodiments. The electric motor assist may help increase the speed of the turbine 30 and thus the boost pressure provided by the compressor 34 to the intake manifold 22. This may be particularly useful when the engine is at low engine RPMs and when higher boost pressure is desired, such as under high acceleration conditions. Under these conditions, the exhaust gas flow may be insufficient to generate the desired boost (MAP) pressure at the intake manifold 22. In the illustrative embodiment, an ETURBO signal may be provided to control the amount of electric motor assist that is provided.

It is contemplated that the compressor 34 may be a variable or non-variable compressor. For example, in some cases, the compressed air that is provided by the compressor 34 may be only a function of the speed at which the turbine 30 rotates the compressor 34. In other cases, the compressor 34 may be a variable geometry compressor (VGC), where in some cases, a VGC SET signal 67 is used to set the vane position at the outlet of the compressor to provide a controlled amount of compressed air to the intake manifold 22.

A compressed air cooler 40 may be provided to help cool the compressed air before the compressed air is provided to the intake manifold 22, as desired. In some embodiments, one or more compressed air cooler control signals 65 may be provided to the compressed air cooler 40 to help control the temperature of the compressed air that is ultimately provided to the intake manifold 22. In some cases, the one or more compressed air cooler control signals 65 may be provided by an air side controller (see FIG. 2), if desired.

5

In some cases, and to reduce the emissions of some diesel engines, an Exhaust Gas Recirculation (EGR) Valve **58** may be inserted between the exhaust manifold **24** and the intake manifold **22**, as shown. In the illustrative embodiment, the EGR valve **58** accepts an EGR SET signal **60**, which is used to set the desired amount of exhaust gas recirculation (EGR). An EGR POSITION output signal **62** may also be provided, if desired, which may indicate the current position of the EGR valve **58**.

In some cases, an EGR cooler **64** may be provided either upstream or downstream of the EGR valve **58** to help cool the exhaust gas before it is provided to the intake manifold **22**. In some embodiments, one or more EGR cooler control signals **69** may be provided to the EGR cooler **64** to help control the temperature of the recirculated exhaust gas. In some cases, the one or more EGR cooler control signals **69** may be provided by an air side controller (see FIG. 2), if desired.

A number of sensors may be provided for monitoring the operation of the engine **20**. For example, an intake manifold air flow (MAF) sensor **50** may provide a measure of the intake manifold air flow (MAF). An intake manifold air pressure (MAP) sensor **52** may provide a measure of the intake manifold air pressure (MAP). A manifold air temperature (MAT) sensor **53** may provide a measure of the intake manifold air temperature (MAT). A NOX sensor **56** may provide a measure of the NOX concentration in the exhaust gas. Similarly, a Particulate Matter (PM) sensor **54** may provide a measure of the particulate matter concentration in the exhaust gas. While the NOX sensor **56** and the PM sensor **54** are shown located at the exhaust manifold **24**, it is contemplated that these sensors may be provided anywhere downstream of the engine **20**, as desired. In addition, the sensors shown in FIG. 1 are only illustrative, and it is contemplated that more or less sensors may be provided, as desired.

FIG. 2 is a schematic view of an illustrative air-side controller for use with the illustrative diesel engine system of FIG. 1. The illustrative air-side controller is generally shown at **80**, and receives a number of engine parameters to help provide air-side control to the engine **20**. For example, and in one illustrative embodiment, the air-side controller **80** receives input signals such as the MAP sensor output **52**, the MAF sensor output **50**, the MAT sensor output **53**, the turbo speed signal **48**, the NOX sensor output **56** and/or the PM sensor output **54**, all shown in FIG. 1. These input parameters are only illustrative, and it is contemplated that more or less input parameters may be received, depending on the application. For example, in some illustrative embodiments, the air-side controller **80** may receive a pedal position signal **66** and/or a fuel profile signal as shown, but this is not required or even desired in some embodiments.

Based on the value of the received input parameters, the illustrative air-side controller **80** may provide a number of control outputs to help provide air-side control to the engine **20**. For example, the air-side controller **80** may provide the VNT SET signal **42**, the EGR SET signal **60**, and in some cases, the COMP. COOLER SET signal, the EGR COOLER Set signal, and the ETURBO signal **44** shown in FIG. 1.

In some cases, the air-side controller may be a multivariable Model Predictive Controller (MPC). The MPC may include a model of the dynamic process of engine operation, and provide predictive control signals to the engine subject to constraints in control variables and measured output variables. The models may be static and/or dynamic, depending on the application. In some cases, the models produce one or more output signals $y(t)$ from one or more input signals $u(t)$. A dynamic model typically contains a static model plus infor-

6

mation about the time response of the system. Thus, a dynamic model is often of higher fidelity than a static model.

In mathematical terms, a linear dynamic model has the form:

$$y(t) = B_0 * u(t) + B_1 * u(t-1) + \dots + B_n * u(t-n) + A_1 * y(t-1) + \dots + A_m * y(t-m)$$

where $B_0 \dots B_n$, and $A_1 \dots A_m$ are constant matrices. In a dynamic model, $y(t)$ which is the output at time t , is based on the current input $u(t)$, one or more past inputs $u(t-1), \dots, u(t-n)$, and also on one or more past outputs $y(t-1) \dots y(t-m)$.

A static model is a special case where the matrices $B_1 = \dots = B_n = 0$, and $A_1 = \dots = A_m = 0$, which is given by the simpler relationship:

$$y(t) = B_0 u(t)$$

A static model as shown is a simple matrix multiplier. A static model typically has no “memory” of the inputs $u(t-1), u(t-2) \dots$ or outputs $y(t-1) \dots$ etc. As a result, a static model can be simpler, but may be less powerful in modeling some dynamic system parameters.

For turbocharged diesel system, the system dynamics can be relatively complicated and several of the interactions may have characteristics known as “non-minimum phase”. This is a dynamic response where the output $y(t)$, when exposed to a step in input $u(t)$, will initially move in one direction, and then turn around and move towards its steady state in the opposite direction. The soot emission in a diesel engine is just one example. In some cases, these dynamics may be important for optimal operation of the control system. Thus, dynamic models are often preferred, at least when modeling some control parameters.

In one example, the MPC may include a multivariable model that models the effect of changes in one or more actuators of the engine (e.g. VNT SET, EGR SET, COMP COOLER SET, EGR COOLER SET, ETURBO SET, Fueling Rate, etc.) on each of two or more parameters (e.g. AFR, MAP, MAF, NOX, PM), and the multivariable controller may then control the actuators to produce a desired response in the two or more parameters. Likewise, the model may, in some cases, model the effects of simultaneous changes in two or more actuators on each of one or more engine parameters, and the multivariable controller may control the actuators to produce a desired response in each of the one or more parameters.

For example, an illustrative state-space model of a discrete time dynamical system may be represented using equations of the form:

$$x(t+1) = Ax(t) + Bu(t)$$

$$y(t) = Cx(t)$$

The model predictive algorithm involves solving the problem:

$$u(k) = \arg \min \{J\}$$

Where the function J is given by,

$$J = \hat{x}(t + N_y | t)^T P \hat{x}(t + N_y | t) +$$

$$\sum_{k=0}^{N_y-1} [\hat{x}(t+k | t)^T Q \hat{x}(t+k | t) + u(t+k)^T R u(t+k)]$$

Subject to Constraints

$$y_{min} \leq \hat{y}(t+k | t) \leq y_{max}$$

$$u_{min} \leq u(t+k) \leq u_{max}$$

7

$$x(t)=x(t)$$

$$\hat{x}(t+k|t)=A\hat{x}(t+k|t)+Bu(t+k)$$

$$\hat{y}(t+k|t)=C\hat{x}(t+k|t)$$

In some embodiments, this is transformed into a Quadratic Programming (QP) problem and solved with standard or customized tools.

The variable “y(k)” contains the sensor measurements (for the turbocharger problem, these include but are not limited to MAP, MAF, MAT, turbospeed, NOx emissions, PM emissions, etc). The variables $\hat{y}(k+t|t)$ denote the outputs of the system predicted at time “t+k” when the measurements “y(t)” are available. They are used in the model predictive controller to choose the sequence of inputs which yields the “best” (according to performance index J) predicted sequence of outputs.

The variables “u(k)” are produced by optimizing J and, in some cases, are used for the actuator set points. For the turbocharger problem these include, but are not limited to, the VNT SET, EGR SET, COMP COOLER SET, EGR COOLER SET, ETURBO, etc. The variable “x(k)” is a variable representing an internal state of the dynamical state space model of the system. The variable $\hat{x}(t+k|t)$ indicates the predicted version of the state variable k discrete time steps into the future and is used in the model predictive controller to optimize the future values of the system.

The variables y_{min} and y_{max} are constraints and indicate the minimum and maximum values that the system predicted measurements $\hat{y}(k)$ are permitted to attain. These often correspond to hard limits on the closed-loop behavior in the control system. For example, a hard limit may be placed on the PM emissions such that they are not permitted to exceed a certain number of grams per second at some given time. In some cases, only a minimum y_{min} or maximum y_{max} constraint is provided. For example, a maximum PM emission constraint may be provided, while a minimum PM emission constraint may be unnecessary or undesirable.

The variables u_{min} and u_{max} are also constraints, and indicate the minimum and maximum values that the system actuators $\hat{u}(k)$ are permitted to attain, often corresponding to physical limitations on the actuators. For example, the EGR valve may have a minimum of zero corresponding to a fully closed valve position and a maximum value of one corresponding to the fully open valve position. Like above, in some cases and depending on the circumstances, only a minimum u_{min} or maximum u_{max} constraint may be provided. Also, some or all of the constraints (e.g. y_{min} , y_{max} , u_{min} , u_{max}) may vary in time, depending on the current operating conditions. The state and actuator constraints may be provided to the air-side controller **80** of FIG. 2 via interface **78**, if desired.

The constant matrices P, Q, R are often positive definite matrices used to set a penalty on the optimization of the respective variables. These are used in practice to “tune” the closed-loop response of the system.

FIG. 3 is a schematic view of an illustrative model predictive controller in accordance with the present invention. In this embodiment, the MPC **80** includes a State Observer **82** and a MPC Controller **84**. As described above, the MPC Controller **84** provides a number of control outputs “u” to actuators or the like of the engine **20**. Illustrative control outputs include, for example, the VNT SET signal **42**, the EGR SET signal **60**, the COMP COOLER SET signal **65**, the EGR COOLER SET signal **69**, and the ETURBO SET signal **44**, all shown in FIGS. 1 and 2. The MPC Controller **84** may include a memory for storing past values of the control outputs $u(t)$, $u(t-1)$, $u(t-2)$, etc.

8

The State Observer **82** receives a number of inputs “y”, a number of control outputs “u”, and a number of internal variables “x”. Illustrative inputs “y” include, for example, the MAP sensor output **52**, the MAF sensor output **50**, a Manifold Air Temperature (MAT) signal **53**, the turbo speed signal **48**, the NOX sensor output **56**, and/or the PM sensor output **54**, shown and described above with respect to FIGS. 1 and 2. It is contemplated that the inputs “y” may be interrogated constantly, intermittently, or periodically, or at any other time, as desired. Also, these input parameters are only illustrative, and it is contemplated that more or less input signals may be provided, depending on the application. In some cases, the State Observer **82** may receive present and/or past values for each of the number of inputs “y”, the number of control outputs “u”, and a number of internal state variables “x”, depending on the application.

The State Observer **82** produces a current set of state variables “x”, which are then provided to the MPC Controller **84**. The MPC Controller **84** then calculates new control outputs “u”, which are presented to actuators or the like on the engine **20**. The control outputs “u” may be updated constantly, intermittently, or periodically, or at any other time, as desired. The engine **20** operates using the new control outputs “u”, and produces new inputs “y”.

In one illustrative embodiment, the MPC **80** is programmed using standard Quadratic Programming (QP) and/or Linear Programming (LP) techniques to predict values for the control outputs “u” so that the engine **20** produces inputs “y” that are at a desired target value, within a desired target range, and/or do not violate any predefined constraints. For example, by knowing the impact of the VNT SET position **42**, the EGR SET position **60** and/or the ETURBO SET signal **44** on the NOX and/or PM emissions, the MPC **80** may predict values for the control outputs VNT SET position **42**, EGR SET position **60** and/or the ETURBO SET signal **44** so that future values of the NOX **56** and/or PM emissions signals **54** are at or remain at a desired target value, within a desired target range, and/or do not violate current constraints. This prediction capability may be particularly useful since there is often a “turbo lag” (e.g. 1 second) from when a change in the VNT SET position **42**, EGR SET position **60** and/or the ETURBO SET signal occurs and when the resulting change in the NOX and/or PM emissions signals **56** and **54** occurs. In some cases, the constraints may change, and may depend on the current operating conditions.

It is contemplated that the MPC **80** may be implemented in the form of online optimization and/or by using equivalent lookup tables computed with a hybrid multi-parametric algorithm. Hybrid multi-parametric algorithms may allow constraints on emission parameters as well as multiple system operating modes to be encoded into a lookup table which can be implemented in an Engine Control Unit (ECU) of a vehicle. The emission constraints can be time-varying signals which enter the lookup table as additional parameters. Hybrid multi-parametric algorithm are further described by F. Borrelli in “Constrained Optimal Control of Linear and Hybrid Systems”, volume 290 of Lecture Notes in Control and Information Sciences, Springer, 2003, which is incorporated herein by reference.

Alternatively, or in addition, the MPC **80** may include one or more Proportional-Integral-Derivative (PID) control loops, one or more predictive constrained control loops—such as a Smith predictor control loop, one or more multi-parametric control loops, one or more multivariable control loops, one or more dynamic matrix control loops, one or more statistical processes control loop, a knowledge based expert system, a neural network, fuzzy logic or any other suitable

control mechanism, as desired. Also, it is contemplated that the MPC may provide commands and/or set points for lower-level controllers that are used to control the actuators of the engine. In some cases, the lower level controllers may be, for example, single-input-single-output (SISO) controllers such as PID controllers.

FIG. 4 is a schematic view of another illustrative diesel engine system in accordance with the present invention. This illustrative diesel engine system is generally shown at 100, and includes a diesel engine 102 that includes a variable nozzle turbine (VNT) turbocharger with electric motor assist and an Exhaust Gas Recirculation (EGR) Valve that is inserted between the engines' exhaust manifold and the intake manifold. A number of sensor outputs are provided for monitoring various parameters of the engine during operation. The illustrative sensor outputs include, for example, an engine speed parameter, an intake manifold air pressure (MAP) parameter, an intake manifold air flow (MAF) parameter, a turbo speed parameter, an NOX parameter and a PM parameter, as shown. These are only illustrative, and it is contemplated that more or less sensor outputs may be provided, depending on the application.

A fuel injector controller 106 is provided for controlling the fuel that is injected into the engine. The illustrative fuel injector controller 106 may include an air-fuel-ratio (AFR) estimator that receives the intake manifold air flow (MAF) parameter and a fuel rate parameter to estimate the air-fuel-ratio (AFR) going into the engine. In some cases, the air-fuel-ratio (AFR) estimator may keep the estimated AFR above a minimum AFR LOW LIMIT value, which if may help reduce smoke or other undesirable emissions that may occur at low AFR values.

The fuel injector controller 106 may control the fuel rate delivered by the fuel injectors to the engine. In some cases, a pedal position signal and an engine speed signal are used to calculate the desired amount of fuel for the engine. In some cases, stepping on the pedal increases the fuel flow in a manner dictated by one or more static and/or dynamic control maps.

In the illustrative embodiment, an air side controller 108 may also be provided. The air side controller 108 may receive a number of engine parameters to help provide air-side control to the engine 102. The term "air-side control" may include both intake air and exhaust or emission control. For example, and in the illustrative embodiment, the air-side controller 108 may receive input signals such as the MAP sensor output, the MAF sensor output, the MAT sensor output, the turbo speed signal, the NOX sensor output and the PM sensor output. These input parameters are only illustrative, and it is contemplated that more or less input signals may be received, depending on the application. Note that in this illustrative embodiment, the air side controller 108 does not receive a measure of the fueling profile 116 provided by the fuel injector controller 106. In other embodiments, however, such as those shown and described below with respect to FIGS. 11-14, the air side controller may receive a measure of the fueling profile as an input.

In any event, based on the value of the received input parameters, and in some cases on one or more past received input parameters, the illustrative air-side controller 108 may provide a number of control outputs to help provide air-side control to the engine 102. For example, the air-side controller 108 may provide a VNT SET signal, an EGR SET signal, a VGC SET signal, an ETURBO SET signal, a COMP COOLER SET signal, an EGR COOLER SET signal, etc. In some cases, the air side controller 108 may be similar to the air side controller 80 of FIG. 2.

FIG. 5 is a schematic view of a prior art speed controller 126 which is conventionally used for controlling the fuel rate delivered by the fuel injectors to an engine. The speed controller 126 receives a pedal position signal 127 and a measured engine speed signal 129, both of which are functions of time. A pedal position signal 127 may be provided to a static map 128, which is a table that relates the pedal position to an engine speed set point 130. The engine speed set point 130 is compared to the measured engine speed signal 129, and an offset signal 134 is provided to a speed control block 136. Using the offset signal, the speed control block 136 then provides a fueling rate signal 138 to one or more of the fuel injectors of the engine. The speed controller 136 may contain a fuel rate limiter designed to maintain the AFR > AFR LOW LIMIT.

FIG. 6 is a schematic view of a speed controller in accordance with one illustrative embodiment of the present invention. One difference between the speed controller 150 of FIG. 6 and the speed controller 126 of FIG. 5 is that the speed controller 150 may receive both a pedal position signal 152 and a pedal change rate signal 154. By knowing the pedal change rate in addition to the current pedal position, the speed controller 150 may anticipate future fuel and/or air needs of the engine, and may adjust the fuel profile and/or air profile to meet those anticipated needs.

For example, the speed controller 150 may provide a larger fueling rate for a given pedal position when the pedal change rate is positive and higher than when the pedal change rate is positive and smaller. Likewise, the speed controller 150 may provide a smaller fueling rate for a given pedal position when the pedal change rate is negative and higher than when the pedal change rate is negative and smaller. Similarly, the speed controller 150 may provide a larger turbo boost (MAP) for a given pedal position when the pedal change rate is positive and higher than when the pedal change rate is positive and smaller. Likewise, the speed controller 150 may provide a smaller turbo boost (MAP) for a given pedal position when the pedal change rate is negative and higher than when the pedal change rate is negative and smaller. EGR and other engine parameters may be controlled in a similar manner.

In some cases, the speed controller 150 may receive a brake position signal 156. Brake pedal sensing may be used to anticipate future fuel side needs of the engine. For example, when a driver removes pressure from a brake pedal, it may be reasonable to assume that pressure will soon be applied to the fuel pedal. The speed controller 150 may use the brake position signal 156 to help anticipate future fuel needs.

FIG. 7 is a schematic view of another illustrative speed controller in accordance with the present invention. In this illustrative embodiment, a pedal position signal 160 is provided to a first dynamic map 162. The first dynamic map 162 may translate the pedal position and a pedal change rate (and in some cases, further derivatives of the pedal position), and provide a corresponding engine speed set point 170. The first dynamic map 162 may help anticipate an acceleration of the engine and increase the current engine speed set point 170, when the pedal change rate is positive. Likewise, the first dynamic map 162 may anticipate a deceleration and decrease the current engine speed set point 170, when the pedal change rate is negative.

In the illustrative embodiment, the engine speed set point 170 is compared to a measured engine speed signal 172 via comparator 174, and an offset signal 175 is provided to a speed control block 176. Using the offset signal 175, the speed control block 176 provides a fueling rate signal 178 to one or more of the fuel injectors of the engine. In some embodiments, the speed controller 176 may also receive an

11

AFR LOW LIMIT signal **180**. As described above, the AFR LOW LIMIT signal **180** may be set to a value that if the estimated AFR of the engine falls below the AFR LOW LIMIT signal **180** value, smoke or other undesirable emissions may be expected to appear in the engine exhaust. To reduce emissions, and if the AFR falls below the AFR LOW LIMIT signal **180**, the speed controller **176** may reduce the fuel rate **178** to at least temporarily increase the AFR provided to the engine.

FIG. **8** is a chart showing an engine speed set point response of a speed controller that has a dynamic map versus a static map. An input pedal position signal is shown at **214**, which includes a step **214a** that rises from a lower position to a higher position. When a static map **128** is used and as shown and described with reference to FIG. **5**, the corresponding engine speed set point **130** produced by the static map **128** (see FIG. **5**) may have a step **130a** that corresponds to the step in the input pedal position signal **214**, as shown in FIG. **8**. However, the corresponding step **130a** in the engine speed signal **130** is merely reactive, and does not include any information or anticipate future needs of the engine.

In contrast, when a dynamic map **162** is used as shown and described with reference to FIG. **6**, the corresponding engine speed set point **170** may have a corresponding step **170a** that has a higher initial amplitude than the step **130** produced by the static map, followed by a decay region **170b** in the engine speed set point **170**, eventually leveling out at a level that is similar to that produced by the static map **128** (see FIG. **8**). When a dynamic map **162** is used, the engine speed set point **170** may include information and/or anticipate future needs of the engine, and produce an engine speed set point **170** that attempts to satisfy those future needs.

In some embodiments, it is contemplated that the dynamic map **162** may translate the pedal position and a pedal change rate (and in some cases, further derivatives of the pedal position), and provide a corresponding engine speed set point **170**. By doing so, the dynamic map **162** may help anticipate an acceleration of the engine and/or a deceleration of the engine, and produce an engine speed set point **170** that attempts to satisfy the anticipated future needs of the engine. This may, for example, help increase the performance and/or reduce the emissions of the engine.

In some embodiments, a combination of dynamic maps and look up tables may be used. For example, and in one illustrative embodiment, a first dynamic map, followed by a look up table, followed by a second dynamic map may be used. The first dynamic map may function as, for example, a pre-filter for the signal(s) entering the look up table, and the second dynamic map may function as a post filter for the signal(s) leaving the look up table. In some cases, the first dynamic filter may be a Kalman filter, an extended Kalman filter or any state observer filter, and the second dynamic filter may be the identity filter.

The look up table may be computed using any suitable method, but in some cases, using optimal or sub-optimal multi-parametric hybrid algorithms discussed above. Consistent with the multi-parametric hybrid algorithms, the lookup table may encode constraints on emission parameters in multiple engine operating modes, and may generate one or more engine control signals that are adapted to keep the engine emission or other parameters within the assigned constraints for the designated engine operating modes. In some embodiments, the look up table may accept emission control constraints as input parameters. The emission control constraints can be static or time-varying, and can be computed offline for a given set of engine operating modes, or in real or near real time, depending on the application.

12

FIG. **9** is a schematic view of another illustrative engine controller in accordance with the present invention. The illustrative engine controller of FIG. **9** is the same as the illustrative embodiment shown in FIG. **7**, but provides the pedal position to an air-side controller **204** of the engine.

In the illustrative embodiment, the pedal position signal **160** is provided to a second dynamic (or static) map **202**, which relates information about the pedal position (e.g. pedal position, pedal change rate, etc.) to one or more air side control parameters. Using the output of the second dynamic map **202**, the air side controller **204** may provide one or more control signals to help control the air side of the engine.

The air side control signals may include, for example, a VNT SET signal **206**, an EGR SET signal **208**, a VGC SET signal **218**, an ETURBO SET signal **210**, a COMP COOLER SET signal **220**, EGR COOLER SET signal **222**, and/or any other suitable signal, as desired. Like above, the air side controller **204** may receive a number of other input signals **212** such as a MAP signal, a MAF signal, a MAT signal, a turbo speed signal, a NOX signal, a PM signal, and/or any other suitable signal, as desired. By knowing, for example, the pedal position and/or pedal change rate (and in some cases, further derivatives of the pedal position), some or all of the air side control signals may be adjusted to anticipate needed changes to improve engine response time, performance and/or emissions.

For example, if the pedal change rate is relatively high, the air side controller **204** may anticipate that extra turbo boost will be necessary and may change the VNT SET signal **206** and/or VGC SET signal **218** to immediately begin providing the anticipated turbo boost with little or no delay. The EGR SET signal **208**, ETURBO SET signal **210**, COMP COOLER SET signal **220**, EGR COOLER SET signal **222**, and/or any other control signal provided by the air side controller **204** may likewise be adjusted to cancel or otherwise compensate for disrupting effects caused by changes in pedal position and/or pedal change rate. This may help improve the responsiveness, performance and/or emissions of the engine.

In some cases, the number of other input signals **212** may include a brake position signal. Brake pedal sensing may be used to anticipate future air side needs of the engine. For example, when a driver removes pressure from a brake pedal, it may be reasonable to assume that pressure will soon be applied to the fuel pedal. The air side controller **204** may use the brake position signal to help anticipate future air side needs.

FIG. **10** is a schematic view of another illustrative engine controller in accordance with the present invention. In this illustrative embodiment, the pedal position **240** is provided to a fuel side position and rate map **242** and an air side position and rate map **250**. The rate maps **242** and **250** may be dynamic maps, static maps, or combinations thereof.

In the illustrative embodiment, the fuel side rate map **242** may translate the pedal position and/or pedal change rate (and in some cases, further derivatives of the pedal position) into one or more fuel side set points **243**. A fuel side controller **244** receives the fuel side set points **243**, along with a number of fuel side sensor outputs **246** such as engine speed, MAF, MAP, MAT, etc., and provides a fueling profile **248** to the fuel injectors of the engine.

The air side rate map **250** may translate the pedal position and/or pedal change rate (and in some cases, further derivatives of the pedal position) into one or more air side parameters. Another air side set point map **252** may receive a number of other engine parameters **254** such as, a brake parameter, a temperature parameter, an outside air pressure parameter, a humidity parameter and/or any other suitable parameters, and

may provide one or more air side set points. The air side set point map **252** may be a dynamic or static map, as desired.

An air side controller **256** receives the one or more air side parameters from the air side rate map **250**, and in some cases, the one or more air side set points from the air side set point map **252**, along with one or more air side sensor output signals such as MAP, MAF, MAT, NOX, PM, turbo speed, VNT POS, EGR POS, etc., and provide one or more air side control signals, such as VNT SET, EGR SET, VGC SET, ETURBO SET, COMP COOLER SET, EGR COOLER SET, and/or any other suitable control signal, as desired.

FIG. **11** is a schematic view of another illustrative diesel engine system in accordance with the present invention. This illustrative diesel engine system is generally shown at **300**, and includes a diesel engine **302** that includes a variable nozzle turbine (VNT) turbocharger with electric motor assist and an Exhaust Gas Recirculation (EGR) Valve that is inserted between the engines' exhaust manifold and the engine's intake manifold. The illustrative diesel engine **302** also includes a variable geometry compressor (VGC), where in some cases, a VGC SET signal is used to set the vane position at the outlet of the compressor to provide a controlled amount of compressed air to the intake manifold **22**.

A number of sensor outputs are provided for monitoring various parameters of the engine during operation. The illustrative sensor outputs include an engine speed parameter, an intake manifold air pressure (MAP) parameter, an intake manifold air flow (MAF) parameter, a turbo speed parameter, an NOX parameter and a PM parameter, as shown. More or less sensor outputs may be provided, if desired.

A fuel injector controller **306** is provided for controlling the fuel that is injected into the engine. The illustrative fuel injector controller **306** may be similar to the fuel injector controller **106** described above with reference of FIG. **4**. The illustrative fuel injector controller **306** may include an air-fuel-ratio (AFR) estimator that receives the intake manifold air flow (MAF) parameter and a fuel rate parameter to estimate the air-fuel-ratio (AFR) going into the engine. In some cases, the air-fuel-ratio (AFR) estimator may keep the estimated AFR above a minimum AFR LOW LIMIT value, which if may help reduce smoke or other undesirable emissions that may occur at low AFR values.

The fuel injector controller **306** may control the fuel rate delivered by the fuel injectors to the engine. In the illustrative embodiment, a pedal position signal, a pedal rate signal, and an engine speed signal are used to calculate the desired amount of fuel for the engine. In some cases, stepping on the pedal increases the fuel flow in a manner dictated by one or more static and/or dynamic control maps, as further described above.

In the illustrative embodiment, an air side controller **320** is also provided. The air side controller **320** receives a number of engine parameters to help provide air-side control to the engine **302**. For example, and in the illustrative embodiment, the air-side controller **320** may receive input signals such as a MAP sensor output, a MAF sensor output, a turbo speed signal, a NOX sensor output and/or a PM sensor output, as shown. These input parameters are only illustrative, and it is contemplated that more or less input signals may be received, depending on the application.

In the illustrative embodiment, the air side controller **320** also receives one or more fuel profile signals **314**, which provide information related to the fuel profile that is currently provided to the engine **302**. Based on the value of the received input parameters, including the fuel profile signal(s) **314**, the illustrative air-side controller **320** provides a number of control outputs to help provide air-side control to the engine **302**.

For example, the air-side controller **320** may provide a VNT SET signal **324**, an VGC SET signal **330**, an EGR SET signal **326**, an ETURBO SET signal **328**, a COMP COOLER SET signal **332** and/or an EGR COOLER SET signal **334**. Other control signals may also be provided by the air side controller **320**, if desired.

By knowing the impact of fueling rate and/or a change in fueling rate on various engine parameters, such as MAP, MAF, MAT, turbo speed, NOX emissions, PM emissions, etc., the air side controller **320** may adjust one or more control signals such as VNT SET signal **324**, VGC SET signal **330**, EGR SET signal **326**, the ETURBO SET signal **328**, the COMP COOLER SET signal **332** and/or the EGR COOLER SET signal **334**, to cancel or mitigate disrupting effects on, for example, MAP, MAF, turbo speed, NOX emissions, PM emissions, etc. This may help improve the responsiveness, performance and/or emissions of the engine.

FIG. **12** is a schematic view of another illustrative air-side controller in accordance with the present invention. The illustrative air-side controller **340** receives a fuel profile signal **342** along with one or more other parameters **344**. The fuel profile signal **342** may include any number of fuel characteristics such as fuel delivery rate, change in fuel delivery rate, fuel timing, fuel pre-injection event(s), fuel post-injection event (s), fuel pulses, and/or any other fuel delivery characteristic, as desired. The one or more other parameters **344** may include, for example, a MAP parameter, a MAF parameter, a turbo speed parameter, a NOX parameter, a PM parameter, an engine speed parameter, a VNT position parameter, an EGR position parameter, a brake position parameter, an outside temperature parameter, an outside air pressure parameter, a humidity parameter and/or any other parameter, as desired.

The illustrative air-side controller **340** then provides one or more air side control signals to an engine. For example, the air-side controller **340** may provide a VNT SET signal **346**, a VGC SET signal **352**, an EGR SET signal **348**, an ETURBO SET signal **350**, a COMP COOLER SET signal **354**, an EGR COOLER SET signal **356** and/or any other air-side control signal, as desired.

It is contemplated that the air-side controller **340** may be implemented in the form of online optimization and/or by using equivalent lookup tables computed with a hybrid multi-parametric algorithm. Hybrid multi-parametric algorithms may allow constraints on emission parameters as well as multiple system operating modes to be encoded into a lookup table which can be implemented in an Engine Control Unit (ECU) of a vehicle. The emission constraints can be time-varying signals which enter the lookup table as additional parameters. Hybrid multi-parametric algorithm are further described by F. Borrelli in "Constrained Optimal Control of Linear and Hybrid Systems", volume 290 of Lecture Notes in Control and Information Sciences, Springer, 2003, which is incorporated herein by reference.

Alternatively, or in addition, the air-side controller **340** may include one or more Proportional-Integral-Derivative (PID) control loops, one or more predictive constrained control loops—such as a Smith predictor control loop, one or more multiparametric control loops, one or more multivariable control loops, one or more dynamic matrix control loops, one or more statistical processes control loop, a knowledge based expert system, a neural network, fuzzy logic or any other suitable control mechanism, as desired. Also, it is contemplated that the air side controller **340** may provide commands and/or set points for lower-level controllers that are used to control the actuators of the engine. In some cases, the lower level controllers may be, for example, single-input-single-output (SISO) controllers such as PID controllers.

FIG. 13 is a schematic view of another illustrative air-side controller in accordance with the present invention. The illustrative air-side controller 360 receives a fuel profile signal 362. The fuel profile signal 362 may include any number of fuel characteristics such as fuel delivery rate, change in fuel delivery rate, fuel timing, fuel pre-injection event(s), fuel post-injection event(s), fuel pulses, and/or any other fuel delivery characteristic, as desired. The illustrative air-side controller 360 may also receive other engine parameters including, for example, a MAP parameter 364, a MAF parameter 366, a turbo speed parameter 368, a NOX parameter 370, a PM parameter 372 and/or any other parameter, as desired.

The illustrative air-side controller 360 then provides one or more air side control signals to an engine. For example, the air-side controller 360 may provide a VNT SET signal 374, a VGC SET signal 380, an EGR SET signal 376, an ETURBO SET signal 378, a COMP COOLER SET signal 382 and/or an EGR COOLER SET signal 384 and/or any other air-side control signal, as desired.

It is contemplated that the air-side controller 360 may be implemented in the form of online optimization and/or by using equivalent lookup tables computed with a hybrid multi-parametric algorithm. Hybrid multi-parametric algorithms may allow constraints on emission parameters as well as multiple system operating modes to be encoded into a lookup table which can be implemented in an Engine Control Unit (ECU) of a vehicle. The emission constraints can be time-varying signals which enter the lookup table as additional parameters. Hybrid multi-parametric algorithms are further described by F. Borrelli in "Constrained Optimal Control of Linear and Hybrid Systems", volume 290 of Lecture Notes in Control and Information Sciences, Springer, 2003, which is incorporated herein by reference.

Alternatively, or in addition, the air-side controller 360 may include one or more Proportional-Integral-Derivative (PID) control loops, one or more predictive constrained control loops—such as a Smith predictor control loop, one or more multiparametric control loops, one or more multivariable control loops, one or more dynamic matrix control loops, one or more statistical processes control loop, a knowledge based expert system, a neural network, fuzzy logic or any other suitable control mechanism, as desired. Also, it is contemplated that the air side controller 360 may provide commands and/or set points for lower-level controllers that are used to control the actuators of the engine. In some cases, the lower level controllers may be, for example, single-input-single-output (SISO) controllers such as PID controllers.

FIG. 14 is a schematic view of another illustrative air-side controller in accordance with the present invention. The illustrative air-side controller is generally shown at 384. A pedal position signal 402 is provided to a Fuel Side Controller 406. The Fuel Side Controller 406 receives a number of input parameters such as an engine speed parameter, a MAF parameter, etc. via interface 408. Uses the pedal position signal 402 and the number of input parameters 408, the Fuel Side Controller 406 provides one or more fuel control signals 410 to one or more fuel side actuators, such as fuel injectors.

In the illustrative embodiment, one or more of the fuel control signals 410 are also provided to an Air Side Controller 414 as an input measured disturbance. The illustrative Air Side Controller 414 also receives a number of input signals from air side sensors via interface 420. The air side sensors may include, for example, a MAP sensor, a MAF sensor, a MAT sensor, a NOX sensor, a PM sensor, a turbo speed sensor, an engine speed sensor, and/or any other type of sensor, as desired. The illustrative Air Side Controller 414 may also receive a number of other air-side set points 417

from a Set Point Map 416. The Set Point Map 416 may translate one or more other engine parameters 418 into the one or more air side set points 417. The one or more other engine parameters may include, for example, a brake parameter, a temperature parameter, an outside air pressure parameter, a humidity parameter and/or any other desired engine parameter. The Set Point Map 416 may be a dynamic or static map, as desired.

Using the various input signals discussed above, the illustrative Air Side Controller 414 may provide one or more air side control signals 422. For example, the Air Side Controller 414 may provide a VNT SET signal, a VGC SET signal, an EGR SET signal, an ETURBO SET signal, a COMP COOLER SET signal, an EGR COOLER SET signal and/or any other air-side control signal, as desired. The illustrative embodiment may be capable of, for example, anticipating an acceleration and/or deceleration (e.g. via increased fuel rate 410), and then increase/decrease the air delivery rate to the engine with little or no delay to help improve the responsiveness, performance and/or emissions of the engine.

Having thus described the preferred embodiments of the present invention, those of skill in the art will readily appreciate that the teachings found herein may be applied to yet other embodiments within the scope of the claims hereto attached.

What is claimed is:

1. A method for controlling an internal combustion engine, the engine having an exhaust recirculation valve for providing a selected amount of exhaust gas to the intake air of the engine, the engine having a pedal position, the method comprising the steps of:

identifying a pedal position;
 identifying a pedal change rate of the pedal position;
 providing a pedal position signal and a pedal change rate signal to at least one map of a controller; and
 controlling the amount of exhaust gas recirculation that is provided to the intake air of the engine based on the pedal position signal, and the pedal change rate signal provided to the at least one map, and one or more past pedal change rates.

2. A method for controlling an internal combustion engine, the engine having a fueling profile that defines the fuel that is provided to the engine, and an air charge profile that defines the air that is provided to the engine, the fueling profile being at least partially controlled by a pedal position, the method comprising the steps of:

identifying a pedal change rate of the pedal position;
 controlling the air charge profile based on the pedal change rate;

wherein said step of controlling the air charge profile based on the pedal change rate includes the step of controlling an exhaust gas recirculation (EGR) valve to provide a selected amount of exhaust gas recirculation to the engine; and

wherein the controlling the air charge profile step uses one or more past pedal change rates.

3. A method for controlling an internal combustion engine, the engine having a fueling profile that defines the fuel that is provided to the engine, and an air charge profile that defines the air that is provided to the engine, the fueling profile being at least partially controlled by a pedal position, the method comprising the steps of:

inputting a pedal position and a pedal change rate into at least one dynamic map;

controlling the air charge profile based partially on the pedal position and based partially on the pedal change rate inputted to the at least one dynamic map; and

17

wherein said step of controlling the air charge profile based partially on the pedal position and partially on the pedal change rate includes the step of controlling an exhaust gas recirculation (EGR) valve to provide a selected amount of exhaust gas recirculation to the engine.

4. The method of claim 3, wherein said at least one dynamic map includes:

a first dynamic map adapted to provide an engine speed setpoint for controlling the fueling profile of fuel provided to the engine; and

a second dynamic map adapted to provide one or more air-side control signals for controlling the air charge profile of air provided to the engine.

5. The method of claim 3, further comprising the step of controlling the fueling profile based, at least in part, on the pedal change rate.

6. The method of claim 3, further comprising the step of controlling the fueling profile based, at least in part, on the pedal position.

7. The method of claim 3, wherein the engine includes a turbo charger for providing a turbo boost to the air that is provided to the engine, wherein the air charge profile includes the turbo boost.

8. The method of claim 7, wherein the controlling step includes controlling the turbo boost based, at least in part, on the pedal change rate.

9. The method of claim 3, wherein the controlling step uses a current pedal change rate.

10. The method of claim 3, wherein the controlling step uses one or more past pedal change rates.

11. A method for controlling an internal combustion engine, the engine having a fueling profile that defines the fuel that is provided to the engine, and an air charge profile that defines the air that is provided to the engine, the fueling profile being at least partially controlled by a pedal position, the method comprising the steps of:

identifying the pedal position;

identifying a pedal change rate of the pedal position; and controlling the air charge profile based on the identified pedal position, and the pedal change rate, and one or more past pedal change rates;

wherein said step of controlling the air charge profile based, on the pedal position, pedal change rate, and one or more past pedal change rates includes the step of controlling an exhaust gas recirculation (EGR) valve to provide a selected amount of exhaust gas recirculation to the engine.

12. A method for controlling an internal combustion engine, the engine having a fueling profile that defines the fuel that is provided to the engine, and an air charge profile that defines the air that is provided to the engine, the fueling profile being at least partially controlled by a pedal position, the method comprising the steps of:

inputting [a] the pedal position and a pedal change rate into at least one dynamic map;

controlling the air charge profile based on the pedal position, and based on pedal change rate, and based on one or more past pedal change rates inputted to the at least one dynamic map; and

wherein said step of controlling the air charge profile based on the pedal position, pedal change rate, and one or more past pedal change rates, includes the step of controlling an exhaust gas recirculation (EGR) valve to provide a selected amount of exhaust gas recirculation to the engine.

13. A method for controlling an internal combustion engine, the engine having a fueling profile that defines the fuel

18

that is provided to the engine, and an air charge profile that defines the air that is provided to the engine, the fueling profile being at least partially controlled by a pedal position, the method comprising the steps of:

identifying a pedal change rate of the pedal position;

controlling the air charge profile based, at least in part, on the pedal change rate;

wherein said step of controlling the air charge profile based, at least in part, on the pedal change rate includes the step of controlling an exhaust gas recirculation (EGR) valve to provide a selected amount of exhaust gas recirculation to the engine;

wherein the engine includes a turbo charger for providing a turbo boost to the air that is provided to the engine, wherein the air charge profile includes the turbo boost; and

wherein the controlling step includes controlling the turbo charger for adjusting the amount of turbo boost based, at least in part, on one or more past pedal change rates.

14. A method for controlling an internal combustion engine, the engine having a fueling profile that defines the fuel that is provided to the engine, and an air charge profile that defines the air that is provided to the engine, the fueling profile being at least partially controlled by a pedal position, the method comprising the steps of:

identifying the pedal position;

identifying a pedal change rate of the pedal position;

providing a pedal position signal and pedal change rate signal to at least one dynamic map of a controller; and controlling the air charge profile based on the pedal position signal and the pedal change rate signal provided to the at least one dynamic map;

wherein said step of controlling the air charge profile based on the pedal position signal and pedal change rate signal includes the step of controlling an exhaust gas recirculation (EGR) valve to provide a selected amount of exhaust gas recirculation to the engine.

15. The method of claim 14 further comprising:

controlling the fueling profile based, at least in part, on the pedal change rate.

16. The method of claim 15 further comprising the step of controlling the fueling profile based, at least in part, on the pedal position.

17. The method of claim 14 further comprising the step of controlling the fueling profile based, at least in part, on the pedal position.

18. The method of claim 14 wherein the engine includes a turbo charger for providing a turbo boost to the air that is provided to the engine, wherein the air charge profile includes the turbo boost.

19. The method of claim 18 wherein the controlling step includes controlling the turbo boost based, at least in part, on the pedal change rate.

20. The method of claim 14 wherein the controlling step uses a current pedal change rate.

21. The method of claim 14 wherein the controlling step uses one or more past pedal change rates.

22. The method of claim 14 wherein the controlling step uses one or more Proportional-Integral-Derivative (PID) control loops.

23. The method of claim 14 wherein the controlling step uses one or more predictive constrained control loops.

24. The method of claim 23 wherein at least one of the predictive constrained control loops includes a Smith predictor.

25. The method of claim 14 wherein the controlling step uses one or more multiparametric control loops.

19

26. The method of claim 14 wherein the controlling step uses one or more model based predictive control loops.

27. The method of claim 14 wherein the controlling step uses one or more dynamic matrix control loops.

28. The method of claim 14 wherein the controlling step uses one or more statistical processes control loop.

29. The method of claim 14 wherein the controlling step uses a knowledge based expert system.

30. The method of claim 14 wherein the controlling step uses a neural network.

31. The method of claim 14 wherein the controlling step uses fuzzy logic.

32. An engine controller for controlling an internal combustion engine, the engine having an exhaust recirculation valve for providing a selected amount of exhaust gas to the intake air of the engine, the engine having a pedal position, the engine controller comprising:

an input for receiving one or more signals related to the pedal position;

a controller that provides the pedal position and a pedal change rate to at least one map of the controller, and controls the amount of exhaust gas recirculation that is provided to the intake air of the engine based on the pedal position, the pedal change rate, and one or more past pedal change rates.

33. An engine controller for controlling an internal combustion engine, the engine having a fueling profile that defines the fuel that is provided to the engine, and an air charge profile that defines the air that is provided to the engine, the fueling profile being at least partially controlled by a pedal position, the engine controller comprising:

an input for receiving one or more signals related to the pedal position;

a controller that identifies a pedal change rate of the pedal position and controls the air charge profile based on the pedal change rate and/or one or more past pedal change rates, including controlling an exhaust gas recirculation (EGR) valve to provide a selected amount of exhaust gas recirculation to the engine.

34. An engine controller for controlling an internal combustion engine, the engine having a fueling profile that defines the fuel that is provided to the engine, and an air charge profile that defines the air that is provided to the engine, the fueling profile being at least partially controlled by a pedal position, the engine controller comprising:

an input for receiving one or more signals related to the pedal position;

a controller that provides a pedal position and a pedal change rate to at least one dynamic map of the controller and controls the air charge profile based at least in part on the pedal position and at least in part on the pedal

20

change rate provided to the at least one dynamic map, including controlling an exhaust gas recirculation (EGR) valve to provide a selected amount of exhaust gas recirculation to the engine.

35. The engine controller of claim 34, wherein said at least one dynamic map of the controller includes:

a first dynamic map for providing an engine speed setpoint for controlling the fueling profile of fuel provided to the engine; and

a second dynamic map for providing one or more air-side control signals for controlling the air charge profile of air provided to the engine.

36. The engine controller of claim 34, wherein the controller controls the fueling profile based, at least in part, on the pedal change rate.

37. The engine controller of claim 34, wherein the controller controls the fueling profile based, at least in part, on the pedal position.

38. The engine controller of claim 34, wherein the engine includes a turbo charger for providing a turbo boost to the air that is provided to the engine, wherein the air charge profile includes the turbo boost.

39. The engine controller of claim 38, wherein the controller controls the turbo boost based, at least in part, on the pedal change rate.

40. The engine controller of claim 34, wherein the controller controls the air charge profile based at least in part on a current pedal change rate.

41. The engine controller of claim 34, wherein the controller controls the air charge profile based at least in part on one or more past pedal change rates.

42. An engine controller for controlling an internal combustion engine, the engine having a fueling profile that defines the fuel that is provided to the engine, and an air charge profile that defines the air that is provided to the engine, wherein the engine includes a turbo charger for providing a turbo boost to the air that is provided to the engine, wherein the air charge profile includes the turbo boost, the fueling profile being at least partially controlled by a pedal position, the engine controller comprising:

an input for receiving one or more signals related to the pedal position;

a controller for controlling the air charge profile based, at least in part, on a pedal change rate and/or one or more past pedal change rates, including controlling an exhaust gas recirculation (EGR) valve to provide a selected amount of exhaust gas recirculation to the engine, and controlling the turbo charger to adjust the amount of turbo boost based, at least in part, on one or more past pedal change rates.

* * * * *