

US00RE44556E

(19) **United States**  
(12) **Reissued Patent**  
**Minich et al.**

(10) **Patent Number:** **US RE44,556 E**  
(45) **Date of Reissued Patent:** **Oct. 22, 2013**

(54) **ELECTRICAL POWER CONNECTOR**  
(75) Inventors: **Steven E. Minich**, York, PA (US);  
**Christopher J. Kolivoski**, Lewisberry,  
PA (US)  
(73) Assignee: **FCI Americas Technology LLC**,  
Carson City, NV (US)

4,821,146 A	4/1989	Behrens et al.	361/383
4,975,084 A	12/1990	Fedder et al.	439/608
5,046,960 A	9/1991	Fedder	439/108
5,139,426 A	8/1992	Barkus et al.	439/65
5,152,700 A	10/1992	Bogursky et al.	439/733
5,286,212 A	2/1994	Broeksteeg	439/108
5,458,426 A	10/1995	Ito	439/274
5,511,987 A	4/1996	Shinchi	439/205

(Continued)

(21) Appl. No.: **12/317,366**

**FOREIGN PATENT DOCUMENTS**

(22) Filed: **Dec. 22, 2008**

JP	05-344728	12/1993
JP	2000228243 A	8/2000

**Related U.S. Patent Documents**

**OTHER PUBLICATIONS**

Reissue of:

(64) Patent No.: **7,168,963**  
Issued: **Jan. 30, 2007**  
Appl. No.: **11/414,062**  
Filed: **Apr. 27, 2006**

1. Patent Abstracts of Japan, JP05-344728, Dec. 24, 1993, 1 page.

(Continued)

U.S. Applications:

(62) Division of application No. 10/969,166, filed on Oct. 17, 2004, now Pat. No. 7,065,871, which is a division of application No. 10/155,819, filed on May 23, 2002, now Pat. No. 6,814,590.

*Primary Examiner* — **Phuong Dinh**  
(74) *Attorney, Agent, or Firm* — **Harrington & Smith**

(57) **ABSTRACT**

(51) **Int. Cl.**  
**H01R 12/00** (2006.01)  
(52) **U.S. Cl.**  
USPC ..... **439/79**  
(58) **Field of Classification Search**  
USPC ..... 439/79, 80, 884  
See application file for complete search history.


A printed circuit board electrical power contact for connecting a daughter printed circuit board to a mating contact on another electrical component. The power contact includes a main section; at least one daughter board electrical contact section extending from the main section; and at least one mating connector contact section extending from the main section. The mating connector contact section includes at least three forward projecting beams. A first one of the beams extends outward in a first direction as the first beam extends forward from the main section and has a contact surface facing the first direction. Two second ones of the beams are located on opposite sides of the first beam and extend outward in a second opposite direction as the second beams extend forward from the main section. The second beams have contact surfaces facing the second direction.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

**21 Claims, 15 Drawing Sheets**

4,790,763 A	12/1988	Weber et al.	439/65
4,818,237 A	4/1989	Weber	439/693
4,820,169 A	4/1989	Weber et al.	439/65



# US RE44,556 E

Page 2

(56)

## References Cited

### U.S. PATENT DOCUMENTS

5,564,952 A 10/1996 Davis ..... 439/682  
5,664,968 A 9/1997 Mickiewicz ..... 439/608  
5,667,392 A 9/1997 Kocher et al. .... 439/79  
5,782,644 A 7/1998 Kiat ..... 439/79  
5,882,214 A 3/1999 Hillbish et al. .... 439/79  
6,041,498 A 3/2000 Hillbish et al. .... 29/883  
6,066,048 A 5/2000 Lees ..... 470/110  
6,206,722 B1 3/2001 Ko et al. .... 439/417  
6,261,132 B1 7/2001 Koseki et al. .... 439/733.1  
6,319,075 B1 11/2001 Clark et al. .... 439/825  
6,514,103 B2 2/2003 Pape et al. .... 439/608  
6,768,643 B1 \* 7/2004 Rust et al. .... 361/732

6,814,590 B2 \* 11/2004 Minich et al. .... 439/79  
6,923,685 B2 8/2005 Holmes et al. .... 439/660  
2002/0031925 A1 3/2002 Clark et al.  
2002/0034889 A1 3/2002 Clark et al.  
2008/0248670 A1 10/2008 Daily et al. .... 439/290


### OTHER PUBLICATIONS

“Metral® 1000 Series, PCB Mounted Receptacle Assembly”, FCI Web Site page, Nov. 26, 2001, 1 pg.

Metral® 1000 Series, PCB Mounted Receptacle Assembly, FCI Web Site page, 1 p.

Metral® 1000 Series, PCB Mounted Header Assembly, FCI Web Site page, 1 p.

\* cited by examiner








FIG. 2




FIG.3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9




FIG. 10






FIG. 11




FIG. 12




FIG. 13A




FIG. 13B






FIG.14




FIG.15

## ELECTRICAL POWER CONNECTOR

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.**

## CROSS REFERENCE TO RELATED APPLICATION

This is a divisional patent application of [co-pending] U.S. patent application Ser. No. 10/969,166 filed Oct. 17, 2004, now U.S. Pat. No. 7,065,871, which is a divisional patent application of U.S. patent application Ser. No. 10/155,819 filed May 23, 2002, now U.S. Pat. No. 6,814,590.

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

The present invention relates to electrical connectors and, more particularly, to electrical power connectors used to supply power to a printed circuit board.

## 2. Brief Description of Prior Developments

FCI USA, Inc. manufactures and sells printed circuit board power and signal connectors known as PwrBlade™ in a connection system. An example of the PwrBlade™ connector can be seen in U.S. Pat. No. 6,319,075. FCI USA, Inc. also manufactures and sells high-speed signal connectors known as Metral™. There is a desire to provide a printed circuit board power connector which can be stacked alongside a Metral™ connector, or a similar connector, such as the connector shown in U.S. Pat. No. 5,286,212 or a Future-Bus™ connector.

There is also a desire to increase amperage density of printed circuit board power connectors. For example, there is a desire to increase amperage density to about 60 amps per half inch in a card-to-back panel interface. Connector specifications for secondary circuits in card-to-back panel interfaces, such as standards for clearance and creepage for a given Voltage, also exist such as in UL 60950, IEC 61984 and IEC 664-1. There is a desire to provide a printed circuit board power connector system which can meet these standards for higher voltage connections, such as 150 volts or more for example.

## SUMMARY OF THE INVENTION

In accordance with one aspect of the present invention, a printed circuit board electrical power contact for connecting a daughter printed circuit board to a mating contact on another electrical component is provided. The power contact includes a main section; at least one daughter board electrical contact section extending from the main section; and at least one mating connector contact section extending from the main section. The mating connector contact section includes at least three forward projecting beams. A first one of the beams extends outward in a first direction as the first beam extends forward from the main section and has a contact surface facing the first direction. Two second ones of the beams are located on opposite sides of the first beam and extend outward in a second opposite direction as the second beams extend forward from the main section. The second beams have contact surfaces facing the second direction. These second beams are preferably one half the width of the first beam so overall normal force is equal in each direction.

In accordance with another aspect of the present invention, a system for connecting a daughter printed circuit board to a mother printed circuit board is provided. The system comprises a first power connector adapted to be mounted to the mother printed circuit board. The first power connector has a first housing and first power contacts. The system comprises a second power connector adapted to be mounted to the daughter printed circuit board. The second power connector has second power contacts with substantially flat main sections and outwardly bent contact beams having outward facing contact areas. The second power contacts are adapted to be inserted into the first housing. The system comprises a first signal connector adapted to be mounted to the mother printed circuit board. The first signal connector comprises male signal contacts. The system comprises a second signal connector adapted to be mounted to the daughter printed circuit board. The second signal connector comprises female signal contacts adapted to receive the male signal contacts therein.

In accordance with one method of the present invention, a method of manufacturing electrical power connectors is provided comprising manufacturing a first type of electrical power terminal from a metal stock material by use of a metal stamping die; inserting an insert tooling punch into the metal stamping die; stamping a second electrical power terminal and a third electrical power terminal substantially simultaneously from the metal stock material when the insert tooling punch is located in the metal stamping die; inserting the first type of electrical power terminal into a first housing to form a first type of electrical power connector, and inserting the second and third types of electrical power terminals into a second housing to form a second type of electrical power connector. The metal stamping die, and optional insertion of the insert tooling punch into the metal stamping die, can be used to form the three different electrical power terminals and subsequently form the two different types of electrical power connectors.

## BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing aspects and other features of the present invention are explained in the following description, taken in connection with the accompanying drawings, wherein:

FIG. 1 is a perspective view of a connector system incorporating features of the present invention and portions of a daughter printed circuit board and a mother printed circuit board;

FIG. 2 is a perspective view of the connector system shown in FIG. 1 from an opposite angle;

FIG. 3 is a perspective view of the first type of power electrical connector shown in FIG. 1;

FIG. 4 is a perspective view of the first type of power electrical connector shown in FIG. 3 taken from an opposite angle;

FIG. 5 is a perspective view of a first type of the electrical power contact used in the connector shown in FIG. 3;

FIG. 6 is a perspective view of the second type of power electrical connector shown in FIG. 1;

FIG. 7 is a perspective view of the second type of power connector shown in FIG. 6 taken from a generally opposite angle;

FIG. 8 is a perspective view of a second type of electrical power contact used in the connector shown in FIG. 6;

FIG. 9 is a perspective view of a third type of electrical power contact used in the connector shown in FIG. 6;

FIG. 10 is a front and top side perspective view of one of the power electrical connectors attached to the mother board shown in FIG. 1;



FIG. 11 is a rear and top side perspective view of the power electrical connector shown in FIG. 10;

FIG. 12 is a perspective view of one of the power contacts used in the power electrical connector shown in FIG. 10;

FIG. 13A is a perspective view of two of the first type of contacts formed from metal stock material on a carry strip;

FIG. 13B is a perspective view of two pairs of the second and third types of contacts formed from metal stock material on a carry strip formed with a same metal stamping die as used to form the first type of contacts shown in FIG. 13A and with use of an additional, optional insert tooling punch;

FIG. 14 is a method flow chart of one method of the present invention; and

FIG. 15 is a method flow chart of another method of the present invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIGS. 1 and 2, there are shown perspective views of a connection system 10 incorporating features of the present invention for removably connecting a daughter printed circuit board 12 to a back panel or mother printed circuit board 14. In alternate embodiments, features of the present invention could be used to connect the daughter printed circuit board to any suitable type of electrical component. Although the present invention will be described with reference to the exemplary embodiments shown in the drawings, it should be understood that the present invention can be embodied in many alternate forms of embodiments. In addition, any suitable size, shape or type of elements or materials could be used.

The connection system 10 generally comprises a daughter board connection section 16 and a mother board connection section 18. The daughter board connection section 16 generally comprises a signal connector 20, a first power connector 22, and a second power connector 24. In the embodiment shown, the three connectors 20, 22, 24 are shown stacked adjacent each other with the signal connector 20 located between the two power connectors 22, 24.

The signal connector 20 generally comprises a housing with a plurality of female signal contacts and possibly ground contacts therein. In a preferred embodiment, the signal connector 20 comprises a Metral™ receptacle connector manufactured and sold by FCI USA, Inc.

The present invention relates to a high power connector system for power-to-daughter card applications. For example, the system can be used to supply 150 Volts or more. Three power connectors will be described below; namely, a 1×2 right angle header, a 2×2 right angle header, and a 2×2 vertical receptacle that will work with both headers.

One of the features of the present invention is the ability to stack the power connectors adjacent to the signal connectors and the modularity of the connector system. For example, a connection section could be provided with two of the first type of connectors 22 located on opposite sides of the signal connector 20 or, with two of the second type of connectors 24 located on opposite sides of the signal connector 20. The present invention also allows a single type of mother board power connector 142 to be used which can be connected to either the first type of connector 22 or the second type of connector 24.

Another feature of the present invention is the increased amperage density which can be provided by the power connectors. For example, the second type of connector 24 can provide for 15 amps of current per contact for a total of 60 amps per connector. The bottom side of the connector 24 can

be as small as a half-inch, for example, such that the amperage density can be provided at about 60 amps per half inch. This increased amperage density, relative to conventional designs, can be provided due to the higher conductivity of the high performance copper alloy and, due to the increased air flow through the connector housings 26, 74, 144 (see FIGS. 4, 7 and 10).

Another feature of the present invention is the ability for the power connectors to meet specification standards for a given voltage for secondary circuit power card-to-back panel interfaces. More specifically, it has been found that implementation of the present invention can meet the specifications for UL 60950, IEC 61984 and IEC 664-1 for a 150-160 Volt secondary circuit power card-to-back panel connection.

Referring also to FIGS. 3-5, the first power connector 22 generally comprises a housing 26 and two electrical power contacts or terminals 28. The housing 26 is preferably comprised of a molded plastic or polymer material. The housing 26 generally comprises a rear section 30 and a front section 32. The rear section 30 generally comprises contact mounting areas 34 formed along air flow passages 36. In the embodiment shown, the air flow passages 36 form a majority of a cross sectional size of the rear section 30.

The air flow passages 36 comprise holes through a top side 38 and a rear side 40 and bottom side of the rear section 30. The bottom side of the rear section 30 includes mounting posts 42 for mounting the housing on the daughter printed circuit board 12. However, in alternate embodiments, any suitable means for mounting the housing 26 on the daughter printed circuit board could be provided.

The front section 32 generally comprises a mating connector receiving area 44, air passage holes 46, 48 at top and bottom sides of the front section, and mating connector aligner receiving grooves 50. The mating connector receiving area 44 is sized and shaped to receive a portion of a mating connector of the mother board connection section 18. The mating connector aligner receiving grooves 50, in the embodiment shown, are located on a top side and two lateral sides of the front section 32. The air passage holes 46, 48 are provided to allow air to flow into and out of the mating connector receiving area 44.

The power contacts 28, in the embodiment shown, are identical to each other. However, in alternate embodiments, the power contacts could be different from one another. The embodiment shown comprises two of the power contacts 28. In alternate embodiments the power connector could comprise more than two power contacts. As seen best in FIG. 5, each power contact 28 generally comprises a main section 52, daughter board electrical contact sections 54, and mating connector contact sections 56. The power contact 28 comprises two of the mating connector contact sections 56. However, in alternate embodiments, the power contact 28 could comprise more or less than two of the mating connector contact sections.

The power contact 28 is preferably comprised of a one-piece metal member which has been stamped and subsequently plated; at least at some of its contact surfaces. The power contact 28 is substantially flat except at the mating connector contact sections 56. In the embodiment shown, the daughter board electrical contact sections 54 comprise a plurality of through-hole contact tails. However, in alternate embodiments, any suitable type of daughter board electrical contact sections could be provided.

The main section 52 comprises a first retention section 66 located at a rear end of the main section and a second retention section 68 extending from a bottom side of the main section. The retention sections 66, 68 engage with the housing 26 to



5

fixedly hold the main section **52** in the housing. However, in alternate embodiments, any suitable system for retaining the power contacts with the housing could be provided. The main section **52** comprises a recess **70** at the first retention section **66**. A crossbar **72** at the rear end of the housing **26** is received in the recess **70**. In the embodiment shown, the contacts **28** are loaded into the housing **26** through the front end of the housing; through the mating connector receiving area **44**.

The mating connector contact sections **56** are substantially identical to each other. However, in alternate embodiments, the mating connector contact sections could be different from each other. Each mating connector contact section **56** generally comprises three forward projecting cantilevered beams; a first beam **58** and two second beams **60**. However, in alternate embodiments, the mating connector contact section could comprise more or less than three cantilevered contact beams.

The first beam **58** extends outward in a first direction as the first beam extends forward from the main section **52**. The first beam **58** has a contact surface **62** facing outward in the first direction. The second beams **60** are located on opposite top and bottom sides of the first beam **58**. The second beams **60** extend outward in a second opposite direction as the second beams extend forward from the main section **52**. The second beams **60** have contact surfaces **64** facing outward in the second direction.

The beams **58**, **60** are bent outward about 15 degrees from a central plain of the power contact. However, in alternate embodiments, any suitable angle could be provided. In the embodiment shown, the front ends of the beams **58**, **60** are curved inward and also comprise coined surfaces on their outer contact surfaces **62**, **64**. When the power contacts are inserted into the housing **26**, the mating connector contact sections **56** are located in the mating connector receiving area **44**.

In a preferred embodiment, the power contact is comprised of a highly conductive high-performance copper alloy material. Some high performance copper alloy materials are highly conductivity material. One example of a highly conductive high-performance copper alloy material is sold under the descriptor C18080 by Olin Corporation. However, in alternate embodiments, other types of materials could be used. A highly conductive high-performance copper alloy material may have a minimum bend radius to material thickness ratio (R/T) of greater than one; whereas common conventional metal conductors may have a R/T of less than 1/2. However, a highly conductive high performance copper alloy material may not be as malleable as other common electrically conductive materials used for electrical contacts. Thus, an electrical contact formed with a highly conductive high-performance copper alloy material may be more difficult to form in conventional contact stamping and forming dies.

Referring also to FIGS. **6-9**, the second power connector **24** generally comprises a housing **74** and four electrical power contacts or terminals **76**, **78**. The housing **74** is preferably comprised of a molded plastic or polymer material. The housing **74** generally comprises a rear section **80** and a front section **82**. The rear section **80** generally comprises contact mounting areas **84** formed along air flow passages **86**.

In the embodiment shown, the air flow passages **86** form a majority of a cross sectional size of the rear section **80**. The air flow passages **86** comprise holes through a top side **88** and a rear side **90** and bottom side of the rear section **80**. The bottom side of the rear section **80** includes mounting posts **92** for mounting the housing on the daughter printed circuit board **12**. In the embodiment shown, the housing **74** is substantially the same as the housing **26** except for the shape of the contact mounting areas **84**.

6

The front section **82** is identical to the front section **32**. However, in alternate embodiments, the front section **82** could comprise a different shape. The front section **82** generally comprises a mating connector receiving area **94**, air passage holes **96**, **98** at top and bottom sides of the front section, and mating connector aligner receiving grooves **100**. The mating connector receiving area **94** is sized and shaped to receive a portion of a mating connector of the mother board connection section **18**. The mating connector aligner receiving grooves **100**, in the embodiment shown, are located on a top side and two lateral sides of the front section **82**. The air passage holes **96**, **98** are provided to allow air to flow into and out of the mating connector receiving area **94**.

As noted above, the connector **24** comprises four power contacts **76**, **78**. However, in alternate embodiments, the connector could comprise more or less than four power contacts. The power contacts are provided in two sets, each set comprising a second type of contact **76** and a third type of contact **78**. The two contacts in each set are aligned with each other in a same plane as an upper contact and a lower contact.

The second and third types of power contacts **76**, **78** are each preferably comprised of a one-piece metal member which has been stamped and subsequently plated. The power contact **76**, **78** are substantially flat except at their mating connector contact sections. In the embodiment shown, the daughter board electrical contact sections comprise a plurality of through-hole contact tails.

As seen best in FIG. **8**, each second type of power contact **78** generally comprises a main section **102**, daughter board electrical contact sections **104**, and mating connector contact section **106**. The power contact **78** comprises only one mating connector contact section **106**. However, in alternate embodiments, the second type of power contact **78** could comprise more than one mating connector contact section.

The main section **102** comprises a retention section **118** located at a bottom side of the main section. The retention sections engage with the housing **26** to fixedly hold the main section **102** in the housing. In the embodiment shown, the contacts **78** are loaded into the housing **74** through the rear end of the housing.

As seen best in FIG. **9**, each third type of power contact **76** generally comprises a main section **122**, daughter board electrical contact sections **124**, and a mating connector contact section **126**. The power contact **76** comprises only one mating connector contact section **126**. However, in alternate embodiments, the second type of power contact **76** could comprise more than one mating connector contact section.

The main section **122** comprises a retention section **138** located at a bottom side of the main section. The retention sections engage with the housing **74** to fixedly hold the main section **122** in the housing. In the embodiment shown, the contacts **76** are loaded into the housing **74** through the front end of the housing; through the mating connector receiving area **94**.

The mating connector contact sections **106**, **126** are identical to each other and to the mating connector contact section **56**. However, in alternate embodiments, the mating connector contact sections could be different from each other. When the power contacts **76**, **78** are inserted into the housing **74**, the mating connector contact sections **106**, **126** are located in the mating connector receiving area **94**. Each mating connector contact section **106**, **126** generally comprises the three forward projecting cantilevered beams; the first beam **58** and the two second beams **60**. However, in alternate embodiments, the mating connector contact section could comprise more or less than three cantilevered contact beams.



The first beam **58** extends outward in a first direction as the first beam extends forward from the main section. The first beam **58** has a contact surface **62** facing the first direction. The second beams **60** are located on opposite top and bottom sides of the first beam **58**. The second beams **60** extend outward in a second opposite direction as the second beams extend forward from the main section **52**. The second beams **60** have contact surfaces **64** facing the second direction.

The beams **58**, **60** are bent outward about 15 degrees from a central plain of the power contacts. However, in alternate embodiments, any suitable angle could be provided. In the embodiment shown, the front ends of the beams **58**, **60** are curved inward and also comprise coined surfaces on their outer contact surfaces **62**, **64**. The front ends of the beams **58**, **60** could comprise any suitable type of shape.

In a preferred embodiment, the power contacts **76**, **78** are comprised of a high-performance copper alloy material. However, in alternate embodiments, other types of materials could be used. As noted above, a highly conductive high performance copper alloy material can have a higher conductivity, but might not be as malleable as other common electrically conductive materials used for electrical contacts. Thus, an electrical contact formed with a highly conductive high-performance copper alloy material might be more difficult to form in a conventional contact stamping and forming die. However, the shape of the mating connector contact sections **56**, **106**, **126** has been specifically designed to be relatively easily formed by a stamping process even though the stock material used to form the contacts comprises a relatively low malleability, high conductivity high-performance copper alloy material.

A feature of the present invention is the contact geometry at the mating connector contact sections **56**, **106**, **126**. The contact geometry provides the ability to raise or lower the normal force of the contact beams **58**, **60** on the contacts **146** by merely lengthening or shortening the length of the beams. The contact geometry requires only minimal forming at the mating interface. This is extremely beneficial for use with relatively low malleability materials, such as some high-performance copper alloys.

Compared to a conventional design, such as disclosed in the U.S. Pat. No. 6,319,075, the contact geometry and the minimized forming needed to be done at the mating interface **56**, **106**, **126**, reduces tooling costs, reduces material costs, maximizes voltage rating, and allows the housing to be designed to permit more air flow through the mated connector system. The header terminal design can be adjusted to optimize the normal force, by adjusting beam length, because of the opposing beam design. Two small beams **60** opposing one larger beam **58** causes the net bending moment on the housing to be minimized.

As noted above, one feature of the present invention is the increased amperage density which can be provided by the power connectors. For example, the second type of connector **24** can provide for 15 amps of current per contact for a total of 60 amps per connector. The bottom side of the connector **24** can be as small as a half-inch, for example, such that the amperage density can be provided at about 60 amps per half inch. This increased amperage density, relative to conventional designs, can be provided due to the higher conductivity of the high performance copper alloy and, due to the increased air flow through the connector housings **26**, **74**, **144** (see FIGS. **4**, **7** and **10**).

Also as noted above, another feature of the present invention is the ability for the power connectors to meet specification standards for a given voltage for secondary circuit power card-to-back panel interfaces. More specifically, it has been

found that implementation of the present invention can meet the specifications for UL 60950, IEC 61984 and IEC 664-1 for a 150-160 Volt secondary circuit power card-to-back panel connection.

The mother board connection section **18** (see FIGS. **1** and **2**) generally comprises a signal connector **140** and two power connectors **142**. In the embodiment shown, the three connectors **140**, **142** are shown stacked adjacent each other with the signal connector **140** located between the two power connectors **142**.

The signal connector **140** generally comprises a header connector with a housing with a plurality of male signal contacts and possibly ground contacts. In a preferred embodiment, the signal connector **140** comprises a Metral™ header connector manufactured and sold by FCI USA, Inc.

Referring also to FIGS. **10-12**, the power connectors **142** each generally comprises a housing **144** and electrical power contacts or terminals **146**. The housing **142** is preferably comprised of a molded plastic or polymer material. The housing **142** generally comprises four receiving areas **148**; one for each of the mating connector contact sections of the connector **22** or **24**. However, in alternate embodiments, the housing could comprise more or less than four receiving areas. In the embodiment shown, the housing **144** also comprises three aligners **154** located on three respective sides of the housing and projecting from a front end of the housing. The aligners **154** are sized and shaped to be received in the aligner receiving areas **50**, **100** of the connector **22** or **24**. The aligners **154** function as protruding guide features to ensure that both mating housings are properly positioned before mating begins.

Top and bottom sides of the housing **144** also comprise holes **156** therethrough. When one of the connectors **22** or **24** are connected to one of the connectors **142**, the holes **156** are at least partially aligned with the holes **46**, **48**, or **96**, **98**. This allows air to flow through the holes into and out of the mating connector receiving area **44** and inside the connector **142**. In a preferred embodiment, the housing **144** is cored to allow for air flow through the mating connector system. The increased air flow allows for increased heat dissipation from the power contacts **28**, **76**, **78**.

In the embodiment shown, the power connector **142** comprises eight of the power contacts **146**. However, in alternate embodiments, more or less than eight power contacts could be provided. Each power contact **146** comprises mother board mounting sections **150** and a main section **152**. The power contacts **146** are preferably formed from a flat stock material and, after being formed, each power contact **146** comprises a general flat shape.

In the embodiment shown, two of the power contacts **146** are inserted into each one of the receiving areas **148**. More specifically, the two power contacts **146** are inserted adjacent opposite sides of each receiving area **148**. This forms an area between the two power contacts **146** in each receiving area **148**, located between the opposing interior facing contact surfaces of the two power contacts, which is sized and shaped to receive one of the mating connector contact sections **56**, **106** or **126**.

The present invention provides an inverse connection system. When the daughter board connection section **16** is mated with the motherboard connection section **18**, the two signal connectors **20**, **140** mate with each other and the two power connectors **22**, **24** mate with respective ones of the power connectors **142**. The mating connector contact sections **56**, **106**, **126** project into the receiving areas **148**. The contact surfaces **62** of the first beams **58** contact a first one of the pair of power contacts **146**, and the contact surfaces **64** of the



second beams **60** contact a second one of the pair of power contacts in the same receiving area **148**. The first contact beams **58** are deflected slightly inward and the second contact beams **60** are also deflected slightly inward in an opposite direction relative to the first contact beams. Thus, the mating connector contact sections **56**, **106**, **126** make electrical contact on two inwardly facing sides with the pairs of power contacts in the mating power connector **142**.

As seen in comparing the a first type of power contact **28** shown in FIG. **5** to the second and third power contacts **78**, **76** shown in FIGS. **8** and **9**, the contacts share numerous similarities. In one type of method for forming the contacts, a same metal stamping die is used to form all of the contacts. The apparatus used to stamp the metal stock material includes an optional insert tooling punch which can be inserted into the metal stamping die. The metal stamping die can form the first type of electrical power contact **28** when the insert tooling punch is not inserted into the metal stamping die. However, when the insert tooling punch is inserted into the metal stamping die, then, when the metal stock material is stamped by both the metal stamping die and the insert tooling punch, the second electrical power contact **78** and the third electrical power contact **76** are substantially simultaneously formed from the metal stock material.

Referring to FIGS. **13A** and **13B**, FIG. **13A** shows a perspective view of two of the first type of contacts **28** formed from metal stock material on a carry strip **116**, and FIG. **13B** shows a perspective view of two pairs of the second and third types of contacts **76**, **78** formed from metal stock material on a carry strip **116** formed with a same metal stamping die as used to form the first type of contacts **28** shown in FIG. **13A** and with use of an additional, optional insert tooling punch. The insert tooling punch removes sections **160**, **161** to separate the contacts **76**, **78**. Thus, the metal stamping die and the optional insert tooling punch can be used to form the three different types of electrical power contacts and subsequently form the two different types of electrical power connectors **22**, **24**.

Referring now to FIGS. **14** and **15**, this method is illustrated. As shown in FIG. **14**, the stock material is inserted into the stamping apparatus. The stamping apparatus then stamps **162** the stock material without the insert tooling punch inserted in the metal stamping die. The formed first type of contact is then plated **164** and inserted **166** into the first type of housing. This forms the first type of connector **22**.

FIG. **15** illustrates the steps for forming the second type of connector **24**. The insert tooling punch is inserted **168** into the metal stamping die. The stock material is inserted **170** into the stamping apparatus. The stamping apparatus then stamps **172** the stock material with both the metal stamping die and the insert tooling punch. This forms the second and third types of contacts **78**, **76** which are subsequently plated **174**. The second and third types of contacts are then inserted **176** into the second type of housing to form the second type of power connector **24**. This method illustrates merely one form of method that can be used to form power connectors incorporating features of the present invention. In alternate embodiments, any suitable method for forming the power connectors as described above could be used.

The present invention could be embodied or used with other alternate embodiments than described above. For example, the daughter board connection section **16** could comprise more or less than the three connectors, and one or more of the connectors might not be stacked adjacent the other connectors. In addition, in another type of alternate embodiment, the housings for two or more of the connectors might be formed by a one-piece molded housing. The signal

connector **20** could comprise any suitable type of signal connector. The air flow passages **36** might not form a majority of a cross sectional size of the rear section **30**. The air flow passages **36** in the rear section **30** could also comprise any suitable size and shape. Any suitable system for loading the contacts into the housing could be provided. The front ends of the beams **58**, **60** could comprise any suitable type of shape. Features of the present invention could be incorporated into vertical headers, right angle receptacles, and power connectors with different contact arrays other than the 1×2 and 2×2 contact arrays described above.

It should be understood that the foregoing description is only illustrative of the invention. Various alternatives and modifications can be devised by those skilled in the art without departing from the invention. Accordingly, the present invention is intended to embrace all such alternatives, modifications and variances which fall within the scope of the appended claims.

What is claimed is:

1. A printed circuit board electrical power contact for connecting a daughter printed circuit board to a mating contact on another electrical component, the power contact comprising:
  - a main section;
  - at least one daughter board electrical contact section extending from the main section; and
  - at least one mating connector contact section extending from the main section, the mating connector contact section comprising at least two forward projecting beams, wherein a first one of the beams extends outward in a first direction as the first beam extends forward from the main section and has a contact surface facing the first direction, and wherein a second one of the beams extends outward in a second opposite direction as the second beam extends forward from the main section and has a contact surface facing the second direction, wherein the first beam is larger than the second beam.
2. A system for connecting a daughter printed circuit board to a mother printed circuit board, the system comprising:
  - a first power connector adapted to be mounted to the mother printed circuit board, the first power connector having a first housing and first power contacts;
  - a second power connector adapted to be mounted to the daughter printed circuit board, the second power connector having a plurality of second power contacts, each second power contact having a main section with outwardly bent contact beams having outward facing contact areas, the outwardly bent contact beams comprising a first contact beam which is larger than a second contact beam, wherein the first and second contact beams extend in generally opposite directions from a front end of the main section, and wherein the second power contacts are adapted to be inserted into the first housing;
  - a first signal connector adapted to be mounted to the mother printed circuit board, the first signal connector comprising male signal contacts; and
  - a second signal connector adapted to be mounted to the daughter printed circuit board, the second signal connector comprising female signal contacts adapted to receive the male signal contacts therein.
3. An electrical contact comprising:
  - a main section;
  - a first electrical contact section extending from the main section, wherein the first electrical contact section is adapted to connect to a first device; and
  - a second electrical contact section extending from the main section, wherein the second electrical contact section is adapted to connect to a second device, wherein the sec-



## 11

ond electrical contact section comprises at least two beams projecting from the main section in a connection direction for connecting the second electrical contact section to the second device, wherein a first one of the beams extends outward in a first direction as well as in the connection direction from the main section and has a first contact surface facing the first direction, wherein a second one of the beams extends outward in a second direction as well as in the connection direction from the main section and has a second contact surface facing the second direction, and wherein the first beam is larger than the second beam.

4. An electrical contact as in claim 3 wherein the second direction is generally opposite to the first direction.

5. An electrical contact as in claim 3 wherein the second direction is a lateral direction relative to the connection direction.

6. An electrical contact as in claim 5 wherein the second direction is generally opposite to the first direction.

7. An electrical contact as in claim 3 wherein the second direction is orthogonal to the connection direction.

8. An electrical contact as in claim 7 wherein the second direction is generally opposite to the first direction.

9. An electrical contact as in claim 3 wherein the second electrical contact section comprises two of the second beams.

10. An electrical contact as in claim 9 wherein the two second contact beams are located on opposite sides of the first beam.

11. An electrical contact as in claim 3 wherein the second electrical contact section comprises a pair of two of the second beams for each first beam, and wherein each of the second beams are located at directly opposite sides of their respective first beam.

12. *An electrical connector assembly comprising:*

*a first electrical connector comprising a first housing and a first electrical contact, wherein the first housing comprises at least two first heat dissipation holes extending from an exterior side of the first housing to an interior of the first housing, where the at least two first heat dissipation holes are located on opposite sides of the first housing;*

*a second electrical connector comprising a second housing and a second electrical contact, wherein the second housing comprises at least two second heat dissipation holes extending from an exterior side of the second housing to an interior of the second housing, where the at least two second heat dissipation holes are located on opposite sides of the second housing;*

*wherein the first housing comprises a receiving area adapted to receive at least a portion of the second housing, wherein the first heat dissipation holes extend into the receiving area of the first housing, wherein a first pair of the first and second heat dissipation holes are located on the housings to at least partially vertically align adjacent each other when the second electrical connector is inserted into the receiving area of the first housing, wherein a second pair of the first and second heat dissipation holes are located on the housings to at least partially vertically align adjacent each other when the second electrical connector is inserted into the receiving area of the first housing, where the first pair of heat dissipation holes is aligned substantially unobstructed relative to the second pair of heat dissipation holes for air to flow from the receiving area of the first housing out of the electrical connector assembly.*

## 12

13. *An electrical connector assembly as in claim 12 wherein the first housing comprises two of the first heat dissipation holes located at the two opposite sides of the first housing.*

14. *An electrical connector assembly as in claim 13 wherein the second housing comprises two of the second heat dissipation holes located at the two opposite sides of the second housing.*

15. *An electrical connector assembly as in claim 12 wherein the opposite sides of the first housing comprise a top side and a bottom side of the first housing.*

16. *An electrical connector assembly comprising:*

*a first electrical connector comprising a first housing and a first electrical contact, wherein the first housing comprises a first heat dissipation hole extending from an exterior side of the first housing to an interior of the first housing;*

*a second electrical connector comprising a second housing and a second electrical contact, wherein the second housing comprises a second heat dissipation hole extending from an exterior side of the second housing to an interior of the second housing;*

*wherein the first housing comprises a receiving area adapted to receive at least a portion of the second housing, wherein the first heat dissipation hole extends into the receiving area of the first housing, wherein the first and second heat dissipation holes are located on the housings to at least partially vertically align adjacent each other when the second electrical connector is inserted into the receiving area of the first housing where the first and second heat dissipation holes are aligned substantially unobstructed for air to flow from the receiving area of the first housing out of the electrical connector assembly,*

*wherein the first electrical contact comprising:*

*a main section;*

*at least one daughter board electrical contact section extending from the main section; and*

*at least one mating connector contact section extending from the main section, the mating connector contact section comprising at least two forward protecting beams, wherein a first one of the beams extends outward in a first direction as the first beam extends forward from the main section and has a contact surface facing the first direction and wherein a second one of the beams extends outward in a second opposite direction as the second beam extends forward from the main section and has a contact surface facing the second direction, wherein the first beam is larger than the second beam.*

17. *An electrical connector comprising:*

*an electrical contact, wherein the electrical contact comprises:*

*a main section;*

*at least one daughter board electrical contact section extending from the main section; and*

*at least one mating connector contact section extending from the main section, the mating connector contact section comprising at least two forward projecting beams, wherein a first one of the beams extends outward in a first direction as the first beam extends forward from the main section and has a contact surface facing the first direction, and wherein a second one of the beams extends outward in a second opposite direction as the second beam extends forward from the main section and has a contact surface facing the second direction, wherein the first beam is larger than the second beam;*



13

a housing having the electrical contact mounted to the housing, wherein the housing comprises a receiving area adapted to receive a portion of a mating electrical connector, wherein the electrical contact extends into the receiving area, wherein the housing comprises heat dissipation holes extending from an exterior side of the housing through different walls of the housing and into the receiving area,

wherein the housing is sized and shaped, and the heat dissipation holes are located at predetermined locations on the housing such that at least some of the heat dissipation holes are aligned relative to each other on opposite sides of the housing, and where the heat dissipation holes are located at the predetermined locations on the housings to at least partially vertically align the heat dissipation holes with heat dissipation holes of a mating electrical connector when the mating electrical connector is connected to the electrical connector for the heat dissipation holes to be substantially unobstructed for air to flow from the receiving area of the first housing out of the electrical connector assembly through the aligned heat dissipation holes.

18. An electrical connector as in claim 17 wherein the different walls of the housing comprise a top side of the housing and an opposite bottom side of the housing.

19. A method comprising:

connecting a first electrical connector to a second electrical connector, wherein the first and second electrical

14

connectors each comprise a housing having an interior open space with mating portions of electrical contacts in the open spaces; and

when the first and second electrical connectors are being connected to each other, at least partially vertically aligning first heat dissipation holes on the housing of the first electrical connector with second heat dissipation holes of the housing of the second electrical connector as aligned pairs of holes,

wherein the heat dissipation holes extend through the housings between exterior sides of the housings and interior open spaces such that heated air can flow from the interior open spaces out of the housings through the aligned pairs of holes, where a first pair of the first and second heat dissipation holes and a second pair of the heat dissipation holes on opposite sides of the housings are aligned substantially unobstructed for the air to flow through the aligned pairs of heat dissipation holes when the electrical connectors are connected.

20. A method as in claim 19 wherein the housing of the first electrical connector comprises two of the first heat dissipation holes and the housing of the second electrical connector comprises two of the second heat dissipation holes, wherein the pairs of heat dissipation holes are located on opposite sides of the electrical connectors when the electrical connectors are connected to each other.

21. A method as in claim 19 wherein the opposite sides of the housings comprise opposite top and bottom sides of the housings.

\* \* \* \* \*



UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : RE44,556 E  
APPLICATION NO. : 12/317366  
DATED : October 22, 2013  
INVENTOR(S) : Steven E. Minich and Christopher J. Kolivoski

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims


In Claim 16:

Column 12, line 41, "protecting" should be deleted and --projecting-- should be inserted.

In Claim 19:

Column 14, line 11, "and interior" should be deleted and --and the interior-- should be inserted.

Signed and Sealed this  
Twenty-fourth Day of December, 2013



Margaret A. Focarino  
*Commissioner for Patents of the United States Patent and Trademark Office*