



US00RE44819E

(19) **United States**  
(12) **Reissued Patent**  
**Braun et al.**

(10) **Patent Number:** **US RE44,819 E**  
(45) **Date of Reissued Patent:** **Apr. 1, 2014**

(54) **TOOTHBRUSH**  
(75) Inventors: **Phillip M. Braun**, Exeter, RI (US);  
**William A. Bredall**, Pacifica, CA (US);  
**Karen Claire-Zimmet**, Waltham, MA  
(US); **Thomas Craig Masterman**,  
Brookline, MA (US); **Mark Edward**  
**McConnell**, Belmont, CA (US);  
**Michael F. Roberts**, Tucson, AZ (US);  
**Thomas Overthun**, San Francisco, CA  
(US)  
(73) Assignee: **Procter & Gamble Business Services**  
**Canada Company**, Cincinnati, OH (US)

601,405 A 3/1898 Shepherd  
819,444 A 5/1906 Monroe  
1,022,920 A 4/1912 Anderson  
1,063,523 A 6/1913 Farrar  
1,128,139 A 2/1915 Hoffman  
1,142,698 A 6/1915 Grove et al.  
1,172,109 A 2/1916 Cammack  
1,191,556 A 7/1916 Blake  
1,268,544 A 12/1916 Cates  
1,251,250 A 12/1917 Libby  
1,323,042 A 11/1919 Gardner  
1,526,267 A 9/1924 Dessau  
1,673,638 A 6/1928 Peterson  
1,693,229 A 11/1928 Felmar  
1,698,128 A 1/1929 Funk  
1,704,564 A 3/1929 Friedland  
1,753,290 A 4/1930 Graves

(Continued)

(21) Appl. No.: **10/820,562**

(22) Filed: **Apr. 8, 2004**

**Related U.S. Patent Documents**

Reissue of:

(64) Patent No.: **6,553,604**  
Issued: **Apr. 29, 2003**  
Appl. No.: **09/526,679**  
Filed: **Mar. 16, 2000**

(51) **Int. Cl.**  
**A46B 9/04** (2006.01)  
**A46B 7/06** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **15/167.1; 15/201**

(58) **Field of Classification Search**  
USPC ..... 15/167.1, 186, 201, 202  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

301,644 A 7/1884 Thompson  
429,839 A 6/1890 Beissbarth

**FOREIGN PATENT DOCUMENTS**

AU 44696/93 8/1993  
CA 454913 3/1949

(Continued)

**OTHER PUBLICATIONS**

“Plastics—Determination of flexural properties”, British Standard,  
BS EN ISO 178:2003, Apr. 9, 2003.

(Continued)



*Primary Examiner* — Randall Chin

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

A toothbrush includes a handle, a head extending from the handle, and a plurality of tooth cleaning elements, such as tufts of bristles, extending from the head. Each tooth cleaning element is supported for rotation about primarily only one axis. Each tooth cleaning element is rotatable independent of the other tooth cleaning element(s).

**41 Claims, 4 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

1,758,632 A	5/1930	Wagner	4,373,541 A	2/1983	Nishioka
1,764,130 A	6/1930	Vardeman	4,391,951 A	7/1983	Scheetz
1,796,893 A	3/1931	McVeigh	4,403,623 A	9/1983	Mark
1,797,946 A	3/1931	Eichel	4,409,701 A	10/1983	Perches
1,863,389 A	5/1931	Anderson	4,429,434 A	2/1984	Sung-shan
1,840,246 A	1/1932	Newman	4,472,853 A	9/1984	Rauch
1,908,510 A	5/1933	Dodson	4,476,280 A	10/1984	Poppe et al.
1,924,152 A	8/1933	Coney et al.	4,480,351 A	11/1984	Koffler
1,963,389 A	6/1934	Vardeman	4,517,701 A	5/1985	Stanford, Jr.
1,993,662 A	3/1935	Green	4,525,531 A	6/1985	Zukosky et al.
2,042,239 A	5/1936	Planding	4,534,081 A	8/1985	Spademan
2,088,839 A	8/1937	Coney et al.	4,545,087 A	10/1985	Nahum
2,117,174 A	5/1938	Jones	4,585,416 A	4/1986	DeNiro et al.
2,129,082 A	9/1938	Byrer	4,603,166 A	7/1986	Poppe et al.
2,139,245 A	12/1938	Ogden	4,616,064 A	10/1986	Zukosky et al.
2,154,846 A	4/1939	Heymann et al.	4,617,342 A	10/1986	Poppe et al.
2,155,473 A	4/1939	Coleman	4,617,694 A	10/1986	Bori
2,164,219 A	6/1939	McGerry	4,623,495 A	11/1986	Degoix et al.
2,172,624 A	9/1939	Robert	4,633,542 A	1/1987	Taravel
2,176,309 A	10/1939	Love et al.	4,654,922 A	4/1987	Chen
2,189,175 A	2/1940	Jackson	4,672,706 A	6/1987	Hill
2,206,726 A	7/1940	Lasater	4,691,405 A	9/1987	Reed
2,219,753 A	10/1940	Seguin	4,694,844 A	9/1987	Berl et al.
2,225,331 A	12/1940	Campbell	4,706,322 A	11/1987	Nicolas
2,238,603 A	4/1941	Runnels	4,751,761 A	6/1988	Breitschmid
2,244,699 A	6/1941	Hosey	4,776,054 A	10/1988	Rauch
2,246,867 A	6/1941	Thomas et al.	4,783,874 A	11/1988	Perches et al.
2,263,802 A	11/1941	Grusin	4,802,255 A	2/1989	Breuer et al.
2,266,195 A	12/1941	Hallock	4,833,194 A	5/1989	Kuan et al.
2,279,355 A	4/1942	Wilensky	4,845,795 A	7/1989	Crawford et al.
2,312,828 A	3/1943	Adamsson	4,852,202 A	8/1989	Ledwitz
2,326,632 A	8/1943	Friedman	4,882,803 A	11/1989	Rogers et al.
2,328,998 A	9/1943	Radford	4,892,698 A	1/1990	Weihrauch
2,364,205 A	12/1944	Fuller	4,894,880 A	1/1990	Aznavoorian
2,486,203 A	10/1949	Pieper	4,913,133 A	4/1990	Tichy
2,486,847 A	11/1949	Hokett	4,979,782 A	12/1990	Weihrauch
2,556,691 A	6/1951	Harshbarger	4,989,287 A	2/1991	Scherer
2,604,649 A	7/1952	Stephenson et al.	4,991,249 A	2/1991	Suroff
2,637,870 A	5/1953	Cohen	5,020,179 A	6/1991	Scherer
2,702,914 A	3/1955	Kittle et al.	5,021,475 A	6/1991	Isayev
2,832,088 A	4/1958	Peilet et al.	5,034,450 A	7/1991	Betz et al.
2,882,544 A	4/1959	Hadidian	5,040,260 A	8/1991	Michaels
2,935,755 A	5/1960	Leira	D325,821 S	5/1992	Schwartz
3,007,441 A	11/1961	Eyer	5,114,214 A	5/1992	Barman
3,016,554 A	1/1962	Peterson	5,120,225 A	6/1992	Amit
3,050,072 A	8/1962	Diener	5,137,039 A	8/1992	Klinkhammer
3,103,027 A	9/1963	Birch	5,142,724 A	9/1992	Park
3,110,918 A	11/1963	Tate	5,150,495 A	9/1992	Discko et al.
3,128,487 A	4/1964	Vallis	5,165,131 A	11/1992	Staar
3,129,449 A	4/1964	Cyzer	5,184,368 A	2/1993	Holland
3,159,859 A	12/1964	Rasmussen	5,186,627 A	2/1993	Amit et al.
3,177,509 A	4/1965	Cyzer	5,228,166 A	7/1993	Gomez
3,230,562 A	1/1966	Birch	5,269,038 A	12/1993	Bradley
3,258,805 A	7/1966	Rossmann	D345,054 S	3/1994	Spence, Jr.
3,295,156 A	1/1967	Brant	5,291,878 A	3/1994	Lombardo et al.
3,302,230 A	2/1967	Poppelman	5,313,909 A	5/1994	Tseng et al.
3,316,576 A	5/1967	Urbush	5,318,352 A	6/1994	Holland
3,327,339 A	6/1967	Lemelson	5,325,560 A	7/1994	Pavone et al.
3,359,588 A	12/1967	Kobler	5,334,646 A	8/1994	Chen
3,398,421 A	8/1968	Rashbaum	D350,851 S	9/1994	Spence, Jr.
3,403,070 A	9/1968	Lewis, Jr.	5,350,248 A	9/1994	Chen
3,411,979 A	11/1968	Lewis	5,357,644 A	10/1994	Therault
RE26,688 E	10/1969	Lemelson	5,392,483 A	2/1995	Heinzelman et al.
3,553,759 A	1/1971	Kramer et al.	5,398,366 A	3/1995	Bradley
3,613,143 A	10/1971	Muhler et al.	5,407,254 A	4/1995	Hegemann
4,033,008 A	7/1977	Warren et al.	5,421,726 A	6/1995	Okada
4,081,877 A	4/1978	Vitale	5,435,032 A	7/1995	McDougall
4,114,222 A	9/1978	Serediuk	5,458,400 A	10/1995	Meyer
4,128,910 A	12/1978	Nakata et al.	5,476,384 A	12/1995	Giuliani et al.
4,156,620 A	5/1979	Clemens	5,524,319 A *	6/1996	Avidor ..... 15/167.1
4,202,361 A	5/1980	Bills	5,528,786 A	6/1996	Porat et al.
4,263,691 A	4/1981	Fakarnseree	5,535,474 A	7/1996	Salazar
4,277,862 A	7/1981	Weideman	5,546,626 A	8/1996	Chung
4,288,883 A	9/1981	Dolinsky	5,590,434 A	1/1997	Imai
4,356,585 A	11/1982	Protell et al.	5,593,213 A	1/1997	Meessmann
			5,604,951 A	2/1997	Shipp
			5,628,082 A	5/1997	Moskovich
			5,651,157 A	7/1997	Hahn
			5,678,275 A	10/1997	Defner

(56)

References Cited

U.S. PATENT DOCUMENTS

D386,617 S 11/1997 Shyu  
 5,706,542 A 1/1998 Okada  
 5,723,543 A 3/1998 Modic  
 5,735,011 A 4/1998 Asher  
 5,778,474 A 7/1998 Shek  
 5,791,007 A 8/1998 Tsai  
 5,799,354 A 9/1998 Amir  
 5,802,656 A 9/1998 Dawson et al.  
 5,813,079 A 9/1998 Halm  
 5,815,872 A 10/1998 Meginniss, III et al.  
 5,823,633 A 10/1998 Weihrauch  
 D401,414 S 11/1998 Vrignaud  
 5,836,033 A 11/1998 Berge  
 5,839,148 A 11/1998 Volpenhein  
 5,842,249 A 12/1998 Sato  
 5,864,915 A 2/1999 Ra  
 5,896,614 A 4/1999 Flewitt  
 5,930,860 A 8/1999 Shipp  
 5,946,759 A 9/1999 Cann  
 5,970,564 A 10/1999 Inns et al.  
 5,974,619 A 11/1999 Weihrauch  
 5,987,681 A 11/1999 Hahn et al.  
 5,987,688 A 11/1999 Roberts et al.  
 5,991,959 A 11/1999 Raven et al.  
 6,006,395 A 12/1999 Tiramani et al.  
 6,018,840 A 2/2000 Guay et al.  
 6,035,476 A 3/2000 Underwood et al.  
 6,058,541 A 5/2000 Masterman et al.  
 6,067,684 A 5/2000 Kweon  
 6,088,870 A 7/2000 Hohlbein  
 6,112,361 A 9/2000 Brice  
 6,138,310 A 10/2000 Porper et al.  
 6,151,745 A 11/2000 Roberts et al.  
 6,161,245 A 12/2000 Weihrauch  
 6,178,582 B1 1/2001 Halm  
 6,202,241 B1 3/2001 Hassell et al.  
 D440,048 S 4/2001 Beals et al.  
 6,209,164 B1 4/2001 Sato  
 D443,985 S 6/2001 Beals et al.  
 6,253,404 B1 7/2001 Boland et al.  
 6,286,173 B1 9/2001 Briones  
 6,298,516 B1 10/2001 Beals et al.  
 6,308,367 B1 10/2001 Beals et al.  
 6,363,565 B1 4/2002 Paffrath  
 6,389,634 B1 5/2002 Devlin et al.  
 6,391,445 B1 5/2002 Weihrauch  
 6,405,401 B1 6/2002 Hellerud et al.  
 6,421,865 B1 7/2002 McDougall  
 6,421,867 B1 7/2002 Weihrauch  
 6,453,497 B1 9/2002 Chiang et al.  
 6,463,618 B1 10/2002 Zimmer  
 6,477,729 B1 11/2002 Ben-Ari  
 6,513,182 B1 2/2003 Calabrese et al.  
 6,553,604 B1 4/2003 Braun et al.  
 6,564,416 B1 5/2003 Claire et al.  
 6,571,417 B1 6/2003 Gavney, Jr. et al.  
 6,658,688 B2 12/2003 Gavney, Jr.  
 6,701,565 B2 3/2004 Hafemann  
 6,725,490 B2 4/2004 Blaustein et al.  
 6,776,597 B2 8/2004 Bühler  
 6,807,703 B2 10/2004 van Gelder et al.  
 6,820,300 B2 11/2004 Gavney, Jr.  
 6,826,797 B1 12/2004 Chenvainu et al.  
 6,859,969 B2 3/2005 Gavney, Jr. et al.  
 6,889,401 B2 5/2005 Fattori et al.  
 6,892,412 B2 5/2005 Gatzemeyer et al.  
 6,892,413 B2 5/2005 Blaustein et al.  
 6,918,154 B2 7/2005 Ben-Ari  
 6,931,688 B2 8/2005 Moskovich et al.  
 6,938,294 B2 9/2005 Fattori et al.  
 6,988,777 B2 1/2006 Pfenniger et al.  
 6,993,804 B1 2/2006 Braun et al.  
 7,008,225 B2 3/2006 Ito et al.  
 7,160,508 B2 1/2007 Lee  
 7,392,562 B2 7/2008 Boland et al.

7,494,566 B2 2/2009 Carroll  
 2001/0020314 A1 9/2001 Calabrese  
 2002/0004964 A1 1/2002 Luchino et al.  
 2002/0084550 A1 7/2002 Roberts et al.  
 2002/0192621 A1 12/2002 Ben-Air  
 2003/0033680 A1 2/2003 Davies et al.  
 2003/0033682 A1 2/2003 Davies et al.  
 2003/0041402 A1 3/2003 Stein et al.  
 2003/0066147 A1 4/2003 Roh  
 2003/0077107 A1 4/2003 Kuo  
 2003/0079304 A1 5/2003 Dworzan  
 2003/0084525 A1 5/2003 Blaustein  
 2003/0084528 A1 5/2003 Chan  
 2003/0140440 A1 7/2003 Gavney, Jr.  
 2003/0159224 A1 8/2003 Fischer et al.  
 2003/0196283 A1 10/2003 Eliav et al.  
 2003/0229959 A1 12/2003 Gavney, Jr. et al.  
 2004/0010869 A1 1/2004 Fattori et al.  
 2004/0016067 A1 1/2004 Kraemer  
 2004/0025275 A1 2/2004 Moskovich et al.  
 2004/0060132 A1 4/2004 Gatzemeyer et al.  
 2004/0060133 A1 4/2004 Eliav  
 2004/0060137 A1 4/2004 Eliav  
 2004/0068809 A1 4/2004 Weng  
 2004/0083566 A1 5/2004 Blaustein et al.  
 2004/0084063 A1 5/2004 Bago  
 2004/0123409 A1 7/2004 Dickie  
 2004/0128784 A1 7/2004 Ben-Ari  
 2004/0168271 A1 9/2004 McDougall  
 2004/0177458 A1 9/2004 Chan  
 2004/0177462 A1 9/2004 Duff, Jr. et al.  
 2004/0221409 A1 11/2004 Gavney, Jr.  
 2004/0231076 A1 11/2004 Gavney, Jr.  
 2004/0231082 A1 11/2004 Gavney, Jr.  
 2004/0237236 A1 12/2004 Gavney, Jr.  
 2004/0261203 A1 12/2004 Dworzan  
 2005/0015901 A1 1/2005 Gavney, Jr.  
 2005/0060822 A1 3/2005 Chenvainu et al.  
 2005/0235439 A1 10/2005 Braun et al.  
 2005/0273961 A1 12/2005 Moskovich et al.  
 2006/0272112 A9 12/2006 Braun et al.  
 2007/0251040 A1 11/2007 Braun et al.  
 2008/0060155 A1 3/2008 Braun et al.  
 2009/0172900 A1 7/2009 Brown, Jr. et al.

FOREIGN PATENT DOCUMENTS

CA 2483825 10/2004  
 CH 103 194 1/1924  
 CH 169312 5/1934  
 CH 609238 2/1979  
 DE 558 852 9/1932  
 DE 813 990 7/1949  
 DE 1 883 020 11/1963  
 DE 1 210 409 2/1966  
 DE 73 43 826 A 11/1974  
 DE 2 402 785 7/1975  
 DE 75 33 143 U 2/1976  
 DE 25 00 132 7/1976  
 DE 25 46 712 A 4/1977  
 DE 27 15 414 10/1978  
 DE 82 15 266.7 U1 9/1982  
 DE 35 29 953 3/1987  
 DE 37 44 630 7/1989  
 DE 003928919 A 3/1991  
 DE 42 07 968 9/1993  
 DE 94 000 231.2 5/1994  
 DE 44 12 301 10/1995  
 DE 19817704 4/1998  
 DE 299 19 053 1/2001  
 DE 100 28 530 12/2001  
 DK 0076598 11/1953  
 EP 0 189 816 8/1986  
 EP 0 322 562 7/1989  
 EP 0 360 766 3/1990  
 EP 0 704 179 4/1996  
 EP 0 857 026 B1 1/2000  
 EP 0 972 464 A1 1/2000  
 EP 0 783 850 3/2001

(56)

## References Cited

FOREIGN PATENT DOCUMENTS		
EP	1 080 664	3/2001
EP	0 870 440	12/2001
FR	459 442	11/1913
FR	936529	6/1948
FR	1075171	10/1954
FR	2 541 100	8/1984
FR	2 548 528	1/1985
FR	2559361	8/1985
FR	2 612 751	9/1988
FR	2 616 306	12/1988
FR	2 789 887	8/2000
FR	2789887	8/2000
GB	193 601 A	3/1923
GB	280 067 A	11/1927
GB	378 129 A	8/1932
GB	490 892 A	8/1938
GB	690 422 A	4/1953
GB	1 164 597 A	9/1969
GB	1 325 860 A	8/1973
GB	1 537 526	12/1978
GB	2 137 080	10/1984
GB	2 214 420	9/1989
GB	2 247 297	2/1992
GB	2 354 432	3/2001
GB	2 371 217	7/2002
JP	51-056165 U	5/1976
JP	52-125962 U	9/1977
JP	55-122633 U	9/1980
JP	58-091931 U	6/1983
JP	59-066433 U	5/1984
JP	61-090877	5/1986
JP	61-187531 U	11/1986
JP	63-066928	5/1988
JP	1-72128	5/1989
JP	2-119031	7/1990
JP	02-180203	7/1990
JP	3-312978	9/1991
JP	4-128627	11/1992
JP	05-076416	3/1993
JP	05069342	3/1993
JP	405076416 A	3/1993
JP	05096597	4/1993
JP	5-123222	5/1993
JP	6-327517	11/1994
JP	08-103326	4/1996
JP	08-103332	4/1996
JP	08-257043	10/1996
JP	08-299372	11/1996
JP	9-140456	3/1997
JP	9-187319	7/1997
JP	2000-157338	6/2000
JP	2000-300345	10/2000
JP	2000-300347	10/2000
JP	2000-308524	11/2000
JP	2001-190333	7/2001
JP	2001-507360	7/2001
JP	2002-010832	1/2002
JP	2002-248118	9/2002
JP	2003-61986	3/2003
JP	2003-93415	4/2003
JP	2003-164473	6/2003
RU	1752336 A1	5/1990
RU	2 045 216	10/1995
SU	1752336	8/1992
WO	WO 91/05088	4/1991
WO	WO 92/04589	3/1992

WO	WO 93/24034	12/1993
WO	WO 95/01113	1/1995
WO	WO 96/15696	5/1996
WO	WO 96/23431	8/1996
WO	WO 96/28994	9/1996
WO	WO 97/14330	4/1997
WO	WO 98/01055	1/1998
WO	WO 98/18364	5/1998
WO	WO 99/37181	7/1999
WO	WO 00/21406	4/2000
WO	00/34022	6/2000
WO	WO 00/30495	6/2000
WO	WO 00/47083	8/2000
WO	WO 00/64307	11/2000
WO	WO 00/76369	12/2000
WO	WO 01/06947	1/2001
WO	WO 01/06946	2/2001
WO	WO 01/21036	3/2001
WO	01/89344	11/2001
WO	WO 01/87101	11/2001
WO	WO 02/05679	1/2002
WO	WO 02/11583	2/2002
WO	WO 02/19942	3/2002
WO	02/38004	5/2002
WO	WO 02/45617	6/2002
WO	WO 03/015575	2/2003
WO	WO 03/086140	10/2003
WO	WO 2004/014181	2/2004

## OTHER PUBLICATIONS

Plastics Extrusion Technology Handbook, Chapter Seven, Coextrusion and Dual-Extrusion Technology, pp. 168-189.

Modern Plastics Encyclopedia, 67:168-175, 1990.

Pebax 3533 SA 00, "Base Polymer for Structural Hot Melt Adhesives".

Product Literature, Kraton Polymers, pp. 13-21.

"Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials [Metric]<sup>1</sup>", *American Society for Testing Materials*, Designation: D 790M-93 Metric, pp. 1-9, Undated.

"Standard Terminology Relating to Plastics<sup>1</sup>", *American Society for Testing Materials*, Designation: D 883-00, pp. 1-15, Undated.

Hendricks et al., "Rubber-Related Polymers I. Thermoplastic Elastomers", *Rubber Technology*, pp. 515-533, Undated.

"Santoprene Rubber Physical Properties Guide, Tensile Properties, Dynamic Mechanical Properties, Tension and Compression Set, Fatigue Resistance", *Advanced Elastomer Systems*, pp. 2-19, Undated.

Board Opinion from the Chinese Patent Office with regard to Application No. 01806615.1 dated Jul. 17, 2007 with translation.

Distinctive Plastics, "Multi-Component Molding", <http://www.distinctiveplastics.com/html/?id=2>, 2006 (2 pages).

U.S. Appl. No. 10/389,448, filed Mar. 14, 2003 and Office Actions dated Jun. 2, 2006, Feb. 22, 2007, Oct. 26, 2007, Apr. 4, 2008, Jul. 2, 2008, and Feb. 25, 2009 (74 pages).

U.S. Appl. No. 11/825,387, Jul. 6, 2007 and Office Actions dated Dec. 6, 2007, Aug. 29, 2008, Feb. 11, 2009, Feb. 19, 2010, and Jun. 22, 2010 (58 pages).


U.S. Appl. No. 12/186,639, filed Aug. 6, 2008 and Office Actions dated Dec. 23, 2009 and Sep. 2, 2010 (27 pages.).

U.S. Appl. No. 10/830,693, filed Apr. 23, 2004 and Office Actions dated Aug. 17, 2006, May 15, 2007, Oct. 24, 2007, Mar. 3, 2008, Jul. 2, 2008, and Feb. 26, 2009 (63 pages).

U.S. Appl. No. 11/799,733, filed May 2, 2007 and Office Actions dated Apr. 25, 2008 and Jun. 19, 2009 (53 pages).

\* cited by examiner

**FIG. 1**






FIG. 3






FIG. 2



**FIG. 4**




**FIG. 5**

# FIG. 6

## Mobile vs. Fixed Tufts

(data points = average of 4 exp., error bars on 95% confidence level)





## TOOTHBRUSH

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.**

*More than one reissue application has been filed for the reissue of U.S. Pat. No. 6,553,604.*

*This application (U.S. application Ser. No. 10/820,562) is a reissue application based on U.S. application Ser. No. 09/526,679, filed Mar. 16, 2000, which previously issued as U.S. Pat. No. 6,553,604. U.S. application Ser. No. 12/828,653 and U.S. application Ser. No. 12/828,667 (now abandoned) were filed on Jul. 1, 2010 as divisional applications of and claim priority to U.S. application Ser. No. 10/820,562, filed on Apr. 8, 2004. Thus, U.S. application Ser. No. 10/820,562, U.S. application Ser. No. 12/828,653, and U.S. application Ser. No. 12/828,667 (now abandoned) are all reissue applications of U.S. Pat. No. 6,553,604.*

## FIELD OF THE INVENTION

The invention relates generally to the field of oral care, and in particular to toothbrushes.

## BACKGROUND OF THE INVENTION

A Japanese patent document having an application number of 3-312978 discloses a toothbrush having a multiplicity of tufts of nylon bristles. In a first embodiment shown in FIGS. 1, 2 and 3, a plurality of cylindrical recessed sections in the head are set orthogonally to the longitudinal axial direction of a shank and are formed at equal intervals. Column-shaped rotary bodies 5 are respectively contained in the recessed sections. On the peripheral surfaces of the rotary bodies 5, along the axial direction, projected strip sections 5a are formed, and they are set in a state that they are positioned at the opening sections of the recessed sections. At the opening sections of the recessed sections, contact surfaces to be positioned on both the sides are formed. At both the ends of the upper surfaces of the projected strip sections 5a, nylon bristles 6 are arranged to be vertically erected.

As shown in FIG. 3, the arrangement described above allows bristles 6 to rotate during use of the brush. A problem with this brush is that two tufts of bristles are secured to each strip section 5a and thus must rotate in unison. As a result, an individual tuft of bristles cannot rotate independently of its "partner" tuft. The individual tuft may thus be prevented from achieving optimal penetration between two teeth during brushing because the partner tuft might contact the teeth in a different manner and interfere with rotation of the individual tuft.

FIGS. 4, 5 and 6 disclose a second embodiment in which each tuft of bristles is secured to the head by a ball and socket type arrangement. While this embodiment allows each tuft of bristles to swivel independent of the other tufts, it does have disadvantages. If a tuft of bristles is tilted out towards the side of the head and that tuft is positioned near the interface between the side and top surfaces of the teeth, chances are increased that the bristle tips will not even be in contact with the teeth during brushing. Further, random orientation in which the tufts can end up after brushing detracts from the attractiveness of the brush.

## SUMMARY OF THE INVENTION

The present invention is directed to overcoming one or more of the problems set forth above. Briefly summarized,

according to one aspect of the present invention, a toothbrush includes a handle, a head extending from the handle, and a plurality of tooth cleaning elements, such as tufts of bristles, extending from the head. Each tooth cleaning element is supported for rotation about primarily only one axis. Each tooth cleaning element is rotatable independent of the other tooth cleaning element(s).

By having each tooth cleaning element supported for rotation about only one axis, the problems mentioned above for the ball and socket tuft support are avoided. That is, the chances are increased that the tooth cleaning element will remain in contact with teeth during brushing and the brush will be more attractive in appearance.

Further, as each tooth cleaning element is rotatable independent of the other tooth cleaning element(s), the problem discussed above with the first Japanese embodiment is avoided. Each tooth cleaning element can achieve optimal interdental penetration without interference from rotation by another tooth cleaning element.

These and other aspects, objects, features and advantages of the present invention will be more clearly understood and appreciated from a review of the following detailed description of the preferred embodiments and appended claims, and by reference to the accompanying drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a toothbrush according to a first embodiment of the invention;

FIG. 2 is a partial sectional view of the head of the toothbrush of FIG. 1 and one of the tooth cleaning elements;

FIG. 3 is a sectional view taken along the lines 3-3 of FIG. 2;

FIG. 4 is a front view of an alternative tooth cleaning element; and

FIG. 5 is a side view of the tooth cleaning element of FIG. 4.

FIG. 6 is a graph showing interproximal residence time of mobile tufts and fixed tufts in the interdental gap(s).

## DETAILED DESCRIPTION OF THE INVENTION

Beginning with FIG. 1, a toothbrush 8 includes a handle 10 from which extends a head 12. Head 12 includes a first group of tooth cleaning elements 14, such as tufts of bristles, which are secured to the head in a conventional manner (e.g. by stapling or hot-tufting). Elements 14 are designed to clean the exposed surfaces of teeth.

A second group of tooth cleaning elements 16 are secured to head 12 such that each element can independently rotate about a single axis during use of the brush. Each elements 16 can be a tuft of bristles or, alternatively, a single unitary fin made of plastic or rubber. Elements 16 are designed to penetrate in between teeth to clean the interdental spaces.

The interproximal residence time of elements 16 is significantly increased as compared to elements 14 which are rigidly fixed to head 12. An experiment was conducted in which the interproximal residence time was determined for fixed tufts at both a 0 degree (like element 14) and 16 degree forward angle, and for rotating tufts such as element 16. The tufts had an average of 40 bristles each with each bristle having a 7-mil diameter. Residence times were measured on a Single Filament Tester (SFT) with a load of 4 g/tuft at velocities between 0.5 and 10 in/s.

The graph of FIG. 6 shows interproximal residence time of mobile tufts and fixed tufts in the interdental gap(s). The data are averages over 4 experiments. The error bars represent the

error of the mean at the 95% confidence level. This experimental data shows that rotating tufts experience 1.6 times more interproximal residence time compared to angled fixed bristle tufts, and 2.7 times more interproximal residence time compared to vertical fixed bristle tufts. More interproximal residence time translates into better cleaning between teeth .

With reference to FIGS. 2 and 3, the structure for enabling element 16 to rotate and its methods of manufacture will be described. Element 16 includes at its lower end a unitary bearing 18 which is cylindrical in shape and rounded at its ends. Bearing 18 can be formed by either melting some of the material from which element 16 is made, or by molding the bearing in a separate molding operation.

Such a molding operation would use a high flow material such as Exxon Escorene Polypropylene PP-1105, or FINA Polypropylene 3824. It is important to gate from both sides and to have very low pack pressure during the molding operation. An undercut on element 16 is preferable in order to secure bearing 18 to element 16. If bearing 18 is molded separately and then secured to element 16, an adhesive can be used in place of the undercut to secure element 16 and bearing 18 together.

An example of a specific molding operation would be to use a 90 Ton Toshiba Injection Molding Machine to mold Exxon Escorene Polypropylene PP-1105. The temperature profile is a 350 F. barrel temperature, a 350 F. rear temperature, a 405 F. front temperature and a 390 F. nozzle temperature. The mold temperature is preferably about 90 F., and a 1/16 inch nozzle should be used. Fill time is 0.25 seconds, screw forward time is 3.75 seconds, injection time is 4.00 seconds and cool time is 15 seconds. Peak hydraulic pressure is 250 psi.

Head 12 is actually made up of a top piece 22 and a bottom piece 24. Both of these pieces are created in separate molding steps with piece 22 being integrally molded with the brush handle. Element 16 is inserted through an aperture 25 in top piece 22 bearing end last to the position shown in the figures. Aperture 25 includes a bearing socket 20 which captures bearing 18. It is preferable to insert a viscous substance, such as some food-grade grease, into socket 20 to provide some resistance to rotation of element 16 to prevent the element from loosely flopping back and forth. Finally, piece 24 is fixed to piece 22 to secure bearing 18 in socket 20. Piece 24 can be secured to piece 22 by, for example, snap features (not shown) or heat welding. Alternatively, piece 24 can be injection molded into place.

An alternative manufacturing method to using two pieces 22, 24 for the head is to injection mold the entire head (and handle) about bearing 18. A higher melting temperature material would need to be used for element 16 and bearing 18 so that they are not softened/melted during injection molding of the head/handle. Element 16 can be exercised after completion of the brush by rotating the element back and forth to free it in the event some plastic from the head is interfering with rotation.

The arrangement described above allows element 16 to rotate back and forth about only one axis 26 which is preferably substantially perpendicular to a long axis of element 16. Preferably, element 16 can rotate about 30 degrees either side of vertical. The top of aperture 25 limits the amount of rotation that can be experienced by element 16. It should be noted that there is no spring force or other force which returns element 16 to a home position, so the element can end up at any one of an infinite number of positions along its 60 degree freedom of movement at the end of the brushing process.

Alternatively, bearing 18 could be made in a spherical shape. Use of such a spherical bearing would still only allow

element 16 to rotate about only one axis because, as shown in FIG. 2, head 12 fits up against opposite sides of element 16, thereby restricting rotation to occurring about one axis only.

Turning to FIGS. 4 and 5, an alternative tooth cleaning element will be described. Element 30 includes a tooth cleaning portion 32 which can be a tuft of bristles or a unitary plastic or rubber fin. A hinge 34 (e.g. a living hinge) made of a soft plastic or elastomer is injection molded onto cleaning portion 32. The material from which hinge 34 is made must be carefully selected, because if it is too soft, retention of element 16 will be poor, and if the material is too hard, the hinge will not be flexible enough. The hinge is preferably made of GLS Corp.'s DYNAFLEX thermoplastic rubber compound G2780 or G2711 and can be injection molded under the conditions outlined above. The living hinge allows cleaning portion 32 to rotate primarily only about an axis 36 which, as described above, is preferably substantially perpendicular to a long axis of portion 32. Resistance to rotation increases as portion 32 is moved away from a position vertical to the top surface of the brush head. A toothbrush head 38 with integral handle (not shown) is injection molded about a base portion of living hinge 34 to capture the living hinge in the head (see FIG. 4).

The invention has been described with reference to a preferred embodiment. However, it will be appreciated that variations and modifications can be effected by a person of ordinary skill in the art without departing from the scope of the invention.

What is claimed is:

1. [A toothbrush] *An apparatus*, comprising[;]:

a *toothbrush* handle;

a *toothbrush* head extending from the *toothbrush* handle; and

a plurality of tufts of bristles extending from the head, *the tufts of bristles sized such that multiple tufts of bristles are placed beside each other in a direction generally orthogonal to the handle*, each tuft of bristles being supported for rotation about only one axis, each tuft of bristles being rotatable independent of [the other tuft(s) of bristles] *one another*.

2. The [toothbrush] *apparatus* of claim 1, wherein each tuft has a range of rotation of about 60 degrees.

3. The [toothbrush] *apparatus* of claim 1, wherein each tuft can rotate about 30 degrees to either side of a vertical position in which the tuft is perpendicular to a top surface of the head.

4. The [toothbrush] *apparatus* of claim 1, further including at least one tooth cleaning element which cannot be rotated.

5. The [toothbrush] *apparatus* of claim 1, wherein each tuft includes at its non-brushing end a bearing which is substantially cylindrical in shape in its major portion, each bearing being secured in its own hollow space within the head, each bearing allowing rotation of its respective tuft.

6. The [toothbrush] *apparatus* of claim 5, wherein the head is made of at least two pieces which are joined together to secure the bearing within the head.

7. The [toothbrush] *apparatus* of claim 5, wherein a viscous substance is provided in each hollow space in the head to provide some resistance to rotation of the tufts.

8. The [toothbrush] *apparatus* of claim 1, wherein a portion of the head limits rotation of each tuft.

9. The [toothbrush] *apparatus* of claim 1, wherein the tufts are rotated by contact with a portion of an oral cavity.

10. The [toothbrush] *apparatus* of claim 1, wherein each tuft includes at its non-brushing end a living hinge, each living hinge being secured partially within the head, each living hinge allowing rotation of its respective tuft.

5

11. The [toothbrush] apparatus of claim 1, wherein the axis about which each tuft is rotatable is substantially perpendicular to a long axis of the [element] tuft.

12. The apparatus of claim 1, wherein two or more of the tufts of bristles are disposed in a row extending generally laterally across a long axis of the toothbrush handle.

13. An apparatus comprising:

a toothbrush head having a longitudinal axis; and  
a first group of tooth cleaning elements extending from the head and a second group of a plurality of tooth cleaning elements extending from the head,

the elements within each of the groups being of a common type and the type of elements in the first group being different from the type of elements in the second group, and

wherein each of the elements of the first group is nonrotatable, and

wherein each of the elements in the second group is supported for rotation about only one axis and independently rotatable with respect to any other rotatable tooth cleaning element on the toothbrush head, the elements of the second group sized such that multiple elements of the second group are placed beside each other in a direction generally orthogonal to the longitudinal axis of the toothbrush head

wherein the axis about which each element in the second group is rotatable is substantially perpendicular to the longitudinal axis of the toothbrush head.

14. The apparatus of claim 13 wherein all of the tooth cleaning elements of the toothbrush are in the first and second group.

15. The apparatus of claim 13 wherein the first group includes a plurality of tooth cleaning elements.

16. The apparatus of claim 13 wherein each of the elements in the second group is adjacent to at least one of the elements in the first group.

17. The apparatus of claim 13 wherein the interproximal residence time of elements in the second group is about 1.6 times or greater than the interproximal residence time of the elements in the first group.

18. The apparatus of claim 13 wherein the elements in the second group are longer than the elements in the first group.

19. The apparatus of claim 13 wherein the elements in the second group are made of polymer.

20. The apparatus of claim 13 wherein each of the elements in the second group is a fin or tuft of bristles.

21. The apparatus of claim 13 wherein each of the elements in the second group is a fin.

22. The apparatus of claim 21 wherein each of the elements in the first group is a tuft of bristles.

23. The apparatus of claim 13, further comprising a handle, and wherein the head extends from the handle.

24. The apparatus of claim 13 wherein the elements in the first group are free of spring bias tending to rotate the elements after deflection.

25. The apparatus of claim 13, wherein the type of elements in the first group is structurally different from the type of elements in the second group.

6

26. The apparatus of claim 13, wherein the type of elements in the first group is compositionally different from the type of elements in the second group.

27. The apparatus of claim 13, wherein the type of elements in the first group is structurally and compositionally different from the type of elements in the second group.

28. The apparatus of claim 13, wherein the elements in the first group are rigidly secured to the toothbrush head.

29. The apparatus of claim 13, wherein two or more of elements of the second group are disposed in a row extending generally laterally across a long axis of the toothbrush head.

30. An apparatus comprising:

a toothbrush head having a longitudinal axis; and  
a plurality of tufts of bristles extending from the head, each tuft of bristles being supported for rotation about only one axis, each tuft of bristles being rotatable independent of all other rotatable tuft(s) of bristles on the toothbrush head, the tufts of bristles sized such that multiple tufts of bristles are placed beside each other in a direction generally orthogonal to the longitudinal axis of the toothbrush head,

further including at least one tooth cleaning element which cannot be rotated.

31. The apparatus of claim 30, wherein each tuft has a range of rotation of about 60 degrees.

32. The apparatus of claim 30, wherein each tuft can rotate about 30 degrees to either side of a vertical position in which the tuft is perpendicular to a top surface of the head.

33. The apparatus of claim 30, wherein each tuft includes at its non-brushing end a bearing which is substantially cylindrical in shape in its major portion, each bearing being secured in its own hollow space within the head, each bearing allowing rotation of its respective tuft.

34. The apparatus of claim 33, wherein the head is made of at least two pieces which are joined together to secure the bearing within the head.

35. The apparatus of claim 33, wherein a viscous substance is provided in each hollow space in the head to provide some resistance to rotation of the tufts.

36. The apparatus of claim 30, wherein a portion of the head limits rotation of each tuft.

37. The apparatus of claim 30, wherein the tufts are rotated by contact with a portion of an oral cavity.

38. The apparatus of claim 30, wherein each tuft includes at its non-brushing end a living hinge, each living hinge being secured partially within the head, each living hinge allowing rotation of its respective tuft.

39. The apparatus of claim 30, wherein the axis about which each tuft is rotatable is substantially perpendicular to a long axis of the element.

40. The apparatus of claim 30, further comprising a handle.

41. The apparatus of claim 30, wherein two or more of the tufts of bristles are disposed in a row extending generally laterally across a long axis of the toothbrush head.

\* \* \* \* \*