

US00RE44915E

(19) **United States**  
(12) **Reissued Patent**  
**de Souza**

(10) **Patent Number:** **US RE44,915 E**  
(45) **Date of Reissued Patent:** **May 27, 2014**

(54) **MODULAR DRILL**  
(75) Inventor: **Filho Ruy Frota de Souza**, Latrobe, PA (US)  
(73) Assignee: **Kennametal Inc.**, Latrobe, PA (US)  
(21) Appl. No.: **12/640,882**  
(22) Filed: **Dec. 17, 2009**

5,154,550 A	10/1992	Isobe et al.	
5,228,812 A	7/1993	Noguchi et al.	
5,649,794 A	7/1997	Kress et al.	
5,685,671 A	11/1997	Packer et al.	
5,863,162 A	1/1999	Karlsson et al.	
5,904,455 A	5/1999	Krenzer et al.	
5,957,631 A *	9/1999	Hecht .....	408/144
5,971,673 A	10/1999	Berglund et al.	
5,980,166 A	11/1999	Ogura	
5,988,953 A	11/1999	Berglund et al.	
6,012,881 A	1/2000	Scheer	
6,059,492 A *	5/2000	Hecht .....	408/144
6,071,045 A	6/2000	Janness	
6,109,841 A	8/2000	Johne	
6,276,879 B1 *	8/2001	Hecht .....	409/234

**Related U.S. Patent Documents**

Reissue of:  
(64) Patent No.: **7,309,196**  
Issued: **Dec. 18, 2007**  
Appl. No.: **10/958,227**  
Filed: **Oct. 5, 2004**

(51) **Int. Cl.**  
**B23B 51/02** (2006.01)  
**B23B 51/12** (2006.01)  
(52) **U.S. Cl.**  
USPC ..... **408/227**; 408/231  
(58) **Field of Classification Search**  
USPC ..... 408/227, 144, 231, 233, 226, 713  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

932,071 A	8/1909	Urbscheit
1,461,548 A	7/1923	West
2,158,120 A	5/1939	Hirschberg
2,294,969 A	9/1942	Engvall et al.
3,153,356 A	10/1964	Dearborn
3,293,727 A	12/1966	Simms
3,359,837 A	12/1967	Andreasson
4,293,253 A	10/1981	Ott
4,561,812 A	12/1985	Linden
5,024,563 A	6/1991	Randall
5,114,286 A	5/1992	Calkins
5,154,549 A	10/1992	Isobe et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE	94 340	9/1896
DE	524 677	4/1931


(Continued)

*Primary Examiner* — Will Fridie, Jr.  
(74) *Attorney, Agent, or Firm* — Larry R. Meenan, Esq.

(57) **ABSTRACT**

A drill having a replaceable cutting head, modified to eliminate forces which would distort the pocket of the drill shank and otherwise concentrate stresses which would cause failure of the drill. The cutting head has a frustoconical depending connecting member received in a receptacle formed in the shank. In different embodiments, contact between the pocket formed in the shank and the cutting head connecting member is limited. In one embodiment, angle of drive surfaces is modified from prior art practice. In another embodiment, transition of at curved joints between vertical and horizontal surfaces is made more gradual. The drill preferably has flutes formed collectively by the shank and cutting head when assembled.

**16 Claims, 7 Drawing Sheets**



# US RE44,915 E

Page 2

(56)

## References Cited

## FOREIGN PATENT DOCUMENTS

### U.S. PATENT DOCUMENTS

6,481,938	B2	11/2002	Widin	
6,485,235	B1 *	11/2002	Mast et al. ....	408/1 R
6,506,003	B1 *	1/2003	Erickson .....	408/226
6,514,019	B1	2/2003	Schulz	
6,551,035	B1 *	4/2003	Bruhn et al. ....	408/144
6,582,164	B1 *	6/2003	McCormick .....	408/226
6,899,495	B2 *	5/2005	Hansson et al. ....	408/144
2002/0159851	A1	10/2002	Krenzer	
2003/0039523	A1	2/2003	Kremmer	
2004/0208716	A1	10/2004	Krenzer	

DE	2 246 965	4/1974
DE	199 45 097 A1	3/2001
DE	100 54 850 A1	5/2002
EP	0 118 806 A1	9/1984
EP	0 441 302 A2	8/1991
EP	0 441 302 B1	8/1991
EP	0 460 237 B1	12/1991
FR	907 980	5/1944
GB	1 395 855	5/1975
GB	2 010 708 A	7/1979

\* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4A






Fig. 4B







**Fig. 5**




**Fig. 7**



**Fig. 6**






**Fig. 8**



Fig. 9



# 1

## MODULAR DRILL

**Matter enclosed in heavy brackets [ ] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.**

### FIELD OF THE INVENTION

The present invention relates to cutting tools, and more particularly to modular drills having replaceable cutting tips.

### DESCRIPTION OF THE RELATED ART

Drills having replaceable cutting tips are known. Illustratively, such tools are shown in U.S. Pat. Nos. 5,957,631 and 6,059,492, both issued to Gil Hecht on Sep. 28, 1999, and May 9, 2000, respectively. The subject drills have replaceable cutting heads which are mounted on shanks. The cutting heads and shanks display continuous and complementing configuration as fluted drills. To this end, each shank has structure for retaining and rotating an associated cutting head. The associated cutting head has complementing structure for being retained and rotated by the shank. While these devices will operate under some circumstances, closer analysis reveals that their useful lives are potentially unduly limited. More specifically, the retaining and drive structure of the shank is subject to deformation and failure during its service life due to concentration of stresses imposed during ordinary service.

### SUMMARY OF THE INVENTION

The present invention provides modifications to drills having replaceable cutting tips, of the type shown in the above referenced patents to Hecht. The modifications of the present invention alter stresses imposed on the shanks such that the shanks either do not undergo deformation and outright failure while in service or alternatively, increase the service life achievable before deformation renders the tool unusable. These modifications generally connote prevention of direct contact of a replaceable cutting head with the shank at certain specified locations. Also, orientations of certain abutting surfaces are modified so that stresses are imposed differently from the original design of Hecht.

One specific example of modifications is that of providing a gap between a frustoconical dovetail formed in the cutting head and a cooperating recess formed in the shank, at the forward and rearward areas of mutual contact. The area of contact is limited to that portion between the forward and rearward areas of contact. A second modification is that of altering the angle of drive or torque transmission surfaces from purely radial to inclined relative to a purely radial direction. This has the effect of redistributing forces which would otherwise act on the walls of a pocket formed in the shank. The pocket, which receives the connection structure of the cutting head, then better resists distorting forces. A third modification is that of lengthening at the walls of that portion of the body forming a pocket which receives the cutting head and eliminating sharp corners in this region of the body. In still another modification, the floor of the pocket is modified in the manner of the third modification.

These modifications redistribute distorting forces away from portions of the shank which are more susceptible to distortion to portions of the shank better able to withstand

# 2

these forces. The ultimate effect is to increase the useful service life of the shank due to reduced distortion of the pocket.

### BRIEF DESCRIPTION OF THE DRAWINGS

Further features of the present invention, as well as the advantages derived therefrom, will become clear from the following detailed description made with reference to the drawings in which:

FIG. 1 is a partial, exploded perspective view of one embodiment of the modular drill of the present invention.

FIG. 2 is an end elevational detail view of the lower end of the upper component of FIG. 1, but showing an alternative embodiment thereof.

FIG. 3 is a cross sectional view of a further embodiment of the invention. The cross section corresponds to that which could be taken through the components of FIG. 1 if the components of FIG. 1 were assembled in axial abutment.

FIG. 4A is a cross sectional view of a still further embodiment of the invention, corresponding to FIG. 3 but with structure modified therefrom.

FIG. 4B is a cross sectional view of still another embodiment of the invention, corresponding to FIG. 4A, but with structure modified therefrom.

FIG. 5 is a top plan view of an alternative embodiment of the lower component of FIG. 1.

FIG. 6 is a partial, exploded view of another embodiment of the invention.

FIG. 7 is a perspective detail view of a further embodiment of the upper component of FIG. 1.

FIG. 8 is a partial, side elevational view of a still further embodiment of the invention.

FIG. 9 is an enlarged perspective detail view of the embodiment of FIG. 8.

### DESCRIPTION OF THE PREFERRED EMBODIMENTS

The documents, patents and patent applications referred to herein, including those pertaining to the prior art, are hereby incorporated by reference in their entirety. FIG. 1 of the drawings shows a first embodiment of a cutting tool assembly 10 for conducting rotary cutting operations on a work piece (not shown), comprising a tool shank 12 and a replaceable cutting head 14 which is installed on and engages tool shank 12. Cutting tool assembly 10 is a modular drill which in the preferred embodiments is of the so-called twist drill type, having helical flutes disposed along the sides of the drill. In the embodiment of FIG. 1, two flutes are provided in diametric opposition to one another, only one flute being visible. The visible flute has a lateral recess forming part of a flute, or cutting head flute portion 16 formed in cutting head 14. A corresponding or complementing lateral recess or shank flute portion 18 is formed in shank 12. The depiction of FIG. 1 shows cutting head 14 in a position for initially being installed on shank 12. In this initial position, cutting head 14 is rotated about ninety degrees with respect to rotational axis 20 of cutting tool 10, which rotational axis 20 is common to both shank 12 and also cutting head 14. Installation of cutting head 14 requires that cutting head 14 be lowered into abutment or near abutment with shank 12 and rotated in a direction opposite that of rotation during cutting operations. This installation procedure will both interlock cutting head 14 with shank 12 at certain respective mating peripheral surfaces in a manner precluding disengagement in the axial direction, taken with respect to axis 20, and will also assure abutment of



driving surfaces **22, 24** of shank **12** with corresponding driven surfaces **26, 28** of cutting head **14**. Driving surfaces **22, 24** of shank **12** are oriented to abut and bear against driven surfaces **26, 28** of cutting head **14** and thereby rotate cutting head **14** in tandem with shank **12** when shank **12** is rotated by its associated cutting tool such as a hand drill, drill press, machine tool, or the like (none shown).

Once cutting head **14** is installed on shank **12**, the flute collectively formed by cutting head flute portion **16** and shank flute portion **18** will align to form a flute in generally continuous and undistorted fashion. A similar flute is of course formed on the other side of cutting tool **10**. Although two flutes are preferred, any number of flutes including only one is possible.

In the depiction of FIG. 1, cutting head flute portion **16** emerges at a leading end **30** of cutting tool **10**. Leading end **30** is defined for semantic purposes, and is that end which engages a work piece (not shown) when cutting. During cutting operations, cutting tool **10** is mounted in the rotary cutting tool, rotated, and advanced progressively into the work piece as cutting progresses. That end of cutting tool located oppositely leading end **30** is termed the trailing end **32**. The terms "leading end **30**" and "trailing end **32**" are semantic devices which apply equally to shank **12** and cutting head **14** as they connote directional orientation with respect to longitudinal and rotational axis **20** rather than specific structure. Leading end **30** is that which penetrates a work piece (not shown), and trailing end **32** is that end opposed to leading end **30**.

That portion of shank **12** which couples to and rotates cutting head **14** is referred to as pocket **34**. The principal elements of pocket **34** include two generally symmetrical and similar castellated wall sections **36, 38**. Wall section **36** will be described, it being understood that wall **38** is a generally symmetrical counterpart thereof. Wall section **36** is essentially a continuation of the body of shank **12** which projects upwardly in the depiction of FIG. 1 past a central floor portion **40** of shank **12**, along the outer periphery of shank **12**. Wall section **36** has a smooth outer surface **42** which conforms to and is generally coextensive with the generally cylindrical outer surface of cutting tool **10**. At the interior of wall section **36**, the term "interior" referring to those surfaces facing axis **20**, wall section **36** has an internally facing, generally cylindrical face **44** and a frustoconical face **46**. Wall section **36** also has an upwardly facing upper face **48**, an upwardly facing lower face **50**, and a lateral face **52**. Lateral face **52** is located on a side opposite that of driving surface **22**.

Cutting head **14** has cutting edges (only cutting edge **54** is visible in FIG. 1), a peripheral generally cylindrical outer surface **56**, and a leading conical surface **58** which conical surface **58** is of course interrupted or incomplete due to presence of the flutes. Cutting edge **54** and leading conical surface **58** collectively form a cutting portion which performs cutting operations to the work piece.

Any or all of central floor portion **40**, faces **48** and **50**, and faces formed in wall portion **38** corresponding to faces **48** and **50** serve as abutment surfaces which abut cutting head **14** when cutting head **14** is installed on shank **12**.

Cutting head **14** has a shank connection portion opposite the cutting portion, or alternatively stated, facing the trailing end of cutting head **14**, in the form of an interlocking member arranged to retain cutting head **14** within pocket **34** of shank **12**. In the embodiment of FIG. 1, this interlocking member comprises a dovetail member **60** which is located centrally along rotational axis **20**. Dovetail member **60** is so-called due to its characteristic frustoconical lateral surface **62** which surface **62** is arranged at an obtuse angle to rotational axis **20**.

Dovetail member **60** provides an interlocking member corresponding to and engaging pocket **34**, which pocket **34** serves as an interlocking member of shank **12**. Surrounding dovetail member **60** is a peripheral base surface facing pocket **34**, comprising cutting head faces **64, 66, 68**, which face downwardly in the depiction of FIG. 1. It should be understood at this point that cutting head **14** is generally bilaterally symmetrical, so that cutting head face **64** is generally a mirror image of cutting head face **68**. Similarly, there exists a cutting head face not visible in FIG. 1 and not identified by reference numeral, which is diametrically opposed to and generally rotationally symmetrical about the central axis. In those embodiments wherein there may be three flutes, for example, there will accordingly be three rather than two similar cutting head faces corresponding to cutting heads **64, 66** disposed about the periphery of the cutting head.

Faces **64, 66** may be stepped, or located at different levels or points along axis **20**, in the same manner as and to correspond to the axial spacing apart of faces **48** and **50** of shank **12**. Any or all of faces **64, 66** serve as abutment surfaces for abutting shank **12**. Abutment of faces **64, 66** with their corresponding surfaces **48, 50** of shank **12** seats cutting head **14** on shank **12** responsive to compressive axial loading. When rotated into the interlocked position with respect to pocket **34**, dovetail member **60** will engage interior frustoconical face **46** of pocket **34**, thereby preventing disengagement in the axial direction away from shank **12**.

It is an important feature of the invention that contact between frustoconical face **46** and frustoconical lateral surface **62** be limited such that contact not occur over the entire extent of face **46** or lateral surface **62**. Rather, frustoconical face **46** and frustoconical lateral surface **62** are dimensioned and configured to abut mutually along part of the extent of surface **62** and to avoid making contact along the balance of lateral surface **62**. This characteristic enables pocket **34** to experience minimized forces imposed thereon during cutting operations by cutting head **14**, which forces would otherwise tend to spread or distort pocket **34**. Alternatively stated, although tangential forces remain unchanged, forces imposing a radially outward component are minimized at critical areas. Pocket **34** is thus less subject to distorting forces which would otherwise cause pocket **34** to spread over time of use, thereby shortening the useful life of shank **12**. Representative areas **70, 72** of non-contact between face **46** and surface **62** are shown stippled in FIG. 1.

Non-contact of face **46** and surface **62** may be accomplished in several ways. Turning now to FIG. 2, dovetail member **60** is seen in bottom plan. The periphery of dovetail member **60** includes reliefs **74, 76** to allow for chip flow after installation, arcuate sections **78, 80**, and chamfers **82, 84, 86, 88**. Chamfers **82, 84, 86, 88** reduce the overall diameter of trailing surface **90** of dovetail member **60**. The resulting discrepancy between the full diameter and that at any of chamfer **82, 84, 86, 88** is indicated by arrowheads as gaps **92, 94, 96, 98** which exist between respective chamfers **82, 84, 86, 88** and extensions (shown in broken lines) of the arcuate configuration of the periphery of surface **90**. In the embodiment of FIG. 2, then, contact between dovetail member **60** and face **46** of pocket **34** is made along arcuate sections **78** and **80**, but is avoided at chamfers **82, 84, 86, 88**, where the diameter of dovetail member **60** is reduced. The pocket of the shank (neither shown) which corresponds to dovetail member **60** thus contacts only first and second arcuate portions **78, 80** of dovetail member **60**, and avoids contacting chamfered portions **82, 84, 86, 88**.

Referring now to FIG. 3, which is an end view of a dovetail member **100** of a cutting head (not shown in its entirety)



installed in a pocket (not shown in its entirety) of a shank, a similar effect is obtained by chamfering walls **102, 104** of the pocket. The cutting head associated with dovetail member **100** may be essentially similar to cutting head **14** of FIG. **1**. The shank of FIG. **3**, apart from chamfering discussed herein, is essentially similar to shank **12** of FIG. **1**, similarity extending to the pocket. In the embodiment of FIG. **3**, chamfered portions **106, 108, 110, 112** formed in internally facing surfaces of pocket walls **102, 104** create gaps **114, 116, 118, 120** which provide functions similar to those of gaps **92, 94, 96, 98** of the embodiment of FIG. **2**. Gaps **114, 116, 118, 120** separate the arcuate sections (not specifically called out by reference numeral) of pocket walls **102, 104** from dovetail member **100** at the ends of pocket walls **102, 104**. Thus the internally facing surfaces of pocket walls **102, 104** contact dovetail member **100** only at their respective arcuate sections and avoid making contact at chamfered portions **106, 108, 110, 112**. The difference between the embodiments of FIGS. **2** and **3** is that in the embodiment of FIG. **2**, dovetail member **90** receives chamfering, whereas in the embodiment of FIG. **3**, walls **102, 104** of the pocket of the shank receive chamfering.

The dovetail member is limited to an extent less than the full extent of the internally facing surfaces of the pocket when the cutting head is installed in the pocket. More particularly, it is presently preferred that the zone of contact extend along the interior of each of walls **124A** and **126A** within a range of about fifteen to about seventy-five degrees.

FIG. **4A** shows an embodiment of the invention utilizing a third way of limiting contact between a dovetail member **122A** of a cutting head (not shown in its entirety) and the pocket of a shank (not shown in its entirety). In FIG. **4A**, walls **124A, 126A** of the pocket may be identical to their counterparts in FIG. **1**. In the embodiment of FIG. **4A**, dovetail member **122A** is non-circular in cross section, such as oblong. Radius  $R_1$  defines that part of the outer contour of dovetail member **122A** which contacts wall **124A**, it being understood that a similar radius defines the opposing end of dovetail member **122A**. Radius  $R_2$  defines the inner contours of wall **126A** (a similar radius defines the inner contour of wall **124A**). In the embodiment of FIG. **4A**, the radius of curvature of the interior wall of the pocket is greater than the radius of curvature of the exterior surface of dovetail member **122A**. These radii and related dimensions and configuration are selected and arranged such that contact of dovetail member **122A** with the inside surfaces of walls **124A, 126A** occurs along only a portion of the inside surfaces of walls **124A, 126A**. End zones **128A, 130A, 132A, 134A** of walls **124A, 126A** are not contacted by dovetail member **122A**. This leaves gaps such as gap **136A** at zone **130A**, corresponding gaps (not identified by reference numerals) existing at the other end zones **128A, 132A, 134A**.

FIG. **4B** shows an alternative to the embodiment of FIG. **4A**. In the embodiment of FIG. **4B**, the radius of curvature of the interior walls of the pocket exceeds the radius of curvature of the exterior surface of the contacting portion of the dovetail member, although this is achieved in a manner different from that of the embodiment of FIG. **4A**. In FIG. **4B**, radius  $R_1$  of dovetail member **122B** originates at the rotational axis of the tool holder. As employed here, the interior surface is that surface of pocket wall **124B** or **126B** which contacts the dovetail member **122B**.

The aforementioned embodiments all relate to ways of limiting contact of a dovetail member with pocket walls. The effect of limiting contact in this manner is that the uncontacted portion of the walls of the pockets of the embodiments of FIGS. **1, 2, 3, 4A, and 4B** serve to allow tangential deflec-

tion of the pocket walls mitigating radial deflection which would create additional stress on the pocket walls. In another type of modification, and referring now to FIG. **5**, structure is introduced to accommodate forces acting on a pocket of a shank **138**. The pocket of shank **138** includes two walls **140, 142** bearing respective driving surfaces **144, 146**. In the view of FIG. **5**, driving surfaces **144, 146** are inclined relative to axis of rotation **148**, and thus are visible in this end view. Orientation of surfaces **144, 146** is such that if hypothetically extended, as shown by straight projection lines **150, 152**, these projection lines **150, 152** avoid overlying axis of rotation **148**. Surfaces **144, 146** are oriented with respect to the direction of rotation of shank **138**, which as indicated by arrows in FIG. **5** is counterclockwise. It will be seen that the innermost portion of surface **144**, that being the closer to axis of rotation **148**, is the leading side, whereas the outermost portion of surface **144** is the trailing side. If the direction of rotation were reversed (although this embodiment is not shown), then projection line **150** associated with surface **144** would extend not from the upper left to the lower right, but rather from the lower left to the upper right. The same relationships hold true but in mirror image for surface **146**. By contrast, in the prior art devices, driving surfaces corresponding to surfaces **144** and **146** are generally arranged radially from the axis of rotation. The modification of the present invention redistributes forces which would promote greater or more quickly occurring opening or spreading of the pocket in the prior art designs.

FIG. **6** shows a modification to the embodiment of FIG. **1**. In FIG. **1**, dovetail member **60** has a relief **154** which modifies the otherwise frustoconical configuration, and an extension **156**. This configuration is modified in the embodiment of FIG. **6** such that an extension **158** is formed in dovetail member **160** below frustoconical lateral surface **162** of a cutting head **164**. As in the embodiment of FIG. **1**, lateral surface **162** is oriented at an obtuse angle to axis of rotation **168**. Extension **158** has an outer partially cylindrical surface **166** which is in addition to surface **162**, and a recessed incuse partial surface **170**. To accommodate this additional structure, pocket **172** of shank **174** has surfaces (only surface **176** is visible in FIG. **6**) corresponding to surface **166** of extension **158** that do not make contact. Extension **158** also has a beveled or a radiused surface including partial beveled surface **178** and incuse partial beveled or radiused surface **180**. Pocket **172** has corresponding surfaces (only radiused surface **182** is visible) to enable cutting head **164** to be received in pocket **172**. In other respects, both cutting head **164** and shank **174** are similar to their counterparts in other embodiments.

It would be possible to eliminate cylindrical surfaces **166, 170** from extension **158**. As seen in FIG. **7**, this is the case in cutting head **184**, which has a dovetail member **186** bearing an upwardly facing frustoconical surface **188** for interlocking to a pocket of a shank (not shown), and a downwardly facing frustoconical surface **190**. An incuse recess **192** is formed in dovetail member **186**. The shank which is to be used with cutting head **184** would of course have configured therein surfaces to accommodate surfaces **188, 190, 192** of cutting head **184** to assure secure retention of cutting head **184** by surface **188** and the corresponding surface in the pocket. In other respects, both cutting head **184** and its associated shank are functionally and structurally similar to their counterparts in other embodiments of the invention. It will be appreciated that surface **190** does not contact the pocket walls.

The effect of the modifications of the embodiments of FIGS. **6** and **7** is to increase the overall length of frustoconical lateral surface **62**, which in the embodiment of FIG. **1** is not extended. This increased length, regardless of whether the



added length extends straight down (surface 166 of FIG. 6) or is tapered (surface 190 of FIG. 7) allows for a smooth transition between either of the surfaces corresponding to frustoconical surfaces 162 and 188 (FIGS. 6 and 7) of the pocket in relation to the pocket floor thereby minimizing stress concentration.

Turning now to FIG. 8, a further embodiment is shown wherein a cutting head 194 is installed to a shank 196. Cutting head 194 has a dovetail member 198 bearing an end surface 200. Pocket 202 of shank 196 is dimensioned and configured to contact base surface 204 of cutting head 194 for resisting compressive axial forces. Contact with end surface 200 of cutting head 194 is avoided. A shelf 208 and a relief trough 206 are formed in the floor or upwardly facing central surface of pocket 202. Trough 206 projects into shank 196, extending towards the trailing end of the tool assembly comprising cutting head 194 and shank 196. Trough 206 extends across and fully spans the floor from one flute 222 to opposed flute 224. A better understanding of the geometry of shank 196 will be obtained by also referring to FIG. 9. The floor of pocket 202, which floor collectively encompasses trough 206, shelf 208, and shelf 216, separates and spaces apart one pocket wall 218 from opposed second pocket wall 220. Referring especially to FIG. 9, shelves 208, 216 each extend laterally across the floor at respective upper edges 226, 228 of relief trough 206. Each shelf 208 or 216 is associated with one pocket wall 218 or 220. Relief trough 206 is angularly oriented relative to rotational axis 230 such that each shelf 208 or 216 intersects only flute 222 or 224, being separated from the other flute 224 or 222 by trough 206. By way of further explanation, it will be seen that shelf 216 terminates at the right side, as depicted in FIG. 9, at flute 224, whereas at the left side in FIG. 9, shelf 216 is spaced apart from flute 222 by a surface 221 which appears as an upward extension of trough 206.

A consequence of this geometry is that trough 206 has at one end a curved end edge 210 which meets the side profile 214 of dovetail member 198 (see FIG. 8) at a tangent at a portion of dovetail member 198. Curved edge 210 has a significantly greater radius of curvature than does end edge 212 (see FIG. 8) located oppositely from end surface 210. The greater radius of curvature provides a transition in wall thickness which is gentler than the relatively small curvature seen at edge 212. Stress concentrations are thereby minimized at the corners of the walls of pocket 202 where dovetail member 198 terminates near the floor of the pocket at relief trough 206.

It will be appreciated that while the dovetail portion of the connector of the cutting head is described in terms of being frustoconical, it would be possible to utilize any configuration wherein there is an upwardly facing surface which can engage one or more corresponding surfaces formed in the retaining structure of the shank. It is preferred to form the dovetail of the connector as frustoconical merely because rotary machining and other inexpensive methods may be employed to form the dovetail.

The novel features presented herein may be present in combinations within a single tool made according to the present invention, where such embodiments are geometrically compatible, for example surface 221 also reduces the contact area between the dovetail and the pocket.

It will further be appreciated that relative locations of connecting and drive structure of the cutting head and of the shank may be reversed if desired, with appropriate accommodation being made to account for differences in the directions in which forces are imposed.

While the invention has been specifically described in connection with certain specific embodiments thereof, it is to be

understood that this is by way of illustration and not of limitation, and the scope of the appended claims should be construed as broadly as the prior art will permit.

What is claimed is:

1. A cutting tool assembly for conducting rotary cutting operations on a work piece, *said cutting tool assembly* comprising a tool shank and a replaceable cutting head which is installed on and engages the tool shank, the tool shank and the cutting head having a common rotational axis and mating peripheral surfaces when assembled together, the cutting tool assembly having a leading end which engages the work piece and a trailing end located oppositely from the leading end, relative to the rotational axis;

the shank having a pocket for coupling to the cutting head, an interlocking member arranged to retain the cutting head when the cutting head is installed within the pocket, at least one abutment surface abutting the cutting head when the cutting head is installed within the pocket, and at least one driving surface arranged to rotate the cutting head when the shank is rotated with the cutting head installed within the pocket;

the cutting head having a cutting portion at the leading end of the cutting tool assembly, an interlocking member engaging the interlocking member of the shank, and a driven surface oriented to abut the driving surface of the shank when the cutting head is installed within the pocket; wherein the interlocking member of the cutting head comprises a lateral surface oriented at an obtuse angle to the rotational axis and facing the cutting portion of the cutting head, and an extension adjacent to the lateral surface and projecting away from the cutting portion of the cutting head,

wherein the pocket of the shank has a floor portion and a surface that corresponds to the lateral surface of the cutting head, whereby the extension reinforces the interlocking member at the lateral surface oriented at an obtuse angle to the rotational axis such that stresses are minimized due to a [smoother] smooth transition between the [dovetail] surface of the pocket corresponding to the lateral surface of the cutting tool and the [pocket] floor portion of the pocket.

2. The cutting tool assembly according to claim 1, wherein the extension projecting away from the cutting portion of the cutting head has a cylindrical outer surface.

3. The cutting tool assembly according to claim 1, wherein the extension projecting away from the cutting portion of the cutting head has a tapered outer surface.

4. The cutting tool assembly according to claim 1, wherein the pocket has at least one internally facing surface oriented to abut the lateral surface [of the dovetail member] of the cutting head, the internally facing surface being dimensioned and configured to abut the [dovetail member] lateral surface of the cutting head along part of the extent of the lateral surface [of the dovetail member] and to avoid making contact along the balance of the lateral surface [of the dovetail member], whereby the uncontacted portion of the pocket allows for deflection of the pocket walls when forces are imposed on the pocket by the cutting head during cutting operations of the cutting tool, thereby mitigating radial deflection of the pocket walls.

5. The cutting tool assembly according to claim 1, wherein the driving surface of the shank is disposed out of radial orientation with respect to the rotational axis such that the driving surface has a leading inner portion and a trailing outer portion, whereby resistive forces imposed by the cutting head during cutting operations acting perpendicularly against the driving surface have an inward component tending to com-



press the wall of the pocket inwardly during cutting operations, thereby opposing forces imposed by the cutting head which would otherwise tend to spread open the pocket.

6. The cutting tool assembly according to claim 1, further comprising a circumferential surface and two opposed flutes each projecting into the tool shank along the circumferential surface, wherein the pocket further comprises a first pocket wall and a diametrically opposed second pocket wall spaced apart from the first pocket wall and the pocket has a floor which separates and spaces apart the first pocket wall from the second pocket wall and which bears a relief trough projecting into the shank towards the trailing end of the cutting tool assembly and extending across and spanning the floor from one flute to the other flute, a first shelf extending laterally across the floor at an upper edge of the relief trough at the first pocket wall and a second shelf extending laterally across the floor at another upper edge of the relief trough at the second pocket wall, and the relief trough is angularly oriented relative to the rotational axis such that the first shelf intersects only one flute and the trough is disposed between the first shelf and the other flute, and the second shelf intersects only one flute and the trough is disposed between the second shelf and the other flute.

7. A cutting tool assembly for conducting rotary cutting operations on a work piece, the cutting tool assembly comprising: a tool shank and a replaceable cutting head which is installed on and engages the tool shank, the tool shank and the cutting head having a common rotational axis and mating peripheral surfaces when assembled together, the cutting tool assembly having a leading end which engages the work piece and a trailing end located oppositely from the leading end, relative to the rotational axis;

*the cutting head having:*

*a cutting portion at the leading end of the cutting tool assembly;*

*a driven surface; and*

*an interlocking member comprising:*

*a lateral surface oriented at an obtuse angle to the rotational axis and facing the cutting portion of the cutting head; and*

*an extension adjacent to the lateral surface and projecting away from the cutting portion of the cutting head; and*

*the shank having:*

*a pocket including a pocket floor and an internally facing surface oriented to abut the lateral surface of the cutting head, the pocket being arranged to engage the interlocking member of the cutting head and retain the cutting head when the cutting head is installed within the pocket;*

*at least one abutment surface abutting the cutting head when the cutting head is installed within the pocket; and*

*at least one driving surface oriented to abut the driven surface of the cutting head and arranged to rotate the cutting head when the shank is rotated with the cutting head installed within the pocket.*

8. The cutting tool assembly according to claim 7, wherein the extension adjacent to the lateral surface and projecting away from the cutting portion of the cutting head has a cylindrical outer surface.

9. The cutting tool assembly according to claim 7, wherein the extension adjacent to the lateral surface and projecting away from the cutting portion of the cutting head has a tapered outer surface.

10. The cutting tool assembly according to claim 7, wherein the pocket has at least one internally facing surface

*oriented to abut the lateral surface of the cutting head, the internally facing surface being dimensioned and configured to abut the lateral surface along part of the extent of the lateral surface and to avoid making contact along the balance of the lateral surface, whereby the uncontacted portion of the pocket allows for deflection of the pocket walls when forces are imposed on the pocket by the cutting head during cutting operations of the cutting tool, thereby mitigating radial deflection of the pocket walls.*

11. The cutting tool assembly according to claim 7, wherein the driving surface of the shank is disposed out of radial orientation with respect to the rotational axis such that the driving surface has a leading inner portion and a trailing outer portion, whereby resistive forces imposed by the cutting head during cutting operations acting perpendicularly against the driving surface have an inward component tending to compress the wall of the pocket inwardly during cutting operations, thereby opposing forces imposed the cutting head which would otherwise tend to spread open the pocket.

12. The cutting tool assembly according to claim 7, further comprising a circumferential surface and two opposed flutes each projecting into the tool shank along the circumferential surface, wherein the pocket further comprises a first pocket wall and a diametrically opposed second pocket wall spaced apart from the first pocket wall and the pocket has a floor which separates and spaces apart the first pocket wall from the second pocket wall and which bears a relief trough projecting into the shank towards the trailing end of the cutting tool assembly and extending across and spanning the floor from one flute to the other flute, a first shelf extending laterally across the floor at an upper edge of the relief trough at the first pocket wall and a second shelf extending laterally across the floor at another upper edge of the relief trough at the second pocket wall, and the relief trough is angularly oriented relative to the rotational axis such that the first shelf intersects only one flute and the trough is disposed between the first shelf and the other flute, and the second shelf intersects only one flute and the trough is disposed between the second shelf and the other flute.

13. A replaceable cutting head for use with a shank for conducting rotary cutting operations on a work piece, the shank having a rotational axis, a driving surface, and a pocket having an internally facing surface, the replaceable cutting head comprising:

*a rotational axis;*

*a cutting portion;*

*a driven surface structured to abut the drive surface of the shank and be rotated when the shank is rotated with the cutting head installed; and*

*an interlocking member structured to engage the pocket of the tool shank in a manner that retains at least a portion of the cutting head within the pocket, the interlocking member comprising:*

*a lateral surface oriented at an obtuse angle to the rotational axis of the cutting head and facing the cutting portion of the cutting head; and*

*an extension adjacent to the lateral surface and projecting away from the cutting portion of the cutting head.*

14. The replaceable cutting head according to claim 13, wherein the extension adjacent to the lateral surface and projecting away from the cutting portion of the cutting head has a cylindrical outer surface.

15. The replaceable cutting head according to claim 13, wherein the extension adjacent to the lateral surface and projecting away from the cutting portion of the cutting head has a tapered outer surface.

16. The replaceable cutting head according to claim 13, wherein the driving surface of the shank is disposed out of radial orientation with respect to the rotational axis such that the driving surface has a leading inner portion and a trailing outer portion, whereby resistive forces imposed by the cutting head during cutting operations acting perpendicularly against the driving surface have an inward component structured to generally compress the wall of the pocket inwardly during cutting operations, thereby opposing forces imposed by the cutting head which would otherwise tend to spread open the pocket.

\* \* \* \* \*