



US00RE45052E

(19) **United States**
 (12) **Reissued Patent**
Li

(10) **Patent Number:** **US RE45,052 E**
 (45) **Date of Reissued Patent:** **Jul. 29, 2014**

(54) **FILE FORMAT FOR MULTIPLE TRACK DIGITAL DATA**

(75) Inventor: **Adam Li**, San Diego, CA (US)
 (73) Assignee: **Sonic IP, Inc.**, San Diego, CA (US)
 (21) Appl. No.: **13/087,348**
 (22) Filed: **Apr. 14, 2011**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **7,519,274**
 Issued: **Apr. 14, 2009**
 Appl. No.: **10/731,809**
 Filed: **Dec. 8, 2003**

(51) **Int. Cl.**
H04N 9/80 (2006.01)
H04N 5/45 (2011.01)
H04N 5/76 (2006.01)
H04N 5/92 (2006.01)
H04N 5/93 (2006.01)
H04N 5/225 (2006.01)
H04N 5/917 (2006.01)
H04N 7/00 (2011.01)
H04N 9/64 (2006.01)
H04N 9/74 (2006.01)
H04N 11/02 (2006.01)
G06F 3/00 (2006.01)
G06T 1/00 (2006.01)
G06T 9/00 (2006.01)

(52) **U.S. Cl.**
 USPC **386/248**; 386/239; 386/244; 386/253;
 386/259; 386/328; 386/337; 386/353; 386/356;
 345/501; 345/555; 348/220.1; 348/231.9;
 348/462; 348/578; 348/699; 375/240.01;
 375/240.12; 375/240.15; 375/240.16; 375/240.25;
 375/240.26; 375/240.28; 715/719

(58) **Field of Classification Search**
 USPC 386/248, 239, 244, 259, 353, 356,
 386/E5.004, E5.067, E9.013, E9.017, 253,
 386/318, 328, 337, E5.072; 348/E5.004,
 348/220.1, 231.9, 330.05, 462, 565, 578,
 348/699, E5.007, E5.051, E7.083; 370/463,
 370/477, 510; 375/240.25, 240.26, E7.008,
 375/E7.027, E7.091, E7.126, E7.129,
 375/E7.134, E7.138, E7.144, E7.155,
 375/E7.172, E7.181, E7.226, E7.231,
 375/E7.264, E7.265, 240.01, 240.12,
 375/240.15, 240.16, 240.28, E7.014,
 375/E7.022, E7.023, E7.094, E7.096,
 375/E7.166, E7.198, E7.211, E7.25;
 382/166, 246, 233; 704/E19.044, 246,
 704/270.1, 273, E17.003; 709/224, 231,
 709/236; G9B/27.013, 27.019, 27.021,
 G9B/27.029, 27.051; 715/719; 345/501,
 345/531, 555, E7.026, E7.093, E7.127,
 345/E7.137, E7.172, E7.181, E7.212,
 345/E7.277; 379/88.02, 93.03, 188, 283,
 379/361; 380/258, 264; 705/51;
 707/E17.028; 713/163; 719/331

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,009,331	A	2/1977	Goldmark et al.
4,694,357	A	9/1987	Rahman et al.
4,802,170	A	1/1989	Trottier
4,964,069	A	10/1990	Ely
5,119,474	A	6/1992	Beitel et al.
5,274,758	A	12/1993	Beitel et al.
5,396,497	A	3/1995	Veltman
5,420,801	A	5/1995	Dockter et al.
5,420,974	A	5/1995	Morris et al.
5,471,576	A	11/1995	Yee
5,487,167	A	1/1996	Dinallo et al.
5,533,021	A	7/1996	Branstad et al.
5,537,408	A	7/1996	Branstad et al.
5,539,908	A *	7/1996	Chen et al. 719/331
5,541,662	A	7/1996	Adams et al.
5,583,652	A	12/1996	Ware
5,627,936	A *	5/1997	Prasad et al. 386/253
5,633,472	A	5/1997	DeWitt et al.
5,642,171	A	6/1997	Baumgartner et al.
5,655,117	A	8/1997	Goldberg et al.
5,664,044	A	9/1997	Ware
5,675,382	A *	10/1997	Bauchspies 375/240.25
5,675,511	A	10/1997	Prasad et al.
5,684,542	A	11/1997	Tsukagoshi
5,719,786	A	2/1998	Nelson et al.
5,745,643	A	4/1998	Mishina

(Continued)

FOREIGN PATENT DOCUMENTS

CN	1221284	6/1999
CN	1723696	1/2006

(Continued)

OTHER PUBLICATIONS

Mark Nelson, "Arithmetic Coding + Statistical Modeling = Data Compression: Part 1—Arithmetic Coding," pp. 1-12, Doctor Dobb's Journal, Feb. 1991, USA.
 "Video Manager and Video Title Set IFO file headers", printed Aug. 22, 2009 from <http://dvd.sourceforge.net/dvdinfo/ifo.htm>, 5 pgs.
 "What is a DVD?", printed Aug. 22, 2009 from <http://www.videohelp.com/dvd>, 5 pgs.
 Noboru, Takematsu, "Play Fast and Fine Video on Web! codec", Co.9 No. 12, Dec. 1, 2003, pp. 178-179.

(Continued)

Primary Examiner — Thai Tran
Assistant Examiner — Syed Hasan
 (74) *Attorney, Agent, or Firm* — KPPB LLP

(57) **ABSTRACT**

A file for storing digital data with high compression rate stores digital data for video and audio signals in multiple streams interleaved with each other. Each track has a stream descriptor list and a stream data list. The stream descriptor list includes a stream header chunk, a stream format chunk, and a stream name chunk. For a video stream, the stream descriptor list also includes a stream header data chunk if the video stream is under digital rights management (DRM) protection. The file format is compatible with high level data compressing algorithms, such as MPEG-4, which provide data compression ratio about six to ten times higher than a standard DVD format.

96 Claims, No Drawings

(56)

References Cited

U.S. PATENT DOCUMENTS

5,751,280 A 5/1998 Abbott et al.
 5,763,800 A 6/1998 Rossum et al.
 5,765,164 A 6/1998 Prasad et al.
 5,794,018 A 8/1998 Vrvilo et al.
 5,822,524 A 10/1998 Chen et al.
 5,828,370 A 10/1998 Moeller et al.
 5,844,575 A * 12/1998 Reid 345/555
 5,848,217 A 12/1998 Tsukagoshi et al.
 5,903,261 A 5/1999 Walsh et al.
 5,907,597 A * 5/1999 Mark 379/93.03
 5,956,729 A 9/1999 Goetz et al.
 5,959,690 A * 9/1999 Toebes et al. 348/578
 6,046,778 A 4/2000 Nonomura et al.
 6,065,050 A 5/2000 DeMoney
 6,079,566 A 6/2000 Eleftheriadis et al.
 6,169,242 B1 1/2001 Fay et al.
 6,204,883 B1 3/2001 Tsukagoshi
 6,308,005 B1 10/2001 Ando et al.
 6,330,286 B1 * 12/2001 Lyons et al. 375/240.28
 6,374,144 B1 4/2002 Viviani et al.
 6,395,969 B1 5/2002 Fuhrer
 6,665,835 B1 12/2003 Gutfreund et al.
 6,671,408 B1 12/2003 Kaku
 6,697,568 B1 2/2004 Kaku
 6,725,281 B1 4/2004 Zintel et al.
 6,819,394 B1 11/2004 Nomura et al.
 6,856,997 B2 2/2005 Lee et al.
 6,917,652 B2 * 7/2005 Lyu 375/240.25
 6,944,629 B1 9/2005 Shioi et al.
 6,985,588 B1 * 1/2006 Glick et al. 380/258
 6,988,144 B1 * 1/2006 Luken et al. 709/231
 7,127,155 B2 10/2006 Ando et al.
 7,209,892 B1 4/2007 Galuten et al.
 7,237,061 B1 6/2007 Boic
 7,330,875 B1 2/2008 Parasnis et al.
 7,356,245 B2 4/2008 Belknap et al.
 7,366,788 B2 4/2008 Jones et al.
 7,457,359 B2 * 11/2008 Mabey et al. 375/240.01
 7,869,691 B2 1/2011 Kelly et al.
 8,289,338 B2 10/2012 Priyadarshi et al.
 8,472,792 B2 6/2013 Butt et al.
 2001/0030710 A1 10/2001 Werner
 2002/0034252 A1 3/2002 Owen et al.
 2002/0051494 A1 5/2002 Yamaguchi et al.
 2002/0062313 A1 5/2002 Lee et al.
 2002/0091665 A1 7/2002 Beek et al.
 2002/0093571 A1 * 7/2002 Hyodo 348/220
 2002/0110193 A1 8/2002 Yoo et al.
 2002/0118953 A1 8/2002 Kim
 2002/0143413 A1 10/2002 Fay et al.
 2002/0143547 A1 10/2002 Fay et al.
 2002/0147980 A1 10/2002 Satoda
 2002/0161462 A1 10/2002 Fay et al.
 2002/0180929 A1 12/2002 Tseng et al.
 2002/0184129 A1 12/2002 Schwartz et al.
 2002/0184159 A1 12/2002 Tadayon et al.
 2002/0191112 A1 12/2002 Akiyoshi et al.
 2002/0191960 A1 * 12/2002 Fujinami et al. 386/95
 2003/0001964 A1 1/2003 Masukura et al.
 2003/0005442 A1 1/2003 Brodersen et al.
 2003/0035488 A1 2/2003 Barrau
 2003/0078930 A1 4/2003 Surcouf et al.
 2003/0093799 A1 5/2003 Kauffman et al.
 2003/0123855 A1 7/2003 Okada et al.
 2003/0133506 A1 * 7/2003 Haneda 375/240.25
 2003/0165328 A1 9/2003 Grecia
 2003/0185302 A1 10/2003 Abrams
 2003/0185542 A1 10/2003 McVeigh et al.
 2003/0206558 A1 * 11/2003 Parkkinen et al. 370/477
 2004/0006701 A1 1/2004 Kresina
 2004/0021684 A1 * 2/2004 Millner 345/719
 2004/0025180 A1 2/2004 Begeja et al.
 2004/0047614 A1 3/2004 Green
 2004/0052501 A1 3/2004 Tam
 2004/0071453 A1 4/2004 Valderas

2004/0114687 A1 6/2004 Ferris et al.
 2004/0117347 A1 6/2004 Seo et al.
 2004/0136698 A1 7/2004 Mock
 2004/0143760 A1 7/2004 Alkove et al.
 2004/0146276 A1 7/2004 Ogawa
 2004/0217971 A1 11/2004 Kim
 2005/0055399 A1 3/2005 Savchuk
 2005/0196147 A1 9/2005 Seo et al.
 2005/0207442 A1 9/2005 Zoest et al.
 2006/0093320 A1 5/2006 Hallberg et al.
 2006/0168639 A1 7/2006 Gan et al.
 2006/0267986 A1 11/2006 Bae
 2006/0274835 A1 * 12/2006 Hamilton et al. 375/240.25
 2007/0005333 A1 1/2007 Setiohardjo et al.
 2008/0120330 A1 5/2008 Reed et al.
 2008/0120342 A1 5/2008 Reed et al.

FOREIGN PATENT DOCUMENTS

EP 757484 2/1997
 EP 1420580 A1 5/2004
 EP 1718074 A1 11/2006
 JP 08287613 11/1996
 JP 11328929 A 11/1999
 JP 02001043668 A 2/2001
 JP 2002-170363 6/2002
 JP 2002218384 A 8/2002
 JP 2003250113 A 9/2003
 KR 10-0221423 6/1999
 KR 0221423D1 6/1999
 KR 100221423 B1 6/1999
 KR 2002013664 2/2002
 KR 1020020064888 8/2002
 WO 9515660 6/1995
 WO 0131497 A1 5/2001
 WO 0150732 7/2001
 WO 0201880 1/2002
 WO 2004/054247 A1 6/2004
 WO 2004097811 11/2004

OTHER PUBLICATIONS

IBM Corporation and Microsoft Corporation, "Multimedia Program Author Unknown, AVI RIFF File Reference (Direct X 8.1 C++ Archive), printed from http://msdn.microsoft.com/archive/en-us/dx81_c/directx_cpp/htm/aviriffreference.asp?fr... on Mar. 6, 2006, 7 pgs.
 Author Unknown, "Entropy and Source Coding (Compression)," pp. 1-22, TCOM 570, 1999, USA.
 Author Unknown, "MPEG-4 Video Encoder: Based on International Standard ISO/IEC 14496-2," pp. 1-15, Patni Computer Systems, Ltd., publication date unknown, USA.
 Broadq—The Ultimate Home Entertainment Software, printed May 11, 2009 from <http://web.archive.org/web/20030401122010/www.broadq.com/qcasttuner/1> pg.
 Darek Blasiak, Ph.D., "Video Transrating and Transcoding: Overview of Video Transrating and Transcoding Technologies," pp. 1-22, Ingenient Technologies, Aug. 6, 2002, Houston, TX, USA. ming Interface and Data Specifications 1.0", Aug. 1991, printed from <http://www.kk.ij4u.or.jp/~kondo/wave/mpidata.txt> on Mar. 6, 2006, 100 pgs.
 Kiss DP-500 from <http://www.kiss-technology.com/?p=dp500>, 10 Kiss Players, 1 pg.
 Linksys Wireless-B Media Adapter Reviews, printed May 4, 2007 from http://reviews.cnet.com/Linksys_Wireless_B_Media_Adapter/4505-6739_7-30421900.html?tag=box, 5 pgs.
 Linksys, Kiss DP-500, printed May 4, 2007 from <http://www.kiss-technology.com/?p=dp500>, 2 pgs.
 LINKSYS®: "Enjoy your digital music and pictures on your home entertainment center, without stringing wires!", Model No. WMA 11B, printed May 9, 2007 from http://www.linksys.com/servlet/Satellite?c=L_Product_C2&childpagename=US/Layout&cid=1115416830950&p.
 Mark, "Arithmetic Coding + Statistical Modeling = Data Compression: Part 1—Arithmetic Coding," pp. 1-12, Doctor Dobb's Journal, Feb. 1991, USA.

(56)

References Cited

OTHER PUBLICATIONS

Microsoft Corporation, "Chapter 8, Multimedia File Formats" 1991, Microsoft Windows Multimedia Programmer's Reference, 3 cover pgs., pp. 8-1 to 8-20.

Microsoft Windows® XP Media Center Edition 2005, Frequently asked Questions, printed May 4, 2007 from <http://www.microsoft.com/windowsxp/mediacenter/evaluation/faq.mspx>.

Microsoft Windows® XP Media Center Edition 2005: Features, printed May 9, 2007, from <http://www.microsoft.com/windowsxp/mediacenter/evaluation/features.mspx>, 4 pgs.

Morrison, "EA IFF 85" Standard for Interchange Format Files, Jan. 14, 1985, printed from <http://www.dcs.ed.ac.uk/home/mxr/gfx/2d/IFF.txt> on Mar. 6, 2006, 24 pgs.

Nam, "Theory of Data Compression," pp. 1-12, publication date unknown, USA.

Open DML AVI-M-JPEG File Format Subcommittee, "Open DML AVI File Format Extensions", Version 1.02, Feb. 28, 1996, 29 pgs.

PC world.com, Future Gear: PC on the HiFi, and the TV, from <http://www.pcworld.com/article/id,108818-page,1/article.html>, printed May 4, 2007, from IDG Networks, 2 pgs.

Qtv—About BroadQ, printed May 11, 2009 from <http://www.broadq.com/en/about.php>, 1 pg.

Taxan, A Vel LinkPlayer2 for Consumer, I-O Data USA—Products—Home Entertainment, printed May 4, 2007 from <http://www.iodata.com/usa/products/products.php?cat=HNP&sc=AVEL&pId=AVLP2/DVDLA&ts=2&tsc>, 1 pg.

Wi-Fi Planet, The Wireless Digital Picture Frame Arrives, printed May 4, 2007 from <http://www.wi-fiplanet.com/news/article.php/3093141>, 3 pgs.

Windows Media Center Extender for Xbox, printed May 9, 2007 from <http://www.xbox.com/en-US/support/systemuse/xbox/console/mediacenterextender.htm>, 2 pgs.

Windows® XP Media Center Edition 2005 from <http://download.microsoft.com/download/c/9/a/c9a7000a-66b3-455b-860b-1c16f2eefec/MCE.pdf>, 2 pgs.

I-O Data, Innovation of technology arrived, from http://www.iodata.com/catalogs/AVLP2DVDLA_Flyer200505.pdf, 2 pgs.

"Container format (digital)", printed Aug. 22, 2009 from [http://en.wikipedia.org/wiki/Container_format_\(digital\)](http://en.wikipedia.org/wiki/Container_format_(digital)), 4 pgs.

"DVD—MPeg differences", printed Aug. 22, 2009 from <http://dvd.sourceforge.net/dvdinfo/dvdmpeg.html>, 2 pgs.

"DVD subtitles", sam.zoy.org/writings/dvd/subtitles, dated Jan. 9, 2001, printed Jul. 2, 2009, 4 pgs.

"DVD-Mpeg differences", <http://dvd.sourceforge.net/dvdinfo/dvdmpeg.html>, printed on Jul. 2, 2009, 1 pg.

"Final Committee Draft of MPEG-4 streaming text format", International Organisation for Standardisation, Feb. 2004, 22 pgs.

"Information Technology—Coding of audio-visual objects—Part 17: Streaming text", International Organisation for Standardisation, Feb. 2004, 16 pgs.

"OpenDML AVI File Format Extensions", www.the-labs.com/Video/odmlffz-avidef.pdf, Authored by the OpenDML AVI M-JPEG File Format Subcommittee, Sep. 1, 1997.

"QCast Tuner for PS2", printed May 11, 2009 from <http://web.archive.org/web/20030210120605/www.divx.com/software/detail.php?ie=39>, 2 pgs.

"Video Manager and Video Title Set IFO file headers", printed Aug. 22, 2009 from <http://dvd.sourceforge.net/dvdinfo/ifo.htm>, 6 pgs.

"What is a DVD?", printed Aug. 22, 2009 from <http://www.videohelp.com/dvd>, 8 pgs.

"What is a VOB file", <http://www.mpuCoder.com/DVD/vobov.html>, printed on Jul. 2, 2009, 2 pgs.

"What's on a DVD?", printed Aug. 22, 2009 from <http://www.doom9.org/dvd-structure.htm>, 8 pgs.

Noboru, "Play Fast and Fine Video on Web! codec", Co.9 No. 12, Dec. 1, 2003, 178-179.

European Supplementary Search Report for Application EP09759600, completed Jan. 25, 2011, 11 pgs.

International Search Report for International Application No. PCT/US09/46588, date completed Jul. 14, 2009, date mailed Jul. 23, 2009, 2 pgs.

International Search Report for International Application No. PCT/US2004/041667, International Filing Date Dec. 8, 2004, Report Completed May 24, 2007, mailed Jun. 20, 2007, 4 pgs.

Written Opinion for International Application No. PCT/US2004/041667, Filing Date Dec. 8, 2004, Report Completed May 24, 2007, Mailed Jun. 20, 2007, 4 pgs.

Written Opinion of the International Searching Authority for International Application No. PCT/US09/46588, date completed Jul. 14, 2009, date mailed Jul. 23, 2009, 5 pgs.

"Text of ISO/IEC 14496-18/COR1", ITU Study Group 16—Video Coding Experts Group—ISO/IEC MPEG & ITU-T VCEG(ISO/IEC JTC1/SC29/WG11 and ITU-T SG16 06), No. N8664, Feb. 1, 2007.

"Text of ISO/IEC 14496-18/FDIS", ITU Study Group 16—Videocoding Experts Group—ISO/IEC MPEG & ITU-T VCEG(ISO/IEC JTC1/SC29/WG11 and ITU-T SG16 06), No. N6215, Jul. 1, 2004.

Casares et al., "Simplifying Video Editing Using Metadata", DIS2002, pp. 157-166.

Long et al., "Silver: Simplifying Video Editing with Metadata", Demonstrations, CHI 2003: New Horizons, pp. 628-629.

Noe, A., "Matroska File Format", Retrieved from the Internet: URL:<http://web.archive.org/web/20070821155146/www.matroska.org/technical/specs/matroska.pdf> [retrieved on Jan. 19, 2011], Jun. 24, 2007, 1-51.

* cited by examiner

FILE FORMAT FOR MULTIPLE TRACK DIGITAL DATA

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

FIELD OF THE INVENTION

The present invention relates, in general, to data storage and archiving and, more specifically, to file formats for storing multiple tracks or streams of data.

BACKGROUND OF THE INVENTION

Thanks to its fidelity, digital video and audio have become increasingly popular in entertainment and information recording. For example, digital versatile disc or digital video disc (DVD) provides a format used to store movies, music, or software programs. A DVD movie often has multiple audio tracks for multilingual presentation of the movie and/or multiple video tracks for including special features such as interviews with the movie producer, movie trailers, etc. A DVD has a memory capacity of approximately six gigabytes (GB). In the standard format, a single sided DVD generally can store approximately two to three hours of video.

It would be advantageous to have a file format for storing digital data with a high compression rate. It would be desirable for the file format to be capable of storing data in multiple streams or tracks. It would also be desirable for the file format to be able to encode and archive video, audio, and text data on easily accessible streams or tracks. It would be of further advantage for the file format to be able to provide copyright protection for the digitized content.

DETAILED DESCRIPTION OF VARIOUS EMBODIMENTS

In accordance with preferred embodiments of the present invention, digitized data, e.g., digital video, audio, and/or text data, are encoded and stored in a multimedia file following a format that is compatible with a standard data coding and compression algorithm. The file is readable and/or executable by a processor, e.g., a specific or generic signal processor, a digital signal processor (DSP), a signal processor on an Application Specific Integrated Circuit (ASIC), an Advanced RISC Machine (ARM) microprocessor, etc.

In accordance with a specific embodiment of the present invention, the file format is based on the audio video interleave (AVI) multimedia format. The AVI file format is a Resource Interchange File Format (RIFF) file specification used with applications that capture, edit, and play back audio-video sequences.

RIFF, introduced in 1991 by Microsoft Corporation and IBM Corporation, is a format for storing tagged data structures. The structure and coding of RIFF can be found at the Microsoft Developer Network (<http://msdn.microsoft.com/>). The related information on the Microsoft Developer Network is incorporated herein by reference.

A RIFF file includes a RIFF header followed by zero or more lists and chunks. The RIFF header has the following form:

'RIFF' fileSize fileType (data)
where 'RIFF' is a four character code (FOURCC) that has the value 'RIFF', fileSize is a 4 byte number giving the size of the

data in the file, and fileType is a FOURCC that identifies the specific file type. The value of fileSize includes the size of the fileType FOURCC and the size of the data that follows, but does not include the size of the 'RIFF' FOURCC or the size of fileSize. The file data includes data chunks and lists, in any order.

A chunk has the form:

ckID ckSize ckData

where ckID is a FOURCC that identifies the data contained in the chunk, ckData is a 4 byte number giving the size of the data in ckData, and ckData is zero or more bytes of data. The data is always padded to nearest WORD boundary. ckSize gives the size of the valid data in the chunk, but it does not include the padding, the size of ckID, or the size of ckSize.

A list is an ordered collection of other chunks, for example a collection of movie frames. In RIFF, a list has the form:

'LIST' listSize listType listData

where 'LIST' is the literal FOURCC code 'LIST', listSize is a 4 byte number giving the size of the list, listType is a FOURCC code identifying the type of the list, and listData consists of chunks or lists, in any order. The value of listSize includes the size of listType plus the size of listData, but it does not include the 'LIST' FOURCC or the size of listSize.

It is customary and efficient to imply the chunk size and adopt a simplified notation to represent a RIFF chunk:

ckID (ckData)

Adopting a similar simplified notation, a list can be represented as:

'LIST' (listType (listData))

The notation places optional elements in brackets, [optional element]

An AVI file is identified by a FOURCC 'AVI' in the RIFF header. All AVI files include two mandatory LIST chunks: the stream format and the stream data. An AVI file may also include an index chunk, which gives the location of the data chunks within the file. An AVI file with these components has the form:

```

RIFF      ('AVI'
          ['CSET' (Character Set)]
          [LIST ('INFO')]
          LIST ('hdr1' ...)
          LIST ('movi' ...)
          ['idx1' (<AVI Index>)]
          )

```

The 'hdr1' list defines the format of the data and is the first required LIST chunk. The 'movi' list contains the data for the AVI sequence and is the second required LIST chunk. The 'idx1' list contains the index, which is optional. AVI files keep these three components in the proper sequence.

The 'hdr1' and 'movi' lists use subchunks for their data. The following example shows the AVI RIFF form expanded with the chunks needed to complete these lists:

```

RIFF      ('AVI'
          ['CSET' (Character Set)]
          [LIST ('INFO')]
          LIST 'hdr1'
                'avih' (<Main AVI Header>)
          LIST ('strl'
                'strh' (<Stream header>)
                'strf' (<Stream format>)
                ['strd' (<Additional header data>)]
                ['strn' (<Stream name>)]
                ...
          )

```

3

-continued

```

...
)
LIST ('movi'
    {SubChunk | LIST ('rec'
        SubChunk1
        SubChunk2
        ...
    )
    }
...
)
['idx1' (<AVI Index>)]
)

```

The character set (CSET) chunk is typically used to define a character set and language information for a RIFF file, a LIST, or a stream. The CSET chunk is defined as follows:

```

CSET (
    WORD wCodePage
    WORD wCountryCode
    WORD wLanguageCode
    WORD wDialect
)

```

In accordance with a preferred embodiment of the present invention, the functions and formats of the fields in the CSET chunk are defined as follows:

wCodePage specifies the code page used for file elements. If the CSET chunk is not present or if this field has a value of zero, a standard ISO 8859/1 code page (identical to code page 1004 without code points defined in hex columns 0, 1, 8, and 9) is assumed in accordance with an embodiment of the present invention.

wCountryCode specifies the country code used for file elements. If the CSET chunk is not present or if this field has value zero, USA (country code 001) is assumed in accordance with an embodiment of the present invention. By way of example, the country codes used in the wCountryCode field of CSET chunk are listed in Table 1.

wLanguage and wDialect specify the language and dialect used for file elements. If the CSET chunk is not present or if these fields have value zero, US English (language code 9, dialect code 1) is assumed in accordance with an embodiment of the present invention. By way of example, the language and dialect codes used in the wLanguage and wDialect fields of CSET chunk are listed in Table 2.

The information 'INFO' list is a registered global form type that can store information, e.g., copyright information and comments, that helps identify the contents of the chunk. This information, although useful, does not affect the way a program interprets the file. An 'INFO' list is a 'LIST' chunk with list type 'INFO'.

In accordance with a preferred embodiment, an 'INFO' list may contain the chunks listed in Table 3. Additional chunks may be defined. Preferably, an application ignores any chunk it doesn't understand. Each chunk contains a null-terminated Unicode text string. The character set used in the string is specified by the global CSET chunk.

The AVI file header ('hdr1') list includes a main AVI header in an 'avih' chunk. One or more stream descriptor lists follow the main AVI header. Each stream descriptor is contained in an 'str1' list.

The main AVI header contains global information for the entire AVI file, such as the number of streams within the file

4

and the width and height of the AVI sequence. The main header chunk includes an AVIMAINHEADER structure, whose syntax is defined as:

```

5 typedef struct _avimainheader {
    FOURCC fcc;
    DWORD cb;
    DWORD dwMicroSecPerFrame;
    DWORD dwMaxBytesPerSec;
10 DWORD dwPaddingGranularity;
    DWORD dwFlags;
    DWORD dwTotalFrames;
    DWORD dwInitialFrames;
    DWORD dwStreams;
    DWORD dwSuggestedBufferSize;
15 DWORD dwWidth;
    DWORD dwHeight;
    DWORD dwReserved[4];
} AVIMAINHEADER

```

In accordance with a preferred embodiment, the members in the AVIMAINHEADER structure have the following variables:

fcc specifies a FOURCC code with the value being 'avih'.
cb specifies the size of the structure, not including the initial 8 bytes of fcc and cb.

dwMicroSecPerFrame

specifies the number of microseconds between frames and indicates the overall timing for the file.

dwMaxBytesPerSec

specifies the approximate maximum data rate of the file. This value indicates the number of bytes per second the system must handle to present an AVI sequence as specified by other parameters contained in the main header and stream header chunks.

dwPaddingGranularity

specifies the alignment for data, in bytes. Data are padded to multiples of this value.

dwFlags

includes a bitwise combination of zero or more of the following flags:

AVIF_HASINDEX—Indicates the AVI file has an index.

AVIF_MUSTUSEINDEX—Indicates that the application should use the index, instead of the physical ordering of the chunks in the file, to determine the order of presentation of the data. For example, this flag could be used to create a list of frames for editing.

AVIF_ISINTERLEAVED—Indicates the AVI file being interleaved.

AVIF_WASCAPTUREFILE—Indicates the AVI file as a specially allocated file used for capturing real-time video. Applications should warn the user before writing over a file with this flag set because the user may defragment this file.

AVIF_COPYRIGHTED—Indicates the AVI file contains copyrighted data and software. When this flag is used, software should not permit the data to be duplicated.

dwTotalFrames

specifies the total number of frames of data in the file.

dwInitialFrames:

specifies the initial frame for interleaved files. For non-interleaved files the value should specify zero. When creating interleaved files, the number of frames in the file should be specified prior to the initial frame of the AVI sequence in this member.

5

dwStreams

specifies the number of streams in the file. For example, a file with audio and video has at least two streams.

dwSuggestedBufferSize

specifies the suggested buffer size for reading the file. Preferably, this size should be large enough to contain the largest chunk in the file. If set to zero, or too small, the playback software will have to reallocate memory during playback, which will reduce performance. For an interleaved file, the buffer size should be large enough to read an entire record, and not just a chunk.

dwWidth

specifies the width of the AVI file in pixels.

dwHeight:

specifies the height of the AVI file in pixels.

dwReserved

reserved, set to zero.

By way of example, the flags in the member dwFlags include the following bitwise combinations:

```

/* flags for use in <dwFlags> in AVIFileHdr */
#define AVIF_HASINDEX          0x00000010
#define AVIF_MUSTUSEINDEX     0x00000020
#define AVIF_ISINTERLEAVED    0x00000100
#define AVIF_TRUSTCKTYPE      0x00000800
#define AVIF_WASCAPTUREFILE   0x00010000
#define AVIF_COPYRIGHTED     0x00020000
    
```

TABLE 1

Country codes (wCountryCode)	
Country Code (wCountryCode)	Country or Region
000	None (ignore this field)
001	USA
002	Canada
003	Latin America
030	Greece
031	Netherlands
032	Belgium
033	France
034	Spain
039	Italy
041	Switzerland
043	Austria
044	United Kingdom
045	Denmark
046	Sweden
047	Norway
049	Germany
052	Mexico
055	Brazil
061	Australia
064	New Zealand
081	Japan
082	Korea
086	People's Republic of China
088	Taiwan
090	Turkey
351	Portugal
352	Luxembourg
354	Iceland
358	Finland

6

TABLE 2

Language codes and dialect codes		
Language Code (wLanguage)	Dialect Code (wDialect)	Language
0	0	None (ignore these fields)
1	1	Arabic
2	1	Bulgarian
3	1	Catalan
4	1	Traditional Chinese
4	2	Simplified Chinese
5	1	Czech
6	1	Danish
7	1	German
7	2	Swiss German
8	1	Greek
9	1	US English
9	2	UK English
10	1	Spanish
10	2	Spanish Mexican
11	1	Finnish
12	1	French
12	2	Belgian French
12	3	Canadian French
12	4	Swiss French
13	1	Hebrew
14	1	Hungarian
15	1	Icelandic
16	1	Italian
16	2	Swiss Italian
17	1	Japanese
18	1	Korean
19	1	Dutch
19	2	Belgian Dutch
20	1	Norwegian - Bokmal
20	2	Norwegian - Nynorsk
21	1	Polish
22	1	Brazilian Portuguese
22	2	Portuguese
23	1	Rhaeto-Romanic
24	1	Romanian
25	1	Russian
26	1	Serbo-Croatian (Latin)
26	2	Serbo-Croatian (Cyrillic)
27	1	Slovak
28	1	Albanian
29	1	Swedish
30	1	Thai
31	1	Turkish
32	1	Urdu
33	1	Bahasa

TABLE 3

Information List (INFO) chunks	
Chunk ID	Description
IARL	Archival Location, indicating where the subject of the file is archived.
IART	Artist, listing the artist of the original subject of the file.
55 ICMS	Commissioned, listing the name of the person or organization that commissioned the subject of the file.
ICMT	Comments, providing general comments about the file or the subject of the file, if multiple sentences in length, each sentence ending with a period, no new line characters.
ICOP	Copyright, recording the copyright information for the file, multiple copyrights separated by a semicolon followed by a space.
60 ICRD	Creation date, specifying the date the subject of the file was created, listing dates in year-month-day format, padding one-digit months and days with a zero on the left.
ICRP	Cropped, indicating whether an image has been cropped and, if so, how it was cropped, e.g., "lower right corner".
65 IDIM	Dimensions, specifying the size of the original subject of the file, e.g., 8.5 inches in height, 11 inches in width.

TABLE 3-continued

Information List (INFO) chunks	
Chunk ID	Description
IDPI	Dots Per Inch, specifying dots per inch setting of the digitizer used to produce the file, such as 300.
IENG	Engineer, specifying the name of the engineer who worked on the file. If there are multiple engineers, the names are separated by a semicolon and a blank, e.g., Smith, John; Adams, Joe.
IGNR	Genre, describing the original work, such as, landscape, portrait, still life, etc.
IKEY	Keywords, providing a list of keywords that refer to the file or subject of the file, with multiple keywords separated with a semicolon and a blank, e.g., "Seattle; aerial view; scenery".
ILGT	Lightness, describing the changes in lightness settings on the digitizer required to produce the file, its format depending on hardware used.
IMED	Medium, describing the original subject of the file, e.g., computer image, drawing, lithograph.
INAM	Name, storing the title of the subject of the file, such as, "Seattle From Above".
IPLT	Palette Setting specifying the number of colors requested when digitizing an image.
IPRD	Product, specifying the name of the product, for which the file was originally intended, e.g., "Encyclopedia of Pacific Northwest Geography".
ISBJ	Subject, describing the contents of the file, e.g., "Aerial view of Seattle".
ISFT	Software, identifying the name of the software package used to create the file, e.g., "Microsoft WaveEdit".
ISHP	Sharpness, identifying the changes in sharpness for the digitizer required to produce the file, its format depending on the hardware used.
ISRC	Source, identifying the person or organization that supplied the original subject of the file.
ISRF	Source Form, identifying the original form of the material that was digitized, e.g., slide, paper, map, which may be different from IMED.
ITCH	Technician, identifying the technician who digitized the subject file.

One or more stream descriptor ('str1') lists follow the main header 'hdr1'. Each 'str1' list corresponds to a data stream and includes information about the data stream in the file. A 'str1' list contains a stream header chunk ('strh') and a stream format chunk ('strf'). In addition, a 'str1' list may contain a stream header data chunk ('strd') and a stream name chunk ('strn'). The stream descriptors in the 'hdr1' list are associated with the stream data in the 'movi' list according to the order of the 'str1' lists. The first 'str1' list applies to stream 0, the second applies to stream 1, and so forth.

The stream header chunk ('strh') in the 'str1' list includes an AVISTREAMHEADER structure containing information about a stream in the AVI file. The AVISTREAMHEADER structure has the syntax:

```
typedef struct _avistreamheader {
    FOURCC      fcc;
    DWORD       cb;
    FOURCC      fccType;
    FOURCC      fccHandler;
    DWORD       dwFlags;
    WORD        wPriority;
    WORD        wLanguage;
    DWORD       dwInitialFrames;
    DWORD       dwScale;
    DWORD       dwRate;
    DWORD       dwStart;
    DWORD       dwLength;
    DWORD       dwSuggestedBufferSize;
    DWORD       dwQuality;
    DWORD       dwSampleSize;
}
```

-continued

```
struct
{
    WORD      left;
    WORD      top;
    WORD      right;
    WORD      bottom;
} rcFrame;
} AVISTREAMHEADER
```

In accordance with a preferred embodiment, the members in the AVISTREAMHEADER structure have following variables:

fcc specifies a FOURCC, with the value being 'strh'.

cb specifies the size of the structure, not including the initial 8 bytes.

fccType

contains a FOURCC that specifies the type of the data in the stream, with the following standard AVI values for video and audio:

'auds' Audio stream

'mids' MIDI stream

'txts' Text stream

'vids' Video stream

fccHandler

optional, may contain a FOURCC that identifies a specific data handler preferred handler for the stream. For audio and video streams, this specifies the codec for decoding the stream.

dwFlags

contains flags for the data stream. The bits in the high-order word of these flags are specific to the type of data contained in the stream. The standard flags are: AVISF_DISABLED—Indicates the stream should not be enabled by default.

AVISF_VIDEO_PALCHANGES—Indicates the video stream contains palette changes, thereby warning the playback software that it will need to animate the palette.

dwPriority

specifies the priority of a stream type. For example, in a file with multiple audio streams, the one with the highest priority might be the default stream.

dwInitialFrames

specifies how far audio data is skewed ahead of the video frames in interleaved files, e.g., 0.75 seconds. For an interleaved file, dwInitialFrames specifies the number of frames in the file prior to the initial frame of the AVI sequence.

dwScale

specifies, in combination with dwRate, the time scale that the stream will use.

dwRate

specifies, in combination with dwScale, the time scale that the stream will use. Dividing dwRate by dwScale gives the number of samples per second. For video streams, this is the frame rate. For audio streams, this rate corresponds to the time needed to play nBlockAlign bytes of audio. For pulse code modulation (PCM) audio this rate corresponds to sample rate.

dwStart

specifies the starting time for this stream, with units defined by the dwRate and dwScale members in the main file header. Usually, its value is zero. A nonzero value specifies a delay time for a stream that does not start concurrently with the file.

dwLength
specifies the length of the stream. The units are defined by dwRate and dwScale.

dwSuggestedBufferSize
specifies how large a buffer should be used to read this stream. Preferably, it has a value corresponding to the largest chunk present in the stream. Using the correct buffer size makes playback more efficient. The value can be set to zero if the correct buffer size is unknown.

dwQuality
specifies the quality of the data in the stream, represented as a number between 0 and 10,000. For compressed data, this typically represents the value of the quality parameter passed to the compression software. If set to -1, drivers use the default quality value.

dwSampleSize
specifies the size of a single sample of data. This is set to zero if the samples can vary in size. For nonzero values, multiple samples of data can be grouped into a single chunk within the file. For a value of zero, each sample of data, e.g., a video frame, must be in a separate chunk. For video streams, the value is typically zero, although it can be nonzero if all video frames are the same size. For audio streams, the value should be the same as the nBlockAlign member of the WAVEFORMATEX structure describing the audio.

rcFrame
specifies, in pixels, the destination rectangle for a text or video stream within the movie rectangle specified by the dwWidth and dwHeight members of the AVI main header structure. The rcFrame member is typically used in support of multiple video streams. The rectangle is preferably set to the coordinates corresponding to the movie rectangle to update the whole movie rectangle. The upper left corner of the destination rectangle is relative to the upper left corner of the movie rectangle. In accordance with the present invention the members in RcFrame may be defined as DWORD as well as WORD.

A stream format ('strf') chunk follows the stream header ('str1') chunk. The stream format chunk describes the format of the data in the stream. The data contained in this chunk depends on the stream type.

For video streams, the information is a BITMAPINFOHEADER structure, including palette information if appropriate. The structure of BITMAPINFOHEADER is defined as:

```

typedef struct BITMAPINFOHEADER {
    DWORD      biSize;
    LONG       biWidth;
    LONG       biHeight;
    WORD       biPlanes;
    WORD       biBitCount;
    DWORD      biCompression;
    DWORD      biSizeImage;
    LONG       biXPelsPerMeter;
    LONG       biYPelsPerMeter;
    DWORD      biClrUsed;
    DWORD      biClrImportant;
} BITMAPINFOHEADER

```

In accordance with a preferred embodiment, the members in the BITMAPINFOHEADER structure have following variables:

BiSize
specifies the number of bytes required by the structure.

BiWidth
specifies the width of the bitmap in pixels, or specifies the width of the decompressed JPEG image file for Microsoft Windows 98, Windows NT 5.0 and later versions if bicompression is BI_JPEG.

BiHeight
specifies the height of the bitmap in pixels, or specifies the height of the decompressed JPEG image file for Microsoft Windows 98, Windows NT 5.0 and later versions if biCompression is BI_JPEG. If biHeight is positive, the bitmap is a bottom-up device independent bitmap (DIB) and its origin is the lower-left corner. If biHeight is negative, the bitmap is a top-down DIB and its origin is the upper-left corner.

biPlanes
specifies the number of planes for the target device. This value is set to 1.

biBitCount
specifies the number of bits per pixel and determining the number of bits that define each pixel and the maximum number of colors in the bitmap. Its values and their meanings are:

0 for Windows 98, Windows NT 5.0, and later, the number of bits per pixel is specified or is implied by the JPEG format.

1 specifies that the bitmap is monochrome, and bmiColors contains two entries. Each bit in the bitmap array represents a pixel. If the bit is clear, the pixel is displayed with the color of the first entry in the bmiColors table. If the bit is set, the pixel has the color of the second entry in the table.

4 specifies that the bitmap has a maximum of 16 colors, and bmiColors contains up to 16 entries. Each pixel in the bitmap is represented by a 4-bit index into the color table. For example, if the first byte in the bitmap is 0x1F, the byte represents two pixels. The first pixel contains the color in the second table entry, and the second pixel contains the color in the sixteenth table entry.

8 specifies that the bitmap has a maximum of 256 colors, and bmiColors contains up to 256 entries. Each byte in the array represents a single pixel.

16 specifies that the bitmap has a maximum of 2^{16} colors. If biCompression is BI_RGB, bmiColors is NULL. Each WORD in the bitmap array represents a single pixel. The relative intensities of red, green, and blue are represented with 5 bits for each color component. The value for blue is in the least significant 5 bits, followed by 5 bits each for green and red. The most significant bit is not used. The bmiColors color table is used for optimizing colors used on palette-based devices, and contains the number of entries specified by biClrUsed. If bicompression is BI_BITFIELDS, bmiColors member contains three DWORD color masks that specify the red, green, and blue components, respectively, of each pixel. Each WORD in the bitmap array represents a single pixel. For Windows NT: When bicompression is BI_BITFIELDS, bits set in each DWORD mask are contiguous and should not overlap the bits of another mask. All the bits in the pixel do not have to be used.

For Windows 95 and Windows 98: When biCompression is BI_BITFIELDS, the system supports only the following 16 bits per pixel (bpp) color masks: A 5-5-5 16-bit image, where the blue mask is 0x001F, the green mask is 0x03E0, and the red mask is

11

0x7C00; and a 5-6-5 16-bit image, where the blue mask is 0x001F, the green mask is 0x07E0, and the red mask is 0xF800.

24 specifies that the bitmap has a maximum of 2^{24} colors, and the bmiColors member is NULL. Each 3-byte triplet in the bitmap array represents the relative intensities of blue, green, and red, respectively, for a pixel. The bmiColors color table is used for optimizing colors used on palette-based devices, and contains the number of entries specified by biClrUsed.

32 specifies that the bitmap has a maximum of 2^{32} colors. If the biCompression member of the BITMAPINFOHEADER is BI_RGB, the bmiColors member is NULL. Each DWORD in the bitmap array represents the relative intensities of blue, green, and red, respectively, for a pixel. The high byte in each DWORD is not used. The bmiColors color table is used for optimizing colors used on palette-based devices, and must contain the number of entries specified by biClrUsed.

If biCompression is BI_BITFIELDS, bmiColors contains three DWORD color masks that specify the red, green, and blue components, respectively, of each pixel. Each DWORD in the bitmap array represents a single pixel. For Windows NT: When biCompression is BI_BITFIELDS, bits set in each DWORD mask must be contiguous and should not overlap the bits of another mask. All the bits in the pixel do not need to be used.

For Windows 95 and Windows 98: When biCompression is BI_BITFIELDS, the system supports only the following 32 bpp color mask. The blue mask is 0x000000FF, the green mask is 0x0000FF00, and the red mask is 0x00FF0000.

BiCompression

specifies the type of compression for a compressed bottom-up bitmap. If biHeight is negative, indicating a top-down DIB, biCompression must be either BI_RGB or BI_BITFIELDS. Top-down DIBs cannot be compressed. The member can be one of the following values:

BI_RGB

specifies an uncompressed format.

BI_RLE8

specifies a run-length encoded (RLE) format for bitmaps with 8 bits per pixel. The compression format is a 2-byte format consisting of a count byte followed by a byte containing a color index.

BI_RLE4

specifies an RLE format for bitmaps with 4 bits per pixel. The compression format is a 2-byte format consisting of a count byte followed by two wordlength color indexes.

BI_BITFIELDS

specifies that the bitmap is not compressed and that the color table consists of three DWORD color masks that specify the red, green, and blue components, respectively, of each pixel. This is valid when used with 16 bpp and 32 bpp bitmaps.

BI_JPEG

Indicates that the image is a JPEG image for Windows 98, Windows NT 5.0, and later versions.

BiSizeImage

specifies the size, in bytes, of the image. Its value may be set to zero for BI_RGB bitmaps. For Windows 98,

12

Windows NT 5.0, and later versions: If bicompression is JBI_JPEG, biSizeImage indicates the size of the JPEG image buffer.

BiXPelsPerMeter

specifies the horizontal resolution, in pixels per meter, of the target device for the bitmap. An application can use this value to select a bitmap from a resource group that best matches the characteristics of the current device.

BiYPelsPerMeter

specifies the vertical resolution, in pixels per meter, of the target device for the bitmap.

BiClrUsed

specifies the number of color indexes in the color table that are actually used by the bitmap.

If BiClrUsed is zero, the bitmap uses the maximum number of colors corresponding to the value of the biBitCount for the compression mode specified by biCompression.

If biClrUsed is nonzero and biBitCount is less than 16, biClrUsed specifies the actual number of colors the graphics engine or device driver accesses. If biBitCount is 16 or greater, biClrUsed specifies the size of the color table used to optimize performance of the system color palettes. If biBitCount equals 16 or 32, the optimal color palette starts immediately following the three DWORD masks.

If the bitmap is a packed bitmap (a bitmap in which the bitmap array immediately follows the BITMAPINFOHEADER and is referenced by a single pointer), biClrUsed should be either zero or the actual size of the color table.

BiClrImportant

specifies the number of color indexes that are required for displaying the bitmap. If its value is zero, all colors are required.

For audio streams, the information is a WAVEFORMATEX structure. For text streams, the information has a TEXTINFO structure:

```
typedef_textinfo {
    WORD    wCodePage;
    WORD    wCountryCode;
    WORD    wLanguageCode;
    WORD    wDialect
} TEXTINFO
```

where the meaning of all the fields (wCodePage, wCountryCode, wLanguageCode, and wDialect) is the same as those defined above with reference to CSET chunk. Different languages can be set for each of the text streams in a file having multiple text streams.

If the optional stream header data ('strd') chunk is present in an AVI file, it follows the stream format chunk. The format and content of the 'strd' chunk are defined by the codec driver. Typically, drivers use this information for configuration. Applications that read and write AVI files do not need to interpret this information, they simply transfer it to and from the driver as a memory block.

The information block for achieving the digital rights management (DRM) protection in the AVI file is presented in the 'strd' chunk associated with the main video stream. The format of the DRM information data for the video stream in the 'strd' should be as following:

```

typedef DRMInfo{
    WORD wVersion;
    STR sDRMInfo;
} DRMINFO

```

where the two members in the structure DRMINFO are defined as:

wVersion
specifies the version of the DRM.

sDRMInfo
specifies the information for the DRM protection, e.g., in an encrypted binary string.

The optional stream name 'strn' chunk includes a null terminated text string describing the stream. In accordance with an embodiment of the present invention, the string is "Video [—Description]" for a video stream, where optional [—Description] part is any string that describes the video stream, e.g., it can be "Video—Main". For an audio stream, the string can be "Audio [—Description]", where the optional [—Description] part is any string that describes the audio stream, e.g., it can be "Audio—English", "Audio—French", "Audio—Main", or "Audio—Auxiliary", etc. For a chapter stream, which is a text stream, the string can be "Chapter [—Description]", where the optional [—Description] part is any string that describes the chapter stream. For a subtitle stream, which can be either a text stream or a video stream, the string can be "Subtitle [—Description]", where the optional [—Description] part is any string that describes the subtitle stream, e.g., it can be "Subtitle—English", or "Subtitle—Chinese".

AVI stream data 'movi' list follows the header information in the AVI RIFF file format. The 'movi' list contains the actual data in the streams, e.g., the video frames and audio samples. The data chunks can reside directly in the 'movi' list, or be grouped together as subchunks within 'rec' lists. The 'rec' grouping implies that the grouped subchunks should be read from disk all at once, and is intended for files that are interleaved to play from CD-ROM.

Each data chunk in the 'movi' list is identified by a FOURCC that includes a two-digit stream number followed by a two-character code that defines the type of information in the chunk. In accordance with an embodiment of the present invention, the two-character codes for defining the data type are:

db	uncompressed video frame
dc	compressed video frame
dd	DRM key info for the video frame
pc	palette change
wb	audio data
st	subtitle (text mode)
sb	subtitle (bitmap mode)
ch	chapter

It should be noted that, in accordance with the present invention, additional two-character codes may be used to identify data streams not specified herein above.

By way of example, if stream 0 contains audio, the FOURCC for the stream would be '00wb'. If stream 1 contains video, the FOURCC for the stream would be '01db' for uncompressed video or '01dc' for compressed video. Video data chunks can also define new palette entries to update the palette during an AVI sequence. Each palette-change chunk ('xxpc') contains an AVIPALCHANGE structure. If a stream contains palette changes, the AVISF_VIDEO_PAL-

CHANGES flag in the dwFlags member of the AVIS-TREAMHEADER structure for that stream is set accordingly.

The optional index list follows the 'movi' list in the AVI RIFF file format. The index contains a list of the data chunks and their location in the file. If the AVI file contains an index, the dwFlags member of the AVIMAINHEADER structure is set to AVIF_HASINDEX.

In version AVI 1.0, the index ('idx1') list includes an AVI-OLDINDEX structure with entries for each data chunk, including 'rec' chunks. The AVIOLDINDEX structure has the syntax:

```

typedef struct avioldindex {
    FOURCC    fcc;
    DWORD     cb;
    struct avioldindex_entry {
        DWORD   dwChunkId;
        DWORD   dwFlags;
        DWORD   dwOffset;
        DWORD   dwSize;
    } aIndex [ ];
} AVIOLDINDEX

```

The members in the structure have following characters:

fcc specifies a FOURCC code, with the value 'idx1'.

cb specifies the size of the structure, not including the initial 8 bytes.

DwChunkId
specifies a FOURCC that identifies a stream in the AVI file, having the form 'nnyy' where nn is the stream number and yy is a two-character code that identifies the contents of the stream:

db	uncompressed video frame
dc	compressed video frame
pc	palette change
wb	audio data

dwFlags
specifies a bitwise combination of zero or more of the following flags:

AVIIF_LIST	0x00000001L	// The data chunk is a 'rec' list.
AVIIF_KEYFRAME	0x00000010L	// The data chunk is a key frame.
AVIIF_NO_TIME	0x00000100L	// The data chunk does not affect the timing of the stream, e.g., for palette changes.
AVIIF_NO_COMPUS	0x0FFF0000L	// The data are for compressor use.

DwOffset
specifies the location of the data chunk in the file. In one embodiment, the value is specified as an offset, in bytes, from the start of the 'movi' list. In another embodiment, the value is the offset from the start of the file.

DwSize
specifies the size of the data chunk, in bytes.

In accordance with a preferred embodiment, the AVIOLDINDEX structure includes the initial RIFF chunk (the fcc and cb members) followed by one index entry for each data chunk in the 'movi' list. The AVIOLDINDEX structure describes an AVI 1.0 index ('idx1' format). New AVI files should use an AVI 2.0 index ('indx' format).

Additional data can be aligned in an AVI file by inserting 'JUNK' chunks as needed. Applications will ignore the contents of a 'JUNK' chunk.

In accordance with the present invention, the video tracks of one or more movies are stored in an AVI file as AVI video streams or tracks. A single AVI file may include multiple video tracks. Preferably, the first of the multiple video tracks is the main video track.

The stream descriptor ('str1') list for a video stream should include a stream header ('strh') chunk, a stream format ('strf'), a stream header data ('strd') chunk if the stream is DRM protected, and a stream name ('strn') chunk. In accordance with an embodiment of the present invention, the member fccType in the structure AVISTREAMHEADER the stream header ('strh') chunk for a video stream has the value 'vids'. The stream header data ('strd') chunk of a video stream should exist only for DRM protected video. If the 'strd' chunks exists, the video stream is protected, and there will be 'xddd' DRM chunks in the video stream. The stream name data ('strn') chunk for a video stream includes a string of the form "Video [—Descriptions]".

The stream data ('movi') list of a video stream in includes an 'nndb' chunk for an uncompressed video data chunk or an 'nndc' for a compressed video data chunk, where 'nn' is a two digit data chunk index. If a video data chunk is DRM protected, the 'movi' list also includes a 'nndd' chunk preceding the corresponding 'nndb' or 'nndc' chunk of the protected video data chunk. In accordance with a specific embodiment of the present invention, the member dwFlags in the structure AVIOLDINDEX of the index entry for the 'nndd' chunk is set to AVIF_NO_TIME.

In one embodiment of the present invention, each video data chunk includes one video frame in variable bit rate coding. For video frames encoded in predicted frames (P frames) and bidirectional frames (B frames), a B frame is preferably placed in a chunk with the following P frame. In such cases, an uncoded dummy P frame (N in the following illustration) is preferably inserted by the codec to keep the timing. For example, a sequence of image frames (I frames), B frames, and P frames $I_m B_{m+1} P_{m+2} P_{m+3} P_{m+4} \dots$ is preferably arranged into the following video stream chunk sequence:

$[I_m] [P_{m+2}, B_{m+1}] [N] [P_{m+4}, B_{m+3}] [N] \dots$

In the expression, the square brackets indicate the data chunks in the AVI stream.

In accordance with the present invention, the audio tracks of one or more movies are stored in an AVI file as AVI audio streams or tracks. A single AVI file may include multiple audio tracks. Preferably, the first of the multiple audio tracks is the main audio track.

The stream descriptor ('str1') list for an audio stream should include a stream header ('strh') chunk, a stream format ('strf'), and a stream name ('strn') chunk. In accordance with a specific embodiment the 'str1' list for an audio stream does not include the stream header data ('strd') chunk. In this embodiment, the application should ignore any data chunk with the 'strd' code in the steam descriptor ('str1') list of the AVI file.

In accordance with an embodiment of the present invention, the member fccType in the structure AVISTREAMHEADER the stream header ('strh') chunk for a video stream has the value 'auds'. The stream name data ('strn') chunk for a video stream includes a string of the form "Audio [—Descriptions]".

The stream data ('movi') list of an audio stream in includes an 'nnwb' chunk for identifying an audio data chunk, where 'nn' is a two digit data chunk index. In one embodiment of the present invention, each audio data chunk includes one audio frame in variable bit rate coding. In another embodiment of the present invention, each audio data chunk includes one or more audio frames in constant bit rate coding.

In accordance with the present invention, the chapter tracks are stored in an AVI file as AVI text streams or tracks. A single AVI file may include multiple chapter tracks. The stream descriptor ('str1') list for a chapter stream should include a

stream header ('strh') chunk, a stream format ('strf'), and a stream name ('strn') chunk. In accordance with a specific embodiment the 'str1' list for a chapter stream does not include the stream header data ('strd') chunk. In this embodiment, the application should ignore any data chunk with the 'strd' code in the steam descriptor ('str1') list of the AVI file.

In accordance with an embodiment of the present invention, the member fccType in the structure AVISTREAMHEADER the stream header ('strh') chunk for a video stream has the value 'txts'. The stream format ('strf') chunk for a chapter stream has the TEXTINFO structure. The stream name data ('strn') chunk for a video stream includes a string of the form "Chapter [—Descriptions]".

The stream data ('movi') list of a chapter stream in includes an 'nnch' chunk for identifying a chapter data chunk, where 'nn' is a two digit data chunk index. In one embodiment of the present invention, each chapter data chunk has a CHAPTERCHUNK structure:

```

typedef struct _chapterchunk {
    FOURCC                fcc;
    DWORD                 cb;
    STR                   time;
    STR                   description
} CHAPTERCHUNK

```

The members in the structure CHAPTERCHUNK are fcc specifies a FOURCC code having the value 'nnxx'. cb specifies the size of the structure, not including the initial 8 bytes.

time specifies the time at the starting of the chapter, having the form [hh:mm:ss.xxx], where hh is a two digit number representing the hours, mm a two digit number representing the minutes, ss a two digit number representing the seconds, and xxx a three digit number representing the milliseconds, of the starting point of the chapter.

Description

specifies the name of the chapter or other description information.

The chapter stream is not a regular interval stream. In accordance with a specific embodiment of the present invention, the member dwFlags in the structure AVIOLDINDEX of the index entry for the 'nnch' chunk is set to AVIF_NO_TIME.

In accordance with one embodiment of the present invention, the subtitle tracks are stored in an AVI file as AVI text streams or tracks. In accordance with another embodiment of the present invention, the subtitle tracks are stored in an AVI file as AVI bitmap streams or tracks. A single AVI file may include multiple subtitle tracks. The stream descriptor ('str1') list for a subtitle stream should include a stream header ('strh') chunk, a stream format ('strf'), and a stream name ('strn') chunk. In accordance with a specific embodiment the 'str1' list for a subtitle stream does not include the stream header data ('strd') chunk. In this embodiment, the application should ignore any data chunk with the 'strd' code in the steam descriptor ('str1') list of the AVI file.

In accordance with an embodiment of the present invention, the member fccType in the structure AVISTREAMHEADER the stream header ('strh') chunk for a video stream has the value 'txts' for text form subtitles or 'vids' for bitmap form subtitles. The stream format ('strf') chunk for a subtitle stream has the TEXTINFO structure for text form subtitles and the BITMAPINFOHEADER structure for bitmap form subtitles. The stream name data ('strn') chunk for a video stream includes a string of the form "Subtitle [—Descriptions]".

17

The stream data (“movi”) list of a subtitle stream includes an ‘ninst’ chunk for identifying a text form subtitle data chunk and/or an ‘nnsb’ chunk for identifying a bitmap form subtitle data chunk, where ‘nn’ is a two digit data chunk index. In one embodiment of the present invention, each subtitle data chunk has a SUBTITLECHUNK structure:

```

typedef struct_subtitlechunk {
    FOURCC          fcc;
    DWORD          cb;
    STR            duration;
    STR            subtitle
} SUBTITLECHUNK

```

The members in the structure SUBTITLECHUNK are fcc specifies a FOURCC code having the value ‘mxxx’. cb specifies the size of the structure, not including the initial 8 bytes.

duration

specifies the time at the starting of the chapter, having the form [hh:mm:ss.xxx—HH:MM:SS:XXX], where hh and HH are a two digit numbers representing the hours, mm and MM two digit numbers representing the minutes, ss and SS two digit numbers representing the seconds, and xxx and XXX three digit numbers representing the milliseconds, of the starting point and ending point, respectively, for displaying the subtitles.

subtitle

contains either the Unicode text of the subtitles for text mode, or a compressed bitmap image of the subtitles for bitmap mode.

The subtitle stream is not a regular interval stream. In accordance with a specific embodiment of the present invention, the member dwFlags in the structure AVIOLDINDEX of the index entry for the subtitle chunk is set to AVIF_NO_TIME.

For bitmap format subtitles, it is preferred to have compressed subtitle bitmaps in the subtitle field in the subtitle chunks. A compressed subtitle bitmap will have the following fields:

```

WORD          width;
WORD          height;
WORD          left;
WORD          top;
WORD          right;
WORD          bottom;
struct {
    BYTE          red;
    BYTE          green;
    BYTE          blue;
} color_background, color_pattern, color_emphasis1,
color_emphasis2;
BITMAP bitmap;

```

The “width” and “height” fields specify the dimension of the subtitle bitmap. The members “left”, “top”, “right”, and “bottom” fields specify the display rectangle of the subtitle bitmap relative to the main video rectangle. The BITMAP includes compressed bitmap data.

In accordance with a preferred embodiment, the subtitle bitmaps are four-level bitmaps with the following definition.

- 00 Background pixel
- 01 Pattern pixel
- 10 Emphasis pixel—1
- 11 Emphasis pixel—2

18

Compression of the subtitle bitmap uses a simple run-length coding according the rules in Table 4. In accordance with an embodiment of the present invention, the size of the run-length coded data within one line is 1440 bits or less.

In accordance with a preferred embodiment of the present invention, the streams in AVI files are interleaved. Audio stream chunks are interleaved ahead of corresponding video stream chunks in time. The amount of the audio stream that is interleaved ahead of corresponding points in the video stream should not exceed an predetermined upper limit, e.g., 2 seconds, 5 seconds, 10 seconds, 15 seconds, etc. The subtitle chunks are interleaved in the file ahead of the corresponding video chunk in time, with the amount of subtitle interleaved ahead of corresponding points in the video stream not exceeding an upper limit, e.g., 5 seconds, 10 seconds, 15 seconds, 20 seconds, etc. The interleaving of the chapter stream is not restricted. It could be all written in the beginning of the “movi” list, or interleaved with the other streams.

TABLE 4

Subtitle bitmap coding rules

Bitmap Pixels	Coding
1 to 3 pixels with the same value follow(s).	Enter the number of pixel(s) followed in the first 2 bits and the pixel data in the next 2 bits. The 4 bits are considered to be one unit.
4 to 15 pixels with the same value follows.	Specify ‘0’ in the first 2 bits, and enter the number of pixels in the following 4 bits and the pixel data in the next 2 bits. The 8 bits are considered to be one unit.
16 to 63 pixels with the same value follows.	Specify ‘0’ in the first 4 bits, and enter the number of pixels in the following 6 bits and the pixel data in the next 2 bits. The 12 bits are considered to be one unit.
64 to 255 pixels with the same value follows.	Specify ‘0’ in the first 6 bits, and enter the number of pixels in the following 8 bits and the pixel data in the next 2 bits. The 16 bits are considered to be one unit.
The same pixels follow to the end of a line.	Specify ‘0’ in the first 14 bits, and describe the pixel data in the following 2 bits. The 16 bits are considered to be one unit.
The byte alignment is not accomplished when the description for pixels on one line is completed.	Insert dummy data of 4 bits ‘0000b’ for adjustment.

An AVI file typically does not contain a time stamp of the streams. Each stream has its frame rate specified in the stream descriptor (‘str1’) list in the AVI header. For variable bit rate streams such as video streams or variable bit rate audio streams, each chunk contains one and only one frame.

Accessing the data of the variable bit rate stream at any given point is feasible with the known frame rate and the data chunk index. For constant bit rate streams, e.g., constant bit rate audio streams, each chunk may contain one or more frames. Because each frame has a known fixed size, locating data at any given point can be achieved by calculating the size of the stream data. Therefore, seeking an arbitrary location in an AVI file in accordance with the present invention can be achieved for either constant bit rate or variable bit rate streams by parsing and recording the index table for each frame.

Many playback devices, particularly consumer electronics devices such as DVD players, are not able to input pointers to arbitrary points as can a slider bar used in computer software. For such devices, it is beneficial to only record the chapter location, i.e., the starting point of audio, video, and subtitles, while parsing the index. For a memory restricted player, it may be preferred for the player to remember index records at the minute points to reduce memory usage, thereby saving

limited memory space. The full index is not required during normal forward play because the chunk is self-contained.

In accordance with the present invention, the version of the video codec used in AVI files is signaled by the FourCC code in the fccHandler field or member of the AVISTREAM-
5 HEADER of the corresponding stream header 'strh' chunks, and the FourCC code bicompression field or member in the BITMAPINFOHEADER of the corresponding 'strf' chunks.

By way of example, for videos encoded according to a codec developed by DivX Networks, Inc., 10350 Science
10 Center Drive, Building 14, Suite 140, San Diego, Calif. 92121, the FourCC codes fccHandler in the stream header ('strh') of the AVISTREAMHEADER is set to "divx" or "DIVX". Furthermore, the FourCC (DWORD) code biCompression in the BITMAPINFOHEADER of the corresponding
15 'strf' chunks is set to signify the detailed codec version.

Specifically by way of example, for version DivX 3.11, 'div3' or 'div4' is used in AVISTREAMHEADER, and 'div3' or 'div4' is used in BITMAPINFOHEADER; for version
20 DivX 4.x, 'divx' is used in AVISTREAMHEADER, and 'divx' is used in BITMAPINFOHEADER; and for version DivX 5.x, 'divx' is used in AVISTREAMHEADER, and 'dx50' is used in BITMAPINFOHEADER.

By now it should be appreciated that a file format for storing digital data with a high compression rate has been described. A file format in accordance with the present invention is compatible with high level data compressing algorithms, such as MPEG-4. Its data compression ratio is about six to ten times higher than a standard DVD format. In accordance with the present invention, the file format is capable of
25 storing data in multiple streams or tracks. The file format is also able to encode and archive video, audio, and text data on easily accessible streams or tracks. Furthermore, the file format is able to provide protection of the copyright of the digitized content.

While the invention is susceptible to various modifications and alternative constructions, certain illustrated embodiments thereof have been described above in detail. It should be understood, however, that there is no intention to limit the invention to the specific form or forms disclosed, but on the
30 contrary, the intention is to cover all modifications, alternative constructions, and equivalents falling within the spirit and scope of the invention. The present invention is limited only by the claims that follow.

The invention claimed is:

1. A playback device configured to play data encoded in a multimedia file, comprising:

- a processor configured to read the multimedia file;
- wherein the multimedia file has at least one video track and includes a video stream descriptor list comprising:
 - a video stream header chunk;
 - a video stream format chunk following said video stream header chunk; and
 - a video stream name chunk including a string indicating
35 a video stream in said at least one video track;
- said video stream descriptor list further comprising a video stream header data chunk in response to said at least one video track being a digital rights management (DRM) protected video, said video stream header data chunk following said video stream format
40 chunk in said video stream descriptor list;
- said video stream header data chunk in said video stream descriptor list including a DRM information data block comprising:
 - a first member specifying a version of the DRM; and
 - a second member specifying a protection of the DRM

said DRM information data block in said video stream header data chunk having a data structure defined as:

```

typedef_DRMInfo {
    WORD wVersion;
    STR sDRMInfo;
} DRMINFO.

```

2. The playback device of claim 1, said second member of said DRM information data block in said video stream header data chunk including an encrypted binary string.

3. The playback device of claim 1, said video stream header chunk in said video stream descriptor list including a four character code "vids" specifying video stream data in said at least one video track.

4. The playback device of claim 1, said video stream format chunk in said video stream descriptor list including data having a BITMAPINFOHEADER structure specifying a format of said at least one video track.

5. The playback device of claim 4, said video stream format chunk in said video stream descriptor list including palette information of said at least one video track.

6. The playback device of claim 4, said BITMAPINFO-HEADER structure further specifying a version of the file.

7. The playback device of claim 1, said video stream name chunk in said video stream descriptor list including a null terminated text string "Video".

8. The playback device of claim 7, said null terminated text string "Video" in said video stream name chunk further including a description field describing said at least one video track.

9. The playback device of claim 1, wherein the multimedia file further includes a video stream data list comprising:

- at least one data chunk identified by a two digit stream index number followed by a two character code, said two character code being "db" in response to said least one data chunk being an uncompressed video frame and being "dc" in response to said least one data chunk being a compressed video frame; and

in response to said at least one data chunk being a digital rights management (DRM) protected video frame, a DRM data chunk identified by said two digit stream index number followed by a two character code "dd", said DRM data chunk preceding said at least one data chunk and having DRM protection information.

10. The playback device of claim 9, each of said at least one data chunk in said video stream data list including data for one video frame.

11. The playback device of claim 9, said at least one data chunk in said video stream data list including an encoded data chunk having a bidirectional frame and a following predicting frame.

12. The playback device of claim 11, said at least one data chunk in said video stream data list further including an uncoded frame following said encoded data chunk.

13. The playback device of claim 1, wherein the multimedia file further includes at least one audio track and an audio stream descriptor list comprising:

- an audio stream header chunk;
- an audio stream format chunk following said audio stream header chunk; and
- an audio stream name chunk including a string indicating an audio stream in said at least one audio track.

14. The playback device of claim 13, said audio stream header chunk in said audio stream descriptor list including a four character code "auds" specifying audio stream data in said at least one audio track.

21

15. The playback device of claim 13, said audio stream format chunk in said audio stream descriptor list including data having a WAVEFORMATEX structure specifying a format of said at least one audio track.

16. The playback device of claim 13, said audio stream name chunk in said audio stream descriptor list including a null terminated text string "Audio".

17. The playback device of claim 16, said null terminated text string "Audio" in said audio stream name chunk further including a description field describing said at least one audio track.

18. The playback device of claim 13, further including an audio stream data list comprising at least one data chunk identified by a two digit stream index number followed by a two character code.

19. The playback device of claim 18, said two character code following said two digit stream index number in said audio stream data list being "wb".

20. The playback device of claim 18, each of said at least one data chunk in said audio stream data list including data for one audio frame in variable bit rate coding.

21. The playback device of claim 18, each of said at least one data chunk in said audio stream data list including data for at least one audio frame in constant bit rate coding.

22. The playback device of claim 18, wherein said at least one audio track is interleaved with said at least one video track.

23. The playback of claim 22, wherein said at least one audio track is interleaved ahead of said at least one video track by a time interval.

24. The playback device of claim 1, wherein the multimedia file further includes at least one chapter track and a chapter stream descriptor list comprising:
a chapter stream header chunk;
a chapter stream format chunk following said chapter stream header chunk; and
a chapter stream name chunk including a string indicating a chapter stream in said at least one chapter track.

25. The playback device of claim 24, said chapter stream header chunk in said chapter stream descriptor list including a four character code "txts" specifying text stream data in said at least one chapter track.

26. The playback device of claim 24, said chapter stream name chunk in said chapter stream descriptor list including a null terminated text string "Chapter".

27. The playback device of claim 26, said null terminated text string "Chapter" in said chapter stream name chunk further including a description field describing said at least one chapter track.

28. The playback device of claim 24, wherein the multimedia file further includes a chapter stream data list comprising a data chunk identified by a two digit stream index number followed by a two character code.

29. The playback device of claim 28, said two character code following said two digit stream index number in said chapter stream data list being "ch".

30. The playback device of claim 1, wherein the multimedia files further includes at least one subtitle track and a subtitle stream descriptor list comprising:

a subtitle stream header chunk;
a subtitle stream format chunk following said subtitle stream header chunk; and
a subtitle stream name chunk including a string indicating a subtitle stream in said at least one subtitle track.

31. The playback device of claim 30, wherein said at least one subtitle track is interleaved with said at least one video track in time.

22

32. The playback device of claim 31, wherein said at least one subtitle track is interleaved ahead of said at least one video track by a time interval.

33. The playback device of claim 30, said subtitle stream header chunk in said subtitle stream descriptor list including a four character code.

34. The playback device of claim 33, said four character code in said subtitle stream header chunk being "txts" in response to a text form subtitle.

35. The playback device of claim 33, said four character code in said subtitle stream header chunk being "vids" in response to a bitmap form subtitle.

36. The playback device of claim 35, said subtitle stream format chunk in said subtitle stream descriptor list including data having a BITMAPINFOHEADER structure specifying a format of said at least one subtitle track.

37. The playback device of claim 30, said subtitle stream name chunk in said subtitle stream descriptor list including a null terminated text string "Subtitle".

38. The playback device of claim 37, said null terminated text string "Subtitle" in said subtitle stream name chunk further including a description field describing said at least one subtitle track.

39. The playback device of claim 30, wherein the multimedia file further includes a subtitle stream data list comprising a data chunk identified by a two digit stream index number followed by a two character code.

40. The playback device of claim 39, said two character code following said two digit stream index number in said subtitle stream data list being "st" in response to a text form subtitle.

41. The playback device of claim 39, said two character code following said two digit stream index number in said subtitle stream data list being "sb" in response to a bitmap form subtitle.

42. A playback device configured to play data encoded in a multimedia file, comprising:

a processor configured to read the multimedia file;
wherein the multimedia file has at least one video track and includes a video stream descriptor list comprising:
a video stream header chunk;
a video stream format chunk following said video stream header chunk; and
a video stream name chunk including a string indicating a video stream in said at least one video track;
the file further having at least one chapter track and including a chapter stream descriptor list comprising:
a chapter stream header chunk;
a chapter stream format chunk following said chapter stream header chunk; and
a chapter stream name chunk including a string indicating a chapter stream in said at least one chapter track;
wherein said chapter stream format chunk in said chapter stream descriptor list including data having a TEXTINFO structure specifying a format of said at least one chapter track, said TEXTINFO structure being:

```
typedef_textinfo {
    WORD wCodePage;
    WORD wCountryCode;
    WORD wLanguageCode;
    WORD wDialect;
} TEXTINFO.
```

23

43. A playback device configured to play data encoded in a multimedia file, comprising:

- a processor configured to read the multimedia file;
- wherein the multimedia file has at least one video track and includes a video stream descriptor list comprising:
 - a video stream header chunk;
 - a video stream format chunk following said video stream header chunk; and
 - a video stream name chunk including a string indicating a video stream in said at least one video track;
- the file further having at least one chapter track and including a chapter stream descriptor list comprising:
 - a chapter stream header chunk;
 - a chapter stream format chunk following said chapter stream header chunk; and
 - a chapter stream name chunk including a string indicating a chapter stream in said at least one chapter track;
- the file further including a chapter stream data list comprising a data chunk identified by a two digit stream index number followed by a two character code;
- wherein said data chunk in said chapter stream data list having a structure defined as:

```
typedef struct chapterchunk {
    FOURCC fcc;
    DWORD cb;
    STR time;
    STR description
} CHAPTERCHUNK
```

wherein:

- the fcc element specifies a four character code “nnxx”;
- the cb element specifies a size of said structure;
- the time element specifies a starting time of said at least one chapter track; and
- the description element specifies a description of said at least one chapter track.

44. The playback device of claim 43, the time element in said data chunk in said chapter stream data list having a form [hh:mm:ss,xxx], wherein:

- hh represents hours;
- mm represents minutes;
- ss represents seconds; and
- mxxx represents milliseconds.

45. A playback device configured to play data encoded in a multimedia file, comprising:

- a processor configured to read the multimedia file;
- wherein the multimedia file has at least one video track and includes a video stream descriptor list comprising:
 - a video stream header chunk;
 - a video stream format chunk following said video stream header chunk; and
 - a video stream name chunk including a string indicating a video stream in said at least one video track;
- further having at least one subtitle track and including a subtitle stream descriptor list comprising:
 - a subtitle stream header chunk;
 - a subtitle stream format chunk following said subtitle stream header chunk; and
 - a subtitle stream name chunk including a string indicating a subtitle stream in said at least one subtitle track;

wherein said subtitle stream header chunk in said subtitle stream descriptor list including a four character code, said four character code in said subtitle stream header chunk being “txts” in response to a text form subtitle;

24

wherein said subtitle stream format chunk in said chapter stream descriptor list including data having a TEXTINFO structure specifying a format of said at least one subtitle track, said TEXTINFO structure being:

```
typedef_textinfo {
    WORD wCodePage;
    WORD wCountryCode;
    WORD wLanguageCode;
    WORD wDialect
} TEXTINFO.
```

46. A playback device configured to play data encoded in a multimedia file, comprising:

- a processor configured to read the multimedia file;
- wherein the multimedia file has at least one video track and includes a video stream descriptor list comprising:
 - a video stream header chunk;
 - a video stream format chunk following said video stream header chunk; and
 - a video stream name chunk including a string indicating a video stream in said at least one video track;
- the file further having at least one subtitle track and including a subtitle stream descriptor list comprising:
 - a subtitle stream header chunk;
 - a subtitle stream format chunk following said subtitle stream header chunk; and
 - a subtitle stream name chunk including a string indicating a subtitle stream in said at least one subtitle track;
- the file further including a subtitle stream data list comprising a data chunk identified by a two digit stream index number followed by a two character code, said data chunk in said subtitle stream data list having a structure defined as:

```
typedef struct_subtitlechunk {
    FOURCC fcc;
    DWORD cb;
    STR duration;
    STR subtitle
} SUBTITLECHUNK
```

wherein:

- the fcc element specifies a four character code “nnxx”; the cb element specifies a size of said structure;
- the time element specifies a starting time and an ending time of said at least one subtitle track; and
- the subtitle element includes:
 - a bitmap image in response to a bitmap form subtitle; and
 - a unicode text in response to a text form subtitle.

47. The playback device of claim 46, the duration element in said data chunk in said subtitle stream data list having a form [hh:mm:ss.xxx-HH:MM:SS.XXX], wherein:

- hh and HH represent hours;
- mm and MM represent minutes;
- ss and SS represent seconds; and
- xxx and XXX represent milliseconds.

48. A playback device configured to play data encoded in a multimedia file, comprising:

- a processor configured to read the multimedia file;
- wherein the multimedia file has at least one video stream, each including:
 - a video stream descriptor list comprising a video stream header chunk, a video stream format chunk, and a video stream name chunk; and

25

a video stream data list comprising a plurality of data chunks, each data chunk identified by a two digit stream index number followed by a two character code, said two character code being “db” in response to the data chunk being an uncompressed video frame and being “dc” in response to the data chunk being a compressed video frame; and

at least one audio stream, each including:

an audio stream descriptor list comprising an audio stream header chunk, an audio stream format chunk, and an audio stream name chunk; and

an audio stream data list comprising a plurality of data chunks, each data chunk identified by a two digit stream index number followed by a two character code “wb”;

wherein said video stream descriptor list further comprising a video stream header data chunk in response to said at least one video stream being digital rights management (DRM) protected, said video stream header data chunk including a DRM information data block having a structure defined as:

```
typedef_DRMinfo {
    WORD wVersion;
    STR sDRMinfo;
} DRMINFO
```

wherein:

said element wVersion specifies a version of the DRM; and said element sDRMinfo specifies a protection of the DRM.

49. The playback device of claim 48, said at least one audio stream in being interleaved ahead of said at least one video stream in said file by a time interval, said time interval having an upper limit of approximately ten seconds.

50. The playback device of claim 48, said video stream header chunk in said video stream descriptor list including a four character code “vids” specifying video stream data in said at least one video stream.

51. The playback device of claim 48, said video stream format chunk in said video stream descriptor list including data having a BITMAPINFOHEADER structure specifying a format of said at least one video stream.

52. The playback device of claim 51, said video stream format chunk further including palette information of said at least one video stream.

53. The playback device of claim 48, said video stream name chunk in said video stream descriptor list including a null terminated text string “Video”.

54. The playback device of claim 53, said video stream name chunk further including a description field describing said at least one video stream.

55. The playback device of claim 48, each of said plurality of data chunks in said video stream data list including data for one video frame.

56. The playback device of claim 48, said element sDRMinfo in said DRM information data block including an encrypted binary string.

57. The playback device of claim 48, said video stream data list further comprising a DRM data chunk identified by said two digit stream index number followed by a two character code “dd”, said DRM data chunk preceding said data chunk and having DRM protection information.

58. The playback device of claim 48, said audio stream header chunk in said audio stream descriptor list including a four character code “auds” specifying audio stream data in said at least one audio stream.

26

59. The playback device of claim 48, said audio stream format chunk in said audio stream descriptor list including data having a WAVEFORMATEX structure specifying a format of said at least one audio stream.

60. The playback device of claim 48, said audio stream name chunk in said audio streamer descriptor list including a null terminated text string “Audio”.

61. The playback device of claim 60, said null terminated text string “Audio” in said audio stream name chunk further including a description field describing said at least one audio stream.

62. The playback device of claim 48, each of said plurality of data chunks in said audio stream data list including data for one audio frame in variable bit rate coding.

63. The playback device of claim 48, each of said plurality of data chunks in said audio stream data list including data for at least one audio frame in constant bit rate coding.

64. The playback device of claim 48, said file further comprising at least one chapter stream, each including:

a chapter stream descriptor list comprising a chapter stream header chunk, a chapter stream format chunk, and

a chapter stream name chunk; and a chapter stream data list comprising a plurality of data chunks, each identified by a two digit stream index number followed by a two character code “ch”.

65. The playback device of claim 64, said chapter stream header chunk in said chapter stream descriptor list including a four character code “txts” specifying a text stream data in said at least one chapter stream.

66. The playback device of claim 64, said chapter stream name chunk in said chapter stream descriptor list including a null terminated text string “Chapter”.

67. The playback device of claim 66, said chapter stream name chunk further including a description field describing said at least one chapter stream.

68. The playback device of claim 48, said file further comprising at least one subtitle stream, each including:

a subtitle stream descriptor list comprising a subtitle stream header chunk, a subtitle stream format chunk, and

a subtitle stream name chunk; and a subtitle stream data list comprising a plurality of data chunks, each identified by a two digit stream index number followed by a two character code, said two character code being “st” in response to a text form subtitle and “sb” in response to a bitmap form subtitle.

69. The playback device of claim 68, said subtitle stream header chunk in said subtitle stream descriptor list including a four character code, said four character code being “txts” in response to a text form subtitle and “vids” in response to a bitmap form subtitle.

70. The playback device of claim 68, said subtitle stream name chunk in said subtitle stream descriptor list including a null terminated text string “Subtitle”.

71. The playback device of claim 70, said subtitle stream name chunk further including a description field describing said at least one subtitle stream.

72. A playback device configured to play data encoded in a multimedia file, comprising:

a processor configured to read the multimedia file; wherein the multimedia file has at least one video stream, each including:

a video stream descriptor list comprising a video stream header chunk, a video stream format chunk, and a video stream name chunk; and

27

a video stream data list comprising a plurality of data chunks, each data chunk identified by a two digit stream index number followed by a two character code, said two character code being “db” in response to the data chunk being an uncompressed video frame and being “dc” in response to the data chunk being a compressed video frame; and
 at least one audio stream, each including:
 an audio stream descriptor list comprising an audio stream header chunk, an audio stream format chunk, and an audio stream name chunk; and
 an audio stream data list comprising a plurality of data chunks, each data chunk identified by a two digit stream index number followed by a two character code “wb”;
 wherein said file further comprising at least one chapter stream, each including:
 a chapter stream descriptor list comprising a chapter stream header chunk, a chapter stream format chunk, and
 a chapter stream name chunk; and a chapter stream data list comprising a plurality of data chunks, each identified by a two digit stream index number followed by a two character code “ch”;
 wherein said chapter stream format chunk in said chapter stream descriptor list including data having a TEXTINFO structure specifying a format of said at least one chapter stream, said TEXTINFO structure being:

```
typedef_textinfo {
    WORD wCodePage;
    WORD wCountryCode;
    WORD wLanguageCode;
    WORD wDialect
} TEXTINFO.
```

73. A playback device configured to play data encoded in a multimedia file, comprising:
 a processor configured to read the multimedia file;
 wherein the multimedia file has at least one video stream, each including:
 a video stream descriptor list comprising a video stream header chunk, a video stream format chunk, and a video stream name chunk; and
 a video stream data list comprising a plurality of data chunks, each data chunk identified by a two digit stream index number followed by a two character code, said two character code being “db” in response to the data chunk being an uncompressed video frame and being “dc” in response to the data chunk being a compressed video frame; and
 at least one audio stream, each including:
 an audio stream descriptor list comprising an audio stream header chunk, an audio stream format chunk, and an audio stream name chunk; and
 an audio stream data list comprising a plurality of data chunks, each data chunk identified by a two digit stream index number followed by a two character code “wb”
 wherein said file further comprising at least one chapter stream, each including:
 a chapter stream descriptor list comprising a chapter stream header chunk, a chapter stream format chunk, and
 a chapter stream name chunk; and a chapter stream data list comprising a plurality of data chunks, each identified by a two digit stream index number followed by a two character code “ch”;

28

wherein said plurality of data chunks in said chapter stream data list having a structure defined as:

```
typedef struct_chapterchunk {
    FOURCC fcc;
    DWORD cb;
    STR time;
    STR description
} CHAPTERCHUNK
```

wherein:

said fcc element specifies a four character code “nnxx”;
 said cb element specifies a size of said structure;
 said time element specifies a starting time of said at least one chapter stream; and
 said description element specifies a description of said at least one chapter stream.

74. The playback device of claim **73**, said time element having a form [hh:mm:ss.xxx], wherein:

hh represents hours;
 mm represents minutes;
 ss represents seconds; and
 xxx represents milliseconds.

75. A playback device configured to play data encoded in a multimedia file, comprising:

a processor configured to read the multimedia file;
 wherein the multimedia file has at least one video stream, each including:

a video stream descriptor list comprising a video stream header chunk, a video stream format chunk, and a video stream name chunk; and

a video stream data list comprising a plurality of data chunks, each data chunk identified by a two digit stream index number followed by a two character code, said two character code being “db” in response to the data chunk being an uncompressed video frame and being “dc” in response to the data chunk being a compressed video frame; and

at least one audio stream, each including:

an audio stream descriptor list comprising an audio stream header chunk, an audio stream format chunk, and an audio stream name chunk; and

an audio stream data list comprising a plurality of data chunks, each data chunk identified by a two digit stream index number followed by a two character code “wb”;

wherein said file further comprising at least one subtitle stream, each including:

a subtitle stream descriptor list comprising a subtitle stream header chunk, a subtitle stream format chunk, and

a subtitle stream name chunk; and a subtitle stream data list comprising a plurality of data chunks, each identified by a two digit stream index number followed by a two character code, said two character code being “st” in response to a text form subtitle and “sb” in response to a bitmap form subtitle;

wherein:

in response to a bitmap form subtitle, said subtitle stream format chunk in said subtitle stream descriptor list includes data having a BITMAPINFOHEADER structure specifying a format of said at least one subtitle stream; and

in response to a text form subtitle, said subtitle stream format chunk in said subtitle stream descriptor list includes data having a TEXTINFO structure specify-

29

ing a format of said at least one subtitle stream, said TEXTINFO structure being:

```
typedef_textinfo {
    WORD wCodePage;
    WORD wCountryCode;
    WORD wLanguageCode;
    WORD wDialect
} TEXTINFO.
```

76. A playback device configured to play data encoded in a multimedia file, comprising:

a processor configured to read the multimedia file;
wherein the multimedia file has at least one video stream,
each including:

a video stream descriptor list comprising a video stream header chunk, a video stream format chunk, and a video stream name chunk; and

a video stream data list comprising a plurality of data chunks, each data chunk identified by a two digit stream index number followed by a two character code, said two character code being “db” in response to the data chunk being an uncompressed video frame and being “dc” in response to the data chunk being a compressed video frame; and

at least one audio stream, each including:

an audio stream descriptor list comprising an audio stream header chunk, an audio stream format chunk, and an audio stream name chunk; and

an audio stream data list comprising a plurality of data chunks, each data chunk identified by a two digit stream index number followed by a two character code “wb”;

wherein said file further comprising at least one subtitle stream, each including:

a subtitle stream descriptor list comprising a subtitle stream header chunk, a subtitle stream format chunk, and

a subtitle stream name chunk; and a subtitle stream data list comprising a plurality of data chunks, each identified by a two digit stream index number followed by a two character code, said two character code being “st” in response to a text form subtitle and “sb” in response to a bitmap form subtitle;

wherein said plurality of data chunks in said subtitle stream data list having a structure:

```
typedef struct_subtitlechunk {
    FOURCC fcc;
    DWORD cb;
    STR duration;
    STR subtitle
} SUBTITLECHUNK
```

wherein:

said fcc element specifies a four character code “nxxx”;
said cb element specifies a size of said structure;
said time element specifies a starting time and an ending time of said at least one subtitle stream; and
said subtitle element includes:

a bitmap image in response to a bitmap form subtitle;
and

a unicode text in response to a text form subtitle.

77. A playback device configured to play data encoded in a multimedia file, comprising:

a processor configured to read the multimedia file;
wherein the multimedia file has a video stream, including:

30

a video stream descriptor list comprising a video stream header chunk, a video stream format chunk, a video stream header data chunk in response to said video stream being digital rights management (DRM) protected, and a video stream name chunk; and

a video stream data list comprising a plurality of video data chunks, each video data chunk identified by a two digit stream index number followed by a two character code, said two character code being “db” in response to the video data chunk being an uncompressed video frame and being “dc” in response to the video data chunk being a compressed video frame;

an audio stream interleaved ahead of said video stream, including:

an audio stream descriptor list comprising an audio stream header chunk, an audio stream format chunk, and an audio stream name chunk; and

an audio stream data list comprising a plurality of audio data chunks, each identified by a two digit stream index number followed by a two character code “wb”;
and

a subtitle stream interleaved ahead of said video stream, including:

a subtitle stream descriptor list comprising a subtitle stream header chunk, a subtitle stream format chunk, and

a subtitle stream name chunk; and a subtitle stream data list comprising a plurality of subtitle data chunks, each identified by a two digit stream index number followed by a two character code, said two character code being “st” in response to a text form subtitle and “sb” in response to a bitmap form subtitle

further comprising a chapter stream, including:

a chapter stream descriptor list comprising: a chapter stream header chunk having a four character code “txts”;

a chapter stream format chunk having a TEXTINFO structure specifying a format of said chapter stream; and

a chapter stream name chunk having a null terminated text string “Chapter”; and a chapter stream data list comprising a plurality of chapter data chunks, each identified by a two digit stream index number followed by a two character code “ch”, said plurality of chapter data chunks having a structure:

```
typedef struct_chapterchunk {
    FOURCC fcc;
    DWORD cb;
    STR time;
    STR description
} CHAPTERCHUNK
```

wherein:

said fcc element specifies a four character code;
said cb element specifies a size of said structure;
said time element specifies a starting time of said at least one chapter stream; and
said description element specifies a description of said at least one chapter stream.

78. The playback device of claim 77, wherein, in response to a video data chunk in said video stream data list being DRM protected, said video stream data list includes a DRM data chunk preceding said video data chunk, said DRM data chunk having DRM protection information and being identified by a two digit stream index number followed by a two character code “dd”.

79. The playback device of claim 77, wherein each of said plurality of audio data chunks in said audio stream data list includes data for one audio frame in variable bit rate coding.

80. The playback device of claim 77, wherein each of said plurality of audio data chunks in said audio stream data list includes data for at least one audio frame in constant bit rate coding.

81. The playback device of claim 77, wherein:

said video stream header chunk includes a four character code "vids" specifying video stream data in said video stream;

said video stream format chunk includes data having a BITMAPINFOHEADER structure specifying a format of said video stream; said video stream name chunk includes a null terminated text string "Video";

said audio stream header chunk includes a four character code "auds" specifying audio stream data in said audio stream;

said audio stream format chunk includes data having a WAVEFORMATEX structure specifying a format of said audio stream;

said audio stream name chunk includes a null terminated text string "Audio";

said subtitle stream header chunk includes a four character code,

said four character code being "txts" in response to a text form subtitle and "vids" in response to a bitmap form subtitle;

said subtitle stream format chunk includes, in response to a bitmap form subtitle, data having a BITMAPINFO-HEADER structure and, in response to a text form subtitle, data having a TEXTINFO structure; and

said subtitle stream name chunk includes a null terminated text string "Subtitle".

82. The playback device of claim 81, wherein said video stream format chunk further includes palette information of said video stream.

83. The playback device of claim 81, wherein:

said video stream name chunk in said video stream descriptor list further includes a description field describing said video stream;

said audio stream name chunk in said audio stream descriptor list further includes a description field describing said audio stream; and

said subtitle stream name chunk in said subtitle stream descriptor list further includes a description field describing said subtitle stream.

84. The playback device of claim 77, wherein each of said plurality of video data chunks in said video stream data list includes data for one video frame.

85. The playback device of claim 77, wherein said plurality of video data chunk in said video stream data list include:

an encoded data chunk having a bidirectional frame and a following predicting frame; and

an uncoded frame following said encoded data chunk.

86. A memory restricted playback device configured to play data encoded in a multimedia file, comprising:

a processor configured to read the multimedia file;

wherein the multimedia file has at least one video track and includes a video stream descriptor comprising:

a video stream name including a string indicating a video stream in said at least one video track;

wherein the multimedia file further includes:

an encoded data chunk having a bidirectional frame (B_{m+1}), a following predicted frame (P_{m+2}), and an uncoded dummy predicted frame (N) arranged in the following chunk sequence: [P_{m+2} , B_{m+1}] [N]

and wherein the processor is configured to decode said encoded data chunk and said uncoded dummy predicted frame as the following sequence of frames: B_{m+1} , P_{m+2} .

87. The memory restricted playback device of claim 86, wherein said video stream descriptor includes a video stream header chunk; and

said video stream header chunk includes a four character code "vids" specifying video stream data in said at least one video track.

88. The memory restricted playback device of claim 86, wherein the multimedia file further comprises:

at least one data chunk identified by a two digit stream index number followed by a two character code, said two character code being "db" in response to said least one data chunk being an uncompressed video frame and being "dc" in response to said least one data chunk being a compressed video frame; and

in response to said at least one data chunk being a digital rights management (DRM) protected video frame, a DRM data chunk identified by said two digit stream index number followed by a two character code "dd", said DRM data chunk preceding said at least one data chunk and having DRM protection information.

89. The memory restricted playback device of claim 86, wherein the multimedia file further comprises:

at least one audio track and an audio stream descriptor list comprising: an audio stream header chunk;

an audio stream format chunk following said audio stream header chunk; and

an audio stream name chunk including a string indicating an audio stream in said at least one audio track.

90. The memory restricted playback device of claim 89, wherein said audio stream header chunk in said audio stream descriptor list including a four character code "auds" specifying audio stream data in said at least one audio track.

91. The memory restricted playback device of claim 86, wherein said multimedia file further includes at least one chapter track and a chapter stream descriptor list comprising:

a chapter stream header chunk including a four character code "txts" specifying text stream data in said at least one chapter track;

a chapter stream format chunk following said chapter stream header chunk; and

a chapter stream name chunk including a string indicating a chapter stream in said at least one chapter track.

92. The memory restricted playback device of claim 86, wherein said multimedia file further includes a RIFF header including a four character code "RIFF" specifying the file as a RIFF file.

93. The memory restricted playback device of claim 92, wherein said multimedia file further includes a RIFF header including a four character code "AVI" specifying the file as an AVI file.

94. The memory restricted playback device of claim 86, wherein said video stream descriptor includes a video stream header chunk; and

said video stream header chunk includes a four character code specifying a data handler for said at least one video track, wherein the four character code is selected from the group consisting of "divx," "div3," and "div4".

95. The memory restricted playback device of claim 86, wherein said video stream descriptor includes a video stream format chunk; and

said video stream format chunk includes data having a BITMAPINFOHEADER structure specifying a format of said at least video track.

96. The memory restricted playback device of claim 95, wherein said BITMAPINFOHEADER structure includes a 5 four character code specifying the detailed codec version, wherein the four character code is selected from the group consisting of "div3," "div4," "divx" and "dx50".

* * * * *